

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE SOUTH BOUNDARY
TOWNSHIP 23 SOUTH, RANGE 4 WEST,
AND A PORTION OF THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTION 5
TOWNSHIP 24 SOUTH, RANGE 4 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated July 31, 2008,
approved September 16, 2008, which provided for the surveys included under
Group No. 2210, and Assignment Instructions dated September 16, 2008.

Survey commenced October 9, 2008

Survey completed November 19, 2008

Tps. 23 and 24 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the south boundary of Township 23 South, Range 4 West, and a portion of the subdivisional lines and the subdivision of section 5, Township 24 South, Range 4 West, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the south boundary of T. 23 S., R. 4 W., as shown in the official field notes.</p> <p>In 1855-56, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed a portion of the subdivisional lines as shown on the official plat of survey approved February 20, 1856.</p> <p>In 1856, Dennis Hathorn, U.S. Deputy Surveyor, surveyed Donation Land Claim No. 37 as shown on the official plat of survey approved June 1, 1860.</p> <p>In 1896-97, Oscar F. Thiel, U.S. Deputy Surveyor, resurveyed a portion of the north boundary and surveyed the remainder of the subdivisional lines as shown on the official plat of survey approved November 6, 1897.</p> <p>In 1963, C. Albert White and Norman J. McDonald, Cadastral Surveyors, resurveyed a portion of the east boundary and subdivisional lines, and remonumented certain corner points as shown on the official plat of survey accepted April 22, 1965.</p> <p>In 1976, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the south boundary and subdivisional lines of T. 23 S., R. 4 W., as shown on the official plat of survey accepted January 28, 1980.</p> <p>In 1979, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the south boundary, T. 23 S., R. 4 W., a portion of the south boundary, subdivisional lines, and claim lines, and subdivided section 15 of T. 24 S., R. 4 W., as shown on the official plat of survey accepted August 28, 1981.</p> <p>In 1984-85, Lance J. Bishop and James L. White, Cadastral Surveyors, correctively resurveyed a portion of the subdivisional lines, resurveyed a portion of the subdivisional lines, and subdivided section 9, as shown on the official plat of survey accepted November 7, 1986.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated July 31, 2008, for Group No. 2210, Oregon.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.</p>
------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Tps. 23 and 24 S., R. 4 W., Willamette Meridian, Oregon

FEET

The directions of the lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) measurements.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.12 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

The geographic position (NAD 1983 (CORS)) of the 1/4 section corner of sections 5 and 6, as determined by direct occupation utilizing dual frequency carrier phase GPS receivers, relative to National Spatial Reference System (NSRS) Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP" and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", is as follows:

Latitude: 43° 30' 41.754" N. Longitude: 123° 12' 25.787" W.

The geographic position (NAD 1983 (CORS)) of the 1/4 section corner of sections 5 and 32, on the North boundary of the township, as determined by a tie from a temporary GPS control point, established utilizing dual frequency carrier phase GPS receivers, relative to NSRS CORS "DODSON BUTTE CORS ARP" and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", is as follows:

Latitude: 43° 31' 08.25" N. Longitude: 123° 11' 49.07" W.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

Restoring the 1855 survey by Harvey Gordon and Charles T. Gardner, the 1896-97 resurvey by Oscar F. Thiel, and the 1979 resurveys by James E. Jelley

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	<p>Beginning at the cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 23 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; margin-top: 5px;"></td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">R 4 W</td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">1963</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <ul style="list-style-type: none"> A sawed fir stump, 36 ins. diam., bears N. 70° E., 27.7 ft. dist., with no marks visible. A sawed fir stump, 44 ins. diam., bears S. 86° E., 29.7 ft. dist., with no marks visible. A sawed fir stump, 48 ins. diam., bears N. 43° W., 25.1 ft. dist., with no marks visible. <p>and the remains of bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 24 S., R. 4 W., Point Identifier No. 303700, reported by Jelley in 1979</p> <ul style="list-style-type: none"> A sawed cedar stump, 17 ins. diam., bears S. 75° E., 37.3 ft. dist., with no marks visible. A fir, 60 ins. diam., bears N. 75 3/4° W., 65.3 ft. dist., with a healed blaze. <p>and a bearing tree mkd. by Jelley in 1976</p> <ul style="list-style-type: none"> A maple, 28 ins. diam., bears N. 77° E., 102.3 ft. dist., with a healed blaze. <p>N. 89° 47' 26" W., bet. secs. 4 and 32, on the S. bdy. of the Tp.</p> <p>Across nearly level N. slope.</p>	T 23 S		S 32	S 33			R 4 W		1963					
T 23 S															
S 32	S 33														
R 4 W															
1963															
180.58	<p>The closing cor. of secs. 4 and 5, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 23 S R 4 W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 32</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; margin-top: 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">C</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">T 24 S R 4 W</td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">1979</td> </tr> </table> </div>	T 23 S R 4 W		S 32				S 5	S 4	C	C	T 24 S R 4 W		1979	
T 23 S R 4 W															
S 32															
S 5	S 4														
C	C														
T 24 S R 4 W															
1979															

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	<p>from which accessories mkd. by Jelley in 1979</p> <p style="padding-left: 40px;">A basalt stone, 2 1/2 X 2 1/2 X 2 ft. above ground, bears S. 47 1/2° E., 6.5 ft. dist., with chisel marks X BO visible on top. (Record, S. 56 1/2° E., 5.9 ft.)</p> <p style="padding-left: 40px;">A basalt stone, 2 1/2 X 1 X 1 ft. above ground, bears S. 19° W., 5.9 ft. dist., with chisel marks X BO visible on top.</p> <p>From this cor., the original closing cor. of secs. 4 and 5, bears S. 0° 44' 27" E., 4.85 ft. dist, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 S R 4 W</p> <hr style="width: 100px; margin: 0 auto;"/> <p>S 5 S 4 C C 1963</p> </div> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A maple, 26 ins. diam., bears S. 40° E., 25.1 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 24 S., R. 4 W., Point Identifier No. 300700, reported by Jelley in 1979</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. 1° E., 55.2 ft. dist., with a healed blaze. (Record, 56.8 ft.)</p> <p style="padding-left: 40px;">A cedar, 27 ins. diam., bears S. 74 1/4° W., 108.0 ft. dist., with a healed blaze. (Record, S. 76° W., 86.5 ft.)</p> <hr style="width: 100%; margin: 10px 0;"/> <p>N. 89° 50' 53" W., bet. secs. 5 and 32, on the S. bdy. of the Tp., posting and blazing the true line.</p> <p>Descend over broken NW slope.</p> <p>1140.15 The E 1/16 sec. cor. of sec. 32 only, established by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1994, filed in the Douglas County Surveyor's Office, Map File No. M119-40, and is accepted as the cor., monumented with a brass cap, 2 1/2 ins. diam., firmly set, cemented into solid rock, flush with the rock, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 23 S R 4 W S 32 E 1/16 _____ PLS 1978 1994</p> </div>
------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	<p>from which bearing trees mkd. by Baker</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 26 1/4° E., 9.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir snag, 16 ins. diam., bears N. 51 1/2° W., 28.2 ft. dist., with a healed double blaze.</p> <p>and bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 53 3/4° E., 13.5 ft. dist., with a healed double blaze.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 48' 09" W., beginning new measurement.</p>
1320.69	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 23 S R 4 W</p> <p style="padding-left: 40px;">S 32</p> <p style="padding-left: 40px;">1/4 _____</p> <p style="padding-left: 40px;">S 5</p> <p>T 24 S R 4 W</p> <p style="padding-left: 40px;">1979</p> </div> <p>from which the remaining bearing tree mkd. by Jelley in 1979</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 13° E., 28.4 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">An oak, 15 ins. diam., bears S. 47° E., 7.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An oak, 20 ins. diam., bears S. 57 1/4° W., 13.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 70° E., 30.8 ft. dist., mkd. 1/4 S5 BT.</p> <hr style="width: 80%; margin: 10px auto;"/> <div style="text-align: center; padding: 10px 0;"> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 4 W., Willamette Meridian, Oregon</p> <hr style="width: 80%; margin: 10px auto;"/> <p>Restoring the 1855-56 survey by Harvey Gordon and Charles T. Gardner, the 1896-97 survey by Oscar F. Thiel, and the 1979 resurvey by James E. Jelley</p> <hr style="width: 30%; margin: 10px auto;"/> </div>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon**

<p>FEET</p>	<p>From the 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 24 S 1/4 S S 4 5 R 4 W 1963 </p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 26 ins. diam., bears N. 62° E., 9.2 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 24 S., R. 4 W., Point Identifier No. 300640, reported by Jelley in 1979</p> <p style="padding-left: 40px;">A roothole bears S. 31° W., 18.5 ft. dist., alongside of which is the fir trunk, 20 ins. diam., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Jelley in 1979</p> <p style="padding-left: 40px;">A sawed fir stump, 15 ins. diam., bears S. 64 1/2° W., 6.3 ft. dist., with scribe marks X S5 BT visible on an open blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 30 1/4° E., 7.3 ft. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 73° W., 9.0 ft. dist., mkd. 1/4 S5 BT.</p> <p>N. 0° 45' 12" W., bet. secs. 4 and 5.</p>
<p>1322.99</p>	<p>The N 1/16 sec. cor. of secs. 4 and 5, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> N 1/16 S 5 S 4 1978 </p> <p>from which bearing trees mkd. by Jelley in 1979</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 54 1/2° E., 153.1 ft. dist., with a healed double blaze. (Record, S. 53 3/4° E.)</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 63° W., 62.7 ft. dist., with a healed double blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>and bearing tree mkd. by person(s) unknown</p> <p>A fir, 12 ins. diam., bears N. 75 3/4° W., 4.0 ft. dist., with a healed double blaze.</p> <hr/> <p>N. 0° 44' 27" W., beginning new measurement, posting and blazing the true line.</p>
1280.91	The original closing cor. of secs. 4 and 5.
1285.76	The closing cor. of secs. 4 and 5.
	<hr/> <p>From the E 1/16 sec. cor. of sec. 5 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 S R 4 W E 1/16 S5</p> <hr/> <p style="text-align: center;">1979</p> <p>from which the remains of bearing trees mkd. by Jelley in 1979</p> <p>A fir stump, 30 ins. diam., bears N. 71° E., 15.2 ft. dist., with a healed blaze.</p> <p>A fir, 30 ins. diam., bears N. 83° W., 77.9 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by person(s) unknown, reported by Jelley</p> <p>A fir, 21 ins. diam., bears S. 29 1/2° W., 55.1 ft. dist., with a healed blaze. (Record, S. 32° W.)</p> <p>S. 89° 36' 56" W., bet. secs. 5 and 8, posting and blazing the true line.</p>
1308.51	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 24 S S 5 1/4 ——— S 8 R 4 W 1963</p> <p>from which the remains of an original bearing tree</p> <p>A roothole bears N. 20° E., 73.9 ft. dist., alongside of which is a displaced fir stump, 36 ins. diam., with no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon**

FEET	<p>and the remains of bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 24 S., R. 4 W., Point Identifier No. 240600, reported by Jelley in 1979</p> <p>A cedar, 31 ins. diam., bears N. 44° E., 67.1 ft. dist., with a healed blaze. (Record, 68.6 ft.)</p> <p>A sawed fir stump, 32 ins. diam., bears S. 29 3/4° W., 119.5 ft. dist., with no marks visible. (Record, S. 31° W.)</p> <p>and a new bearing tree</p> <p>A fir, 4 ins. diam., bears S. 29 1/4° E., 17.1 ft. dist., mkd. X BT.</p> <hr/> <p align="center">Subdivision of Section 5, T. 24 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 1° 27' 24" E., on the N. and S. centerline of sec. 5, posting and blazing the true line.</p> <p>2635.92 Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 S R 4 W C 1/4 S 5 2008</p> <p>from which</p> <p>An oak, 15 ins. diam., bears N. 82 3/4° E., 43.3 ft. dist., mkd. C 1/4 S5 BT.</p> <p>A fir, 6 ins. diam., bears S. 26 1/4° E., 47.0 ft. dist., mkd. C 1/4 S5 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by the Bureau of Land Management (BLM), Roseburg District Office, in 1978, in the course of an unofficial administrative survey, bears N. 70° 37' 42" W., 1.16 ft. dist., monumented with a steel fence post, 1 in. diam., firmly set, projecting 25 ins. above the ground, and is not utilized in the course of this survey.</p>
------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Subdivision of Section 5,
T. 24 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
3959.50	<p>Discontinue posting and blazing.</p> <p>Point for the center N 1/16 sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C N 1/16 S 5 C 2008</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 73 1/2° E., 29.7 ft. dist., mkd. C N 1/16 S5 BT with a Mag-Nail driven at the base on left side center.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 9 1/2° W., 24.6 ft. dist., mkd. C N 1/16 S5 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by the BLM, Roseburg District Office, in 1978, in the course of an unofficial administrative survey, bears S. 47° 55' 33" W., 1.78 ft., monumented with a steel fence post, 1 in. diam., firmly set, projecting 18 ins. above the ground, and is not utilized in the course of this survey.</p> <p>Recommence posting and blazing.</p>
5285.72	<p>The 1/4 sec. cor. of secs. 5 and 32.</p> <hr/>
1232.47	<p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>S. 89° 15' 57" W., on the E. and W. centerline of sec. 5, posting and blazing the true line.</p> <p>Point for the center E 1/16 sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 1/2 ft. diam. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16 C ————— C S 5 2008</p> </div> <p>from which</p>

**Subdivision of Section 5,
T. 24 S., R. 4 W., Willamette Meridian, Oregon**

FEET							
	<p>A cedar, 11 ins. diam., bears S. 25 1/2° E., 36.7 ft. dist., mkd. C E 1/16 S5 BT.</p> <p>A fir, 8 ins. diam., bears N. 87 1/2° W., 4.6 ft. dist., mkd. C E 1/16 S5 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by the BLM, Roseburg District Office, in 1978, in the course of an unofficial administrative survey, bears S. 79° 31' 13" W., 1.16 ft., monumented with a steel fence post, 1 in. diam., loosely set and badly bent, projecting 60 ins. above the ground, is not utilized in the course of this survey, and removed from the ground.</p>						
2562.71	<p>The center 1/4 sec. cor. of sec. 5.</p> <p>Discontinue posting and blazing.</p>						
5201.27	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>1/4</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S 6</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 5</td> </tr> <tr> <td style="padding: 0 5px;">T 24 S</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 4 W</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1963</td> </tr> </table> </div> <p>from which the remains of a bearing tree mkd. by White and McDonald</p> <p>A fir snag, 12 ins. diam., bears S. 33° W., 132.0 ft. dist., with a healed blaze. (Record, S. 32° W., 129.4 ft.)</p> <p>and new bearing trees</p> <p>A fir, 8 ins. diam., bears S. 81 3/4° E., 296.7 ft. dist., mkd. 1/4 S5 BT.</p> <p>A fir, 10 ins. diam., bears S. 54 1/2° W., 55.7 ft. dist., mkd. 1/4 S6 BT.</p> <hr style="border: 0.5px solid black;"/>	S 6	S 5	T 24 S	R 4 W	1963	
S 6	S 5						
T 24 S	R 4 W						
1963							
2511.52	<p>From the N 1/16 sec. cor. of secs. 4 and 5.</p> <p>S. 89° 15' 26" W., on the E. and W. centerline of the NE 1/4 of sec. 5, posting and blazing the true line.</p> <p>The center N 1/16 sec. cor. of sec. 5.</p> <hr style="border: 0.5px solid black;"/> <p>From the E 1/16 sec. cor. of sec. 5 only.</p> <p>N. 1° 55' 28" E., on the N. and S. centerline of the SE 1/4 of sec. 5, posting and blazing the true line.</p>						

**Subdivision of Section 5,
T. 24 S., R. 4 W., Willamette Meridian, Oregon**

<p>FEET 2644.82</p>	<p>The center E 1/16 sec. cor. of sec. 5.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in mountainous terrain, approximately 8 miles northeasterly from the community of Sutherlin, Oregon.</p> <p>Elevation ranges from approximately 2600 feet above sea level near the 1/4 section corner of sections 4 and 5, to approximately 1200 feet above sea level near the 1/4 section corner of sections 5 and 6.</p> <p>The area is drained by many small, seasonal unnamed tributaries, which flow westerly into Bachelor Creek and northerly into Elk Creek.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>Access to the survey is by way of graveled roads branching from Douglas County Road No. 50 (Elkhead Road) and Douglas County Road No. 69 (Romie Howard Road).</p> <hr/>
-------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------