

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

THE DEPENDENT RESURVEY OF  
A PORTION OF THE SUBDIVISIONAL LINES  
AND SUBDIVISION-OF-SECTION LINES OF SECTION 17  
AND THE SUBDIVISION OF SECTIONS 18 AND 19,  
**TOWNSHIP 24 SOUTH, RANGE 7 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***A. Bert Skeesick, Cadastral Surveyor***

***Robert H. Browning, Surveying Technician***

Under Special Instructions dated March 30, 2005, approved April 8, 2005,  
which provided for the surveys included under Group No. 2104,  
and Assignment Instructions dated June 17, 2005.

***Survey commenced July 6, 2005***

***Survey completed January 3, 2006***

**T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and subdivision-of-section lines of section 17, and the subdivision of sections 18 and 19, Township 24 South, Range 7 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1857-58, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the north, south, east, and a portion of west boundaries and subdivisional lines.

In 1893-94, Williams R. Whipple, U.S. Deputy Surveyor, surveyed the east boundary, completed the north boundary, surveyed a portion of the west and south boundaries, and completed the survey of the subdivisional lines.

In 1894, Henry L. Chandler, U.S. Deputy Surveyor, surveyed a portion of the west boundary.

In 1963, C. Albert White, Cadastral Surveyor, and Donald R. Beck, Surveying Technician, dependently resurveyed a portion of the north boundary and subdivisional lines and subdivided section 5.

In 1975-76, James E. Jelley, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines and subdivided section 17.

In 2003, A. Bert Skeesick, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines and subdivided section 9.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 30, 2005, for Group No. 2104, Oregon.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May 9, 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.3 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

**T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The following published stations from the National Spatial Reference System Continuously Operating Reference Station (CORS) were used for control:

1. CAPE BLANCO CORS ARP, National Geodetic Survey.  
42° 50' 09.93681" N.; 124° 33' 47.99046" W.; NAD 1983 (CORS 2000)
2. DODSON BUTTE CORS ARP, National Geodetic Survey.  
43° 07' 07.62977" N.; 123° 14' 39.21270" W.; NAD 1983 (CORS 2002)

The geographic position (NAD 83 (CORS 96)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations noted above.

The corner of sections 17, 18, 19 and 20:

Latitude: 43° 28' 35.25" N. Longitude: 123° 33' 54.25" W.

The corner of sections 8, 9, 16, and 17:

Latitude: 43° 29' 27.31" N. Longitude: 123° 32' 41.92" W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

---

Restoring the 1857-58 survey by Dennis Hathorn,  
the 1893-94 survey by Williams R. Whipple,  
and the 1975-76 resurvey by James E. Jelley

---

Beginning at the cor. of secs. 19, 20, 29, and 30, remonumented by the Douglas County Surveyors Office in 1926 from orig. evidence no longer in existence, and perpetuated by the Douglas County Surveyors Office in 1958 and 1970, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 200300, monumented with a car axle, 1 1/4 ins. diam., firmly set, projecting 1 in. above ground, with flange, 8 ins. diam. on top, with no marks visible, from which the remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1926

A decayed fir stump, 23 ins. diam., bears S. 88 1/4° E., 28.3 ft. dist.,  
with axe marks and scribe marks BT visible on a decayed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>and remains of bearing trees mkd. by the Douglas County Surveyors Office in 1958</p> <p style="padding-left: 40px;">A twin red oak, 47 ins. diam., bears N. 85 1/2° E., 67.1 ft. dist., with a healed blaze on northerly trunk.</p> <p style="padding-left: 40px;">A roothole bears N. 28° W., 100.4 ft. dist., with decayed fir trunk, size indeterminate, lying alongside, no marks visible.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office in 1970</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N. 15 1/2° E., 86.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A broken-topped fir, 28 ins. diam., bears N. 44° W., 90.5 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Reset the existing car axle, 33 ins. long, in place, 26 ins. in the ground, with flange down, and over it, set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T24S</td> <td style="padding: 2px 5px;">R7W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S19</td> <td style="padding: 2px 5px;">S20</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S30</td> <td style="padding: 2px 5px;">S29</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">2005</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 22 3/4° E., 22.2 ft. dist., mkd. T24S R7W S29 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 73 3/4° W., 17.2 ft. dist., mkd. T24S R7W S30 BT.</p> <p>S. 89° 56' 23" W., bet. secs. 19 and 30.</p> <p>Ascend broken S. slope.</p> <p>1346.00 Point for the E 1/16 sec. cor. of secs. 19 and 30, not monumented.</p> <p>2692.00 The 1/4 sec. cor. of secs. 19 and 30, remonumented by the Douglas County Surveyors Office in 1928 from orig. evidence no longer in existence, and perpetuated by the Douglas County Surveyors Office in 1970, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 140300, monumented with a car axle, 1 1/4 ins. diam., firmly set, projecting 3 ins. above ground, with flange, 8 ins. diam., on top, with no marks visible, from which the remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1928</p>	T24S	R7W	S19	S20	S30	S29	2005	
T24S	R7W								
S19	S20								
S30	S29								
2005									

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A maple, 18 ins. diam., bears S. 78 1/4° W., 4.8 ft. dist., with fragmentary scribe marks visible on an open blaze.</p> <p>and bearing tree mkd. by the Douglas County Surveyors Office in 1970</p> <p>A fir, 30 ins. diam., bears N. 69° E., 77.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Reset the existing car axle, 33 ins. long, 27 ins. in the ground, with flange down, and over it, set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R7W S19 1/4 ——— S30 2005</p> </div>
	<hr/>
	<p>From the cor. of secs. 19, 20, 29 and 30, hereinbefore described.</p> <p>N. 0° 03' 34" E., bet. secs. 19 and 20.</p> <p>Descend broken NE. and E. slopes.</p>
1321.92	Point for the S 1/16 sec. cor. of secs. 19 and 20, not monumented.
2643.84	<p>The 1/4 sec. cor. of secs. 19 and 20, remonumented by the Douglas County Surveyors Office in 1928, and remonumented by the Douglas County Surveyors Office again in 1958, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 200340, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS T 24 S 1/4   S19 S20 R 7 W OFFICE 1958</p> </div> <p>from which the remains of the orig. bearing trees</p> <p>A sawed and decayed fir stump, 36 ins. diam., bears N. 89 1/2° E., 34.8 ft. dist., with no marks visible. (Record, N. 88° E., 33.0 ft.)</p> <p>A clump of myrtle sprouts growing from a decayed myrtle stump, size indeterminate, bears S. 44 1/2° W., 11.2 ft. dist., with no marks visible. (Record, S. 50° W.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>and remains of bearing trees mkd. by the Douglas County Surveyors Office in 1958</p> <p style="padding-left: 40px;">A sawed cedar stump, 39 ins. diam., bears S. 28° E., 76.1 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 29 ins. diam., bears N. 62 1/2° W., 67.3 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears S. 27 1/2° E., 137.5 ft. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A myrtle, 9 ins. diam., bears S. 51 1/2° W., 9.1 ft. dist., mkd. 1/4 S19 BT.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 0° 17' 39" E., beginning new measurement.</p> <p>Ascend broken SE. and E. slopes.</p>																		
1335.24	Point for the N 1/16 sec. cor. of secs. 19 and 20, not monumented.																		
2670.48	<p>The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border: none; padding: 0 5px;">COUNTY</td> <td style="border: none; padding: 0 5px;">SURVEYORS</td> <td style="border: none; padding: 0 5px;">OFFICE</td> </tr> <tr> <td style="border: none; padding: 0 5px;"></td> <td style="border: none; padding: 0 5px;">T24S R7W</td> <td style="border: none; padding: 0 5px;"></td> </tr> <tr> <td style="border: none; padding: 0 5px;"></td> <td style="border: none; padding: 0 5px;">S18   S17</td> <td style="border: none; padding: 0 5px;"></td> </tr> <tr> <td style="border: none; padding: 0 5px;"></td> <td style="border: none; padding: 0 5px;">-----</td> <td style="border: none; padding: 0 5px;"></td> </tr> <tr> <td style="border: none; padding: 0 5px;"></td> <td style="border: none; padding: 0 5px;">S19   S20</td> <td style="border: none; padding: 0 5px;"></td> </tr> <tr> <td style="border: none; padding: 0 5px;"></td> <td style="border: none; padding: 0 5px;">1960</td> <td style="border: none; padding: 0 5px;"></td> </tr> </table> </div> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A fir snag, 44 ins. diam., bears N. 1° E., 24.7 ft. dist., with fragmentary scribe marks visible on an opened blaze. (Record, 26.1 ft.)</p> <p style="padding-left: 40px;">A roothole bears S. 75° E., 30.4 ft. dist., with no remains of the trunk visible.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyors Office in 1960, reported by Jelley</p> <p style="padding-left: 40px;">A fir snag, 21 ins. diam., bears N. 44° E., 69.3 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fallen fir snag, 22 ins. diam., bears S. 56 3/4° W., 65.0 ft. dist., with a healed blaze. (Record S. 60 1/2° W.)</p>	COUNTY	SURVEYORS	OFFICE		T24S R7W			S18   S17			-----			S19   S20			1960	
COUNTY	SURVEYORS	OFFICE																	
	T24S R7W																		
	S18   S17																		
	-----																		
	S19   S20																		
	1960																		

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A fir snag, 25 ins. diam., bears N. 5° W., 64.0 ft. dist., with a healed blaze. (Record, 66.0 ft.)</p> <p>and bearing trees mkd. by Mark F. Smalley, Oregon Professional Land Surveyor (PLS) No. 2354, in 1996 and 2003, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 200400,</p> <p>A fir, 16 ins. diam., bears N. 27 1/2° E., 32.5 ft. dist., with a healed blaze.</p> <p>A fir, 20 ins. diam., bears N. 32 1/2° E., 26.9 ft. dist., with scribe marks S17 BT visible on a partially healed blaze.</p> <p>A fir, 13 ins. diam., bears N. 82 1/2° E., 29.7 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and new accessories</p> <p>An iron rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 18°06'46" E., 8.7 ft. dist. with aluminum cap mkd. T24S R7W RM S20 8.7 FT TO COR 2005 and an arrow pointing to the cor.</p> <p>An iron rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 49°27'50" W., 7.5 ft. dist. with aluminum cap mkd. T24S R7W RM S19 7.5 FT TO COR 2005 and an arrow pointing to the cor.</p> <hr/> <p>N. 89° 59' 11" W., bet. secs. 18 and 19, posting and blazing.</p> <p>Ascend broken E. slope</p>																		
1321.35	<p>The E 1/16 sec. cor. of secs. 18 and 19, established by Leslie D. Roberts, Oregon PLS No. 1039, in 1981, filed in the Douglas County Surveyors Office, Map File No. M90-12, and is accepted as the cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T24S</td> <td style="text-align: center; padding: 0 10px;">PLS1039</td> <td style="padding: 0 10px;">R7W</td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">E 1/16</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">S 18</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">-----</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">S 19</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 0 10px;">1981</td> <td></td> </tr> </table> <p>from which the remains of bearing trees mkd. by Roberts</p> <p>A fallen fir snag, 14 ins. diam., bears N. 62 3/4° E., 14.8 ft. dist., with scribe marks E 1/16 S18 BT visible on unhealed double blaze.</p>	T24S	PLS1039	R7W		E 1/16			S 18			-----			S 19			1981	
T24S	PLS1039	R7W																	
	E 1/16																		
	S 18																		
	-----																		
	S 19																		
	1981																		

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 29 ins. diam., bears S. 35 3/4° E., 13.3 ft. dist., with a healed double blaze.</p> <p>and new bearing tree</p> <p>A fir, 31 ins. diam., bears N. 50° E., 46.8 ft. dist., mkd. E 1/16 S18 BT.</p> <p>From this cor., an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, set by person(s) unknown, bears N. 13° E., 1.0 ft. dist., with no cap.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 58' 41" W., beginning new measurement.</p> <p>Continue asc. steep E. slope.</p>																		
605	<p>Spur, slopes N. 13° W., and graveled road, 12 ft. wide, bears S. 26° E. and N. 20° W.; desc. broken W. slope.</p>																		
1321.30	<p>The 1/4 sec. cor. of secs. 18 and 19, remonumented by the Douglas County Surveyors Office in 1959, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 140400, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">COUNTY</td> <td style="padding: 0 5px;">SURVEYORS</td> <td style="padding: 0 5px;">OFFICE</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S18</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">1/4 ———</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S19</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">T24S R7W</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">1959</td> <td style="padding: 0 5px;"></td> </tr> </table> </div> <p>from which the remaining orig. bearing tree</p> <p>A fir, 24 ins. diam., bears N. 58° E., 8.6 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by the Douglas County Surveyors Office in 1959</p> <p>A fir, 19 ins. diam., bears S. 44 1/4° W., 29.8 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 40' 50" W., beginning new measurement; resume posting and blazing.</p> <p>Continue desc. W. slope.</p>	COUNTY	SURVEYORS	OFFICE		S18			1/4 ———			S19			T24S R7W			1959	
COUNTY	SURVEYORS	OFFICE																	
	S18																		
	1/4 ———																		
	S19																		
	T24S R7W																		
	1959																		
1405	<p>Creek, 2 ft. wide, course N. 33° W.; asc. broken NE. slope.</p>																		
2255	<p>Spur, slopes N. 30° W.; desc. broken NW. slope.</p>																		

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2435	Ravine, drains N. 32° W.; asc. broken NE. slope.
2600	Spur, slopes N. 19° W.; desc. broken SW. slope.
2722.70	<p>The closing cor. of secs. 18 and 19, described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 24 S., R. 8 W., executed concurrently under this same group.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p align="center">           1/4            S 18   S 17            T 24 S R 7 W            1975         </p> <p>from which the remains of an orig. bearing tree</p> <p style="padding-left: 40px;">A sawed cedar stump, 25 ins. diam. bears N. 9° W., 7.3 ft. dist., with fragmentary scribe marks visible on an opened blaze. (Rescribed by Byron in 1961)</p> <p>and bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A fir, 35 ins. diam. bears N. 38 1/2° E., 71.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam. bears N. 79 1/2° W., 37.6 ft. dist., with a healed blaze.</p> <p>N. 0° 03' 13" W., bet. secs. 17 and 18,</p> <p>Ascend over a broken SW slope</p>
1318.21	The N 1/16 sec. cor. of sec. 18 only, not monumented.
1326.45	<p>The N 1/16 sec. cor. of sec. 17 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p align="center">             N 1/16              S 17            1975         </p> <p>from which accessories, by Jelley</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam. bears N. 8 1/2° E., 90.2 ft. dist., with healed blaze. (Record, 89.1 ft. dist)</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, buried 4 ins. below ground, bears N. 73° 34' 25" E., 19.6 ft. dist., with brass cap mkd. N 1/16</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>S17 RM 1996 and an arrow pointing to the cor. (Record, N. 72 1/2° E., 19.1 ft. dist.)</p> <p>A fir, 17 ins. diam. bears S. 15° E., 16.8 ft. dist., with healed blaze.</p> <p>Corner is located on the south side of a gravel road, 25 ft. wide, bears N. 50° E. and S. 50° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 01' 38" E., beginning new measurement,</p> <p>Descend over a broken NW slope</p>														
1325.15	<p>The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">COUNTY</td> <td style="padding: 0 5px;">SURVEYORS</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">T 24 S</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 7   S 8</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">----- -----</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 18   S 17</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">R 7 W</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">OFFICE 1957</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1957, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 200500, reported by Jelley</p> <p>A tin-capped, sawed fir stump, 25 ins. diam., bears S. 50° E., 48.2 ft. dist., with no scribe marks visible on an opened blaze.</p> <p>A decayed fir snag, 50 ins. diam., bears N. 63° W., 27.1 ft. dist., with scribe marks S R visible in the bark.</p> <p>and remains of bearing trees mkd. by Jelley</p> <p>A fir, 15 ins. diam., bears N. 45 1/2° E., 7.6 ft. dist., with a healed blaze.</p> <p>A dead fir, 14 ins. diam., bears S. 59 1/4° W., 132.7 ft. dist., with a healed blaze.</p> <p>A fir, 22 ins. diam., bears N. 84 3/4° W., 17.8 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p>A fir, 12 ins. diam., bears N. 15° W., 13.0 ft. dist., mkd. T24S R7W S7 BT.</p> <hr style="width: 20%; margin: 10px auto;"/>	COUNTY	SURVEYORS		T 24 S		S 7   S 8		----- -----		S 18   S 17		R 7 W		OFFICE 1957
COUNTY	SURVEYORS														
	T 24 S														
	S 7   S 8														
	----- -----														
	S 18   S 17														
	R 7 W														
	OFFICE 1957														

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>From the cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS T 24 S <u>S 8   S 9</u> S17   S16 R 7 W OFFICE 1957</p> <p>from which the remains of bearing trees mkd. by the Douglas County Surveyors Office, reported by Skeesick</p> <p style="padding-left: 40px;">A roothole bears N. 64 1/4° E., 20.9 ft. dist., with fallen trunk, size indeterminate, lying alongside, with no marks visible.</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 80° E., 8.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A roothole bears S. 12 3/4° W., 25.4 ft. dist., with fallen trunk, 23 ins. diam., lying alongside, with no marks visible.</p> <p style="padding-left: 40px;">A roothole bears N. 28 1/4° W., 34.6 ft. dist., with fallen trunk, 18 ins. diam., lying alongside, with no marks visible.</p> <p>and bearing tree mkd. by Smalley, reported by Skeesick</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 36 1/4° E., 29.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and bearing tree mkd. by Hoffine, reported by Skeesick</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 5 3/4° E., 44.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and bearing tree mkd. by Skeesick</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 85 1/2° W., 71.7 ft. dist., with no scribe marks visible on a mostly healed blaze.</p> <p>N. 89° 47' 04" W., bet. secs. 8 and 17, posting and blazing.</p> <p>Descend SW. slope.</p>
735	Spur, slopes S. 50° W.; desc. W. slope.
985	Spur, slopes North; desc. NW. slope.
1610	Ravine, drains S. 70° W.; asc. SE. slope.
1620	Spur, slopes S. 10° E.; desc. SW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET 1655	Creek, course S. 30° E.; asc. E. slope.																																	
2633.97	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td style="padding: 0 5px;">COUNTY</td> <td style="padding: 0 10px;">SURVEYORS</td> <td style="padding: 0 5px;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">T 24 S</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S 8</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1/4 —————</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S 17</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R 7 W</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1963</td> <td></td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1963, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 240500, reported by Jelley</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 40 3/4° E., 17.5 ft. dist., with a healed blaze. (Record, S. 43° E.)</p> <p style="margin-left: 40px;">A decayed fir snag, 19 ins. diam., bears N. 44 3/4° W., 35.4 ft. dist., with a healed blaze. (Record, 36.3 ft.)</p> <p>and new bearing tree</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 30 3/4° W., 29.3 ft. dist., mkd. 1/4 S8 BT.</p> <p>Discontinue posting and blazing.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the W 1/16 sec. cor. of secs. 8 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td></td> <td style="padding: 0 10px;">S 8</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">W 1/16</td> <td style="padding: 0 10px;">—————</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S 17</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1976</td> <td></td> </tr> </table> </div> <p>from which bearing trees mkd. by Jelley</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 9° E., 20.1 ft. dist., with a healed blaze. (Record, N. 8° W.)</p> <p style="margin-left: 40px;">A fir, 29 ins. diam., bears S. 9 1/2° W., 39.6 ft. dist., with a healed blaze. (Record, S. 8° W.)</p> <p>N. 89° 45' 54" W., bet. secs. 8 and 17, posting and blazing.</p> <p>Ascend E. slope.</p>	COUNTY	SURVEYORS	OFFICE		T 24 S			S 8			1/4 —————			S 17			R 7 W			1963			S 8		W 1/16	—————			S 17			1976	
COUNTY	SURVEYORS	OFFICE																																
	T 24 S																																	
	S 8																																	
	1/4 —————																																	
	S 17																																	
	R 7 W																																	
	1963																																	
	S 8																																	
W 1/16	—————																																	
	S 17																																	
	1976																																	
95	Spur, slopes S. 10° W.; desc. SW. slope.																																	

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
290	Dirt road, 12 ft. wide, bears S. 44° E. and N. 44° W.
420	Draw bottom, drains S. 15° W.; asc SE. slope.
730	Spur, slopes South; desc. SW. slope.
860	Dirt road, 12 ft. wide, bears S. 55° E. and N. 55° W.
1010	Draw bottom, drains S. 10° W.; asc. SE. slope.
1360	Dirt road, 12 ft. wide, bears N. 64° E. and S. 64° W.
1390.27	The cor. of secs. 7, 8, 17, and 18, hereinbefore described.  Discontinue posting and blazing.
	<hr/>
	S. 89° 31' 19" W., bet. secs. 7 and 18.
	Ascend broken SE. slope.
1100	Spur, slopes N. 50° E.; desc. broken NW. slope.
1605	Graveled road, 16 ft. wide, bears S. 6° E and N. 3° W.
2230	Creek, 1 ft. wide, course N. 38° W.
2410	Same creek, 1 ft. wide, course S. 66° W.; asc. broken S. slope.
2665	Dirt road, 12 ft. wide, bears N. 80° E. and West.
2666.59	The 1/4 sec. cor. of secs. 7 and 18, determined at record bearing and dist. from the remaining orig. bearing tree  A fir, 20 ins. diam., bears N. 30° W., 17.8 ft. dist., with fragmentary scribe and axe marks visible on a partially healed blaze and X mkd. in the bark. This tree also has BLM BT tag mkd. Healy 5NOV54 Shoemaker-79 and GLO Location Tag mkd. YT12-17-53 RBradley 6-20-55 DLynn 5/13/63 Henriksen, BB6-94 and GKerr.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 29 ins. in the ground, below road surface, with brass cap mkd.
	<p>T24S R7W S 7 1/4 ————— S 18  2005</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 63 3/4° W., 38.7 ft. dist., mkd. 1/4 S18 BT.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89° 58' 28" W., beginning new measurement, posting and blazing.</p>
330	Left edge of dirt road, 12 ft. wide, bears East and N. 60° W.; desc. broken S. slope.
890	Creek, 3 ft. wide, course N. 36° W.; asc. N. slope.
1250	Spur, slopes North; desc. NW. slope.
1560	Same creek, 3 ft. wide, course S. 28° W.
1610	Same creek, 3 ft. wide, course N. 70° W.
1640	Same creek, 3 ft. wide, course S. 38° W.
1705	Same creek, 3 ft. wide, course N. 54° W.; asc. N. slope.
1895	Spur, slopes North; desc. NW. slope.
2145	Same creek, 3 ft. wide, course S. 72° W.
2180	Same creek, 3 ft. wide, course S. 26° W.
2205	Same creek, 3 ft. wide, course S. 64° W.
2235	Same creek, 3 ft. wide, course N. 26° W.; asc. N. slope.
2345	Spur, slopes North; desc. NW. slope.
2600	Same creek, 3 ft. wide, course S. 65° W.
2655	Same creek, 3 ft. wide, course N. 16° W.
2711.34	<p>The closing cor. of secs. 7 and 18, described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 24 S., R. 8 W., executed concurrently under this same group.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0° 06' 44" W., bet. secs. 7 and 8, posting and blazing.</p> <p>Ascend broken SE. slope.</p>
710	Spur, slopes S. 60° W.; desc. broken NE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

<p>FEET 1325.40</p>	<p>The S 1/16 sec. cor. of secs. 7 and 8, established by Burton W. Holt, Oregon PLS No. 418, in 1977, filed in the Douglas County Surveyors Office, Map File No. M68-34, and is accepted as the cor., monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 15 ins. above ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T24S R7W S 1/16 S7   S8 PLS418 1977</p> </div> <p>from which the remains of bearing trees mkd. by Holt</p> <p style="margin-left: 40px;">A dead fir snag, 25 ins. diam., bears S. 4 1/4° E., 26.6 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears S. 37° W., 47.8 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 22 1/4° E., 32.9 ft. dist., mkd. S 1/16 S8 BT.</p> <p>Corner is located 6.5 ft. east of a woven wire fence, extending N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' 05" W., beginning new measurement; continue posting and blazing.</p>
<p>635</p>	<p>Spring branch, 1 ft. wide, course N.56° E.; continue desc. NE. slope.</p>
<p>1324.72</p>	<p>The 1/4 sec. cor. of secs. 7 and 8, remonumented by the Douglas County Surveyors Office in 1960, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 200540, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE T 24 S R7W 1/4 S7   S 8 1960</p> </div> <p>from which the remains of the orig. bearing trees</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears N. 74 1/2° E., 29.7 ft. dist., with fragmentary scribe marks visible on an opened blaze. (Record, N. 74 1/2° W.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET																																			
	<p>A fir snag, 30 ins. diam., bears S. 75° W., 31.0 ft. dist., with no marks visible on an opened blaze.</p> <p>and remaining bearing tree mkd. by the Douglas County Surveyors Office</p> <p>A fir, 28 ins. diam., bears N. 51° W., 15.0 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p>A fir, 15 ins. diam., bears N. 48 3/4° E., 23.7 ft. dist., mkd. 1/4 S8 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 48' 11" E., beginning new measurement; continue posting and blazing.</p> <p>Continue desc. E. slope.</p>																																		
715	Graveled road, 16 ft. wide, bears S. 34° E. and N. 34° W.																																		
1095	Saddle, aspect changes to NE. slope; desc. NE. slope.																																		
1795	Ravine, drains N. 85° W.; asc. SW. slope.																																		
1985	Spur, slopes N. 84° W.; desc. NW. slope.																																		
2190	Ravine, drains West; asc. SE. slope.																																		
2395	Spur, slopes West; desc. NW. slope.																																		
2672.50	<p>The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td colspan="2"></td> </tr> <tr> <td colspan="2"></td> <td style="text-align: center;">T24S</td> <td style="text-align: center;">R7W</td> <td colspan="2"></td> </tr> <tr> <td rowspan="3" style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;">S6</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S5</td> <td colspan="3"></td> </tr> <tr> <td style="border-top: 1px solid black; text-align: center;">S7</td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-top: 1px solid black; text-align: center;">S8</td> <td colspan="3"></td> </tr> <tr> <td colspan="2" style="text-align: center;">1960</td> <td colspan="3"></td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> <td colspan="1"></td> </tr> </table> </div> <p>from which the remains of the orig. bearing trees</p> <p>A decayed fir stump, size indeterminate, bears N. 79 3/4° E., 17.8 ft. dist., with fragmentary scribe marks visible on a decayed blaze. (Record, N. 85° E., 16.5 ft.)</p> <p>A sawed, decayed fir stump, 32 ins. diam., bears N. 35° W., 19.2 ft. dist., with no marks visible. (Record, 21.1 ft.)</p> <p>bearing trees mkd. by the Douglas County Surveyors Office, reported by White and Beck</p> <p>A hemlock, 26 ins. diam., bears N. 43° E., 26.2 ft. dist., with a healed blaze. (Record, 27.7 ft.)</p>			SURVEYORS						T24S	R7W			COUNTY	S6	S5				S7	S8				1960									OFFICE	
		SURVEYORS																																	
		T24S	R7W																																
COUNTY	S6	S5																																	
	S7	S8																																	
	1960																																		
				OFFICE																															

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A roothole bears S. 52 1/2° W., 37.6 ft. dist., with fallen, decayed fir trunk, 8 ins. diam., lying alongside, no marks visible. (Record, 36.3 ft.)</p> <p>A hemlock, 23 ins. diam., bears N. 36 1/2° W., 29.0 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Mark F. Smalley, Oregon PLS No. 2354, in 1996, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 200600</p> <p>A hemlock, 8 ins. diam., bears N. 43 3/4° E., 19.0 ft. dist., with scribe marks 5 BT visible on a partially healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 19° W., 35.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr/> <p>N. 89° 52' 23" W., bet. secs. 6 and 7, posting and blazing.</p> <p>Descend broken W. slope.</p>			
340	<p>Creek, 3 ft. wide, course N. 48° E.; asc. broken NE. slope.</p>			
1321.94	<p>The E 1/16 sec. cor. of secs. 6 and 7, established by Mark F. Smalley, Oregon PLS No. 2354, in 1996, filed in the Douglas County Surveyors Office, Map File No. M125-67, and is accepted as the cor., monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 30 ins. above ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td style="padding: 0 10px;">T24S</td> <td style="text-align: center;">                 R.R.C.O.                  E 1/16  <hr style="width: 20px; margin: 0 auto;"/>                 6  <hr style="width: 20px; margin: 0 auto;"/>                 7                  1996                  LS2354             </td> <td style="padding: 0 10px;">R7W</td> </tr> </table> </div> <p>from which bearing trees mkd. by Smalley</p> <p>A cedar, 14 ins. diam., bears S. 56 1/4° W., 18.7 ft. dist., with scribe marks 1/16 BT visible on an unhealed blaze.</p> <p>A cedar, 20 ins. diam., bears N. 6 3/4° W., 23.1 ft. dist., with scribe marks 1/16 BT visible on an unhealed blaze.</p> <hr/> <p>N. 89° 52' 23" W., beginning new measurement; continue posting and blazing.</p> <p>Continue asc. broken E. slope.</p>	T24S	R.R.C.O. E 1/16 <hr style="width: 20px; margin: 0 auto;"/> 6 <hr style="width: 20px; margin: 0 auto;"/> 7 1996 LS2354	R7W
T24S	R.R.C.O. E 1/16 <hr style="width: 20px; margin: 0 auto;"/> 6 <hr style="width: 20px; margin: 0 auto;"/> 7 1996 LS2354	R7W		
550	<p>Dirt road, 20 ft. wide, bears S. 33° E. and N. 33° W.</p>			

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET																
905	Spur, slopes N. 7° E.; desc. broken W. slope.															
1321.14	<p>The 1/4 sec. cor. of secs. 6 and 7, remonumented by the Douglas County Surveyors Office in 1960, and perpetuated by Mark F. Smalley, Oregon PLS No. 2354, in 1996, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 07 W., Point Identifier No. 140600, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground (alongside of which is the orig. cor. stone, showing 6x9x6 ins. above ground, crumbling, mkd. S on N. face), with brass cap mkd.</p> <div style="text-align: center;"> <table style="border: none;"> <tr> <td style="writing-mode: vertical-rl; transform: rotate(180deg);">COUNTY</td> <td style="text-align: center;">SURVEYORS</td> <td style="writing-mode: vertical-rl; transform: rotate(180deg);">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">T24S R7W</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1 S 6</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">4 S 7</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1960</td> <td></td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A cedar, 27 ins. diam., bears S. 23 1/4° W., 26.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 23 ins. diam., bears N. 16 3/4° W., 9.1 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Smalley</p> <p style="padding-left: 40px;">A hemlock, 13 ins. diam., bears S. 43 3/4° E., 44.9 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 28 ins. diam., bears S. 7° W., 46.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 41' 53" W., beginning new measurement; continue posting and blazing.</p>	COUNTY	SURVEYORS	OFFICE		T24S R7W			1 S 6			4 S 7			1960	
COUNTY	SURVEYORS	OFFICE														
	T24S R7W															
	1 S 6															
	4 S 7															
	1960															
20	Creek, 2 ft. wide, course N. 47° E.; asc. broken E. slope.															
2737.02	<p>The closing cor. of secs. 6 and 7, described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 24 S., R. 8 W., executed concurrently under this same group.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Subdivision of Section 17, T. 24 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p style="text-align: center;">Restoring the 1975-76 survey by James E. Jelley</p> <hr/>															

**Dependent Resurvey of a Portion of the Subdivision of Section 17,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>From the center N 1/16 sec. cor. of sec. 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd.</p> <div style="text-align: center;"> </div> <p>from which the bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A pear tree, 10 ins. diam., bears S. 52 3/4° E., 4.6 ft. dist., with scribe marks CN 1/16 S17 BT visible on a partially healed blaze. (Record, apple tree. Note: blaze points SW.)</p> <p style="padding-left: 40px;">An oak, 34 ins. diam., bears S. 41 1/2° W., 147.8 ft. dist., with a healed blaze.</p> <p>Corner is located at the intersection of wire fences extending North and West. N. 0° 19' 51" E., on the N. and S. centerline of sec. 17, posting and blazing.</p> <p>Descend broken NE. slope.</p>
385	Ravine, drains N. 66° E.; asc. broken SE. slope.
655	Barbed-wire fence, 5 strands, bears East and West.
661.18	An iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, with no cap, set by person(s) unknown. There is no record of this monument being set and it is not utilized in the course of this survey.
805	Ravine, drains S. 50° E.; asc. broken SW. slope.
1326.18	The 1/4 sec. cor. of secs. 8 and 18.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 17.</p> <p>N. 89° 43' 34" W., on the E. and W. centerline of the NW 1/4 of sec. 17, posting and blazing.</p>
155	Corner of wire fences extending East, S. 36° E., and West; asc. E. slope.
210	Graveled road, 8 ft. wide, bears S. 17° E. and N. 17° W.
210	Power/telephone line, 4 wires, bears S. 12° E. and N. 12° W.
825	Dirt road, 12 ft. wide. bears S. 56° E. and N. 56° W.
1145	Spur, slopes S. 60° W.; desc. SW. slope.

**Dependent Resurvey of a Portion of the Subdivision of Section 17,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1318.39	<p>The NW 1/16 sec. cor. of sec. 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p align="center">NW 1/16 S17</p> <p align="center">1976</p> <p>from which the bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 40 1/2° E., 31.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 47° W., 44.2 ft. dist., with a healed blaze.</p> <hr/> <p>N. 0° 37' 18" E., on the N. and S. centerline of the NW 1/4 of sec. 17, posting and blazing.</p> <p>Ascend broken SW. slope.</p>
195	Spur, slopes S. 45° E.; continue asc. SE. slope.
415	Dirt road, 10 ft. wide, bears S. 62° E. and N. 62° W.
664.62	An iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, with no cap, set by person(s) unknown. There is no record of this monument being set and it is not utilized in the course of this survey.
1325.52	<p>The W 1/16 sec. cor. of secs. 8 and 17.</p> <hr/> <p align="center"><b>Subdivision of Section 18, T. 24 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs 18 and 19.</p> <p>N. 0° 18' 20" W., on the N. and S. centerline of sec. 18, posting and blazing.</p> <p>Ascend SW. slope.</p>
340	Spur, slopes S. 68° W.; desc. NW. slope.
940	Ravine, drains S. 72° W.; asc. SW. slope.
1275	Spur, slopes N. 89° W.; desc. NW. slope.
1855	Ascend SW. slope.
2635.16	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. centerline.

**Subdivision of Section 18,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24S R7W</p> <p style="text-align: center;">C 1/4 S18</p> <p style="text-align: center;">2005</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 24 1/2° W., 25.0 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 48 3/4° W., 12.3 ft. dist., mkd. C 1/4 S18 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
2960	Spur, slopes N. 40° W.; desc. N. slope.
4410	Dirt road, 12 ft. wide, bears S. 32° E. and N. 32° W.
5175	Creek, 1 ft. wide, course S. 54° W.; asc. steep S. slope.
5271.03	The 1/4 sec. cor. of secs. 7 and 18. Discontinue posting and blazing.
	<hr/> <p>From the 1/4 sec. cor. of secs 17 and 18.</p> <p>S. 89° 51' 36" W., on the E. and W. centerline of sec. 18.</p> <p>Ascend broken E. slope and desc. broken SW. slope.</p>
2653.38	The center 1/4 sec. cor. of sec. 18.
	Descend broken S. slope.
5371.02	The 1/4 sec. cor. of sec. 18 only, described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 24 S., R. 8 W., executed concurrently under this same group.
	<hr/> <p style="text-align: center;"><b>Subdivision of Section 19, T. 24 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 42' 08" E., on the N. and S. centerline of sec. 19, posting and blazing.</p> <p>Ascend steep S. slope.</p>

**Subdivision of Section 19,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
965	Spur, slopes S. 4° E.; asc. gentle S. slope.
1324.25	<p>The center S 1/16 sec. cor. of sec. 19, established by Leslie D. Roberts, Oregon PLS No. 1039, in 1981, filed in the Douglas County Surveyors Office, Map File No. 90-12, and is accepted as the cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p> <p align="center"> <span style="display: inline-block; transform: rotate(-90deg);">T24S</span> <span style="display: inline-block; transform: rotate(90deg);">R7W</span>                  PLS1039                  CS 1/16                  S 19                  1981             </p> <p>from which bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears S. 69 1/2° E., 23.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 33° W., 26.6 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 42' 08" E., beginning new measurement.</p> <p>Discontinue posting and blazing.</p>
1265	Descend steep N. slope.
1323.93	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <span style="display: inline-block; transform: rotate(-90deg);">T24S</span> <span style="display: inline-block; transform: rotate(90deg);">R7W</span>                  C 1/4                  S19                  2005             </p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 78° E., 16.0 ft. dist., mkd. C 1/4 S19 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 21° W., 5.4 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Descend broken N. and NW. slopes.</p>
2658.50	Point for the center N 1/16 sec. cor. of sec. 19, not monumented.

**Subdivision of Section 19,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET 3993.07	<p>The 1/4 sec. cor. of secs 18 and 19.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>N. 89° 56' 59" W., on the E. and W. centerline of sec. 19.</p> <p>Ascend steep SE. and NE. slopes.</p>
1331.51	<p>The center E 1/16 sec. cor. of sec. 19, established by Leslie D. Roberts, Oregon PLS No. 1039, in 1981, filed in the Douglas County Surveyors Office, Map File No. 90-12, and is accepted as the cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T24S      PLS1039      R7W                           CE 1/16                           S 19                           1981</p> </div> <p>from which bearing trees mkd. by Roberts</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. 2 3/4° E., 38.4 ft. dist., with a healed double blaze.</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears S. 78° W., 5.6 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 59' 38" W., beginning new measurement.</p> <p>Continue asc. steep NE. slope.</p>
1330.54	<p>The center 1/4 sec. cor. of sec. 19.</p> <p>Descend steep W. slope and asc. NE. slope.</p>
4010.62	<p>The 1/4 sec. cor. of sec. 19 only, described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 24 S., R. 8 W., executed concurrently under this same group.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 19.</p> <p>N. 0° 31' 42" E., on the N. and S. centerline of the NE 1/4 of sec. 19, posting and blazing.</p>
20	<p>Spring branch, 1 ft. wide, course East; asc. broken SE. slope.</p>

**Subdivision of Section 19,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET 1329.54	<p>The witness cor. for the NE 1/16 sec. cor. of sec. 19, established by Leslie D. Roberts, Oregon PLS No. 1039, in 1981, filed in the Douglas County Surveyors Office, Map File No. 90-12, and is accepted as the witness cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p align="center"> <span style="display: inline-block; transform: rotate(-90deg); font-weight: bold;">T24S</span> <span style="display: inline-block; transform: rotate(90deg); font-weight: bold;">R7W</span>                  PLS1039                  NE 1/16                  S 19                  WITNESS                  CORNER                  1981             </p> <p>from which bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 35 1/2° E., 5.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 43 ins. diam., bears N. 21 1/4° W., 4.0 ft. dist., with a healed double blaze.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 0° 29' 25" E., beginning new measurement, posting and blazing.</p> <p>Continue asc. NE. slope.</p>
4.85	<p>True point for the NE 1/16 sec. cor. of sec. 19, at the calculated intersection of the east and west centerline of the NE 1/4, not monumented.</p>
1340.16	<p>The E 1/16 sec. cor. of secs. 18 and 19.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center S 1/16 sec. cor. of sec. 19.</p> <p>N. 89° 58' 08" E., on the E. and W. centerline of the SE 1/4 of sec. 19, posting and blazing.</p> <p>Descend E. slope.</p>
1338.63	<p>The SE 1/16 sec. cor. of sec. 19, established by Leslie D. Roberts, Oregon PLS No. 1039, in 1981, filed in the Douglas County Surveyors Office, Map File No. 90-12, and is accepted as the cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <p align="center"> <span style="display: inline-block; transform: rotate(-90deg); font-weight: bold;">T24S</span> <span style="display: inline-block; transform: rotate(90deg); font-weight: bold;">R7W</span>                  PLS1039                  SE 1/16                  S 19                  1981             </p> <p>from which bearing trees mkd. by Roberts</p>

**Subdivision of Section 19,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">A fir, 27 ins. diam., bears N. 88° W., 271.8 ft. dist., with a healed blaze.</p> <p style="text-align: center;">A fir, 32 ins. diam., bears N. 33 1/2° W., 162.3 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p style="text-align: center;">A fir, 9 ins. diam., bears S. 68 1/4° W., 9.2 ft. dist., mkd. SE 1/16 S19 BT.</p> <hr/> <p>N. 0° 21' 27" E., on the N. and S. centerline of the SE 1/4 of sec. 19, posting and blazing.</p> <p>Ascend steep SE. slope.</p> <p>585 Spur, slopes S. 70° E.; desc. NE. slope.</p> <p>790 Draw bottom, drains S. 80° E.; asc. SE. slope.</p> <p>890 Spur, slopes East; desc. NE. slope.</p> <p>1322.99 The center E 1/16 sec. cor. of sec. 19.</p> <hr/> <p style="text-align: center;"><b>GENERAL DESCRIPTION</b></p> <p>The lands included in the foregoing survey are located in mountainous terrain, approximately 16 miles west-northwesterly from the community of Sutherlin, Oregon.</p> <p>The elevation ranges from approximately 800 feet above sea level near the closing corner of sections 7 and 18, on the West boundary of the township, to approximately 1360 feet above sea level near the S 1/16 section corner of sections 7 and 8.</p> <p>The southerly portion of the survey is drained by minor unnamed tributaries of the Umpqua River. The central portion of the survey is drained by Basin Creek which flows southeasterly to the Umpqua River. The northerly portion of the survey is drained by minor unnamed tributaries of McGee Creek which flows northeasterly to the Umpqua River.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>Access to the survey was made by graveled roads branching from McGee Creek Road and Basin Creek Road.</p> <hr/>
------	---