

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
THE DEPENDENT RESURVEY OF
A PORTION OF THE NORTH AND EAST BOUNDARIES
AND SUBDIVISIONAL LINES,
TOWNSHIP 24 SOUTH, RANGE 8 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor
Robert H. Browning, Surveying Technician

Under Special Instructions dated March 30, 2005, approved April 8, 2005,
which provided for the surveys included under Group No. 2104,
and Assignment Instructions dated June 17, 2005.

Survey commenced July 6, 2005

Survey completed January 3, 2006

T. 24 S., R. 8 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the north and east boundaries and a portion of the subdivisional lines, Township 24 South, Range 8 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1857-58, Dennis Hathorn, U.S. Deputy Surveyor, surveyed a portion of the east and south boundaries and subdivisional lines.

In 1858, Thomas H. Hutchinson, U.S. Deputy Surveyor surveyed a portion of the south boundary and subdivisional lines, T. 23 S., R. 8 W.

In 1894, Henry L. Chandler, U.S. Deputy Surveyor, resurveyed the north boundary and surveyed the south, west, and a portion of the east boundary and completed the survey of the subdivisional lines.

In 1893-94, Williams R. Whipple, U.S. Deputy Surveyor, completed the survey of the subdivisional lines, T. 24 S., R. 7 W.

In 1894, Williams R. Whipple, U.S. Deputy Surveyor, resurveyed portions of the north, south, east, and west boundaries, and a portion of the subdivisional lines, T. 24 S., R. 7 W.

In 1959, Harold D. Corbin, Cadastral Surveyor, dependently resurveyed a portion of the south boundary and subdivisional lines and remonumented certain original corner points.

In 1963, C. Albert White, Cadastral Surveyor, and Donald R. Beck, Surveying Technician, dependently resurveyed a portion of the south boundary of T. 23 S., R. 7 W., and a portion of the subdivisional lines and subdivided section 5, T. 24 S., R. 7 W.

In 1984, Stephen J. Malloy, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines and subdivided section 35, T. 23 S., R. 8 W.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 30, 2005, for Group No. 2104, Oregon.

The survey was performed using a combination of Global Positioning System (GPS) satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May 9, 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.3 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares

T. 24 S., R. 8 W., Willamette Meridian, Oregon

FEET

adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The following published stations from the National Spatial Reference System Continuously Operating Reference Station (CORS) were used for control:

- 1 CAPE BLANCO CORS ARP, National Geodetic Survey.
42° 50' 09.93681" N.; 124° 33' 47.99046" W.; NAD 1983 (CORS 2000)
2. DODSON BUTTE CORS ARP, National Geodetic Survey.
43° 07' 07.62977" N.; 123° 14' 39.21270" W.; NAD 1983 (CORS 2002)

The geographic position (NAD 1983 (CORS 96)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations noted above.

The corner of sections 19, 24, 25, and 30, on the east boundary of the township.:

Latitude: 43° 27' 42.68" N. Longitude: 123° 35' 06.84" W.

The 1/4 section corner of section 2 only, on the north boundary of the township.:

Latitude: 43° 31' 09.67" N. Longitude: 123° 36' 53.95" W.

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

Restoring the 1857-58 survey by Dennis Hathorn,
the 1893-94 survey by Williams R. Whipple,
and the 1894 survey by Henry L. Chandler

Beginning at the cor. of secs 19, 24, 25, and 30, on the E. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1958, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S.,

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>R. 08 W., Point Identifier No. 700300, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS T24S R S24 S19 R 8 ——— ——— 7 W S25 S30 W OFFICE 1958</p> <p>from which the remains of bearing trees mkd. by Chandler</p> <p style="padding-left: 40px;">A maple, 33 ins. diam., bears N. 14 3/4° E., 45.8 ft. dist., with scribe marks BT visible on a partially healed blaze. (Record, N. 17° E., 49.5 ft. Rescribed by the Douglas County Surveyors Office in 1958.)</p> <p style="padding-left: 40px;">A maple, 22 ins. diam., bears S. 84 3/4° W., 37.6 ft. dist., with no marks visible. (Record, S. 88° W.)</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 51° W., 45.3 ft. dist., with fragmentary scribe marks visible on blaze face lying alongside. (Record, 52.1 ft.)</p> <p>and accessories mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A chisel mark "+" on a vertical rock face, 5 ft. above ground, bears S. 48° E., 7.9 ft. dist., with chisel marks BO alongside.</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears S. 9 1/4° W., 38.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 83 3/4° W., 61.3 ft. dist., with a healed double blaze.</p> <p>N. 0° 02' 50" W., bet. secs. 19 and 24, posting and blazing.</p> <p>25 Ravine, drains S. 40° W. Ascend broken S. slope.</p> <p>135 Graveled road, 12 ft. wide, bears N. 65° E. and S. 60° W.</p> <p>585 Spur, slopes N. 55° W.; desc. broken NW. slope.</p> <p>2255 Graveled road, 16 ft. wide, bears S. 60° E. and N. 60° W.</p> <p>2610.77 The 1/4 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1960 from orig. evidence no longer in existence, and perpetuated by Ronald L. Rice, Oregon Professional Land Surveyor (PLS) No. 54633, in 2003, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700340, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p>
------	--

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET									
2420	Spur, slopes N. 75° W.; desc. broken NW. slope.								
2562.63	<p>The cor. of secs. 13 and 24 only, on the E. Bdy. of the Tp., remonumented by Leslie D. Roberts, Oregon PLS No. 1039, in 1981, and perpetuated by Ronald L. Rice, Oregon PLS No. 54633, in 2003, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700400, monumented with an iron post, 1 3/4 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>PLS 1039 T24S</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">R 8 W</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S13</td> <td style="border-left: 1px solid black; padding: 0 5px;">S19</td> <td style="text-align: center;">R 7 W</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S24</td> <td></td> <td></td> </tr> </table> <p>1981</p> </div> <p>from which the remains of the orig. bearing trees</p> <ul style="list-style-type: none"> A fir, 52 ins. diam., bears S. 80° E., 118.8 ft. dist., with no marks visible on an opened blaze. A fallen, decayed fir, size indeterminate, bears S. 72 1/2° W., 42.9 ft. dist., with fragmentary scribe marks visible on an opened blaze. (Record, S. 76° W.) A decayed fir stump, size indeterminate, bears N. 59 3/4° W., 84.8 ft. dist., with no marks visible. (Record, N. 58° W., 89.7 ft.) <p>and bearing trees mkd. by Roberts</p> <ul style="list-style-type: none"> A fir, 33 ins. diam., bears S. 16 1/4° W., 23.7 ft. dist., with a healed blaze. A fir, 21 ins. diam., bears N. 51 3/4° W., 25.0 ft. dist., with a healed blaze. <p>and a bearing tree mkd. by Rice</p> <ul style="list-style-type: none"> A fir, 23 ins. diam., bears N. 72 3/4° E., 20.3 ft. dist., with a healed blaze. <p>Discontinue posting and blazing.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 20' 57" E., bet. secs. 13 and 19.</p>	R 8 W	S13	S19	R 7 W		S24		
R 8 W	S13	S19	R 7 W						
	S24								
90.86	The closing cor. of secs. 18 and 19, T. 24 S., R. 7 W., on the E. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1959, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 8 W., Point Identifier No. 700402, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 19 ins. above ground, with brass cap mkd.								

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	SURVEYORS COUNTY R CC R OFFICE 8 7 W S13 S18 W S24 T24S 1959
	<p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 56° E., 51.1 ft. dist., with no marks visible. (Record, 60.1 ft.)</p> <p style="padding-left: 40px;">A fir, 62 ins. diam., bears N. 64° W., 96.4 ft. dist., with a healed blaze. (Record, 100.3 ft.)</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 21 1/2° E., 36.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 72 1/4° E., 27.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 7 ins. diam., bears S. 76 3/4° W., 22.1 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 12' 10" W., bet. secs 13 and 18, posting and blazing.</p> <p>Descend broken NW. slope.</p> <p>460 Creek, 2 ft. wide, course S. 70° W.; asc. broken S. slope.</p> <p>2220 Dirt road, 12 ft. wide, bears N. 35° E. and S. 30° W.</p> <p>2250 Ridge, bears N. 45° E., S. 55° W.; desc. broken NW. slope.</p> <p>2379.54 Point for the 1/4 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., at proportionate distance. There is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> T 24 S R8W R7W 1/4 S13 2005 </div>

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 86 3/4° W., 13.1 ft. dist., mkd. 1/4 S13 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 19 3/4° W., 11.4 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>																										
2643.69	<p>Point for the 1/4 sec. cor. of sec. 18 only, on the E. bdy. of the Tp., at proportionate distance. There is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 24 S</p> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R8W</td> <td style="padding: 0 5px;">R7W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1/4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S18</td> </tr> </table> <p>2005</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 20° E., 25.1 ft. dist., mkd. 1/4 S18 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 43 1/4° E., 12.0 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case, at the base of the stainless steel post.</p>	R8W	R7W		1/4		S18																				
R8W	R7W																										
	1/4																										
	S18																										
3120	<p>Ravine, drains N. 85° W.; asc. broken SW. slope.</p>																										
4420	<p>Spur, slopes West; desc. NW. slope.</p>																										
5044.06	<p>The cor. of secs. 12 and 13 only, remonumented by the Douglas County Surveyors Office in 1960, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700500, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td colspan="2"></td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">T24S</td> <td colspan="2"></td> </tr> <tr> <td rowspan="3" style="writing-mode: vertical-rl; transform: rotate(180deg); border-right: 1px solid black; padding: 0 5px;">COUNTY</td> <td style="padding: 0 5px;">R</td> <td style="border-right: 1px solid black; padding: 0 5px;">S12</td> <td style="padding: 0 5px;">R</td> <td rowspan="3" style="writing-mode: vertical-rl; transform: rotate(180deg); border-left: 1px solid black; padding: 0 5px;">OFFICE</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">8</td> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">7</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">W</td> <td style="border-right: 1px solid black; padding: 0 5px;">S13</td> <td style="padding: 0 5px;">W</td> <td></td> </tr> </table> <p>1960</p> <p>from which the remains of the orig. bearing trees</p> </div>			SURVEYORS						T24S				COUNTY	R	S12	R	OFFICE		8		7		W	S13	W	
		SURVEYORS																									
		T24S																									
COUNTY	R	S12	R	OFFICE																							
	8		7																								
	W	S13	W																								

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>A cedar, 40 ins. diam., bears N. 70° E., 5.3 ft. dist., with no marks visible on an opened blaze.</p> <p>A decayed fir stump, 38 ins. diam., bears N. 20° W., 10.9 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A cedar, 34 ins. diam., bears S. 22 1/2° W., 84.0 ft. dist., with a healed blaze.</p> <p>A cedar, 36 ins. diam., bears N. 47 1/4° W., 55.9 ft. dist., with a healed blaze.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 46" E., bet. secs. 12 and 18, beginning new measurement.</p> <p>243.32 The true point for the closing cor. of secs. 7 and 18, on the E. Bdy. of the Tp., at the intersection with the section line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 24 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">R8W</td> <td style="border-left: 1px solid black; padding: 0 5px;">R7W</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">C S7</td> </tr> <tr> <td style="padding: 0 5px;">S12</td> <td style="border-left: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">C</td> </tr> </table> <p>S18</p> <p>2005</p> </div> <p>from which</p> <p>A fir, 14 ins. diam., bears S. 40 1/4° E., 16.5 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case, at the base of the stainless steel post.</p> <p>From this point, the orig. closing cor. of secs. 7 and 18, established by Whipple in 1893-94, remonumented by the Douglas County Surveyors Office in 1960, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700504, bears N. 89° 58' 28" W., 8.55 ft. dist., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p>	R8W	R7W		C S7	S12	C
R8W	R7W						
	C S7						
S12	C						

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>SURVEYORS</p> <p>T24S</p> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R</td> <td style="border-right: 1px solid black; padding: 0 5px;">CC</td> <td style="border-right: 1px solid black; padding: 0 5px;">S7</td> <td style="padding: 0 5px;">R</td> <td rowspan="3" style="border-left: 1px solid black; padding-left: 5px; vertical-align: middle;">OFFICE</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">8</td> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="border-right: 1px solid black; padding: 0 5px;">7</td> <td style="padding: 0 5px;">7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">W</td> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="border-right: 1px solid black; padding: 0 5px;">S18</td> <td style="padding: 0 5px;">W</td> </tr> </table> <p>1960</p>	R	CC	S7	R	OFFICE	8		7	7	W		S18	W
R	CC	S7	R	OFFICE										
8		7	7											
W		S18	W											
	<p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A fir, 54 ins. diam., bears N. 82° E., 23.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 54 ins. diam., bears S. 14 1/2° W., 33.3 ft. dist., with scribe marks 7W 7 & 18 visible on a partially opened blaze. (Record, S. 17 1/2° W., 37.0 ft.)</p> <p>and a bearing tree mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears S. 66 1/4° E., 31.7 ft. dist., with a healed blaze.</p> <p>Add the marks AM to the brass cap.</p> <p>From this same point, the 1/4 sec. cor. of secs. 7 and 18, T. 24 S., R. 7 W., bears S. 89° 58' 28" E., 2711.34 ft. dist., described in the field notes of the resurvey of a portion of the subdivisional lines, T. 24 S., R. 7 W., executed concurrently under this same group.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 46" E., bet. secs. 7 and 12, beginning new measurement, posting and blazing.</p>													
15	Creek, 4 ft. wide, course N. 80° W.; asc broken SW. slope.													
590	Spur, slopes West; desc. broken NW. slope.													
1290	Creek, 3 ft. wide, course S. 32° W.; asc. broken SE. slope.													
2130	Spur, slopes S. 55° E.; desc. broken NE. slope.													
2375.36	The 1/4 sec. cor. of sec. 12 only, on the E. Bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1959, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700540, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.													

Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

<p>FEET</p>	<div style="text-align: center;"> <p>SURVEYORS</p> <p>T24S</p> <p>1/4 </p> <p>S12 </p> <p>R8W R7W</p> <p>1959</p> <p>COUNTY</p> <p>OFFICE</p> </div> <p>from which the remains of the orig. bearing trees</p> <p>A decayed fir stump, 43 ins. diam., bears N. 84 1/2° E., 18.5 ft. dist., with no marks visible. (Record, N. 80° E.)</p> <p>A decayed fir stump, 54 ins. diam., bears S. 28 3/4° W., 11.9 ft. dist., with no marks visible. (Record, S. 22° W.)</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A fir, 28 ins. diam., bears S. 59 3/4° W., 32.4 ft. dist., with a healed blaze.</p> <p>A cedar, 14 ins. diam., bears N. 70° W., 36.0 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 32' 51" E., beginning new measurement; continue posting and blazing.</p> <p>170 Creek, 1 ft. wide, course S. 36° E.; asc. broken SW. slope.</p> <p>306.52 Point for the 1/4 sec. cor. of sec. 7 only, on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 S</p> <p>R8W R7W</p> <p>1/4</p> <p> </p> <p>S7</p> <p>2005</p> </div> <p>from which</p> <p>A fir, 13 ins. diam., bears N. 32° E., 30.5 ft. dist., mkd. 1/4 S7 BT.</p> <p>A fir, 18 ins. diam., bears S. 53 3/4° E., 17.0 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>950 Spur, slopes S. 20° E.; desc. broken NE. slope.</p>
-------------	---

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET													
1605	Creek, 2 ft. wide, course S. 65° E.; asc. broken SE. slope.												
2040	Graveled road, 14 ft. wide, bears N. 52° E. and S. 45° W.												
2631.56	<p>The cor. of secs. 1 and 12 only, remonumented by the Douglas County Surveyors Office in 1959, perpetuated by Howard W. Johnstone, Oregon PLS No. 498, in 1963, and remonumented by the Douglas County Surveyors Office in 1967, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700600, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 1 in. above ground, with no cap, from which the remains of an orig. bearing tree</p> <p style="padding-left: 40px;">A broken fir stump, size indeterminate, bears N. 39° W., 49.8 ft. dist., with scribe marks 24 R8 visible on open blaze. (Record, 51.5 ft. Rescribed by the Douglas County Surveyors Office in 1959.)</p> <p>and remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1959</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 71° W., 12.3 ft. dist., with scribe marks BT visible on wood fragment lying alongside stump.</p> <p>and bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 6 1/4° W., 48.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 60 1/2° W., 40.9 ft. dist., with a healed blaze.</p> <p>Remove the existing iron post, 36 ins long, from the ground and in its place, drive a finned aluminum rod, 36 ins. long, 3/4 in. diam., 39 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td></td> <td style="text-align: center;">T 24 S</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R8W</td> <td style="text-align: center;">R7W</td> </tr> <tr> <td></td> <td style="text-align: center;">S1</td> <td style="border-left: 1px solid black; text-align: center;">S7</td> </tr> <tr> <td style="border-top: 1px solid black;"></td> <td style="text-align: center;">S12</td> <td style="border-left: 1px solid black;"></td> </tr> </table> <p>2005</p> </div> <p>Cut the existing iron post in half and drive the pieces alongside the aluminum rod. Deposit a magnet in a white plastic case alongside the aluminum rod.</p> <p>Corner is located approx. 2 ft. W. of bottom of ditch, approx. 12 ft. W. of a gravel road, 12 ft. wide, which bears S. 16° E and N. 16° W.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>		T 24 S			R8W	R7W		S1	S7		S12	
	T 24 S												
	R8W	R7W											
	S1	S7											
	S12												

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>N. 0° 08' 01" E., bet. secs. 1 and 7.</p>
35	<p>Graveled road, 12 ft. wide, bears S. 16° E. and N. 16° W.</p>
356.87	<p>The true point for the closing cor. of secs. 6 and 7, at the intersection with the section line, established by Leslie D. Roberts, Oregon PLS No. 1039, in 1979, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700606, and is accepted as the cor., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>PLS 1039 T24S R7W R8W S6 S1 S7 1979</p> </div> <p>from which a bearing tree by Roberts</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears S. 81° E., 33.6 ft. dist., with a healed blaze. (Note: This bearing tree was mkd. by the Douglas County Surveyors Office in 1960 as a new accessory to the orig. closing cor. of secs. 6 and 7.)</p> <p>From this point, the orig. closing cor. of secs. 6 and 7, established by Whipple in 1893-94, remonumented by the Douglas County Surveyors Office in 1960, and perpetuated by the Douglas County Surveyors Office in 1967, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700606, bears N. 89° 41' 53" W., 1.18 ft. dist., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SURVEYORS T24S COUNTY R C S6 R OFFICE 8 C 7 W S7 W 1960</p> </div> <p>from which the remains of the orig. bearing trees</p> <p style="margin-left: 40px;">A sawed and decayed fir stump, 41 ins. diam., bears N. 73° E., 24.0 ft. dist., with scribe marks 24S 7W S6 visible on an opened blaze. (Record, 26.4 ft.)</p> <p style="margin-left: 40px;">A roothole bears S. 2° E., 23.1 ft. dist., with uprooted fir stump, 49 ins. diam., lying alongside, no marks visible.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 45 ins. diam., bears S. 60° W., 22.4 ft. dist., with a healed blaze. (Record, S. 64° W.)</p> <p>and bearing tree mkd. by the Douglas County Surveyors Office in 1960</p> <p>A fir, 24 ins. diam., bears S. 81° E., 34.8 ft. dist., with a healed blaze. and bearing tree mkd. by the Douglas County Surveyors Office in 1967</p> <p>A fir, 20 ins. diam., bears N. 59 1/2° E., 22.7 ft. dist., with a healed double blaze.</p> <p>From this same point, the 1/4 sec. cor. of secs. 6 and 7, T. 24 S., R. 7 W., bears S. 89° 41' 53" E., 2737.02 ft. dist., described in the field notes of the resurvey of a portion of the subdivisional lines, T. 24 S., R. 7 W., executed concurrently under this same group.</p> <hr/> <p>N. 0° 08' 01" E., bet. secs. 1 and 6, beginning new measurement, posting and blazing.</p>
215	Graveled road, 9 ft. wide, bears N. 30° E. and S. 35° W.
380	Spur, slopes N. 70° E.; desc. broken NE. slope.
1345	Creek, 2 ft. wide, course N. 50° E.
1385	Creek, 2 ft. wide, course S. 70° E.; asc. broken SE. slope.
1800	Spur, slopes S. 82° E.; desc. broken NE. slope.
1960	Ravine, drains East; asc. broken SE. slope.
2260.54	<p>Point for the 1/4 sec. cor. of sec. 1 only, at proportionate distance. There is no remaining evidence of the orig. cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 S R8W R7W 1/4 S1 </p> <p>2005</p> </div> <p>from which</p> <p>A fir, 7 ins. diam., bears S. 29 1/4° W., 15.3 ft. dist., mkd. 1/4 S1 BT.</p> <p>A fir, 8 ins. diam., bears N. 63 1/4° W., 31.1 ft. dist., mkd. X BT.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
2614.28	The 1/4 sec. cor. of sec. 6 only, T. 24 S., R. 7 W., on the E. bdy. of the Tp., established by Leslie D. Roberts, Oregon PLS No. 1039, in 1979, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700646, and is accepted as the cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.
	<p style="text-align: center;">PLS 1039 T24S R7W 1/4 S6 1979</p>
	<p>from which the remains of a bearing tree mkd. by Roberts</p> <p style="padding-left: 40px;">A high-sawn fir stump, 8 ins. diam., bears S. 60° E., 46.6 ft. dist., with scribe marks 1/4 visible on a partially healed blaze.</p>
	<p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 89° E., 30.6 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 30° E., 25.1 ft. dist., mkd. 1/4 S6 BT.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N. 0° 08' 01" E., beginning new measurement; continue posting and blazing.</p>
	<p>Descend broken NE. slope.</p>
110	Creek, 1 ft. wide, course N. 68° E.; asc. broken SE. slope.
405	Spur, slopes N. 55° E.; desc. broken NW. slope.
965	Dry creek, course N. 75° E.; asc. broken SE. slope.
1965	Spur, slopes S. 60° E.; desc. broken NE. slope.
2372.47	The true point for the closing cor. of secs. 1 and 6, at the intersection with the township line, established by Leslie D. Roberts, Oregon PLS No. 1039, in 1979, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700700, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET

PLS 1039
T23S R8W
 S36
S1 | S6
R8W | R7W
1979

from which bearing trees mkd. by Roberts

A fir, 14 ins. diam., bears S. 57° E., 11.3 ft. dist., with a healed double blaze.

A fir, 23 ins. diam., bears S. 61 1/2° W., 64.1 ft. dist., with a healed double blaze.

From this point, the orig. closing cor. of secs. 1 and 6, T. 24 S., Rs. 7 and 8 W., established by Chandler in 1893, remonumented by the Douglas County Surveyors Office in 1960, and perpetuated by the Douglas County Surveyors Office in 1966 and 1984, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 700700, bears N. 0° 08' 01" E., 2.17 ft. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

SURVEYORS
T23S
AM
COUNTY R — CC — R OFFICE
8 S1 | S6 7
W W
T24S
1960

from which the remains of the orig. bearing trees

A decayed fir stump, size indeterminate, bears S. 57° E., 54.8 ft. dist., with no marks visible

A sawed fir stump, 50 ins. diam., bears S. 9 1/4° W., 77.2 ft. dist., with no marks visible. (Record, S. 12° W., 79.2 ft.)

and bearing trees mkd. by the Douglas County Surveyors Office in 1966

A fir, 28 ins. diam., bears N. 88 3/4° E., 32.6 ft. dist., with a healed blaze.

A fir, 20 ins. diam., bears S. 52 1/4° W., 73.0 ft. dist., with a healed blaze.

From this same point, the orig. cor. of secs. 31 and 36, T. 23 S., Rs. 7 and 8 W., established by Hutchinson in 1857, remonumented by the Douglas County Surveyors Office in 1960, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 08 W., Point Identifier No. 700100, bears N. 89° 52' 34" E., 216.01 ft. dist., monumented with an iron

**Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>post, 1 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SURVEYORS</p> <p>T23S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R S36</td> <td style="padding: 0 5px;">S31 R</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">8</td> <td style="padding: 0 5px;">7</td> </tr> </table> <p>W T24S W</p> <p>1960</p> </div> <p>from which the remains of the orig. bearing trees</p> <p style="margin-left: 40px;">A decayed fir stump, 30 ins. diam., bears S. 65° W., 38.9 ft. dist., with illegible scribe marks visible.</p> <p style="margin-left: 40px;">A fir, 40 ins. diam., bears N. 29° W., 75.9 ft. dist., with a healed blaze. (Record, 72.6 ft. dist.)</p> <p>and bearing tree mkd. by the Douglas County Surveyors Office, reported by White and Beck</p> <p style="margin-left: 40px;">A fir, 29 ins. diam., bears N. 72° E., 62.7 ft. dist., with a healed double blaze.</p> <p>and bearing tree mkd. by the Douglas County Surveyors Office, not reported by White and Beck</p> <p style="margin-left: 40px;">A fir, 32 ins. diam., bears N. 63° W., 53.4 ft. dist., with a healed double blaze.</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the North Boundary, T. 24 S., R. 8 W., Willamette Meridian, Oregon</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p style="text-align: center;">Restoring the 1893-94 survey by Williams R. Whipple and the 1894 survey by Henry L. Chandler</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p>From the true point for the closing cor. of secs. 1 and 6, on the N. bdy. of the Tp.</p> <p style="margin-left: 40px;">S. 89° 52' 34" W., bet. secs. 1 and 36, on the N. bdy of the Tp., posting and blazing.</p> <p style="margin-left: 40px;">Ascend broken NE. slope.</p> <p>360 Spur, slopes N. 30° W.; desc. broken W. slope.</p> <p>425 Graveled road, 12 ft. wide, bears S. 14° W. and N. 6° W.</p> <p>1720 Creek, 2 ft. wide, course North; asc. broken E. slope.</p>	R S36	S31 R	8	7
R S36	S31 R				
8	7				

**Dependent Resurvey of a Portion of the North Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
1990	Spur, slopes N. 50° E.; desc. broken NW. slope.
2145	Creek, 1 ft. wide, course N. 54° E.; asc. broken SE. slope.
2421.07	<p>The 1/4 sec. cor. of sec. 36 on the N. bdy of the Tp., reestablished by Leslie D. Roberts, Oregon PLS No. 1039, in 1982, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 643700, and is accepted as the cor., monumented with an iron post, 1 3/4 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> PLS 1039 R8W S36 1/4 <u>T23S</u> T24S 1982 </p> <p>from which the remains of bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A high-sawn fir stump, 14 ins. diam., bears N. 14° E., 10.8 ft. dist., with scribe marks 1/4 S36 visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 48 1/4° W., 12.7 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 55 3/4° W., 15.6 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>S. 89° 52' 34" W., on the N. bdy of the Tp., beginning new measurement; continue posting and blazing.</p> <p>Ascend broken E. slope.</p>
212.71	<p>The 1/4 sec. cor. of sec. 1 only, on the N. bdy of the Tp., remonumented by the Douglas County Surveyors Office in 1965, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 640700, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> SURVEYORS T24S COUNTY 1/4 OFFICE S1 R8W 1965 </p> <p>from which the remains of an orig. bearing tree</p>

**Dependent Resurvey of a Portion of the North Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET																					
	<p>A fir, 40 ins. diam., bears N. 11° W., 40.3 ft. dist., with scribe marks 1/4 S visible on an open blaze. (Record, N. 16 1/2° W.)</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A fir, 17 ins. diam., bears S. 16 1/2° E., 15.8 ft. dist., with a healed double blaze.</p> <p>A fir, 12 ins. diam., bears S. 58 1/2° W., 13.8 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 46' 45" W., on the N. bdy of the Tp., beginning new measurement; continue posting and blazing.</p>																				
320	Dirt road, 12 ft. wide, bears S. 6° E. and N. 6° W.																				
760	Spur, slopes N. 10° W.; desc. broken SW. slope and asc. broken NE. slope.																				
2245	Spur, slopes N. 25° E.; desc. NW. slope.																				
2330	Ravine, drains North; asc. NE slope.																				
2424.57	<p>The cor. of secs 35 and 36 on the N. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1964, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 603700, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: 0 auto;"> <tr> <td></td> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td></td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;">T24S</td> <td style="text-align: center;">OFFICE</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S35 S36</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R8W</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1964</td> <td></td> <td></td> </tr> </table> </div> <p>from which the remains of the orig. bearing trees</p> <p>A sawed fir stump, 55 ins. diam., bears N. 73 1/2° E., 35.0 ft. dist., with no marks visible.</p> <p>A sawed fir stump, 61 ins. diam., bears S. 48 1/2° W., 21.1 ft. dist., with no marks visible on an opened blaze. (Record, S. 2° W.)</p> <p>A sawed fir stump, 56 ins. diam., bears N. 5 1/2° W., 29.7 ft. dist., with no marks visible on an opened blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A fir, 22 ins. diam., bears N. 21 3/4° E., 16.3 ft. dist., with a healed double blaze.</p>		SURVEYORS			COUNTY	T24S	OFFICE			S35 S36				R8W				1964		
	SURVEYORS																				
COUNTY	T24S	OFFICE																			
	S35 S36																				
	R8W																				
	1964																				

**Dependent Resurvey of a Portion of the North Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 16 ins. diam., bears N. 74° W., 6.8 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 01' 47" W., bet. secs. 1 and 35; on the N. bdy of the Tp., beginning new measurement; continue posting and blazing.</p>																								
65	<p>Graveled road, 15 ft. wide, bears North and South.</p>																								
218.10	<p>The cor. of secs. 1 and 2, on the N. bdy of the Tp., remonumented by the Douglas County Surveyors Office in 1964, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 600700, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td></td> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R8W</td> <td style="text-align: center;">OFFICE</td> <td></td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;"> </td> <td></td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">S2 S1</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">T24S</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1964</td> <td></td> <td></td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by person(s) unknown, reported by the Douglas County Surveyors Office</p> <p>A roothole bears N. 9 1/2° E., 13.5 ft. dist., with fallen fir trunk, 16 ins. diam., lying alongside, scribe marks T23 8W S35 visible on a decayed blaze.</p> <p>A roothole bears N. 33 3/4° E., 22.5 ft. dist., with fallen fir trunk, 35 ins. diam., lying alongside, no marks visible.</p> <p>A roothole bears S. 69° E., 24.7 ft. dist., with fallen fir trunk, 14 ins. diam., lying alongside, no marks visible.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A roothole bears S. 77 3/4° E., 21.9 ft. dist., with fallen fir trunk, 16 ins. diam., lying alongside, scribe marks 24S R8W S1 C visible on a decayed blaze.</p> <p>A sawed fir stump, 33 ins. diam., bears S. 38 3/4° W., 34.3 ft. dist., with scribe marks 24S R8W S2 visible on a decayed blaze.</p> <p>and new bearing trees</p> <p>A fir, 12 ins. diam., bears S. 45 1/2° E., 25.7 ft. dist., mkd. T24S R8W S1 BT.</p> <p>A fir, 7 ins. diam., bears S. 73° W., 9.9 ft. dist., mkd. T24S R8W S2 BT.</p> <hr style="width: 20%; margin: 10px auto;"/>		SURVEYORS				R8W	OFFICE		COUNTY			OFFICE		S2 S1				T24S				1964		
	SURVEYORS																								
	R8W	OFFICE																							
COUNTY			OFFICE																						
	S2 S1																								
	T24S																								
	1964																								

**Dependent Resurvey of a Portion of the North Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET																															
	<p>N. 89° 27' 16" W., bet. secs. 2 and 35; on the N. bdy of the Tp., beginning new measurement; continue posting and blazing.</p> <p>Descend broken NW. slope.</p>																														
165	<p>Spur, slopes N. 7 E.; continue desc. broken NW. slope and asc. N. slope.</p>																														
1745	<p>Graveled road, 12 ft. wide, bears N. 40° E. and S. 40° W.</p>																														
2412.85	<p>The 1/4 sec. cor. of sec. 35 only, on the N. bdy. of the Tp., monumented with an iron post, 1 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td colspan="3">SURVEYORS</td> <td></td> </tr> <tr> <td></td> <td>T23S</td> <td></td> <td></td> <td></td> </tr> <tr> <td>COUNTY</td> <td>1/4 S35</td> <td>R</td> <td></td> <td>OFFICE</td> </tr> <tr> <td></td> <td colspan="3" style="border-top: 1px solid black;">8</td> <td></td> </tr> <tr> <td></td> <td>T24S</td> <td>W</td> <td></td> <td></td> </tr> <tr> <td></td> <td>1967</td> <td></td> <td></td> <td></td> </tr> </table> </div> <p>from which the remains of an orig. bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 26 ins. diam., bears N. 71° W., 9.2 ft. dist., with no marks visible.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyors Office in 1967, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 543700, reported by Malloy</p> <p style="padding-left: 40px;">A roothole bears N. 20° E., 21.1 ft. dist., with fallen fir trunk, 16 ins. diam., lying alongside, with a healed blaze. (Record, N. 30° E.)</p> <p style="padding-left: 40px;">A roothole bears N. 36 1/2° W., 21.8 ft. dist., with fallen hemlock trunk, 11 ins. diam., lying alongside, with a healed blaze. (Record, N. 30 1/2° W.)</p> <p>and bearing tree mkd. by Malloy</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears N. 58° E., 19.1 ft. dist., with scribe marks 1/4 S35 visible on a partially healed blaze.</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 23 1/2° E., 5.5 ft. dist., mkd. 1/4 S35 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 85° 34' 14" W., on the N. bdy of the Tp., beginning new measurement; continue posting and blazing.</p>		SURVEYORS					T23S				COUNTY	1/4 S35	R		OFFICE		8					T24S	W				1967			
	SURVEYORS																														
	T23S																														
COUNTY	1/4 S35	R		OFFICE																											
	8																														
	T24S	W																													
	1967																														
215.85	<p>The 1/4 sec. cor. of sec. 2 only, on the N. bdy of the Tp., remonumented by the Douglas County Surveyors Office in 1967, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point</p>																														

**Dependent Resurvey of a Portion of the North Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>Identifier No. 540700, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td></td> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td></td> </tr> <tr> <td rowspan="4" style="writing-mode: vertical-rl; transform: rotate(180deg); text-align: center;">COUNTY</td> <td style="text-align: center;">T23S</td> <td style="text-align: center;">R</td> <td rowspan="4" style="writing-mode: vertical-rl; transform: rotate(180deg); text-align: center;">OFFICE</td> </tr> <tr> <td style="text-align: center;">—</td> <td style="text-align: center;">8</td> </tr> <tr> <td style="text-align: center;">1/4 S2</td> <td style="text-align: center;">W</td> </tr> <tr> <td style="text-align: center;">T24S</td> <td></td> </tr> <tr> <td></td> <td colspan="2" style="text-align: center;">1967</td> <td></td> </tr> </table> </div> <p>from which the remains of an orig. bearing tree</p> <p style="margin-left: 40px;">A sawed fir stump, 66 ins. diam., bears N. 40° E., 10.6 ft. dist., with fragmentary scribe marks visible on an opened blaze.</p> <p>and remains of a bearing tree mkd. by the Douglas County Surveyors Office</p> <p style="margin-left: 40px;">A sawed cedar stump, 23 ins. diam., bears S. 27 1/4° W., 20.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 27° W., 8.6 ft. dist., mkd. 1/4 S2 BT.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 88 3/4° W., 8.7 ft. dist., mkd. 1/4 S2 BT.</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 8 W., Willamette Meridian, Oregon</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p style="text-align: center;">Restoring the 1894 survey by Henry L. Chandler and the 1959 remonumentation by Harold D. Corbin</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy of the Tp.</p> <p>N. 88° 44' 37" W., bet. secs. 1 and 12, posting and blazing.</p> <p>Ascend broken SE. slope.</p> <p>1140 Ridge, bears South and N. 15° W.; desc. broken NW. slope.</p> <p>2370 Creek, 1 ft. wide, course S. 32 E.; over flat, timbered ground.</p> <p>2570 Dirt road, 8 ft. wide, bears N. 25° E. and S. 25° W.</p> <p>2618.83 The 1/4 sec. cor. of secs. 1 and 12, remonumented by the Douglas County Surveyors Office in 1971 from orig. evidence no longer in existence, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 640600, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>		SURVEYORS			COUNTY	T23S	R	OFFICE	—	8	1/4 S2	W	T24S			1967		
	SURVEYORS																		
COUNTY	T23S	R	OFFICE																
	—	8																	
	1/4 S2	W																	
	T24S																		
	1967																		

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

FEET																																					
	<div style="text-align: center;"> <table border="0"> <tr> <td></td> <td colspan="2">SURVEYORS</td> <td></td> </tr> <tr> <td></td> <td>T24S</td> <td></td> <td>OFFICE</td> </tr> <tr> <td></td> <td>S 1</td> <td></td> <td></td> </tr> <tr> <td></td> <td>1/4</td> <td>_____</td> <td></td> </tr> <tr> <td></td> <td>S12</td> <td></td> <td></td> </tr> <tr> <td></td> <td>R8W</td> <td></td> <td></td> </tr> <tr> <td></td> <td>1971</td> <td></td> <td></td> </tr> </table> </div> <p>from which bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 26 3/4° E., 102.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 15° W., 12.4 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 53' 31" W., beginning new measurement; continue posting and blazing.</p> <p>Ascend broken SE. slope.</p> <p>1310 Graveled road, 16 ft. wide, bears N. 58° E. and S. 58° W.</p> <p>1470 Spur, slopes N. 48° E.; desc. broken SW. slope.</p> <p>2626.30 The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="0"> <tr> <td>T24S</td> <td>R8W</td> </tr> <tr> <td>S2</td> <td>S1</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> </table> <p>1959</p> </div> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A roothole bears N. 42 1/2° E., 16.5 ft. dist., with fallen hemlock trunk, 24 ins. diam., lying alongside, no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 66 ins. diam., bears S. 57° E., 29.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 63 ins. diam., bears S. 63° W., 11.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed hemlock stump, size indeterminate, bears N. 22° W., 38.3 ft. dist., with no marks visible.</p> <p>and remaining bearing trees mkd. by Corbin</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears S. 68 1/4° E., 33.8 ft. dist., with a healed blaze. (Record, 35.6 ft.)</p>		SURVEYORS				T24S		OFFICE		S 1				1/4	_____			S12				R8W				1971			T24S	R8W	S2	S1			S11	S12
	SURVEYORS																																				
	T24S		OFFICE																																		
	S 1																																				
	1/4	_____																																			
	S12																																				
	R8W																																				
	1971																																				
T24S	R8W																																				
S2	S1																																				
S11	S12																																				

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>A hemlock, 18 ins. diam., bears N. 27° W., 26.4 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 7 ins. diam., bears N. 52 3/4° E., 23.5 ft. dist., mkd. T24S R8W S1 BT.</p> <p>A hemlock, 13 ins. diam., bears S. 25° W., 50.4 ft. dist., mkd. T24S R8W S11 BT.</p> <hr/> <p>N. 0° 14' 54" W., bet. secs. 1 and 2, posting and blazing.</p> <p>Ascend SW. slope.</p> <p>25 Spur, slopes West; desc. broken NW. slope.</p> <p>310 Creek, 3 ft. wide, course S. 89° W.; asc. broken SE. slope.</p> <p>2280 Graveled road, 16 ft. wide, bears N. 37° E. and S. 14° W.</p> <p>2624.18 The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T24S R8W</p> <p>1/4</p> <p>— —</p> <p>S2 S1</p> <p>1959</p> </div> <p>from which the remains of the orig. bearing trees</p> <p>A sawed cedar stump, 28 ins. diam., bears S. 15° E., 28.8 ft. dist., with a healed blaze. (Record, 30.4 ft.)</p> <p>A sawed fir stump, 42 ins. diam., bears S. 44° W., 27.7 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Corbin</p> <p>A fir, 18 ins. diam., bears S. 26° E., 32.3 ft. dist., with a healed blaze.</p> <p>A fir, 32 ins. diam., bears N. 82 1/2° W., 28.4 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 13' 48" W., beginning new measurement; continue posting and blazing.</p> <p>Ascend broken SE. slope.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
460	Ridge, bears East and West; desc. broken NE. slope.
1245	Graveled road, 12 ft. wide, bears S. 41° E. and N. 41° W.
2766.00	The cor. of secs. 1 and 2 only.
	<hr/>
	GENERAL DESCRIPTION
	<p>The lands included in the foregoing survey are located in mountainous terrain, approximately 16 miles west-northwesterly from the community of Sutherlin, Oregon.</p> <p>The elevation ranges from approximately 800 feet above sea level near the closing corner of sections 7 and 18, on the east boundary of the township, to approximately 1400 feet above sea level near the 1/4 section corner of sections 1 and 2.</p> <p>The southerly portion of the survey is drained by minor unnamed tributaries of and flowing southwesterly to Rader Creek which continues southeasterly and combines with Wolf Creek which flows southeasterly to the Umpqua River. The northerly portion of the survey is drained by minor unnamed tributaries of Waggoner Creek which flows easterly to the Umpqua River.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>Access to the survey was made by graveled roads branching from Wolf Creek Road and Basin Creek Road.</p> <hr/>