

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
AND SUBDIVISIONAL LINES, AND SUBDIVISION OF SECTION 34

TOWNSHIP 25 SOUTH, RANGE 3 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Kenneth W. Saveland, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated April 10, 2008, approved April 14, 2008,
which provided for the surveys included under Group No. 2212,
and Assignment Instructions dated July 21, 2008.

Survey commenced July 23, 2008

Survey completed October 20, 2008

T. 25 S., R. 3 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and the subdivision of section 34, Township 25 South, Range 3 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855, Addison R. Flint, U.S. Deputy Surveyor, surveyed the north boundary and a portion of the subdivisional lines of T. 26 S., R. 3 W., as shown on the official plat of survey approved December 10, 1855.

In 1867, John Sittrell, U.S. Deputy Surveyor, surveyed a portion of the north and west boundaries, and a portion of the subdivisional lines, as shown on the official plat of survey approved July 31, 1867.

In 1877, W. H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines of T. 26 S., R. 3 W., as shown on the official plat of survey approved September 11, 1877.

In 1882, Samuel C. Flint, U.S. Deputy Surveyor, surveyed the remaining subdivisional lines of T. 26 S., R. 3 W., as shown on the official plat of survey approved October 23, 1882.

In 1883, Laban H. Wheeler, U.S. Deputy Surveyor, surveyed the remainder of the subdivisional lines, as shown on the official plat of survey approved May 19, 1884.

In 1943-44, Norman D. Price, Associate Cadastral Engineer, resurveyed the north, east, south, and west boundaries and subdivisional lines, as shown on the official plat of survey accepted January 7, 1946.

In 1993, Dale T. Bedell, Cadastral Surveyor, subdivided section 23, as shown on the official plat of survey accepted March 3, 1995.

In 1995, Bryan S. Seibold, Cadastral Surveyor, and Robert H Browning, Surveying Technician, resurveyed a portion of the north boundary and subdivisional lines, and subdivided section 3 of T. 26 S., R. 3 W., as shown on the official plat of survey accepted September 2, 1998.

The history of state authority surveys pertaining to this survey is as follows:

In 1948, Arthur R. Evans, Deputy County Surveyor, retraced a portion of the east boundary and subdivisional lines, and subdivided section 25, filed in the Douglas County Surveyor's Office, Map File No. M12-62 and at page No. 9 of Volume No. 5.

In 1959, Glen McChesney, Land Agent for the Springfield Branch of the Weyerhaeuser Timber Company, perpetuated certain corners, filed in the Douglas County Surveyor's Office, C.S. File No. 53/113.

T. 25 S., R. 3 W., Willamette Meridian, Oregon

FEET

In 1963, William S. Barnes, Registered Professional Engineer No. 2128, retraced a portion of the subdivisional lines and subdivided section 34, filed in the Douglas County Surveyor's Office, C.S. File No. 51/261A.

In 1963, William L. Wilt, Land Agent for the Springfield Branch of the Weyerhaeuser Timber Company, monumented certain corners in and around section 34, whose positions were established by Barnes prior that same year (see above), filed in the Douglas County Surveyor's Office, C.S. File No. 53/111, pages 13-15.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 10, 2008, for Group No. 2212, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) measurements.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.05 meters based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP", and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", are as follows:

The corner of sections 21, 22, 27, and 28:

Latitude: 43° 22' 32.84" N. Longitude: 123° 03' 09.44" W.

1/4 section corner of sections 13 and 24:

T. 25 S., R. 3 W., Willamette Meridian, Oregon

FEET

Latitude: 43° 23' 20.31" N. Longitude: 122° 59' 57.53" W.

The 1/4 section corner of sections 2 and 35, on the south boundary of the township:

Latitude: 43° 20' 38.07" N. Longitude: 123° 01' 13.77" W.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

**Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

Restoring the 1855 survey by Addison R. Flint and the 1943-44
resurvey by Norman D. Price

Beginning at the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 340100, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

S 33
1/4 —•—
S 4

1943

from which the remains of an original bearing tree

A fir snag, broken at base, 48 ins. diam., bears S. 85° E., 117.4 ft. dist., with fragmentary scribe marks visible on a broken open, weathered blaze. (Record, 114.2 ft.)

and bearing trees mkd. by Price

A fir, 16 ins. diam., bears S. 10 3/4° W., 10.6 ft. dist., with a healed blaze.

A fir, 22 ins. diam., bears N. 52 3/4° W., 17.8 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office

A fir snag, 8 ins. diam., bears S. 48° W., 21.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

**Dependent Resurvey of a Portion of South Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>Corner is located on a S. slope, N., 10 ft. dist. from the approximate intersection of a woven and barbed-wire fence line extending S. and a barbed-wire fence line extending E.</p> <p>S. 88° 56' 54" E., bet. secs. 4 and 33, on the S. bdy. of the Tp.</p> <p>Begin posting and blazing, along a wandering, dilapidated, woven and barbed-wire fence line.</p>												
275	Spur, slopes S. 40° E.												
330	Creek, 2 ft. wide, course S. 15° E.												
2642.46	<p>The cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1965, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 400100, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 25 S</td> <td style="padding: 0 5px;">R 3 W</td> </tr> <tr> <td style="padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; height: 1px;"></td> </tr> <tr> <td style="padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 26 S</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1943</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Price</p> <ul style="list-style-type: none"> A sawed, decayed fir stump, 38 ins. diam., bears N. 28° E., 73.6 ft. dist., with no marks visible. (Record, N. 30 1/2° E., 69.3 ft.) A roothole bears S. 56 1/2° E., 57.4 ft. dist., alongside of which is a down, decayed, cedar snag, 14 ins. diam., with no marks visible. A decayed cedar stump, 15 ins. diam., bears S. 14 3/4° W., 59.4 ft. dist., with no marks visible. A roothole bears N. 74 1/2° W., 39.6 ft. dist., alongside of which is an uprooted, sawed, decayed cedar stump, 36 ins. diam., with scribe marks S R3W S33 BT visible on an open blaze. <p>and bearing trees mkd. by the Douglas County Surveyor's Office</p> <ul style="list-style-type: none"> A cedar, 31 ins. diam., bears N. 34 3/4° E., 38.8 ft. dist., with a healed blaze. A cedar, 19 ins. diam., bears S. 65 1/2° E., 77.0 ft. dist., with a healed blaze. A cedar, 27 ins. diam., bears S. 85 1/2° W., 64.5 ft. dist., with a healed blaze. 	T 25 S	R 3 W	S 33	S 34			S 4	S 3	T 26 S		1943	
T 25 S	R 3 W												
S 33	S 34												
S 4	S 3												
T 26 S													
1943													

**Dependent Resurvey of a Portion of South Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>A cedar, 33 ins. diam., bears N. 4 1/4° W., 97.1 ft. dist., with a healed blaze.</p> <p>Corner is located on an E. slope, E., approximately 10 ft. dist. from the cor. of woven and barbed-wire fence lines extending S. and W.</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px;">T 25 S</td> <td style="padding: 2px;">R 3 W</td> </tr> <tr> <td style="padding: 2px;">S 34</td> <td style="padding: 2px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 3</td> <td style="padding: 2px;">S 2</td> </tr> <tr> <td colspan="2" style="padding: 2px;">T 26 S</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1943</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A sawed fir stump, 26 ins. diam., bears N. 69° E., 23.1 ft. dist., with no marks visible on an opened blaze.</p> <p>A fir, 46 ins. diam., bears S. 45° W., 6.6 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Price</p> <p>A decayed cedar stump, size indeterminate, bears N. 20 1/2° E., 29.7 ft. dist., alongside of which is a down, decayed cedar snag, 12 ins. diam., with scribe marks W 3 and other fragmentary scribe marks visible on a partially healed blaze.</p> <p>A cedar, 30 ins. diam., bears N. 62 1/2° W., 12.5 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Glen McChesney, Land Agent, in 1965, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 500100</p> <p>A sawed, decayed fir stump, 47 ins. diam., bears N. 1/2° W., 23.1 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by Seibold</p> <p>A fir, 10 ins. diam., bears N. 56 1/2° E., 10.9 ft. dist., with a healed double blaze.</p> <p>A fir, 13 ins. diam., bears S. 26 1/2° E., 41.9 ft. dist., with a healed blaze.</p> <p>Corner is located on a SE. slope.</p>	T 25 S	R 3 W	S 34	S 35	S 3	S 2	T 26 S		1943	
T 25 S	R 3 W										
S 34	S 35										
S 3	S 2										
T 26 S											
1943											

**Dependent Resurvey of a Portion of South Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	S. 88° 55' 19" E., bet. secs. 2 and 35, on the S. bdy. of the Tp., posting and blazing.
265	Gravel road, 16 ft. wide, bears N. 50° E. and S. 50° W.
2635.00	<p>The 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., perpetuated by Glen McChesney, Land Agent, in 1965, subsequently perpetuated by the Douglas County Surveyor's Office in 1966 and 1997, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 540100, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p align="center">DOUGLAS COUNTY SURVEYORS OFFICE T 25 S S 35 R 1/4 ——— 3 S 2 W T 26 S 1997</p> <p>from which the remains of bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A sawed fir stump, 47 ins. diam., bears S. 51° W., 35.6 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by McChesney</p> <p style="padding-left: 40px;">A roothole bears N. 18 3/4° E., 13.4 ft. dist.</p> <p style="padding-left: 40px;">A burnt, hollow cedar snag, size indeterminate, bears N. 49 1/4° W., 43.2 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1966</p> <p style="padding-left: 40px;">A roothole bears S. 25 1/2° W., 67.9 ft. dist., alongside of which is a down hemlock, 18 ins. diam., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Douglas County Surveyor's Office in 1997</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 45 1/4° E., 22.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 33° E., 24.0 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A roothole bears S. 85° W., 19.4 ft. dist., alongside of which is a down fir snag, 9 ins. diam., with a healed double blaze.</p> <p style="padding-left: 40px;">A roothole bears N. 54 3/4° W., 20.3 ft. dist., alongside of which is a down fir snag, 7 ins. diam., with scribe marks 1/4 visible on upper</p>

**Dependent Resurvey of a Portion of South Boundary,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>portion and BT visible on lower portion of a partially healed double blaze.</p> <p>Corner is located on a gradual, broken, SE. slope.</p> <hr/> <p align="center">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 3 W., Willamette Meridian, Oregon</p> <hr/> <p align="center">Restoring the 1883 survey by Laban H. Wheeler, the 1943-44 resurvey by Norman D. Price, and the 1993 survey by Dale T. Bedell</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p align="center"> $\begin{array}{c} 1/4 \\ S\ 26 \ \ S\ 25 \\ 1943 \end{array}$ </p> <p>from which the remains of the original bearing trees</p> <p>A partially uprooted cedar, 23 ins. diam., bears N. 37 3/4° E., 39.6 ft. dist., with no scribe marks visible on an opened blaze.</p> <p>A sawed, decayed fir stump, 37 ins. diam., bears N. 75° W., 5.9 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Price</p> <p>A roothole bears N. 42° E., 33.0 ft. dist., alongside of which is a down, decayed, fir snag, 21 ins. diam., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 8 ins. diam., bears N. 26 3/4° E., 7.6 ft. dist., mkd. 1/4 S25 BT.</p> <p>A cedar, 8 ins. diam., bears S. 53 1/4° W., 24.6 ft. dist., mkd. 1/4 S26 BT.</p> <p>Corner is located on a gradual E. slope, E., 180 ft. dist. from a gravel road, 12 ft. wide, bears N. 30° W. and S. 30° E.</p> <p>N. 1° 23' 33" E., bet. secs. 25 and 26, posting and blazing.</p> <p>1210 Spur, slopes S. 20° E.</p> <p>1360 Draw, drains N. 85° E.</p>
------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
1489.01	<p>The N 1/16 sec. cor. of secs. 25 and 26, established by Arthur R. Evans, Deputy County Surveyor, in 1948, and is accepted as the cor., monumented with an iron pipe, 23 ins. long, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of bearing trees mkd. by Evans</p> <p style="padding-left: 40px;">A sawed, decayed hemlock stump, size indeterminate, bears N. 83° E., 46.9 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed cedar stump, 42 ins. diam., bears S. 84 3/4° E., 29.9 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S 26 S 25 2008</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 71 1/4° E., 7.7 ft. dist., mkd. N 1/16 S25 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 35° W., 9.9 ft. dist., mkd. N 1/16 S26 BT.</p> <p>Place iron pipe inside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 27' 32" E., beginning a new measurement.</p>
1275	<p>Spur, slopes S. 45° E.</p>
1487.98	<p>The cor. of secs. 23, 24, 25, and 26, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 600300, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 3 W S 23 S 24 ----- S 26 S 25 1943</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole bears N. 11 1/2° E., 22.4 ft. dist., alongside of which is an uprooted, sawed, decayed hemlock stump, 40 ins. diam., with no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>A roothole bears S. 42° E., 52.8 ft. dist., alongside of which is a down, decayed fir snag, 34 ins. diam., with a healed blaze.</p> <p>A yew, 13 ins. diam., bears S. 45° W., 6.6 ft. dist., with scribe marks BT visible on a partially healed blaze.</p> <p>and the remains of a bearing trees mkd. by Price</p> <p>A sawed fir stump, 37 ins. diam., bears S. 51 1/4° W., 47.5 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A hemlock, 23 ins. diam., bears N. 41 1/2° E., 40.3 ft. dist., with a healed blaze.</p> <p>A roothole bears S. 18 1/4° E., 148.3 ft. dist., alongside of which is a down, decayed hemlock snag, size indeterminate, with no marks visible.</p> <p>A hemlock, 19 ins. diam., bears N. 9 3/4° W., 52.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 13 ins. diam., bears S. 63 1/4° E., 22.3 ft. dist., mkd. T25S R3W S25 BT.</p> <p>A fir, 13 ins. diam., bears S. 13 3/4° W., 16.6 ft. dist., mkd. T25S R3W S26 BT.</p> <p>Corner is located on a gradual E. slope.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25, perpetuated by Glen McChesney, Land Agent, in 1959, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 24 1/4 ——— S 25 1943</p> <p>from which bearing trees mkd. by Price</p> <p>A cedar, 28 ins. diam., bears S. 5° W., 14.5 ft. dist., with a healed blaze.</p> <p>A sawed, decayed fir stump, 55 ins. diam., bears N. 84 1/2° W., 46.2 ft. dist., with a healed blaze.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>and bearing trees mkd. by McChesney</p> <p style="padding-left: 40px;">A sawed cedar stump, 23 ins. diam., bears N. 52° E., 7.0 ft. dist., with no marks visible on a partially healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 25 3/4° W., 9.1 ft. dist., mkd. 1/4 S24 BT.</p> <p>Corner is located on a broken, NE. slope.</p> <p>S. 72° 44' 45" W., bet. secs. 24 and 25, posting and blazing.</p>
220	Spur, slopes South.
345	Gravel road, 14 ft. wide, bears N. 50° W. and S. 50° E.
1606.50	<p>The W 1/16 sec. cor. of secs. 24 and 25, established by Arthur R. Evans, Deputy County Surveyor, in 1948, perpetuated Glen McChesney, Land Agent, in 1959, and is accepted as the cor., monumented with an iron pipe, 29 ins. long, 1 1/4 ins. diam., firmly set, buried 3 ins. below ground surface, from which the remains of a bearing tree mkd. by Evans</p> <p style="padding-left: 40px;">A sawed, decayed hemlock snag, 27 ins. diam., bears N. 19 1/2° E., 44.8 ft. dist., with scribe marks 16 S24 CS visible on a partially healed blaze.</p> <p>and a bearing tree mkd. by McChesney</p> <p style="padding-left: 40px;">A sawed, decayed hemlock stump, 60 ins. diam., bears N. 60 3/4° W., 17.2 ft. dist., with axe marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p style="margin: 0;">S 24</p> <p style="margin: 0;">W 1/16 ———</p> <p style="margin: 0;">S 25</p> <p style="margin: 0;">2008</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 58 1/2° E., 5.5 ft. dist., mkd. W 1/16 S25 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 53 1/2° W., 10.1 ft. dist., mkd. W 1/16 S24 BT.</p> <p>Place iron pipe inside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner is located on a gradual E. slope.</p> <hr/>
	<p>S. 72° 41' 45" W., beginning a new measurement.</p>
135	<p>Gravel road, 18 ft. wide, bears N. 50° E. and S. 60° W., in curve.</p>
1607.10	<p>The cor. of secs. 23, 24, 25, and 26.</p> <hr/>
	<p>N. 0° 23' 39" E., bet. secs. 23 and 24, posting and blazing.</p>
35	<p>Dirt road, 8 ft. wide, bears N. 55° E. and S. 55° W.</p>
205	<p>Gravel road, 12 ft. wide, bears N. 55° W. and S. 55° E.</p>
2829.24	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a collar of stone, with brass cap mkd.</p>
	<p align="center"> $\begin{array}{c} 1/4 \\ S\ 23 \ \ S\ 24 \\ 1943 \end{array}$ </p>
	<p>from which the remains of the original bearing trees</p>
	<p>A roothole bears N. 20° E., 17.8 ft. dist., alongside of which is an uprooted, sawed, decayed fir stump, 60 ins. diam., with fragmentary scribe marks visible on a partially healed blaze.</p>
	<p>A sawed fir stump, 36 ins. diam., bears S. 65° W., 48.8 ft. dist., with scribe marks 23 visible on a partially healed blaze, with a metal cover.</p>
	<p>and the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1966, reported by Bedell</p>
	<p>A sawed, decayed fir stump, 15 ins. diam., bears N. 55° E., 141.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p>
	<p>A sawed hemlock stump, 18 ins. diam., bears S. 37° W., 70.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze, with a metal cover.</p>
	<p>and bearing trees mkd. by Bedell</p>
	<p>A fir, 17 ins. diam., bears S. 50° E., 10.2 ft. dist., with a healed blaze.</p>
	<p>A fir, 8 ins. diam., bears S. 82° W., 16.5 ft. dist., with a healed blaze.</p>
	<p>and the remains of a bearing tree mkd. by person(s) unknown</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>A sawed, decayed fir stump, 48 ins. diam., bears N. 31 1/2° W., 55.2 ft. dist., with a healed blaze and Weyerhaeuser aluminum bearing tree tag mkd. W.T. CO. Sec. 23 TWP 25 S. R. 8 W. 54.5 FT. S 31 E TO E 1/4 COR.</p> <p>Corner is located on a gradual S. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 24' 19" E., beginning a new measurement, posting and blazing.</p>								
215	<p>Spur, slopes East.</p>								
3075.29	<p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 25 S</td> <td style="padding: 0 5px;">R 3 W</td> </tr> <tr> <td style="padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 23</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 24</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1943</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A sawed fir stump, 27 ins. diam., bears S. 11 1/2° E., 29.7 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A sawed fir stump, 44 ins. diam., bears S. 46 1/2° W., 25.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. (Record, 21.8 ft.)</p> <p style="margin-left: 40px;">A fir, 29 ins. diam., bears N. 78° W., 24.4 ft. dist., with a healed double blaze.</p> <p>and the remains of bearing trees mkd. by Price</p> <p style="margin-left: 40px;">A sawed, decayed fir stump, 48 ins. diam., bears N. 12 1/2° E., 48.2 ft. dist., with fragmentary scribe marks visible on an open blaze.</p> <p style="margin-left: 40px;">A fir, 57 ins. diam., bears N. 37 1/2° W., 35.0 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Tony Hostetter, Registered Professional Land Surveyor (PLS) No. 1975, in 2000, filed in the Douglas County Surveyor's Office, C.S. File No. 65/45-31</p> <p style="margin-left: 40px;">A hemlock, 23 ins. diam., bears N. 59° E., 18.1 ft. dist., with scribe marks BT visible on a partially healed blaze, with an aluminum bearing tree tag mkd. LS1975 5/03.</p> <p style="margin-left: 40px;">A hemlock, 19 ins. diam., bears N. 35 1/2° W., 8.0 ft. dist., with fragmentary scribe marks visible on a partially healed blaze, with an aluminum bearing tree tag mkd. LS1975 5/03.</p>	T 25 S	R 3 W	S 14	S 13	S 23	S 24	1943	
T 25 S	R 3 W								
S 14	S 13								
S 23	S 24								
1943									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 6 ins. diam., bears S. 73 3/4° E., 31.3 ft. dist., mkd. T25S R3W S24 BT.</p> <p>Corner is located on a gradual SE. slope.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 640400, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td></td> <td style="text-align: center;">S 13</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">—————</td> </tr> <tr> <td></td> <td style="text-align: center;">S 24</td> </tr> <tr> <td></td> <td style="text-align: center;">1943</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir snag, 45 ins. diam., bears N. 11 1/4° E., 24.4 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A roothole bears S. 11° E., 28.4 ft. dist.</p> <p>and a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A fir, 59 ins. diam., bears N. 32° E., 77.9 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A sawed fir stump, 21 ins. diam., bears S. 31° E., 53.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears N. 32 1/4° W., 8.6 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 33 1/4° W., 49.1 ft. dist., mkd. 1/4 S24 BT.</p> <p>Corner is located on broken S. slope.</p> <p>S. 68° 54' 43" W., bet. secs. 13 and 24, posting and blazing.</p>		S 13	1/4	—————		S 24		1943
	S 13								
1/4	—————								
	S 24								
	1943								
3745.68	<p>The cor. of secs. 13, 14, 23, and 24.</p> <hr/> <p>N. 0° 12' 34" W., bet. secs. 13 and 14, posting and blazing.</p>								

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET 2974.23	<p>The 1/4 sec. cor. of secs. 13 and 14, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 600440, subsequently perpetuated by Tony Hostetter, Registered PLS No. 1975, in 2000, filed in the Douglas County Surveyor's Office, C.S. File No. 65/30-9, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p align="center"> $\begin{array}{c} 1/4 \\ S\ 14 \ \ S\ 13 \\ 1943 \end{array}$ </p> <p>from which the remains of bearing trees mkd. Price</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 36 ins. diam., bears S. 59° E., 37.0 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A burnt, decayed fir stump, 61 ins. diam., bears N. 77° W., 16.5 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A hemlock, 17 ins. diam., bears S. 87 3/4° E., 60.7 ft. dist., with scribe marks S13 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A roothole bears S. 71 3/4° W., 12.4 ft. dist., downhill from which is an uprooted, sawed fir stump, 12 ins. diam., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Hostetter</p> <p style="padding-left: 40px;">A hemlock snag, 13 ins. diam., bears S. 3 1/2° E., 6.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 6 1/2° W., 6.1 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 9 ins. diam., bears N. 70 1/4° E., 22.3 ft. dist., mkd. 1/4 S13 BT.</p> <p>Corner is located on a SW. slope.</p> <p align="center">_____</p> <p>N. 0° 48' 45" E., beginning a new measurement, posting and blazing.</p>
2972.79	<p>The cor. of secs. 11, 12, 13, and 14, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 600500, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET

T 25 S	R 3 W
S 11	S 12
S 14	S 13
1943	

from which the remains of the original bearing trees

- A sawed fir stump, 47 ins. diam., bears N. 86 1/2° E., 26.4 ft. dist., with no marks visible.
- A cedar, 31 ins. diam., bears S. 68 1/4° E., 15.2 ft. dist., with no marks visible on a hollow, burnt blaze.
- A sawed hemlock stump, 37 ins. diam., bears S. 53° W., 11.9 ft. dist., with fragmentary scribe marks visible on an open blaze.
- A sawed, decayed fir stump, 52 ins. diam., bears N. 38 1/4° W., 11.9 ft. dist., with a healed blaze.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office

- A hemlock, 24 ins. diam., bears N. 13 3/4° E., 14.9 ft. dist., with a healed blaze.
- A sawed, decayed cedar stump, 28 ins. diam., bears S. 41 1/2° E., 48.0 ft. dist., with a healed blaze.
- A hemlock, 10 ins. diam., bears N. 54 1/4° W., 21.0 ft. dist., with a healed blaze.

and a bearing tree mkd. by person(s) unknown

- A hemlock, 12 ins. diam., bears S. 53° E., 24.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze, and a brass washer, mkd. 2354, driven in blaze.

and a new bearing tree

- A fir, 5 ins. diam., bears S. 89° W., 16.8 ft. dist., mkd. T25S R3W S14 BT.

Raise a mound of stone, 2 1/2 ft. diam., 2 ft. high, around iron post.

Corner is located on a steep, N. slope.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.

N. 2° 08' 48" E., bet. secs. 34 and 35, posting and blazing.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

<p>FEET 3059.76</p>	<p>The 1/4 sec. cor. of secs. 34 and 35, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 500140, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p align="center"> $\begin{array}{c} 1/4 \\ S\ 34 \ \ S\ 35 \\ 1943 \end{array}$ </p> <p>from which the remains of an original bearing tree</p> <p>A decayed cedar stump, size indeterminate, bears N. 62° E., 14.5 ft. dist., with axe marks visible.</p> <p>and the remains of bearing trees mkd. by Price</p> <p>A decayed fir snag, 12 ins. diam., bears S. 35° E., 3.3 ft. dist., with scribe mark 3 and other fragmentary scribe marks visible on a partially healed blaze.</p> <p>A fir, 42 ins. diam., bears S. 88° W., 23.8 ft. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p>A fir, 23 ins. diam., bears S. 54 1/2° E., 31.8 ft. dist., with a healed blaze.</p> <p>Corner is located on a broken E. slope.</p> <p>Discontinue posting and blazing.</p> <hr/> <p>N. 0° 12' 00" E., beginning a new measurement.</p>
<p>1285</p>	<p>Gravel road, 12 ft. wide, bears N. 40° E and S. 40° W.</p>
<p>1338.56</p>	<p>The N 1/16 sec. cor. of secs. 34 and 35, established by William S. Barnes, Registered Professional Engineer No. 2128, in 1963, filed in the Douglas County Surveyors Office, C.S. File No. 51/261A, monumented by William L. Wilt, Land Agent, in 1963, filed in the Douglas County Surveyors Office, C.S. File No. 53/111, and is accepted as the cor., monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with an electrician's star lock nut and a smashed, threaded top, from which reference trees mkd. by Barnes</p> <p>A cedar, 13 ins. diam., bears N. 35 1/2° E., 19.7 ft. dist., with no marks visible, with a brass washer mkd. REG. ENGR. NO. ORE. 2128 at base and a metal tag.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p align="center">A fir, 20 ins. diam., bears N. 29 1/2° W., 17.7 ft. dist., with no marks visible and a metal tag.</p> <p>At the corner point</p> <p>Drive in iron pipe and set a stainless steel post directly over it, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table style="margin: auto; border-collapse: collapse;"> <tr><td align="center">N 1/16</td></tr> <tr><td align="center">S 34 S 35</td></tr> <tr><td align="center">2008</td></tr> </table> </p> <p>from which new bearing trees</p> <p align="center">A fir, 7 ins. diam., bears N. 53 1/4° E., 23.5 ft. dist., mkd. N 1/16 S35 BT.</p> <p align="center">A fir, 10 ins. diam., bears N. 50° W., 17.0 ft. dist., mkd. N 1/16 S34 BT.</p> <p>Place iron pipe inside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on a broken SE. slope.</p> <p align="center">_____</p> <p>N. 0° 09' 02" E., beginning a new measurement, posting and blazing.</p>	N 1/16	S 34 S 35	2008					
N 1/16									
S 34 S 35									
2008									
1337.64	<p>The cor. of secs. 26, 27, 34, and 35, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 500200, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <p align="center"> <table style="margin: auto; border-collapse: collapse;"> <tr><td align="center">T 25 S</td><td align="center">R 3 W</td></tr> <tr><td align="center">S 27 S 26</td><td></td></tr> <tr><td align="center">S 34 S 35</td><td></td></tr> <tr><td align="center">1943</td><td></td></tr> </table> </p> <p>from which the remains of the original bearing trees</p> <p align="center">A decayed hemlock stump, size indeterminate, bears S. 50 1/2° E., 26.4 ft. dist., with no marks visible.</p> <p align="center">A burned, decayed fir stump, 19 ins. diam., bears N. 45° W., 29.7 ft. dist., with no marks visible on an open blaze.</p> <p>and the remains of bearing trees mkd. by Price</p> <p align="center">A decayed pine stump, size indeterminate, bears N. 19 1/2° E., 14.5 ft. dist., with no marks visible.</p>	T 25 S	R 3 W	S 27 S 26		S 34 S 35		1943	
T 25 S	R 3 W								
S 27 S 26									
S 34 S 35									
1943									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>A sawed, decayed fir stump, 28 ins. diam., bears S. 15 1/2° E., 40.9 ft. dist., with no marks visible.</p> <p>A sawed, decayed, hollow pine stump, 72 ins. diam., bears S. 18° W., 44.2 ft. dist., with no marks visible.</p> <p>A fir snag, 56 ins. diam., bears N. 82 1/4° W., 38.3 ft. dist., with axe marks visible on a healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p>A hemlock, 17 ins. diam., bears S. 50 3/4° E., 37.6 ft. dist., with fragmentary scribe marks visible on a partially healed double blaze.</p> <p>and new bearing trees</p> <p>A fir, 8 ins. diam., bears N. 45 3/4° E., 42.8 ft. dist., mkd. T25S R3W S26 BT.</p> <p>A fir, 4 ins. diam., bears S. 72 1/4° W., 32.3 ft. dist., mkd. X at breast height and BT at base.</p> <p>A fir, 12 ins. diam., bears N. 60 3/4° W., 7.4 ft. dist., mkd. T25S R3W S27 BT.</p> <p>Corner is located on a gradual, broken, SE. slope.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 25 S</td> <td style="padding: 0 5px;">R 3 W</td> </tr> <tr> <td style="padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 35</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1943</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Price</p> <p>A fir, 50 ins. diam., bears N. 14 1/4° E., 43.6 ft. dist., with a healed blaze.</p> <p>A sawed, decayed fir stump, 29 ins. diam., bears S. 26 3/4° E., 36.3 ft. dist., with no marks visible.</p> <p>A fir, 45 ins. diam., bears S. 71 3/4° W., 27.1 ft. dist., with a healed blaze.</p> <p>A sawed, decayed fir stump, 17 ins. diam., bears N. 53 1/2° W., 40.9 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p>	T 25 S	R 3 W	S 26	S 25	S 35	S 36	1943	
T 25 S	R 3 W								
S 26	S 25								
S 35	S 36								
1943									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>A cedar, 16 ins. diam., bears S. 49 3/4° E., 62.0 ft. dist., mkd. T25S R3W S36 BT.</p> <p>A fir, 6 ins. diam., bears N. 45 1/2° W., 62.6 ft. dist., mkd. T25S R3W S26 BT.</p>
	<p>Corner is located on a broken E. slope.</p>
	<p>N. 72° 38' 26" W., bet. secs. 26 and 35, posting and blazing.</p>
2465	<p>Spur, slopes S. 60° E.</p>
2620	<p>Bottom of swale, drains S. 10° E.</p>
2710	<p>Spur, slopes South.</p>
2768.24	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;"> S 26 1/4 ——— S 35 1943 </p>
	<p>from which remains of bearing trees mkd. by Price</p>
	<p>A roothole bears N. 22 3/4° E., 17.2 ft. dist., alongside of which is a down fir snag, 19 ins. diam., with a healed blaze.</p>
	<p>A yew, 17 ins. diam., bears S. 30 1/2° E., 35.6 ft. dist., with scribe marks 1/4 S visible on a partially healed blaze.</p>
	<p>and a new bearing tree</p>
	<p>A fir, 7 ins. diam., bears N. 39 3/4° E., 31.3 ft. dist., mkd. 1/4 S26 BT.</p>
	<p>Corner is located in a swale, drains S. 30° E.</p> <hr style="width: 20%; margin: 0 auto;"/>
	<p>N. 72° 26' 39" W., beginning a new measurement.</p>
2769.38	<p>The cor. of secs. 26, 27, 34, and 35.</p> <hr style="width: 60%; margin: 0 auto;"/>
	<p>From the 1/4 sec. cor. of secs. 26 and 27, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 500240, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

<p>FEET</p>	<p style="text-align: center;"> $\frac{1}{4}$ S 27 S 26 1943 </p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 53 ins. diam., bears South, 35.6 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A sawed fir stump, 68 ins. diam., bears S. 60 1/2° W., 104.9 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A hemlock stump, size indeterminate, bears S. 53 3/4° W., 27.7 ft. dist., with no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 1/4° E., 13.3 ft. dist., mkd. 1/4 S26 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 60° W., 4.8 ft. dist., mkd. 1/4 S27 BT.</p> <p>N. 0° 33' 27" E., bet. secs. 26 and 27, posting and blazing.</p> <p>2895 Graveled road, 25 ft. wide, bears S. 80° E. and N. 80° W.</p> <p>2969.13 The cor. of secs. 22, 23, 26, and 27, perpetuated by the Douglas County Surveyor's Office in 1966, subsequently perpetuated by Mark F. Smalley, Oregon PLS No. 2354, in 1996, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 500300, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, with brass cap oriented south, mkd.</p> <p style="text-align: center;"> T 25 S R 3 W S 22 S 23 ----- S 27 S 26 1943 </p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 38 ins. diam., bears S. 60° W., 17.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 29 ins. diam., bears N. 64 1/4° W., 19.1 ft. dist., with no marks visible.</p> <p>and the remaining bearing tree mkd. by Price</p>
-------------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>A hemlock snag, 20 ins. diam., bears S. 23° W., 15.8 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p>A hemlock, 19 ins. diam., bears N. 58 1/4° W., 42.6 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Smalley</p> <p>A fir, 8 ins. diam., bears N. 62° E., 23.8 ft. dist., with a healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 46 1/2° E., 22.9 ft. dist., with a healed blaze.</p> <p>A fir, 9 ins. diam., bears N. 77 3/4° W., 16.4 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 11 ins. diam., bears S. 4 1/2° W., 40.9 ft. dist., mkd. T25S R3W S27 BT.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26, determined at record bearing and dist. from the bearing trees mkd. by Bedell</p> <p>A fir, 25 ins. diam., bears N. 7 1/2° E., 43.6 ft. dist., with a healed blaze.</p> <p>A fir, 9 ins. diam., bears S. 5 1/4° W., 13.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 3 W S 23 1/4 ——— S 26 2008</p> <p>(Note: The iron post, 36 ins. long, 1 in. diam., with brass cap mkd. 1/4 S23 S26 1943, set by Price, was found lying loose on the ground nearby.)</p> <p>Bury the iron post along the SE. side of the stainless steel post and bury a magnet in a white plastic case at the base of the stainless steel post.</p> <p>N. 61° 39' 16" W., bet. secs. 23 and 26, posting and blazing.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
2255	Graveled road, 25 ft. wide, bears N. 60° E. and S. 80° W.
2573.04	The cor. of secs. 22, 23, 26 and 27.
	<hr/> <p>N. 6° 33' 53" E., bet. secs. 22 and 23, posting and blazing.</p> <p>Ascend over broken SW. slope.</p>
3295.05	<p>The 1/4 sec. cor. of secs. 22 and 23, perpetuated by James W. Byron, Deputy County Surveyor, in 1960, subsequently perpetuated by the Douglas County Surveyor's Office in 1966, further perpetuated by Mark F. Smalley, Oregon PLS No. 2354, in 1996, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 500340, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p align="center"> $\begin{array}{c} 1/4 \\ S\ 22 \ \ S\ 23 \\ 1943 \end{array}$ </p> <p>from which the remains of a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A fir stump, size indeterminate, bears S. 86° W., 27.1 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A hemlock stump, size indeterminate, bears S. 83 3/4° E., 48.7 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 41 ins. diam., bears N. 22 1/4° W., 4.0 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 57 1/2° E., 50.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 72 1/2° W., 39.4 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by Smalley</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 43 1/4° E., 5.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 85 1/4° W., 22.2 ft. dist., with a healed blaze.</p> <hr/>
	<hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

FEET	
	<p>N. 50° 46' 06" W., bet. secs. 14 and 23, posting and blazing.</p>
2345	<p>Draw, drains S. 80° E.</p>
2454.28	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 14 1/4 ——— S 23 1943</p> </div> <p>from which the remains of bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A decayed hemlock stump, size indeterminate, bears N. 56 1/2° E., 33.7 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A decayed fir snag, 40 ins. diam., bears S. 79° W., 207.9 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by Tracy, reported by Bedell</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 20 1/2° W., 53.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 6° W., 5.9 ft. dist., with a healed blaze.</p> <p>Corner is located on a gradual SE. slope, N., 45 ft. dist. from a draw, drains S. 80° E.</p> <hr/>
2510.53	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.</p> <p>N. 2° 11' 01" E., bet. secs. 33 and 34, posting and blazing.</p> <p>The 1/4 sec. cor. of secs. 33 and 34, perpetuated by Frank O. Williams, Registered Professional Engineer No. 875, in 1978, filed in Douglas County Surveyor's Office, C.S. File No. 58/8-44, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 33 S 34 1943</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole bears S. 23° E., 17.8 ft. dist., alongside of which is an uprooted, sawed fir stump, 36 ins. diam., with axe marks visible.</p> <p style="padding-left: 40px;">A vine maple cluster bears N. 60° W., 6.6 ft. dist., with no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>and the remains of bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A cedar, 33 ins. diam., bears N. 87 1/2° E., 27.7 ft. dist., with axe marks visible.</p> <p style="padding-left: 40px;">A roothole bears S. 86 1/4° W., 24.4 ft. dist., alongside of which is an uprooted, sawed, decayed fir stump, with no marks visible.</p> <p>and the remains of a bearing tree by Williams</p> <p style="padding-left: 40px;">A sawed fir stump, 41 ins. diam., bears N. 49° E., 80.1 ft. dist., with no marks visible.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 68 3/4° W., 23.1 ft. dist., mkd. 1/4 S33 BT.</p> <p>Corner is located on a broken S. slope.</p> <p style="text-align: center;">_____</p> <p>N. 1° 45' 54" W., beginning a new measurement.</p>								
2612.36	<p>The cor. of secs. 27, 28, 33, and 34, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 400200, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 25 S</td> <td style="padding: 0 10px;">R 3 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1943</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, size indeterminate, bears N. 32° E., 62.0 ft. dist., with scribe mark T visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, size indeterminate, bears S. 61 3/4° E., 50.2 ft. dist., with axe marks visible.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 84° W., 18.5 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 31° W., 23.8 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office</p>	T 25 S	R 3 W	S 28	S 27	S 33	S 34	1943	
T 25 S	R 3 W								
S 28	S 27								
S 33	S 34								
1943									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>A sawed fir stump, 19 ins. diam., bears N. 13° E., 73.4 ft. dist., with scribe marks CS BT visible on a partially healed blaze.</p> <p>A sawed fir stump, 23 ins. diam., bears N. 25 3/4° W., 47.1 ft. dist., with no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 9 ins. diam., bears N. 66 1/4° E., 17.9 ft. dist., mkd. T25S R3W S27 BT.</p> <p>A fir, 9 ins. diam., bears S. 84 1/2° E., 8.9 ft. dist., mkd. T25S R3W S34 BT.</p> <p>A fir, 8 ins. diam., bears S. 49° W., 10.6 ft. dist., mkd. T25S R3W S33 BT.</p> <p>A fir, 9 ins. diam., bears N. 46° W., 20.4 ft. dist., mkd. T25S R3W S28 BT.</p> <p>Corner is located on a broken S. slope.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 84° 22' 43" W., bet. secs. 27 and 34, posting and blazing.</p>
260	Creek, 1 ft. wide, course S. 30° W.
1351.93	Point for the E 1/16 sec. cor. of secs. 27 and 34, no permanent monument set.
2703.86	<p>The 1/4 sec. cor. of secs. 27 and 34, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 440200, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 27</p> <p>1/4 ———</p> <p>S 34</p> <p>1943</p> </div> <p>from which the remains of bearing trees mkd. by Price</p> <p>A fir snag, 37 ins. diam., bears N. 7° E., 28.4 ft. dist., with a hollow blaze.</p> <p>A sawed fir stump, 36 ins. diam., bears S. 64° E., 10.6 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

<p>FEET</p>	<p>A decayed hemlock snag, 12 ins. diam., bears N. 51° E., 26.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>A hemlock, 20 ins. diam., bears S. 29° E., 10.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 9 ins. diam., bears N. 56 1/2° E., 10.2 ft. dist., mkd. 1/4 S27 BT.</p> <p>Corner is located on a broken E. slope.</p> <hr/> <p>S. 84° 24' 07" W., beginning a new measurement.</p>
<p>2450</p>	<p>Draw, drains East.</p>
<p>2698.72</p>	<p>The cor. of secs. 27, 28, 33, and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 400240, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 28 S 27 1943</p> </div> <p>from which the remains of a bearing tree mkd. by Price</p> <p>A sawed fir stump, 47 ins. diam., bears S. 44° W., 38.9 ft. dist., with no marks visible.</p> <p>and the bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A hemlock, 16 ins. diam., bears S. 34 3/4° E., 28.0 ft. dist., with a healed blaze.</p> <p>A cedar, 15 ins. diam., bears N. 86 1/4° W., 46.3 ft. dist., with a healed blaze.</p> <p>N. 5° 50' 25" W., bet. secs. 27 and 28, posting and blazing.</p>
<p>3202.04</p>	<p>The cor. of secs. 21, 22, 27, and 28, perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 400300, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 25 S</td> <td style="padding: 0 5px;">R 3 W</td> </tr> <tr> <td style="padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 28</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1943</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <ul style="list-style-type: none"> A sawed fir stump, 24 ins. diam., bears N. 29 3/4° E., 26.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. A hemlock stump, 32 ins. diam., bears S. 55° E., 18.5 ft. dist., with scribe marks 25S R W visible on a partially healed blaze. A fir stump, size indeterminate, bears N. 24° W., 9.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. (Record, 8.6 ft.) <p>and remains of bearing trees mkd. by the Douglas County Surveyor's Office</p> <ul style="list-style-type: none"> A hemlock stump, 17 ins. diam., bears N. 56 1/2° E., 13.8 ft. dist., with no marks visible. A hemlock, 24 ins. diam., bears S. 27° W., 59.0 ft. dist., with a healed double blaze. A hemlock, 8 ins. diam., bears N. 73 3/4° W., 41.5 ft. dist., with a healed double blaze. <p>and new accessories</p> <ul style="list-style-type: none"> A rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears N. 50° 15' 41" E., 31.00 ft. dist., with aluminum cap mkd. RM T25S R3W S22 31.0 FT TO COR 2008 and an arrow pointing to the corner. A fir, 15 ins. diam., bears S. 80 3/4° E., 8.7 ft. dist., mkd. T25S R3W S27 BT. <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>S. 88° 59' 50" W., bet. secs. 22 and 27, posting and blazing.</p> <p>3082.07 The 1/4 sec. cor. of secs. 22 and 27, perpetuated by the Douglas County Surveyor's Office in 1966 and 1986, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 440300, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>	T 25 S	R 3 W	S 21	S 22	S 28	S 27	1943	
T 25 S	R 3 W								
S 21	S 22								
S 28	S 27								
1943									

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">S 22 1/4 ——— S 27 1943</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 47 ins. diam., bears S. 20° E., 10.6 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A roothole bears N. 42° W., 12.5 ft. dist., alongside of which is the fallen cedar trunk, 38 ins. diam., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1966</p> <p style="padding-left: 40px;">A hemlock stump, size indeterminate, bears S. 49 1/4° E., 26.2 ft. dist., with scribe marks 1/4 S visible on an open blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office in 1986</p> <p style="padding-left: 40px;">A hemlock, 13 ins. diam., bears N. 13 3/4° E., 24.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A hemlock, 22 ins. diam., bears N. 62 3/4° W., 45.5 ft. dist., with a healed double blaze.</p> <p>and bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A hemlock, 11 ins. diam., bears N. 46 3/4° E., 8.9 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 42 3/4° E., 10.9 ft. dist., mkd. 1/4 S27 BT.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. 89° 06' 43" W., beginning new measurement.</p>
3041.18	<p>The cor. of secs. 21, 22, 27, and 28.</p> <hr style="width: 80%; margin-left: 0;"/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 89° 48' 48" W., bet. secs. 28 and 33, posting and blazing.</p>
2587.93	<p>The 1/4 sec. cor. of secs. 28 and 33, perpetuated by the Douglas County Surveyor's Office in 1966, filed in Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 340200, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above a collar of stone, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p align="center">S 28 1/4 ——— S 33 1943</p> <p>from which the remains of an original bearing tree</p> <p>A sawed, decayed fir stump, 49 ins. diam., bears N. 61° E., 4.0 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Price</p> <p>A sawed fir stump, 29 ins. diam., bears S. 23 1/2° E., 31.0 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A cedar, 25 ins. diam., bears S. 76 1/2° E., 34.7 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears N. 7 1/2° W., 4.9 ft. dist., with a healed blaze.</p> <p>Corner is located on a W. slope.</p> <hr/> <p align="center">Subdivision of Section 34, T. 25 S., R. 3 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <p align="center">S 34 1/4 ——— S 3 1943</p> <p>from which the remaining original bearing tree</p> <p>A cedar, 27 ins. diam., bears S. 17° W., 2.6 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Price</p> <p>A sawed fir stump, 52 ins. diam., bears N. 15° W., 15.2 ft. dist., with axe marks visible.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office in 1966, reported by Seibold</p>

**Subdivision of Section 34,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>A cedar, 23 ins. diam., bears S. 7 1/2° E., 31.7 ft. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office, in 1976, reported by Seibold</p> <p>A cedar, 26 ins. diam., bears N. 77° E., 23.8 ft. dist., with a healed double blaze.</p> <p>Corner is located on a SW. slope, E., 25 ft. dist. from a creek, 3 ft. wide, course S. 35° E.</p> <p>N. 0° 54' 08" E., on the N. and S. centerline of sec. 34.</p>
2768.98	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 3 W C 1/4 S 34 2008</p> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 78 1/4° E., 24.1 ft. dist., mkd. C 1/4 S34 BT.</p> <p>A cedar, 7 ins. diam., bears N. 18 1/4° W., 14.4 ft. dist., mkd. C 1/4 S34 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located E., 185 ft. dist. from a dirt road, 11 ft. wide, bears N. 10° W. and S. 25° E., in curve.</p>
4093.43	Point for the center N 1/16 sec. cor. of sec. 34, no permanent monument set.
5417.88	The 1/4 sec. cor. of secs. 27 and 34.
	<hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>S. 85° 04' 51" W., on the E. and W. centerline of sec. 34, posting and blazing.</p>
1367.05	The center E 1/16 sec. cor. of sec. 34, established by William S. Barnes, Registered Professional Engineer No. 2128, in 1963, filed in the Douglas County Surveyors Office, C.S. File No. 51/261A, monumented by William L. Wilt, Land Agent, in 1963, filed in the Douglas County Surveyors Office, C.S. File No. 53/111, and is accepted as the cor., monumented with an

**Subdivision of Section 34,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>iron pipe, 33 ins. long, 1 1/4 ins. diam., loosely set, projecting 12 ins. above a collar of stone, from which the remains of reference trees mkd. by Barnes</p> <p style="padding-left: 40px;">A sawed cedar stump, 36 ins. diam., bears S. 53° W., 21.1 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed, decayed cedar stump, 12 ins. diam., bears N. 37° W., 26.8 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E \ 1/16 \\ \hline C \ \ \ \ C \\ S \ 34 \\ 2008 \end{array}$ </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 1 1/4° W., 13.7 ft. dist., mkd. CE 1/16 S34 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 88 1/2° W., 11.1 ft. dist., mkd. X at breast height and BT at base.</p> <p>Place iron pipe inside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 25%; margin-left: auto; margin-right: auto;"/> <p>S. 84° 58' 01" W., beginning a new measurement.</p>
1367.97	The center 1/4 sec. cor. of sec. 34.
3941.88	The 1/4 sec. cor. of secs. 33 and 34.
	<hr/> <p>From the center E 1/16 sec. cor. of sec. 34.</p> <p>N. 0° 31' 48" E., on the N. and S. centerline of the NE 1/4 of sec. 34, posting and blazing.</p>
1330.07	<p>Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E. and W. centerline of the NE 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

T. 25 S., R. 3 W., Willamette Meridian, Oregon

<p>FEET</p>	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands embraced in the foregoing survey are located in mountainous terrain, approximately 6 miles northeasterly of Glide, Oregon.</p> <p>The elevation ranges from about 1600 feet above sea level near the corner of sections 25, 26, 35, and 36, to about 3400 feet above sea level near the 1/4 section corner of sections 13 and 14.</p> <p>The area is drained by McComas Creek which flows southeasterly into Rock Creek and Old Hatchery Creek which flows southerly into the North Umpqua River.</p> <p>Timber consists of alder, cedar, chinquapin, fir, madrone, maple, oak, pine, and yew. Undergrowth consists of fern, Oregon grape, poison oak, salal, and vine maple.</p> <p>The soil is generally composed of rocky clay. No mineral deposits were noted along the lines surveyed, however there is a rock pit situated in the NW 1/4 of section 35.</p> <p>Access to the survey was made by graveled roads branching from Oregon State Highway No. 138 and County Route No. 78.</p> <hr/>
-------------	--