

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF PORTIONS OF THE EAST BOUNDARY
AND SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTIONS 2 AND 13,
TOWNSHIP 26 SOUTH, RANGE 5 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

A. Bert Skeesick, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated February 2, 2004, approved February 6, 2004,
which provided for the surveys included under Group No. 2065,
and Assignment Instructions dated February 13, 2004

Survey commenced May 4, 2004

Survey completed April 4, 2005

T. 26 S., R. 5 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of portions of the east boundary and subdivisional lines, and the subdivision of sections 2 and 13, Township 26 South, Range 5 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1851, James E. Freeman, U.S. Deputy Surveyor, surveyed a portion of the east boundary.

In 1853, Robert Elder and Henry T. Gile, U.S. Deputy Surveyors, surveyed a portion of the east boundary and subdivisional lines.

In 1963, C. Albert White and Donald R. Beck, Cadastral Surveyors, dependently resurveyed portions of the south boundary and subdivisional lines and subdivided section 35, Township 25 South, Range 5 West.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated February 2, 2004, for Group No. 2065, Oregon.

The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) static measurement techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The GPS portion of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys using Global Positioning System Methods", dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management (BLM), and the United States Department of Agriculture, Forest Service.

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS techniques and carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The Standard Error of Unit Weight for the least squares adjustment of the survey data fell between 0.7 and 2.5. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

T. 26 S., R. 5 W., Willamette Meridian, Oregon

FEET

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 13, 18, 19, and 24, as determined from a tie to geodetic control station EC 41298, established by the BLM in 2004, (see the Control Data Sheet attached to these field notes following the General Description), is as follows:

Latitude: 43° 18' 04.05" N. Longitude: 123° 13' 36.74" W.

The geographic position (NAD 1983 (CORS 96)) of the 1/4 section corner of sections 10 and 11, as determined from a tie to geodetic control station EC 41298, established by the BLM in 2004, (see the Control Data Sheet attached to these field notes following the General Description), is as follows:


Latitude: 43° 19' 25.23" N. Longitude: 123° 15' 58.93" W.

**Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

Restoring the 1851 survey of James E. Freeman,
and the 1853 survey by Robert Elder and Henry T. Gile

Beginning at the cor. of secs. 13, 18, 19, and 24, reestablished at proportionate dist. by James W. Byron, Deputy County Surveyor, in 1958, perpetuated by Randall Smith, of the Douglas County Surveyors Office, in 1986, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier No. 700400, accepted as the cor., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, buried 15 ins. below the surface of the ground, with brass cap (oriented to the east) mkd.

COUNTY SURVEYORS OFFICE



1958

from which the remaining bearing tree mkd. by Byron

An oak, 19 ins. diam., bears S. 42 3/4° W., 296.2 ft. dist., with a healed double blaze.

**Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>and the remaining bearing tree mkd. by Smith</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears S. 72 1/4° E., 317.4 ft. dist., with a healed double blaze.</p> <p>and unrecorded reference monuments set by Kenneth W. Hoffine, Registered Professional Land Surveyor (PLS) No. 2291, date unknown</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground for a reference monument, bears N. 61° 01' 55" W., 314.0 ft. dist., with yellow plastic cap mkd. LONE ROCK TIMBER LS 2291.</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., firmly set, flush with the ground for a reference monument, bears N. 11° 59' 15" W., 340.5 ft. dist., with yellow plastic cap mkd. LONE ROCK TIMBER LS 2291.</p> <p>Corner is located in the center of a cultivated field, and located 208.4 ft. N. of County Road No. 200, 20 ft. wide, which bears N. 50° E., S. 50° W.</p> <p>From this cor., the meander cor. on the left bank of the North Umpqua River, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, further perpetuated by William C. Stiles, Registered PLS No. 432, in 1960, recorded in the Douglas County Surveyors Office Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier No. 700343, bears S. 0° 16' 36" E., 2466.92 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, buried 26 ins. below the surface of the ground, with no cap, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears S. 63° E., 157.1 ft. dist., with no marks remaining on an opened and decayed double blaze.</p> <p>and a reference monument set by Byron</p> <p style="padding-left: 40px;">An iron pipe, 1 1/2 ins. diam., projecting 12 ins. above the ground for a reference monument, bears S. 0° 00' 16" E., 165.0 ft. dist. with brass cap mkd. COUNTY SURVEYORS OFFICE WIT. COR. 165 FT. NORTH TO M.C. R5W S24 S19 R4W T26S 1958.</p> <p>and bearing trees mkd. by Byron for the reference monument</p> <p style="padding-left: 40px;">An oak, 9 ins. diam., bears N. 64 1/4° E., 16.7 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An oak, 11 ins. diam., bears S. 35 1/4° W., 53.2 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Remove the iron rod, and in its place, drive a finned aluminum rod, 36 ins. long, 3/4 in. diam., 50 ins. in the ground, with aluminum cap mkd.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>2630.42 The 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier No. 700440, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; padding: 0 5px;">R</td> <td style="text-align: center; padding: 0 5px;">1</td> <td style="text-align: center; padding: 0 5px;">S</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="text-align: center; padding: 0 5px;">S</td> <td style="text-align: center; padding: 0 5px;">R</td> </tr> <tr> <td style="text-align: center; padding: 0 5px;">5</td> <td style="text-align: center; padding: 0 5px;">/</td> <td style="text-align: center; padding: 0 5px;">4</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="text-align: center; padding: 0 5px;">18</td> <td style="text-align: center; padding: 0 5px;">4</td> </tr> <tr> <td style="text-align: center; padding: 0 5px;">W</td> <td></td> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td></td> <td style="text-align: center; padding: 0 5px;">W</td> </tr> </table> <p style="margin: 5px 0 0 0;">T 26 S 1958</p> </div> <p>from which the remains of the original bearing tree</p> <p style="margin-left: 40px;">An oak, 48 ins. diam., bears N. 8° W., 211.2 ft. dist., with fragmentary scribe marks visible on a partially opened blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="margin-left: 40px;">An oak, 14 ins. diam., bears N. 23 1/4° E., 104.7 ft. dist., with a healed double blaze.</p> <p style="margin-left: 40px;">An oak, 18 ins. diam., bears S. 81 1/2° W., 91.2 ft. dist., with a healed double blaze.</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <div style="text-align: center; margin: 0 auto 20px auto;"> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 5 W., Willamette Meridian, Oregon</p> </div> <hr style="border: 0.5px solid black; margin: 0 auto 20px auto; width: 60%;"/> <p style="margin-left: 40px;">Restoring the 1853 survey by Robert Elder and Henry T. Gile</p> <hr style="border: 0.5px solid black; margin: 0 auto 20px auto; width: 30%;"/> <p>From the cor. of secs. 13, 18, 19, and 24.</p> <p>N. 89° 19' 10" W., bet. secs. 13 and 24.</p> <p>Ascend over cultivated pastures and cleared SE. slopes.</p>	R	1	S		S	R	5	/	4		18	4	W					W
R	1	S		S	R														
5	/	4		18	4														
W					W														
2619.92	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>																		

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<div style="text-align: center; margin-bottom: 20px;"> <p>T 26 S R 5 W S 13 1/4 _____ S 24 2004</p> </div> <p>from which</p> <p style="margin-left: 40px;">A finned aluminum rod, 36 ins. long, 3/4 in. diam., driven flush with the ground for a reference monument, bears S. 11° 28' 57" E., 37.9 ft. dist. with aluminum cap mkd. RM T26SR5W 1/4 S24 37.9 FT. TO COR. 2004 and an arrow pointing to the corner.</p> <p style="margin-left: 40px;">A finned aluminum rod, 36 ins. long, 3/4 in. diam., driven flush with the ground for a reference monument, bears N. 60° 27' 15" W., 19.3 ft. dist. with aluminum cap mkd. RM T26SR5W 1/4 S13 19.3 FT. TO COR. 2004 and an arrow pointing to the corner.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend over cleared broken SE. slope.</p> <p>2740 Spur, slopes S. 35° E., desc. over SW. slope.</p> <p>4885 Ridge, bears N. 55° E. and S. 55° W., desc. over Westerly slope.</p> <p>5239.84 The cor. of secs. 13, 14, 23, and 24, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier No. 600400, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 14</td> <td style="padding: 2px 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 23</td> <td style="padding: 2px 5px;">S 24</td> </tr> </table> <p>T 26 S R 5 W</p> <p>1958</p> </div> <p>from which the remaining bearing trees mkd. by Byron</p> <p style="margin-left: 40px;">An oak, 20 ins. diam., bears S. 67 1/2° W., 73.4 ft. dist., with a healed double blaze.</p> <p style="margin-left: 40px;">An oak, 31 ins. diam., bears N. 8° W., 148.7 ft. dist., with a healed double blaze.</p>	S 14	S 13	S 23	S 24
S 14	S 13				
S 23	S 24				

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>and a new bearing tree</p> <p>An oak, 54 ins. diam., bears S. 12 1/4° E., 239.5 ft. dist., mkd. T26S R5W S24 BT.</p> <hr/>
1321.45	<p>N. 0° 02' 56" E., bet. secs. 13 and 14.</p> <p>Descend over broken SW. slope.</p> <p>Point for the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16</p> <p>S 14 S 13</p> <p>2004</p> </div> <p>from which</p> <p>An oak, 10 ins. diam., bears N. 23° E., 21.7 ft. dist., mkd. S 1/16 S13 BT.</p> <p>An oak, 13 ins. diam., bears N. 66 1/4° W., 18.4 ft. dist., mkd. S 1/16 S14 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Descend over broken SW. slope.</p>
2642.90	<p>The 1/4 sec. cor. of secs. 13 and 14, perpetuated by James W. Byron, Deputy County Surveyor, in 1954, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier No. 600440, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 26 S R 5 W</p> <p>14 13 C</p> <p>1954 O</p> <p>R</p> </div> <p>from which the remains of original bearing trees</p> <p>A roothole bears N. 18 1/4° E., 396.7 ft. dist., with oak trunk alongside, 35 ins. diam., with no marks visible on an opened blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>An oak snag, 36 ins. diam., bears N. 5 1/2° W., 462.9 ft. dist., with scribe mark S visible on an opened blaze. (Record, N. 5° W., 463.3 ft.)</p> <p>and bearing trees mkd. by Byron</p> <p>An oak, 40 ins. diam., bears S. 85 1/2° E., 242.6 ft. dist., with a healed double blaze.</p> <p>An oak, 19 ins. diam., bears N. 42 1/4° W., 95.4 ft. dist., with a healed double blaze.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier No. 500540, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE $\frac{1}{4}$ S S 4 10 11 T 26 S R 5 W</p> <p align="center">1958</p> <p>from which the remains of an original bearing tree</p> <p>A roothole bears N. 3° W., 457.5 ft. dist., alongside of which is the oak trunk, 50 ins. diam., with no marks visible on an opened blaze. (Record, N. 1° W., 456.1 ft.)</p> <p>and the bearing trees mkd. by Byron</p> <p>An oak, 20 ins. diam., bears S. 9 1/4° E., 36.0 ft. dist., with a healed double blaze.</p> <p>An oak, 14 ins. diam., bears N. 74 1/4° W., 24.7 ft. dist., with a healed double blaze.</p> <p>Corner is located 4.1 ft. N. of the cor. of fences, woven wire fences, extending south and east.</p> <p>From this point, the BLM Geodetic Control Station No. EC 41298, determined by the NAVSTAR GPS, utilizing static dual frequency, carrier phase receivers, (see Control Data Sheet attached to these field notes following the General Description) bears N. 85° 16' 36" E., 19791.39 ft. dist. (mean bearing and sea level dist.), monumented with an aluminum cap, 3 1/2 ins. diam., firmly set flush with the ground, with top mkd. EC 41298 GPS 2004.</p> <p>N. 0° 01' 04" E., bet. secs. 10 and 11.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>Ascend over broken SE. slope, through second growth timber and dense undergrowth.</p> <p>640 Spur, slopes S. 38° W.; desc. broken NW. slope.</p> <p>1520 Draw, drains S. 48° W.; asc. broken S. slope.</p> <p>2145 Spur, slopes West; desc. broken NE. slope.</p> <p>2485.05 Point for the cor. of secs. 2, 3, 10, and 11, at proportionate position, by the method of three-point control, based on the official record of the 1853 survey; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 26 S</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">R 5 W</td> </tr> <tr> <td style="padding: 0 5px;">S 3</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 2</td> </tr> <tr style="border-top: 1px solid black;"> <td style="padding: 0 5px;">S 10</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p>2004</p> </div> <p>from which</p> <p style="margin-left: 40px;">An oak, 13 ins. diam., bears N. 16 1/4° E., 177.9 ft. dist., mkd. T26S R5W S2 BT.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 43 1/4° E., 20.3 ft. dist., mkd. T26S R5W S11 BT.</p> <p style="margin-left: 40px;">A fir, 29 ins. diam., bears S. 25 1/4° W., 60.0 ft. dist., mkd. T26S R5W S10 BT.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 83 1/4° W., 34.2 ft. dist., mkd. T26S R5W S3 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Note: The three-point control method was utilized to reestablish the cor. of secs. 2, 3, 10, and 11 in its true original position. During the retracement, record calls for topography were recovered and a blunder in the original survey measurement was identified between the 1/4 sec. cor. of secs. 10 and 11 and the cor. of secs. 2, 3, 10, and 11. Not including the measurement to the south in the computation harmonizes this cor. position with the nearest recovered original cors. to the north, east, and west.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the cor. of secs. 1, 2, 11, and 12, perpetuated by the Douglas County Surveyors Office, in 1957, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier</p>	T 26 S		R 5 W	S 3		S 2	S 10		S 11
T 26 S		R 5 W								
S 3		S 2								
S 10		S 11								

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>No. 600600, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> COUNTY SURVEYORS OFFICE T 26 S R 5 W <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">SEC</td> <td style="border-right: 1px solid black; padding: 0 5px; text-align: center;">2</td> <td style="padding: 0 5px; text-align: center;">1</td> </tr> <tr> <td style="padding: 0 10px;">COR</td> <td style="border-right: 1px solid black; padding: 0 5px; text-align: center;">11</td> <td style="padding: 0 5px; text-align: center;">12</td> </tr> </table> 1956 </p> <p>from which the remaining original bearing trees</p> <p style="padding-left: 40px;">An oak, 51 ins. diam., bears N. 73 1/4° E., 402.3 ft. dist., with no marks visible on an opened blaze. (Record, 401.3 ft.)</p> <p style="padding-left: 40px;">An oak, 20 ins. diam., bears S. 87 1/4° E., 404.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An ash, 22 ins. diam., bears S. 7 1/2° W., 131.3 ft. dist., with no marks visible on an opened and decayed blaze.</p> <p>and the bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears N. 82 3/4° E., 139.7 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 41 1/4° E., 107.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 26° W., 113.1 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An ash, 21 ins. diam., bears N. 80° W., 19.0 ft. dist., with a healed double blaze.</p> <p>N. 89° 02' 23" W., bet. secs. 2 and 11.</p> <p>Ascend over gentle broken SE. slope.</p> <p>2628.95 Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	SEC	2	1	COR	11	12
SEC	2	1					
COR	11	12					

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>T 26 S R 5 W S 2 1/4 ——— S 11 2004</p>
	<p>from which</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 19 3/4° W., 38.0 ft. dist., mkd. 1/4 S11 BT.</p> <p style="padding-left: 40px;">A double trunk oak, 15 ins. diam., bears N. 73 1/4° W., 57.1 ft. dist., mkd. 1/4 S2 BT.</p> <p>From this cor., a point established as the 1/4 sec. cor. of secs. 2 and 11, by George R. Lecklider, Registered Professional Engineer No. 4079, in 1961, recorded in the Douglas County Surveyors Office, Map File No. M21-29, bears S. 0° 51' 36" E., 25.55 ft. dist., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 4 ins. above the ground. This point was established using improper procedure and is not utilized in the course of this survey, from which bearing trees mkd. by Lecklider,</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears S. 47 1/4° E., 32.4 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 87° W., 26.0 ft. dist., with a healed double blaze.</p> <p>This point is located 12.0 ft. W. of a woven wire fence, with fences extending north and south, and is also located 55.0 ft. N. of a graveled road, 15 ft. wide, which bears S. 45° E. and N. 45° W.</p> <p>Across rolling S. slope.</p>
5257.90	<p>The cor. of secs. 2, 3, 10, and 11.</p> <hr/> <p>N. 0° 49' 34" W., bet. secs. 2 and 3.</p> <p>Ascend over broken SE. slope.</p>
895	<p>Spur, slopes N. 64° E.; desc. broken NE. slope.</p>
2590	<p>Enter valley, edge bears S. 35° E. and N. 35° W., across level valley.</p>
2640.25	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Drive a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">T 26 S R 5 W 1/4 S 3 S 2 2004</p>
	<p>from which</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears N. 47 1/4° E., 278.7 ft. dist., mkd. 1/4 S2 BT.</p> <p style="padding-left: 40px;">A maple, 8 ins. diam., bears S. 74 3/4° W., 84.4 ft. dist., mkd. 1/4 S3 BT.</p> <p>Deposit a magnet in a white plastic case alongside of the finned aluminum rod.</p> <p>Continue across level valley.</p>
3095	<p>Leave valley, edge bears S. 30° E. and N. 45° W., ascend over broken SW. slope.</p>
3120	<p>Graveled road, 10 ft. wide, bears S. 38° E. and N. 38° W.</p>
5320.10	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 25 S R 5 W S 34 S 35 ----- S 3 S 2 T 26 S 1963</p>
	<p>from which the remains of a bearing tree mkd. by White and Beck</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 19 ins. diam., bears S. 80° W., 297.3 ft. dist., with no marks visible. (Record, S. 84° W., 295.0 ft.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 18° E., 37.9 ft. dist., mkd. T25S R5W S35 BT.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 36 1/2° E., 37.2 ft. dist., mkd. T26S R5W S2 BT.</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 81 1/4° W., 308.8 ft. dist., mkd. T26S R5W S3 BT.</p> <hr/>


**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89° 14' 22" E., bet. secs. 3 and 10.</p> <p>Ascend over broken NE. slope.</p>
755	<p>Ridge, bears North and South; desc. broken W. slope.</p>
2646.72	<p>The 1/4 sec. cor. of secs. 3 and 10, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1964, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier No. 440600, monumented with an iron pipe, 1 1/2 ins. diam., loosely set, projecting 20 ins. above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T26S 1/4 S3 S10 R5W 1964</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A roothole bears N. 33 1/2° E., 27.7 ft. dist., alongside of which is the oak trunk, 19 ins. diam., with no marks visible on an opened decayed blaze.</p> <p>and the bearing trees mkd. by Godfrey</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 9° E., 50.4 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An oak, 21 ins. diam., bears S. 6° E., 18.1 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Remove the loosely set iron pipe, and in its place, set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 26 S R 5 W</p> <p style="margin-left: 100px;">S 3</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 10</p> <p style="margin-left: 100px;">2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the iron pipe along S. side of stainless steel post.</p> <hr style="width: 60%; margin-left: 0;"/>

**Subdivision of Section 2,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
2580.00	<p>From the 1/4 sec. cor. of secs. 2 and 11.</p> <p>N. 0° 38' 59" W., on the N. and S. centerline of sec. 2, posting and blazing.</p> <p>Ascend over broken SW. slope, through second growth timber and dense undergrowth.</p> <p>Point selected for a witness point on the N. and S. centerline of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP C S 2 C 2004</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 8° E., 9.1 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 53° W., 14.8 ft. dist., mkd. WP S2 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on NE. slope, and 2.0 ft. W. of a woven wire fence, with fences extending north and south.</p> <p>Ascend over NE. slope.</p>
5356.40	<p>The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground (alongside of which is a geared steering shaft, 1 in. diam., firmly set, projecting 18 ins. above the ground), with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 5 W S 35 1/4 ——— S 2 T 26 S 1963</p> </div> <p>from which the remains of bearing trees mkd. by George R. Lecklider, Registered Professional Engineer No. 4079, in 1961, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 25 S., R. 05 W., Point Identifier No. 540100</p> <p style="padding-left: 40px;">A sawed fir stump, 26 ins. diam., bears S. 60 1/4° W., 37.0 ft. dist., with a healed double blaze. (Record, S. 80 1/2° W., 37.6 ft.)</p>

**Subdivision of Section 2,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed pine stump, 41 ins. diam., bears N. 11° W., 41.1 ft. dist., with a healed blaze. (Record, fir, 42.9 ft.)</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 23 1/4° E., 21.3 ft. dist., mkd. 1/4 S35 BT.</p> <p>A fir, 12 ins. diam., bears S. 63 3/4° W., 22.8 ft. dist., mkd. 1/4 S2 BT.</p> <p>Corner is located 1.0 ft. W. of a woven wire fence, with fences extending north and south.</p> <p>Discontinue posting and blazing.</p>
	<p align="center">Subdivision of Section 13, T. 26 S., R. 5 W., Willamette Meridian, Oregon</p>
	<p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0° 12' 36" W., on the N. and S. centerline of sec. 13.</p> <p>Ascend over broken SE. slope.</p>
1318.37	<p>Point for the center S 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;">  </div>
	<p>from which</p> <p>An oak, 11 ins. diam., bears N. 16 3/4° E., 18.4 ft. dist., mkd. CS 1/16 S13 BT.</p> <p>An oak, 6 ins. diam., bears N. 87 1/4° W., 74.7 ft. dist., mkd. CS 1/16 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend over SW. slope.</p>
2636.74	<p>Point for the center 1/4 sec. cor. of sec. 13, at the intersection with the E. and W. centerline.</p>

**Subdivision of Section 13,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 S R 5 W C 1/4</p> <p align="center">S 13 2004</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 20 ins. diam., bears N. 37 1/2° E., 103.4 ft. dist., mkd. C 1/4 S13 BT.</p> <p style="padding-left: 40px;">An oak, 16 ins. diam., bears N. 63° W., 27.5 ft. dist., mkd. C 1/4 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend over SE. slope.</p>
5274.62	<p>The 1/4 sec. cor. of secs. 12 and 13, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1964, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 05 W., Point Identifier No. 640500, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, flush with the ground, with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE T 26 S S 12 1/4 ——— S 13 R 5 W 1964</p> <p>from which the remains of the remaining original bearing tree</p> <p style="padding-left: 40px;">A roothole bears N. 75° W., 15.8 ft. dist., alongside of which is the oak trunk, 18 ins. diam., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Godfrey</p> <p style="padding-left: 40px;">A sawed fir stump, 18 ins. diam., bears S. 24 3/4° E., 14.0 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 21 ins. diam., bears N. 13° W., 23.4 ft. dist., with a healed double blaze.</p> <p>and new bearing trees</p>

**Subdivision of Section 13,
T. 26 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 12 ins. diam., bears N. 55 3/4° E., 45.2 ft. dist., mkd. 1/4 S12 BT.</p> <p style="text-align: center;">A double trunk madrone, 14 ins. diam., bears S. 76 3/4° W., 50.4 ft. dist., mkd. 1/4 S13 BT.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp. N. 89° 10' 49" W., on the E. and W. centerline of sec. 13.</p> <p>Descend over broken SW. changing to ascent over broken SE. slope.</p>
2617.31	<p>The center 1/4 sec. cor. of sec. 13.</p> <p>Ascend over broken SE. slope.</p>
5225.08	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 13 and 18, on the E. bdy of the Tp., posting and blazing.</p> <p>N. 89° 15' 00" W., on the E. and W. centerline of the SE 1/4 of sec. 13.</p> <p>Descend over broken SW. slope, through second growth timber and dense undergrowth.</p>
2618.62	<p>The center S 1/16 sec. cor. of sec. 13.</p> <hr/>
	<p>N. 89° 15' 00" W., on the E. and W. centerline of the SW 1/4 of sec. 13.</p> <p>Descend over SW. slope.</p>
55	<p>Ravine, drains S. 20° E., asc. over SE. slope.</p>
2613.84	<p>The S 1/16 sec. cor. of secs. 13 and 14.</p> <p>Discontinue posting and blazing.</p> <hr/>

T. 26 S., R. 5 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located about 7 miles westerly from Glide, Oregon. The area is drained by the North Umpqua River, and a number of small seasonal streams. Elevations range from about 510 feet above mean sea level, near the meander corner on the left bank of the North Umpqua River, to about 1380 feet above mean sea level, near the center 1/4 section corner of section 13.</p> <p>Access is gained by way of County Road No. 200, with numerous logging and private roads.</p> <p>Soil consists of rock, clay, and sandy loam. There were a number of rock outcroppings throughout the area.</p> <p>Timber in this area consists of fir, cedar, hemlock, oak, alder, madrone, maple, and chinquapin. Undergrowth consists of vine maple, hazel, ceanothus, fern, poison oak, salal, Oregon grape, arrowwood, and huckleberry.</p> <p>There were no mineral deposits along the lines resurveyed. The lands are used primarily for ranching and recreation.</p> <hr/>
------	--