

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A PORTION OF THE  
WEST BOUNDARY AND SUBDIVISIONAL LINES  
THE WEST BOUNDARY OF DONATION LAND CLAIM NO. 47  
AND THE SUBDIVISION OF SECTIONS 18 AND 33

**TOWNSHIP 26 SOUTH, RANGE 7 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***Timothy J. Moore, Cadastral Surveyor***

***Robert H. Browning, Surveying Technician***

Under Special Instructions dated April 7, 2006,  
approved April 24, 2006,

which provided for the surveys included under Group No. 2140,  
and Assignment Instructions dated June 5, 2006.

***Survey commenced June 6, 2006***

***Survey completed August 23, 2006***

**T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines, and the west boundary of Donation Land Claim (DLC) No. 47, and subdivision of sections 18 and 33, Township 26 South, Range 7 West, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1856, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the township lines and a portion of the subdivisional lines.</p> <p>In 1856-57, J.A. Burnett, U.S. Deputy Surveyor, surveyed the Josiah Atterbury DLC No. 47.</p> <p>In 1881, Addison R. and Samuel C. Flint, U.S. Deputy Surveyors, retraced a portion of north, south, and west boundaries, and completed the subdivisional lines.</p> <p>In 1959, Irving Zirpel, Jr., and Leo J. Martin, Cadastral Surveyors, retraced and re-established a portion of the west boundary and a portion of the subdivisional lines, and remonumented certain corners.</p> <p>In 1969, Lynn M. Roseberry, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines.</p> <p>In 1971, Peter A. Peterson and Daniel L. Berry, Cadastral Surveyors, dependently resurveyed a portion of the east boundary of T. 26 S., R. 8 W.</p> <p>In 1971-74, Peter A. Peterson, Daniel L. Berry, Gurdon S. Popken, and Harvey E. Wofford, Cadastral Surveyors, dependently resurveyed a portion of the north and south boundaries, subdivisional lines and claim lines.</p> <p>In 2001-2002, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, dependently resurveyed a portion of the subdivisional lines of T. 26 S., R. 8 W.</p> <p>In 2001-02, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, dependently resurveyed a portion of the south boundary and subdivisional lines, and subdivided sections 21 and 32.</p> <p>In 2005, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, dependently resurveyed a portion of the west boundary and subdivisional lines and subdivided sections 7 and 9.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated April 7, 2006, for Group No. 2140, Oregon.</p> <p>The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis using Trimble Geomatics Office (TGO). The GPS</p>
------	---

**T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET

position of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of the Agriculture, Forest Service.

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS measurements and carried forward by means of sustained angulation using conventional survey techniques. Directions along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The Standard Error of Unit Weight for the least squares adjustment of the survey data fell between 0.7 and 2.5. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 in. X 1/4 in. Magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations "CAPE BLANCO CORS ARP" and "OBEC CONS COOP CORS ARP", is as follows:

The 1/4 section corner of sections 17 and 18.

Latitude: 43° 18' 30.55" N. Longitude: 123° 33' 52.62" W.

The 1/4 section corner of sections 33 and 34.

Latitude: 43° 15 '55.25" N. Longitude: 123° 31' 31.57" W.

---

**Dependent Resurvey of a Portion of the West Boundary,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

---

Restoring the 1856 survey by Dennis Hathorn, the 1881 retracement  
by Addison R. and Samuel C. Flint, and the 1971 resurvey by  
Peter A. Peterson and Daniel L. Berry

---



**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p align="center">Restoring the 1856 survey by Dennis Hathorn, the 1881 survey by Addison R. and Samuel C. Flint, the 1959 resurvey by Irving Zirpel, Jr., and Leo J. Martin, the 1969 resurvey by Lynn M. Roseberry, and the 1971-74 resurvey by Peter A. Peterson, Daniel L. Berry, Gurdon S. Popken, and Harvey E. Wofford</p> <hr/> <p>From the 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <p align="center">           T 26 S R 7 W                  1/4                               S 33   S 34                                     1974         </p> <p>from which the remains of a bearing tree mkd. by Peterson, Berry, Popken, and Wofford in 1971-74</p> <p align="center">A sawed oak stump, 22 ins. diam., bears N. 83° W., 49.5 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p align="center">An iron rod, 30 ins. long, 5/8 in. diam., driven 27 ins. in the ground for a reference monument, bears N. 32° 04' 11" E., 8.1 ft. dist., with aluminum cap mkd. RM 1/4 S34 8.1 FT TO COR 2006, and an arrow pointing to the corner.</p> <p align="center">An iron rod, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears N. 34° 28' 51" W., 8.0 ft. dist., with aluminum cap mkd. RM 1/4 S33 8.0 FT TO COR 2006, and an arrow pointing to the corner.</p> <p>N. 0° 05' 46" W., bet. secs. 33 and 34.</p> <p>Ascend over gentle SE. slope.</p>
1319.34	<p>The N 1/16 sec. cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <p align="center">           N 1/16            S 33   S 34                                     1974         </p> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p align="center">A madrone, 25 ins. diam., bears S. 73 1/2° E., 14.5 ft. dist., with no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET									
	<p align="center">A fir, 28 ins. diam., bears N. 75 1/2° W., 83.8 ft. dist., with a healed blaze.</p> <hr/> <p>N. 0° 05' 41" W., beginning new measurement.</p> <p>Ascend over SE. slope.</p>								
395	<p>Spur, slopes East, desc. over NE. slope.</p>								
1320.73	<p>The true point for the cor. of secs. 27, 28, 33, and 34, established at record bearing and distance from the witness cor., hereinafter described. This point is located in a beaver pond, where it is impracticable to establish a permanent monument.</p> <hr/>								
	<p>S. 89° 40' 00" W., bet. secs. 28 and 33.</p> <p>Across beaver pond.</p>								
41.58	<p>The witness cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, 10 ins. below the surface of the water, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <table border="0"> <tr> <td>T 26 S</td> <td>R 7 W</td> <td></td> </tr> <tr> <td>S 28</td> <td>S 27</td> <td rowspan="2">}</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table> <p>1974</p> </div>	T 26 S	R 7 W		S 28	S 27	}	S 33	S 34
T 26 S	R 7 W								
S 28	S 27	}							
S 33	S 34								
	<p>from which the remains of a bearing tree mkd. by Peterson, Berry, Popken, and Wofford</p> <p align="center">A sawed madrone stump, 8 ins. diam., bears N. 3° E., 31.7 ft. dist., no marks visible.</p>								
	<p>No new accessories available within limits.</p> <hr/>								
	<p>S. 85° 46' 29" W., beginning new measurement.</p> <p>Across beaver pond.</p>								
3	<p>West edge of beaver pond, edge bears N. 20° E. and S. 20° W.</p>								
5.08	<p>The crossing closing cor. of secs. 28 and 33 on the W. bdy. of DLC No. 47, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p>								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	$\begin{array}{r} \text{T 26 S} \quad \text{R 7 W} \\ \hline \text{S 28} \quad   \quad \text{C} \\ \text{S 33} \quad   \quad \text{47} \\ \hline 1974 \end{array}$
	from which new bearing trees
	<p>A fir, 20 ins. diam., bears S. 73 1/4° W., 49.8 ft. dist., mkd. T26S R7W S33 BT.</p> <p>A fir, 6 ins. diam., bears N. 44 1/2° W., 63.8 ft. dist., mkd. T26S R7W S28 BT.</p>
	_____
	S. 89° 19' 04" W., beginning new measurement.
	Ascend over broken NE. slope.
90	Dirt road, 12 ft. wide, bears N. 10° W. and S. 10° E.
221.61	Angle Point for secs. 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, (alongside of which is the decayed remains of the original line tree, size indeterminate, with no marks visible), with brass cap mkd.
	$\begin{array}{r} \text{AP} \\ \hline \text{S 28} \\ \hline \text{S 33} \\ 1974 \end{array}$
	_____
	S. 89° 53' 47" W., beginning new measurement.
	Continue ascending over broken NE. slope.
1040.69	The E 1/16 sec. cor. of secs. 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.
	$\begin{array}{r} \text{S 28} \\ \hline \text{E 1/16} \quad \hline \text{S 33} \\ 1974 \end{array}$
	from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford
	<p>A fir, 16 ins. diam., bears N. 46° E., 37.0 ft. dist., with a healed blaze. (Record, N. 44 1/2° E.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1306.90	<p align="center">A fir, 13 ins. diam., bears S. 68° W., 46.9 ft. dist., with a healed blaze.</p> <hr/> <p>S. 89° 37' 32" W., beginning new measurement.</p> <p>Continue ascending over broken NE. slope.</p> <p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p align="center">           T 26 S R 7 W                      S 28            1/4     ———                      S 33                      1974         </p> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p align="center">A fir, 17 ins. diam., bears N. 76° E., 31.7 ft. dist., with a healed blaze.</p> <p align="center">A fir, 21 ins. diam., bears S. 11 3/4° W., 4.3 ft. dist., with a healed blaze. (Record, S. 17 1/2° W.)</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 18 and 19, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p align="center">                             S 18            E 1/16     ———                              S 19                              1969         </p> <p>from which the remaining bearing tree mkd. by Roseberry</p> <p align="center">A fir, 19 ins. diam., bears N. 34 1/2° W., 17.8 ft. dist., with a healed blaze. (Record, N. 38° W.)</p> <p>and a new bearing tree</p> <p align="center">A fir, 14 ins. diam., bears S. 56 1/2° W., 20.3 ft. dist., mkd. E1/16 S19 BT.</p> <p>Corner is located on a gentle NW. slope.</p> <p>N. 88° 57' 44" W., bet. secs. 18 and 19.</p> <p>Descend over broken NW. slope.</p>
1326.24	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	T 26 S R 7 W S 18 1/4 <u>        </u> S 19 1969
	from which bearing trees mkd. by Roseberry
	A fir, 14 ins. diam., bears S. 15° E., 13.5 ft. dist., with a healed blaze. (Record, S. 23 1/2° E.)
	A fir, 16 ins. diam., bears N. 16 1/2° W., 7.6 ft. dist., with a healed blaze.
	_____
	N. 89° 12' 45" W., beginning new measurement.
	Descend over broken SW. slope.
2490	Hubbard Creek 15 ft. wide, course N. 10° W., asc. over NE. slope.
2625	Graveled road, 25 ft. wide, bears N. 10° E. and S. 5° E.
2674.72	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp.
	_____
	From the S 1/16 sec. cor. of secs. 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.
	S 1/16 S 18   S 17 1969
	from which bearing trees mkd. by Roseberry
	A fir, 39 ins. diam., bears N. 42 1/2° E., 55.1 ft. dist., with a healed blaze.
	An alder, 15 ins. diam., bears N. 79° W., 35.0 ft. dist., with a healed blaze.
	N. 0° 25' 04" E., bet. secs. 17 and 18.
	Descend over NW. slope.
125	Creek 1 ft. wide, course S. 80° W., asc. over SW. slope.
1317.02	The 1/4 cor. of secs. 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET

T 26 S R 7 W  
1/4  
S 18 | S 17  
1969

from which the remains of bearing trees mkd. by Roseberry

A madrone snag, 7 ins. diam., bears S. 47 1/4° E., 11.2 ft. dist., with a healed blaze.

A fir, 50 ins. diam., bears S. 35 1/2° W., 41.6 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears S. 69 1/4° E., 9.5 ft. dist., mkd. 1/4 S17 BT.

**Dependent Resurvey of the West Boundary of  
Donation Land Claim No. 47,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

Restoring the 1856-57 survey by J.A. Burnett, and the  
1971-74 resurvey by Peter A. Peterson, Daniel L. Berry,  
Gurdon S. Popken, and Harvey E. Wofford

From the SW. cor. of DLC No. 47, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.

S33 | C  
47  
1974

from which the remains of a bearing tree mkd. by Peterson, Berry, Popken, and Wofford



A sawed oak stump, 24 ins. diam., bears N. 84 1/4° W., 10.6 ft. dist., with a healed blaze.

and new accessories

An iron rod, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground for a reference monument, bears N. 89° 25' 17" W., 7.4 ft. dist., with aluminum cap mkd. RM T26S R7W S33 7.4 FT TO COR 2006, and an arrow pointing to the corner.

An iron rod, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground for a reference monument, bears N. 10° 27' 46" W., 7.0 ft. dist., with

**Dependent Resurvey of the West Boundary of  
Donation Land Claim No. 47,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>aluminum cap mkd. RM T26S R7W S33 7.0 FT TO COR 2006, and an arrow pointing to the corner.</p> <p>N. 0° 02' 27" W., on the W. bdy of DLC No. 47.</p> <p>Ascend over SE. slope.</p>
643.90	Intersect the E. and W. centerline of sec. 33, point for the crossing closing cor., not monumented.
1963.37	<p>Intersect the E. and W. centerline of the NE 1/4 of sec. 33, point for the crossing closing cor. Set an iron rod, 30 ins. long, 5/8 in. diam., 27 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  <p>CCC C N —   — N S33 47 2006</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 5 ins. diam., bears S. 66 1/2° E., 24.6 ft. dist., mkd. C47 CCC BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 43° W., 10.2 ft. dist., mkd. S33 CCC BT.</p> <p>Corner is located 1.5 ft. E. of a 3 strand barbed wire fence extending N. 15° E. and S. 15° W.</p> <p>Ascend over SE. slope.</p>
2360	Spur, slopes East, desc. over NW. slope.
3283.83	<p>The crossing closing corner of DLC No. 47, on the line bet. secs. 28 and 33, hereinbefore described.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 02' 59" E., beginning new measurement.</p> <p>Descend over gentle NE. slope.</p>
672.37	<p>The NW. cor. of DLC No. 47, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T26S R7W S28 —┐             C           └ 47           1974</p> </div>

**Dependent Resurvey of the West Boundary of  
Donation Land Claim No. 47,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>from which a bearing tree mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A madrone, 20 ins. diam., bears N. 65 3/4° W., 116.8 ft. dist., with a healed blaze.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 18, T. 26 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N. 0° 18' 42" E., on the N. and S. centerline of sec. 18.</p> <p>Ascend over gentle SW. slope.</p> <p>1325.20 Point for the center S 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>C</p> <p>S 1/16   S 18</p> <p>C</p> <p>2006</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 22 3/4° E., 18.6 ft. dist., mkd. CS 1/16 S18 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 72 1/4° E., 17.2 ft. dist., mkd. CS 1/16 S18 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., an iron pipe, 1 in. diam., firmly set, projecting 3 in. above the ground, with no cap, bears N. 86° 33' 02" E., 1.75 ft. dist., established without authority by a 1978 Bureau of Land Management (BLM) administrative survey, from which unmarked bearing trees</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 84 1/4° E., 14.3 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 37 3/4° W., 10.1 ft. dist., with no marks visible.</p> <p>This point is not accepted as the true cor. position; we remove the iron pipe, 24 ins. long, and bury it inside the stainless steel post.</p>
------	---

**Subdivision of Section 18,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2650.40	<p>Descend over NW. slope, changing to ascend over SW. slope.</p> <p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. centerline of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W C 1/4 S 18 2006</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 19 3/4° E., 33.5 ft. dist., mkd. C 1/4 S18 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 22 3/4° W., 41.1 ft. dist., mkd. C 1/4 S18 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend over SW. Slope, changing to descend over NW. slope.</p>
5306.64	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W S 7 1/4 <u>        </u> S 18 1983 PLS 1988</p> <p>from which bearing trees mkd. by Ronald S. Geisler, Registered Professional Land Surveyor No. 1988, in 1983, reported by Moore and Browning</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears S. 31 1/4° W., 15.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 55 3/4° W., 10.0 ft. dist., with a healed blaze.</p> <p>From this cor., an iron pipe, 3/4 in. diam., firmly set, projecting 1 in. above the ground, with no cap, bears N. 64° 30' 58" E., 5.94 ft. dist., established without authority by a 1978 BLM administrative survey.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p>

**Subdivision of Section 18,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	N. 88° 47' 41" W., on the E. and W. centerline of sec. 18.
	Descend over SW. slope.
1328.27	Point for the center E 1/16 sec. cor. of sec. 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{ --- } \text{C} \\ \text{S } 18 \\ 2006 \end{array}$
	from which
	A fir, 11 ins. diam., bears S. 19 3/4° E., 8.7 ft. dist., mkd. CE 1/16 S18 BT.
	A fir, 10 ins. diam., bears S. 65 3/4° W., 26.6 ft. dist., mkd. X BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this cor., an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, with no cap, bears N. 74° 52' 41" E., 2.87 ft. dist., established without authority by a 1978 BLM administrative survey, from which unmarked bearing trees
	A fir, 14 ins. diam., bears N. 37° E., 7.8 ft. dist., with no marks visible.
	A fir, 14 ins. diam., bears S. 73 3/4° W., 10.7 ft. dist., with no marks visible.
	This point is not accepted as the true cor. position; we remove the iron pipe, 24 ins. long, and bury it inside the stainless steel post.
	Continue descending over SW. slope.
2656.54	The center 1/4 sec. cor. of sec. 18.
5350.86	The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.
	From the center S 1/16 sec. cor. of sec. 18.
	S. 88° 58' 14" E., on the E. and W. centerline of the SE 1/4 of sec. 18.
	Ascend over broken N. slope.
1327.23	Point for the SE 1/16 sec. cor. of sec. 18, at intersection with the N. and S. centerline of the SE 1/4 of sec. 18.

**Subdivision of Section 18,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 18 2006</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 80° E., 10.7 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 29 1/2° E., 14.5 ft. dist., mkd. SE 1/16 S18 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, with no cap, bears S. 85° 33' 54" E., 0.84 ft. dist., established without authority by a 1978 BLM administrative survey, from which unmarked bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 33° E., 21.1 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 60° W., 4.6 ft. dist., with no marks visible.</p> <p>This point is not accepted as the true cor. position; we remove the iron pipe, 24 ins. long, and bury it inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 21' 28" E., on the N. and S. centerline of the SE 1/4 of sec. 18.</p> <p>Descend over N. slope.</p>
430	Creek 5 ft. wide, course S. 60° W., asc. over SW. slope.
1321.11	The center E 1/16 sec. cor. of sec. 18.
<hr/> <p><b>Subdivision of Section 33, T. 26 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/>	
<p>From the 1/4 sec. cor. of secs. 4 and 33, on the S bdy. of the Tp., perpetuated by James W. Byron, Deputy County Surveyor, in 1961, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T, 26 S., R. 7 W., Point Identifier No. 340100, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd.</p>	

**Subdivision of Section 33,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	COUNTY SURVEYORS OFFICE T 26 S R 7 W S 33 ————— 1/4 S 4 T 27 S R 7 W 1960
	from which  A fir, 14 ins. diam., bears N. 72 1/4° E., 24.3 ft. dist., mkd. 1/4 S33 BT.  A fir, 10 ins. diam., bears S. 9 3/4° W., 39.0 ft. dist., mkd. 1/4 S4 BT.  N. 0° 04' 21" E., on the N. and S. centerline of sec. 33.  Descend over broken NE. slope.
49.16	The crossing closing cor., on the W. bdy. of DLC No. 47, hereinbefore described.
350	Creek, 0.5 ft. wide, course N. 45° E., asc. over SE. slope.
785	Creek, 12 ft. wide, course S. 80° E., asc. over SE. slope.
2629.84	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. centerline.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T 26 S R 7 W  C 1/4 S 33 2006
	from which  A fir, 17 ins. diam., bears S. 20 1/2° E., 16.9 ft. dist., mkd. C1/4 S33 BT.  A fir, 9 ins. diam., bears N. 24 1/2° W., 9.7 ft. dist., mkd. C1/4 S33 BT.  Deposit a magnet in a white plastic case at the base of the stainless steel post.  Continue asc. over SE. slope.
3955.82	Point for the center N 1/16 sec. cor. of sec. 33, not monumented.

**Subdivision of Section 33,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
5281.80	The 1/4 sec. cor. of secs. 28 and 33.
	<hr/> From the 1/4 sec. cor. of secs. 33 and 34. S. 89° 26' 29" W., on the E. and W. centerline of sec. 33. Ascend over broken SE. slope.
49.16	Intersect the W. bdy. of DLC No. 47, point for the crossing closing cor., not monumented.
1312.00	Point for the center E 1/16 sec. cor. of sec. 33, not monumented.
2624.00	The center 1/4 sec. cor. of sec. 33.  Continue asc. over broken SE. slope.
5250.94	The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.
	T 26 S R 7 W 1/4 S 32   S 33 1974
	from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford  A fir, 20 ins. diam., bears S. 32° E., 19.1 ft. dist., with a healed blaze.  A fir, 29 ins. diam., bears S. 70 1/4° W., 38.9 ft. dist., with a healed blaze.
	<hr/> From the N 1/16 sec. cor. of secs. 33 and 34. S. 89° 35' 10" W., on the E. and W. centerline of the NE 1/4 of sec. 33. Ascend over broken SE. slope.
47.89	The crossing closing cor., on the W. bdy. of DLC No. 47, hereinbefore described.
410	Graveled road, 24 ft. wide, bears N. 60° W. and S. 40° E.
1310.45	Point for the NE 1/16 sec. cor. of sec. 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

**Subdivision of Section 33,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">NE 1/16 S 33 2006</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 11 1/2° E., 23.4 ft. dist., mkd. NE 1/16 S33 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 22 1/4° W., 2.3 ft. dist., mkd. NE 1/16 S33 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0° 02' 01" W., on the N. and S. centerline of the NE 1/4 of sec. 33.</p> <p>Ascend over SE. slope, changing to descend over NE. slope.</p>
1285	Ravine, drains N. 50° E., asc. over SE. slope.
1325.06	The E 1/16 sec. cor. of secs. 28 and 33.
	<p><b>GENERAL DESCRIPTION</b></p> <p>The lands included in the notes of the foregoing resurvey are located about 26 miles southwesterly from Sutherlin, Oregon. The area is drained by Hubbard Creek and a number of small seasonal streams. Elevations range from about 1100 feet above sea level, near the 1/4 section corner of sections 33 and 34, to about 2200 feet above sea level near the 1/4 section corner of sections 32 and 33.</p> <p>Access is gained by way of Hubbard Creek Road, a paved and graveled road, which extends westerly from Sutherlin, also by Callahan Road and numerous other logging and private roads.</p> <p>Soil consists of rock, clay, and sandy loam. There were a number of rock outcroppings and bluffs throughout the area.</p> <p>Timber in this area consists of fir, cedar, hemlock, oak, alder, madrone, maple, and chinquapin. Undergrowth consists of vine maple, hazel, ceanothus, fern, poison oak, salal, Oregon Grape, arrowwood, huckleberry, salmonberry, and rhododendron.</p> <p>The lands are used primarily for timber production.</p>