

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
AND OF THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTIONS 29 AND 33

TOWNSHIP 30 SOUTH, RANGE 3 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated September 8, 2005, approved
September 9, 2005, which provided for the surveys included under
Group No. 2127, and Assignment Instructions dated January 31, 2006.

Survey commenced February 2, 2006

Survey completed April 20, 2006

T. 30 S., R. 3 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines and the subdivision of sections 29 and 33, Township 30 South, Range 3 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1858, Dennis Hathorn, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1893, William Bushey, U.S. Deputy Surveyor, completed the survey of the south, east, west, and north boundaries and the subdivisional lines.

In 1983-84, Wayne L. Rogers, Lance J. Bishop, and James L. White, Cadastral Surveyors, resurveyed portions of the subdivisional lines and subdivided sections 19 and 35.

In 1985-86, Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, resurveyed a portion of the south boundary, T. 30 S., R. 3 W., and a portion of the subdivisional lines, T. 31 S., R. 3 W.

In 2004-05, A. Bert Skeesick, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, retraced a portion of the subdivisional lines, and remonumented and rehabilitated certain cor. points.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 8, 2005, for Group No. 2127, Oregon.

The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis using Trimble Geomatics Office (TGO), version 1.62. The GPS position of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of the Agriculture, Forest Service.

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS measurements and carried forward by means of sustained angulation using conventional survey techniques. Directions along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The Standard Error of Unit Weight for the least squares adjustment of the survey data fell between 0.7 and 2.5. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

T. 30 S., R. 3 W., Willamette Meridian, Oregon

FEET

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all cors. and other calls of record. Identified cors. were remonumented in their original positions. Lost cors. were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 in. x 1/4 in. Magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the cor. description.

The following published stations from the National Spatial Reference System Continuously Operating Reference Station (CORS) were used for control:

1. "ROSEBURG COOP CORS ARP", National Geodetic Survey.
43° 12' 39.61530" N.; 123° 20' 29.39067" W.; NAD 1983 (CORS 2002)
2. "DODSON BUTTE CORS ARP", National Geodetic Survey.
43° 07' 07.63111" N.; 123° 14' 39.21292" W.; NAD 1983 (CORS 2002)

The geographic position (NAD 1983 (CORS 2002)) of the cor. of sections 28, 29, 32, and 33, was determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System Stations noted above, is:

Latitude: 42° 55' 52.52" N. Longitude: 123° 04' 51.83" W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

Restoring the survey by William Bushey, in 1893

Beginning at the closing cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., monumented with a finned aluminum rod, 3/4 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd.

T 30 S	R 3 W
S 33	S 34
S 4	
T 31 S	
2004	

from which the remains of bearing trees mkd. by John H. Markham, Jr., Registered Professional Engineer (PE) No. 2880, in 1960, reported by Skeesick and Browning

**Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>A burnt and decayed fir snag, 17 ins. diam., bears S. 66° W., 15.4 ft. dist., with a healed blaze.</p> <p>A burnt and decayed fir stump, 34 ins. diam., bears S. 84° W., 27.4 ft. dist., with a healed blaze.</p> <p>A burnt and decayed fir snag, 18 ins. diam., bears N. 88° W., 11.9 ft. dist., with a healed blaze.</p> <p>and reference monuments set by Skeesick and Browning</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, bears N. 48° 00' 00" E., 7.50 ft. dist. with aluminum cap mkd. RM S34 7.5 FT TO COR 2004 and an arrow pointing to the cor.</p> <p>An iron rod, 5/8 in. diam., firmly set, flush with the ground, bears N. 48° 00' 00" W., 7.50 ft. dist. with aluminum cap mkd. RM S33 7.5 FT TO COR 2004 and an arrow pointing to the cor.</p> <p>S. 89° 52' 53" W., bet. secs. 4 and 33, on the S. bdy. of the Tp., posting and blazing.</p> <p>Descend over broken NW. slope, through burnt area.</p>
149.01	<p>A point established as the 1/4 sec. cor. of sec. 4 only by Howard W. Johnstone, Registered PLS (PLS) No. 498, in 1982, recorded in the Douglas County Surveyors Office, Map File M92-44, bears South, 0.43 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. T31S R3W SEC 4 ONLY 1/4 LS 498 1982, from which the remains of a bearing tree mkd. by Johnstone</p> <p>A roothole bears N. 2 1/2° W., 5.6 ft. dist., with no trunk remains.</p> <p>This point was established using improper procedures and is not accepted as the cor.</p>
186.02	Point for the 1/4 sec. cor. of sec. 4 only, not monumented.
470	Creek, 1.5 ft. wide, course N. 15° E., asc. over NE. slope.
1920	Spur, slopes N. 70° E., desc. over NW. slope.
2570	Creek 4 ft. wide, course N. 60° E., asc. over NE. slope.
2662.18	The 1/4 sec. cor. of sec. 33 only, on the S. bdy. of the Tp., perpetuated by John H. Markham, Jr., Registered PE No. 2880, in 1951 from original evidence no longer in existence, further perpetuated by John M. Powell, of the Douglas County Surveyors Office, in 1966, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 03 W., Point Identifier No. 340100, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

FEEET	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S S 33 R 1/4 — 3 W T 31 S 1966</p> <p>from which the remains of bearing trees mkd. by Markham</p> <p style="padding-left: 40px;">A roothole bears S. 59 1/2° E., 13.4 ft. dist., with no trunk remains. An alder stump, 8 ins. diam., bears S. 37 3/4° E., 10.4 ft. dist., with no marks visible.</p> <p>and new reference monuments</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 27 ins. in the ground, bears N. 66° 56' 13" E., 6.82 ft. dist. with aluminum cap mkd. RM 1/4 S33 6.8 FT TO COR 2006 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 27 ins. in the ground, bears N. 3° 04' 34" W., 7.90 ft. dist. with aluminum cap mkd. RM 1/4 S33 7.9 FT TO COR 2006 and an arrow pointing to the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 46' 06" W., beginning new measurement; continue posting and blazing.</p> <p>Ascend over broken NE. slope, through burnt area.</p> <p>181.20 The closing cor. of secs. 4 and 5 only, on the S. bdy. of the Tp., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 18 ins. above the ground (alongside of which is an iron pipe, 1 in. diam., firmly set, projecting 13 ins. above the ground), with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S R 3 W S 33</p> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">T 31 S</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1966</td> </tr> </table> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A burnt fir snag, 10 ins. diam., bears N. 11 1/2° W., 24.3 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by John M. Powell, of the Douglas County Surveyors Office, in 1966, reported by Skeesick and Browning</p> <p style="padding-left: 40px;">A burnt and sawed fir stump, 14 ins. diam., bears North, 31.8 ft. dist., with no marks visible.</p>	S 5	S 4	T 31 S		1966	
S 5	S 4						
T 31 S							
1966							

**Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>An iron rod, 5/8 in. diam., firmly set, flush with the ground, bears N. 48° 06' 56" W., 7.50 ft. dist. with aluminum cap mkd. RM T30S R3W S32 7.5 FT TO COR 2005 and an arrow pointing to the cor. (Record, N. 45° W.)</p> <hr/> <p>N. 88° 47' 19" W., bet. secs. 5 and 32, on the S. bdy. of the Tp.; begin posting and blazing.</p> <p>Descend over broken W. slope, through burnt area.</p>
195	Ravine, drains N. 40° W., asc. over NE. slope.
1055	Spur, slopes N. 35° W., desc. over SW. slope.
1725	Ravine, drains S. 30° W., asc. over SE. slope.
1925	Spur, slopes S. 30° W., desc. over SW. slope.
2120	Ravine, drains S. 15° W., asc. over SE. slope.
2260	Spur, slopes S. 20° W., desc. over SW. slope.
2602.67	<p>The 1/4 sec. cor. of sec. 32 only, on the S. bdy. of the Tp., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground (alongside of which is the original stone, projecting 3 ins. above the ground, with the marks 1/4 visible, and an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground), with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE T 30 S S 32 R 1/4 ——— 3 T 31 S W 1966</p> <p>from which the remains of original bearing trees</p> <p>A sawed and burnt fir stump, 24 ins. diam., bears N. 71 1/2° E., 10.2 ft. dist., with no marks visible.</p> <p>A roothole bears S. 15° W., 31.4 ft. dist., with no trunk remains.</p> <p>and the remains of bearing trees mkd. by John H. Markham, Jr., Registered PE No. 2880, in 1959</p> <p>A live oak, 15 ins. diam., bears S. 44 3/4° E., 33.0 ft. dist., with a healed blaze.</p> <p>A fir, 25 ins. diam., bears S. 6 1/4° E., 36.3 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>A live oak, 15 ins. diam., bears S. 19 1/2° W., 70.0 ft. dist., no marks visible.</p> <p>A fir, 27 ins. diam., bears S. 77 1/2° W., 15.2 ft. dist., with a healed blaze.</p>
	<hr/> <p align="center">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 30 S., R. 3 W., Willamette Meridian, Oregon</p> <hr/>
	<p align="center">Restoring the surveys by Dennis Hathorn in 1858, and William Bushey in 1893</p> <hr/>
	<p>From the closing cor. of secs. 33 and 34, on the S. bdy. of the Tp. N. 0° 29' 36" W., bet. secs. 33 and 34, posting and blazing. Descend over NW. slope.</p>
670	<p>Coon Creek, 3 ft. wide, course East, asc. over SE. slope.</p>
757.91	<p>The S 1/16 sec. cor. of secs. 33 and 34, established by Howard W. Johnstone, Registered PLS, No. 498, in 1983, recorded in the Douglas County Surveyors Office, Map File No. 95-6, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., badly bent, with aluminum cap mkd. T30S R3W SEC 34 S 1/16 LS 498 1983, from which the remains of a bearing tree mkd. by Johnstone</p> <p>A burnt fir stump, 22 ins. diam., bears N. 42 1/2° W., 19.3 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">S 1/16 S 33 S 34 2006</p> <p>from which</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 10° 00' 00" E., 7.50 ft. dist. with aluminum cap mkd. RM S 1/16 S34 7.5 FT TO COR 2006 and an arrow pointing to the cor.</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 80° 00' 00" W., 7.50 ft. dist. with aluminum cap mkd. RM S 1/16 S33 7.5 FT TO COR 2006 and an arrow pointing to the cor.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>Straighten the iron rod and bury it inside the stainless steel post. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0° 27' 06" W., beginning new measurement; continue posting and blazing.</p> <p>Ascend over broken SE. slope.</p>
60	Graveled road, 12 ft. wide, bears and N. 60° E. and S. 60° W.
1005	Spur, slopes N. 70° E., desc. over NE. slope.
1292.18	<p>The 1/4 sec. cor. of secs. 33 and 34, established by Howard W. Johnstone, Registered PLS, No. 498, in 1983, recorded in the Douglas County Surveyors Office, Map File M95-6, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, 3 ins. below the surface of the ground, with aluminum cap mkd.</p> <p align="center"> T 30 S R 3 W 1/4 S 33 S 34 1983 RLS 498 </p> <p>from which the remains of a bearing tree mkd. by Johnstone</p> <p align="center">A sawed and decayed fir stump, 14 ins. diam., bears N. 45 1/2° W., 23.9 ft. dist., with no marks visible.</p> <p>and new bearing trees</p> <p align="center">A fir, 7 ins. diam., bears N. 84 3/4° E., 10.3 ft. dist., mkd. 1/4 S34 BT.</p> <p align="center">A fir, 8 ins. diam., bears N. 21 1/4° W., 20.7 ft. dist., mkd. 1/4 S33 BT.</p> <p>Discontinue posting and blazing.</p> <hr/>
1290.27	N. 0° 32' 38" W., beginning new measurement.
	Descend over NE. slope.
2580.54	Point for the N 1/16 sec. cor. of secs. 33 and 34, not monumented.
	<p>The cor. of secs. 27, 28, 33, and 34, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1940, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 3 W., Point Identifier No. 400200, and perpetuated by Howard W. Johnstone, Registered PLS No. 498, in 1983, recorded in the Douglas County Surveyors Office, Map File M95-6, and is accepted as the best available evidence of the cor., monumented with an axle, 1 1/4 ins. diam., firmly set, flush with the ground, from which a bearing tree mkd. by Byron</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

F E E T	<p>An oak, 21 ins. diam., bears N. 8 1/4° E., 39.7 ft. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by Johnstone</p> <p>A fir, 27 ins. diam., bears S. 11° E., 30.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the axle, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 30 S</td><td>R 3 W</td></tr> <tr><td>S 28</td><td>S 27</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td colspan="2">2006</td></tr> </table> </div> <p>from which</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears N. 26° 23' 25" W., 63.47 ft. dist., with aluminum cap mkd. RM T30S R3W S28 63.4 FT TO COR 2006 and an arrow pointing to the cor.</p>	T 30 S	R 3 W	S 28	S 27	<hr/>		S 33	S 34	2006	
T 30 S	R 3 W										
S 28	S 27										
<hr/>											
S 33	S 34										
2006											
1996.85	<hr/> <p>From the closing cor. of secs. 32 and 33 only, on the S. bdy. of the Tp.</p> <p>N. 0° 08' 38" E., bet. secs. 32 and 33, posting and blazing.</p> <p>Descend over broken NW. slope, through burnt area.</p> <p>The 1/4 sec. cor. of secs. 32 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 30 S</td><td>R 3 W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 32</td><td>S 33</td></tr> <tr><td colspan="2">2005</td></tr> </table> </div> <p>from which the remains of original bearing trees</p> <p>A fir snag, 23 ins. diam., bears S. 27 1/4° E., 27.1 ft. dist., with no marks visible.</p> <p>A sawed and decayed fir stump, 37 ins. diam., bears S. 19 1/2° W., 13.9 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by John H. Markham, Jr., Registered PE No. 2880, in 1960, reported by Skeesick and Browning</p>	T 30 S	R 3 W	1/4		S 32	S 33	2005			
T 30 S	R 3 W										
1/4											
S 32	S 33										
2005											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET									
	<p>A sawed and burnt cedar stump, 37 ins. diam., bears S. 78° E., 29.5 ft. dist., no marks visible.</p> <p>A sawed and burnt fir stump, 15 ins. diam., bears N. 42° W., 10.9 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Skeesick and Browning</p> <p>A fir, 5 ins. diam., bears S. 35° E., 21.7 ft. dist., with scribe marks 1/4 S33 BT visible on open blaze.</p> <p>A fir, 6 ins. diam., bears S. 56° W., 12.8 ft. dist., with scribe marks 1/4 S32 BT visible on open blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 23' 36" W., beginning new measurement.</p> <p>Continue descending over broken NW. slope, through burnt area.</p>								
440	Graveled road, 16 ft. wide, bears N. 40° W. and S. 50° E.								
520	Graveled road, 20 ft. wide, bears S. 85° E. and S. 60° W.								
2673.24	<p>The cor. of secs. 28, 29, 32, and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, (along the N. side of which is the original stone), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 30 S</td> <td style="padding: 0 5px;">R 3 W</td> </tr> <tr> <td style="padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 32</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 33</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2004</td> </tr> </table> </div> <p>from which the remains of original bearing trees</p> <p>A roothole bears S. 70° W., 19.8 ft. dist., with no trunk remains.</p> <p>A burnt mandrone stump, size indeterminate, bears N. 82° W., 30.4 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by John H. Markham, Jr., Registered PE No. 2880, in 1960, reported by Skeesick and Browning</p> <p>A burnt cedar snag, 15 ins. diam., bears S. 76° E., 27.0 ft. dist., no marks visible.</p> <p>A burnt chinquapin stump, size indeterminate, bears S. 47° W., 9.7 ft. dist., no marks visible.</p> <p>A burnt mandrone stump, size indeterminate, bears N. 70° W., 36.0 ft. dist., no marks visible.</p>	T 30 S	R 3 W	S 29	S 28	S 32	S 33	2004	
T 30 S	R 3 W								
S 29	S 28								
S 32	S 33								
2004									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>and reference monuments set by Skeesick and Browning</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, bears S. 33° 30' 00" E., 7.50 ft. dist. with aluminum cap mkd. RM T30S R3W S33 7.5 FT TO COR 2005 and an arrow pointing to the cor.</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears S. 38° 30' 00" W., 7.50 ft. dist. with aluminum cap mkd. RM T30S R3W S32 7.5 FT TO COR 2005 and an arrow pointing to the cor.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>Across nearly level ground, changing to ascend over broken NE. slope.</p> <p>N. 89° 19' 38" W., bet. secs. 28 and 33.</p>
1330.21	<p>Point for the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a collar of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 28 E 1/16 ——— S 33 2006</p> </div> <p>from which</p> <p>A fir, 15 ins. diam., bears S. 45 1/2° W., 20.4 ft. dist., mkd. E 1/16 S33 BT.</p> <p>A fir, 14 ins. diam., bears N. 39 1/2° W., 22.5 ft. dist., mkd. E 1/16 S28 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue ascending over broken NE. slope; begin posting and blazing.</p>
1965	<p>Spur, slopes N. 10° W., desc. over NW. slope.</p>
2555	<p>Creek 2 ft. wide, course N. 15° W., asc. over NE. slope.</p>
2660.42	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	T 30 S R 3 W S 28 1/4 ——— S 33 2004
	from which the remains of original bearing trees
	A sawed and burnt fir stump, 52 ins. diam., bears S. 78° E., 64.5 ft. dist., with no marks visible.
	A sawed and burnt fir stump, 33 ins. diam., bears N. 57 1/2° W., 33.0 ft. dist., with no marks visible.
	and bearing trees mkd. by Skeesick and Browning
	A fir, 4 ins. diam., bears S. 77° W., 11.9 ft. dist., with a healed blaze.
	A fir, 15 ins. diam., bears N. 1° W., 30.0 ft. dist., with scribe marks 1/4 S28 BT visible on a partially healed blaze.
	<hr/>
	S. 89° 39' 59" W., beginning new measurement; continue posting and blazing.
	Continue ascending NE. slope.
2669.15	The cor. of secs. 28, 29, 32, and 33.
	<hr/>
	N. 0° 05' 49" E., bet. secs. 28 and 29, posting and blazing.
	Descend over NW. slope, through burnt area.
985	Graveled road, 16 ft. wide, bears S. 75° E. and N. 75° W.
1336.06	The S 1/16 sec. cor. of secs. 28 and 29, established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, with no cap.
	At the corner point
	Drive an aluminum finned rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.
	S 1/16 S 29 S 28 2006
	from which

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner is located 25 ft. South of the S. shoulder of Douglas County Highway No. 1, paved surface, 34 ft. wide, bears N. 40° W. and S. 40° E.</p> <hr/>
2585	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89° 44' 38" W., bet. secs. 29 and 32, posting and blazing.</p> <p>Descend over broken NW. slope, through burnt area.</p> <p>Graveled road, 16 ft. wide, bears N. 35° E. and S. 45° W.</p>
2626.12	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p>
	<p align="center">T 30 S R 3 W S 29 1/4 ——— S 32 2004</p>
	<p>and the remains of a bearing tree mkd. by John H. Markham, Jr., Registered PE No. 2880, in 1960, reported by Skeesick and Browning</p> <p>A sawed and burnt fir stump, 20 ins. diam., bears S. 41° E., 122.0 ft. dist., with scribe marks BT visible on partially opened blaze.</p> <p>A roothole, bears N. 73° W., 59.0 ft. dist., alongside of which is a fallen fir trunk, 12 ins. diam., no marks visible.</p>
	<p>and reference monuments set by Skeesick and Browning</p> <p>An iron rod, 5/8 in. diam., firmly set, flush with the ground, bears S. 47° 30' 00" W., 7.50 ft. dist. with aluminum cap mkd. RM 1/4 S32 7.5 FT TO COR 2004 and an arrow pointing to the cor.</p> <p>An iron rod, 5/8 ins. diam., firmly set, flush with the ground, bears N. 46° 00' 00" W., 7.50 ft. dist. with aluminum cap mkd. RM 1/4 S29 7.5 FT TO COR 2004 and an arrow pointing to the cor.</p>
	<p>Corner is located 35 ft. N. of a graveled road, 16 ft. wide, which bears N. 60° E. and S. 74° W.</p> <hr/> <p>N. 89° 47' 27" W., beginning new measurement; continue posting and blazing.</p> <p>Ascend over NE. slope, through burnt area.</p>
2685.25	<p>The cor. of secs. 29, 30, 31, and 32, perpetuated by Larry E. Monrean, Deputy County Surveyor, in 1988, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 3 W., Point Identifier</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

<p>F E E T</p>	<p>No. 200200, occupied by a burnt fir snag, 33 ins. diam., with burnt and decayed opened blazes on the SE. and SW. faces, no marks visible, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A burnt and decayed fir stump, 34 ins. diam., bears N. 59° W., 5.7 ft. dist., with no marks visible. (Record; N. 40° W., 6.6 ft. dist.)</p> <p>and the remains of a bearing tree mkd. by Bushey</p> <p style="padding-left: 40px;">A roothole bears S. 42° W., 31.0 ft. dist., with no trunk remains.</p> <p>and bearing trees mkd. by Monrean</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 12 3/4° E., 15.6 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 21 1/4° W., 25.4 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A chinquapin, 12 ins. diam., bears N. 32 1/4° W., 24.5 ft. dist., with no marks visible on a decayed, partially healed blaze.</p> <p>At the corner point</p> <p>Sawed off the original fir snag, and drive a finned aluminum rod, 3/4 in. diam., 36 ins. long, 32 ins. into the center of the stump, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 30 S</td> <td style="padding: 0 10px;">R 3 W</td> </tr> <tr> <td style="padding: 0 10px;">S 30</td> <td style="padding: 0 10px;">S 29</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S 31</td> <td style="border-top: 1px solid black; padding: 0 10px;">S 32</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">2006</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears S. 52° 49' 29" E., 7.24 ft. dist. with aluminum cap mkd. RM T30S R3W S32 7.2 FT. TO COR. 2006 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., 28 ins. in the ground for a reference monument, bears N. 32° 21' 43" W., 7.65 ft. dist. with aluminum cap mkd. RM T30S R3W S30 7.6 FT. TO COR. 2006 and an arrow pointing to the cor.</p> <p>Deposit a magnet without its white plastic case alongside the finned aluminum rod.</p> <p>From this cor., a point erroneously perpetuated as the cor. of sections 29, 30, 31, and 32, by John H. Markham, Jr., Registered PE No. 2880, in 1960, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 3 W., Point Identifier No. 200200, perpetuated and used in the subdivision of sec. 29, by Victor M. McLind, Registered PLS No. 934, in</p>	T 30 S	R 3 W	S 30	S 29	S 31	S 32	2006	
T 30 S	R 3 W								
S 30	S 29								
S 31	S 32								
2006									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

<p>F E E T</p>	<p>1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, bears S. 89° 43' 53" E., 70.03 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, from which bearing trees of unknown origin</p> <p>A fir, 36 ins. diam., bears N. 53° E., 15.8 ft. dist., with a healed blaze.</p> <p>A burnt and sawed fir stump, 31 ins. diam., bears S. 71° E., 12.6 ft. dist., with opened and decayed blaze and no marks visible.</p> <p>and a bearing tree mkd. by Markham</p> <p>A madrone, 16 ins. diam., bears N. 9° E., 24.4 ft. dist., with partially healed blaze and no marks visible.</p> <p>This point was established from bearing trees not of record, substantiated by Larry E. Monrean, Deputy County Surveyor, in 1988, and was not utilized in the course of this survey.</p>
<p>1330.44</p>	<hr/> <p>N. 0° 04' 51" W., bet. secs. 29 and 30, posting and blazing.</p> <p>Descend over NW. slope, through burnt area.</p> <p>Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center"> S 1/16 S 30 S 29 2006 </p> <p>from which</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 45° 00' 00" E., 7.50 ft. dist. with aluminum cap mkd. RM S 1/16 S29 7.5 FT TO COR 2006 and an arrow pointing to the cor.</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 45° 00' 00" W., 7.50 ft. dist. with aluminum cap mkd. RM S 1/16 S30 7.5 FT TO COR 2006 and an arrow pointing to the cor.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, a point established by Bruce A. Shaner, Registered PLS, No. 430, in 1995, recorded in the Douglas County Surveyors Office, Map File No. M119-52, bears N. 88° 27' 24" E., 17.84 ft. dist., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
2660.88	<p>cap mkd. S1/16 S30 S29 1995 RLS 430, along the N., S., and W., 1 ft. dist., of which are fence posts, firmly set, projecting 48 ins. above the ground.</p> <p>This point was established using improper control and was not utilized in the course of this survey.</p> <p>Discontinue posting and blazing.</p> <p>Continue descending over broken NW. slope, through burnt area.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30 at proportionate dist. There is no remaining evidence of the original cor.</p> <p>Set an iron rod, 30 ins. long, 5/8 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <p align="center">T 30 S R 3 W 1/4 S 30 S 29 2006</p> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 2° 00' 00" E., 43.00 ft. dist. with aluminum cap mkd. RM 1/4 S29 43.0 FT TO COR 2006 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 88° 00' 00" W., 20.00 ft. dist. with aluminum cap mkd. RM 1/4 S30 20.0 FT TO COR 2006 and an arrow pointing to the cor.</p> <p>From this point, a point established as the 1/4 sec. cor. of secs. 29 and 30 by Victor M. McLind, Registered PLS No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, perpetuated by Bruce A. Shaner, Registered PLS, No. 430, in 1995, recorded in the Douglas County Surveyors Office, Map File No. M119-52, bears N. 89° 29' 32" E., 35.01 ft. dist., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T30S R3W 1/4 S30 S29 RLS 934 1972.</p> <p>This point was established using improper control and was not utilized in the course of this survey.</p> <p>Descend over nearly level farm land.</p>
5321.76	<p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET

COUNTY SURVEYORS OFFICE

T 30 S
S 19 | S 20

S 30 | S 29
R 3 W
1963

from which the remains of an original bearing tree

A burnt oak stump, 28 ins. diam., bears S. $6\ 1/4^\circ$ W., 138.6 ft. dist., no marks visible. (Record, S. 8° W.)

and the remains of a bearing tree mkd. by Byron, reported by Skeesick and Browning

A roothole bears S. 48° W., 25.7 ft. dist., with no trunk remains.

and the remains of bearing trees mkd. by Rogers, Bishop, and White

A roothole bears N. 32° E., 88.4 ft. dist., with no trunk remains.

A roothole bears S. 80° E., 133.3 ft. dist., with no trunk remains.

A burnt fir snag, 13 ins. diam., bears N. $58\ 1/4^\circ$ W., 100.3 ft. dist., with no marks visible. (Record, N. $59\ 1/4^\circ$ W.)

and reference monuments set by Skeesick and Browning

An iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears S. $45^\circ\ 00'\ 00''$ W., 7.50 ft. dist. with aluminum cap mkd. RM T30S R3W S30 7.50 FT. TO COR. 2004 and an arrow pointing to the cor.

An iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears N. $45^\circ\ 00'\ 00''$ W., 7.50 ft. dist. with aluminum cap mkd. RM T30S R3W S19 7.50 FT. TO COR. 2004 and an arrow pointing to the cor.

A woven wire fence bears E., 11.5 ft. dist., extends North and South.

**Subdivision of Section 29,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

From the 1/4 sec. cor. of secs. 29 and 32.

N. $0^\circ\ 27'\ 05''$ W., on the N. and S. centerline of sec. 29.

Descend over broken NW. slope, through burnt area.

Subdivision of Section 29,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

<p>F E E T</p> <p>1332.50</p>	<p>The center S 1/16 sec. cor. of sec. 29, established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, flush with the ground, from which the remains of a bearing tree mkd. by McLind</p> <p style="text-align: center;">A roothole bears S. 39 1/4° W., 33.9 ft. dist., no trunk remains.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>C S 1/16 S 29 C 2006</p> </div> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 45° 00' 00" E., 7.60 ft. dist. with aluminum cap mkd. RM CS 1/16 S29 7.6 FT TO COR 2006 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 45° 00' 00" W., 7.50 ft. dist. with aluminum cap mkd. RM CS 1/16 S29 7.5 FT TO COR 2006 and an arrow pointing to the cor.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 21' 32" W., beginning new measurement.</p> <p>Descend over gentle N. slope.</p>
<p>100</p>	<p>Graveled road, 12 ft. wide, bears E. and W.</p>
<p>1333.29</p>	<p>The center 1/4 sec. cor. of sec. 29, established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, and is accepted as the cor., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 3 W C 1/4 S 29 RLS 934 1972</p> </div> <p>from which bearing trees mkd. by McLind</p>

**Subdivision of Section 29,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
2681.12	<p>An oak, 39 ins. diam., bears S. 48 1/2° W., 241.9 ft. dist., with a healed double blaze.</p> <p>An oak, 40 ins. diam., bears N. 8 3/4° W., 258.2 ft. dist., with a healed double blaze.</p> <p>Corner is located in level pasture land.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 21' 32" W., beginning new measurement.</p> <p>Across nearly level pasture land, changing to asc. over SW. slope.</p> <p>The 1/4 sec. cor. of secs. 20 and 29, perpetuated by John H. Markham, Jr., Registered PE, No. 2880, in 1951, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 3 W., Point Identifier No. 240300, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A roothole bears S. 60° W., 10.6 ft. dist., with no trunk remains.</p> <p>and the remains of bearing trees mkd. by Markham</p> <p style="padding-left: 40px;">A roothole bears S. 2° E., 32.2 ft. dist., with no trunk remains.</p> <p style="padding-left: 40px;">A burnt maple stump, 24 ins. diam., bears N. 24 1/4° W., 31.0 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 30 S R 3 W S 20 1/4 ——— S 29 2006 </div> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears N. 37° 16' 50" E., 10.00 ft. dist., with aluminum cap mkd. RM T30S R3W 1/4 S20 10.0 FT TO COR 2006 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground for a reference monument, bears S. 52° 59' 38" E., 8.00 ft. dist., with aluminum cap mkd. RM T30S R3W 1/4 S29 8.0 FT TO COR 2006 and an arrow pointing to the cor.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 28 and 29.</p>

**Subdivision of Section 29,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
2649.30	<p>N. 89° 49' 59" W., on the E. and W. centerline of sec. 29.</p> <p>Across nearly level pasture land.</p> <p>The center 1/4 sec. cor. of sec. 29.</p> <hr/>
2665	<p>N. 89° 53' 37" W., beginning new measurement.</p> <p>Continue across nearly level pasture land.</p> <p>Ferguson Lane, graveled road, 12 ft. wide, bears S. 10° E. and N. 10° W.</p>
2669.80	<p>The 1/4 sec. cor. of secs. 29 and 30.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 28 and 29.</p> <p>N. 89° 50' 38" W., on the E. and W. centerline of the SE 1/4 of sec. 29, posting and blazing.</p> <p>Across nearly level slope.</p> <p>325.28 Angle point No. 1, a parcel cor., established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 7 ins. above the ground, with no cap.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the iron rod, mkd.</p> <div style="text-align: center;"> <p>AP 1</p> <p>S—S</p> <p>S 29</p> <p>2006</p> </div> <hr/>
319.89	<p>N. 89° 49' 25" W., beginning new measurement; continue posting and blazing.</p> <p>Across nearly level slope.</p> <p>319.89 Angle point No. 2, a parcel cor., established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 7 ins. above the ground, with no cap.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the iron rod, mkd.</p>

**Subdivision of Section 29,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
100.04	<div style="text-align: center;"> AP 2 S ——— S S 29 2006 </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 46' 46" W., beginning new measurement; continue posting and blazing.</p> <p>Across nearly level slope.</p> <p>Angle point No. 3, a parcel cor., established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with no cap.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the iron rod, mkd.</p>
319.95	<div style="text-align: center;"> AP 3 S ——— S S 29 2006 </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 49' 38" W., beginning new measurement; continue posting and blazing.</p> <p>Across nearly level slope.</p> <p>Angle point No. 4, a parcel cor., established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with no cap.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the iron rod, mkd.</p>
319.92	<div style="text-align: center;"> AP 4 S ——— S S 29 2006 </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 49' 10" W., beginning new measurement; continue posting and blazing.</p> <p>Across nearly level slope.</p> <p>Angle point No. 5, a parcel cor., established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with no cap.</p>

**Subdivision of Section 29,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the iron rod, mkd.</p> <p style="text-align: center;">AP 5 S — S S 29 2006</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 48' 19" W., beginning new measurement; continue posting and blazing.</p> <p>Across nearly level slope.</p>
320.14	<p>Angle point No. 6, a parcel cor., established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with no cap.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the iron rod, mkd.</p> <p style="text-align: center;">AP 6 S — S S 29 2006</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 50' 05" W., beginning new measurement; continue posting and blazing.</p> <p>Across nearly level slope.</p>
319.90	<p>Angle point No. 7, a parcel cor., established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with no cap.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the iron rod, mkd.</p> <p style="text-align: center;">AP 7 S — S S 29 2006</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 48' 12" W., beginning new measurement; continue posting and blazing.</p> <p>Across nearly level slope.</p>

**Subdivision of Section 29,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
51.44	<p>Angle point No. 8, a parcel cor., established by Victor M. McLind, Registered PLS, No. 934, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M42-63, monumented with an iron rod, 5/8 in. diam., firmly set, buried 3 ins. below the surface of the ground, with no cap.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the iron rod, mkd.</p> <div style="text-align: center;"> <p>AP 8 S—S S 29 2006</p> <hr style="width: 20%; margin: auto;"/> </div> <p>N. 89° 49' 30" W., beginning new measurement; continue posting and blazing.</p> <p>Across nearly level land.</p>
15	Ferguson Lane, a graveled road, 15 ft. wide, bears S. 55° E. and N. 55° W.
562.16	<p>The center S 1/16 sec. cor. of sec. 29.</p> <hr/> <p>N. 89° 50' 00" W., on the E. and W. centerline of the SW 1/4 of sec. 29, posting and blazing.</p> <p>Continue across nearly level land, changing to ascend over broken NE. slope, through burnt area.</p>
955	Graveled road, 12 ft. wide, bears S. 45° E. and N. 45° W.
2245	Creek 2 ft. wide, course N. 50° E., asc. over NE. slope.
2676.46	<p>The S 1/16 sec. cor. of secs. 29 and 30.</p> <hr/> <p style="text-align: center;">Subdivision of Section 33, T. 30 S., R. 3 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of sec. 33 only, on the S. bdy. of the Tp.</p> <p>N. 0° 29' 20" W., on the N. and S. centerline of sec. 33.</p> <p>Ascend over broken SE. slope, through burnt area.</p>
2017.18	<p>Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 33,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">T 30 S R 3 W C 1/4 S 33 2006</p> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 ins. diam., driven 30 ins. in the ground for a reference monument, bears S. 30° 00' 00" E., 15.00 ft. dist., with aluminum cap mkd. RM C 1/4 S33 15.0 FT TO COR 2006 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 ins. diam., 30 ins. in the ground for a reference monument, bears S. 60° 00' 00" W., 8.00 ft. dist., with aluminum cap mkd. RM C 1/4 S33 8.0 FT TO COR 2006 and an arrow pointing to the cor.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, the cor. of 4-strand barbed wire fences bears N. 13 3/4° W., 27.0 ft. dist., extends North and East.</p> <p>Begin posting and blazing.</p> <p>Descend over broken NE. slope, through burnt area.</p> <p>3342.27 Point for the center N 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 33 C 2006</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears N. 8 3/4° E., 116.6 ft. dist., mkd. CN 1/16 S33 BT.</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears N. 84 1/4° E., 154.8 ft. dist., mkd. CN 1/16 S33 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, the cor. of fences bears N. 15° E., 5.8 ft. dist., extends South and East.</p> <p>Discontinue posting and blazing</p>
------	---

**Subdivision of Section 33,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	Across nearly level ground.
4667.36	The 1/4 sec. cor. of secs. 28 and 33. <hr/>
	From the 1/4 sec. cor. of secs. 33 and 34. S. 89° 10' 24" W., on the E. and W. centerline of sec. 33, posting and blazing. Ascend over SE. slope, through second growth timber and dense undergrowth.
40	Graveled road, 12 ft. wide, bears S. 25° E. and N. 25° W.
335	A 3 strand barbed wire fence bears South, 42.7 ft. dist., extends S. 86° E. and N. 86° W.
410	Spur, slopes N. 10° W.; desc. over NW. slope.
430	Barbed wire fence, bears S. 65° E. and N. 65° W.
575	Graveled road, 15 ft. wide, bears S. 65° E. and N. 65° W.
1015	Graveled road, 12 ft. wide, bears N. 45° E. and S. 45° W.
1045	Graveled road, 12 ft. wide, bears S. 5° E. and N. 5° W.
1070	Graveled road, 12 ft. wide, bears N. 10° E. and S. 10° W.
1220	Bottom of descent, asc. over SE. slope.
1331.35	Point for the center E 1/16 sec. cor. of sec. 33, not monumented. Continue asc. over broken SE. slope.
2662.70	The center 1/4 sec. cor. of sec. 33. Discontinue posting and blazing. Continue asc. over broken SE. slope, changing to desc. over broken NE. slope, through burnt area.
5290.00	The 1/4 sec. cor. of secs. 32 and 33. <hr/>
	From the center N 1/16 sec. cor. of sec. 33. N. 89° 55' 22" E., on the E. and W. centerline of the NE 1/4 sec. 33, posting and blazing. Across nearly level ground.
1080	Graveled road, 15 ft. wide, bears S. 55° E. and N. 60° W.

**Subdivision of Section 33,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
1245	Enter pond, edge bears N. 60° E. and S. 60° W.
1330.67	Point for the NE 1/16 sec. cor. of sec. 33 falls in pond; impractical to establish a permanent monument.
	<hr/> <p>N. 0° 30' 58" W., on the N. and S. centerline of the NE 1/4 of sec. 33, posting and blazing.</p> <p>Through pond.</p>
20	Leave pond, edge bears S. 13° E. and N. 13° W.
30.00	Point selected for the witness cor. to the NE 1/16 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p>WC NE 1/16 S 33 ↓ 2006</p>
	from which
	A madrone, 20 ins. diam., bears N. 26 1/4° E., 71.2 ft. dist., mkd. X BT.
	A fir, 8 ins. diam., bears N. 69 1/4° W., 47.4 ft. dist., mkd. X BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Continue across nearly level ground.
415	Descent steepens, edge bears S. 45° E. and N. 25° W., desc. over NE. slope.
1307.68	The E 1/16 sec. cor. of secs. 28 and 33.
	<hr/>

T. 30 S., R. 3 W., Willamette Meridian, Oregon

<p>F E E T</p>	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands include in the foregoing survey are located about 1.5 miles westerly from Milo, Oregon. The area is drained by the South Umpqua River, Stouts Creek, and Coon Creek, and a number of small seasonal streams. Elevations range from about 920 feet above mean sea level, near the center 1/4 section corner of section 29, to about 2620 feet above sea level, near the corner of sections 32 and 33, on the south boundary of the township.</p> <p>Access is gained by way of Douglas County Highway No. 1, also Stouts Creek Road, with numerous graveled roads leading into the area.</p> <p>Soil consists of rock, clay, and sandy loam. There were a number of rock outcroppings in the area.</p> <p>Timber in this area consists of fir, cedar, hemlock, oak, alder, madrone, maple, and chinquapin. Undergrowth consists of vine maple, hazel, ceanothus, ferns, poison oak, salal, Oregon grape, arrowwood, huckleberry, salmonberry, and rhododendron.</p> <p>The lands are used primarily for farm land, and timber production.</p> <hr/>
----------------	---