

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF
THE EAST BOUNDARY
AND A PORTION OF
THE SUBDIVISIONAL LINES
TOWNSHIP 29 SOUTH, RANGE 3 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated January 23, 2007, approved
January 26, 2007, which provided for the surveys included under
Group No. 2157, and Assignment Instructions dated March 7, 2007.

Survey commenced March 19, 2007

Survey completed May 10, 2007

T. 29 S., R. 3 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the east boundary and subdivisional lines, Township 29 South, Range 3 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1858, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the west boundary and a portion of the south boundary of the township and a portion of the subdivisional lines.

In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed the north and east boundaries and the remainder of the south boundary of the township, and the remainder of the subdivisional lines.

In 1917, Elmer F. Strickler, U.S. Transitman, resurveyed the west boundary, and surveyed the subdivisional lines of T. 29 S., R. 2 W.

In 1979-80, James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, resurveyed a portion of the north boundary, subdivisional lines, and Donation Land Claim No. 37, and subdivided section 21.

In 2002-03, Timothy J. Moore and A. Bert Skeesick, Cadastral Surveyors, resurveyed a portion of the subdivisional lines and subdivided section 23.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 23, 2007, for Group No. 2157, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement Management (CMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

T. 29 S., R. 3 W., Willamette Meridian, Oregon

FEET

The following published stations from the National Spatial Reference System Continuously Operating Reference Station (CORS) were used for control: "CAPE BLANCO CORS ARP", "DODSON BUTTE CORS ARP", and "ROSEBURG COOP CORS ARP".

The geographic position (NAD 1983 (CORS)) of the following corners was determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.05 meters, 95% confidence level, relative to the National Spatial Reference System stations noted above.

The 1/4 section corner of section 25 only, on the east boundary of the township:

Latitude: 43° 01' 11.01" N. Longitude: 123° 00' 10.04" W.

The corner of sections 25, 26, 35, and 36:

Latitude: 43° 00' 45.24" N. Longitude: 123° 01' 17.57" W.


The corner of sections 22, 23, 26, and 27:

Latitude: 43° 01' 38.41" N. Longitude: 123° 02' 26.36" W.

**Dependent Resurvey of a Portion of the East Boundary,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

(Restoring the 1881 survey by William H. Byars
and the 1917 resurvey by Elmer F. Strickler)

Beginning at the 1/4 sec. cor. of sec. 25 only, on the E. bdy. of the Tp., perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier No. 700240, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.



from which the remains of bearing trees mkd. by Strickler

A decayed fir stump, 21 ins. diam., bears S. 14° W., 38.9 ft. dist., with no marks visible.

A fir, 42 ins. diam., bears N. 8° W., 164.3 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the East Boundary,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>and the remains of bearing trees mkd. by Byron</p> <p>A chinquapin, 10 ins. diam., bears S. 34° W., 4.3 ft. dist., with scribe marks 1/4 S25 CS visible on a partially healed blaze.</p> <p>A fir, 17 ins. diam., bears N. 68 1/4° W., 17.5 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p>A fir, 8 ins. diam., bears N. 89 3/4° E., 13.7 ft. dist., mkd. X BT.</p> <p>From this cor., the cor. of secs 30 and 31 only, T. 29 S., R. 2 W., perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier No. 700237, bears S. 0° 58' 00" E., 185.78 ft. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R3W R2W S25 S30 ----- S31 1917</p> </div> <p>from which bearing trees mkd. by Strickler</p> <p>A fir, 37 ins. diam., bears N. 7 1/4° E., 49.2 ft. dist., with a healed blaze. (Record; N. 16 1/4° E., 51.5 ft.)</p> <p>A fir, 47 ins. diam., bears S. 25 1/2° E., 99.9 ft. dist., with a healed blaze. (Record; S. 16 1/2° E., 106.3 ft.)</p> <p>and the remains of bearing trees mkd. by Byron</p> <p>A madrone, 14 ins. diam., bears N. 46 1/4° E., 30.0 ft. dist., with a healed blaze.</p> <p>A fir, 20 ins. diam., bears S. 47° E., 33.4 ft. dist., with a healed blaze.</p> <p>N. 0° 02' 17" W., bet. secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>Ascend broken SE. slope, posting and blazing.</p> <p>210 Graveled road, 12 ft. wide, bears N. 50° E. and S. 50° W.</p> <p>495 Spur, slopes N. 70° E.; desc. steep, broken NW. slope.</p> <p>1360 Creek, 2 ft. wide, course N. 88° E.; asc. steep SE. slope.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

<p>F E E T</p> <p>2455.77</p>	<p>The 1/4 sec. cor. of sec. 30 only, T. 29 S., R. 2 W., perpetuated by James W. Byron, Deputy County Surveyor, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier No. 700278, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with the original stone, 13 x 6 x 9 ins., lying alongside, mkd 1/4, and a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; vertical-align: middle;">C O U N T Y</td> <td style="text-align: center; vertical-align: middle;">T29S 1/4</td> <td style="text-align: center; vertical-align: middle;">O F F I C E</td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">R 3 W</td> <td style="text-align: center; vertical-align: middle;"> </td> <td style="text-align: center; vertical-align: middle;">R 2 W</td> </tr> <tr> <td colspan="3" style="text-align: center;">S30 W</td> </tr> <tr> <td colspan="3" style="text-align: center;">WEST</td> </tr> <tr> <td colspan="3" style="text-align: center;">1962</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <ul style="list-style-type: none"> A fir, 42 ins. diam., bears N. 65° E., 56.8 ft. dist., with a healed blaze. A decayed fir stump, size indeterminate, bears S. 31 3/4° E., 11.9 ft. dist., with no marks visible. (Record, S. 25° E.) <p>and bearing tree mkd. by Byron</p> <ul style="list-style-type: none"> A fir, 29 ins. diam., bears S. 38 3/4° E., 24.3 ft. dist., with a healed blaze. <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 55' 07" E., beginning new measurement.</p>	C O U N T Y	T29S 1/4	O F F I C E	R 3 W		R 2 W	S30 W			WEST			1962		
C O U N T Y	T29S 1/4	O F F I C E														
R 3 W		R 2 W														
S30 W																
WEST																
1962																
<p>51.97</p>	<p>The cor. of secs 24 and 25 only, on the E. bdy. of the Tp., perpetuated by James W. Byron, Deputy County Surveyor, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier No. 700300, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with the original stone, 12 x 12 x 9 ins., lying alongside, with 5 grooves visible, and a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; vertical-align: middle;">C O U N T Y</td> <td style="text-align: center; vertical-align: middle;">T29S 1/4</td> <td style="text-align: center; vertical-align: middle;">O F F I C E</td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">R S24 3 W S25</td> <td style="text-align: center; vertical-align: middle;"> </td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center;">1962</td> </tr> </table> </div> <p>from which bearing trees mkd. by Strickler</p>	C O U N T Y	T29S 1/4	O F F I C E	R S24 3 W S25			1962								
C O U N T Y	T29S 1/4	O F F I C E														
R S24 3 W S25																
1962																

**Dependent Resurvey of a Portion of the East Boundary,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>A cedar, 42 ins. diam., bears S. 10° W., 8.6 ft. dist., with a healed blaze.</p> <p>A fir, 34 ins. diam., bears N. 18° W., 28.6 ft. dist., with a healed blaze. (Record, 30.4 ft.)</p>
	<hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 29 S., R. 3 W., Willamette Meridian, Oregon</p> <hr/>
	<p>(Restoring the 1881 survey by William H. Byars, the 1979-80 resurvey by James E. Jelley and Wayne L. Rogers, and the 2002-03 resurvey by Timothy J. Moore and A. Bert Skeesick)</p> <hr/>
	<p>From the cor. of secs 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89° 46' 17" W., bet. secs. 24 and 25.</p> <p>Ascend broken SE. slope, posting and blazing.</p>
1555	Ridge, bears N. 25° E. and S. 25° W.; desc. NW. slope.
1570	Graveled road, 12 ft. wide, bears N. 25° E. and S. 25° W.
2561.83	<p>The 1/4 sec. cor. of secs. 24 and 25, perpetuated by John H. Markham, Jr., Oregon Professional Engineer No. 2880, in 1957, and by Mark F. Smalley, Oregon Professional Land Surveyor (PLS) No. 2354, in 1999, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier No. 640300, monumented with an iron pipe, 1 3/4 ins. diam., firmly set, projecting 6 ins. above ground, with no cap, from which the remains of an original bearing tree</p> <p align="center">A tin capped sawed fir stump, 43 ins. diam., bears S. 35° W., 23.8 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by Markham</p> <p align="center">A fir, 25 ins. diam., bears S. 85 1/4° W., 36.6 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Smalley</p> <p align="center">A fir, 12 ins. diam., bears N. 35 1/4° E., 15.1 ft. dist., with a healed blaze.</p> <p align="center">A fir, 12 ins. diam., bears N. 49 1/2° W., 16.2 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 13 ins. diam., bears N. 24 1/4° W., 23.3 ft. dist., with a healed blaze.</p> <p>On top of the existing iron pipe</p> <p>Cement a brass cap, 3 ins. diam., with 3 1/2 in. stem, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T29S</td><td>R3W</td></tr> <tr><td colspan="2" style="text-align: center;">S24</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td colspan="2" style="text-align: center;">S25</td></tr> <tr><td colspan="2" style="text-align: center;">2007</td></tr> </table> </div> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2" style="text-align: center;">COUNTY</td><td style="text-align: center;">SURVEYORS</td><td colspan="2" style="text-align: center;">OFFICE</td></tr> <tr><td colspan="2" style="text-align: center;">T29S</td><td style="text-align: center;">R3W</td><td colspan="2"></td></tr> <tr><td colspan="2" style="text-align: center;">S26</td><td style="text-align: center;">S25</td><td colspan="2"></td></tr> <tr><td colspan="2" style="text-align: center;">-----</td><td style="text-align: center;">-----</td><td colspan="2"></td></tr> <tr><td colspan="2" style="text-align: center;">S35</td><td style="text-align: center;">S36</td><td colspan="2"></td></tr> <tr><td colspan="2" style="text-align: center;">1973</td><td colspan="2"></td><td></td></tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A fir stump, 41 ins. diam., bears N. 73 1/4° E., 12.9 ft. dist., with a healed blaze.</p> <p>A decayed fir stump, 31 ins. diam., bears S. 16 3/4° E., 44.6 ft. dist., with a previously opened and rehealed blaze.</p> <p>A decayed fir stump, size indeterminate, bears S. 41° W., 4.6 ft. dist., with no marks visible.</p> <p>A decayed fir stump, 12 ins. diam., bears N. 45° W., 7.3 ft. dist., with a healed blaze.</p> <p>and remains of bearing trees mkd. by John H. Markham, Jr., Oregon Registered Professional Engineer No. 2880, in 1959, reported by Moore and Skeesick</p> <p>A decayed fir stump, 15 ins. diam., bears S. 67 1/2° E., 35.7 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>A decayed fir stump, 26 ins. diam., bears S. 41° W., 14.7 ft. dist., with scribe marks BT visible on a bark blaze.</p> <p>and a reference monument set by Markham, reported by Moore and Skeesick</p> <p>An iron pipe, 3 ins. diam., firmly set, projecting 3 ins. above ground, bears S. 64 1/2° E., 3.5 ft. dist., with no cap or marks visible.</p>	T29S	R3W	S24		-----		1/4		S25		2007		COUNTY		SURVEYORS	OFFICE		T29S		R3W			S26		S25			-----		-----			S35		S36			1973				
T29S	R3W																																										
S24																																											

1/4																																											
S25																																											
2007																																											
COUNTY		SURVEYORS	OFFICE																																								
T29S		R3W																																									
S26		S25																																									
-----		-----																																									
S35		S36																																									
1973																																											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>and bearing trees mkd. by Moore and Skeesick</p> <p>A fir, 11 ins. diam., bears N. 9 1/2° E., 23.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>A fir, 14 ins. diam., bears S. 17 1/2° E., 11.7 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 31 1/2° W., 27.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>A fir, 11 ins. diam., bears N. 62 3/4° W., 9.1 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>N. 87° 58' 29" W., bet. secs. 26 and 35.</p> <p>Ascend broken SW. slope, posting and blazing.</p>
250	Graveled road, 12 ft. wide, bears S. 59° E. and N. 59° W.
515	Graveled road, 16 ft. wide, bears N. 57° E. and S. 57° W., and top of ridge, bears N. 68° E. and West; asc. NE. slope.
1085	Spur, slopes N. 35° W.; desc. SW. slope.
1690	Graveled road, 16 ft. wide, bears S. 18° E. and N. 30° W.
2578.26	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R3W</p> <p>S26</p> <p>1/4 ———</p> <p>S35</p> <p>2007</p> </div> <p>from which</p> <p>A fir, 17 ins. diam., bears S. 38 1/2° W., 4.6 ft. dist., mkd. 1/4 S35 BT.</p> <p>A fir, 18 ins. diam., bears N. 51 1/4° W., 50.1 ft. dist., mkd. 1/4 S26 BT.</p> <p>Deposit magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by Donald R. Martin, Registered Forest Engineer No. 3900, in 1960, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

FEET																			
	<p>No. 540200, and is not accepted as the cor., bears S. 88° 34' 43" W., 18.36 ft. dist., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 16 ins. above ground, with no cap, from which the remains of bearing trees mkd. by Martin</p> <p style="padding-left: 40px;">A tin capped sawed madrone stump, 17 ins. diam., bears N. 40 1/4° E., 4.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A decayed stump, size and species indeterminate, bears S. 35 1/4° W., 26.4 ft. dist., with no marks visible.</p> <p>Continue desc. steep SW. slope, posting and blazing.</p>																		
2990	Graveled road, 16 ft. wide, bears S. 20° E. and N. 18° W.																		
3670	Creek, 2 ft. wide, course S. 53° W.; asc. S. slope.																		
5156.52	<p>The cor. of secs. 26, 27, 34, and 35, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier No. 500200, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;"> <table style="border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td style="text-align: center;">T29S</td> <td style="text-align: center;">R3W</td> <td></td> </tr> <tr> <td style="text-align: center;">S27</td> <td style="text-align: center;">S26</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">S34 S35</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1961</td> <td></td> </tr> </table> </td> <td></td> </tr> </table> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole bears N. 42° E., 21.8 ft. dist., with fallen fir trunk, 20 ins. diam., lying alongside, with no marks visible on an opened blaze.</p> <p style="padding-left: 40px;">A decayed fir snag, 15 ins. diam., bears S. 84° E., 19.8 ft. dist., with fragmentary scribe marks visible on a previously opened blaze. (Record, S. 89° E.)</p> <p style="padding-left: 40px;">A sawed cedar stump, 12 ins. diam., bears S. 55° W., 41.5 ft. dist., with no marks visible. (Record, 37.0 ft.)</p> <p style="padding-left: 40px;">A fallen decayed fir snag, size indeterminate, bears N. 50° W., 19.1 ft. dist., with no marks visible.</p> <p>and remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fallen decayed cedar, 16 ins. diam., bears N. 7 1/4° E., 21.8 ft. dist., with a healed blaze.</p>	COUNTY	<table style="border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td style="text-align: center;">T29S</td> <td style="text-align: center;">R3W</td> <td></td> </tr> <tr> <td style="text-align: center;">S27</td> <td style="text-align: center;">S26</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">S34 S35</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1961</td> <td></td> </tr> </table>	SURVEYORS		OFFICE	T29S	R3W		S27	S26		S34 S35			1961			
COUNTY	<table style="border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td style="text-align: center;">T29S</td> <td style="text-align: center;">R3W</td> <td></td> </tr> <tr> <td style="text-align: center;">S27</td> <td style="text-align: center;">S26</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">S34 S35</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1961</td> <td></td> </tr> </table>	SURVEYORS		OFFICE	T29S	R3W		S27	S26		S34 S35			1961					
SURVEYORS		OFFICE																	
T29S	R3W																		
S27	S26																		
S34 S35																			
1961																			

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

F E E T	<p>A cedar, 15 ins. diam., bears S. 43 1/2° E., 14.6 ft. dist., with a healed blaze.</p> <p>A cedar, 13 ins. diam., bears S. 1 1/4° E., 32.3 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears N. 28 1/4° W., 43.3 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p>A cedar, 7 ins. diam., bears N. 29 1/4° E., 28.0 ft. dist., mkd. T29S R3W S26 BT.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS CO SURVEYOR T29S R3W S22 S23 ----- S27 S26 1976</p> <p>from which the remaining original bearing tree</p> <p>A maple, 30 ins. diam., bears N. 45° E., 6.6 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by the Douglas County Surveyors Office in 1976, reported by Moore and Skeesick</p> <p>A cedar, 30 ins. diam., bears S. 65 1/2° E., 103.5 ft. dist., with scribe marks BT visible on a partially healed blaze.</p> <p>and bearing trees mkd. by person(s) unknown reported by Moore and Skeesick</p> <p>A fir, 25 ins. diam., bears S. 24 1/4° E., 33.2 ft. dist., with a healed blaze.</p> <p>A fir, 25 ins. diam., bears S. 40 1/4° W., 61.2 ft. dist., with a healed double blaze.</p> <p>N. 85° 46' 35" W., bet. secs. 22 and 27.</p> <p>Over level creek bottom, posting and blazing.</p> <p>160 Days Creek, 10 ft. wide, course S. 40° W.</p> <p>535 Graveled road, 20 ft. wide, bears N. 46° E. and S. 46° W., and creek, 5 ft. wide, course S. 12° E., in culvert under road; asc. broken SE. slope.</p>
---------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

FEEET																
1940	Spur, slopes S. 4° E.; continue asc. SE. slope.															
2255	Spur, slopes S. 28° E.; continue asc. S. slope.															
2545.17	<p>The 1/4 sec. cor. of secs. 22 and 27, perpetuated by John H. Markham, Jr., Oregon Professional Engineer No. 2880, in 1950, remonumented by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier No. 440300, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">SURVEYORS</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center; vertical-align: middle;">T29S R3W</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">S22</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1/4 _____</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S27</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1961</td> <td></td> </tr> </table> <p>from which the remains of the original bearing trees</p> <ul style="list-style-type: none"> A roothole bears N. 40° E., 2.0 ft. dist., with decayed fallen fir trunk, size indeterminate, lying alongside, with no marks visible. A decayed fir stump, size indeterminate, bears S. 70° W., 7.9 ft. dist., no trunk remains. <p>and remains of a bearing tree mkd. by Markham</p> <ul style="list-style-type: none"> A burned madrone root bears S. 13° E., 21.4 ft. dist., with no marks visible and madrone trunks, 4 ins. diam., growing from it. <p>and bearing trees mkd. by Byron</p> <ul style="list-style-type: none"> A fir, 20 ins. diam., bears N. 43 3/4° E., 13.6 ft. dist., with a healed blaze. A cedar, 21 ins. diam., bears S. 72 1/2° E., 43.0 ft. dist., with a healed blaze. <p>An iron pipe, 1 1/4 ins. diam., projects 22 ins. above ground, from the base of the iron post.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. 86° 15' 26" W., beginning new measurement.</p> <p>Descend broken SW. slope; continue posting and blazing.</p>	COUNTY	T29S R3W	OFFICE		S22			1/4 _____			S27			1961	
COUNTY	T29S R3W	OFFICE														
	S22															
	1/4 _____															
	S27															
	1961															
185	Ravine, drains S. 15° E.; asc. broken E. slope.															
340	Dirt road, 15 ft. wide, bears S. 6° E. and N. 6° W.															

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

FEET													
1010	Spur, slopes S. 45° W.; desc. broken W. slope.												
1930	Creek, 3 ft. wide, course S. 10° E.												
1995	Creek, 1 ft. wide, course S. 46° E.; asc. E. slope.												
2440.01	<p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td rowspan="5" style="writing-mode: vertical-rl; transform: rotate(180deg);">COUNTY</td> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td rowspan="5" style="writing-mode: vertical-rl; transform: rotate(180deg);">OFFICE</td> </tr> <tr> <td style="text-align: center;">T29S</td> <td style="text-align: center;">R3W</td> </tr> <tr> <td style="text-align: center;">S21</td> <td style="text-align: center;">S22</td> </tr> <tr> <td style="text-align: center;">S28</td> <td style="text-align: center;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1959</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <ul style="list-style-type: none"> A decayed fir stump, size indeterminate, bears N. 5° E., 52.8 ft. dist., with no marks visible. A fir, 20 ins. diam., bears S. 16° E., 16.5 ft. dist., with a healed blaze A madrone, 27 ins. diam., bears S. 10° W., 29.0 ft. dist., with no marks visible. A fir, 27 ins. diam., bears N. 13° W., 21.8 ft. dist., with no marks visible. <p>and remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1959, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 03 W., Point Identifier No. 400300, reported by Jelley and Rogers</p> <ul style="list-style-type: none"> A fir, 16 ins. diam., bears S. 57° W., 55.4 ft. dist., with a healed blaze. <p>and remains of a bearing tree mkd. by Jelley and Rogers</p> <ul style="list-style-type: none"> A fir snag, 14 ins. diam., bears N. 76° E., 44.9 ft. dist., with no marks visible on a partially healed blaze. <p>and bearing tree mkd. by person(s) unknown</p> <ul style="list-style-type: none"> A fir, 8 ins. diam., bears S. 41 1/2° E., 10.4 ft. dist., with scribe marks T29S R3W S27 BT visible on an unhealed blaze. <p>and new bearing tree</p> <ul style="list-style-type: none"> A fir, 9 ins. diam., bears N. 47° E., 55.9 ft. dist., mkd. T29S R3W S22 BT. <p>Discontinue posting and blazing.</p> <hr/>	COUNTY	SURVEYORS		OFFICE	T29S	R3W	S21	S22	S28	S27	1959	
COUNTY	SURVEYORS		OFFICE										
	T29S			R3W									
	S21			S22									
	S28			S27									
	1959												

T. 29 S., R. 3 W., Willamette Meridian, Oregon

<p>F E E T</p>	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in mountainous terrain, approximately 8.0 miles northeasterly from the community of Days Creek, Oregon.</p> <p>The elevation ranges from approximately 1240 feet above sea level near the corner of sections 22, 23, 26, and 27 to approximately 3120 feet above sea level near the corner of sections 25, 26, 35, and 36.</p> <p>The survey is drained by Days Creek, which flows southwesterly to the South Fork of the Umpqua River and Coffey Creek, which flows southerly to the South Fork of the Umpqua River.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>Access to the survey was made by graveled roads branching from Days Creek Road.</p>
----------------	--