

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE SOUTH BOUNDARY
AND SUBDIVISIONAL LINES

TOWNSHIP 23 SOUTH, RANGE 4 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated April 17, 2007, approved
April 23, 2007, which provided for the surveys included under
Group No. 2168, and Assignment Instructions dated May 17, 2007.

Survey commenced May 29, 2007

Survey completed November 6, 2007

T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, Township 23 South, Range 4 West, of the Willamette Meridian, Oregon.

The history of surveys that pertain to this survey is as follows:

In 1855-56, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed a portion of the south boundary and subdivisional lines.

In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed a portion of the south boundary and subdivisional lines.

In 1897, Winfield S. Chapman and Carl S. Nicklin, U.S. Deputy Surveyors, surveyed the remainder of the south boundary, retraced a portion of the subdivisional lines, and surveyed the remainder of the subdivisional lines.

In 1957, Lynn M. Roseberry, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, T. 24 S., R. 4 W.

In 1971, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1976, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the south boundary and subdivisional lines.

In 1979, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the north boundary, a portion of the south boundary, subdivisional lines and claim lines, and subdivided section 15, T. 24 S., R. 4 W.

In 1981-82, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 14.

In 1988, Boyd W. Peterson, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, T. 24 S., R. 4 W.

In 2000-01, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the north boundary, and subdivisional lines, and subdivided sections 3, 9, 11, 15, and 33.

In 2006, A. Bert Skeesick, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the east and west boundaries and subdivisional lines and subdivided sections 13 and 19.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 17, 2007, for Group No. 2168, Oregon.

The survey was performed using both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier

T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET

phase GPS receivers. The baselines were computed in and adjusted by least squares analysis. The GPS portion of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of Agriculture, Forest Service.

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS measurements and carried forward by means of sustained angulation using conventional survey techniques. Directions along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.050 meters, 95% confidence level, relative to the National Spatial Reference System stations "DCSO CORS ARP" and "OBEC CONS COOP CORS ARP", is as follows:

The corner of sections 14, 15, 22, and 23.

Latitude: 43° 33' 44.96" N. Longitude: 123° 08' 49.96" W.

The 1/4 section corner of sections 23 and 26.

Latitude: 43° 32' 52.58" N. Longitude: 123° 08' 14.90" W.

The corner of sections 25, 26, 35, and 36.

Latitude: 43° 32' 00.64" N. Longitude: 123° 07' 40.09" W.

The corner of sections 26, 27, 34, and 35.

Latitude: 43° 32' 00.93" N. Longitude: 123° 08' 49.89" W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">(Restoring the 1855-56 survey by Harvey Gordon and Charles T. Gardner, the 1884 survey by William P. Wright, the 1897 survey by Winfield S. Chapman and Carl S. Nicklin, the 1976 and 1979 resurveys by James E. Jelley, and the 1988 resurvey by Boyd W. Peterson)</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 2 ft. base, 18 ins. high, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border: none;"> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;"> SURVEYORS T23S 1/4 S35 R <hr style="width: 50%; margin: 0 auto;"/> 4 S2 W T24S 1963 </td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> </table> <p>from which the remains of an orig. bearing tree</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 82° W., 18.5 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 540100, reported by Jelley in 1976</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 87 1/4° W., 166.3 ft. dist., with no marks visible. (Record, West)</p> <p>and an accessory mkd. by Jelley in 1976</p> <p style="padding-left: 40px;">A conglomerate boulder, 8 x 6 x 4 ft. above ground, bears S. 25 1/4° W., 50.8 ft. dist., with no marks visible. (Record; S. 28 3/4° W., 42.9 ft.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A maple, 15 ins. diam., bears S. 8° W., 9.9 ft. dist., mkd. 1/4 S2 BT.</p> <p style="padding-left: 40px;">A chinquapin, 10 ins. diam., bears N. 70 1/2° W., 44.3 ft. dist., mkd. 1/4 S35 BT.</p> <p>N. 89° 57' 34" W., bet. secs. 2 and 35, on the S. bdy. of the Tp.</p> <p>Descend SW. slope, posting and blazing.</p> <p>2577.67 The closing cor. of secs 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p>	COUNTY	SURVEYORS T23S 1/4 S35 R <hr style="width: 50%; margin: 0 auto;"/> 4 S2 W T24S 1963	OFFICE
COUNTY	SURVEYORS T23S 1/4 S35 R <hr style="width: 50%; margin: 0 auto;"/> 4 S2 W T24S 1963	OFFICE		

Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T23S</td><td>R4W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">C</td><td style="padding: 0 5px;">C</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S34</td><td style="padding: 0 5px;">S35</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; border-right: 1px solid black;"></td></tr> <tr><td>T24S</td><td>R4W</td></tr> <tr><td colspan="2">1976</td></tr> </table> </div> <p>from which bearing trees mkd. by Jelley in 1976</p> <p style="margin-left: 40px;">A fir, 21 ins. diam., bears N. 10° E., 23.4 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 58 1/4° W., 26.4 ft. dist., with a healed blaze.</p> <p>From this cor., an unrecorded point established by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, bears N. 10° 19' 55" W., 7.86 ft. dist., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 5 ins. above ground, with 1 in. diam. brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE affixed to top.</p> <p>Corner is located approximately 15 ft. southerly of the cor. of old 4-strand barbed wire fences extending N. and W.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>S. 89° 41' 31" W., on the S. bdy. of sec. 34.</p> <p>Continue desc. broken SW. slope, posting and blazing.</p> <p>63.48 The cor. of secs. 2 and 3 only, T. 24 S., R. 4 W., on the S. bdy. of the Tp., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px auto;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="3">SURVEYORS</td></tr> <tr><td rowspan="3" style="writing-mode: vertical-rl; transform: rotate(180deg);">COUNTY</td><td style="border-right: 1px solid black; padding: 0 5px;">T24S</td><td style="padding: 0 5px;">R4W</td><td rowspan="3" style="writing-mode: vertical-rl; transform: rotate(180deg);">OFFICE</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S3</td><td style="padding: 0 5px;">S2</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; border-right: 1px solid black;"></td></tr> <tr><td colspan="3">1962</td></tr> </table> </div> <p>from which the remains of the orig. bearing trees</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears S. 33 1/2° E., 54.8 ft. dist., with no marks visible.</p> <p style="margin-left: 40px;">A sawed fir stump, 38 ins. diam., bears S. 81° W., 52.1 ft. dist., with no marks visible.</p> <p style="margin-left: 40px;">A madrone, 22 ins. diam., bears N. 64° W., 23.8 ft. dist., with no marks visible.</p>	T23S	R4W	C	C	S34	S35			T24S	R4W	1976		SURVEYORS			COUNTY	T24S	R4W	OFFICE	S3	S2			1962		
T23S	R4W																										
C	C																										
S34	S35																										
T24S	R4W																										
1976																											
SURVEYORS																											
COUNTY	T24S	R4W	OFFICE																								
	S3	S2																									
1962																											

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	<p>and bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 479100, reported by Jelley in 1976, not reported by Peterson</p> <p style="padding-left: 40px;">A fir stump, 11 ins. diam., bears S. 44 1/4° W., 42.6 ft. dist., with no marks visible.</p> <p>and bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1962, reported by Peterson</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 67° E., 37.6 ft. dist., with a healed double blaze.</p> <p>and bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, reported by Peterson</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 49 1/2° W., 92.4 ft. dist., with a healed blaze. (Record, 87.8 ft.)</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 36 1/4° E., 27.9 ft. dist., mkd. T24S R4W S2 BT.</p> <p>From this cor., a point established by Wilford N. Haines, Oregon Professional Land Surveyor (PLS) No. 239, bears N. 3° 11' 35" W., 4.80 ft. dist. (Record; N. 2° 30' 00" W., 4.62 ft.), monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 10 ins. above ground, with 1 in. diam. brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE affixed to top.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 41' 56" W., beginning new measurement.</p> <p>Continue desc. broken SW. slope, posting and blazing.</p>									
2601.87	<p>The 1/4 sec. cor. of sec. 34 only on the S. bdy. of the Tp., remonumented by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 440100, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <table style="margin: 10px auto; border-collapse: collapse;"> <tr> <td colspan="3" style="text-align: center;">SURVEYORS</td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;">T23S R4W S1/4 S34</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center; border-top: 1px solid black;">T24S 1963</td> <td></td> </tr> </table> <p>from which the remains of an orig. bearing tree</p>	SURVEYORS			COUNTY	T23S R4W S1/4 S34	OFFICE		T24S 1963	
SURVEYORS										
COUNTY	T23S R4W S1/4 S34	OFFICE								
	T24S 1963									

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 26 ins. diam., bears N. 0 1/4° E., 11.9 ft. dist., with a healed double blaze. (Record, N. 5° W.)</p> <p>and remains of a bearing tree mkd. by Nicklin and Chapman</p> <p>A sawed, tin-capped fir stump, 32 ins. diam., bears S. 42° W., 42.2 ft. dist., with no marks visible.</p> <p>and remains of a bearing tree mkd. by Godfrey</p> <p>A cedar, 41 ins. diam., bears N. 81° E., 20.1 ft. dist., with a healed double blaze.</p> <p>and new bearing tree</p> <p>A fir, 59 ins. diam., bears N. 51 1/2° W., 104.4 ft. dist., mkd. 1/4 S34 BT.</p> <hr/> <p>N. 89° 45' 35" W., beginning new measurement.</p> <p>Continue desc. broken SW. slope, posting and blazing.</p>
48.75	<p>Point for the 1/4 sec. cor. of sec. 3 only, T. 24 S., R. 4 W., on the S. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <u>T23S</u> 1/4 S 3 T24S R4W 2007 </p> <p>from which</p> <p>A fir, 6 ins. diam., bears S. 47 1/4° E., 11.9 ft. dist., mkd. 1/4 S3 BT.</p> <p>A fir, 4 ins. diam., bears S. 43° W., 4.3 ft. dist., mkd. X BT.</p>
1251.51	<p>The W 1/16 sec. cor. of sec. 34 only on the S. bdy. of the Tp., established by David L. Brown, Oregon PLS No. 2609, in 1995, recorded in the Douglas County Surveyors Office, Map File No. 121-69, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, flush with the ground, with yellow plastic cap mkd. BRANCH ENG LS 2609, from which the remaining bearing tree mkd. by Brown</p> <p>A fir, 17 ins. diam., bears N. 79 1/4° W., 215.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;"><u>W 1/16 S34</u> 2007</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 17 ins. diam., bears N. 0 1/2° W., 329.5 ft. dist., mkd. W 1/16 S34 BT.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 48' 08" W., beginning new measurement.</p> <p>Continue desc. broken SW. slope and asc. broken NE. slope, posting and blazing.</p>
1251.32	<p>The cor. of secs. 33 and 34 only on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R4W <u>S33 S34</u> S3 T24S R4W 1976</p> <p>from which the remains of an orig. bearing tree</p> <p style="padding-left: 40px;">A maple, 31 ins. diam., bears S. 67° W., 38.3 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1959, reported by Jelley in 1976</p> <p style="padding-left: 40px;">A hemlock, 19 ins. diam., bears N. 29 1/2° W., 5.3 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 400100, reported by Jelley in 1976</p> <p style="padding-left: 40px;">A hemlock, 26 ins. diam., bears N. 39° E., 47.9 ft. dist., with a healed blaze.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 89° 59' 32" W., on the S. bdy. of sec. 33.</p> <p>Ascend broken SE. slope, posting and blazing.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET																			
196.53	<p>True point for the closing cor. of secs. 3 and 4, T. 24 S., R. 4 W., described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 24 S., R. 4 W., surveyed concurrently under this same group.</p> <p>Continue asc. broken SE. slope and desc. broken N. slope, posting and blazing.</p>																		
2687.47	<p>The 1/4 sec. cor. of sec. 33 only on the S. bdy. of the Tp., monumented with a brass tablet, firmly set, flush with rock ledge, mkd.</p> <div style="text-align: center;"> <p>T23S R4W 1/4 S33</p> <hr style="width: 50px; margin: 0 auto;"/> <p>T24S R4W 1976</p> </div> <p>from which the remaining bearing tree mkd. by Jelley in 1976</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 7° W., 49.4 ft. dist., with a healed blaze. (Record; N. 11 3/4° W., 50.6 ft.)</p> <p>and a bearing tree not of record</p> <p style="padding-left: 40px;">A maple, 21 ins. diam., bears N. 87 3/4° E., 46.1 ft. dist., with a healed blaze.</p> <hr style="width: 200px; margin: 20px auto;"/> <p>N. 89° 49' 19" W., beginning new measurement.</p> <p>Ascend broken NE. slope, posting and blazing.</p>																		
2682.70	<p>The cor. of secs. 32 and 33 only on the S. bdy. of the Tp., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY</p> <table style="margin: 0 auto;"> <tr> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td style="text-align: right;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">T23S</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S32 S33</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><hr style="width: 50px; margin: 0 auto;"/></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R4W</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1963</td> <td></td> </tr> </table> <p></p> </div> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 44 ins. diam., bears N. 70° E., 27.7 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 55 ins. diam., bears S. 86° E., 29.7 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 48 ins. diam., bears N. 43° W., 25.1 ft. dist., with no marks visible.</p>	SURVEYORS		OFFICE		T23S			S32 S33			<hr style="width: 50px; margin: 0 auto;"/>			R4W			1963	
SURVEYORS		OFFICE																	
	T23S																		
	S32 S33																		
	<hr style="width: 50px; margin: 0 auto;"/>																		
	R4W																		
	1963																		

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET

and the remains of bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 300100, reported by Jelley in 1976

A cedar snag, 19 ins. diam., bears S. 75° E., 37.3 ft. dist., with no marks visible.

A fir, 52 ins. diam., bears N. 75 3/4° W., 65.3 ft. dist., with a healed double blaze.

and bearing tree mkd. by Jelley in 1976


A maple, 26 ins. diam., bears N. 77° E., 102.3 ft. dist., with a healed blaze.

Discontinue posting and blazing.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the 1855-56 survey by Harvey Gordon and Charles T. Gardner, the 1884 survey by William P. Wright, the 1897 survey by Winfield S. Chapman and Carl S. Nicklin, and the 1976 and 1981-82 resurveys by James E. Jelley)

From the cor. of secs 1, 2, 35, and 36, on the S. bdy. of the Tp., perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, and perpetuated by Glen McChesney for Weyerhaeuser Timber Co., in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 600100, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, in a mound of stone, 3 ft. base, 12 ins. high, with brass cap mkd.



from which the remains of the orig. bearing trees

A decayed chinquapin stump, size indeterminate, bears N. 8° E., 30.4 ft. dist., with no marks visible.

A decayed fir snag, size indeterminate, bears S. 58° E., 48.2 ft. dist., with fragmentary scribe marks visible on an opened blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

F E E T	<p>A fir, 35 ins. diam., bears S. 28° W., 48.2 ft. dist., with a healed blaze.</p> <p>A cedar, 51 ins. diam., bears N. 83° W., 38.9 ft. dist., with no marks visible on an opened blaze.</p> <p>and remains of bearing trees mkd. by Roseberry</p> <p>A sawed fir stump, 21 ins. diam., bears N. 46° E., 31.0 ft. dist., with a healed blaze.</p> <p>A cedar, 18 ins. diam., bears S. 48 1/2° E., 49.5 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Godfrey</p> <p>A fir, 26 ins. diam., bears S. 10 1/4° E., 17.7 ft. dist., with a healed blaze.</p> <p>A cedar, 25 ins. diam., bears N. 31 3/4° W., 43.7 ft. dist., with a healed blaze.</p> <p>and remains of a bearing tree mkd. by McChesney</p> <p>A sawed, decayed fir stump, 39 ins. diam., bears N. 1° W., 56.9 ft. dist., with no marks visible.</p> <p>and new bearing tree</p> <p>A cedar, 6 ins. diam., bears N. 33 1/2° E., 7.4 ft. dist., mkd. X BT.</p> <p>N. 0° 20' 01" W., bet. secs. 35 and 36.</p> <p>Ascend broken SW. slope, posting and blazing.</p>						
1990	Graveled road, 14 ft. wide, bears S. 80° E. and N. 80° W.						
2540	Spur, slopes S. 70° W.; desc. broken NW. slope.						
2662.15	<p>The 1/4 sec. cor. of secs. 35 and 36, perpetuated by Vernon "Ray" Tracy, Douglas County Surveyors Office, in 1965 and 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 600140, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 9 ins. above ground, (alongside of which is an iron pipe, 3/4 in. diam., firmly set, projecting 6 ins. above ground), with brass cap mkd.</p>						
<table style="margin: auto; border: none;"> <tr> <td colspan="3" style="text-align: center;">SURVEYORS</td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">C O U N T Y</td> <td style="text-align: center;"> T23S S35 S36 1/4 R4W 1968 </td> <td style="text-align: center; vertical-align: middle;">O F F I C E</td> </tr> </table>		SURVEYORS			C O U N T Y	T23S S35 S36 1/4 R4W 1968	O F F I C E
SURVEYORS							
C O U N T Y	T23S S35 S36 1/4 R4W 1968	O F F I C E					

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of the orig. bearing trees</p> <p>A fir snag, 52 ins. diam., bears S. 34° E., 5.9 ft. dist., with no marks visible on an opened blaze.</p> <p>A fir snag, 38 ins. diam., bears N. 35° W., 5.9 ft. dist., with fragmentary scribe marks visible on an opened blaze.</p> <p>and the remains of a bearing tree mkd. by Tracy</p> <p>A sawed fir stump, 15 ins. diam., bears N. 89 1/4° W., 31.8 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A chinquapin, 7 ins. diam., bears N. 32 1/2° E., 7.7 ft. dist., mkd. 1/4 S36 BT.</p> <p>A hemlock, 17 ins. diam., bears S. 37° W., 12.6 ft. dist., mkd. 1/4 S35 BT.</p> <hr/> <p>N. 0° 27' 35" W., beginning new measurement.</p> <p>Continue desc. broken NW. slope, posting and blazing.</p>
2657.36	<p>The cor. of secs 25, 26, 35, and 36, perpetuated by Wilford N. Haines, Oregon PLS No. 239, in about 1960, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 600200, accepted as a careful and faithful perpetuation of the orig. cor. position, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 8 ins. above ground, with 1 in. diam. brass disk mkd. WILFORD N HAINES 239 affixed to top, from which the remains of the orig. bearing trees</p> <p>A decayed fir snag, size indeterminate, bears S. 51 3/4° E., 82.6 ft. dist., with no marks visible. (Record; S. 49 1/4° E., 73.9 ft.)</p> <p>A decayed fir stump, size indeterminate, bears S. 72 1/2° W., 107.8 ft. dist., with no marks visible. (Record; S. 75° W., 113.5 ft.)</p> <p>A decayed fir stump, 34 ins. diam., bears N. 2 1/4° W., 231.3 ft. dist., with no marks visible. (Record; N. 5° W., 221.1 ft.)</p> <p>and bearing trees mkd. by person(s) unknown, reported by Haines</p> <p>A fir stump, 22 ins. diam., bears N. 67 3/4° E., 22.5 ft. dist., with a healed blaze.</p> <p>A sawed madrone stump, 19 ins. diam., bears S. 37 1/4° E., 62.7 ft. dist., with no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

<p>F E E T</p>	<p>A cedar, 53 ins. diam., bears S. 72° W., 94.2 ft. dist., with a healed blaze.</p> <p>A fir, 35 ins. diam., bears N. 9 3/4° W., 61.8 ft. dist., with a healed blaze</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the existing "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T23S</td> <td>R4W</td> </tr> <tr> <td style="border-right: 1px solid black;">S26</td> <td>S25</td> </tr> <tr> <td style="border-right: 1px solid black;">S35</td> <td>S36</td> </tr> <tr> <td colspan="2">2007</td> </tr> </table> </div> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established as the cor. of secs. 25, 26, 35, and 36 by Ken W. Hoffine, Oregon PLS No. 2291, in 1990, recorded in the Douglas County Surveyors Office, Map File Nos. 109-56 and 111-30, bears S. 88 1/4° E., 8.45 ft. dist., determined at record bearing and dist. from bearing trees mkd. by Hoffine</p> <p>A sawed cedar stump, 30 ins. diam., bears S. 62° E., 61.3 ft. dist., with a healed blaze.</p> <p>A hemlock, 15 ins. diam., bears S. 65° W., 52.3 ft. dist., with a healed blaze.</p> <p>A hemlock, 15 ins. diam., bears N. 64° W., 46.0 ft. dist., with a healed blaze.</p> <p>There is no remaining evidence of Hoffine's monument of record and this point is not accepted as the cor.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs 23, 24, 25, and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T23S</td> <td>R4W</td> </tr> <tr> <td style="border-right: 1px solid black;">S23</td> <td>S24</td> </tr> <tr> <td style="border-right: 1px solid black;">S26</td> <td>S25</td> </tr> <tr> <td colspan="2">1981</td> </tr> </table> </div> <p>from which the remains of the orig. bearing trees</p> <p>A cedar, 37 ins. diam., bears N. 22° E., 31.0 ft. dist., with a healed blaze.</p>	T23S	R4W	S26	S25	S35	S36	2007		T23S	R4W	S23	S24	S26	S25	1981	
T23S	R4W																
S26	S25																
S35	S36																
2007																	
T23S	R4W																
S23	S24																
S26	S25																
1981																	

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed fir stump, size indeterminate, bears S. 15° W., 38.4 ft. dist., with no marks visible. (Record, 35.6 ft.)</p> <p>A sawed, decayed fir stump, 72 ins. diam., bears N. 25° W., 7.3 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Wilford N. Haines, Oregon PLS No. 239, date unknown, Oregon PLS No. 239, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 600300, reported by Jelley in 1981-82</p> <p>A cedar, 41 ins. diam., bears S. 27° E., 11.2 ft. dist., with a healed blaze.</p> <p>A cedar, 28 ins. diam., bears S. 44° W., 19.8 ft. dist., with a healed blaze.</p> <p>A cedar snag, 28 ins. diam., bears N. 70° W., 49.5 ft. dist., with no marks visible.</p> <p>and new bearing tree</p> <p>A fir, 11 ins. diam., bears N. 80 3/4° W., 32.3 ft. dist., mkd. T23S R4W S23 BT.</p> <p>N. 1° 04' 07" W., bet. secs. 23 and 24.</p> <p>Ascend broken SW. slope, posting and blazing.</p>
749	Graveled road, 10 ft. wide, bears N. 52° E. and S. 52° W.
827	Graveled road, 10 ft. wide, bears S. 50° E. and N. 50° W.
2631.71	<p>The 1/4 sec. cor. of secs. 23 and 24, perpetuated by Wilford N. Haines, Oregon PLS No. 239, date unknown, perpetuated by Vernon "Ray" Tracy, Douglas County Surveyors Office, in 1965, perpetuated by Donald L. Branch, Oregon PLS No. 1137, in 1987, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 600340, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 9 ins. above ground, with 1 in. diam. brass disk mkd. WILFORD N HAINES 239 DRAIN ORE affixed to top, from which the remains of the orig. bearing trees</p> <p>A sawed decayed fir stump, 52 ins. diam., bears N. 60° E., 14.5 ft. dist., with no marks visible.</p> <p>A tin-capped, decayed fir stump, 34 ins. diam., bears N. 88 3/4° W., 46.2 ft. dist., with no marks visible. (Record, S. 87° W.)</p> <p>and bearing trees mkd. by Tracy</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

<p>F E E T</p>	<p>A hemlock, 20 ins. diam., bears N. 77 1/4° E., 19.7 ft. dist., with a healed blaze.</p> <p>A yew, 10 ins. diam., bears N. 21 3/4° W., 34.2 ft. dist., with a healed blaze.</p> <p>and remains of a bearing tree mkd. by Branch</p> <p>A hemlock snag, 9 ins. diam., bears N. 87 3/4° E., 11.0 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the existing "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R4W 1/4 S23 S24 2007</p> </div> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2° 12' 14" E., beginning new measurement.</p> <p>Continue asc. broken SW. slope, posting and blazing.</p> <p>581 Spur, slopes N. 45° W.; desc. broken NW. slope.</p> <p>1332.43 The N 1/16 sec. cor. of secs. 23 and 24, established by Ken W. Hoffine, Oregon PLS No. 2291, in 1994, recorded in the Douglas County Surveyors Office, Map File No. M120-66, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>ROCK N 1/16 LONE S23 S24 TIMBER 1994 PLS 2291</p> </div> <p>from which the remains of bearing trees incorrectly mkd. by Hoffine</p> <p>A fir stump, 16 ins. diam., bears N. 70 1/2° E., 17.1 ft. dist., with scribe marks 1/4 S24 BT visible on an open blaze.</p> <p>A fir stump, 36 ins. diam., bears N. 60° W., 40.2 ft. dist., with scribe marks 1/4 S23 BT visible on an open blaze.</p>
----------------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET											
	and new bearing trees										
	A fir, 7 ins. diam., bears S. 21 1/2° E., 23.1 ft. dist., mkd. N 1/16 S24 BT.										
	A fir, 7 ins. diam., bears S. 63 3/4° W., 25.9 ft. dist., mkd. N 1/16 S23 BT.										

	N. 2° 11' 50" E., beginning new measurement.										
	Continue desc. broken NW. slope, posting and blazing.										
1194	Creek, 2 ft. wide, course N. 85° W.; asc. SW. slope.										
1288	Spur, slopes N. 70° W.; desc. NW. slope.										
1332.78	The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T23S R4W</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1971</td> </tr> </table>	T23S R4W		S14	S13	-----		S23	S24	1971	
T23S R4W											
S14	S13										

S23	S24										
1971											
	from which the remains of bearing trees mkd. by Wilford N. Haines, Registered PLS No. 239, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 600400, reported by Skeesick and Browning										
	A tin-capped, sawed fir stump, 22 ins. diam., bears N. 9 1/2° E., 38.0 ft. dist., with scribe marks T23S R4W1 visible on the bark.										
	A sawed and decayed fir stump, 24 ins. diam., bears S. 17 1/4° E., 28.1 ft. dist., with no marks visible.										
	A tin-capped, sawed fir stump, 23 ins. diam., bears S. 55° W., 63.0 ft. dist., with no marks visible.										
	A tin-capped, sawed and decayed fir stump, 13 ins. diam., bears N. 74 1/4° W., 8.6 ft. dist., with no marks visible.										
	and bearing trees mkd. by Skeesick and Browning										
	A fir, 7 ins. diam., bears N. 12 3/4° E., 12.6 ft. dist., with scribe marks T23S R4W S13 BT visible on a partially healed blaze.										
	A fir, 10 ins. diam., bears S. 62 3/4° E., 5.8 ft. dist., with scribe marks T23S R4W S24 BT on a partially healed blaze.										

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET									
	<p>A fir, 6 ins. diam., bears S. 33 1/4° W., 29.9 ft. dist., with scribe marks T23S R4W S23 BT visible on a partially healed blaze.</p> <p>A fir, 10 ins. diam., bears N. 23° W., 7.4 ft. dist., with scribe marks T23S R4W S14 BT visible on a partially healed blaze.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T23S</td> <td style="border-left: 1px solid black; padding: 0 5px;">R4W</td> </tr> <tr> <td style="padding: 0 5px;">S27</td> <td style="border-left: 1px solid black; padding: 0 5px;">S26</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 0 5px;">S34 S35</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1976</td> </tr> </table> <p>from which the remains of the bearing trees mkd. by Jelley in 1976</p> <p>A roothole bears N. 57 3/4° E., 8.9 ft. dist., with fallen fir snag, 12 ins. diam., lying alongside, with a healed blaze.</p> <p>A fir, 13 ins. diam., bears S. 76 1/2° E., 39.6 ft. dist., with a healed blaze. (Record, S. 77 1/4° E.)</p> <p>A fir snag, 7 ins. diam., bears S. 34 1/4° W., 18.8 ft. dist., with a healed blaze.</p> <p>A fir snag, 7 ins. diam., bears N. 71° W., 5.0 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 16 ins. diam., bears N. 49 1/4° E., 19.8 ft. dist., mkd. T23S R4W S26 BT.</p> <p>A fir, 13 ins. diam., bears N. 30° W., 34.2 ft. dist., mkd. T23S R4W S27 BT.</p> <p>S. 0° 26' 54" W., bet. secs. 34 and 35.</p> <p>Ascend broken NW. slope, posting and blazing.</p>	T23S	R4W	S27	S26	S34 S35		1976	
T23S	R4W								
S27	S26								
S34 S35									
1976									
590	Spur, slopes S. 75° W.; desc. broken SW. slope.								
1895	Shingle Mill Creek, 5 ft. wide, course S. 60° W.; asc. broken NW. slope.								
2375	Spur, slopes S. 80° W.; desc. broken SW. slope.								
2540	Ravine, drains S. 72° W.; asc. broken NW. slope.								
2576.16	The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.								

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">1/4 S34 S35 T23S R4W 1976</p>
	<p>from which the remains of an orig. bearing tree</p>
	<p>A decayed, sawed fir stump, 37 ins. diam., bears N. 24° E., 6.6 ft. dist., with no marks visible.</p>
	<p>and bearing trees mkd. by Jelley in 1976</p>
	<p>A fir, 13 ins. diam., bears S. 73 1/2° E., 8.6 ft. dist., with a healed blaze.</p>
	<p>A fir, 13 ins. diam., bears S. 36 1/2° W., 6.3 ft. dist., with a healed blaze.</p>
	<p>Corner is located in a wire fence, extends N. and S.</p>
	<p style="text-align: center;">_____</p> <p>S. 0° 25' 01" W., beginning new measurement.</p>
	<p>Continue asc. broken NW. slope, posting and blazing.</p>
85	<p>Spur, slopes S. 60° W.; desc. broken SW. slope.</p>
580	<p>Creek, 3 ft. wide, course N. 50° W.; asc. broken N. slope.</p>
985	<p>Spur, slopes N. 70° W.; desc. broken SW. slope.</p>
1418.13	<p>The angle point of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">AP T23S R4W S34 S35 1976</p>
	<p>from which the remains of the orig. bearing trees</p>
	<p>A roothole bears S. 70° E., 11.9 ft. dist., with no remaining evidence of the trunk.</p>
	<p>A decayed cedar stump, 20 ins. diam., bears N. 87° W., 26.7 ft. dist., with axe marks visible.</p>
	<p>and bearing trees mkd. by Jelley in 1976</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 24 ins. diam., bears N. 43 1/4° E., 35.3 ft. dist., with a healed blaze.</p> <p>A fir, 15 ins. diam., bears N. 32 1/4° W., 9.9 ft. dist., with a healed blaze.</p> <p>Corner is located 6 ft. W. of a 4 strand barbed-wire fence, extends N. and S.</p> <hr/> <p>S. 0° 16' 27" E., beginning new measurement.</p> <p>Continue desc. broken SW. slope, posting and blazing.</p>
25	Creek, 3 ft. wide, course N. 65° W.; asc. broken NE. slope.
910	Ridge, bears S. 35° E. and N. 45° W.; desc. broken NW. slope.
1065	Ravine, drains West; asc. broken N. slope.
1250	Spur, slopes S. 75° W.; desc. broken S. slope.
1381.09	The closing cor. of secs. 34 and 35 only, on the S. bdy. of the Tp.
	<hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89° 43' 16" W., bet. secs. 23 and 26.</p> <p>Descend broken SW. slope, posting and blazing.</p>
267	Graveled road, 10 ft. wide, bears S. 35° E. and N. 35° W.
2587.94	The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground (alongside of which is a "T" shaped iron rod, 1 in. diam.), with aluminum cap mkd.
	<p>T23S R4W S23 1/4— S26 1982</p>
	<p>from which the remains of bearing trees mkd. by Jelley in 1981-82</p> <p>A fir, 18 ins. diam., bears N. 34° E., 6.6 ft. dist., with a healed blaze.</p> <p>A roothole bears S. 60° W., 9.9 ft. dist., with fallen fir snag, 15 ins. diam., lying alongside, with a healed blaze.</p> <p>and new bearing tree</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 6 ins. diam., bears S. 36° E., 40.5 ft. dist., mkd. 1/4 S26 BT.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <p style="text-align: center;">S14 1/4 ——— S23 T23S R4W 1976</p> <p>from which the remains of bearing trees mkd. by Jelley in 1981-82</p> <p>A fir, 11 ins. diam., bears N. 67 1/2° E., 46.2 ft. dist., with a healed blaze.</p> <p>A decayed fir stump, size indeterminate, bears S. 53 1/4° E., 38.3 ft. dist., with no marks visible.</p> <p>and new bearing tree</p> <p>A hemlock, 6 ins. diam., bears S. 2 1/2° W., 16.3 ft. dist., mkd. 1/4 S23 BT.</p> <p>N. 89° 47' 21" W., bet. secs. 14 and 23.</p> <p>Ascend broken NE. slope, posting and blazing.</p>
1090	<p>Spur, slopes N. 60° W.; desc broken SW. slope.</p>
2609.76	<p>The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 1 1/2 ins. diam., firmly set, bent over, projecting 8 ins. above ground (alongside of which is a "T" shaped iron rod, 1 in. diam.), with brass cap mkd. COUNTY SURVEYORS OFFICE T23S S15 S14 S22 S23 R4W 1963, from which the remaining bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 500400, reported by Moore and Browning</p> <p>A fir, 28 ins. diam., bears N. 54 1/2° E., 21.8 ft. dist., with a healed blaze.</p> <p>A fir, 13 ins. diam., bears S. 75° W., 5.6 ft. dist., with a healed blaze.</p> <p>A fir, 12 ins. diam., bears N. 49° W., 12.5 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by Moore and Browning</p> <p>A fir, 16 ins. diam., bears S. 50° E., 38.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET									
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T23S</td> <td>R4W</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2">2007</td> </tr> </table> </div> <p>Bury a magnet in a white plastic case at the base of the stainless steel post. Bury the existing iron post alongside the stainless steel post.</p> <hr/>	T23S	R4W	S15	S14	S22	S23	2007	
T23S	R4W								
S15	S14								
S22	S23								
2007									
1321.44	<p>From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp.</p> <p>N. 0° 35' 59" W., bet. secs. 33 and 34.</p> <p>Descend broken E. slope and asc. broken SE. slope, posting and blazing.</p> <p>The S 1/16 sec. cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">S 1/16</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2">1976</td> </tr> </table> </div> <p>from which bearing trees mkd. by Jelley in 1976</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 72° E., 26.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 84° W., 15.8 ft. dist., with a healed blaze.</p> <hr/>	S 1/16		S33	S34	1976			
S 1/16									
S33	S34								
1976									
1316.41	<p>From the cor. of secs. 32 and 33 only, on the S. bdy. of the Tp.</p> <p>N. 0° 09' 03" W., bet. secs. 32 and 33.</p> <p>Descend broken NW. slope, posting and blazing.</p> <p>The S 1/16 sec. cor. of secs. 32 and 33, established by David A. Edwards, Oregon PLS No. 2339, in 2007, recorded in the Douglas County Surveyors Office, Map File No. M152-55, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>ROSEBURG RESOURCES</p> <p>S 1/16</p> <p>S32 S33</p> <p>LS2339</p> <p>2007</p> <p>COMPANY</p>
1316.26	<p>from which bearing trees mkd. by Edwards</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 75 1/4° E., 24.7 ft. dist., with scribe marks S1/16 S33 BT visible on an open blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 4° E., 20.4 ft. dist., with scribe marks S1/16 S33 BT visible on an open blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 08' 16" W., beginning new measurement.</p> <p>Continue desc. broken NW. slope, posting and blazing.</p> <p>The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4</p> <p style="text-align: center;">S32 S33</p> <p style="text-align: center;">T23S R4W</p> <p style="text-align: center;">1976</p> <p>from which bearing trees mkd. by Jelley in 1976</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 28 1/2° E., 10.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 73 1/4° W., 15.0 ft. dist., with a healed blaze.</p> <p>Corner is located 6.5 ft. W. of a woven wire fence, extends N. and S.</p> <hr style="width: 60%; margin: 10px auto;"/>

T. 23 S., R. 4 W., Willamette Meridian, Oregon

F E E T

GENERAL DESCRIPTION

The lands included in the foregoing survey are located in mountainous terrain of Douglas County, approximately 8 miles southeasterly of the community of Yoncalla, Oregon.

The elevation ranges from approximately 2600 feet above sea level near the 1/4 section corner of sections 35 and 36 to approximately 1000 feet above sea level near the S 1/16 section corner of sections 33 and 34.

The area is drained by Shingle Mill Creek and numerous unnamed creeks which flow westerly to Elk Creek.

Timber consists of fir, cedar, maple, and madrone. Undergrowth consists of salal, vine maple, poison oak, Oregon Grape, and fern.

The soil is generally composed of rocky clay.

Access to the survey was made by graveled roads branching from Romy Howard Road.