

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
A PORTION OF THE SOUTH BOUNDARY  
AND SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF SECTION 33  
**TOWNSHIP 20 SOUTH, RANGE 6 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***A. Bert Skeesick, Cadastral Surveyor***

***Robert H. Browning, Surveying Technician***

Under Special Instructions dated March 23, 2009, approved March 27, 2009,  
which provided for the surveys included under Group No. 2268,  
and Assignment Instructions dated March 23, 2009.

***Survey commenced March 24, 2009***

***Survey completed July 7, 2009***

**T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and the subdivision of section 33, Township 20 South, Range 6 West, of the Willamette Meridian, Oregon.

The history of federal surveys pertaining to this survey is as follows:

In 1872, John H. McClung, U.S. Deputy Surveyor, surveyed the north, south, and west boundaries, and subdivisional lines.

In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, T. 21 S., R. 6 W.

In 1950, Marvin J. Lytle, Cadastral Engineer, resurveyed a portion of the north boundary and subdivisional lines.

In 1962, William W. Glenn, Cadastral Surveyor, resurveyed a portion of the north and east boundaries and subdivisional lines, subdivided section 1, and remonumented certain corner points.

In 1984-85, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the south boundary, T. 20 S., R. 6 W., and resurveyed a portion of the subdivisional lines, T. 21 S., R. 6 W.

In 1989, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1995, Daniel N. Patterson and Craig L. Wanless, Cadastral Surveyors, correctively resurveyed a portion of the subdivisional lines.

In 2003, A. Bert Skeesick, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 35.

The following plats filed in the Douglas County Surveyor's Office were evaluated, and a portion of them are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) number, and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Type</u>	<u>File Number</u>
1956	Wilford N. Haines PLS 239	Survey	M3-23
1961	Wilford N. Haines PLS 239	Survey	M21-75
1966	Wilford N. Haines PLS 239	Survey	M32-34
1970	Wilford N. Haines PLS 239	Survey	M38-79
1979	Bruce A. Shaner PLS 430	Roll Map	RM3-53
1983	Lloyd D. Smith PLS 1101	Survey	M95-49
1987	Dale E. Marx PLS 2196	Survey	M105-45
1991	Donald L. Peel PLS 752	Survey	M113-45
1994	Steven P. Ness PLS 811	Survey	M121-24 A&B
1996	Richard P. Hankins PLS 687	Survey	M123-45
1997	Leslie D. Roberts PLS 1039	Survey	M127-70
1998	Harvey M. Christensen PLS 2603	Survey	M130-35

## T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Type</u>	<u>File Number</u>
1999	David A. Edwards PLS 2339	Survey	M131-70
2000	Leslie D. Roberts PLS 1039	Survey	M134-6
2002	Robert B. Ward PLS 1091	Survey	M139-52
2006	Ronald L. Rice PLS 54633	Survey	M150-43

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 23, 2009, for Group No. 2268, Oregon.

The survey was performed using a combination of Global Positioning System (GPS) satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The directions of the lines are based on the true meridian as determined by a combination of direct solar observations and GPS measurements carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment.

Static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.10 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The unadjusted data assured a closure not exceeding 1:4000 in error. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position (NAD 1983 (CORS)) of the corner of sections 33 and 34 only, on the south boundary of the township, as determined by direct occupation, utilizing dual frequency, carrier phase GPS receivers, relative to the National Spatial Reference System (NSRS) Continuously Operating Reference Stations (CORS) "DODSON BUTTE CORS ARP" and "CAPE BLANCO CORS ARP", is as follows:

Latitude: 43° 46' 49.315" N. Longitude: 123° 24' 34.070" W.

The geographic position (NAD 1983 (CORS)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, relative to "DODSON BUTTE CORS ARP" and "CAPE BLANCO CORS ARP", are as follows:

**T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET

The corner of sections 26, 27, 34, and 35

Latitude: 43° 47' 41.40" N. Longitude: 123° 23' 21.49" W.

The corner of sections 28, 29, 32, and 33

Latitude: 43° 47' 42.51" N. Longitude: 123° 25' 46.41" W.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

---

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

---

Restoring the 1872 survey by John H. McClung,  
and the 1984-85 resurvey by Wayne L. Rogers

---

Beginning at the closing cor. of secs. 3 and 4, T. 21 S., R. 6 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

```

T 20 S R 6 W
  S 34
-----
  S 4 | S 3
      C C
T 21 S R 6 W
  1984
    
```

from which the remaining bearing tree mkd. by Rogers

A fir, 27 ins. diam., bears S. 41 1/2° W., 38.3 ft. dist., with a healed blaze.

and new bearing tree

A fir, 6 ins. diam., bears S. 16° E., 24.6 ft. dist., mkd. X BT.

From this cor., the original closing cor. of secs. 3 and 4, T. 21 S., R. 6 W., perpetuated by Wilford N. Haines, Oregon PLS No. 239, in 1956, bears N. 0° 34' 00" W., 17.49 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, flush with the ground, with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree

A sawed fir stump, 30 ins. diam., bears S. 22° W., 54.8 ft. dist., with no marks visible.

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>and a bearing tree mkd. by Haines, reported by Rogers</p> <p style="padding-left: 40px;">A fir, 56 ins. diam., bears S. 60° E., 15.2 ft. dist., with a healed blaze.</p> <p>N. 88° 55' 43" W., on the S. bdy. of sec. 34.</p>				
419.59	<p>The cor. of secs. 33 and 34 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 20 S R 6 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; padding: 0 10px;">S</td> <td style="text-align: center; padding: 0 10px;">S</td> </tr> <tr> <td style="text-align: center; padding: 0 10px;">33</td> <td style="text-align: center; padding: 0 10px;">34</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 49 ins. diam., bears N. 71° E., 21.1 ft. dist., with scribe marks BT visible on an opened blaze.</p> <p>and a bearing tree mkd. by N.E. Richardson, Deputy County Surveyor, in 1948, filed in the Douglas County Surveyor's Office, C.S. File No. 39/176, reported by Rogers</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears N. 24° W., 35.0 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 78 3/4° E., 91.7 ft. dist., mkd. T20S R6W S34 BT.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 89° 19' 16" W., on the S. bdy. of sec. 33.</p>	S	S	33	34
S	S				
33	34				
1289.97	<p>From this point, a point established by Ted C. Baker, Oregon PLS No. 2488, in 2006, filed in the Douglas County Surveyor's Office, Map File No. M151-48, not utilized during the course of this survey, bears North, 0.19 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1/2 in. above the ground, with yellow plastic cap, mkd. ROBERTS SURV INC.</p>				
2190.32	<p>The 1/4 sec. cor. of sec. 4 only, T. 21 S., R. 6 W., established by Wilford N. Haines, Oregon PLS No. 239, in 1956, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above the ground (alongside of which is a galvanized steel pipe, 3/4 in. diam., firmly set, projecting 18 ins. above the ground, of unknown origin), with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY DRAIN ORE, from which bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 39 ins. diam., bears N. 78° E., 13.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 57° W., 17.0 ft. dist., with a healed blaze.</p>				

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

<p>FEET</p>	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the "T" shaped iron rod and the galvanized steel pipe, with brass cap mkd.</p> <p style="text-align: center;"> <u>          T 20 S          </u>              1/4 S 4              T 21 S R 6 W              2009         </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="text-align: center;">_____</p> <p>N. 89° 09' 09" W., beginning new measurement.</p> <p>490.89 The 1/4 sec. cor. of sec. 33 only, reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1956, by proportionate measurement and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above the ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY DRAIN ORE laying alongside, from which bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N. 3 1/2° E., 25.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 53 3/4° E., 45.0 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">             T 20 S R 6 W  <u>          1/4 S 33          </u>              T 21 S              2009         </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="text-align: center;">_____</p> <p>N. 89° 18' 49" W., beginning new measurement.</p> <p>2118.25 The closing cor. of secs. 4 and 5, T. 21 S., R. 6 W., reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1956, by proportionate measurement and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, buried 2 ins. below the surface of the ground (alongside of which is a copper pipe, 3/4 in. diam., loosely set, projecting</p>
-------------	---



**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>and a bearing tree mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 4 3/4° E., 11.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the "T" shaped iron rod and the copper pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 20 S</td> <td style="padding: 0 10px;">R 6 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">S5 T21S 2009</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 89° 16' 19" W., on the S. bdy of sec. 32.</p> <p>2680.93 The 1/4 sec. cor. of sec. 32 only, reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1956, by proportionate measurement, perpetuated by Leslie D. Roberts, Oregon PLS No. 1039, in 1997, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of accessories mkd. by Haines</p> <p style="padding-left: 40px;">An X chiseled on a rock face bears S. 25° W., 3.7 ft. dist.</p> <p style="padding-left: 40px;">A decayed fir stump, 43 ins. diam., bears N. 32 1/4° W., 50.2 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir snag, 6 ins. diam., bears S. 43° W., 5.0 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A double trunk maple, 9 ins. diam., bears N. 57 1/4° W., 8.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	T 20 S	R 6 W	S 32	S 33
T 20 S	R 6 W				
S 32	S 33				

Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">T 20 S R 6 W 1/4 S 32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T 21 S 2009</p> <p>Deposit a magnet in a white plastic case at the base and bury the "T" shaped iron rod alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 15' 29" W., beginning new measurement.</p> <p>1970.70 From this point, the original closing cor. of secs. 5 and 6, T. 21 S., R. 6 W., bears South, 11.69 ft. dist., perpetuated by Wilford N. Haines, Oregon PLS No. 239, in 1956, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 2 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir snag, 51 ins. diam., bears S. 27° W., 20.7 ft. dist., with a healed blaze. (Record, 17.8 ft.)</p> <p>and a bearing tree of unknown origin</p> <p style="padding-left: 40px;">A fir snag, 15 ins. diam., bears S. 10 1/2° W., 20.3 ft. dist., with scribe marks CC S6 BT visible on a partially healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 20 S S 32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 6   S 5 C C</p> <p style="text-align: center;">T 21 S R 6 W 2009</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 45° 52' 27" E., 7.65 ft. dist., with aluminum cap mkd. RM T21S R6W CC S5 7.7 FT TO COR 2009 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 34° 19' 53" W., 5.05 ft. dist., with aluminum cap mkd. RM T21S R6W CC S6 5.1 FT TO COR 2009 and an arrow pointing to the cor.</p>
------	--

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET					
2681.21	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 31 and 32 only, reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1956, by proportionate measurement, perpetuated by Leslie D. Roberts, Oregon PLS No. 1039, in 1997, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 7 ins. above the ground, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 39 ins. diam., bears N. 22 3/4° E., 150.8 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 49 ins. diam., bears N. 35° W., 115.7 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A sawed fir stump, 7 ins. diam., bears N. 26 1/4° E., 14.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 10 ins. diam., bears N. 64 3/4° W., 16.0 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 20 S</td> <td style="padding: 0 10px;">R 6 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> </table> <p style="margin: 5px 0;">S 6</p> <p style="margin: 5px 0;">T 21 S</p> <p style="margin: 5px 0;">2009</p> </div> <p>from which</p> <p style="padding-left: 40px;">A rebar, 30 ins. long, 5/8 in. diam., driven 36 ins. in the ground, buried 6 ins. below the surface, for a reference monument, bears N. 55° 37' 29" E., 10.66 ft. dist., with aluminum cap mkd. RM T20S R6W S32 10.7 FT TO COR 2009 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 49 1/2° W., 85.1 ft. dist., mkd. T20S R6W S31 BT.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>N. 89° 21' 47" W., on the S. bdy. of sec. 31.</p>	T 20 S	R 6 W	S 31	S 32
T 20 S	R 6 W				
S 31	S 32				
1992.48	<p>The 1/4 sec. cor. of sec. 6 only, T. 21 S., R. 6 W., established by Wilford N. Haines, Oregon PLS No. 239, in 1956, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above the ground, from which the remains of bearing trees mkd. by Haines</p>				

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

<p>FEET</p>	<p>A sawed fir stump, 78 ins. diam., bears N. 15 3/4° E., 67.8 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 58 ins. diam., bears N. 15 1/4° W., 62.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree of unknown origin</p> <p>A cedar, 23 ins. diam., bears S. 86 3/4° E., 14.7 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 20 S ----- 1/4 S 6 T 21 S R 6 W 2009</p> <p>from which</p> <p>A hemlock, 16 ins. diam., bears N. 26° W., 16.1 ft. dist., mkd. 1/4 S6 BT.</p> <p style="text-align: center;">-----</p> <p>N. 89° 19' 25" W., beginning new measurement.</p>
<p>689.16</p>	<p>The 1/4 sec. cor. of sec. 31 only, reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1956, by proportionate measurement and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 5 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p> <p>A sawed, decayed fir stump, 47 ins. diam., bears N. 59 1/2° W., 102.3 ft. dist., with a healed blaze.</p> <p>A sawed, decayed fir stump, 63 ins. diam., bears N. 44 3/4° W., 87.7 ft. dist., with no marks visible.</p> <p>and a bearing tree of unknown origin</p> <p>A fir, 17 ins. diam., bears N. 86 1/4° E., 28.5 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p align="center">T 20 S R 6 W 1/4 S 31</p> <hr/> <p align="center">T21S 2009</p> <p>from which</p> <p align="center">A fir, 22 ins. diam., bears N. 43° W., 44.0 ft. dist., mkd. T20S R6W S31 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89° 06' 57" W., beginning new measurement.</p> <p>662.67 The W 1/16 sec. cor. of sec. 6 only, T. 21 S., R. 6 W., established by Wilford N. Haines, Oregon PLS No. 239, in 1956, and is accepted as the cor., determined at record distances from the remains of bearing trees mkd. by Haines</p> <p align="center">A fir, 54 ins. diam., bears N. 78 3/4° E., 110.8 ft. dist., with a healed blaze.</p> <p align="center">A fir snag, 36 ins. diam., bears N. 53 1/4° W., 22.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <hr/> <p align="center">W 1/16 S 6 2009</p> <p>from which</p> <p align="center">A fir, 17 ins. diam., bears S. 55° W., 19.2 ft. dist., mkd. W 1/16 S6 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89° 29' 01" W., beginning new measurement.</p> <p>670.91 The original closing cor. of T. 21 S., Rs. 6 and 7 W., perpetuated by Wilford N. Haines, Oregon PLS No. 239, in 1956, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 14 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of the original bearing trees</p>
------	---

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>A sawed fir stump, 32 ins. diam., bears S. 18° E., 25.1 ft. dist., with a healed blaze. (Record, 29.7 ft.)</p> <p>A fir snag, 20 ins. diam., bears N. 20° W., 15.1 ft. dist., with no marks visible. (Record, 12.5 ft.)</p> <p>and a bearing tree of unknown origin</p> <p>A fir, 7 ins. diam., bears S. 76 1/2° W., 20.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="border-bottom: 1px solid black; padding: 2px 10px;">T 20 S R 6 W</td> </tr> <tr> <td style="padding: 2px 5px;">S 1</td> <td style="padding: 2px 5px;">S 6</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">C C</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">T 21 S</td> </tr> <tr> <td style="padding: 2px 5px;">R 7 W</td> <td style="padding: 2px 5px;">R 6 W</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">2009</td> </tr> </table> </div> <p>from which</p> <p>A fir, 6 ins. diam., bears S. 54 3/4° E., 6.3 ft. dist., mkd. T21S R6W S6 CC BT.</p> <p>A fir, 16 ins. diam., bears S. 9 1/4° W., 28.2 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 07' 02" W., beginning new measurement.</p>	T 20 S R 6 W		S 1	S 6	C C		T 21 S		R 7 W	R 6 W	2009	
T 20 S R 6 W													
S 1	S 6												
C C													
T 21 S													
R 7 W	R 6 W												
2009													
1347.24	<p>The cor. of T. 20 S., Rs. 6 and 7 W., perpetuated by Wilford N. Haines, Oregon PLS No. 239, in 1956, from original evidence no longer in existence, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, flush with the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of accessories mkd by Haines</p> <p>A sawed fir stump, 58 ins. diam., bears N. 42 1/4° E., 20.1 ft. dist., with scribe marks XXX1 BT visible on the bark.</p> <p>An X chiseled on a rock face bears S. 68° W., 95.7 ft. dist., with a brass disk mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE nailed 8 ins. above the X.</p> <p>A sawed fir stump, 42 ins. diam., bears N. 57 1/4° W., 91.1 ft. dist., with scribe marks T20S R7W S36 BT visible on the bark.</p>												

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 20 S</td></tr> <tr><td>R 7 W</td><td>R 6 W</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table>   <table border="1"> <tr><td colspan="2">S 1</td></tr> <tr><td>T 21 S</td><td>R 7 W</td></tr> <tr><td colspan="2">2009</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">An alder, 17 ins. diam., bears S. 74 1/2° E., 38.9 ft. dist., mkd. T21S R7W S1 BT in the bark.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 56 1/2° W., 125.0 ft. dist., mkd. T20S R7W S36 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located 55.0 ft. East of the South Fork of Smith River, 30 ft. wide, course N. 5° W.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 20 S., R. 6 W., Willamette Meridian, Oregon</b></p> <hr/> <p style="text-align: center;">Restoring the 1872 survey by John H. McClung, the 1950 resurvey by Marvin J. Lytle, the 1962 resurvey by William W. Glenn, the 1989 resurvey by Wayne L. Rogers, the 1995 resurvey by Daniel N. Patterson and Craig L. Wanless, and the 2003 resurvey by A. Bert Skeesick</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS</p> <table border="1"> <tr><td colspan="2">T 20 S R 6 W</td></tr> <tr><td>S 27</td><td>S 26</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td colspan="2">1954</td></tr> <tr><td colspan="2">OFFICE</td></tr> </table> </div> <p>from which the remains of the original bearing trees</p>	T 20 S		R 7 W	R 6 W	S 36	S 31	S 1		T 21 S	R 7 W	2009		T 20 S R 6 W		S 27	S 26	-----		S 34	S 35	1954		OFFICE	
T 20 S																									
R 7 W	R 6 W																								
S 36	S 31																								
S 1																									
T 21 S	R 7 W																								
2009																									
T 20 S R 6 W																									
S 27	S 26																								
-----																									
S 34	S 35																								
1954																									
OFFICE																									

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>A fir snag, size indeterminate, bears N. 59° E., 13.2 ft. dist., with no marks visible.</p> <p>A fir snag, size indeterminate, bears N. 30° W., 2.6 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. Ben B. Irving, Douglas County Surveyor, in 1954, reported by Skeesick</p> <p>A fir, 41 ins. diam., bears N. 25° E., 59.4 ft. dist., with a healed double blaze.</p> <p>A tin-capped, sawed fir stump, 23 ins. diam., bears S. 28 3/4° E., 43.6 ft. dist., with no marks visible.</p> <p>A sawed fir stump, 42 ins. diam., bears S. 19 1/2° W., 81.2 ft. dist., with no marks visible.</p> <p>A fir, 49 ins. diam., bears N. 22° W., 31.0 ft. dist., with a healed blaze and scribe marks BT visible on the bark.</p> <p>and a bearing tree mkd. by Rogers</p> <p>A hemlock, 17 ins. diam., bears N. 69° E., 23.8 ft. dist., with a healed blaze.</p> <p>and remains of bearing trees mkd. by Skeesick</p> <p>A chinquapin, 7 ins. diam., bears S. 33 3/4° E., 23.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>A fir snag, 9 ins. diam., bears S. 62 3/4° W., 40.2 ft. dist., with a healed blaze.</p> <p>There are no suitable trees to the SW.</p> <p>N. 3° 57' 37" E., bet. secs. 26 and 27.</p> <p>Ascend over broken SE. slope.</p>
200	Spur, slopes S. 80° E., desc. over NE. slope.
2405	Spur, slopes N. 70° W., desc. over NW. slope.
2562.25	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p>
	<p>T 20 S R 6 W 1/4 S 27   S 26 1989</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>from which bearing trees mkd. by Rogers</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 62° E., 9.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears S. 9 1/2° W., 13.2 ft. dist., with a healed blaze.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 3° 59' 56" E., beginning new measurement.</p> <p>Descend over broken NW. slope.</p>								
175	<p>Ravine, drains N. 85° W., asc. over SW. slope.</p>								
2561.48	<p>The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="2">T 20 S R 6 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 22</td> <td style="padding: 2px 5px;">S 23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 27</td> <td style="padding: 2px 5px;">S 26</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1950</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Lytle</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 60 1/4° E., 51.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A roothole bears S. 37 1/4° E., 66.7 ft. dist., alongside of which is a decayed fir trunk, 23 ins. diam., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 43 ins. diam., bears S. 70 1/4° W., 21.8 ft. dist., with axe mark visible on the bark.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 48 3/4° W., 44.2 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Rogers, not reported by Patterson and Wanless</p> <p style="padding-left: 40px;">A roothole bears S. 32 1/2° E., 19.8 ft. dist., alongside of which is a fir trunk, 7 ins. diam., with no marks visible.</p> <p>and a bearing tree mkd. by Patterson and Wanless</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 29 3/4° E., 37.0 ft. dist., with a healed blaze.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 33 and 34, remonumented by Ben B. Irving, Douglas County Surveyor, in 1954, filed in the Douglas County Surveyor's Office, C.S. File Nos. 45/275 and 41/274, monumented with an iron post,</p>	T 20 S R 6 W		S 22	S 23	S 27	S 26	1950	
T 20 S R 6 W									
S 22	S 23								
S 27	S 26								
1950									

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>1 1/4 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p align="center">COUNTY 1954 SURVEYORS T 20 S R 6 W 33   34 1/4 S OFFICE</p> <p>from which the remaining original bearing tree</p> <p>A fir, 31 ins. diam., bears S. 37 1/2° E., 19.8 ft. dist., with a hollow blaze, with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Irving</p> <p>A sawed fir stump, 40 ins. diam., bears N. 74° W., 51.2 ft. dist., with no marks visible.</p> <p>and new bearing tree</p> <p>A fir, 5 ins. diam., bears S. 40° W., 13.5 ft. dist., mkd. 1/4 S33 BT.</p> <p>From this cor., a point established by David A. Edwards, Oregon PLS No. 2339, in 1999, bears S. 0° 16' 53" W., 94.28 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with yellow plastic cap mkd. DA EDWARD LS 2939, and is not utilized in the course of this survey.</p> <p>From this same cor., a point established by person(s) unknown, bears S. 3° 34' 09" W., 87.34 ft. dist., monumented with an iron pipe, 2 1/2 ins. diam., loosely set, projecting 24 ins. above the ground, and is not utilized in the course of this survey.</p> <p>N. 0° 25' 55" W., bet. secs. 33 and 34.</p> <p>Ascend over broken E. slope.</p> <p>1343.40 The N 1/16 sec. cor. of secs. 33 and 34, established by Wilford N. Haines, Oregon PLS No. 239, in 1966, perpetuated by Robert B. Ward, Jr., Oregon PLS No. 1091, in 2002, and is accepted as the cor., monumented with a rebar, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, from which the remaining bearing tree mkd. by Haines</p> <p>A fir, 22 ins. diam., bears S. 80 1/4° W., 23.7 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Ward</p> <p>A fir, 12 ins. diam., bears S. 23 3/4° E., 11.7 ft. dist., with a healed blaze.</p>
------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the rebar, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 6 W N 1/16 S 33   S 34 2009</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 21' 48" W., beginning new measurement.</p> <p>Ascend over broken E. slope.</p>
160	<p>Ridge, bears N. 20° E. and S. 20° W., also graveled road, 16 ft. wide, bears N. 20° E. and S. 20° W., desc. over NW. slope.</p>
1345.66	<p>The cor. of secs. 27, 28, 33, and 34, perpetuated by Charles C. Hayden, Oregon PLS No. 131, in 1950, filed in the Douglas County Surveyor's Office, C.S. File No. 40/255, further perpetuated by Wilford N. Haines, Oregon PLS No. 239, in 1956, further perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, filed in the Douglas County Surveyor's Office, C.S. File No. 49/89, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 20 S R 6 W S 28   S 27 ----- S 33   S 34 1962</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir snag, 20 ins. diam., bears S. 76° E., 13.9 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A decayed fir snag, 25 ins. diam., bears S. 72° W., 15.9 ft. dist., with no marks visible. (Record, 13.2 ft.)</p> <p>and the remains of a bearing tree mkd. by Hayden</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 1 3/4° W., 17.9 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Godfrey</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 37 ins. diam., bears N. 3 3/4° E., 62.7 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 36 ins. diam., bears S. 76 3/4° W., 26.1 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A hemlock, 26 ins. diam., bears S. 42 1/4° E., 31.1 ft. dist., mkd. T20S R6W S34 BT.</p> <p>A fir, 12 ins. diam., bears N. 27 1/4° W., 40.3 ft. dist., mkd. T20S R6W S28 BT.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 88° 21' 11" W., bet secs. 22 and 27.</p> <p>Descend over broken SW. slope.</p>
2608.24	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 22 1/4 ——— S 27 1950</p> </div> <p>from which bearing trees mkd. by Lytle</p> <p>A cedar, 50 ins. diam., bears S. 44 1/4° W., 5.9 ft. dist., with a healed blaze.</p> <p>A hemlock, 44 ins. diam., bears N. 7 1/4° W., 54.1 ft. dist., with a healed blaze.</p> <p>and a bearing tree of unknown origin</p> <p>A cedar, 60 ins. diam., bears N. 57 3/4° E., 39.0 ft. dist., with no marks visible.</p> <p>Corner is located on left bank of Beaver Creek, 5 ft. wide, course S. 85° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 85° 14' 00" W., beginning new measurement.</p> <p>Across broken S. slope.</p>
3600.66	<p>The cor. of secs. 21, 22, 27, and 28, perpetuated by William L. Wilt, Weyerhaeuser Timber Co. Land Agent, in 1961, filed in the Douglas County Surveyor's Office, C.S. File Nos. 53/1 and 52/104, determined at record bearing and distance from the remains of the original bearing trees</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>A maple, 6 ins. diam., bears N. 25° E., 16.5 ft. dist., with no marks visible.</p> <p>A dogwood, 10 ins. diam., bears S. 45 3/4° E., 11.9 ft. dist., with no marks visible. (Record, S. 54° E.)</p> <p>and the remains of bearing trees mkd. by Lytle</p> <p>A fir, 46 ins. diam., bears N. 48° E., 33.7 ft. dist., with a healed blaze. (Record, 25.7 ft. dist.)</p> <p>A fir, 43 ins. diam., bears S. 53° W., 78.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and bearing tree mkd. by Wilt</p> <p>A fir, 67 ins. diam., bears N. 30 3/4° W., 78.0 ft. dist., with a healed blaze.</p> <p>(Note: The iron post set by Lytle in 1950, was disturbed by road construction and found wired to a rebar driven nearby in an unrelated position.)</p> <p>At the corner point</p> <p>Reset the iron post, 30 ins. long, 2 ins. diam., 14 ins. in the ground, in sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 20 S</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 6 W</td> </tr> <tr> <td style="padding: 0 5px;">S 21</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 22</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 5px 0 0 0;"></td> </tr> <tr> <td style="padding: 0 5px;">S 28</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1950</td> </tr> </table> </div> <p>from which</p> <p>A fir, 19 ins. diam., bears S. 50 1/4° W., 65.2 ft. dist., mkd. T20S R6W S28 BT.</p> <p>Corner is located on a steep E. cut bank of a dirt road, 12 ft. wide, bears N. 5° E. and S. 5° W.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 89° 51' 06" W., bet. secs. 28 and 33.</p> <p>Ascend over broken SE. slope.</p> <p>1326.13 The E 1/16 sec. cor. of secs. 28 and 33, established by Wilford N. Haines, Oregon PLS No. 239, in 1956, perpetuated by Ronald L. Rice, Oregon PLS No. 54633, in 2006, and is accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, buried 4 ins. below the surface of the ground, from which the bearing tree mkd. by Rice</p>	T 20 S	R 6 W	S 21	S 22			S 28	S 27	1950	
T 20 S	R 6 W										
S 21	S 22										
S 28	S 27										
1950											

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 41 ins. diam., bears S. 50 1/4° W., 52.9 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 36 ins. in the ground, buried 8 ins. below the surface, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">             S 28              E 1/16 ———              S 33              2009         </p> <p>from which</p> <p>A rebar, 30 ins. long, 5/8 in. diam., driven 27 ins. in the ground for a reference monument, bears S. 35° 33' 25" W., 19.67 ft. dist., with aluminum cap mkd. RM E 1/16 S33 19.7 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>A rebar, 30 ins. long, 5/8 in. diam., driven 24 ins. in the ground for a reference monument, bears N. 65° 42' 56" W., 19.96 ft. dist., with aluminum cap mkd. RM E 1/16 S28 20.0 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>Corner is located near the center of an abandoned dirt road, 16 ft. wide, bears N. 45° E. and S. 50° W.</p> <p>From this cor., the witness cor. to the E 1/16 sec. cor. of secs. 28 and 33, established by Wilford N. Haines, Oregon PLS No. 239, in 1956, bears N. 66° 58' 25" W., 20.34 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., projecting 2 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p> <p style="text-align: center;">             A decayed fir snag, size indeterminate, bears N. 18 1/2° E.,              13.0 ft. dist., with no marks visible.              _____         </p> <p>N. 89° 48' 34" W., beginning new measurement.</p> <p>Ascend over broken SE. slope.</p>
180	<p>Spur, slopes S. 20° E., desc. over NW. slope.</p>
1328.71	<p>The 1/4 sec. cor. of secs. 28 and 33, reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1956, by proportionate measurement and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 2 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 38 ins. diam., bears N. <math>0\ 1/4^\circ</math> E., 6.4 ft. dist., with a healed blaze.</p> <p>A fir, 49 ins. diam., bears S. <math>9\ 1/4^\circ</math> E., 23.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\ 1/2</math> ins. diam., 25 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p align="center">T 20 S R 6 W S 28 <math>1/4</math> ——— S 33 2009</p> <p>from which</p> <p>A fir, 7 ins. diam., bears N. <math>19\ 1/2^\circ</math> E., 39.0 ft. dist., mkd. <math>1/4</math> S28 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33, reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1956, by proportionate measurement, and is accepted as the cor., monumented with a "T" shaped iron rod, <math>3/4</math> in. diam., firmly set, projecting 2 in. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p> <p>A sawed, decayed fir stump, 40 ins. diam., bears N. <math>26\ 1/2^\circ</math> E., 71.0 ft. dist., with no marks visible.</p> <p>A fir, 39 ins. diam., bears S. <math>87\ 3/4^\circ</math> E., 42.0 ft. dist., with no marks visible.</p> <p>A sawed fir stump, 46 ins. diam., bears S. <math>48^\circ</math> W., 50.2 ft. dist., with no marks visible.</p> <p>A fir, 42 ins. diam., bears N. <math>22\ 3/4^\circ</math> W., 72.6 ft. dist., with fragmentary scribe marks visible on the bark.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\ 1/2</math> ins. diam., 24 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 20 S</td> <td style="padding: 0 5px;">R 6 W</td> </tr> <tr> <td style="padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 32</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 33</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2009</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears N. 17 1/2° E., 93.9 ft. dist., mkd. T20S R6W S28 BT.</p> <p style="margin-left: 40px;">A hemlock, 14 ins. diam., bears S. 21° W., 28.1 ft. dist., mkd T20S R6W S32 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>N. 3° 39' 01" W., bet. secs. 28 and 29.</p> <p>2723.61 The 1/4 sec. cor. of secs. 28 and 29, reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1961, by proportionate measurement, filed in the Douglas County Surveyor's Office, C.S. File No. 51/173, and is accepted as the cor., monumented with an angle iron, 1 in. x 1 in., firmly set, projecting 15 ins. above the ground, from which the remains of a bearing tree mkd. by Haines</p> <p style="margin-left: 40px;">A roothole bears S. 16 1/2° W., 51.6 ft. dist., alongside of which is a yew trunk, 18 ins. diam., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the angle iron, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 20 S</td> <td style="padding: 0 5px;">R 6 W</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1/4</td> </tr> <tr> <td style="padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2009</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 78 1/2° E., 43.7 ft. dist., mkd. 1/4 S28 BT.</p> <p style="margin-left: 40px;">A fir, 19 ins. diam., bears N. 50 3/4° W., 10.5 ft. dist., mkd. 1/4 S29 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3° 32' 47" W., beginning new measurement.</p>	T 20 S	R 6 W	S 29	S 28	S 32	S 33	2009		T 20 S	R 6 W	1/4		S 29	S 28	2009	
T 20 S	R 6 W																
S 29	S 28																
S 32	S 33																
2009																	
T 20 S	R 6 W																
1/4																	
S 29	S 28																
2009																	

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

<p>FEET 2712.58</p>	<p>The cor. of secs. 20, 21, 28, and 29, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, filed in the Douglas County Surveyor's Office, C.S. File No. 49/89, further perpetuated by Daniel W. Baker, Oregon PLS No. 1978, in 1998, filed in the Douglas County Surveyor's Office, C.S. File No. 65/20-17, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 20 S</td> <td style="padding: 0 5px;">R 6 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1950</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Lytle</p> <p style="margin-left: 40px;">A roothole bears N. 56 1/2° E., 38.3 ft. dist., alongside of which is a fallen fir trunk, 9 ins. diam., with no marks visible.</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears S. 34° E., 25.1 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Godfrey</p> <p style="margin-left: 40px;">A sawed fir stump, size indeterminate, bears N. 75° W., 8.1 ft. dist., with no marks visible.</p> <p>and the bearing trees mkd. by Baker</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 79 1/4° E., 15.0 ft. dist., with a healed double blaze.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 49 1/2° W., 9.0 ft. dist., with a healed double blaze.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 40° W., 5.3 ft. dist., with a healed double blaze.</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>S. 89° 55' 02" W., bet. secs. 29 and 32.</p>	T 20 S	R 6 W	S 20	S 21	S 29	S 28	1950	
T 20 S	R 6 W								
S 20	S 21								
S 29	S 28								
1950									
<p>2651.08</p>	<p>The 1/4 sec. cor. of secs. 29 and 32, reestablished by Wilford N. Haines, Oregon PLS No. 239, in 1956, by proportionate measurement, perpetuated by Leslie D. Roberts, Oregon PLS No. 1039, in 2000, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 22 ins. above the ground, from which bearing trees mkd. by Roberts</p> <p style="margin-left: 40px;">An alder, 8 ins. diam., bears N. 42 1/4° E., 16.1 ft. dist., with scribe marks 1/4 S29 BT visible on the bark.</p> <p style="margin-left: 40px;">An alder, 13 ins. diam., bears S. 53 1/4° E., 8.7 ft. dist., with scribe marks 1/4 S29 BT visible on the bark.</p>								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>At the corner point</p> <p>Cut 1 ft. off the exposed "T" shaped iron rod (iron rod now projects 5 ins. above ground), and drive an aluminum cap, 3 1/4 ins. diam., onto the "T" shaped iron rod, with top mkd.</p> <p align="center">T 20 S R 6 W S 29 1/4 ——— S 32 2009</p> <p>Corner is located on the S. bank of a creek, 4 ft. wide, course S. 45° E.</p> <hr/> <p>S. 89° 57' 24" W., beginning new measurement.</p> <p>2652.28 The cor. of secs. 29, 30, 31, and 32, perpetuated by Wilford N. Haines, Oregon PLS No. 239, in 1956, further perpetuated by Donald L. Peel, Oregon PLS No. 752, in 1991, further perpetuated by Leslie D. Roberts, Oregon PLS No. 1039, in 2000, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 5 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 47 1/2° W., 37.6 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 43 ins. diam., bears N. 60 1/4° E., 37.4 ft. dist., with scribe marks T20S R6W S29 visible on the bark.</p> <p style="padding-left: 40px;">A roothole bears S. 57 3/4° E., 31.1 ft. dist.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 62 1/4° W., 40.7 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Peel</p> <p style="padding-left: 40px;">A burnt fir snag, 25 ins. diam., bears S. 17° E., 22.8 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Roberts</p> <p style="padding-left: 40px;">A hemlock snag, 7 ins. diam., bears S. 64 1/2° E., 7.6 ft. dist., with scribe marks T20S R6W S32 BT visible on a partially healed double blaze.</p> <p>At the corner point</p>
------	--



**Subdivision of Section 33,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
1318.85	<p>Deposit a magnet in a white plastic case at the base and bury the "T" shaped iron rod, 48 ins. long, alongside the stainless steel post.</p> <p>Corner is located 30.0 ft. E. of a graveled road, 16 ft. wide, bears S. 5° E. and N. 5° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 22' 35" E., beginning new measurement.</p> <p>Descend over NW. slope.</p> <p>The center 1/4 sec. cor. of sec. 33, established by Wilford N. Haines, Oregon PLS No. 239, in 1966, and is accepted as the cor., monumented with a rebar, 1/2 in. diam., firmly set, projecting 10 ins. above the ground, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A sawed fir stump, 29 ins. diam., bears N. 34° E., 12.4 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A roothole bears S. 50° E., 17.3 ft. dist., alongside of which is a fallen, decayed fir trunk, 32 ins. diam., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, directly over the rebar, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 6 W C 1/4 S 33 2009</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 7 ins. diam., bears S. 11 1/2° W., 9.7 ft. dist., mkd. C 1/4 S33 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 83° W., 28.8 ft. dist., mkd. C 1/4 S33 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 39" E., beginning new measurement.</p> <p>Descend over broken NW. slope.</p>
1358.73	<p>The center N 1/16 sec. cor. of sec. 33, established by Wilford N. Haines, Oregon PLS No. 239, in 1966, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above the ground (6 ins. of "T" shaped iron rod, broken off and lying alongside), from which bearing trees mkd. by Haines</p>

**Subdivision of Section 33,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 31 ins. diam., bears S. 0 3/4° W., 36.5 ft. dist., with a healed blaze.</p> <p>A fir, 36 ins. diam., bears N. 3° W., 14.3 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, buried 6 ins. below the surface, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>C N 1/16   S 33 C 2009</p> </div> <p>Deposit a magnet in a white plastic case and the broken piece of the iron rod at the base of the stainless steel post.</p> <hr/> <p>N. 0° 15' 20" E., beginning new measurement.</p>
1340.63	<p>The 1/4 sec. cor. of secs. 28 and 33.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 33 and 34.</p> <p>S. 89° 55' 11" W., on the E. and W. centerline of sec. 33.</p> <p>Ascend over broken E. slope.</p>
1339.81	<p>The center E 1/16 sec. cor. of sec. 33, established by Wilford N. Haines, Oregon PLS No. 239, in 1966, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p> <p>A fir, 18 ins. diam., bears S. 67 3/4° W., 59.5 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 45 ins. diam., bears N. 72 3/4° W., 34.4 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p>

Subdivision of Section 33,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T 20 S R 6 W E 1/16 C ————— C S 33 2009</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 7 1/2° W., 5.8 ft. dist., mkd. CE 1/16 S33 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located 35.0 ft. S. of a spur, slopes S. 80° W., and 40 ft. S. of a graveled road, 14 ft. wide, bears S. 85° E. and S. 80° W.</p> <hr style="width: 30%; margin: 10px auto;"/> <p style="padding-left: 40px;">S. 89° 58' 26" W., beginning new measurement.</p> <p style="padding-left: 40px;">Ascend over broken NE. slope.</p>
1175	<p style="padding-left: 40px;">Spur, slopes N. 15° W., desc. over NW. slope.</p>
1342.23	<p style="padding-left: 40px;">The center 1/4 sec. cor. of sec. 33.</p> <hr style="width: 30%; margin: 10px auto;"/> <p style="padding-left: 40px;">S. 89° 53' 40" W., beginning new measurement.</p> <p style="padding-left: 40px;">Ascend over broken SE. slope.</p>
1356.10	<p style="padding-left: 40px;">The center W 1/16 sec. cor. of sec. 33, established by Wilford N. Haines, Oregon PLS No. 239, in 1966, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above the ground, from which the bearing trees mkd. by Haines</p> <p style="padding-left: 80px;">A fir, 14 ins. diam., bears S. 74° W., 17.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 80px;">A fir, 19 ins. diam., bears N. 11 3/4° W., 56.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ————— C S 33 2009</p>

Subdivision of Section 33,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>S. 89° 51' 55" W., beginning new measurement.</p>
	<p>Ascend over broken SE. slope.</p>
105	<p>Spur, slopes S. 15° E.; desc. over SW. slope.</p>
275	<p>Ravine, drains S. 25° W.; asc. over SE. slope.</p>
1255	<p>Creek, 4 ft. wide, course S. 10° W.; asc. over SE. slope.</p>
1355.76	<p>The 1/4 sec. cor. of secs. 32 and 33, perpetuated by Wilford N. Haines, Oregon PLS No. 239, in 1956, further perpetuated by Leslie D. Roberts, Oregon PLS No. 1039, in 1997, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 15 ins. above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree</p>
	<p style="padding-left: 40px;">A roothole bears N. 1° W., 33.0 ft. dist., alongside of which is a decayed fir trunk, 32 ins. diam., with axe marks visible.</p>
	<p>and bearing trees mkd. by Roberts</p>
	<p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 73 1/2° E., 12.7 ft. dist., with a healed blaze.</p>
	<p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 6° W., 11.2 ft. dist., with a healed blaze.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p>
	<p style="text-align: center;">T 20 S R 6 W 1/4 S 32   S 33 2009</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>From the center E 1/16 sec. cor. of sec. 33.</p>
	<p>N. 0° 25' 39" W., on the N. and S. centerline of the NE 1/4 of sec. 33.</p>
	<p>Descend over a broken W. slope.</p>

**Subdivision of Section 33,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
1353.43	<p>The NE 1/16 sec. cor. of sec. 33, established by Wilford N. Haines, Oregon PLS No. 239, in 1966, perpetuated by Ronald L. Rice, Oregon PLS No. 54633, in 2006, and is accepted as the cor., monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A roothole bears S. 23 1/2° E., 11.3 ft. dist., alongside of which is a fallen fir trunk, 47 ins. diam., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 18 3/4° W., 28.6 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Rice</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears S. 74° E., 55.0 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the rebar, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 33 2009</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 33 and 34.</p> <p>N. 89° 39' 06" W., on the E. and W. centerline of the NE 1/4 of sec. 33.</p> <p>Ascend over E. slope.</p>
1339.73	<p>The NE 1/16 sec. cor. of sec. 33.</p> <hr/>