

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
A PORTION OF THE NORTH BOUNDARY  
AND SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF SECTION 11  
**TOWNSHIP 30 SOUTH, RANGE 2 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***Kenneth W. Saveland, Cadastral Surveyor***

Under Special Instructions dated September 25, 2008,  
approved September 26, 2008, which provided for the surveys included  
under Group No. 2232, and Assignment Instructions dated October 15, 2008.

***Survey commenced October 21, 2008***

***Survey completed April 21, 2009***

**T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET

The following field notes are those of the dependent resurvey of a portion of the north boundary and subdivisional lines, and the subdivision of section 11, Township 30 South, Range 2 West, of the Willamette Meridian, Oregon.

A history of surveys pertaining to this survey is as follows:

In 1858, Dennis Hathorn, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1909, Fred Mensch, U.S. Deputy Surveyor, surveyed the north boundary and the remainder of the subdivisional lines.

In 1917, Elmer F. Strickler, U.S. Transitman, resurveyed the north boundary.

In 1963, C. Albert White, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1998, Wayne L. Rogers, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the north and east boundaries and subdivisional lines, and subdivided sections 1 and 12.

In 2000, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the subdivisional lines.

In 2008, Kenneth W. Saveland, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

The following plat and field notes filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name and year.

<u>Date</u>	<u>Name and Registration No.</u>	<u>File Type</u>	<u>File No.</u>
1949	John H. Markham, Jr. RE 2880	C.S.	40/185
1959-62	John H. Markham, Jr. RE 2880	C.S.	42/421
1968	Douglas County Surveyor's Office	C.S.	54/73
1971	James Byron, Deputy County Surveyor	C.S.	54/73
1974	Douglas County Surveyor's Office	C.S.	57/12
1975	Douglas County Surveyor's Office	C.S.	54/73
1975	Douglas County Surveyor's Office	C.S.	57/39

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 25, 2008, for Group No. 2232, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data

**T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET

were thoroughly verified and only the corner description field notes are given herein. Only those lines bounding public lands were posted and blazed.

The direction of the lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) measurements.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.1 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

The geographic positions (NAD 1983 (CORS)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP", and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", are as follows:

The corner of sections 32 and 33 only, on the north boundary of the Township:

Latitude: 43° 00' 17.00" N. Longitude: 122° 57' 42.61" W.

The 1/4 section corner of sections 15 and 22:

Latitude: 42° 57' 37.90" N. Longitude: 122° 55' 57.40" W.

The 1/4 section corner of sections 2 and 11:

Latitude: 42° 59' 23.36" N. Longitude: 122° 54' 44.49" W.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

---

**Resurvey of a Portion of the North Boundary,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">Restoring the 1909 survey by Fred Mensch and the 1917 resurvey by Elmer F. Strickler</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1968 and 1975, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 29 S R 2 W</p> <p style="text-align: center;">1/4 —●— S 4 T 30 S 1968</p> <p>from which the remains of an orig. bearing tree</p> <p style="padding-left: 40px;">A sawed cedar stump, 26 ins. diam., bears S. 20° W., 31.7 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Strickler in 1917</p> <p style="padding-left: 40px;">A sawed fir stump, 52 ins. diam., bears S. 20° E., 24.4 ft. dist., with scribe marks 1/4 visible on an opened blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office in 1968</p> <p style="padding-left: 40px;">A hemlock, 20 ins. diam., bears S. 5° E., 19.4 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears S. 73 1/4° W., 22.2 ft. dist., mkd. 1/4 S4 BT.</p> <p>Corner is located on a broken N. slope, in a large roothole.</p> <p>S. 88° 15' 39" W., bet. secs. 4 and 33, on the N. bdy. of the Tp., posting and blazing the true line.</p> <p>43.69 The 1/4 sec. cor. of sec. 33 only, on the N. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 33</p> <p style="text-align: center;">—●—</p> <p style="text-align: center;">1917</p>
------	---

**Resurvey of a Portion of the North Boundary,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of bearing trees mkd. by Strickler in 1917</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears N. 20 1/2° E., 69.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 28 ins. diam., bears N. 56° W., 48.2 ft. dist., with no marks visible.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A hemlock, 20 ins. diam., bears N. 49 3/4° W., 34.8 ft. dist., with a healed blaze.</p> <p>Corner is located on a broken N. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 50' 15" W., bet. secs. 4 and 33, on the N. bdy. of the Tp., beginning new measurement, posting and blazing.</p>
2550	Gravel road, 11 ft. wide, bears N. 5° W. and S. 5° W., in curve.
2577.85	<p>The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with brass mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 29 S R S 33 R 2 ——— 2 W S 5   S 4 W T 30 S 1968</p>
	<p>from which the remaining orig. bearing tree</p> <p style="padding-left: 40px;">A fir, 43 ins. diam., bears S. 29° E., 4.0 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office in 1968</p> <p style="padding-left: 40px;">A hemlock, 19 ins. diam., bears S. 64 1/2° W., 40.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 35° W., 9.8 ft. dist., with a healed blaze.</p> <p>Corner is located at the base of the westerly shoulder of a gravel road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 38' 10" W., bet. secs. 5 and 33, posting and blazing.</p>
35	Overgrown dirt road, 12 ft. wide, bears N. 60° W. and S. 60° E.

**Resurvey of a Portion of the North Boundary,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
61.77	<p>The cor. of secs. 32 and 33 only, on the N. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE T 29 S R 2 W S 32   S 33 S 5 T 30 S 1968</p> <p>from which the remains of bearing trees mkd. by Strickler in 1917</p> <p>A fir, 46 ins. diam., bears N. 21 1/4° E., 33.7 ft. dist., with a healed blaze.</p> <p>A fir snag, 23 ins. diam., bears N. 63 3/4° W., 37.0 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p>A cedar, 16 ins. diam., bears S. 10 1/2° E., 28.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 8 ins. diam., bears N. 75 1/4° W., 33.9 ft. dist., mkd. T29S R2W S32 BT.</p> <p>Corner is located on a NE. slope.</p> <hr/> <p align="center"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 30 S., R. 2 W., Willamette Meridian, Oregon</b></p> <hr/> <p align="center">Restoring the 1858 survey by Dennis Hathorn, the 1909 survey by Fred Mensch, the 1963 resurvey by C. Albert White, the 1998 resurvey by Wayne L. Rogers and Robert H. Browning, the 2000 resurvey by Timothy J. Moore and Robert H. Browning and the 2008 resurvey by Kenneth W. Saveland</p> <hr/> <p>From the cor. of secs. 10 and 11 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above a mound of stone, 3 1/2 ft. diam., 2 ft. high, (alongside of which is an iron pipe, 3/4 in. diam., loosely set, projecting 10 ins. above the mound of stone), with brass cap mkd.</p>

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET

T 30 S   R 2 W  
S 10 | S 11

S 14  
1963

from which the remains of the orig. bearing trees

A decayed and partially uprooted fir stump, size indeterminate, bears N. 84° E., 4.6 ft. dist., with no marks visible.

A fir, 31 ins. diam., bears N. 14 1/2° W., 50.2 ft. dist., with a healed double blaze.

and the remains of bearing trees mkd. by Markham, Jr., Registered Logging Engineer No. 2880, in 1959, reported by White in 1963

A fir, 19 ins. diam., bears N. 29 1/4° E., 12.5 ft. dist., with a healed blaze.

A madrone, 13 ins. diam., bears N. 53° E., 33.0 ft. dist., with no marks visible.

A fir snag, 11 ins. diam., bears S. 55° E., 25.1 ft. dist., with illegible scribe marks visible on an open blaze.

A madrone, 7 ins. diam., bears N. 45° W., 19.8 ft. dist., with no marks visible.

From this cor., the cor. of secs. 14 and 15 only, bears N. 88° 40' 01" W., 114.92 ft. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, (alongside of which is an iron rod, 1 in. diam., firmly set, projecting 10 ins. above ground) with brass cap mkd.

T 30 S R 2 W  
S 10

S 15 | S 14  
1963

from which the remains of an orig. bearing tree

A sawed pine stump, 37 ins. diam., bears S. 74° W., 18.5 ft. dist., with no marks visible.

and the remains of a bearing tree mkd. by Mensch in 1909

A sawed fir stump, 28 ins. diam., bears S. 47 1/2° E., 56.1 ft. dist., with a healed blaze.

and bearing trees mkd. by Markham, Jr., Registered Logging Engineer No. 2880, in 1959, reported by White in 1963

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 13 ins. diam., bears N. 65 1/2° E., 13.2 ft. dist., with a healed double blaze.</p> <p>A madrone, 10 ins. diam., bears S. 59 1/2° E., 31.7 ft. dist., with no marks visible.</p> <p>A maple, 14 ins. diam., bears S. 55° W., 57.4 ft. dist., with no marks visible on a partially opened blaze.</p> <p>and a bearing tree mkd. by White</p> <p>A fir, 11 ins. diam., bears S. 64 1/2° E., 24.4 ft. dist., with a healed blaze.</p> <p>N. 0° 21' 46" E., bet. secs. 10 and 11, posting and blazing.</p>
2165	<p>Gravel road, 12 ft. wide, bears N. 60° W and S. 60° E.</p>
2655.37	<p>The 1/4 sec. cor. of secs. 10 and 11, perpetuated by Markham, Jr., Registered Logging Engineer No. 2880, in 1960, monumented with an iron pipe, 30 ins. long, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a threaded and smashed top, (alongside of which is the orig. basalt stone, 8 x 8 x 15 ins. firmly set, projecting 4 ins. above ground, mkd. 1/4 on W. face, with a cross chiseled on top) from which the remains of an orig. bearing tree</p> <p>A roothole bears S. 47° E., 19.1 ft. dist., alongside of which is an uprooted fir stump, size indeterminate, with no marks visible.</p> <p>and the remains of bearing trees mkd. by Markham, Jr.</p> <p>A cedar, 19 ins. diam., bears S. 75 1/4° E., 26.0 ft. dist., with no marks visible.</p> <p>A fir snag, size indeterminate, bears S. 33° E., 44.4 ft. dist., with no marks visible.</p> <p>A fir, 24 ins. diam., bears S. 17 3/4° W., 33.5 ft. dist., with a healed blaze.</p> <p>A cedar snag, 16 ins. diam., bears N. 11° W., 41.2 ft. dist., with scribe marks S 10 visible on an open, weathered blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 2 W 1/4 S 10   S 11 2009</p>

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 89 1/4° E., 32.7 ft. dist., mkd. 1/4 S11 BT.</p> <p>Bury orig. stone alongside, place iron pipe inside, and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 51" E., beginning a new measurement, posting and blazing.</p>										
2120	<p>Gravel road, 12 ft. wide, bears N. 60° E. and S. 60° W.</p>										
2660.66	<p>The cor. of secs. 2, 3, 10, and 11, perpetuated by Byron, Deputy County Surveyor, in 1971, monumented with the remains of the orig. cor. tree, a debarked, sawed fir stump, 36 ins. diam., 5 ft. high, with 5 notches on S. face, 2 notches on E. face, and fragmentary scribe marks visible on decayed and open SW. blaze, with a metal cap, from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 23 ins. diam., bears N. 70° E., 21.1 ft. dist., with scribe marks 30S R2W 2 BT visible on an open blaze.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 32 ins. diam., bears S. 47° W., 23.1 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir snag, 29 ins. diam., bears N. 27° W., 16.5 ft. dist., with scribe marks R2 S3 visible on an open, decayed blaze.</p> <p>At the corner point</p> <p>Sawed the stump of the orig. cor. tree to ground level and drove an aluminum rod, 36 ins. long, 3/4 in. diam., 34 ins. into stump, with an aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 30 S</td> <td style="padding: 0 10px;">R 2 W</td> </tr> <tr> <td style="padding: 0 10px;">S 3</td> <td style="padding: 0 10px;">S 2</td> </tr> <tr> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 10px;"></td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;">S 10</td> <td style="padding: 0 10px;">S 11</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">2009</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 75 1/2° E., 20.4 ft. dist., mkd. T30S R2W S11 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 34 1/4° W., 27.1 ft. dist., mkd. T30S R2W S3 BT.</p> <p>Deposit magnet in a white plastic case under the aluminum cap and alongside the aluminum rod.</p>	T 30 S	R 2 W	S 3	S 2			S 10	S 11	2009	
T 30 S	R 2 W										
S 3	S 2										
S 10	S 11										
2009											

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET

From this cor., a witness cor. to the cor. of secs. 2, 3, 10, and 11, established by Byron, Deputy County Surveyor, in 1971, bears East, 3.00 ft. dist., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T30S R2W  
W S 3 | S 2  
-----  
C S 10 | S 11  
3 FT W. TO  
COR  
1971

from which bearing trees mkd. by Byron

- A sawed, decayed fir stump, size indeterminate, bears N. 44 1/2° E., 63.2 ft. dist., with no marks visible.
- A fir, 18 ins. diam., bears S. 43 1/4° W., 36.1 ft. dist., with scribe mark 3 and other illegible scribe marks visible on a partially healed blaze.
- A decayed fir snag, 13 ins. diam., bears N. 70 1/2° W., 26.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

Corner is located on a N. slope.

From the 1/4 sec. cor. of secs. 2 and 11, perpetuated by the Douglas County Surveyor's Office, in 1968, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 30 S R 2 W  
S 2  
1/4 -----  
S 11  
1968

from which the remains of the orig. bearing trees

- A sawed, decayed fir stump, 21 ins. diam., 5 ft. high, bears S. 61° W., 14.5 ft. dist., with no marks visible on a decayed, open blaze.
- A sawed, decayed fir stump, 26 ins. diam., bears N. 37° W., 21.8 ft. dist., with scribe marks S 2 visible on an open blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office

- A cedar, 14 ins. diam., bears S. 71 1/4° W., 17.3 ft. dist., with a healed double blaze.

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A cedar, 10 ins. diam., bears N. 42 1/2° W., 20.9 ft. dist., with scribe marks S2 CS BT and other fragmentary scribe marks visible on a partially healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 10 ins. diam., bears N. 25 3/4° W., 15.5 ft. dist., mkd. 1/4 S2 BT.</p> <p>Corner is located on a SE. slope.</p> <p>S. 89° 35' 09" W., bet. secs. 2 and 11.</p>
1317.69	<p>Point for the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 2 W 1/16 ——— S 11 2009</p> </div> <p>from which</p> <p>A cedar, 17 ins. diam., bears S. 20° W., 35.8 ft. dist., mkd. W 1/16 S11 BT.</p> <p>A fir, 10 ins. diam., bears N. 55 1/4° W., 18.7 ft. dist., mkd. 1/4 S2 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on an E. slope.</p> <p>Begin posting and blazing.</p>
2635.38	<p>The cor. of secs. 2, 3, 10, and 11.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 15 1/4 ——— S 22 T 30 S R 2 W 1963</p> </div> <p>from which a bearing object mkd. by White in 1963</p>

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A conglomerate boulder, 16 X 15 X 14 ft., bears S. 36 3/4° E., 35.0 ft. dist., mkd. B X O.</p> <p>and a new bearing tree</p> <p>A fir, 10 ins. diam., bears N. 7 1/2° E., 9.0 ft. dist., mkd. 1/4 S15 BT.</p> <p>Corner is located on a SE. slope, in the area affected by the 1962 landslide reported by White.</p> <p>S. 89° 16' 40" W., bet. secs. 15 and 22</p> <p>Ascend over landslide cavity, posting and blazing.</p>
345	<p>West edge of landslide area, edge bears generally N. and S., along a barbed wire fence.</p>
665	<p>From this point, a cedar snag, 10 ins. diam., bears South, 0.5 ft. dist., utilized as the cor. of barb-wire fences extending S., E., and W.</p>
1333.29	<p>The W 1/16 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 15 W 1/16 ——— S 22 T 30 S R 2 W</p> <p>1963</p> </div> <p>from which the remains of bearing trees mkd. by White in 1963</p> <p>A sawed, decayed cedar stump, 26 ins. diam., bears S. 51° E., 91.1 ft. dist., with no marks visible.</p> <p>A fir, 23 ins. diam., bears N. 3 3/4° W., 44.9 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A pine, 8 ins. diam., bears S. 59 1/2° W., 33.0 ft. dist., mkd. W 1/16 S22 BT.</p> <p>Corner is located on a gradual E. slope, 1 ft. N. of a barbed wire fence, bears E. and W.</p> <div style="text-align: center; margin: 10px 0;"> <p>—————</p> </div> <p>S. 89° 14' 33" W., beginning new measurement, posting and blazing.</p> <p>Continuing along said fence.</p>

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET 1331.25	<p>The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, (alongside of which is a granite stone mkd. by Mensch, 14 x 10 x 9 ins., loosely set, projecting 10 ins. above ground, with 3 grooves visible on N. face and a cross on top), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 30 S</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R 3 W</td> </tr> <tr> <td style="padding: 0 5px;">S 16</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 15</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 21</td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-top: 1px solid black; padding: 0 5px;">S 22</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1963</td> </tr> </table> </div> <p>from which the remains of the orig. bearing trees</p> <ul style="list-style-type: none"> <li>A sawed fir stump, 48 ins. diam., bears N. 2° E., 84.5 ft. dist., with a healed blaze.</li> <li>A fir, 70 ins. diam., bears S. 66° E., 80.5 ft. dist., with axe marks visible.</li> <li>A madrone, 54 ins. diam., bears N. 22° W., 166.3 ft. dist., with no marks visible on a hollow blaze.</li> </ul> <p>and the remains of bearing trees mkd. by Mensch in 1909</p> <ul style="list-style-type: none"> <li>A roothole bears N. 41° E., 11.9 ft. dist., alongside of which is a down, decayed, fir stump, 14 ins. diam., with no marks visible.</li> <li>A roothole bears S. 54° W., 6.6 ft. dist.</li> </ul> <p>and bearing trees mkd. by Markham, Jr., Registered Logging Engineer No. 2880, in 1962, reported by White in 1963</p> <ul style="list-style-type: none"> <li>A fir, 27 ins. diam., bears N. 0 1/4° E., 28.4 ft. dist., with a healed blaze.</li> <li>A fir, 22 ins. diam., bears N. 17 1/4° E., 20.5 ft. dist., with no marks visible.</li> <li>A fir, 22 ins. diam., bears N. 62° E., 41.6 ft. dist., with a healed blaze.</li> <li>A cedar, 29 ins. diam., bears N. 50 1/2° W., 7.9 ft. dist., with no marks visible.</li> </ul> <p>and the remains of a bearing tree mkd. by White</p> <ul style="list-style-type: none"> <li>A sawed fir stump, 31 ins. diam., bears S. 32 1/4° W., 99.7 ft. dist., with a healed blaze.</li> </ul> <p>and a new bearing tree</p>	T 30 S	R 3 W	S 16	S 15	S 21	S 22	1963	
T 30 S	R 3 W								
S 16	S 15								
S 21	S 22								
1963									

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">A fir, 5 ins. diam., bears S. 25 3/4° W., 38.2 ft. dist., mkd. T30S R2W S21 BT.</p> <p>Bury Mensch stone alongside the iron post.</p> <p>Corner is located on nearly level ground, 2 ft. S. 45° W. of a wood post at the cor. of barbed wire fences extending N., E., and W.</p> <hr/> <p>N. 0° 35' 55" W., bet. secs. 15 and 16, along a barbed wire fence, posting and blazing.</p>
2545	<p>Ravine, drains N. 80° E.</p>
2674.00	<p>The 1/4 sec. cor of secs. 15 and 16, perpetuated by Markham, Jr. Registered Engineer No. 2880, in 1962, from original evidence no longer in existence, subsequently perpetuated by the Douglas County Surveyor's Office in 1975, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS CO. SURVEYOR T 30 S R 2 W</p> <div style="text-align: center;"> </div> <p style="text-align: center;">1975</p> <p>from which the remains of bearing trees mkd. by Markham, Jr.</p> <p style="padding-left: 40px;">A sawed fir stump, 15 ins. diam., bears N. 79° E., 31.1 ft. dist., with scribe marks 1/4 visible on a partially healed blaze and metal cover.</p> <p style="padding-left: 40px;">A sawed fir stump, 41 ins. diam., bears S. 36° E., 20.2 ft. dist., with a healed blaze and metal cover.</p> <p style="padding-left: 40px;">A cedar, 29 ins. diam., bears S. 33 3/4° W., 40.6 ft. dist., with axe marks visible.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 62° E., 11.2 ft. dist., mkd. 1/4 S15 BT.</p> <p>Corner is located on an E. slope, in a barbed wire fence, bears N. and S.</p> <hr/> <p>N. 0° 09' 19" E., beginning new measurement, posting and blazing.</p> <p>Continue along a barbed wire fence.</p>
30	<p>Broad spur, slopes E.</p>

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
90	Ravine, drains S. 70° E.
2720.62	<p>The cor. of secs. 15 and 16 only, perpetuated by Markham, Jr., Registered Logging Engineer No. 2880, in 1960, subsequently perpetuated by the Douglas County Surveyor's Office in 1975, monumented with the orig. cor. tree, a fir, 22 ins. diam., with numerous healed blazes, wrapped with barbed wire, (alongside of which is an iron pipe, 24 ins. long, 1 1/2 ins. diam., out of the ground), from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 15 ins. diam., bears S. 18° E., 31.6 ft. dist., with no marks visible on a partially healed blaze and metal cover. (Record, S. 22 1/2° E., 33.7 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 38 1/2° W., 26.4 ft. dist., with a healed blaze. (Record, S. 33 1/2° W.)</p> <p>and a bearing tree mkd. by Markham, Jr.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 49° E., 12.9 ft. dist., with no marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears S. 22 1/2° W., 46.8 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p style="padding-left: 40px;">A rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 64° 39' 07" E., 16.00 ft. dist., with an aluminum cap mkd. RM S15 16.0 FT TO COR T30S R2W 2008 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 28° 00' 28" W., 14.00 ft. dist. with an aluminum cap mkd. RM S16 14.0 FT TO COR T30S R2W 2008 and an arrow pointing to the cor..</p> <p>Corner is located at the intersection of barbed wire fences extending S., E., and W.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89° 55' 06" W., bet. secs. 3 and 10, posting and blazing.</p>
1955	Gravel road, 22 ft. wide, bears N. 40° E. and South, in curve.
2645.91	The 1/4 sec. cor. of secs. 3 and 10, perpetuated by Markham, Jr., Registered Logging Engineer No. 2880, in 1960, subsequently perpetuated by the Douglas County Surveyor's Office in 1974, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 1 in. above ground, (with the orig. granite stone, 4 x 6 x 8 ins. (Record, 6 x 8 x 12 ins.) mkd. 1/4 on a face, lying nearby) with brass cap mkd.

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	COUNTY SURVEYORS OFFICE T 30 S S 3 1/4 ——— S 10 R 2 W 1974
	from which the remains of the orig. bearing trees
	A sawed fir stump, 25 ins. diam., bears N. 14 1/2° E., 9.9 ft. dist., with no marks visible and metal cover.
	A sawed, decayed fir stump, size indeterminate, bears S. 42 1/2° E., 19.8 ft. dist., with a healed blaze.
	and bearing trees mkd. by Markham, Jr.
	A fir, 22 ins. diam., bears S. 64 1/4° E., 10.0 ft. dist., with a healed blaze.
	A fir, 23 ins. diam., bears S. 20° W., 15.6 ft. dist., with a healed blaze.
	A roothole bears N. 20 1/4° W., 8.8 ft. dist.
	and a new bearing tree
	A fir, 9 ins. diam., bears N. 51 1/4° W., 16.9 ft. dist., mkd. 1/4 S3 BT.
	Bury orig. stone alongside the iron post.
	<hr style="width: 20%; margin: auto;"/>
	N. 89° 56' 16" W., beginning new measurement, posting and blazing.
2635.33	The cor. of secs. 3, 4, 9, and 10, perpetuated by Markham, Jr., Registered Logging Engineer No. 2880, in 1960, monumented with an iron pipe, 22 ins. long, 1 in. diam., firmly set, projecting 12 ins. above ground, (alongside of which is a portion of the orig. basalt stone, 8 x 7 x 6 ins.) (Record, 15 x 8 x 8 ins.), lying loose on the ground, with 5 notches on one face and 3 notches on an adjacent face), from which the remains of the orig. bearing trees
	A cedar, 11 ins. diam., bears N. 13 1/2° E., 11.2 ft. dist., with a healed blaze.
	A sawed cedar stump, 22 ins. diam., bears S. 36° W., 5.9 ft. dist., with a decayed healed blaze and metal cover.
	A fir, 23 ins. diam., bears N. 23 1/2° W., 11.2 ft. dist., with a healed blaze.
	and bearing trees mkd. by Markham, Jr.

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A madrone, 21 ins. diam., bears N. 78° E., 10.8 ft. dist., with no marks visible on a partially healed blaze.</p> <p>A cedar, 14 ins. diam., bears S. 31 1/2° E., 10.2 ft. dist., with scribe marks R2W S10 BT visible on a partially healed blaze.</p> <p>A cedar, 19 ins. diam., bears N. 36 3/4° W., 20.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 30 S</td> <td style="padding: 0 5px;">R 2 W</td> </tr> <tr> <td style="padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td style="padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td colspan="2" style="text-align: center;">2009</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 9 1/2° W., 31.1 ft. dist., mkd. T30S R2W S9 BT.</p> <p>Bury orig. stone alongside, place iron pipe inside, and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located 1.0 ft. S. 70° E. of a wooden fence post at the cor. of barbed wire fences extending S. and W.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0° 05' 01" W. bet. secs. 3 and 4, posting and blazing.</p> <p>2440 Creek, 2 ft. wide, course S. 80° E.</p> <p>2637.17 The 1/4 sec. cor. of secs. 3 and 4, perpetuated by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T30S R2W</p> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">1/4 S 4</td> <td style="padding: 0 5px;">•</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="3" style="text-align: center;"> </td> </tr> <tr> <td colspan="3" style="text-align: center;">1968</td> </tr> </table> </div> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A sawed cedar stump, 24 ins. diam., bears N. 41° E., 4.6 ft. dist., with no marks visible on a partially healed blaze.</p>	T 30 S	R 2 W	S 4	S 3			S 9	S 10	2009		1/4 S 4	•	S 3				1968		
T 30 S	R 2 W																			
S 4	S 3																			
S 9	S 10																			
2009																				
1/4 S 4	•	S 3																		
1968																				

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET

A sawed cedar stump, 11 ins. diam., bears N. 20° W., 23.1 ft. dist., with scribe marks S4 BT visible on a opened blaze. (Record, N. 9° W.)

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office

A sawed cedar stump, 25 ins. diam., bears N. 62 1/4° E., 20.6 ft. dist., with scribe marks 1/4 S3 visible on an open, weathered blaze.

A fir, 14 ins. diam., bears S. 15 3/4° W., 41.6 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 7 ins. diam., bears N. 66 1/2° E., 24.0 ft. dist., mkd. 1/4 S3 BT.

Corner is located on gentle SE. slope

From the cor. of secs. 9 and 10 only, perpetuated by Markham, Jr., Registered Logging Engineer No. 2880, in 1960, subsequently perpetuated by Douglas County Surveyor's Office in 1975, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, (alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground) with brass cap mkd.

DOUGLAS CO. SURVEYOR  
T 30 S    R 2 W  
S 9    |    S 10  
-----  
          •  
          S15  
          1975

from which the remains of the orig. bearing trees

A sawed fir stump, 46 ins. diam., bears N. 60° E., 17.2 ft. dist., with a healed blaze.

A sawed, decayed cedar stump, 36 ins. diam., bears N. 70° W., 22.4 ft. dist., with a hollow blaze and an X hacked in the bark.

and the remains of bearing trees mkd. by Markham, Jr.

A fir, 21 ins. diam., bears S. 64° W., 21.9 ft. dist., with a healed blaze.

A roothole bears N. 7 1/2° W., 22.1 ft. dist., alongside of which is a down, decayed cedar snag, size indeterminate, with a hollow blaze.

and new bearing trees

**Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 7 ins. diam., bears N. 46 3/4° E., 6.8 ft. dist., mkd. T30S R2W S10 BT.</p> <p>A fir, 6 ins. diam., bears N. 65 3/4° W., 10.4 ft. dist., mkd T30S R2W S9 BT.</p> <p>Corner is located on a broken SE. slope, 0.8 ft. S. of a barbed wire fence line, bears E. and W.</p> <p>S. 89° 56' 23" W., bet. secs. 9 and 15, posting and blazing, along a barbed wire fence.</p>
201.63	<p>The cor. of secs. 15 and 16 only.</p> <hr/> <p>N. 89° 55' 41" W., bet. secs. 9 and 16, posting and blazing, along a barbed wire fence.</p>
2435.32	<p>The 1/4 sec. cor. of sec. 9 only, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">             COUNTY SURVEYORS OFFICE              T 30 S    R 2 W              1/4    S 9              —●—              1968         </p> <p>from which the remains of the orig. bearing trees</p> <p>A roothole bears N. 32° E., 22.4 ft. dist., alongside of which is an uprooted, sawed, fir stump, 36 ins. diam., with no marks visible.</p> <p>A roothole bears N. 84° W., 54.1 ft. dist., alongside of which is a down fir snag, size indeterminate, with a healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyors Office, reported by Saveland in 2008</p> <p>A cedar, 26 ins. diam., bears N. 84 1/2° W., 17.9 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Shaner, Professional Land Surveyor No. 430, in 1980, reported by Saveland</p> <p>A cedar, 11 ins. diam., bears N. 19° W., 32.0 ft. dist., with a healed blaze.</p> <p>Corner is located on a broken NE. slope in a barbed wire fence, bears E. and W.</p> <hr/>

**Subdivision of Section 11,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>From the 1/4 sec. cor. of sec. 11 only, perpetuated by Markham, Jr., Registered Logging Engineer No. 2880, in 1959, monumented with an iron axle rod, 40 ins. long, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with a toothed, iron gear on top, 2 1/2 ins. diam., from which the remains of an orig. bearing tree</p> <p style="padding-left: 40px;">A fir snag, 28 ins. diam., bears N. 50° W., 37.0 ft. dist., with scribe marks 1/4 S11 BT visible on a partially healed blaze.</p> <p>and bearing trees mkd. by Markham, Jr.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 40° E., 5.6 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 27 1/2° W., 21.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A madrone, 19 ins. diam., bears N. 51 3/4° W., 50.5 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 2 W 1/4 S 11 ----- 2009</p> </div> <p>Bury iron axle rod alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., the 1/4 sec. cor. of sec. 14 only, perpetuated by Markham, Jr., Registered Logging Engineer No. 2880, in 1959, bears N. 89° 24' 49" W., 116.03 ft. dist., monumented with an iron rod, 40 ins. long, 3/4 in. diam., firmly set, projecting 9 ins. above ground, (alongside of which is the stone set by Mensch in 1909, 6 x 9 x 12 ins. (Record, 15 x 8 x 6 ins.), with marks 1/4 visible on N. face and cross on top, from which the remains of a bearing tree mkd. by Mensch</p> <p style="padding-left: 40px;">A sawed fir stump, 23 ins. diam., bears S. 26 1/2° W., 41.6 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Markham, Jr.</p> <p style="padding-left: 40px;">A madrone, 15 ins. diam., bears S. 15 3/4° E., 34.6 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A forked fir, 8 ins. diam., bears N. 47° W., 16.9 ft. dist., with a healed blaze.</p>

Subdivision of Section 11,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 2 W ----- 1/4 S14 2009</p> <p>Bury the iron pipe inside, Mensch's stone alongside, and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>N. 0° 06' 15" E., on the N. and S. centerline of sec. 11.</p>
365	Gravel road, 14 ft. wide, bears N 75° E. and S. 75° W.
2655.48	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. centerline, occupied by a hemlock, 17 ins. diam. I mark tree T30S R2W C1/4 S11 on S. face, from which</p> <p style="padding-left: 40px;">A rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 66° 50' 05" W., 13.04 ft. dist. with an aluminum cap mkd. RM C1/4 S11 13.0 FT TO COR 2009 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A rebar, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears N. 21° 47' 13" W., 21.07 ft. dist. with an aluminum cap mkd. RM C1/4 S11 21.1 FT TO COR 2009 and an arrow pointing to the cor.</p>
2785	Dirt road, 16 ft. wide, bears N. 70° W. and S. 70° E.
5296.02	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above the top of a mound of stone 3 1/2 ft. base, 1 1/2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S R 2 W 1/4 S 11   S 12 1968</p> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 18 ins. diam., bears N. 60° E., 16.5 ft. dist., with no marks visible.</p>

**Subdivision of Section 11,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A sawed, decayed fir stump, 19 ins. diam., bears N. 31 1/2° W., 25.1 ft. dist., with scribe marks S11 BT visible on a partially healed, decayed blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office, in 1968, reported by Rogers and Browning in 1998</p> <p>A fir, 22 ins. diam., bears S. 85 3/4° E., 29.7 ft. dist., with a healed blaze.</p> <p>A fir, 25 ins. diam., bears S. 72 1/4° W., 61.1 ft. dist., with a healed blaze.</p> <p>Corner is located on a S. slope.</p> <p>S. 89° 08' 54" W., on the E. and W. centerline of sec. 11.</p>
300	<p>Overgrown dirt road, 9 ft. wide, bears N. 60° W. and S. 60° E.</p>
1319.80	<p>Point for the center E 1/16 sec. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{ --- } \text{C} \\ \text{S } 11 \\ 2009 \end{array}</math> </div> <p>from which</p> <p>A fir, 7 ins. diam., bears N. 8 1/4° E., 18.7 ft. dist., mkd. X BT.</p> <p>A fir, 13 ins. diam., bears S. 60 3/4° E., 24.7 ft. dist., mkd. CE 1/16 S11 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by person(s) unknown bears N. 38° 02' 41" W., 25.35 ft. dist., monumented with a steel saw blade, 1/8 in. thick, 7 ins. wide, loosely set, projecting 4 ft. above ground from which a reference tree mkd. by person(s) unknown</p> <p>A fir, 22 ins. diam., bears N. 68° W., 13.6 ft. dist., with no marks visible and a metal tag mkd. MARKHAM.</p> <p>Begin posting and blazing.</p>
2415	<p>Dirt road, 11 ft. wide, bears N. 20° E. and S. 40° W., in curve.</p>
2639.60	<p>The center 1/4 sec. cor. of sec. 11.</p>
3945	<p>Dirt road, 11 ft. wide, bears N. 10° E. and S. 10° W.</p>

**Subdivision of Section 11,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
3957.42	<p>Point for the center W 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">C \frac{W \ 1/16}{S \ 11} C</math> <p>2009</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 49 1/2° W., 24.2 ft. dist., mkd. CW 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 43° W., 30.7 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established as the center W 1/16 sec. cor. of sec. 11 by Markham, Jr., Registered Engineer No. 2880, in 1960, bears N. 89° 24' 06" E., 65.70 ft. dist., monumented with a threaded iron pipe, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, from which the remains of a bearing tree mkd. by Markham, Jr.</p> <p style="padding-left: 40px;">A fir snag, size indeterminate, bears N. 40° E., 30.7 ft. dist., with scribe marks BT visible on lower blaze of a decayed, partially healed, double blaze.</p> <p>This point was not correctly positioned and is not utilized in the course of this survey.</p> <p>Discontinue posting and blazing.</p>
5275.24	<p>The 1/4 sec. cor. of secs. 10 and 11.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 11.</p> <p>N. 0° 06' 03" E., on the N. and S. centerline of the NW 1/4 of sec. 11, posting and blazing.</p>
2650.60	<p>The W 1/16 sec. cor. of secs. 2 and 11.</p> <hr/>

**T. 30 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;"><b>GENERAL DESCRIPTION</b></p> <p>The lands embraced in the forgoing survey are located in mountainous terrain, approximately 4 miles northerly of Tiller, Oregon.</p> <p>The elevation ranges from about 2000 feet above sea level near the 1/4 section corner of sections 15 and 22, to about 3050 feet above sea level near the corner of sections 2, 3, 10, and 11.</p> <p>The area is drained by Granite Creek, which flows southwesterly into Coffee Creek and Dompier Creek, which flows southeasterly into the South Umpqua River.</p> <p>Timber consists of alder, cedar, chinquapin, fir, madrone, maple, and pine. Undergrowth consists of fern, Oregon grape, salal, and vine maple.</p> <p>The soil is generally composed of rocky clay.</p> <p>Access to the survey was made by various dirt and graveled roads branching from the South Umpqua Highway, County Route No. 1, and County Route No. 46.</p>
------	--