

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION
OF THE SUBDIVISIONAL LINES
AND SUBDIVISION OF SECTION
LINES IN SECTION 26
TOWNSHIP 26 SOUTH, RANGE 3 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated April 21, 2009, approved April 24, 2009,
which provided for the surveys included under Group No. 2273,
and Assignment Instructions dated May 15, 2009.

Survey commenced July 8, 2009

Survey completed November 12, 2009

T. 26 S., R. 3 W., Willamette Meridian, Oregon

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and subdivision of section lines in section 26, T. 26 S., R. 3 W., Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855, Addison R. Flint, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1871, Addison R. Flint and L.L. Williams, U.S. Deputy Surveyors, surveyed a portion of the subdivisional lines.

In 1882, Samuel C. Flint, U.S. Deputy Surveyor, surveyed the remainder of the subdivisional lines.

In 1972-75, Daniel L. Berry, G. Steven Popken, and James J. Carlson, Cadastral Surveyors, resurveyed a portion of the subdivisional lines, and subdivided section 26.

In 1981, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 35.

In 1991-94, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 27.

In 2004, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, retraced a portion of the subdivisional lines.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 21, 2009, for Group No. 2273, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the corner description field notes are given herein.

The direction of the lines refer to the true meridian as determined by Global Positioning System (GPS) measurements carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.2 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer

T. 26 S., R. 3 W., Willamette Meridian, Oregon

software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS)) of the following corners, as determined in a least squares adjusted network of conventional survey control and GPS occupied points, utilizing dual frequency carrier phase GPS receivers, relative to National Spatial Reference System (NSRS) Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP" and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", are as follows:

The 1/4 section corner of sections 24 and 25:

Latitude: 43° 17' 09.13" N. Longitude: 123° 00' 00.17" W.

The corner of sections 25, 26, 35, and 36:

Latitude: 43° 16' 17.52" N. Longitude: 123° 00' 35.72" W.

The 1/4 section corner of sections 23 and 26:

Latitude: 43° 17' 09.70" N. Longitude: 123° 01' 11.87" W.

The 1/4 section corner of sections 26 and 27:

Latitude: 43° 16' 43.62" N. Longitude: 123° 01' 47.71" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S	
S 26	S 25
S 35	S 36
R 3 W	
1966	

from which the remains of the original bearing trees

A fir, 35 ins. diam., bears S. 32° W., 13.2 ft. dist., with a healed blaze.

A sawed fir stump, 43 ins. diam., bears N. 30° W., 21.1 ft. dist., with a healed blaze.

and bearing trees mkd. by Thomas E. Shrum, Jr., Oregon Registered Logging Engineer No. 4287, in 1962, filed in the Douglas County Surveyor's Office, C.S. File No. 51/254, reported by Rogers in 1981

A yew, 9 ins. diam., bears N. 57° E., 27.1 ft. dist., with scribe marks S25 BT visible on a partially healed double blaze.

A maple, 15 ins. diam., bears S. 71° E., 46.2 ft. dist., with a healed double blaze.

A cedar, 28 ins. diam., bears N. 85° W., 30.4 ft. dist., with a healed double blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.

T 26 S	R 3 W
S 23	S 24
S 26	S 25
1972	

from which the remains of bearing trees mkd. by Berry, Carlson, and Popken in 1972-75

- A fir, 59 ins. diam., bears N. 31° E., 8.6 ft. dist., with a healed blaze.
- A hemlock, 22 ins. diam., bears S. 47° E., 14.5 ft. dist., with a healed blaze.
- A hemlock, 20 ins. diam., bears S. 11° W., 31.7 ft. dist., with a healed blaze.
- A roothole bears N. 40° W., 16.5 ft. dist., alongside of which is a fallen, decayed hemlock trunk, size indeterminate, with scribe marks T26S R3W S visible on a wood fragment.

and a bearing tree mkd. by Ronald G. Geisler, Oregon Professional Land Surveyor (PLS) No. 1988, in 1984, filed in the Douglas County Surveyor's Office, C.S. File No. 58/146

- A hemlock, 16 ins. diam., bears N. 14° W., 19.0 ft. dist., with a healed double blaze.
-

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 24 and 25, perpetuated by Karen Reed, Douglas County Surveyor's Office, in 1979, filed in the Douglas County Surveyor's Office, C.S. File No. 60/24, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 20 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS
T 26 S R 3 W
24
1/4 S —
25
1957
OFFICE

from which the remains of the original bearing trees

A fir, 32 ins. diam., bears N. 10° E., 16.9 ft. dist., with a healed blaze. (Record, 15.2 ft.)

A decayed fir stump, size indeterminate, bears S. 10° E., 9.9 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957, filed in the Douglas County Surveyor's Office, C.S. File No. 47/190, reported by Berry, Popken, and Carlson in 1972-75

A fir, 22 ins. diam., bears N. 89° E., 3.3 ft. dist., with a healed double blaze.

A pine, 19 ins. diam., bears S. 78° E., 31.7 ft. dist., with a healed double blaze.

and a bearing tree mkd. by Reed

A cedar, 21 ins. diam., bears S. 33 1/4° W., 73.7 ft. dist., with a healed blaze.

Corner is located 60 ft. W. of a dirt road, 10 ft. wide, bears N. 20° W. and S. 20° E.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S

1/4

S 23 | S 24

R 3 W

1965

from which the remains of an original bearing tree

A decayed cedar stump, 31 ins. diam., bears S. 85° E., 16.5 ft. dist., with axe marks visible.

and the remains of a bearing tree mkd. by Lester E. Calder, Oregon Registered Logging Engineer No. 2149, in 1960, filed in the Douglas County Surveyor's Office, C.S. File No. 51/87, not reported by Berry, Popken, and Carlson in 1972-75

A sawed, decayed fir stump, 48 ins. diam., bears N. 81 1/4° W., 40.7 ft. dist., with no marks visible.

and a bearing tree mkd. by Vernon R. Tracy, Douglas County Surveyor's Office, in 1965, filed in the Douglas County Surveyor's Office, C. S. File No. 54/7, reported by Berry, Popken, and Carlson

A cedar, 29 ins. diam., bears N. 76° E., 44.9 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by Berry, Popken, and Carlson

A fir snag, 20 ins. diam., bears S. 47° W., 13.9 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 17 ins. diam., bears N. 6° W., 32.7 ft. dist., mkd. 1/4 S23 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The N 1/16 sec. cor. of secs. 23 and 24, established by Nick Juliano, Oregon Registered Logging Engineer No. 3449, in 1973, filed in the Douglas County Surveyor's Office, C.S. File No. 55/316-3, and is accepted as the cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.

T 26 S R 3 W
N 1/16 23 | 24
1973

from which the remains of bearing trees mkd. by Juliano

A sawed fir stump, 35 ins. diam., bears N. 75 1/4° E., 45.9 ft. dist., with no marks visible, and a railroad spike driven into the face.

A maple, 22 ins. diam., bears S. 41 3/4° W., 42.5 ft. dist., with a healed blaze.

and a new bearing tree

A cedar, 17 ins. diam., bears S. 50 1/4° E., 12.2 ft. dist., mkd. N 1/16 S24 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The cor. of secs. 13, 14, 23, and 24, perpetuated by Lester E. Calder, Oregon Registered Logging Engineer No. 2149, in 1952, filed in the Douglas County Surveyor's Office, C.S. File No. 41/76, further perpetuated by Vernon R. Tracy, Douglas County Surveyor's Office, in 1965, filed in the Douglas County Surveyor's Office, C.S. File No. 54/7, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S	
S 14	S 13
S 23	S 24
R 3 W	
1965	

from which the remains of the original bearing trees

- A roothole bears N. 70° E., 38.3 ft. dist., alongside of which is a cedar trunk, 15 ins. diam., with no marks visible.
- A broken, decayed cedar stump, size indeterminate, bears S. 82° E., 12.5 ft. dist., alongside of which is a cedar trunk, 35 ins. diam., with axe marks visible.

and bearing trees mkd by Calder

- A fir, 48 ins. diam., bears N. 63 1/2° E., 41.4 ft. dist., with a healed blaze.
- A fir, 40 ins. diam., bears S. 21° W., 57.9 ft. dist., with no marks visible.

and bearing trees mkd. by Tracy

- A hemlock, 25 ins. diam., bears N. 12 1/2° E., 9.8 ft. dist., with a healed double blaze.
- A sawed, decayed cedar stump, 24 ins. diam., bears S. 40° E., 39.3 ft. dist., with no marks visible.
- A sawed fir stump, 27 ins. diam., bears N. 87° W., 31.0 ft. dist., with a healed double blaze.

and a new bearing tree

- A hemlock, 12 ins. diam., bears S. 26 1/2° E., 44.3 ft. dist., mkd. T26S R3W S24 BT.
-

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 26 and 35, perpetuated by Mark F. Smalley, Oregon PLS No. 2354, in 2003, filed in the Douglas County Surveyor's Office, C.S. File No. 65/48-12, monumented with an iron post, 2 1/2 ins. diam., firmly set, buried 20 ins. below the ground, with brass cap mkd.

T 26 S R 3 W
S 26
1/4 ———
S 35
1972

from which the bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A cedar, 33 ins. diam., bears N. 47 3/4° E., 55.1 ft. dist., with a healed blaze.
(Record, N. 53° E., 56.8 ft.)

A cedar, 25 ins. diam., bears S. 83° E., 20.5 ft. dist., with a healed blaze.

and bearing trees mkd. by Smalley

A fir, 17 ins. diam., bears S. 78° W., 34.8 ft. dist., with a healed blaze.

A pine, 13 ins. diam., bears N. 58 1/4° W., 25.3 ft. dist., with a healed blaze.

Corner is located on the E. edge of a dirt road, 15 ft. wide, bears N. 35° E. and S. 25° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.

T 26 S R 3 W
1/4
S 27 | S 26
1972

from which the remains of bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A decayed cedar stump, 15 ins. diam., bears N. 45° E., 24.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

A cedar, 22 ins. diam., bears S. 61° W., 39.6 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 9 ins. diam., bears S. 78 1/4° E., 26.5 ft. dist., mkd. 1/4 S26 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The N 1/16 sec. cor. of secs. 26 and 27, established by Kenneth W. Hoffine, Oregon PLS No. 2291, in 1995, filed in the Douglas County Surveyor's Office, Map File No. M122-80, and is accepted as the cor., monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd.

LONE ROCK TIMBER
N 1/16
S 27 | S 26
1995
PLS 2291

from which bearing trees mkd. by Hoffine

A fir, 21 ins. diam., bears N. 6 1/2° E., 20.4 ft. dist., with a healed blaze.

A fir, 19 ins. diam., bears S. 17 1/2° E., 28.9 ft. dist., with a healed blaze.

Corner is located 52 ft. N. of a graveled road, 12 ft. wide, bears N. 54° W. and S. 54° E.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.

T 26 S	R 3 W
S 22	S 23
— —	
S 27	S 26
1972	

from which bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

- A fir, 25 ins. diam., bears N. 47 1/4° E., 86.5 ft. dist., with a healed blaze. (Record, N. 52° E.)
 - A fir, 23 ins. diam., bears S. 30° E., 15.2 ft. dist., with a healed blaze.
 - A fir, 26 ins. diam., bears S. 85° W., 61.4 ft. dist., with a healed blaze.
 - A fir, 19 ins. diam., bears N. 61° W., 17.8 ft. dist., with a healed blaze.
-

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The E 1/16 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 19 ins. above the ground, with brass cap mkd.

S 23
E 1/16 ———
S 26
1972

from which bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A fir, 22 ins. diam., bears N. 62° E., 31.7 ft. dist., with a healed blaze.

A fir, 24 ins. diam., bears S. 24° W., 25.1 ft. dist., with a healed blaze.

22706

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, buried 16 ins. below the ground, with brass cap mkd.

T 26 S R 3 W
S 23
1/4 ———
S 26
1972

from which the remains of bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A fir, 24 ins. diam., bears N. 26° E., 39.6 ft. dist., with a healed blaze.

A fir snag, 31 ins. diam., bears S. 22° W., 66.7 ft. dist., with a healed blaze.

and a new bearing tree

A cedar, 17 ins. diam., bears S. 8° E., 37.7 ft. dist., mkd. 1/4 S26 BT.

Corner is located on a shallow SW. slope, 9 ft. E. of a graveled road, 12 ft. wide, bears N. 40° W. and S. 55° E.

22707

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 22 and 23, determined at record distance from the remains of bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A sawed cedar stump, 29 ins. diam., bears S. 38° E., 28.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

A fir, 21 ins. diam., bears S. 89° W., 36.3 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 3 W
1/4
S 22 | S 23
2009

from which

A fir, 6 ins. diam., bears N. 6 3/4° E., 42.4 ft. dist., mkd. 1/4 S23 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 17 ins. above the ground, in a collar of stone, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 26 S R 3 W
S 22
1/4 ———
S 27
1959

from which the remains of an original bearing tree

A sawed cedar stump, 25 ins. diam., bears N. 10° W., 22.4 ft. dist., with fragmentary scribe marks visible on an opened blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1959, filed in the Douglas County Surveyor's Office, C.S. File No. 49/48, reported by Rogers in 1991-94

A fir, 21 ins. diam., bears S. 64 1/2° E., 60.7 ft. dist., with a healed double blaze.
(Record, S. 63° E.)

A fir, 26 ins. diam., bears N. 30° W., 26.4 ft. dist., with a healed double blaze.

22709

**Dependent Resurvey of a Portion of the
Subdivision of Section Lines in Section 26,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The center 1/4 sec. cor. of sec. 26, perpetuated by Mark F. Smalley, Oregon PLS No. 2354, in 2003, filed in the Douglas County Surveyor's Office, C.S. File No. 65/48-14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.

T 26 S R 3 W
C 1/4 S 26
1972

from which bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A maple, 13 ins. diam., bears N. 28 1/4° E., 8.3 ft. dist., with a healed blaze.
(Record, N. 19° E., 10.6 ft.)

A fir, 28 ins. diam., bears S. 3 1/2° E., 21.2 ft. dist., with a healed blaze. (Record,
S. 8° E., 19.1 ft.)

and bearing trees mkd. by Smalley

A fir, 20 ins. diam., bears S. 20 3/4° W., 15.1 ft. dist., with a healed blaze.

A maple, 10 ins. diam., bears N. 70 1/2° W., 48.1 ft. dist., with scribe marks
C 1/4 BT visible on a partially healed blaze.

Corner is located 47 ft. S. of a creek, 2 ft. wide, course S. 70° W.

22710

**Dependent Resurvey of a Portion of the
Subdivision of Section Lines in Section 26,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The center N 1/16 sec. cor. of sec. 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, buried 5 ins. below the ground, with brass cap mkd.

C
N 1/16 | S 26
C
1972

from which bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A fir, 23 ins. diam., bears S. 2° E., 32.3 ft. dist., with a healed blaze.

A fir, 19 ins. diam., bears N. 15 1/4° W., 33.0 ft. dist., with a healed blaze. (Record, N. 12° W.)

Corner is located on the N. edge of a dirt road, 12 ft. wide, bears N. 30° E. and S. 30° W.

22711

**Dependent Resurvey of a Portion of the
Subdivision of Section Lines in Section 26,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The center E 1/16 sec. cor. of sec. 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.

E 1/16
C—C
S 26
1972

from which bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A fir, 12 ins. diam., bears N. 14° E., 24.4 ft. dist., with a healed blaze.

A fir, 16 ins. diam., bears S. 15° E., 21.8 ft. dist., with a healed blaze.

22712

**Dependent Resurvey of a Portion of the
Subdivision of Section Lines in Section 26,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The N 1/16 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.

N 1/16
S 26 | S 25
1972

from which bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A fir, 17 ins. diam., bears N. 71° E., 13.2 ft. dist., with a healed double blaze.

A fir, 24 ins. diam., bears S. 73° W., 37.0 ft. dist., with a healed double blaze.

22713

**Dependent Resurvey of a Portion of the
Subdivision of Section Lines in Section 26,
T. 26 S., R. 3 W., Willamette Meridian, Oregon**

The NE 1/16 sec. cor. of sec. 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

NE 1/16 S 26
1972

from which the remains of bearing trees mkd. by Berry, Popken, and Carlson in 1972-75

A fir, 26 ins. diam., bears N. 73° E., 37.6 ft. dist., with a healed blaze.

A sawed fir stump, 18 ins. diam., bears S. 52 3/4° E., 48.2 ft. dist., with a healed blaze. (Record, S. 55° E.)

and a new bearing tree

A fir, 9 ins. diam., bears S. 67 3/4° E., 21.6 ft. dist., mkd. NE 1/16 S26 BT.

T. 26 S., R. 3 W., Willamette Meridian, Oregon**GENERAL DESCRIPTION**

The lands embraced in the foregoing survey are located in mountainous terrain, approximately 4 miles southeasterly of Glide, Oregon.

The elevation ranges from about 1800 feet above sea level near the 1/4 section corner of sections 26 and 35, to about 3100 feet above sea level near the 1/4 section corner of sections 24 and 25.

The area is drained by Engles Creek, Rattlesnake Creek, and Williams Creek, which flow southwesterly into Little River.

Timber consists of alder, cedar, chinquapin, fir, madrone, maple, oak, pine, and yew. Undergrowth consists of fern, Oregon grape, poison oak, salal, and vine maple.

The soil is generally composed of rocky clay. No mineral deposits were noted along the lines surveyed.

Access to the survey was made by graveled roads branching from Douglas County Road No. 17 (Little River Road).