

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF
THE WEST BOUNDARY AND SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTION 19
TOWNSHIP 29 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Kenneth W. Saveland, Cadastral Surveyor

Under Special Instructions dated April 28, 2009, approved April 29, 2009,
which provided for the surveys included under Group No. 2270,
and Assignment Instructions dated May 21, 2009.

Survey commenced May 21, 2009

Survey completed August 27, 2009

T. 29 S., R. 6 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines, and the subdivision of section 19, Township 29 South, Range 6 West, of the Willamette Meridian, Oregon.

A history of surveys pertaining to this survey is as follows:

In 1855, Nathaniel Ford, U.S. Deputy Surveyor, surveyed a portion of the east boundary and subdivisional lines of T. 29 S., R. 7 W., as shown on the official plat of survey approved March 9, 1855.

In 1855, Nathaniel Ford, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines as shown on the official plat of survey approved March 9, 1855, October 1, 1872, and December 16, 1878.

In 1905, Fred Mensch, U.S. Deputy Surveyor, resurveyed a portion of the west boundary and surveyed the remainder of the subdivisional lines as shown on the official plat of survey approved June 29, 1906.

In 1910, Roy T. Campbell, U.S. Deputy Surveyor, retraced a portion of the east boundary and surveyed the remainder of the subdivisional lines of T. 29 S., R. 7 W., as shown on the official plat of survey approved April 5, 1911.

In 1924, Fred Mensch, U.S. Cadastral Engineer, resurveyed a portion of the south and east boundaries and subdivisional lines of T. 29 S., R. 7 W., as shown on the official plat of survey approved February 15, 1926.

In 1957, Hans W. Thielsen, Cadastral Surveyor, resurveyed a portion of the east boundary and subdivisional lines of T. 29 S., R. 7 W., as shown on the plat of survey accepted July 11, 1958.

In 1958-59, Hans W. Thielsen and C. Albert White, Cadastral Surveyors, resurveyed a portion of the south boundary and subdivisional lines as shown on the plat of survey accepted March 1, 1961.

In 1959, Hans W. Thielsen, Cadastral Surveyor, resurveyed a portion of the east boundary and subdivisional lines of T. 29 S., R. 7 W., as shown on the plat of survey accepted February 9, 1961.

In 1980, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the south and west boundaries and subdivisional lines, and subdivided section 31, as shown on the plat of survey accepted May 11, 1984.

In 1990, Wayne L. Rogers and Bryan S. Seibold, Cadastral Surveyors, correctively resurveyed a portion of the subdivisional lines, resurveyed a portion of the subdivisional lines, and subdivided sections 21 and 27, as shown on the plat of survey accepted March 21, 1994.

In 1991, Robert J. Chappel, Cadastral Surveyor, resurveyed a portion of the west boundary, subdivisional lines, and donation land claim boundaries, and subdivided sections 7 and 9, as shown on the plat of survey accepted September 30, 1992.

T. 29 S., R. 6 W., Willamette Meridian, Oregon

FEET

In 2002, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, remonumented and rehabilitated certain corner points on the east boundary and subdivisional lines of T. 29 S., R. 7 W., as shown in the field notes approved November 3, 2004.

The following plats and field notes, filed in the Douglas County Surveyor's Office, are referred to in subsequent corner descriptions and are referenced by surveyor's last name, title or registration number, and year. The dates listed below are either the date on which the survey was filed or the date indicated on the plat or field notes.

<u>Date</u>	<u>Name and Title or Registration No.</u>	<u>File No.</u>
3/09/1918	F. C. Frear, Deputy County Surveyor	Vol. 1, pg. 9
5/1934	Ben B. Irving, Deputy County Surveyor	M 1-27
4/1962	James W. Byron, Deputy County Surveyor	CS 49/139
1/24/1974	R. H. Gee, RE 3723	M 52-25
9/11/1989	Howard W. Johnstone, PLS 498	M 101-60
12/28/1989	Howard W. Johnstone, PLS 498	M 101-73

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 28, 2009, for Group No. 2270, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the corner description field notes are given herein.

The direction of the lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) measurements.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.13 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

The geographic position (NAD 1983 (CORS)) of the 1/4 section corner of secs. 19 and 20, as determined by direct occupation utilizing dual frequency, carrier phase GPS receivers, using for control the National Spatial Reference System Continuously Operating Reference Station (CORS)

T. 29 S., R. 6 W., Willamette Meridian, Oregon

FEET

“DODSON BUTTE CORS ARP”, and National Cooperative CORS Network Station “ROSEBURG COOP CORS ARP”, is as follows:

Latitude: 43° 02' 06.175" N. Longitude: 123° 26' 35.091" W.

The geographic position (NAD 1983 (CORS)) of the corner of sections 25, 30, 31, and 36, on the west boundary of the township, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control the National Spatial Reference System CORS “DODSON BUTTE CORS ARP”, and National Cooperative CORS Network Station “ROSEBURG COOP CORS ARP”, is as follows:

Latitude: 43° 00' 48.89" N. Longitude: 123° 27' 52.85" W.


Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

Restoring the 1855 survey by Nathaniel Ford, the 1905 resurvey and survey by Fred Mensch, the 1910 survey by Roy T. Campbell, the 1924 resurvey by Fred Mensch, the 1957 resurvey by Hans W. Thielsen, the 1958-59 resurvey by Hans W. Thielsen and C. Albert White, the 1959 resurvey by Hans W. Thielsen, the 1980 resurvey by Wayne L. Rogers, the 1990 resurvey by Wayne L. Rogers and Brian S. Seibold, the 1991 resurvey by Robert J. Chappel, and the 2002 remonumentation and rehabilitation by Timothy J. Moore and Robert H. Browning

Beginning at the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE



from which the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1952, reported by Moore and Browning

A decayed fir snag, size indeterminate, bears S. 89 1/2° E., 19.1 ft. dist., with scribe marks 30 29 BT visible on bark of healed double blazes. (Record, S. 89 1/2° W.)

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>A sawed, decayed fir stump, 26 ins. diam., bears S. 56° E., 71.9 ft. dist., with scribe marks BT visible on bark.</p> <p>and the remains of bearing trees mkd. by Rogers</p> <p>A fir snag, 16 ins. diam., bears N. 79° E., 32.0 ft. dist., with a healed blaze.</p> <p>A fir, 13 ins. diam., bears S. 27° W., 24.4 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears N. 63° W., 38.3 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Moore and Browning</p> <p>A fir, 15 ins. diam., bears S. 77° E., 48.8 ft. dist., with scribe marks T29S R6W S31 BT visible on a partially healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 15 ins. diam., bears N. 72° E., 17.2 ft. dist., mkd. T29S R6W S30 BT.</p> <p>Corner is located S., 1 ft. dist. from a wood fence post at the cor. of woven wire fences extending N. and W., on a gradual N. slope.</p> <p>N. 2° 43' 41" E., bet. secs. 25 and 30, on the W. bdy. of the Tp., along a woven wire fence, posting and blazing.</p> <p>1349.81 The S 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., established by Gee, Registered Engineer No. 3723, in 1974, and is accepted as the cor., monumented with a rebar, 5/8 in. diam., firmly set, projecting 7 ins. above ground.</p> <p>At the corner point</p> <p>Place an aluminum cap on the existing rebar, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 1/16 S 25 S 30 2009</p> </div> <p>from which new bearing trees</p> <p>A fir, 18 ins. diam., bears N. 87 3/4° E., 22.8 ft. dist., mkd. S 1/16 S30 BT.</p> <p>A fir, 18 ins. diam., bears S. 31 1/2° W., 16.1 ft. dist., mkd. S 1/16 S25 BT.</p> <p>Corner is located E., 1.5 ft. dist. from a barbed and woven wire fence extending N. 3° E. and S. 3° W.</p> <hr style="width: 20%; margin: 10px auto;"/>
------	---

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>N. 2° 42' 11" E., beginning a new measurement.</p>
1280.00	<p>From this point, a point established by person(s) unknown bears East, 0.67 ft. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 6 ins. above ground, in a woven wire fence line, and is not utilized in the course of this survey.</p>
1344.75	<p>The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., perpetuated by Irving, Deputy County Surveyor, in 1934, subsequently perpetuated by Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above ground, (lying loose nearby is the fractured original basalt stone, 13 x 9 x 6 ins., with marks 1/4 visible on a face and a cross on top), with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 1/4 R 7 S 25 S 30 6 W 1962 W</p> </div> <p>from which the remains of a bearing tree mkd. by Mensch</p> <p style="padding-left: 40px;">A roothole bears S. 60° E., 11.6 ft. dist.</p> <p>and the remains of a bearing tree mkd. by Irving</p> <p style="padding-left: 40px;">A roothole bears S. 80° W., 15.4 ft. dist.</p> <p>and the remains of a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A sawed fir stump, 31 ins. diam., bears N. 48 1/4° E., 70.9 ft. dist., with a healed blaze and axe marks.</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 30 1/4° W., 115.8 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 87 1/2° E., 51.2 ft. dist., mkd. 1/4 S30 BT.</p> <p>Bury the original stone alongside the iron post.</p> <p>The cor. is located in a barbed and woven wire fence extending N. 3° E. and S. 3° W., on a N. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3° 25' 44" E., beginning a new measurement.</p>
10	<p>Ravine, drains N. 65° W.</p>
623.73	<p>From this point, a corner established by Gee, Registered engineer No. 3723, in 1974, bears West, 4.70 ft. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 10 ins. above ground. This cor. was not correctly positioned and is not utilized in the course of this survey.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

<p>FEET 1246.81</p>	<p>The N 1/16 sec. cor. of secs. 30 only, on the W. bdy. of the Tp., established by Gee, Registered Engineer No. 3723, in 1974, and is accepted as the cor., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground.</p> <p>At the corner point</p> <p>Place an aluminum cap on the existing rebar, mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \text{ N } 1/16 \\ \text{ S } 30 \\ \hline 2009 \end{array}$ </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 84 3/4° E., 31.9 ft. dist., mkd. N 1/16 S30 BT.</p> <p style="margin-left: 40px;">An oak, 8 ins. diam., bears S. 25° E., 43.2 ft. dist., mkd. N 1/16 S30 BT.</p> <p>Corner is located N. 7 3/4° E., 35.6 ft. dist. from a wood post at the intersection of barbed and woven wire fences extending N. 3° E., S. 3° W., and West, on a W. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3° 31' 55" E., beginning a new measurement.</p>
<p>52.85</p>	<p>Point for the N 1/16 sec. cor. of sec. 25 only, on the W. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \text{ N } 1/16 \\ \text{ S } 25 \\ \hline 2009 \end{array}$ </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears S. 23 3/4° W., 30.0 ft. dist., mkd. N 1/16 S25 BT.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 73° W., 16.4 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
<p>1248.26</p>	<p>The cor. of secs. 19 and 30 only, perpetuated by person(s) unknown, recovered by Ben B. Irving, Deputy County Surveyor, in 1934, perpetuated by Byron, Deputy County Surveyor, in 1962, and is accepted as the best available evidence of the original cor. position, monumented with a yew fence post, 5 ft. high, 6 ins. diam., (an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>above ground, with a brass cap mkd. COUNTY SURVEYORS OFFICE T29S R6W R7W S19 S30 1962 bears West, 0.6 ft. dist.)</p> <p>from which a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A myrtle, 11 ins. diam., bears N. 14 1/4° E., 43.3 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A maple, 9 ins. diam., bears S. 31 1/4° E., 75.0 ft. dist., mkd. T29S R6W S30 BT.</p> <p>Corner is the fence post at intersection of barbed and woven wire fence lines extending S. 3° W. and E.</p> <hr/> <p>N. 0° 26' 34" E., bet. secs. 19 and 25, on the W. bdy. of the Tp.</p>
65	<p>Rice Creek, 8 ft. wide, course East.</p>
104.19	<p>The closing cor. of secs. 24 and 25 only, on the W. bdy. of the Tp., perpetuated by Byron, Deputy County Surveyor, in 1962, from original evidence no longer in existence, subsequently perpetuated by Johnstone, Professional Land Surveyor (PLS) No. 498, in 1989, monumented with an iron post, 36 ins. long, 1 1/4 ins. diam., firmly set, bent S., projecting 20 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> COUNTY SURVEYORS OFFICE T 29 S R S 24 R 7 ——— 6 W S 25 C.C. W 1962 </p> <p>from which a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears S. 61 1/4° W., 22.6 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Johnstone</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears N. 55 1/4° W., 202.3 ft. dist., with a healed blaze.</p> <p>Reset iron post, 36 ins. long, 33 ins. in the ground.</p> <p>Corner is located S., 170 ft. dist. from Rice Creek Road, asphalt surfaced, 23 ft. wide, bears N. 65° E. and S. 65° W., at the intersection of a barbed and woven wire fence extending N. with a broken down barbed wire fence extending W.</p> <hr/>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>From the 1/4 sec. cor. of sec. 19 only, on the W. bdy. of the Tp., reestablished by proportionate measurement by Johnstone, PLS No. 498, in 1989; there is no remaining evidence of the original cor., therefore this position is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 13 ins. above ground, with an aluminum cap mkd.</p> <p align="center">T 29 S R.R. CO. R 6 W 1/4 SEC 19 ONLY LS 498 1989</p> <p>from which bearing trees mkd. by Johnstone</p> <p>A fir, 13 ins. diam., bears N. 26 3/4° E., 13.1 ft. dist., with a healed blaze.</p> <p>A madrone, 36 ins. diam., bears S. 76 1/4° E., 3.1 ft. dist., with scribe marks 19 T visible on a partially healed blaze.</p> <p>Corner is located E., 2.0 ft. from a broken down woven wire fence extending N. and S., on a gradual E. slope</p> <p>N. 0° 02' 49" W., bet. secs. 19 and 24.</p>
104.18	<p>The 1/4 sec. cor. of sec. 24 only, on the W. bdy. of the Tp., reestablished by proportionate measurement by Johnstone, PLS No. 498, in 1989; there is no remaining evidence of the original cor., therefore this position is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 17 ins. above ground, with an aluminum cap mkd.</p> <p align="center">T 29 S R.R. CO. R 7 W 1/4 SEC 24 ONLY LS 498 1989</p> <p>from which bearing trees mkd. Johnstone</p> <p>A fir, 12 ins. diam., bears S. 32 1/2° W., 3.3 ft. dist., with a healed blaze.</p> <p>A fir, 26 ins. diam., bears N. 52 1/4° W., 5.7 ft. dist., with a healed blaze.</p> <hr/> <p>N. 0° 02' 06" W., bet. secs. 19 and 24, along a broken down barbed and woven wire fence.</p>
1217.37	<p>Point for the N 1/16 sec. cor. of sec. 19 only, on the W. bdy. of the Tp.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

<p>FEET</p>	<p>Drive a rebar, 30 ins. long, 5/8 in. diam., 22 ins. in the ground, with an aluminum cap mkd.</p> <p style="text-align: center;"> N 1/16 S 19 2009 </p> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 72 1/2° E., 13.0 ft. dist., mkd. N 1/16 S19 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 59° E., 23.4 ft. dist., mkd. X BT, with a Mag-nail driven at the base on left side center.</p> <p>Corner is located immediately N. of a burnt, hollow, sawed, cedar stump, 44 ins. diam., on a gradual N. slope.</p> <p>From this cor., a wood post at the cor. of a broken down barbed wire fence bears N. 61 1/4° E., 29.4 ft. dist., with wire extending N. and E.</p> <p>1321.60 The N 1/16 sec. cor. of sec. 24 only, on the W. bdy. of the Tp., established by Johnstone, PLS No. 498, in 1989, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 13 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;"> T 29 S R.R. CO. R 7 W N 1/16 SEC 24 LS 498 1989 </p> <p>from which bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 64° W., 16.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 11 1/4° W., 6.7 ft. dist., with a healed blaze.</p> <p>Corner is located on a gradual N. slope.</p> <p style="text-align: center;">_____</p> <p>N. 0° 01' 59" W., beginning a new measurement.</p> <p>350 Gravel road, 15 ft. wide, bears N. 75° E. and S. 80° W., in curve.</p> <p>1217.33 The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p>
-------------	--

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET													
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 29 S</td></tr> <tr><td>R 7 W</td><td>R 6 W</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2">1957</td></tr> </table> </div> <p>from which the remains of bearing trees mkd. by Campbell</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 15 1/2° E., 17.2 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, size indeterminate, bears S. 44 1/2° W., 17.8 ft. dist., with fragmentary scribe marks visible on an open, decayed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 17 ins. diam., bears N. 52° W., 7.9 ft. dist., with scribe marks 13 visible on a partially healed blaze.</p> <p>and the remains of bearing trees mkd. by Thielsen in 1957</p> <p style="padding-left: 40px;">A decayed fir stump, 22 ins. diam., bears N. 45° E., 47.5 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A madrone, 25 ins. diam., bears S. 82° E., 62.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 47° W., 93.5 ft. dist., with a healed blaze. (Record, 91.7 ft. dist.)</p> <p>and bearing trees mkd. by Johnstone, PLS No. 498, in 1989, reported by Rogers and Seibold</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 81 1/2° E., 13.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 53° W., 7.9 ft. dist., with a healed blaze.</p> <p>Corner is located S. 20° E., 4.7 ft. dist. from a wood post at the intersection of barbed and woven wire fences extending N. 2° W. and N. 88° W.</p> <hr/> <p>N. 1° 58' 15" W., bet. secs. 13 and 18, on the W. bdy. of the Tp., posting and blazing.</p> <p>370 Porter Creek Road, dirt, 7 ft. wide, bears N. 60° E. and S. 60° W.</p> <p>2535.26 The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., determined at record bearing and dist. from the remains of the bearing trees mkd. by Thielsen</p>	T 29 S		R 7 W	R 6 W	S 13	S 18	<hr/>		S 24	S 19	1957	
T 29 S													
R 7 W	R 6 W												
S 13	S 18												
<hr/>													
S 24	S 19												
1957													

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>A sawed fir stump, 6 ft. high, 21 ins. diam., bears S. 89° E., 62.7 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 29 ins. diam., bears N. 19° W., 53.5 ft. dist., with scribe marks 1/4 S13 BT visible on a partially opened blaze.</p> <p>Thielsen's iron post, 36 ins. Long, 1 in. diam., was found lying loose on the ground nearby, in an unrelated position.</p> <p>At the corner point</p> <p>Reset the iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, and add marks 2009 to the brass cap to now read</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">1/4</td><td></td></tr> <tr><td style="text-align: center;">S 13</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 18</td></tr> <tr><td style="text-align: center;">R 7 W</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 6 W</td></tr> <tr><td></td><td style="text-align: center;">T 29 S</td><td></td></tr> <tr><td></td><td style="text-align: center;">2009</td><td></td></tr> <tr><td></td><td style="text-align: center;">1957</td><td></td></tr> </table> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 58 1/4° E., 23.6 ft. dist., mkd. 1/4 S18 BT.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 9 1/2° W., 13.4 ft. dist., mkd. 1/4 S13 BT.</p> <p>Corner is located in a barbed and woven wire fence extending N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2° 04' 25" W., beginning a new measurement.</p>		1/4		S 13		S 18	R 7 W		R 6 W		T 29 S			2009			1957	
	1/4																		
S 13		S 18																	
R 7 W		R 6 W																	
	T 29 S																		
	2009																		
	1957																		
2528.62	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">T 29 S</td><td></td></tr> <tr><td style="text-align: center;">R 7 W</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 6 W</td></tr> <tr><td style="text-align: center;">S 12</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="3" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 13</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 18</td></tr> <tr><td></td><td style="text-align: center;">1957</td><td></td></tr> </table> </div> <p>from which bearing trees mkd. by Thielsen in 1957</p> <p style="margin-left: 40px;">A maple, 15 ins. diam., bears N. 80° E., 71.9 ft. dist., with no marks visible on a hollow, partially healed blaze.</p> <p style="margin-left: 40px;">A maple, 24 ins. diam., bears S. 42 1/2° E., 89.1 ft. dist., with scribe marks 7W S1 visible on a partially opened blaze.</p> <p>and bearing trees mkd. Chappel</p>		T 29 S		R 7 W		R 6 W	S 12		S 7	-----			S 13		S 18		1957	
	T 29 S																		
R 7 W		R 6 W																	
S 12		S 7																	

S 13		S 18																	
	1957																		

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET

A fir, 16 ins. diam., bears S. 36 1/2° W., 13.5 ft. dist., with a healed blaze.


A madrone, 10 ins. diam., bears N. 10° W., 23.1 ft. dist., with scribe marks BT visible on bark.

Corner is located at the intersection of broken down barbed and woven wire fences extending S. and W., in a shallow draw, drains N. 40° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

Restoring the 1855 survey by Nathaniel Ford, the 1905 resurvey and survey by Fred Mensch, the 1958-59 resurvey by Hans W. Thielsen and C. Albert White, the 1990 resurvey by Wayne L. Rogers and Brian S. Seibold, and the 2002 remonumentation and rehabilitation by Timothy J. Moore and Robert H. Browning

From the cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.



from which the remains of bearing trees mkd. by Mensch

A decayed fir stump, size indeterminate, bears N. 20 1/2° E., 11.8 ft. dist., with no marks visible.

A sawed fir stump, 24 ins. diam., bears S. 31° E., 41.6 ft. dist., with a healed blaze.

A fir, 29 ins. diam., bears S. 20° W., 33.0 ft. dist., with a healed blaze.

and the remains of bearing trees mkd. by Thielsen and White

A sawed fir stump, 26 ins. diam., bears N. 22 3/4° E., 24.4 ft. dist., with a healed blaze.

A fir, 30 ins. diam., bears N. 22 1/2° W., 60.1 ft. dist., with a healed blaze.

and a bearing tree mkd. by Rogers and Seibold

A fir, 13 ins. diam., bears S. 13° E., 13.8 ft. dist., with a healed blaze. (Record, 14.2 ft. dist.)

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	<p>and a bearing tree mkd. by Moore and Browning</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 25° E., 38.7 ft. dist., with a healed double blaze.</p> <p>Corner is located W., 2.5 ft. dist. from the cor. of broken down barbed and woven wire fences extending N., E., and W., on a N. slope.</p> <p>S. 88° 56' 03" W., bet. secs. 19 and 30.</p>
1328.15	<p>The E 1/16 sec. cor. of secs. 19 and 30, established by Frear, Deputy County Surveyor, in 1918, and is accepted as the cor., monumented with an iron pipe, 2 in. diam., firmly set, projecting 12 ins. above ground, with a smashed top, from which the remains of bearing trees mkd. by Frear</p> <p style="padding-left: 40px;">A roothole bears N. 42 1/4° E., 13.8 ft. dist.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 81° W., 17.4 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 19 E 1/16 ——— S 30 2009</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 0 1/4° W., 55.0 ft. dist., mkd. E1/16 S30 BT.</p> <p>Bury the iron pipe, 28 ins. long, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 53' 00" W., beginning a new measurement.</p> <p>Begin posting and blazing.</p>
1331.25	<p>The 1/4 sec. cor. of secs. 19 and 30, perpetuated by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, (alongside of which is a portion of Mensch's basalt stone, 9 x 6 x 5 ins., (Record, 12 x 8 x 6 ins.), loosely set, with an incomplete 4 mark visible on a face) with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T 29 S R 6 W S 19 1/4 _____ S 30 1962</p> <p>from which the remains of bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A roothole bears N. 72° E., 17.2 ft. dist.</p> <p style="padding-left: 40px;">A madrone, 39 ins. diam., bears S. 3° E., 21.8 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A madrone, 22 ins. diam., bears N. 78 3/4° E., 50.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 20 ins. diam., bears S. 29 3/4° W., 49.4 ft. dist., with a healed blaze.</p> <p>Bury remains of Mensch's basalt stone alongside the iron post.</p> <hr/> <p style="text-align: center;">Subdivision of Section 19, T. 29 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 35' 58" W., on the N. and S. centerline of sec. 19, posting and blazing.</p> <p>1245 Dirt road, 9 ft. wide, bears N. 80° E. and S. 80° W.</p> <p>1302.01 Point for the center S 1/16 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 19 C 2009</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 87 1/4° E., 6.9 ft. dist., mkd. CS 1/16 S19 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 33° W., 18.0 ft. dist., mkd. X BT.</p>

Subdivision of Section 19,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on a steep N. slope.</p> <p>Discontinue posting and blazing.</p>
1375	Rice Creek Road, asphalt surfaced, 25 ft. wide, bears N. 65° E. and S. 65° W.
2550	Overgrown road, 11 ft. wide, bears East and West.
2604.02	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. centerline of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 6 W C 1/4 S 19 2009</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 11° E., 24.8 ft. dist., mkd. C 1/4 S19 BT.</p> <p style="padding-left: 40px;">A cedar, 26 ins. diam., bears N. 63 1/4° W., 17.7 ft. dist., mkd. C 1/4 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on a gradual S. slope.</p>
3919.29	<p>Point for the center N 1/16 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 19 C 2009</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 68° E., 38.3 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 42 1/4° W., 16.2 ft. dist., mkd. CN 1/16 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Subdivision of Section 19,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
3965	<p>Corner is located on a S. slope.</p> <p>Intersect broken down woven wire fence line with the fence posts removed, bears E. and W.</p>
5234.56	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with a threaded iron rod, 5/8 in. diam., firmly set, projecting 11 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R.R. CO. R 6 W 1/4 S S 18 <hr style="width: 20%; margin: auto;"/>S 19 1989 LS 498</p> <p>from which bearing trees mkd. by Johnstone, PLS No. 498, in 1989, reported by Rogers and Seibold</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 86° E., 25.7 ft. dist., with a healed blaze. (Record, N. 89° E.)</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears S. 14° E., 36.3 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 10 3/4° W., 29.0 ft. dist., with a healed blaze. (Record, S. 13° W.)</p> <p style="margin-left: 40px;">A maple, 18 ins. diam., bears N. 45° W., 3.3 ft. dist., with a healed blaze.</p> <p>Corner is located on an E. slope.</p> <hr style="border: 0.5px solid black;"/> <p>From the 1/4 sec. cor. of secs. 19 and 20, monumented with a threaded iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R.R. CO. R 6 W 1/4 S S 19 S 20 1989 LS 498</p> <p>from which the remains of a bearing tree mkd. by Mensch</p> <p style="margin-left: 40px;">A roothole bears N. 53° W., 17.8 ft. dist., alongside of which is an uprooted, decayed chinquapin stump, size indeterminate, with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Cain, Deputy County Surveyor, in 1914, reported by Rogers and Seibold</p>

**Subdivision of Section 19,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A roothole bears S. 52° E., 37.6 ft. dist.</p> <p>and the remains of bearing trees mkd. by Johnstone, PLS No. 498, in 1989, reported by Rogers and Seibold</p> <p>A sawed fir stump, 13 ins. diam., bears N. 75 1/2° E., 6.6 ft. dist., with no marks visible.</p> <p>A fir, 16 ins. diam., bears S. 22 1/2° W., 10.2 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 9 ins. diam., bears North, 13.2 ft. dist., with no marks visible.</p> <p>and a new accessory</p> <p>A rebar, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears S. 50° 02' 58" E., 15.02 ft. dist. with aluminum cap mkd. RM 1/4 S20 15.0 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>Corner is located N., 105 ft. dist. from a dirt road, 9 ft. wide, bears N. 65° W. and S. 70° E., in curve.</p> <p>N. 89° 58' 17" W., on the E. and W. centerline of sec. 19.</p>
145	Dirt road, 9 ft. wide, bears N. 50° W. and S. 50° E.
250	Creek, 4 ft. wide, course N. 30° W.
1342.78	<p>The center E 1/16 sec. cor. of sec. 19, established by Johnstone, PLS No. 498, in 1989, and is accepted as the cor., monumented with a threaded iron rod, 5/8 in. diam., firmly set, projecting 13 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R.R. CO. R 6 W CE 1/16 S 19 1989 LS 498</p> <p>from which bearing trees mkd. by Johnstone</p> <p>An alder, 16 ins. diam., bears S. 50 1/4° E., 136.3 ft. dist., with scribe marks CE 1/16 BT visible on a partially healed blaze and a brass washer stamped RLS 498 in the center of the blaze.</p> <p>A fir, 38 ins. diam., bears N. 22 3/4° W., 181.0 ft. dist., with a healed blaze.</p> <p>Corner is located N., 17 ft. dist. from Rice Creek, 4 ft. wide, course S. 75° E.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

**Subdivision of Section 19,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	S. 89° 59' 57" W., beginning a new measurement.
1340.79	The center 1/4 sec. cor. of sec. 19.
4155.92	The 1/4 sec. cor. of sec. 19 only, on the W. bdy. of the Tp.
	<hr/> <p>From the NE 1/16 sec. cor. of sec. 19, determined at record bearing and distance from the remains of bearing trees mkd. by Johnstone, PLS No. 498, in 1989, and is accepted as the cor., from which the remains of bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A fir snag, 6 ins. diam., bears S. 30° E., 10.2 ft. dist., with scribe marks NE 1/16 visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 77° W., 2.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 19 2009</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 20 1/2° E., 19.1 ft. dist., mkd. NE 1/16 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by person(s) unknown bears N. 63° 42' 00" E., 61.72 ft. dist., monumented with an iron pipe, 36 ins. long, 1 1/2 ins. diam., wired to a wooden fence post, with the base of the pipe resting on top of the ground, at the intersection of a barbed and woven wire fence extending W., with a broken down barbed and woven wire fence extending N. This point is not utilized during the course of this survey.</p> <p>From this same cor., the N 1/16 sec. cor. of secs. 19 and 20 bears S. 89° 52' 19" E., 1335.58 ft. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 19 20 T29S R6W 1990 1958</p> <p>from which the remains of bearing trees mkd. by Johnstone, PLS No. 498, reported by Rogers and Seibold</p>

**Subdivision of Section 19,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A triple maple, 14 ins. diam., bears S. 11° E., 66.0 ft. dist., with scribe marks /16 T and other fragmentary scribe marks visible on a partially healed blaze.</p> <p>A sawed cottonwood stump, 45 ins. diam., bears N. 29 3/4° W., 146.5 ft. dist., with no marks visible.</p> <p>and a new accessory</p> <p>A rebar, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears S. 68° 23' 29" W., 15.00 ft. dist. with aluminum cap mkd. RM N 1/16 S19 15.0 FT TO COR and an arrow pointing to the cor.</p> <p>Add a collar of stone around iron post.</p> <p>N. 0° 51' 22" W., on the N. and S. centerline of the NE 1/4 of sec. 19, posting and blazing.</p>
30	Barbed and woven wire fence line, bears E. and W.
215	Ravine, drains S. 75° E.
1025	Ravine, drains S. 45° E.
1313.00	<p>The E 1/16 sec. cor. of secs. 18 and 19, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 13 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R.R. CO. R 6 W E 1/16 S 18 S 19 1989 LS 498</p> <p>from which the remains of bearing trees mkd. by Johnstone, PLS No. 498, in 1989, reported by Rogers and Seibold</p> <p>A sawed fir stump, 10 ins. diam., bears N. 47° E., 36.6 ft. dist., with a healed blaze. (Record, 39.6 ft. dist.)</p> <p>A sawed fir stump, 18 ins. diam., bears S. 75° E., 18.5 ft. dist., with no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 20 ins. diam., bears S. 44° W., 30.6 ft. dist., mkd. E 1/16 S19 BT.</p> <p>A cedar, 18 ins. diam., bears N. 69° W., 19.9 ft. dist., mkd. E 1/16 S18 BT.</p> <hr style="width: 60%; margin-left: 0;"/>

Subdivision of Section 19,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

FEET	<p>From the NE 1/16 sec. cor. of sec. 19</p> <p>N. 89° 50' 35" W., on the E. and W. centerline of the NE 1/4 of sec. 19, posting and blazing.</p>
1333.77	<p>The center N 1/16 sec. cor. of sec. 19.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 01' 19" W., on the N. and S. centerline of the SE 1/4 of sec. 19, posting and blazing.</p>
90	<p>Ravine, drains N. 65° E.</p>
1282.32	<p>The SE 1/16 sec. cor. of sec. 19, established by Frear, Deputy County Surveyor, in 1918, perpetuated by person(s) unknown, and is accepted as the cor., monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of a bearing tree mkd. by Frear</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 37 ins. diam., bears S. 68° W., 21.8 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Place an aluminum cap on the existing rebar, mkd.</p> <p style="text-align: center;">SE 1/16 S 19 2009</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 39 1/2° W., 27.8 ft. dist., mkd. SE 1/16 S19 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 75° W., 14.6 ft. dist., mkd. X BT.</p> <p>Corner is located W., 10 ft. dist. from a gravel road, 12 ft. wide, bears N. 30° W. and S. 30° E., alongside a gate post.</p> <p>From this cor., the S 1/16 sec. cor. of secs. 19 and 20 bears N. 88° 52' 04" E., 1327.72 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, driven inside an iron pipe, 2 ins. diam., with an aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R.R. CO. R 6 W S 1/16 S 19 S 20 1989 LS 498</p> <p>from which a bearing tree mkd. by Thielsen and White</p>

**Subdivision of Section 19,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 19 ins. diam., bears N. 73° W., 38.9 ft. dist., with a healed blaze. and a bearing tree mkd. by Johnstone, PLS No. 498, in 1989, reported by Rogers and Seibold</p> <p style="text-align: center;">A fir, 19 ins. diam., bears N. 75° E., 29.7 ft. dist., with a healed blaze. Corner is located S. 80° W., 2.0 ft. dist., from a wood fence post at the intersection of broken down barbed and woven wire fences, extending N., S., and W., on a S. slope.</p> <p style="text-align: center;">S. 89° 43' 50" W., on the E. and W. centerline of the SE 1/4 of sec. 19.</p>
1344.06	<p>The center S 1/16 sec. cor. of sec. 19.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 19.</p> <p>N. 89° 52' 15" W., on the E. and W. centerline of the NW 1/4 of sec. 19, posting and blazing.</p>
2802.02	<p>The N 1/16 sec. cor. of secs. 19 only, on the W. bdy. of the Tp.</p> <hr/>