

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTION 15,
TOWNSHIP 29 SOUTH, RANGE 7 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Kenneth W. Saveland, Cadastral Surveyor

Under Special Instructions dated April 28, 2009, approved April 29, 2009,
which provided for the surveys included under Group No. 2270,
and Assignment Instructions dated May 21, 2009.

Survey commenced May 21, 2009

Survey completed August 27, 2009

T. 29 S., R. 7 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of section 15, Township 29 South, Range 7 West, of the Willamette Meridian, Oregon.

A history of surveys pertaining to this survey is as follows:

In 1855, Nathaniel Ford, U.S. Deputy Surveyor, surveyed a portion of the east boundary and subdivisional lines as shown on the official plat of survey approved March 9, 1855.

In 1910, Roy T. Campbell, U.S. Deputy Surveyor, retraced a portion of the east boundary and surveyed the remainder of the subdivisional lines as shown on the official plat of survey approved April 5, 1911.

In 1924, Fred Mensch, U.S. Cadastral Engineer, resurveyed a portion of the subdivisional lines as shown on the official plat of survey approved February 15, 1926.

In 1957, Hans W. Thielsen, Cadastral Surveyor, resurveyed a portion of the east boundary and subdivisional lines as shown on the plat of survey accepted July 11, 1958.

In 1959, Hans W. Thielsen, Cadastral Surveyor, resurveyed a portion of the east boundary and subdivisional lines as shown on the plat of survey accepted February 9, 1961.

In 1966, John M. Jelley, Cadastral Surveyor, correctively resurveyed a portion of the subdivisional lines, resurveyed a portion of the subdivisional lines, and subdivided section 21, as shown on the plat of survey accepted June 5, 1970.

In 1981, James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, resurveyed a portion of the north boundary and subdivisional lines, and subdivided sections 3, 23, and 33, as shown on the plat of survey accepted March 18, 1982.

In 1984-85, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, and subdivided section 11, as shown on the plat of survey accepted September 19, 1986.

In 2002, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, remonumented and rehabilitated certain corner points on the east boundary and subdivisional lines as shown in the field notes approved November 3, 2004.

The following plats and field notes, filed in the Douglas County Surveyor's Office, are referred to in subsequent corner descriptions and are referenced by surveyor's last name, title or registration number, and year. The dates listed below are either the date on which the survey was filed or the date indicated on the plat or field notes.

T. 29 S., R. 7 W., Willamette Meridian, Oregon

FEET	<u>Date</u>	<u>Name and Title or Registration No.</u>	<u>File No.</u>
	5/1956	Clifford Bryden, RE 3937	CS 42/158
	5/1962	James W. Byron, Deputy County Surveyor	CS 49/139
	4/20/1965	Bruce R. Rogers, Deputy County Surveyor	CS 54/2
	10/15/1969	John M. Powell, Deputy County Surveyor	CS 49/139
	3/ 3/1981	Larry E. Monrean, Deputy County Surveyor	CS 61/19
	9/11/1989	Howard W. Johnstone, PLS 498	M101-60
	4/13/1999	Douglas County Surveyor's Office	CS66/8-25
	4/14/1999	Douglas County Surveyor's Office	CS66/8-37
	<p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated April 28, 2009, for Group No. 2270, Oregon.</p>		
	<p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the corner description field notes are given herein.</p>		
	<p>The direction of the lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) measurements.</p>		
	<p>The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.</p>		
	<p>The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.13 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p>		
	<p>The geographic positions (NAD 1983 (CORS)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP", and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", are as follows:</p>		
	<p>The corner of sections 25, 26, 35, and the 36:</p>		
	<p>Latitude: 43° 00' 48.85" N. Longitude: 123° 29' 07.62" W.</p>		
	<p>The 1/4 section corner of sections 13 and 14:</p>		

T. 29 S., R. 7 W., Willamette Meridian, Oregon

FEET

Latitude: 43° 02' 59.92" N. Longitude: 123° 29' 07.80" W.

The corner of sections 10, 11, 14, and 15:


Latitude: 43° 03' 25.22" N. Longitude: 123° 30' 24.41" W.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

Restoring the 1855 survey by Nathaniel Ford, the 1910 survey by Roy T. Campbell, the 1924 resurvey by Fred Mensch, the 1957 resurvey by Hans W. Thielsen, the 1959 corrective resurvey by Hans W. Thielsen, the 1966 corrective resurvey by James E. Jelley and Wayne L. Rogers, the 1984-85 resurvey by Wayne L. Rogers, and the 2002 remonumentation and rehabilitation by Timothy J. Moore and Robert H. Browning

Beginning at the cor. of secs. 25, 26, 35, and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground (alongside of which is an iron pipe, 1 1/4 ins. diam., firmly set, projecting 2 ins. above ground, with yellow plastic cap mkd. DOUG CO SURVEYOR), with brass cap mkd.



from which the remains of the original bearing trees

A fir, 25 ins. diam., bears S. 22 1/4° E., 19.1 ft. dist., with a healed blaze.

A fir, 30 ins. diam., bears S. 19 1/2° W., 35.0 ft. dist., with a healed blaze.

A sawed fir stump, 40 ins. diam., bears N. 61 1/2° W., 19.1 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyors Office, in 1962, reported by Moore and Browning

A cedar, 29 ins. diam., bears N. 58 1/4° E., 63.5 ft. dist., with a healed double blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 26 ins. diam., bears N. 27 1/2° W., 65.8 ft. dist., with a healed blaze. (Record, 66.2 ft.)</p> <p>Corner is located W., 1 ft. dist. from the intersection of barbed wire fences extending N., E., and W.</p> <p>N. 0° 01' 26" W., bet. secs. 25 and 26, along a woven wire fence, posting and blazing.</p>
120	<p>Spur, slopes generally NE.</p>
1580	<p>Dirt road, 15 ft. wide, bears N. 70° E. and S. 70° W.</p>
2420	<p>Spur, slopes East.</p>
2620	<p>Dirt road, 9 ft. wide, bears N. 40° W. and S. 40° E.</p>
2637.28	<p>Point for the 1/4 sec. cor. of secs. 25 and 26 at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 29 S R 7 W 1/4 S 26 S 25 2009</p> <p>from which</p> <p>A fir, 18 ins. diam., bears S. 53 3/4° E., 25.0 ft. dist., mkd. 1/4 S25 BT.</p> <p>A fir, 14 ins. diam., bears S. 62 1/2° W., 43.8 ft. dist., mkd. 1/4 S26 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located W., 4.5 ft. dist. from a woven wire fence extending N. and S.</p> <p>From this cor., a sawed fir stump, 32 ins. diam., referenced by person(s) unknown, bears N. 29 1/4° W., 14.5 ft. dist., with no marks visible and a metal tag mkd. S 30 E 16.0 BY BOND 12/4/63.</p>
3955.91	<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 26 S 25 2009</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 71 3/4° E., 30.8 ft. dist., mkd. N 1/16 S25 BT.</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears S. 23 3/4° W., 17.4 ft. dist., mkd. N 1/16 S26 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located S. 35° W., 3.6 ft. dist. from a wood fence post at the cor. of barbed and woven wire fences extending N. 10° E., S., and E., on a gentle S. slope.</p> <p>From this cor., a madrone, 26 ins. diam., referenced by person(s) unknown, bears N. 76° E., 24.6 ft. dist., with no marks visible and a metal tag mkd. S 83 W 23.3 FT BOND 12/4/63.</p> <p>Discontinue posting and blazing.</p>				
4365	<p>Gravel road, 12 ft. wide, bears N. 20° E. and S. 20° W.</p>				
5274.54	<p>The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 3/4 in. diam., firmly set, projecting 14 ins. above ground (alongside of which is an iron pipe, 1 1/2 ins. diam., projecting 8 ins. above ground), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEY OFFICE</p> <p>T 29 S R 7 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">23</td> <td style="padding: 0 5px;">24</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">26</td> <td style="padding: 0 5px;">25</td> </tr> </table> <p>1969</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, size indeterminate, bears S. 57° E., 27.1 ft. dist., with scribe marks T29S R7W S25 T visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, size indeterminate, bears N. 16 1/2° W., 19.1 ft. dist., with scribe marks 7W visible on an open blaze.</p> <p>and the remains of a bearing tree mkd. by person(s) unknown, reported by Jelley and Rogers</p> <p style="padding-left: 40px;">A sawed fir stump, 18 ins. diam., bears N. 84° W., 15.2 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Powell, Deputy County Surveyor, in 1969, reported by Jelley and Rogers</p>	23	24	26	25
23	24				
26	25				

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A sawed fir stump, 18 ins. diam., bears N. 59° W., 80.5 ft. dist., with no marks visible.</p> <p>A fir, 36 ins. diam., bears N. 21° W., 116.8 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Jelley and Rogers</p> <p>A fir, 18 ins. diam., bears N. 58° W., 109.6 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 29 3/4° E., 18.6 ft. dist., mkd. T29S R7W S24 BT.</p> <p>A fir, 4 ins. diam., bears S. 68 3/4° E., 28.6 ft. dist., mkd. X BT.</p> <p>A fir, 14 ins. diam., bears S. 38 3/4° W., 9.8 ft. dist., mkd. T29S R7W S26 BT.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the W. bdy. of T. 29 S., R. 6 W., executed concurrently under this same group.</p> <p>N. 88° 04' 09" W., bet. secs. 13 and 24, along a woven and barbed wire fence, posting and blazing.</p> <p>450 Porter Creek Road, 11 ft. wide, bears N. 70° E., and S. 85° W., in curve.</p> <p>1855.04 The E 1/16 sec. cor. of sec. 24 only, established by Johnstone, Professional Land Surveyor (PLS) No. 498, in 1989, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 17 ins. above ground, with an aluminum cap mkd.</p> <p align="center">T29S R.R. CO. R7W E 1/16 S 24 ONLY 1989 LS498</p> <p>from which bearing trees mkd. by Johnstone</p> <p>A fir, 11 ins. diam., bears S. 66 1/4° E., 18.8 ft. dist., with a healed blaze.</p> <p>A fir, 17 ins. diam., bears S. 84 1/2° W., 34.3 ft. dist., with a healed blaze.</p> <hr/> <p>N. 88° 03' 49" W., beginning a new measurement.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET 1042.54	<p>The 1/4 sec. cor. of sec. 13 only, perpetuated by Johnstone, PLS No. 498, in 1989, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p> <p align="center">T 29 S R 7 W S 13 1/4 ——— 1957</p> <p>from which the remains of bearing trees mkd. by Thielsen in 1957</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears N. 19° E., 98.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A decayed cedar stump, size indeterminate, bears N. 14° W., 77.9 ft. dist., with scribe marks S13 BT and other fragmentary scribe marks visible on decayed root crown.</p> <p>and bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 11° E., 16.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 45 1/2° E., 30.2 ft. dist., with a healed blaze.</p> <p>Corner is located at the terminus of a barbed and woven wire fence extending S. 88° E.</p> <p align="center">—————</p> <p>N. 88° 01' 20" W., beginning a new measurement.</p>
282.80	<p>The 1/4 sec. cor. of sec. 24 only, established by Johnstone, PLS No. 498, in 1989, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, with an aluminum cap mkd.</p> <p align="center">T 29 S R.R. CO. R 7 W N 1/4 S 24 ONLY LS 498 1989</p> <p>from which the remains of bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A sawed fir stump, 20 ins. diam., bears S. 76° E., 30.8 ft. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 27 ins. diam., bears S. 24 3/4° E., 29.4 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 8 ins. diam., bears S. 44 1/4° W., 19.4 ft. dist., mkd. 1/4 S24 BT. Corner is located on nearly level ground.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 01' 30" W., beginning a new measurement.</p>								
30	Dirt road, 12 ft. wide, bears N. 20° E. and S. 20° W.								
400	Gravel road, 13 ft. wide, bears N. 20° E. and S. 20° W.								
2650.69	<p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 29 S</td> <td style="padding: 0 5px;">R 7 W</td> </tr> <tr> <td style="padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 23</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 24</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1957</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Campbell</p> <p style="margin-left: 40px;">A roothole bears S. 67 1/2° E., 30.4 ft. dist., downhill of which is an uprooted, sawed, decayed fir stump, size indeterminate, with no marks visible.</p> <p style="margin-left: 40px;">A sawed, decayed fir stump, 30 ins. diam., bears S. 73° W., 18.5 ft. dist., with scribe marks T29S and other fragmentary scribe marks visible on a chopped open blaze.</p> <p style="margin-left: 40px;">A fir, 56 ins. diam., bears N. 13° W., 34.3 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Thielsen in 1957</p> <p style="margin-left: 40px;">A fir, 37 ins. diam., bears N. 73° E., 110.2 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A sawed, decayed fir stump, 27 ins. diam., bears S. 45° E., 81.8 ft. dist., with scribe marks T29S R7W visible on an open blaze.</p> <p style="margin-left: 40px;">A fir, 32 ins. diam., bears S. 14° W., 91.1 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A cedar, 11 ins. diam., bears S. 10 1/4° E., 28.3 ft. dist., mkd. T29S R7W S24 BT.</p> <p>Corner is located on a NE. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 17' 43" W., bet. secs. 13 and 14, posting and blazing.</p>	T 29 S	R 7 W	S 14	S 13	S 23	S 24	1957	
T 29 S	R 7 W								
S 14	S 13								
S 23	S 24								
1957									
1990	Gravel road, 23 ft. wide, bears S. 80° E. and N. 70° W., in curve.								

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

<p>FEET 2598.97</p>	<p>The 1/4 sec. cor. of secs. 13 and 14, perpetuated by the Douglas County Surveyor's Office in 1999, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above ground, with brass cap mkd.</p> <p align="center"> T 29 S R 7 W 1/4 S 14 S 13 1957 </p> <p>from which bearing trees mkd. by Thielsen in 1957</p> <p>A fir, 11 ins. diam., bears S. 47° E., 40.9 ft. dist., with a healed blaze.</p> <p>A fir, 32 ins. diam., bears N. 71° W., 64.7 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A cedar, 13 ins. diam., bears N. 43 1/2° E., 5.6 ft. dist., with scribe marks 1/4 S13 CS BT visible on an open blaze.</p> <p>A fir, 12 ins. diam., bears S. 64 1/4° W., 22.1 ft. dist., with a healed double blaze.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p align="center"> T 29 S R 7 W S 11 S 12 ----- S 14 S 13 1957 </p> <p>from which bearing trees mkd. by Thielsen in 1957</p> <p>A fir, 17 ins. diam., bears N. 53° E., 125.8 ft. dist., with a healed blaze. (Record, N. 51° E., 132.0 ft.)</p> <p>A fir, 20 ins. diam., bears S. 44° E., 72.6 ft. dist., with a healed blaze.</p> <p>A fir, 26 ins. diam., bears S. 15° W., 46.2 ft. dist., with a healed blaze.</p> <p>A fir, 24 ins. diam., bears N. 66 1/2° W., 40.3 ft. dist., with a healed blaze.</p> <p>Corner is located on a N. slope at the intersection of a broken down barbed and woven wire fences extending N., E., and W.</p> <p>N. 0° 42' 33" W., bet. secs. 11 and 12, along a barbed and woven wire fence, posting and blazing.</p>
<p>2385</p>	<p>Ravine, drains S. 30° E.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET 2595.03	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p align="center"> T 29 S R 7 W 1/4 S 11 S 12 1957 </p> <p>from which the remains of bearing trees mkd. by Thielsen in 1957</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 54° E., 30.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A madrone snag, 45 ins. diam., bears S. 3° E., 44.2 ft. dist., with no marks visible. (Record, S. 1° W.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears N. 68 3/4° W., 56.3 ft. dist., mkd. 1/4 S11 BT.</p> <p>Corner is located S. 25° E., 1.0 ft. dist. from a wood post at the intersection of barbed and woven wire fences extending N., S. 5° E., and W., on a moderate S. slope.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15, perpetuated by Byron, Deputy County Surveyor, in 1962, subsequently perpetuated by the Douglas County Surveyor's Office in 1999, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, in an embedded collar of stone, with brass cap mkd.</p> <p align="center"> 1/4 S 15 S 14 T 29 S R 7 W 1957 </p> <p>from which a bearing tree mkd. by Thielsen in 1957</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears S. 10 1/4° W., 157.3 ft. dist., with a healed blaze.</p> <p>and an accessory by Byron</p> <p style="padding-left: 40px;">An iron rod, 3/4 in. diam., firmly set, projecting 1 in. above ground, bears S. 89° 13' 21" W., 59.07 ft. dist.</p> <p>and accessories by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">The base of the westernmost steel angle iron stanchion of a windmill, 7 1/2 ft. square, bears N. 86 1/4° E., 324.1 ft. dist.</p>
-----------------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A pine, 17 ins. diam., bears N. 58 1/2° W., 181.2 ft. dist., with a healed double blaze.</p> <p>a new bearing tree</p> <p>A pine, 14 ins. diam., bears S. 19° E., 150.1 ft. dist., mkd. 1/4 S14 BT.</p> <p>Corner is located W., 1.0 ft. dist., from a barbed and woven wire fence extending N. and S.</p> <p>N. 0° 29' 33" E., bet. secs. 14 and 15, posting and blazing.</p>																				
362	<p>From this point, a wood post at the cor. of barbed and woven wire fences extending N. 60° E. and S., bears West, 0.4 ft. dist.</p>																				
2585.95	<p>The cor. of secs. 10, 11, 14, 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 29 S</td> <td colspan="2">R 7 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 11</td> <td></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> <td colspan="2"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 14</td> <td></td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 0 10px;">1957</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Thielsen in 1957</p> <p>A fir snag, 15 ins. diam., bears N. 74° E., 25.7 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 13 ins. diam., bears S. 70 1/2° E., 19.5 ft. dist., with a healed blaze. (Record, 17.2 ft.)</p> <p>A sawed fir stump, 14 ins. diam., 7 ft. high, bears N. 65° W., 25.9 ft. dist., with a healed blaze. (Record, 27.1 ft.)</p> <p>and the remains of bearing trees mkd. by Bryden, Registered Engineer No. 3937, in 1956, reported by Rogers</p> <p>A decayed fir stump, size indeterminate, bears N. 36° E., 19.8 ft. dist., alongside of which is a down, decayed fir, size indeterminate, with no marks visible on an opened healed blaze.</p> <p>A sawed fir stump, 27 ins. diam., bears S. 19 1/2° E., 8.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>A fir, 26 ins. diam., bears S. 76° W., 8.4 ft. dist., with a healed double blaze. (Record, 10.2 ft.)</p> <p>and a bearing tree mkd. by Rogers</p> <p>A fir, 19 ins. diam., bears S. 34° E., 15.9 ft. dist., with a healed blaze. (Record, S. 31 1/2° E., 14.5 ft.)</p>	T 29 S		R 7 W		S 10		S 11						S 15		S 14		1957			
T 29 S		R 7 W																			
S 10		S 11																			
S 15		S 14																			
1957																					

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 28 1/2° E., 75.7 ft. dist., mkd. T29S R7W S11 BT.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 70° W., 36.4 ft. dist., mkd. T26S R7W S10 BT.</p> <p>Corner is located S. 10° W., 2.0 ft. dist., from a wood fence post at the intersection of a broken down barbed and woven wire fence, extending N. and E., on a NW. slope.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S. 89° 38' 10" W., bet. secs. 11 and 14, along a broken down barbed and woven wire fence, posting and blazing.</p>
2575	<p>Spur, slopes N. 15° W.</p>
2837.52	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 29 S R 7 W</p> <p style="margin-left: 40px;">S 11</p> <p style="margin-left: 40px;">1/4 ———</p> <p style="margin-left: 40px;">S 14</p> <p style="margin-left: 40px;">1957</p> </div> <p>from which the remains of bearing trees mkd. by Thielsen in 1957</p> <p style="padding-left: 40px;">A roothole bears South, 46.2 ft. dist., alongside of which is a down, decayed fir, size indeterminate, with no marks visible.</p> <p>and bearing trees mkd. by Rogers</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 42° W., 44.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 32° W., 17.5 ft. dist., with a healed double blaze.</p> <p>Corner is located on a W. slope.</p> <hr/> <p>S. 89° 41' 29" W., beginning a new measurement, continuing along a broken down barbed and woven wire fence.</p>
55	<p>McNabb Creek, 2 ft. wide, course N. 50° E.</p>
2655	<p>Gravel road, 15 ft. wide, bears N. 25° E. and S. 25° W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

<p>FEET 2838.81</p>	<p>The cor. of secs. 10, 11, 14, and 15.</p> <hr/> <p>N. 84° 21' 18" W., bet. secs. 10 and 15, posting and blazing.</p>
<p>2015</p>	<p>Gravel road, 9 ft. wide, bears N. 40° E. and S. 40° W.</p>
<p>2457.23</p>	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> T 29 S R 7 W S 10 1/4 _____ S 15 1957 </p> <p>from which the remains of bearing trees mkd. by Thielsen in 1957</p> <p style="padding-left: 40px;">A fir, 41 ins. diam., bears S. 72° E., 25.1 ft. dist., with a healed blaze and axe marks visible on bark.</p> <p style="padding-left: 40px;">A sawed fir stump, 38 ins. diam., bears N. 36 1/2° W., 35.6 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 25 1/2° E., 9.1 ft. dist., mkd. X BT.</p> <hr/> <p style="text-align: center;"> Subdivision of Section 15, T. 29 S., R. 7 W., Willamette Meridian, Oregon </p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> T 29 S R 7 W S 15 1/4 _____ S 22 1966 1957 </p> <p>from which bearing trees mkd. by Byron, Deputy County Surveyor, in 1962, reported by Jelley</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears North, 40.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears S. 44° W., 85.1 ft. dist., with a healed double blaze.</p>

**Subdivision of Section 15,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner is N., 8 ft. dist. from the base of a rock shelf, base bears N. 60° E. and S. 60° W., on a N. slope.</p>
	<p>N. 1° 08' 58" E., on the N. and S. centerline of section 15, posting and blazing.</p>
2205	<p>Gravel road, 10 ft. wide, bears N. 60° E. and S. 60° W.</p>
2325	<p>Same gravel road, 9 ft. wide, on ridge, both bear N. 75° E. and S. 75° W.</p>
2606.20	<p>The center 1/4 sec. cor. of sec. 15, established by Rogers, Deputy County Surveyor, in 1965, perpetuated by Monrean, Deputy County Surveyor, in 1981, and is accepted as the cor., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. diam., with brass cap mkd.</p> <p align="center">DOUGLAS CO. SURVEYOR T 29 S R 7 W C 1/4 S 15 1981</p> <p>from which the remains of bearing trees mkd. by Rogers</p> <p style="padding-left: 40px;">A fir snag, 15 ins. diam., bears S. 35 1/4° E., 172.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 17 1/4° E., 158.3 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Monrean</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 37 3/4° E., 63.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 82 3/4° W., 4.4 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A pine snag, 14 ins. diam., bears N. 27 1/2° W., 93.1 ft. dist., with scribe marks C 4 5 and other fragmentary scribe marks visible on a partially healed blaze.</p> <p>Corner is located on a N. slope.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. 1° 05' 01" E., beginning a new measurement.</p>
30	<p>Gravel road, 10 ft. wide, bears S. 85° E. and N. 55° W., in curve.</p>
2611.36	<p>The 1/4 sec. cor. of secs. 10 and 15.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p>

**Subdivision of Section 15,
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	N. 84° 59' 33" W., on the E. and W. centerline of sec. 15, posting and blazing.
130	Unimproved dirt road, 9 ft. wide, bears S. 60° E. and N. 60° W.
2205	Gravel road, 12 ft. wide, bears S. 25° E. and N. 25° W.
2482.22	The center 1/4 sec. cor. of sec. 15. Discontinue posting and blazing. <hr style="width: 20%; margin: 5px auto;"/>
2488.00	N. 84° 53' 48" W., beginning a new measurement. The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. <div style="text-align: center; padding: 10px 0;"> <p>T 29 S R 7 W 1/4 S 16 S 15 1966 1957</p> </div> <p>from which the remains of a bearing tree mkd. by Thielsen in 1957</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 60° E., 44.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 20 ins. diam., bears S. 50° W., 37.6 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 52° W., 22.6 ft. dist., mkd. 1/4 S16 BT.</p> <hr style="width: 60%; margin: 10px auto;"/>