

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH
AND WEST BOUNDARIES AND SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTION 26

TOWNSHIP 25 SOUTH, RANGE 2 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated April 21, 2010, approved April 29, 2010,
which provided for the surveys included under Group No. 2317,
and Assignment Instructions dated May 3, 2010.

Survey commenced June 8, 2010

Survey completed June 8, 2011

T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the south and west boundaries and subdivisional lines, and the subdivision of section 26, Township 25 South, Range 2 West, of the Willamette Meridian, Oregon.</p> <p>The history of the official surveys pertaining to this survey is as follows:</p> <p>In 1883, John A. McQuinn, U.S. Deputy Surveyor, surveyed the township lines and a portion of the subdivisional lines, T. 26 S., R. 2 W., approved April 7, 1884, and accepted May 8, 1884.</p> <p>In 1883, Laban H. Wheeler, U.S. Deputy Surveyor, surveyed the township lines and subdivisional lines, T. 25 S., R. 3 W., approved May 19, 1884, and accepted June 17, 1884.</p> <p>In 1900, Hezekiah H. Johnson, U.S. Deputy Surveyor, dependently resurveyed the east boundary, T. 25 S., R. 2 W., surveyed the south boundary, 25 S., R. 1 W., and retraced the south and west boundaries and surveyed the subdivisional lines, T. 25 S., R. 2 W., approved May 6, 1901, and accepted March 7, 1902.</p> <p>In 1913-14, Charles M. Collier, U.S. Deputy Surveyor, retraced and reestablished the north and portions of the south, east, and west boundaries, T. 26 S., R. 2 W., approved June 21, 1917, and accepted June 22, 1919.</p> <p>In 1943-44, Norman D. Price, Cadastral Surveyor, resurveyed the south boundary, T. 24 S., R. 3 W., the south, east, and west boundaries, a portion of the north boundary of section 6, and subdivisional lines, T. 25 S., R. 3 W., approved July 24, 1945, accepted January 7, 1946.</p> <p>In 1951-63, Levi E. Tallett and C. Albert White, Cadastral Surveyors, resurveyed portions of the south and west boundaries, T. 24 S., R. 1 W., and portions of the east boundary and subdivisional lines, T. 25 S., R. 2 W., accepted November 2, 1964.</p> <p>In 1959, Irving Zirpel, Jr., and William W. Glenn, Cadastral Surveyors, resurveyed portions of the north and west boundaries and a portion of the subdivisional lines, and subdivided sections 15 and 17, T. 26 S., R. 2 W., approved August 29, 1960.</p> <p>In 1962, Floyd A. Brooks, Cadastral Surveyor, remonumented certain original corner points, T. 25 S., R. 2 W., as shown in the field notes approved May 13, 1964.</p> <p>In 1972-75, Daniel L. Berry, Harvey E. Wofford and G. Steven Popken, Cadastral Surveyors, and Glenn S. Baughman, Oregon Professional Land Surveyor No. 536, under Contract No. 52500-CT5-1116, resurveyed a portion of the north boundary, T. 26 S., R. 2 W., a portion of the east boundary, T. 25 S., R. 3 W., and a portion of the subdivisional lines and subdivided sections 31 and 32, T. 25 S., R. 2 W., approved March 7, 1977.</p>
------	--

T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET

In 1995-98, Bryan S. Seibold, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, correctively resurveyed a portion of the south boundary, resurveyed a portion of the subdivisional lines, and subdivided section 34, approved August 4, 2000.

In 2001-02, A. Bert Skeesick, Cadastral Surveyor, resurveyed a portion of the east boundary and subdivisional lines, and subdivided sections 11 and 13, accepted June 24, 2004.

The following plats filed in the Douglas County Surveyor's Office were evaluated, and a portion of them are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) or Professional Engineer (PE) number, and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Type</u>	<u>File Number</u>
1959	G. Robert Lecklider PLS 362	Map	M11-31
1957	Vernon W. Hosford PLS 253	Map	M13-13
1960	G. Robert Lecklider PLS 362	Map	M19-40
1973	Nick Juliano PE 3449	Map	M51-27
1977	Leslie D. Roberts PLS 1039	Map	M67-61
1977	Nick Juliano PE 3449	Map	M68-32
2004	Larry E. Monrean PLS 1830	Map	M144-47

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the Special Instructions dated April 21, 2010, for Group No. 2317, Oregon.

The directions of the lines are based on true meridian as determined by direct solar observations and Global Positioning System (GPS) measurements carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, relative to

T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET

“DODSON BUTTE CORS ARP” and “CAPE BLANCO CORS ARP”, are as follows:

The corner of sections 25, 26, 35, and 36.

Latitude: 43° 21' 28.18" N. Longitude: 122° 53' 36.77" W.

The corner of sections 7, 8, 17, and 18.

Latitude: 43° 24' 09.08" N. Longitude: 122° 58' 21.40" W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

Restoring the 1883 survey by John A. McQuinn, the 1900 retracement by Hezekiah H. Johnson, the 1913-14 resurvey by Charles M. Collier, the 1959 resurvey by Irving Zirpel, Jr. and William W. Glenn, the 1972-75 resurvey by Daniel L. Berry, Harvey E. Wofford, G. Steven Popken, and Glenn S. Baughman, and the 1995-98 resurvey by Bryan S. Seibold and Robert H. Browning

Beginning at the cor. of Tps. 25 and 26 S., R. 2 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.

```

T 25 S R R
  S 36 2 | 1
          |
  S 1 W | W
T 26 S
      1966
    
```

from which the remains of the original bearing trees reported by Collier

A fir, 47 ins. diam., bears S. 87 1/4° E., 76.6 ft. dist., with no marks visible. (Record, N. 85° E.)

A pine, 37 ins. diam., bears S. 44° E., 29.7 ft. dist., with no marks visible. (Record, S. 55° E.)

A pine snag, 35 ins. diam., bears S. 60° W., 43.6 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Office, C.S. File No. 52/77

A hemlock, 31 ins. diam., bears S. 51 3/4° W., 7.9 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 11 ins. diam., bears N. 57 3/4° W., 27.2 ft. dist., with a healed blaze.</p> <p>N. 89° 53' 42" W., bet. secs. 1 and 36, on the S. bdy. of the Tp., posting and blazing.</p>
950	<p>Graveled road, 12 ft. wide, bears S. and N. 5° W, also top of ridge, bears the same.</p>
2550.99	<p>The 1/4 sec. cor. of sec. 1 only, T. 26 S., R. 2 W., perpetuated by the Douglas County Surveyor's Office in 1967, filed in the Douglas County Surveyor's Office, C.S. File No. 54/40, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, (along the S. side of which is the original stone, 18 x 10 x 8 ins., with no marks showing), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R <hr style="width: 50px; margin: 0 auto;"/> 2 S 1 W T 26 S 1967</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A sawed, decayed fir stump, 41 ins. diam., bears N. 54° E., 26.0 ft. dist., with no marks visible. (Record, N. 60° E., 23.1 ft.)</p> <p style="margin-left: 40px;">A sawed fir stump, 46 ins. diam., bears S. 26 1/2° E., 44.2 ft. dist., no marks visible. (Record, S. 5° W.)</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office</p> <p style="margin-left: 40px;">A sawed fir stump, 19 ins. diam., bears S. 35 1/2° E., 22.7 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir snag, 21 ins. diam., bears S. 50 1/4° W., 4.2 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 72° E., 13.5 ft. dist., mkd. 1/4 S1 BT.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 8 1/4° E., 21.8 ft. dist., mkd. X BT.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 16' 33" W., beginning new measurement, continue posting and blazing.</p>
52.96	<p>Point for the 1/4 sec. cor. of sec. 36 only, on the S. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">T 25 S R 2 W 1/4 S 36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T 26 S 2010</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 52 1/4° E., 23.6 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 30 1/4° W., 31.9 ft. dist., mkd. 1/4 S36 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>2375 Creek 3 ft. wide, course S. 30° W.</p> <p>2559.32 The cor. of secs. 1 and 2 only, T. 26 S., R. 2 W., perpetuated by G. Robert Lecklider, Oregon PLS No. 362, in 1959, further perpetuated by Leslie D. Roberts, Oregon PLS No. 1039, in 1977, monumented with an aluminum pipe, 1 in. diam., firmly set, projecting 15 ins. above the ground, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 55° E., 13.2 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Lecklider</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 3 3/4° W., 33.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 5 1/2° W., 10.6 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 77 1/2° E., 47.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 87° W., 21.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the aluminum pipe, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 2 W S 36</p> <hr style="width: 10%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> </table> <p style="text-align: center;">T 26 S R 2 W 2010</p>	S 2	S 1
S 2	S 1		

**Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89° 47' 08" W., bet. secs. 2 and 36, continue posting and blazing.</p> <p>97.78 The closing cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., reestablished by Leslie D. Roberts, Oregon PLS No. 1039, in 1977, and is accepted as a careful and faithful reestablishment of the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, from which bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 23° E., 8.8 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 44° W., 12.4 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Drive an aluminum cap onto the iron rod, mkd.</p> <div style="text-align: center;"> <p>C C</p> <p>T 25 S R 2 W</p> <p>S 35 S 36</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 2</p> <p>T 26 S R 2 W</p> <p>2010</p> </div> <p>Deposit a magnet in a white plastic case alongside the iron rod.</p> <p>Discontinue posting and blazing.</p> <hr/>
<p>575</p> <p>2492.55</p>	<p>S. 89° 56' 51" W., bet. secs. 2 and 35.</p> <p>Creek, 2 ft. wide, course S. 65° E.</p> <p>The 1/4 sec. cor. of sec. 2 only, T. 26 S., R. 2 W., perpetuated by G. Robert Lecklider, Oregon PLS No. 362, in 1959, further perpetuated by Larry E. Monrean, Oregon PLS No. 1830, in 2004, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, (alongside of which is the original stone, 14 x 12 ins., projecting 8 ins. above the ground, with no marks visible), with aluminum cap mkd.</p> <div style="text-align: center;"> <p>ROSEBURG RESOURCES</p> <p>T 25 S R 2 W</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1/4 S 2</p> <p>T 26 S R 2 W</p> <p>LS 1830</p> <p>2004</p> <p>COMPANY</p> </div>

**Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>from which the remains of bearing trees mkd. by Collier</p> <p style="padding-left: 40px;">A fir, 48 ins. diam., bears S. 52 1/4° E., 22.4 ft. dist., with a healed double blaze. (Record, S. 60° E.)</p> <p style="padding-left: 40px;">A fir, 39 ins. diam., bears S. 44° E., 27.7 ft. dist., with scribe marks 1/4 S2 visible on the bark.</p> <p>and a bearing tree mkd. by Lecklider</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 34 1/4° E., 5.6 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by Monrean</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 55 3/4° W., 27.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 6 1/2° W., 25.0 ft. dist., with a healed blaze.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 50' 33" W., beginning new measurement.</p>
150.88	<p>Point for the 1/4 sec. cor. of sec. 35 only, on the S. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R 2 W 1/4 S 35</p> <hr style="width: 20%; margin: 0 auto;"/> <p>T 26 S R 2 W 2010</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 80 3/4° E., 5.2 ft. dist., mkd. 1/4 S35 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 29 3/4° W., 13.2 ft. dist., mkd. 1/4 S35 BT.</p>
1235	<p>Ridge, bears S. 15° E. and N. 15° W.</p>
1294.54	<p>Point for the W 1/16 sec. cor. of sec. 2 only, T. 26 S., R. 2 W.</p> <p>At the corner point</p> <p>Drive an iron rod, 5/8 in. diam., 30 ins. long, 22 ins. in the ground, with aluminum cap mkd.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>and a bearing tree mkd. by G. Robert Lecklider, Oregon PLS No. 362, in 1959, reported by Seibold and Browning</p> <p style="padding-left: 40px;">A fir, 55 ins. diam., bears S. 44 1/2° E., 37.0 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Monrean</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 1 1/4° E., 50.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 43 3/4° W., 14.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>Discontinue posting and blazing.</p> <hr/> <p>N. 89° 11' 20" W., bet. secs. 3 and 35.</p>														
180	<p>Creek, 3 ft. wide, course S. 25° W.</p>														
205.25	<p>The closing cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, (alongside of which is an iron pipe, 1/2 in. diam., firmly set, projecting 16 ins. above the ground, with aluminum cap mkd. PROPERTY CORNER), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">C</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="padding: 0 5px;">T 25 S</td> <td style="padding: 0 5px;">R 2 W</td> </tr> <tr> <td style="padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black; width: 100px; margin: 0 auto;"></td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">T 26 S R 2 W</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">1974</td> </tr> </table> </div> <p>from which accessories mkd. by G. Robert Lecklider, Oregon PLS No. 362, in 1960, reported by Seibold and Browning</p> <p style="padding-left: 40px;">A rock in place, 4 1/2 x 3 1/2 x 2 1/2 ft., bears N. 18° E., 5.9 ft. dist., with marks CC + BO visible on S. face.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 49 1/4° W., 8.6 ft. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by Wofford, Berry, Popken, and Baughman, reported by Seibold and Browning</p> <p style="padding-left: 40px;">An alder, 18 ins. diam., bears N. 34 1/4° E., 51.5 ft. dist., with scribe marks T25S R2W S35 CC BT visible on the bark.</p> <hr/>	C	C	T 25 S	R 2 W	S 34	S 35			S 3		T 26 S R 2 W		1974	
C	C														
T 25 S	R 2 W														
S 34	S 35														
S 3															
T 26 S R 2 W															
1974															

**Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>Restoring the 1883 survey by Laban H. Wheeler, the 1900 resurvey by Hezekiah H. Johnson, and the 1943-44 resurvey by Norman D. Price</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the closing cor. of secs. 7 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T 25 S</td> <td style="padding: 2px;">T 25 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">R 3 W</td> <td style="padding: 2px;">S 7 C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 13</td> <td style="padding: 2px;">S 18 C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;"></td> <td style="padding: 2px;">R 2 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;"></td> <td style="padding: 2px;">1943</td> </tr> </table> </div> <p>from which bearing trees mkd. by Price</p> <p style="margin-left: 40px;">A sawed, decayed cedar stump, size indeterminate, bears N. 11 3/4° E., 52.1 ft. dist., with scribe marks 2W S7 CC BT visible on a weathered blaze.</p> <p style="margin-left: 40px;">A sawed, decayed cedar stump, 18 ins. diam., bears S. 63° E., 74.6 ft. dist., with scribe marks 25 S R2W S18 CC BT visible on a partially healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office, in 1966, filed in the Douglas County Surveyor's Office, C.S. File No. 54/7</p> <p style="margin-left: 40px;">A cedar, 26 ins. diam., bears N. 84 3/4° E., 61.8 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears S. 40 3/4° E., 37.8 ft. dist., mkd. T25S R2W S18 CC BT.</p> <p>N. 1° 01' 21" W., bet. secs. 7 and 13.</p> <p>451.64 The cor. of secs. 12 and 13, T. 25 S., R. 3 W., perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Office, C.S. File No. 54/27, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T 25 S</td> <td style="padding: 2px;">T 25 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 12</td> <td style="padding: 2px;">R 2 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;"></td> <td style="padding: 2px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 13</td> <td style="padding: 2px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">R 3 W</td> <td style="padding: 2px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;"></td> <td style="padding: 2px;">1943</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p>	T 25 S	T 25 S	R 3 W	S 7 C	S 13	S 18 C		R 2 W		1943	T 25 S	T 25 S	S 12	R 2 W		S 7	S 13		R 3 W			1943
T 25 S	T 25 S																						
R 3 W	S 7 C																						
S 13	S 18 C																						
	R 2 W																						
	1943																						
T 25 S	T 25 S																						
S 12	R 2 W																						
	S 7																						
S 13																							
R 3 W																							
	1943																						

**Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET							
	<p>A decayed hemlock stump, size indeterminate, bears N. 15° W., 11.2 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Price</p> <p>A fir, 38 ins. diam., bears S. 56 1/2° W., 31.0 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 23 ins. diam., bears N. 53 1/2° W., 24.4 ft. dist., with fragmentary scribe marks visible on a burnt, partially healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p>A fir, 11 ins. diam., bears S. 10 3/4° W., 9.1 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p>A hemlock, 7 ins. diam., bears N. 41° W., 42.8 ft. dist., mkd. T25S R3W S12 BT.</p>						
1324.97	<hr/> <p>N. 0° 45' 38" E., bet. secs. 7 and 12, posting and blazing.</p> <p>The S 1/16 sec. cor. of sec. 12 only, T. 25 S., R. 3 W., established by Nick Juliano, Oregon PE No. 3449, in 1977, and is accepted as the cor., monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 9 ins. above the ground, from which the remains of bearing trees mkd. by Juliano</p> <p>A sawed, decayed fir stump, 13 ins. diam., bears N. 14 3/4° E., 33.9 ft. dist., with a railroad spike in the face and axe marks visible on a partially healed blaze.</p> <p>A sawed, decayed hemlock stump, 32 ins. diam., bears N. 35 3/4° W., 16.0 ft. dist., with a railroad spike at the base and no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>S 1/16</td> <td> </td> </tr> <tr> <td>S 12</td> <td> </td> </tr> <tr> <td>2010</td> <td> </td> </tr> </table> </div> <p>from which</p> <p>A fir, 7 ins. diam., bears S. 34° W., 16.5 ft. dist., mkd. S 1/16 S12 BT.</p> <p>A cedar, 14 ins. diam., bears N. 66 1/4° W., 13.6 ft. dist., mkd. S 1/16 S12 BT.</p>	S 1/16		S 12		2010	
S 1/16							
S 12							
2010							

**Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
833.61	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 0° 47' 26" E., beginning new measurement, continue posting and blazing.</p> <p>The 1/4 sec. cor. of sec. 7 only, on the W. bdy. of the Tp., perpetuated by the Douglas County Surveyors Office in 1966, filed in the Douglas County Surveyor's Office, C.S. File No. 54/7, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p> 1/4 S 7 1943</p> </div> <p>from which the remains of bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 40 ins. diam., bears S. 89 1/2° E., 33.0 ft. dist., with a healed blaze. (Record, S. 81 1/2° E.)</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 35 ins. diam., bears S. 67° E., 37.6 ft. dist., with scribe marks S7 B visible on a partially healed blaze. (Record, S. 57 1/2° E.)</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A hemlock, 38 ins. diam., bears N. 19 1/2° E., 19.4 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 36° E., 19.0 ft. dist., mkd. 1/4 S7 BT.</p> <hr style="width: 20%; margin: 0 auto;"/>
454	<p>N. 0° 45' 29" E., beginning new measurement, continue posting and blazing.</p> <p>Creek, 2 ft. wide, course S. 55° E.</p>
491.30	<p>The 1/4 sec. cor. of sec. 12 only, T. 25 S., R. 3 W., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 12 1943</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole bears S. 40° E., 12.5 ft. dist., with no remains of the hemlock trunk.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 32 ins. diam., bears S. 78° W., 15.2 ft. dist., with no marks visible.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>and the remains of a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 35 ins. diam., bears S. 21° W., 14.2 ft. dist., with a healed blaze. (Record, 11.2 ft. dist.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A hemlock, 7 ins. diam., bears N. 82 1/4° W., 20.2 ft. dist., mkd. 1/4 S12 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 10 1/4° W., 39.0 ft. dist., mkd. 1/4 S12 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 16' 15" E., beginning new measurement, continue posting and blazing.</p>												
2119.00	<p>The closing cor. of secs. 6 and 7 only, on the W. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1966, filed in the Douglas County Surveyor's Office, C.S. File No. 54/27, further perpetuated by the Douglas County Surveyor's Office in 1997, filed in the Douglas County Surveyor's Office, C.S. File No. 64/78-7, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 25 S</td> <td style="padding: 0 5px;">T 25 S</td> </tr> <tr> <td style="padding: 0 5px;">R 3 W</td> <td style="padding: 0 5px;">S 6 C</td> </tr> <tr> <td style="padding: 0 5px;">S 12</td> <td style="border-left: 1px solid black; padding-left: 5px; text-align: center;"> <hr style="width: 50%; margin: 0 auto;"/> </td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px; text-align: center;">S 7 C</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px; text-align: center;">R 2 W</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1943</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 36 ins. diam., bears N. 50 3/4° E., 15.2 ft. dist., with scribe marks T25S R2W S6 visible on fragment of a partially healed blaze.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 35 ins. diam., bears S. 20 1/2° E., 13.9 ft. dist., with scribe marks T25S R2 visible on a partially healed blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office in 1966</p> <p style="padding-left: 40px;">A hemlock, 29 ins. diam., bears N. 6° E., 221.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A yew, 11 ins. diam., bears S. 62 3/4° E., 169.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office in 1997</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 66 3/4° E., 6.8 ft. dist., with a healed double blaze.</p>	T 25 S	T 25 S	R 3 W	S 6 C	S 12	<hr style="width: 50%; margin: 0 auto;"/>		S 7 C		R 2 W		1943
T 25 S	T 25 S												
R 3 W	S 6 C												
S 12	<hr style="width: 50%; margin: 0 auto;"/>												
	S 7 C												
	R 2 W												
	1943												

**Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 10 ins. diam., bears S. 12 1/4° E., 36.5 ft. dist., with a healed double blaze.</p> <p>Discontinue posting and blazing.</p>
	<hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/>
	<p style="text-align: center;">Restoring the 1900 survey by Hezekiah H. Johnson, the 1951-63 resurvey by Levi E. Tallett and C. Albert White, the 1962 remonumentation by Floyd A. Brooks, the 1972-75 resurvey by Daniel L. Berry, Harvey E. Wofford, G. Steven Popken, and Glenn S. Baughman, the 1995-98 resurvey by Bryan S. Seibold and Robert H. Browning, and the 2001-02 resurvey by A. Bert Skeesick</p> <hr/>
	<p>From the closing cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p>
	<p>N. 1° 10' 13" W., bet. secs. 35 and 36, posting and blazing.</p>
<p>1025</p>	<p>Graveled road, 12 ft. wide, bears N. 15° E. and S. 15° W.</p>
<p>2525</p>	<p>Edge of rock bluff, edge bears N. 65° E. and S. 65° W.</p>
<p>2535.86</p>	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, determined at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Drive an aluminum rod, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 2 W 1/4 S 35 S 36 2010</p> </div> <p>from which</p>
	<p>An ash, 13 ins. diam., bears S. 45 1/2° E., 10.7 ft. dist., mkd. 1/4 S36 BT, with Mag Nail driven at the base on left side center.</p>
	<p>A rock face bears S. 79 1/2° W., 2.8 ft. dist., mkd. X BO.</p>
	<p>Deposit a magnet in a white plastic case alongside the aluminum rod.</p>
<p>2579.82</p>	<p>A point established by Leslie D. Roberts, Oregon PLS No. 1039, in 1977, and is accepted as witness cor. for the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron rod, 5/8 in. diam., firmly, projecting 10 ins. above a collar of stone, 1 1/2 ft. base, from which the remains of bearing trees mkd. by Roberts</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A sawed fir stump, 40 ins. diam., bears N. 11 1/4° E., 15.5 ft. dist., with a railroad spike in the face and no marks visible.</p> <p>A fir, 29 ins. diam., bears S. 34 1/2° W., 31.4 ft. dist., with a railroad spike in the face and no marks visible.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 12' 40" W., beginning new measurement, continue posting and blazing.</p>														
1395	<p>Creek, 1 ft. wide, course S. 30° E.</p>														
2590.67	<p>The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above a mound of stone, 2 ft. base, 5 ins. high, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 25 S</td> <td style="padding: 0 5px;">R 2 W</td> </tr> <tr> <td style="padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 35</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1962</td> </tr> </table> </div> <p>from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A fir, 47 ins. diam., bears N. 23° E., 38.9 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 33 ins. diam., bears S. 70° E., 51.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. 29 1/4° W., 83.7 ft. dist., with a healed double blaze. (Record, S. 31° W., 85.5 ft.)</p> <p style="padding-left: 40px;">A fir, 78 ins. diam., bears N. 40° W., 28.4 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 43 1/2° E., 9.2 ft. dist., mkd. T25S R2W S36 BT.</p> <p>Discontinue posting and blazing.</p> <p>From this cor., the S 1/16 sec. cor. of secs. 25 and 26 bears N. 2° 39' 08" W., 1473.71 ft. dist., perpetuated by the Douglas County Surveyor's Office in 1992, filed in the Douglas County Surveyor's Office, C.S. File No. 64/23-13, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="2" style="padding: 0 5px;">S 1/16</td> </tr> <tr> <td style="padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1974</td> </tr> </table> </div>	T 25 S	R 2 W	S 26	S 25	S 35	S 36	1962		S 1/16		S 26	S 25	1974	
T 25 S	R 2 W														
S 26	S 25														
S 35	S 36														
1962															
S 1/16															
S 26	S 25														
1974															

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of bearing trees mkd. by Berry, Wofford, Popken, and Baughman</p> <p>A hemlock stump, size indeterminate, bears N. 47° E., 55.4 ft. dist., alongside of which is a decayed trunk, size indeterminate, with a partially healed blaze.</p> <p>A hemlock stump, 21 ins. diam., bears S. 73 1/2° W., 24.4 ft. dist., with scribe marks S 1/16 S26 BT visible on an open blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A hemlock, 27 ins. diam., bears S. 15 1/4° W., 95.9 ft. dist., with a healed double blaze.</p> <p>A hemlock, 30 ins. diam., bears S. 43 1/4° W., 79.7 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p>A fir, 12 ins. diam., bears N. 75 3/4° E., 27.3 ft. dist., mkd. S 1/16 S25 BT.</p> <p>From this same cor., the E 1/16 sec. cor. of secs. 26 and 35, bears N. 89° 17' 10" W., 1318.34 ft. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above a mound of stone, 2 ft. base, 12 ins. high, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 26 E 1/16 ——— S 35 1974</p> </div> <p>from which bearing trees mkd. by Berry, Wofford, Popken, and Baughman</p> <p>A fir, 17 ins. diam., bears S. 13° W., 57.1 ft. dist., with a healed blaze.</p> <p>A fir, 20 ins. diam., bears N. 33° W., 11.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17, perpetuated by Harvey M. Christensen, Oregon PLS No. 2603, in 1999, filed in the Douglas County Surveyor's Office, C.S. File No. 65/23-11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, (alongside of which is an iron pipe, 2 in. diam., firmly set, projecting 15 ins. above the ground), with brass cap mkd.</p> <div style="text-align: center;"> <p>S 8 1/4 ——— S 17 T 25 S R 2 W 1962</p> </div>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed hemlock stump, size indeterminate, bears S. 6° W., 13.2 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A decayed hemlock stump, size indeterminate, bears N. 21° W., 25.1 ft. dist., with scribe marks 1/4 S8 visible on a partially healed blaze.</p> <p>and bearing trees mkd. by Christensen</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 34 1/4° E., 11.6 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 60 1/2° E., 39.9 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 70 1/4° W., 31.1 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 86 3/4° W., 27.9 ft. dist., with a healed double blaze.</p> <p>S. 88° 43' 56" W., bet. secs. 8 and 17, posting and blazing.</p>								
1880	Graveled road, 20 ft. wide, bears N. 55° W. and S. 55° E.								
2483.04	<p>The cor. of secs. 7, 8, 17, and 18, perpetuated by Harvey M. Christensen, Oregon PLS No. 2603, in 1999, filed in the Douglas County Surveyor's Office, C.S. File No. 65/23-12, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 25 S</td> <td style="padding: 0 10px;">R 2 W</td> </tr> <tr> <td style="padding: 0 10px;">S 7</td> <td style="padding: 0 10px;">S 8</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S 18</td> <td style="border-top: 1px solid black; padding: 0 10px;">S 17</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1962</td> </tr> </table> </div> <p>from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A decayed hemlock stump, size indeterminate, bears N. 18° E., 19.1 ft. dist., with fragmentary scribe marks visible on blazed fragment lying alongside.</p> <p style="padding-left: 40px;">A sawed fir stump, 48 ins. diam., bears S. 51° W., 54.1 ft. dist., with scribe marks 2W 8 BT visible on open double blaze.</p> <p style="padding-left: 40px;">A fir, 53 ins. diam., bears N. 64° W., 39.6 ft. dist., with a healed blaze.</p>	T 25 S	R 2 W	S 7	S 8	S 18	S 17	1962	
T 25 S	R 2 W								
S 7	S 8								
S 18	S 17								
1962									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>and the remains of bearing trees mkd. by Vernon W. Hosford, Oregon PLS No. 253, in 1957, filed in the Douglas County Surveyor's Office, C.S. File No. 42/308, reported by Brooks</p> <p>A sawed, decayed cedar stump, 48 ins. diam., bears N. 4° E., 58.7 ft. dist., with scribe marks S8 253 visible on a partially healed blaze.</p> <p>A fir stump, 60 ins. diam., bears S. 54° E., 54.1 ft. dist., with no marks visible.</p> <p>A decayed hemlock stump, size indeterminate, bears S. 30 3/4° W., 109.6 ft. dist., with no marks visible. (Record, S. 32 1/2° W.)</p> <p>and bearing trees mkd. by Brooks</p> <p>A decayed hemlock snag, 15 ins. diam., bears N. 28° E., 134.9 ft. dist., with no marks visible. (Record, 137.3 ft.)</p> <p>A hemlock snag, 24 ins. diam., bears S. 77 1/2° E., 113.5 ft. dist., with no marks visible on a partially healed blaze. (Record, S. 76 1/2° E.)</p> <p>and the remains of bearing trees mkd. by Christensen</p> <p>A fir, 11 ins. diam., bears N. 57 1/2° E., 14.2 ft. dist., with a healed blaze.</p> <p>A roothole bears S. 76 3/4° E., 35.9 ft. dist., alongside of which is a fir trunk, 9 ins. diam., with a healed blaze.</p> <p>A fir, 12 ins. diam., bears S. 77 3/4° W., 12.0 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 12 ins. diam., bears S. 59 3/4° E., 38.9 ft. dist., mkd. T25S R2W S17 BT.</p> <hr/> <p>N. 89° 02' 12" W., bet. secs. 7 and 18, continue posting and blazing.</p>
2110	Creek, 1.5 ft. wide, course S. 10° E.
2651.07	The 1/4 sec. cor. of secs. 7 and 18, perpetuated by the Douglas County Surveyor's Office in 1995, filed in the Douglas County Surveyor's Office, C.S. File No. 64/63-5, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with a mound of stone, 2 ft. base, 6 ins. high, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">S 7 1/4 ——— S 18 T 25 S R 2 W 1962</p>
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A hemlock stump, 28 ins. diam., bears S. 12 1/4° W., 39.4 ft. dist., with a healed blaze. (Record, S. 16° W., 40.9 ft. dist.)</p> <p>and the remains of a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A sawed hemlock stump, 16 ins. diam., bears N. 50° W., 51.5 ft. dist., with a healed blaze and a metal cover.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 28 1/4° E., 8.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A chinquapin, 7 ins. diam., bears S. 89° E., 9.9 ft. dist., with scribe marks 1/4 S18 CS BT visible on a partially healed double blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 50° E., 3.4 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 83° 05' 17" W., beginning new measurement, continue posting and blazing.</p>
90	Graveled road, 15 ft. wide, bears N. 75° W. and S. 55° W.
225	Graveled road, 12 ft. wide, bears N. 40° E. and S. 40° W.
1935.73	The closing cor. of secs. 7 and 18 only, on the W. bdy. of the Tp.
	Discontinue posting and blazing
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0° 03' 37" E., bet. secs. 7 and 8, posting and blazing.</p>
1329.25	<p>The S 1/16 sec. cor. of secs. 7 and 8, established by Vernon W. Hosford, Oregon PLS No. 253, in 1957, and is accepted as the cor., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, from which the remains a bearing tree mkd. by Hosford</p> <p style="padding-left: 40px;">A sawed, decayed cedar stump, 33 ins. diam., bears S. 84° W., 19.0 ft. dist., with a healed blaze and a "W" nail in lower chaining notch.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>and bearing trees of unknown origin</p> <p style="padding-left: 40px;">A hemlock, 11 ins. diam., bears S. 62 1/2° W., 21.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears N. 7° W., 17.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>S 1/16 S 7 S 8 2010</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' 48" E., beginning new measurement, continue posting and blazing.</p>
435	<p>Creek, 1 ft. wide, course S. 65° E.</p>
1328.99	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, (alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground), with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>1/4 S 7 S 8 T 25 S R 2 W 1962</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A roothole bears N. 33° W., 9.9 ft. dist., alongside of which is a fallen yew trunk, 11 ins. diam., with no marks visible on a decayed blaze.</p> <p>and the remains of accessories mkd. by Brooks</p> <p style="padding-left: 40px;">A roothole bears N. 44 1/2° E., 75.2 ft. dist., alongside of which is a fallen yew trunk, 16 ins. diam., with no marks visible.</p> <p style="padding-left: 40px;">A rock outcrop bears S. 68 1/2° W., 12.5 ft. dist., mkd. X BO. (Record, S. 73° W., 13.2 ft. dist.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 37° E., 20.1 ft. dist., mkd. 1/4 S8 BT.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET	<p>A fir, 18 ins. diam., bears S. 12 3/4° W., 33.7 ft. dist., mkd. 1/4 S7 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 50' 58" W., beginning new measurement, continue posting and blazing.</p>												
2515	<p>Creek, 4 ft. wide, course N. 85° E.</p>												
2656.39	<p>The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 25 S</td> <td style="padding: 0 5px;">R 2 W</td> </tr> <tr> <td style="padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 7</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1951</td> </tr> </table> </div> <p>from which the original bearing trees</p> <ul style="list-style-type: none"> A yew, 14 ins. diam., bears N. 52 3/4° E., 42.9 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. A fir, 28 ins. diam., bears S. 34 1/2° E., 7.3 ft. dist., with a healed blaze. A yew, 19 ins. diam., bears S. 56° W., 46.2 ft. dist., with a healed blaze. A yew, 16 ins. diam., bears N. 77 3/4° W., 38.9 ft. dist., with no marks visible on an open, decayed blaze. <p>and the remains of bearing trees mkd. by Tallett and White</p> <ul style="list-style-type: none"> A fir, 58 ins. diam., bears N. 31 3/4° E., 29.7 ft. dist., with a healed blaze. A sawed fir stump, 45 ins. diam., bears N. 86 1/2° W., 50.2 ft. dist., with a healed blaze. <p>Discontinue posting and blazing.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="padding: 0 5px;">1/4 ———</td> </tr> <tr> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="padding: 0 5px;">1951</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p>	T 25 S	R 2 W	S 6	S 5	S 7	S 8	1951		S 6	1/4 ———	S 7	1951
T 25 S	R 2 W												
S 6	S 5												
S 7	S 8												
1951													
S 6													
1/4 ———													
S 7													
1951													

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>A burnt, decayed fir stump, size indeterminate, bears N. 17° E., 21.1 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Tallett and White</p> <p>A roothole bears N. 46 1/4° E., 40.3 ft. dist., lying downhill from which is a sawed, decayed fir stump, size indeterminate, with a partially healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 5 ins. diam., bears S. 24 1/4° W., 14.5 ft. dist., mkd. 1/4 S7 BT.</p> <p>A fir, 5 ins. diam., bears N. 28 1/2° W., 10.2 ft. dist., mkd. 1/4 S6 BT.</p> <p>S. 83° 34' 27" W., bet. secs. 6 and 7, posting and blazing.</p>
1305	Graveled road, 12 ft. wide, bears N. 10° E. and S. 5° E.
1873.85	<p>The closing cor. of secs. 6 and 7, on the W. bdy. of the Tp.</p> <p>Discontinue posting and blazing.</p> <hr/> <p align="center">Subdivision of Section 26, T. 25 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35, perpetuated by the Douglas County Surveyor's Office in 1967, filed in the Douglas County Surveyor's Office, C.S. File No. 54/27, occupied by the original cor. tree, a hemlock snag, 7 ins. diam., with no marks remaining, alongside of which is an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T25S 1/4 S26 S35 R2W 1967</p> <p>from which the original bearing trees</p> <p>A hemlock, 12 ins. diam., bears S. 8° E., 16.5 ft. dist., with scribe marks 4S visible on an open blaze.</p> <p>A hemlock, 36 ins. diam., bears N. 10° W., 2.0 ft. dist., with scribe marks 4S visible on an open blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A hemlock, 29 ins. diam., bears S. 25° W., 41.9 ft. dist., with a healed blaze.</p> <p>A hemlock, 23 ins. diam., bears N. 64° W., 4.6 ft. dist., with a healed blaze.</p> <p>and a reference monument established by Berry, Popken, Wofford, and Baughman</p>

**Subdivision of Section 26,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>An iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, bears S. 10° 11' 55" W., 9.89 ft. dist., with brass cap mkd. T25S R2W S35 RM 1974 and an arrow pointing to the cor.</p> <p>From this cor., the E 1/16 sec. cor. of secs. 26 and 35, bears S. 89° 11' 00" E., 1320.95 ft. dist.</p> <p>N. 1° 22' 35" W., on the N. and S. centerline of sec. 26.</p>
1453.66	<p>The center S 1/16 sec. cor. of sec. 26, established by Nick Juliano, Oregon PE No. 3449, in 1973, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above a mound of stone, 1 1/2 ft. base, 10 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 2 W S 26 CS 1/16 1973</p> <p>from which the remains of bearing trees mkd. by Juliano</p> <p style="padding-left: 40px;">A fir snag, 47 ins. diam., bears S. 71 1/2° E., 21.2 ft. dist., with a railroad spike in the face and no marks visible.</p> <p style="padding-left: 40px;">A roothole bears S. 26° W., 26.7 ft. dist., alongside of which is a cedar trunk, 36 ins. diam., with no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A hemlock, 5 ins. diam., bears S. 47° E., 6.3 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A hemlock, 5 ins. diam., bears S. 66 1/2° W., 2.8 ft. dist., mkd. CS 1/16 S26 BT.</p> <hr style="width: 20%; margin: 10px auto;"/>
1453.76	<p>N. 1° 18' 14" W., beginning new measurement.</p> <p>The center 1/4 sec. cor. of sec. 26, established by Nick Juliano, Oregon PE No. 3449, in 1973, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 2 W S 26 C 1/4 1973</p> <p>from which the remains of bearing trees mkd. by Juliano</p> <p style="padding-left: 40px;">A sawed fir stump, 47 ins. diam., bears S. 53 1/2° E., 10.2 ft. dist., with a railroad spike in the face and no marks visible.</p>

**Subdivision of Section 26,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">A sawed fir stump, 57 ins. diam., bears N. 21 1/2° W., 22.0 ft. dist., with a railroad spike in the face and no marks visible.</p> <p>and new bearing trees</p> <p style="text-align: center;">A fir, 11 ins. diam., bears N. 37° E., 2.0 ft. dist., mkd. C 1/4 S26 BT.</p> <p style="text-align: center;">A fir, 11 ins. diam., bears N. 61 1/4° W., 24.7 ft. dist., mkd. C 1/4 S26 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 21' 48" W., beginning new measurement.</p>
2645.94	<p>The true point for the 1/4 sec. cor. of secs. 23 and 26, determined at record bearing and dist. from the remains of an original bearing tree</p> <p style="text-align: center;">A sawed hemlock stump, 14 ins. diam., bears S. 25° E., 20.5 ft. dist., with scribe marks 1/4 visible on a partially healed blaze.</p> <p>and the remains of a bearing tree mkd. by Brooks, reported by Skeesick</p> <p style="text-align: center;">A sawed hemlock stump, 26 ins. diam., bears S. 3° E., 46.2 ft. dist., with no marks visible.</p> <p>The cor. point is located in a creek, 1 ft. wide, course N. 75° W., not monumented.</p> <p>From this cor., a point established by the Douglas County Surveyor's Office in 1981 as witness cor. for the 1/4 sec. cor. of secs. 23 and 26, bears East, 10.00 ft. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. DOUGLAS COUNTY SURVEYOR T25S WC 1/4 S23 S26 R2W 1981 and an arrow pointing to the cor., from which the remains of bearing trees mkd. by the Douglas County Surveyor's Office, reported by Skeesick</p> <p style="text-align: center;">A bridge spike driven into top of a fir stump, 48 ins. diam., bears N. 19° E., 6.4 ft. mkd. WC BO1.</p> <p style="text-align: center;">A bridge spike driven into top of fir stump, 48 ins. diam., bears S. 82 1/2° E., 35.9 ft. dist., mkd. WC BO2.</p> <p>and bearing trees mkd. by Skeesick</p> <p style="text-align: center;">A fir, 9 ins. diam., bears N. 28° E., 25.9 ft. dist., with a healed double blaze.</p> <p style="text-align: center;">A cedar, 16 ins. diam., bears S. 30° W., 13.2 ft. dist., with scribe marks WC 1/4 S26 BT visible on a partially healed blaze.</p> <p style="text-align: center;">A fir, 14 ins. diam., bears N. 39 1/4° W., 27.4 ft. dist., with a healed double blaze.</p> <hr style="width: 60%; margin: 10px auto;"/>

**Subdivision of Section 26,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>From the 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above a mound of stone, 1 ft. base, 6 ins. high, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 26 S 25 T 25 S R 2 W 1962</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears S. 59° E., 19.1 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears N. 33 1/2° W., 6.9 ft. dist., with a healed blaze.</p> <p>From this cor., the S 1/16 sec. cor. of secs. 25 and 26 bears S. 2° 47' 19" E., 1477.41 ft. dist.</p> <p>S. 89° 51' 52" W., on the E. and W. centerline of sec. 26, posting and blazing.</p>
1283.66	<p>The center E 1/16 sec. cor. of sec. 26, established by Nick Juliano, Oregon PE No. 3449, in 1973, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above a collar of stone, 2 ft. base, 6 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 2 W S 26 CE 1/16 1973</p> <p>from which the remains of bearing trees of unknown origin</p> <p style="padding-left: 40px;">A sawed fir stump, 38 ins. diam., bears N. 34 1/2° E., 19.2 ft. dist., with a "W" nail in the face and no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 53 ins. diam., bears S. 6 1/4° W., 68.7 ft. dist., with a "W" nail in the face and no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 21 1/4° W., 10.8 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 30 3/4° W., 12.2 ft. dist., mkd. CE 1/16 S26 BT.</p> <p>Discontinue posting and blazing.</p> <p style="text-align: center;">_____</p> <p>S. 89° 52' 17" W., beginning new measurement.</p>

**Subdivision of Section 26,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
1282.98	<p>The center 1/4 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 89° 52' 07" W., beginning new measurement.</p>
1388.86	Point for the center W 1/16 sec. cor. of sec. 26, not monumented.
2777.72	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, (alongside of which is a basalt stone 14 x 10 ins., with no marks visible), with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 27 S 26 T 25 S R 2 W 1962</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A yew, 12 ins. diam., bears S. 81° E., 21.1 ft. dist., with no marks visible on a decayed blaze.</p> <p style="padding-left: 40px;">A sawed yew stump, 10 ins. diam., bears S. 80 1/2° W., 25.1 ft. dist., with no marks visible. (Record, S. 85° W.)</p> <p>and the remains of a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A sawed fir stump, 37 ins. diam., bears S. 19 1/2° W., 27.1 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears S. 58 3/4° W., 21.4 ft. dist., mkd. 1/4 S27 BT.</p> <p>From this cor., the S 1/16 sec. cor. of secs. 26 and 27 bears S. 3° 57' 38" E., 1438.33 ft. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S 27 S 26 1974</p> </div> <p>from which bearing trees mkd. by Berry, Wofford, Popken, and Baughman</p> <p style="padding-left: 40px;">A hemlock, 28 ins. diam., bears N. 70° E., 58.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 38 ins. diam., bears S. 25 1/2° W., 29.4 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 0 auto;"/>

**Subdivision of Section 26,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>From the SE 1/16 sec. cor. of sec. 26, established by Nick Juliano, Oregon PE No. 3449, in 1973, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p align="center">T 25 S R 2 W S 26 SE 1/16 1973</p> <p>from which the remains of bearing trees mkd. by Juliano</p> <p style="padding-left: 40px;">A fir stump, 24 ins. diam., bears N. 24 1/2° E., 11.3 ft. dist., with a railroad spike in the face and no marks visible.</p> <p style="padding-left: 40px;">A fir stump, 29 ins. diam., bears S. 54° E., 16.0 ft. dist., with a railroad spike in face and no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A hemlock, 7 ins. diam., bears N. 0 3/4° E., 14.3 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 46 1/4° E., 3.4 ft. dist., mkd. SE 1/16 S26 BT.</p> <p>From this cor., the E 1/16 sec. cor. of secs. 26 and 35 bears S. 2° 06' 53" E., 1466.07 ft. dist.</p> <p>From this same cor., the S 1/16 sec. cor. of secs. 25 and 26 bears S. 89° 35' 18" E., 1304.09 ft. dist.</p> <p>N. 2° 01' 05" W. on the N. and S. centerline of the SE 1/4 of sec. 26, posting and blazing.</p>
1464.16	<p>The center E 1/16 sec. cor. of sec. 26</p> <hr/> <p>From the SE 1/16 sec. cor. of sec. 26.</p> <p>N. 89° 41' 32" W., on the E. and W. centerline of the SE 1/4 of sec. 26, posting and blazing.</p>
1301.56	<p>The center S 1/16 sec. cor. of sec. 26.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p align="center">T 25 S R 2 W S 26 W 1/16 ——— S 35 1973</p>

**Subdivision of Section 26,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>from which the remains of bearing trees mkd. by Nick Juliano, Oregon PE No. 3449, in 1973, reported by Berry, Wofford, Popken, and Baughman</p> <p style="padding-left: 40px;">A fir snag, 13 ins. diam., bears N. 21 1/2° E., 3.6 ft. dist., with a railroad spike in the face and a healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 15 ins. diam., bears S. 1° W., 10.6 ft. dist., with a railroad spike in the face and a healed blaze.</p> <p>and the remains of bearing trees mkd. by Berry, Wofford, Popken, and Baughman</p> <p style="padding-left: 40px;">A sawed fir stump, 14 ins. diam., bears N. 33 1/2° E., 22.1 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 23 1/2° W., 18.5 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 4 ins. diam., bears S. 85 1/4° E., 11.4 ft. dist., mkd. X BT.</p> <p>From this cor., the 1/4 sec. cor. of secs. 26 and 35 bears S. 89° 29' 22" E., 1322.91 ft. dist.</p> <p>N. 2° 40' 01" W., on the N. and S. centerline of the SW 1/4 of sec. 26, posting and blazing.</p>
1447.02	<p>The SW 1/16 sec. cor. of sec. 26, established by Nick Juliano, Oregon PE No. 3449, in 1973, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 2 ft. diam., 6 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 2 W SW 1/16 S 26 1973</p> <p>from which the remains of bearing trees mkd. by Juliano</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 17 ins. diam., bears N. 3 1/2° E., 6.1 ft. dist., with a railroad spike in the face and no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 38 ins. diam., bears S. 43 3/4° E., 21.9 ft. dist., with a railroad spike in the face and no marks visible.</p> <p>and the remains of a bearing tree of unknown origin</p> <p style="padding-left: 40px;">A sawed fir stump, 54 ins. diam., bears N. 70 1/2° E., 38.5 ft. dist., with a "W" nail in the face and no marks visible.</p> <p>and new bearing trees</p>

**Subdivision of Section 26,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">A fir, 7 ins. diam., bears S. $1\ 1/2^\circ$ E., 2.4 ft. dist., mkd. SW 1/16 S26 BT.</p> <p style="text-align: center;">A fir, 8 ins. diam., bears N. $46\ 1/2^\circ$ W., 9.5 ft. dist., mkd. X BT.</p> <p>From this cor., the S 1/16 sec. cor. of secs. 26 and 27 bears N. $89^\circ\ 39'\ 28''$ W., 1356.46 ft. dist.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 26.</p> <p>N. $89^\circ\ 49'\ 50''$ W., on the E. and W. centerline of the SW 1/4 sec. 26, posting and blazing.</p>
1355.19	<p>The SW 1/16 sec. cor. of sec. 26.</p> <hr/>