

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH BOUNDARY  
AND SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF SECTION 14,  
**TOWNSHIP 23 SOUTH, RANGE 6 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***Kenneth W. Saveland, Cadastral Surveyor***

Under Special Instructions dated March 30, 2010, approved April 5, 2010,  
and Supplemental Special Instructions dated June 16, 2010, approved  
June 16, 2010, which provided for the surveys included under  
Group No. 2308, and Assignment Instructions dated April 5, 2010,  
and June 16, 2010.

***Survey commenced April 8, 2010***

***Survey completed July 12, 2010***

**T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The following field notes are those of the dependent resurvey of portions of the south boundary and subdivisional lines, and the subdivision of section 14, Township 23 South, Range 6 West, of the Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1853, Robert Elder and Henry Gile, U.S. Deputy Surveyors, surveyed the exterior lines of T. 24 S., R. 6 W., as shown on the official plat of survey approved June 30, 1853.

In 1879, William Thiel, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines as shown on the official plat of survey approved April 2, 1879.

In 1883, John A. McQuinn, U.S. Deputy Surveyor, surveyed the remainder of the subdivisional lines as shown on the official plat of survey approved April 7, 1884.

In 1891, Williams R. Whipple, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines of T. 24 S., R. 6 W., as shown of the official plat of survey approved February 3, 1892.

In 1943-57, Otis O. Gould, Cadastral Engineer, and Joseph S. Gawron and Orville N. Eggen, Cadastral Surveyors, resurveyed the Fifth Standard Parallel South along the north boundary of the township, and a portion of the north boundary of T. 23 S., R. 7 W., and the east, south, and west boundaries and subdivisional lines as shown on the official plat of survey accepted August 24, 1960.

In 1982-83, James E. Jelley, Wayne L. Rogers, and Lance J. Bishop, Cadastral Surveyors, correctively resurveyed the east half mile between section 20 and 29, resurveyed a portion of the subdivisional lines, and subdivided sections 20 and 26 as shown on the official plat of survey accepted February 8, 1985.

In 1986-95, Wayne L. Rogers, Boyd W. Peterson, Philip G. Griffin, and Dale T. Bedell, Cadastral Surveyors, and Robert H. Browning, Surveying Technician, correctively resurveyed a portion of the south, east, and west boundaries and subdivisional lines, correctively surveyed sections 20 and 26, resurveyed a portion of the north boundary (Fifth Standard Parallel South) and portions of the east and south boundaries and subdivisional lines, and subdivided sections 1, 25, and 28 as shown on the official plat of survey accepted October 17, 1995.

In 1996, Wayne L. Rogers, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, correctively resurveyed a portion of the subdivisional lines, and resurveyed a portion of the north boundary (Fifth Standard Parallel South) and subdivisional lines as shown on the official plat of survey accepted September 4, 1998.

In 2005, Timothy J. Moore, Cadastral Surveyor, remonumented and amended the original corner of sections 9, 10, 15, and 16, as shown in the official field notes approved August 7, 2006.

In 2010, Kenneth W. Saveland, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines of T. 24 S., R. 6 W., under Group 2314, Oregon, not yet approved.

**T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The following records filed in the Douglas County Surveyor's Office were evaluated and are referred to in subsequent corner descriptions and are referenced by the surveyor's last name, title or Professional Land Surveyor (PLS) number, and year.

<u>Year</u>	<u>Name and Title or Registration Number</u>	<u>File Type</u>	<u>File No.</u>
1956	Wilford N. Haines PLS No. 239 and Leo J. Marvin PLS No. 363	Roll Map	RM 1-17
1962	Milo E. Godfrey, Deputy County Surveyor	C.S.	52/102
1964	Wilford N. Haines PLS No. 239	Survey	M30-51
1972	Douglas County Surveyor's Office	C.S.	49/143
1973	Douglas County Surveyor's Office	C.S.	56/25
1975	Douglas County Surveyor's Office	C.S.	57/21
1982	Douglas County Surveyor's Office	C.S.	61/36
1987	Douglas County Surveyor's Office	C.S.	62/40
1992	Ken W. Hoffine PLS No. 2291	C.S.	63/138-19C
2002	David A. Edwards PLS No. 2339	Survey	M140-13
2005	Douglas County Surveyor's Office	C.S.	67/13-14

The survey was executed in accordance with the specification set forth in the *Manual of Surveying Instructions* (2009), the Special Instructions dated March 30, 2010, and the Supplemental Special Instructions dated June 16, 2010, for Group No. 2308, Oregon.

The directions of the lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) techniques and are carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through conventional survey techniques. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data were thoroughly verified and only the corner descriptions are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Only those lines bounding Federal interest land were blazed.

The geographic position in NAD 1983 (CORS 96) of the following corners as determined by ties from temporary GPS control points established utilizing dual frequency, carrier phase GPS receivers and processed using for control National Spatial Reference System Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP" and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", are:

The 1/4 section corner of sections 2 and 35 on the south boundary of the township.

Latitude: 43° 31' 09.87" N. Longitude: 123° 22' 33.97" W.

**T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The corner of sections 13, 14, 23, and 24:

Latitude: 43° 33' 42.44" N. Longitude: 123° 21' 59.50" W.

The 1/4 section corner of sections 14 and 15:

Latitude: 43° 34' 04.38" N. Longitude: 123° 23' 05.47" W.

The corner of sections 2, 3, 10, and 11:

Latitude: 43° 35' 25.05" N. Longitude: 123° 23' 09.04" W.

The 1/4 section corner of sections 21 and 28:

Latitude: 43° 32' 52.51" N. Longitude: 123° 24' 57.21" W.

---

**Dependent Resurvey of a Portion of South Boundary,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1975, subsequently perpetuated by person(s) unknown, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

T 23 S		R 6 W
S 35		S 36
-----		
S 2		S 1
T 24 S		
1943		

from which the remains of an original bearing tree

A roothole bears N. 74 1/2° E., 66.0 ft. dist., downhill of which is a portion of a down, burnt, decayed madrone snag, size indeterminate, with no marks visible.

and the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 35 ins. diam., bears N. 62 1/2° E., 64.7 ft. dist., with a healed blaze.

A sawed, decayed fir stump, 26 ins. diam., bears S. 43 1/2° E., 17.2 ft. dist., with a healed blaze.

A sawed, decayed fir stump, size indeterminate, bears S. 33 1/2° W., 21.1 ft. dist., with scribe marks BT visible on an open blaze.

A fir, 40 ins. diam., bears N. 23° W., 44.9 ft. dist., with a healed blaze. (Record, 48.8 ft. dist.)

and a bearing tree mkd. by the Douglas County Surveyor's Office

A fir, 23 ins. diam., bears S. 68 1/2° W., 11.1 ft. dist., with a healed double blaze.

and a bearing tree mkd. by person(s) unknown

A fir stump, 4 ins. diam., bears S. 58 1/4° E., 7.4 ft. dist., downhill of which is a down fir snag, 4 ins. diam., with scribe marks S1 BT visible on an open blaze and a metal tag mkd. LS 2339 2002.

and a new bearing tree

A fir, 6 ins. diam., bears S. 54 1/4° E., 92.1 ft. dist., mkd. T24S R6W S1 BT.

Corner is located in a down, woven and barbed wire fence line extending E. and W., 25 ft. E. of a seasonal creek, 2 ft. wide, course S. 70° E.

---

**Dependent Resurvey of a Portion of South Boundary,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 2 and 35, on the S. bdy of the Tp., perpetuated by Edwards, PLS No. 2339, in 2002, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with a brass cap mkd.

S 35  
1/4 ———  
S 2  
1943

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

- A decayed fir stump, size indeterminate, bears N. 23 1/2° E., 38.3 ft. dist., with no marks visible. (Record, N. 19° E.)
- A roothole bears S. 24° W., 31.7 ft. dist., alongside of which is an uprooted, sawed, decayed fir stump, size indeterminate, with no marks visible.

and bearing trees mkd. by Edwards

- A fir, 28 ins. diam., bears N. 50 3/4° E., 15.9 ft. dist., with a healed blaze.
  - A fir, 6 ins. diam., bears S. 54 3/4° W., 28.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.
  - A fir, 15 ins. diam., bears N. 8° W., 20.8 ft. dist., with a healed blaze.
-

**Dependent Resurvey of a Portion of South Boundary,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1973, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.

T 23 S	R 6 W
S 34	S 35
S 3	S 2
T 24 S	
1943	

from which the remains of an original bearing tree

- A decayed fir snag, size indeterminate, bears N.  $46\frac{3}{4}^{\circ}$  W., 17.8 ft. dist., with scribe mark S visible on an opened blaze. (Record, N.  $33^{\circ}$  W., 15.2 ft. dist.)

and the remains of bearing trees mkd. by Gould, Gawron, and Eggen

- A roothole bears S.  $30\frac{1}{2}^{\circ}$  E., 43.6 ft. dist., alongside of which is an uprooted, sawed, decayed fir stump, size indeterminate, with scribe marks R6W visible on an open blaze.
- A sawed, decayed fir stump, size indeterminate, bears S.  $45^{\circ}$  W., 45.5 ft. dist., with no marks visible.
- A roothole bears N.  $57\frac{1}{2}^{\circ}$  W., 27.7 ft. dist., alongside of which is an uprooted, sawed, decayed cedar stump, size indeterminate, with no marks visible.

and bearing trees mkd. by the Douglas County Surveyor's Office


- A fir, 30 ins. diam., bears N.  $56\frac{3}{4}^{\circ}$  E., 24.0 ft. dist., with a healed blaze.
- A fir, 37 ins. diam., bears S.  $72^{\circ}$  E., 99.0 ft. dist., with a healed blaze.
- A fir, 33 ins. diam., bears S.  $80\frac{3}{4}^{\circ}$  W., 84.5 ft. dist., with a healed blaze.
- A cedar, 39 ins. diam., bears N.  $22\frac{1}{2}^{\circ}$  W., 26.7 ft. dist., with a healed blaze.

Corner is located 70 ft. S. of a gravel road, 11 ft. wide, bears N.  $85^{\circ}$  W. and S.  $85^{\circ}$  E., and 195 ft. E. of the same gravel road, bears N.  $10^{\circ}$  W. and S.  $30^{\circ}$  E., and 2 ft. W. of a creek, 1 ft. wide, course N.  $45^{\circ}$  W.

---

**Dependent Resurvey of a Portion of South Boundary,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The witness cor. to the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above a mound of stone, 2 ft. diam., 1 ft. high, (alongside of which is a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 24 ins. above the mound of stone, with a brass washer mkd. WILFORD N. HAINES SURVEY 239 DRAIN, ORE., with a tack in center) with a brass cap mkd.



from which bearing trees mkd. by Gould, Gawron, and Eggen

- A fir, 13 ins. diam., bears N.  $1\ 1/2^\circ$  E., 18.5 ft. dist., with axe mark X visible and a healed blaze at base.
- A fir, 12 ins. diam., bears S.  $10\ 1/4^\circ$  E., 11.2 ft. dist., with axe mark X visible and a healed blaze at base.

The true point for the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., in a location impracticable to establish a permanent monument, determined at Elder and Gile's record bearings and distances from the original bearing trees

- A fir, 43 ins. diam., bears S.  $83^\circ$  W., 37.6 ft. dist., with a hollow blaze. (Gould, Gawron, and Eggen's record is S.  $84^\circ$  W., 46.9 ft. dist.)
- A fir, 39 ins. diam., bears N.  $37^\circ$  W., 10.6 ft. dist., with illegible scribe marks visible on a partially healed blaze. (Gould, Gawron, and Eggen's record is N.  $57^\circ$  W., 16.5 ft. dist.)

Note: Bearings and dists. from the true point for the original 1/4 sec. cor. of secs. 3 and 34 to the original bearing trees were erroneously reported by Gould, Gawron, and Eggen in 1943-57 as bearings and dists. from the witness cor. to the original bearing trees.

**Dependent Resurvey of a Portion of South Boundary,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above a mound of stone, 2 ft. diam., 1 ft. high (alongside of which is a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 7 ins. above the mound of stone, with a brass washer mkd. WILFORD N. HAINES SURVEY 239 DRAIN, ORE., with a tack in center), with a brass cap mkd.

T 23 S	R 6 W
S 33	S 34
S 4	S 3
T 24 S	R 6 W
1957	

from which the remains of the original bearing trees

- A roothole bears S. 3° E., 61.4 ft. dist., downhill of which is a down, decayed fir snag, size indeterminate, with no marks visible.
- A decayed fir stump, 48 ins. diam., bears S. 71° W., 11.2 ft. dist., with scribe marks R6W T24 S4 visible on an open blaze.

and the remains of bearing trees mkd. by Whipple

- A sawed, decayed fir stump, 55 ins. diam., bears N. 48 1/4° E., 45.5 ft. dist., with a healed blaze. (Record, 62 ins. diam.)
- A roothole bears S. 31 1/4° E., 31.7 ft. dist., downhill of which is an uprooted fir snag, 29 ins. diam., with a healed blaze. (Not identified and rescribed as new by Gould, Gawron, and Eggen in 1943-57.)
- A decayed fir stump, 3 ins. diam., bears S. 43° W., 8.6 ft. dist., with scribe mark T visible on an open, pitched blaze.
- A fir, 35 ins. diam., bears N. 17 1/4° W., 16.5 ft. dist., with a healed double blaze. (Misidentified as a bearing tree not of record by Rogers, et al, in 1986-95.)

and the remains of a bearing tree mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

- A fir, 13 ins. diam., bears N. 51 1/2° E., 32.7 ft. dist., with a healed blaze.

and new bearing trees

- A fir, 25 ins. diam., bears S. 72 1/4° E., 45.1 ft. dist., mkd. T24S R6W S3 BT.
- A cedar, 18 ins. diam., bears S. 54 1/2° W., 28.8 ft. dist., mkd. T24S R6W S4 BT.

Corner is located 90 ft. W. of Yellow Creek, 17 ft. wide, course S. 20° E.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.

1/4  
S 35 | S 36  
1943

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A decayed fir stump, size indeterminate, bears N. 27° E., 33.0 ft. dist., with no marks visible.

A roothole bears S. 69° W., 20.5 ft. dist.

and new bearing trees

A fir, 9 ins. diam., bears N. 64 1/4° E., 36.5 ft. dist., mkd. 1/4 S36 BT.

A fir, 5 ins. diam., bears N. 49° W., 8.4 ft. dist., mkd. 1/4 S35 BT.

The cor. of secs. 25, 26, 35, and 36, perpetuated by the Douglas County Surveyor's Office in 1972, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.

T 23 S    R 6 W  
S 26 | S 25  
-----  
S 35 | S 36  
1943

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Jelley, Rogers, and Bishop in 1982-83

A fir, 41 ins. diam., bears S. 16° E., 56.1 ft. dist., with a healed blaze.

A decayed fir stump, size indeterminate, bears S. 66 1/2° W., 17.8 ft. dist., with no marks visible.

and bearing trees mkd. by the Douglas County Surveyor's Office, reported by Jelley, Rogers, and Bishop in 1982-83

A fir, 24 ins. diam., bears N. 11° E., 21.1 ft. dist., with a healed blaze.

A fir, 34 ins. diam., bears S. 82° W., 11.2 ft. dist., with two healed blazes parallel to one another.

A maple, 22 ins. diam., bears N. 86 1/2° W., 20.5 ft. dist., with a healed blaze.

Corner is located 125 ft. N. of a ridge, bears N. 40° E. and S. 40° W., and 295 ft. E. of a gravel road, 14 ft. wide, bears N. 30° E. and S. 30° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 25 and 26, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
1/4  
S 26 | S 25  
1982

from which the remains of a bearing tree mkd. by McQuinn in 1883, reported by Rogers, et al, in 1986-95

A roothole bears East, 50.8 ft. dist., alongside of which is a down fir snag, size indeterminate, with no marks visible.

and the remains of bearing trees mkd. by Godfrey, reported by Rogers, et al, in 1986-95

A fir, 26 ins. diam., bears N. 11° E., 50.2 ft. dist., with a healed blaze.

A decayed fir stump, size indeterminate, bears S. 41° W., 86.5 ft. dist., with no marks visible.

and a bearing tree mkd. by Jelley, Rogers, and Bishop in 1982-83, reported by Rogers, et al, in 1986-95

A fir, 10 ins. diam., bears S. 53 1/2° W., 8.9 ft. dist., with a healed double blaze.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The N 1/16 sec. cor. of secs. 25 and 26, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.

N  
1/16  
S 26 | S 25  
1957

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Jelley, Rogers, and Bishop in 1982-83

A fir, 24 ins. diam., bears S. 67 1/2° E., 12.5 ft. dist., with a healed blaze.

A decayed fir stump, size indeterminate, bears S. 50 1/2° W., 19.8 ft. dist., with no marks visible.

and the remains of a bearing tree mkd. by Godfrey, reported by Jelley, Rogers, and Bishop in 1982-83

A sawed fir stump, 26 ins. diam., bears N. 7° W., 41.6 ft. dist., with no marks visible.

and a new bearing tree

A fir, 16 ins. diam., bears S. 63° W., 15.4 ft. dist., mkd. N 1/16 S26 BT.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above ground, with a brass cap mkd.

T 23 S	R 6 W
S 23	S 24
S 26	S 25
57	
1943	

from which the remains of the original bearing trees

- A fir, 48 ins. diam., bears East, 52.8 ft. dist., with scribe mark S visible on an opened blaze.
- A decayed fir stump, size indeterminate, bears N. 70° W., 30.4 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

- A decayed fir stump, size indeterminate, bears N. 12° E., 24.4 ft. dist., with no marks visible.
- A decayed fir stump, size indeterminate, bears S. 66° E., 3.3 ft. dist., with scribe marks S R6W S25 visible on an open blaze.
- A chinquapin snag, 23 ins. diam., bears S. 14° W., 42.2 ft. dist., with a healed blaze.
- A roothole bears N. 15° W., 26.4 ft. dist., alongside of which is a down fir snag, size indeterminate, with no marks visible.

and bearing trees mkd. by Jelley, Rogers, and Bishop in 1982-83, reported by Rogers and Browning in 1996

- A fir, 12 ins. diam., bears N. 77° E., 23.1 ft. dist., with a healed blaze.
- A fir, 20 ins. diam., bears S. 52° E., 42.9 ft. dist., with a healed blaze.
- A fir, 12 ins. diam., bears N. 8° W., 6.9 ft. dist., with a healed double blaze.

and a new bearing tree

- A fir, 12 ins. diam., bears S. 24 3/4° W., 30.6 ft. dist., mkd. T23S R6W S26 BT.

Corner is located 95 ft. N. of a ravine, course S. 65° W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
1/4  
S 23 | S 24  
57  
1943

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

A sawed, decayed fir stump, 12 ins. diam., bears S. 56 1/2° E., 29.7 ft. dist., with a healed blaze.

A fir, 28 ins. diam., bears N. 66° W., 34.3 ft. dist., with a healed blaze.

and a bearing tree mkd. by Rogers and Browning in 1996

A fir, 13 ins. diam., bears N. 29° E., 9.9 ft. dist., with a healed blaze. (Record, hemlock.)

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

T 23 S	R 6 W
S 14	S 13
S 23	S 24
1943	

from which the remaining original bearing trees

A fir, 65 ins. diam., bears N.  $57\frac{1}{4}^{\circ}$  E., 74.6 ft. dist., with scribe marks T23 6 and other fragmentary scribe marks visible on bark.

A fir, 55 ins. diam., bears S.  $45\frac{1}{2}^{\circ}$  W., 34.3 ft. dist., with a healed blaze.

A fir, 30 ins. diam., bears N.  $26\frac{1}{2}^{\circ}$  W., 26.4 ft. dist., with no marks visible on a partially healed blaze. (Record, N.  $22\frac{1}{2}^{\circ}$  W.)

and the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

A fir, 56 ins. diam., bears N.  $45\frac{1}{2}^{\circ}$  E., 71.3 ft. dist., with axe marks visible. (Record, N.  $48^{\circ}$  E.)

A sawed, decayed fir stump, size indeterminate, bears S.  $80^{\circ}$  E., 49.5 ft. dist., with no marks visible.

and a bearing tree mkd. by person(s) unknown, reported by Rogers and Browning in 1996

A hemlock, 20 ins. diam., bears S.  $85^{\circ}$  E., 3.3 ft. dist., with a healed double blaze.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 34 and 35, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
1/4  
S 34 | S 35  
1957

from which the remains of bearing trees mkd. by Godfrey

A roothole bears S.  $37\ 1/4^\circ$  E., 74.0 ft. dist., alongside of which is a down, decayed fir snag, 45 ins. diam., with scribe marks 5 B visible on an open blaze.

A cedar, 28 ins. diam., bears N.  $61^\circ$  W., 88.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

and a new bearing tree

A fir, 13 ins. diam., bears N.  $62^\circ$  E., 17.9 ft. dist., mkd. 1/4 S35 BT.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 26, 27, 34, and 35, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, subsequently perpetuated by the Douglas County Surveyor's Office in 1987, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, (alongside of which is a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 15 ins. above ground, with a brass washer mkd. WILFORD N. HAINES SURVEY 239 DRAIN, ORE., with a tack in center) with a brass cap mkd.

T 23 S	R 6 W
S 27	S 26
S 34	S 35
1957	

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

- A decayed maple stump, 28 ins. diam., bears N. 87° E., 141.9 ft. dist., with no marks visible.
- A roothole bears S. 50° E., 32.3 ft. dist., alongside of which is a down cedar snag, 30 ins. diam., with no marks visible.
- A burnt cedar snag, 45 ins. diam., bears S. 34 3/4° W., 91.1 ft. dist., with no marks visible.
- A fir, 47 ins. diam., bears N. 47 1/4° W., 208.6 ft. dist., with a healed blaze.

and a bearing tree mkd. by Godfrey, reported by Rogers, et al, in 1986-95

- A cedar, 45 ins. diam., bears S. 30° E., 90.4 ft. dist., with a healed double blaze.

and a bearing tree mkd. by the Douglas County Surveyor's Office in 1987, previously misidentified as mkd. by person(s) unknown by Rogers, et al, in 1986-95

- An alder, 13 ins. diam., bears N. 14° E., 15.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

and a new bearing tree

- A cedar, 6 ins. diam., bears S. 81 3/4° W., 54.8 ft. dist., mkd. X BT.

Corner is located 115 ft. N. of the an overgrown gravel road, bears N. 85° E. and S. 65° W., in curve, and 285 ft. W. of the same gravel road, 11 ft. wide, bears N. 75° E. and S. 75° W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
S 26  
1/4 ———  
S 35  
1957

from which bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A hemlock, 26 ins. diam., bears N. 39° E., 80.5 ft. dist., with no marks visible on a decayed, partially healed blaze.

A fir, 13 ins. diam., bears S. 11° E., 37.1 ft. dist., with a healed blaze. (Record, 38.3 ft. dist.)

Corner is located 80 ft. E. of a spur, slopes N. 15° W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with a brass cap mkd.

T 23 S	R 6 W
S 15	S 14
1994	

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A decayed fir stump, size indeterminate, bears N. 57° E., 30.4 ft. dist., with no marks visible.

A roothole bears S. 50° E., 46.2 ft. dist., alongside of which is a down fir snag, 30 ins. diam., with no marks visible.

and bearing trees mkd. by Rogers, et al, in 1986-95

A chinquapin, 13 ins. diam., bears S. 80 1/2° W., 87.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

A fir, 22 ins. diam., bears N. 51 1/2° W., 156.4 ft. dist., with a healed blaze.

and new bearing trees

A fir, 8 ins. diam., bears N. 23 1/4° E., 4.5 ft. dist., mkd. T23S R6W S14 BT.

A fir, 8 ins. diam., bears S. 61 3/4° E., 12.8 ft. dist., mkd. T23S R6W S23 BT.

From this cor., a point erroneously reestablished by Gould, Gawron, and Eggen, bears N. 86° 17' 48" E., 7.42 ft. dist., monumented with an iron pipe, 2 ins. diam., firmly set, top 3 ins. below ground surface.

Corner is located 65 ft. S. of a gravel road, 11 ft. wide, bears N. 65° W. and S. 80° E.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
1/4  
S 15 | S 14  
1994

from which the remains of a bearing tree mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A sawed fir stump, 36 ins. diam., bears S. 27 3/4° E., 42.9 ft. dist., with a healed blaze.

and a bearing tree mkd. by Haines, PLS No. 239, in 1965, as an accessory to the 1/4 sec. cor. of secs. 14 and 15 erroneously reestablished by Gould, Gawron, and Eggen, misidentified as a bearing tree mkd. by Gould, Gawron, and Eggen, by Rogers, et al, in 1986-95

A fir, 36 ins. diam., bears S. 60 1/2° W., 15.8 ft. dist., with a healed double blaze and scribe marks 239 visible on bark.

and a new bearing tree

A hemlock, 16 ins. diam., bears S. 74 1/4° E., 42.6 ft. dist., mkd. 1/4 S14 BT.

Corner is located on a steep E. bank, 15 ft. W. of Snail Creek, 4 ft. wide, course N. 10° W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above a collar of stone, with a brass cap mkd.

S 2  
1/4 —  
S 11  
1943

from which the remains of a bearing mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

A decayed fir stump, 22 ins. diam., bears N. 42° W., 12.5 ft. dist., with no marks visible.

and bearing trees mkd. by Rogers and Browning in 1996

A hemlock, 16 ins. diam., bears S. 59 1/2° W., 37.6 ft. dist., with a healed blaze.

A hemlock, 10 ins. diam., bears N. 36 3/4° W., 34.8 ft. dist., with a healed blaze.  
(Record, N. 35° W., 37.6 ft. dist.)

Corner is located 6 ft. E. of a creek, 1 ft. wide, course N. 10° W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 2, 3, 10, and 11, perpetuated by the Douglas County Surveyor's Office in 1982, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above a collar of stone, with a brass cap mkd.

T 23 S	R 6 W
S 3	S 2
S 10	S 11
1943	

from which a bearing tree mkd. by person(s) unknown, reported by Gould, Gawron, and Eggen, subsequently reported as an original bearing tree by Rogers and Browning in 1996

A fir, 60 ins. diam., bears S. 80° E., 15.5 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

A sawed cedar stump, 36 ins. diam., bears N. 29 1/2° E., 58.1 ft. dist., with a healed blaze. (Record, N. 31 3/4° E.)

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office, reported by Rogers and Browning in 1996

A sawed ash stump, 9 ins. diam., bears S. 44 3/4° W., 33.9 ft. dist., with scribe marks W S10 CS BT visible on bark. (Record, alder, S. 42 1/2° W.)

A decayed fir stump, 8 ins. diam., bears N. 31° W., 14.5 ft. dist., with no marks visible.

and a bearing tree mkd. by Rogers and Browning in 1996

A fir, 10 ins. diam., bears N. 10 3/4° E., 11.2 ft. dist., with a healed blaze. (Record, N. 15 1/2° E.)

and new bearing trees

An alder, 9 ins. diam., bears S. 86 1/2° W., 39.6 ft. dist., mkd. T23S R6W S10 BT on bark.

A fir, 12 ins. diam., bears N. 21 3/4° W., 41.9 ft. dist., mkd. T23S R6W S3 BT.

Corner is located 45 ft. N. of a draw, drains N. 50° W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above a collar of stone, with a brass cap mkd.

T 23 S R 6 W  
S 15  
1/4 —  
S 22  
1994

from which a bearing tree mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A cedar, 19 ins. diam., bears S. 12° W., 25.1 ft. dist., with a healed blaze.

and a bearing tree mkd. by Rogers, et al, in 1986-95

A fir, 12 ins. diam., bears N. 39 1/2° W., 63.4 ft. dist., with a healed blaze.

Corner is located on a steep SE. bank, 30 ft. E. of a creek, 3 ft. wide, course N. 50° E.

From this cor., a point erroneously reestablished by Gould, Gawron, and Eggen, bears N. 17° 40' 06" E., 13.15 ft. dist., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, top 6 ins. below ground surface.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above a collar of stone, with a brass cap mkd.

T 23 S	R 6 W
S 16	S 15
— —	
S 21	S 22
1957	

from which bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

- A hemlock, 24 ins. diam., bears N. 37 1/2° E., 16.5 ft. dist., with a healed blaze.
- A hemlock, 32 ins. diam., bears S. 32 1/2° E., 47.5 ft. dist., with a healed blaze.
- A hemlock, 21 ins. diam., bears S. 7 1/2° W., 64.0 ft. dist., with a healed blaze.
- A hemlock, 24 ins. diam., bears N. 64 1/2° W., 52.8 ft. dist., with a healed blaze.

and a bearing tree mkd. by Haines, PLS No. 239, in 1956, reported by Rogers and Browning in 1996

- A fir, 52 ins. diam., bears N. 54 3/4° W., 20.7 ft. dist., with fragmentary scribe marks visible on bark blaze and a brass washer tacked in blaze mkd. WILFORD HAINES SURVEY 239 DRAIN, ORE. (Record, 19.1 ft. dist.)

Corner is located 40 ft. W. of a ravine, drains N. 60° E., and 145 ft. W. of a creek, 4 ft. wide, course N. 35° W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
1/4  
S 16 | S 15  
1957

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A fir, 9 ins. diam., bears S. 46° E., 23.1 ft. dist., with a healed blaze.

A decayed fir stump, 11 ins. diam., bears S. 62 1/2° W., 45.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears S. 35 1/2° W., 19.8 ft. dist., mkd. 1/4 S16 BT.

From this cor., a point established by Haines, PLS No. 239, in 1956, bears N. 80° 23' 53" W., 6.51 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with a brass washer mkd. WILFORD N HAINES SURVEY 239 DRAIN, ORE., with a tack in center, from which bearing trees mkd. by Haines (misidentified by Rogers, et al, in 1986-95, as bearing trees mkd. by person(s) unknown for the 1/4 sec. cor. of secs. 15 and 16)

A fir, 54 ins. diam., bears N. 49 3/4° E., 9.4 ft. dist., with scribe marks 1/4 S 239 BT visible on bark.

A fir, 32 ins. diam., bears S. 28 3/4° E., 35.4 ft. dist., with a healed blaze.

This point was not utilized during the course of this survey.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 9, 10, 15, and 16, perpetuated by the Douglas County Surveyor's Office in 2005, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above a collar of stone, with a brass cap mkd.

T 23 S	R 6 W
S 9	S 10
S 16	S 15
1955	

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Moore

- A sawed, decayed fir stump, 24 ins. diam., bears S. 59 1/2° E., 38.3 ft. dist., with a healed blaze.
- A maple, 42 ins. diam., bears S. 42° W., 57.4 ft. dist., with a healed blaze.
- A sawed, decayed fir stump, 14 ins. diam., bears N. 85° W., 45.5 ft. dist., with no marks visible.

and bearing trees mkd. by the Douglas County Surveyor's Office, reported by Moore

- A fir, 10 ins. diam., bears N. 57° E., 6.3 ft. dist., with illegible scribe marks visible on a partially healed double blaze.
- A fir, 8 ins. diam., bears S. 55° E., 9.7 ft. dist., with scribe marks X CS BT visible on a partially healed double blaze.
- A fir, 14 ins. diam., bears N. 46° W., 27.0 ft. dist., with a healed double blaze.

From this cor., the original cor. of secs. 9, 10, 15, and 16, amended and remonumented by Moore in 2005, bears S. 74° 56' 02" E., 49.96 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, flush with ground surface, with an aluminum cap mkd. BLM AM 2005

from which the remains of the original bearing trees

- A sawed, decayed fir stump, 42 ins. diam., bears N. 73° E., 29.7 ft. dist., with no marks visible.
- A sawed, decayed fir stump, 50 ins. diam., bears S. 5° E., 36.3 ft. dist., with no marks visible.
- A sawed, decayed fir stump, 58 ins. diam., bears N. 41° W., 48.5 ft. dist., with fragmentary scribe marks visible on an open blaze.

Corner is located 60 ft. N. of a spur, slopes S. 35° E.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam. (Record, 1 1/2 ins. diam.), firmly set, projecting 10 ins. above ground, with a brass cap mkd.

T 23 S	R 6 W
S 10	S 11
S 15	S 14
1943	

from which the remains of the original bearing trees

- A fir, 55 ins. diam., bears N. 35 3/4° E., 64.0 ft. dist., with a healed blaze.
- A fir, 40 ins. diam., bears S. 5 1/2° E., 16.5 ft. dist., with scribe marks 2 R 15 BT visible on bark.
- A sawed fir stump, 47 ins. diam., bears N. 64 1/4° W., 9.9 ft. dist., with a healed blaze.

and a bearing tree mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

- A fir, 74 ins. diam., bears S. 41° W., 40.3 ft. dist., with a healed double blaze.

and a bearing tree mkd. by Rogers and Browning in 1996

- A fir, 8 ins. diam., bears N. 23 3/4° W., 28.7 ft. dist., with a healed double blaze. (Record, 27.4 ft. dist.)
-

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 10 and 15, perpetuated by Ken W. Hoffine, PLS No. 2291, in 1992, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
S 10  
1/4 —●—  
S 15  
1957

from which bearing trees mkd. by Hoffine

A fir, 21 ins. diam., bears S. 30° W., 27.7 ft. dist., with a healed blaze.

A fir, 20 ins. diam., bears N. 32 3/4° W., 22.4 ft. dist., with a healed blaze.

and a reference tree reported by Hoffine

A hemlock, 15 ins. diam., bears S. 41° E., 12.0 ft. dist., with a metal tag.

Corner is located 45 ft. W. of the top of a gradual spur, slopes N. 20° W., and 350 ft. W. of a gravel road, 15 ft. wide, bears N. 10° E. and S. 10° W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec cor. of secs. 21 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
S 21  
1/4 —●—  
S 28  
1994

from which bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A fir, 42 ins. diam., bears S. 20 1/2° E., 77.9 ft. dist., with a healed blaze.

A fir, 56 ins. diam., bears S. 88 1/4° W., 37.0 ft. dist., with a healed blaze.

and a bearing tree mkd. by Rogers, et al, in 1986-95

A chinquapin, 9 ins. diam., bears N. 5 1/2° W., 28.4 ft. dist., with a healed blaze.

From this cor., a point erroneously reestablished by Gould, Gawron, and Eggen, bears S. 83° 17' 41" W., 38.47 ft. dist., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, top 4 ins. below ground surface.

Corner is located 35 ft. E. of a ridge, bears N. 30° W. and S. 30° E., and 85 ft. E. of a gravel road, 14 ft. wide, bears N. 40° W. and S. 40° E.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The W 1/16 sec. cor. of secs. 21 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a collar of stone, with a brass cap mkd.

S 21  
W 1/16 ———  
S 28  
1994

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A fir, 13 ins. diam., bears S. 67° W., 37.0 ft. dist., with a healed blaze.

A fir, 9 ins. diam., bears N. 28° W., 26.4 ft. dist., with a healed blaze.

From this cor., a point erroneously established by Gould, Gawron, and Eggen, bears N. 86° 50' 36" W., 39.29 ft. dist., monumented with an iron pipe, 2 ins. diam. (Record, 1 1/2 ins. diam.), firmly set, top 2 ins. below ground surface.

---

**Subdivision of Section 14,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above a collar of stone, with a brass cap mkd.

T 23 S R 6 W  
S 14  
1/4 ———  
S 23  
1994

from which bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A fir, 30 ins. diam., bears N. 23° E., 46.2 ft. dist., with a healed blaze.

A fir, 33 ins. diam., bears S. 1° E., 17.2 ft. dist., with a healed blaze.

From this cor., a point erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 86° 40' 46" E., 5.67 ft. dist., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, top 5 ins. below ground surface.

Corner is located 150 ft. S. of a creek, 3 ft. wide, course S. 30° E., and 50 ft. W. of the same creek, 3 ft. wide, course S. 15° E.

---

**Subdivision of Section 14,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The center S 1/16 sec. cor. of sec. 14, established by Haines, PLS No. 239, in 1964, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 11 ins. above ground, from which the remains of bearing trees mkd. by Haines

- A forked fir, with 25 and 38 in. diam. trunks, bears S. 26 1/4° E., 8.0 ft. dist., with scribe marks 1/16 visible on bark.
- A sawed fir stump, 42 ins. diam., bears N. 67 1/4° W., 28.8 ft. dist., with a healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a brass cap mkd.

C  
S 1/16 | S 14  
C  
2010

from which a new bearing tree

- A fir, 6 ins. diam., bears S. 85 1/2° W., 19.0 ft. dist., mkd. CS 1/16 S14 BT.

Place the "T" shaped iron rod, 48 ins. long, inside and deposit a magnet at the base of the stainless steel post.

Corner is located 20 ft. S. of a wide spur, slopes S. 60° E., and 55 ft. N. of an unimproved dirt road, 8 ft. wide, bears N. 35° W. and S. 35° E.

The center 1/4 sec. cor. of sec. 14, established by Haines, PLS No. 239, in 1964, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, from which bearing trees mkd. by Haines

- A fir, 46 ins. diam., bears S. 59 1/4° E., 82.1 ft. dist., with a healed blaze.
- A fir, 36 ins. diam., bears N. 87 1/4° W., 42.4 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with a brass cap mkd.

T 23 S R 6 W  
C 1/4 S 14  
2010

Place the "T" shaped iron rod, 48 ins. long, inside and deposit a magnet at the base of the stainless steel post.

**Subdivision of Section 14,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 1/2 ins. diam., firmly set, flush with ground, with a brass cap mkd.

S 11  
1/4 ———  
S 14  
1943

from which a bearing tree mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

A fir, 21 ins. diam., bears N. 22° W., 4.0 ft. dist., with a healed blaze. (Record, N. 16 1/4° E.)

and a bearing tree mkd. by Rogers and Browning in 1996

A fir, 27 ins. diam., bears S. 6 1/2° W., 72.9 ft. dist., with a healed blaze.

Corner is located 30 ft. W. of a gravel road, 10 ft. wide, bears N. 30° W. and S. 30° E.

---

The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with a brass cap mkd.

T 23 S R 6 W  
1/4  
S 14 | S 13  
1957

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

A fir, 18 ins. diam., bears S. 47° E., 6.6 ft. dist., with a healed blaze.

A roothole bears West, 40.9 ft. dist., downhill of which is a down, decayed fir snag, 9 ins. diam., with no marks visible.

and a bearing tree mkd. Rogers and Browning in 1996

A fir, 11 ins. diam., bears S. 11° W., 17.8 ft. dist., with a healed blaze.

Corner is located 200 ft. E. of a spur, slopes N. 35° E.

---

**Subdivision of Section 14,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

A point established by Haines, PLS No. 239, in 1964, and is accepted as a witness point on the E. and W. center line of sec. 14, monumented with a rebar, 3/4 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Haines

A fir, 37 ins. diam., bears S. 53 1/2° W., 103.5 ft. dist., with scribe marks WP BT visible on bark.

A sawed fir stump, 20 ins. diam., bears N. 29° W., 46.5 ft. dist., with a healed blaze.

Place an aluminum cap on the existing rebar, mkd.

W P  
S  
C ——— C  
14  
2010

from which a new bearing tree

A fir, 4 ins. diam., bears N. 30 1/4° W., 32.2 ft. dist., mkd. X BT.

---