

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A PORTION  
OF THE SUBDIVISIONAL LINES,  
AND CERTAIN CLAIM LINES OF MINERAL SURVEY NO. 789,  
AND THE SUBDIVISION OF SECTIONS 14 AND 20,  
**TOWNSHIP 33 SOUTH, RANGE 5 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***Arthur R. Rambo, Cadastral Surveyor***

Under Special Instructions dated August 3, 2010, approved August 9, 2010,  
which provided for the surveys included under Group No. 2346,  
and Assignment Instructions dated August 9, 2010.

***Survey commenced August 11, 2010***

***Survey completed July 14, 2011***

**T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and certain claim lines of Mineral Survey No. 789, and the subdivision of sections 14 and 20, Township 33 South, Range 5 West, Willamette Meridian, Oregon.

The history of official surveys pertaining to this resurvey is as follows:

In 1894, Edward F. Sharp, U.S. Deputy Surveyor, surveyed the subdivisional lines, as shown on the official plat of survey approved November 10, 1894.

In 1916, Horace C. Hall, U.S. Deputy Mineral Surveyor, surveyed the G & A, Portland and Josephine Lodes, Mineral Survey No. 789, as shown on the official plat of survey approved June 20, 1916.

In 1965-67, Joseph S. Gawron, John M. Jelley, and Rollin D. Aanrud, Cadastral Surveyors, remonumented certain original corner points as shown in the official field notes approved August 1, 1968.

In 1968, Rollin D. Aanrud, Cadastral Surveyor, remonumented certain original corner points as shown in the official field notes approved August 16, 1971.

In 1973-74, Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, remonumented certain original corner points as shown in the official field notes approved February 27, 1978.

In 1977-80, Lynn M. Roseberry, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, and certain claim lines, and remonumented certain original corner points as shown on the official plat of survey accepted November 10, 1982, and in the official field notes approved November 10, 1982.

In 1986-89, Terrence O. Nickerson, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, and certain claim lines, as shown on the official plat of survey accepted June 4, 1991.

In 2004, Stephen L. Barott, Land Surveyor, U.S. Forest Service, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted March 20, 2009.

The following local surveys filed in the Josephine County Surveyor's Office, are referred to in subsequent corner descriptions and are referenced by the surveyor's last name, Professional Land Surveyor No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1955	Norman D. Price, PLS No. 33	76-54
1993	Max H. Hull, PLS No. 901	137-93
2009	Raymond W. Wytcherley, PLS No. 2724	014-2009

**T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions dated August 3, 2010, for Group No. 2346, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and the true line field notes are given herein.

The direction of the lines are based on the true meridian as determined by Global Positioning System (GPS) observations and carried forward by means of sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment.

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Only those lines which represent Bureau of Land Management (BLM) property lines were posted with aluminum angle posts, 5 feet long, 1 inch x 1 inch, blazed, painted, and tagged with BLM boundary signs.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position NAD 1983 (CORS 96) of the following corners, as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), are as follows:

The corner of sections 13, 14, 23, and 24.

Latitude: 42° 41' 42.36" N.      Longitude: 123° 14' 57.08" W.

The corner of sections 17, 18, 19, and 20.

Latitude: 42° 41' 44.55" N.      Longitude: 123° 19' 43.82" W.

The 1/4 section corner of sections 20 and 21.

Latitude: 42° 41' 18.02" N.      Longitude: 123° 18' 32.41" W.

The 1/4 section corner of sections 22 and 23.

Latitude: 42° 41' 18.00" N.      Longitude: 123° 16' 09.29" W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>Restoring the 1894 survey by Edward F. Sharp, the 1965-67 remonumentation by Joseph S. Gawron, John M. Jelley, and Rollin D. Aanrud, the 1973-74 remonumentation by Lynn M. Roseberry and Larry D. Evans, the 1977-80 resurvey by Lynn M. Roseberry, and the 2004 resurvey by Stephen L. Barott</p> <hr/> <p>Beginning at the cor. of secs. 13, 14, 23, and 24, perpetuated from evidence no longer in existence by the BLM in 1977 for administrative purposes, and further perpetuated by the Josephine County Surveyor's Office in 2008, filed in C.S. Book 10, page 218 in 2011; monumented with an aluminum post, 2 1/2 ins. diam., loosely set, projecting 10 ins. above a mound of stone 3 ft. base, 2 ft. high, with aluminum cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYOR T 33 S R 5 W S 14   S 13 S 23   S 24 2008</p> <p>from which bearing trees mkd. by the BLM in the administrative survey, and scribe marks added on new face at breast height, by the Josephine County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 0 1/4° W., 37.5 ft. dist., with a healed blaze at base and mkd. CS at breast height.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 55 1/2° W., 30.5 ft. dist., with a healed blaze at base and mkd. CS at breast height.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 49° W., 67.2 ft. dist., with a healed blaze at base and mkd. CS at breast height.</p> <p>Stabilized aluminum post in place in mound of stone.</p> <p>N. 0° 09' 04" W., bet. secs. 13 and 14.</p>
1265	Gravel road, 12 ft. wide, bears N. 40° E. and S. 40° W.
1309.91	<p>The remains of the original 1894 line tree, recovered by the BLM in an administrative survey in 1977; a fir, 50 ins. diam., with 2 notches on the N. and S. sides; now a fir stump, 46 ins. diam., with no marks visible. This now becomes an angle point.</p> <p>At the corner point</p> <p>Set an iron rod, 5/8 in. diam., 24 ins. long, driven 18 ins. into the fir stump, with an aluminum cap, 3 1/4 ins. diam., mkd.</p> <p style="text-align: center;">A P S 14   S 13 2011</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>N. 0° 09' 04" W., beginning new measurement.</p>
13.46	<p>Point for the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p align="center">S 1/16 S 14   S 13 2011</p> <p>from which</p> <p>A fir, 11 ins. diam., bears N. 38 1/2° E., 44.3 ft. dist., mkd. S 1/16 S13 BT.</p> <p>A fir, 19 ins. diam., bears N. 12 1/2° W., 22.4 ft. dist., mkd. S 1/16 S14 BT.</p>
1359.28	<p>The 1/4 sec. cor. of secs. 13 and 14; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <p align="center">T 33 S R 5 W 1/4 S 14   S 13 1967</p> <p>from which remains of the original bearing trees</p> <p>A fir, 37 ins. diam., bears N. 20° E., 132.0 ft. dist., with a healed blaze.</p> <p>A rotted fir stump, 22 ins. diam., bears S. 49° W., 276.5 ft. dist., no marks visible. (Record, S. 49 1/2° W., 271.3 ft. dist.)</p> <p>and a bearing tree mkd. by Gawron, Jelly, and Aanrud</p> <p>A sugar pine, 44 ins. diam., bears N. 54° W., 23.4 ft. dist., with a healed blaze. (Record, fir)</p> <hr/> <p>N. 0° 19' 06" W., beginning new measurement.</p>
330.16	<p>The original 1894 line tree, a fir, 36 ins. diam., with 2 healed notches on the N. and S. sides. This now becomes an angle point.</p> <p>from which new accessories</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 35° 15' 45" E., 42.12 ft. dist., with brass cap mkd. RM S13 42.1 ft. with an arrow pointing to the cor. Deposit a magnet in a silver plastic case at the base of the iron post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
1336.26	<p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears S. 41° 07' 08" E., 35.92 ft. dist., with brass cap mkd. RM S13 35.9 ft. with an arrow pointing to the cor. Deposit a magnet in a purple plastic case at the base of the iron post.</p> <p>Point for the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S 14   S 13 2011</p> </div> <p>from which bearing trees mkd. by the BLM in an administrative survey in 1977</p> <p>A fir, 12 ins. diam., bears N. 58 1/2° E., 73.4 ft. dist., with partially healed blaze.</p> <p>A fir, 19 ins. diam., bears S. 19° W., 104.7 ft. dist., with partially healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 9 ins. diam., bears S. 26 1/2° E., 81.5 ft. dist., mkd. N 1/16 S13 BT.</p> <p>A fir, 9 ins. diam., bears S. 73 1/4° W., 41.5 ft. dist., mkd. N 1/16 S14 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by the BLM in 1977, for administrative purposes, bears S. 45° 59' 30" W., 0.95 ft.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, and was not utilized for control in this survey. Remove the iron rod and place under the iron post.</p>
2677.73	<p>The cor. of secs. 11, 12, 13, and 14; monumented with an iron post, 2 1/2 ins. diam. firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 5 W S 11   S 12 ----- S 14   S 13 1967</p> </div> <p>from which remains of the original bearing trees</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>A cedar snag, 25 ins. diam., bears N. 51 1/4° E., 37.0 ft. dist., with scribe marks 3 S 12 BT visible on partially healed blaze. (Record, N. 48 1/2° E.)</p> <p>A fir, 44 ins. diam., bears S. 21 1/2° E., 51.5 ft. dist., with a healed blaze. (Record, S. 25° E.)</p> <p>A cedar, 34 ins. diam., bears S. 17° W., 47.5 ft. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, S. 14 1/2° W.)</p> <p>A fir snag, 29 ins. diam., impracticable to measure due to snow covered cliffs, with scribe marks 3S 5W BT visible on partially healed blaze.</p> <p>from which bearing trees mkd. by Gawron, Jelley, and Aanrud</p> <p>A fir, 18 ins. diam., bears N. 57° E., 37.5 ft. dist., with a healed blaze (Record, N. 54° E., 37.0 ft.).</p> <p>A fir, 19 ins. diam., bears N. 60° W., 12.9 ft. dist., with a healed blaze.</p> <p>The cor. is located at the southeast base of a rock bluff 45 ft. high.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with a brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W 1/4 S 20   S 21 1974</p> <p>from which remains of the original bearing trees</p> <p>A black oak snag, 18 ins. diam., bears N. 2 1/2° E., 65.3 ft. dist., with a healed blaze.</p> <p>A ponderosa pine, 27 ins. diam., bears S. 75 3/4° W., 69.0 ft. dist., with a healed blaze. (Record, 68.0 ft.)</p> <p>and a bearing tree mkd. by Roseberry and Evans</p> <p>A fir, 16 ins. diam., bears N. 4 1/2° E., 15.2 ft. dist., with a healed blaze.</p> <p>N. 0° 09' 37" W., bet. secs. 20 and 21.</p>
1324.64	<p>The N 1/16 sec. cor. of secs. 20 and 21, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass washer mkd. RS 33, from which the remains of bearing trees mkd. by Price</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>A rotted fir stump, 9 ins. diam., bears S. 32 3/4° E., 13.4 ft. dist., no marks visible.</p> <p>A fir, 18 ins. diam., bears N. 74° W., 6.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., with a stem 2 1/2 ins. long, inside of the iron pipe, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>N 1/16</td></tr> <tr><td>S 20   S 21</td></tr> <tr><td>2010</td></tr> </table> </div> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 0 1/4° W., 12.0 ft. dist., mkd. N 1/16 S20 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 17" W., beginning new measurement.</p>	N 1/16	S 20   S 21	2010	
N 1/16					
S 20   S 21					
2010					
1324.55	<p>The cor. of secs. 16, 17, 20, and 21; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 33 S R 5 W</td></tr> <tr><td>S 17   S 16</td></tr> <tr><td>S 20   S 21</td></tr> <tr><td>1967</td></tr> </table> </div> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A madrone, 18 ins. diam., bears N. 62° E., 10.6 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Price, PLS No. 33, in 1955</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 49° E., 6.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 73° W., 12.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 71 1/2° W., 51.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Gawron, Jelley, and Aanrud</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 19° E., 30.8 ft. dist., with a healed blaze. (Record, 31.7 ft.)</p> <hr style="width: 20%; margin: 10px auto;"/>	T 33 S R 5 W	S 17   S 16	S 20   S 21	1967
T 33 S R 5 W					
S 17   S 16					
S 20   S 21					
1967					

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>From the 1/4 sec. cor. of secs. 19 and 20; monumented with the original cor. tree, a fir, 33 ins. diam., with healed blaze on the W. and E. sides. from which remains of the original bearing trees</p> <p style="padding-left: 40px;">A rotted fir stump, 16 ins. diam., bears N. 30° E., 26.4 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A root hole, bears S. 37° W., 10.6 ft. dist., with a dead and down fir alongside, 18 ins. diam., no marks visible.</p> <p>and bearing trees mkd. by the Josephine County Surveyor's office in 1971</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 78° E., 16.5 ft. dist., with a healed double blaze and a mag nail in the right side center. (Record, N. 79 1/2° E.)</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 6° W., 27.4 ft. dist., with a healed double blaze and a mag nail in the right side center.</p> <p>and a reference monument established by the Josephine County Surveyor's Office in 1971, filed in C. S. Book 6, page 116, in 1971, and utilized by Barott in 2004</p> <p style="padding-left: 40px;">An iron post, 1 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, bears North 3.0 ft. dist., with brass cap mkd. COUNTY SURVEYOR RM 1971 and an arrow pointing to the corner. (Record, N. 2° 19' 22" W., 2.7 ft.)</p> <p>N. 0° 56' 45" E., bet. secs. 19 and 20.</p>
1307.35	<p>The N 1/16 sec. cor. of secs. 19 and 20, perpetuated by Wytcherley, PLS No. 2724, in 2009; monumented with an iron pipe, 1 in. diam., loosely set, projecting 12 ins. above the ground, with brass washer mkd. RS 33.</p> <p>from which the remains of bearing trees mkd. by Price, PLS No. 33, in 1955</p> <p style="padding-left: 40px;">A sawed and rotted fir stump, 14 ins. diam., bears S. 27 1/2° E., 42.4 ft. dist., no marks visible. (Record, 41.6 ft.)</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S. 21 1/2° W., 97.7 ft. dist., with a healed blaze and a mag nail in the right side center. (Record, S. 21° W.)</p> <p>and the remains of a bearing tree mkd. by Barott</p> <p style="padding-left: 40px;">A sawed fir stump, 14 ins. diam., bears S. 64 1/2° E., 29.7 ft. dist., no marks visible and a mag nail in the right side center. (Record, S. 66° E.)</p> <p>and bearing trees mkd. by Wytcherley</p> <p style="padding-left: 40px;">A madrone, 7 ins. diam., bears N. 65 1/2° E., 2.3 ft. dist., with scribe marks 1/16 BT visible on open blaze and a nail in the right side center.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 9 ins. diam., bears S. 13° E., 18.0 ft. dist., with scribe marks 1/16 BT visible on partially healed blaze and a nail in the right side center.</p> <p>Stabilized iron pipe in place.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 58' 48" E., beginning new measurement.</p>						
1305.63	<p>The cor. of secs. 17, 18, 19, and 20; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYOR</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 33 S</td> <td style="padding: 0 5px;">R 5 W</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 18</td> <td style="padding: 0 5px; border-right: 1px solid black;">S 17</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 19</td> <td style="padding: 0 5px; border-right: 1px solid black;">S 20</td> </tr> </table> <p>1971</p> </div> <p>from which remains of the original bearing trees</p> <ul style="list-style-type: none"> <li>A broken fir snag, 54 ins. diam., bears S. 15° E., 20.5 ft. dist., with a healed blaze.</li> <li>A rotted fir stump, 50 ins. diam., bears S. 33° W., 42.2 ft. dist., with a healed blaze.</li> <li>A root hole, bears N. 21° W., 58.7 ft. dist., with a dead and down fir alongside, size indeterminate, no marks visible.</li> </ul> <p>and bearing trees mkd. by Price, PLS No. 33, in 1955</p> <ul style="list-style-type: none"> <li>A fir, 18 ins. diam., bears N. 24 3/4° E., 7.3 ft. dist., with a healed blaze. (Record, N. 20 1/2° E.)</li> <li>A tan oak, 5 ins. diam., bears S. 64 1/4° W., 27.1 ft. dist., with a healed blaze and a mag nail in the right side center.</li> </ul> <p>and bearing trees mkd. by Josephine County Surveyor's Office in 1971</p> <ul style="list-style-type: none"> <li>A fir, 12 ins. diam., bears S. 81 1/4° W., 32.5 ft. dist., with a healed double blaze. (Record, S. 80° W.)</li> <li>A fir, 15 ins. diam., bears N. 78° W., 27.9 ft. dist., with a healed blaze and a mag nail in the right side center. (Record, 28.4 ft.)</li> </ul> <p>and remains of a bearing tree mkd. by Barott</p> <ul style="list-style-type: none"> <li>A sawed fir stump, 16 ins. diam., 14 ft. tall, bears S. 39 1/2° E., 30.6 ft. dist., with a partially healed blaze, no marks visible and a mag nail in the right side center.</li> </ul>	T 33 S	R 5 W	S 18	S 17	S 19	S 20
T 33 S	R 5 W						
S 18	S 17						
S 19	S 20						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>From this cor., a point established by Price, PLS No. 33, in 1955, bears S. 28° 57' 03" W., 0.38 ft. dist.; monumented with an iron pipe, 1 in. diam., loosely set, projecting 14 ins. above the ground, with brass washer mkd. RS 33. This pipe was set by Price alongside on the south edge of the original stone. Not utilized for control in this survey.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89° 52' 50" W., bet. secs. 17 and 20.</p>								
1336.08	<p>The E 1/16 sec. cor. of secs. 17 and 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass washer mkd. RS 33, from which a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears N. 67 3/4° W., 24.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a brass cap with a stem, 3 1/4 ins. diam., 2 1/2 ins. long, inside of the iron pipe, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">E 1/16</td> <td style="border-bottom: 1px solid black; padding: 0 10px;">S 17</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">2010</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 24 1/2° W., 15.8 ft. dist., mkd. E 1/16 S20 BT.</p> <hr style="width: 30%; margin: 10px auto;"/>	E 1/16	S 17		S 20		2010		
E 1/16	S 17								
	S 20								
	2010								
1341.75	<p>N. 89° 45' 53" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 17 and 20; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td></td> <td style="padding: 0 10px;">T 33 S R 5 W</td> </tr> <tr> <td></td> <td style="border-bottom: 1px solid black; padding: 0 10px;">S 17</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">1967</td> </tr> </table> </div> <p>from which remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole, bears N. 71 1/2° E., 65.3 ft. dist., with a down and decayed oak alongside, size indeterminate, no marks visible.</p>		T 33 S R 5 W		S 17	1/4	S 20		1967
	T 33 S R 5 W								
	S 17								
1/4	S 20								
	1967								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>A black oak, 32 ins. diam., bears S. 79° W., 89.6 ft. dist., with a healed blaze. (Record, S. 78 1/4° W., 90.4 ft.)</p> <p>and bearing trees mkd. by Gawron, Jelley, and Aanrud</p> <p>A ponderosa pine, 12 ins. diam., bears N. 15° E., 9.2 ft. dist., with a healed blaze.</p> <p>A fir, 19 ins. diam., bears S. 30° E., 18.5 ft. dist., with a healed blaze. Note: A fir, 22 ins. diam., is growing directly against the northeast side of the tree.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 22' 42" W., beginning new measurement.</p>						
1326.12	<p>The W 1/16 sec. cor. of secs. 17 and 20, established by Price, PLS No. 33, in 1955, and perpetuated by Wytcherley, PLS No. 2724, in 2009, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass washer mkd. RS 33, from which the remains of bearing trees mkd. by Price</p> <p>A fir, 28 ins. diam., bears N. 41 1/2° E., 17.0 ft. dist., with a healed blaze.</p> <p>A rotted fir stump, 40 ins. diam., bears S. 21° E., 17.3 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Wytcherley</p> <p>A fir, 6 ins. diam., bears N. 60 1/2° E., 7.7 ft. dist., with scribe marks 1/16 BT visible on partially healed blaze and a spike in the right side center.</p> <p>A fir, 7 ins. diam., bears S. 0 3/4° E., 22.7 ft. dist., with scribe marks 1/16 BT visible on partially healed blaze and a spike in the right side center.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: 0 auto;"> <tr> <td style="padding-right: 20px;">W 1/16</td> <td style="border-top: 1px solid black; padding-top: 5px;">S 17</td> </tr> <tr> <td></td> <td style="padding-top: 5px;">S 20</td> </tr> <tr> <td></td> <td style="padding-top: 5px;">2010</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 22' 34" W., beginning new measurement.</p>	W 1/16	S 17		S 20		2010
W 1/16	S 17						
	S 20						
	2010						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET  
1323.35

The cor. of secs. 17, 18, 19, and 20.

---

**Dependent Resurvey of a Portion of Certain Claim Lines of  
Mineral Survey No. 789 (G & A Lode),  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

---

Restoring the 1916 Survey by Horace C. Hall,  
United States Mineral Surveyor

---

From corner No. 1, G. & A. Lode, Mineral Survey No. 789, perpetuated by the Josephine County Surveyor's Office in 1979, filed in C. S. Book 7, page 118; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a collar of stone, with brass cap mkd.

COUNTY SURVEYOR  
1 - 789  
G. A.  
1979

from which bearing trees mkd. by the Josephine County Surveyor's Office

A fir, 32 ins. diam., bears N. 83 1/4° E., 15.5 ft. dist., with a healed double blaze.

A fir, 22 ins. diam., bears S. 30° W., 29.1 ft. dist., with a healed double blaze.

A fir, 27 ins. diam., bears S. 37 3/4° W., 8.0 ft. dist., with a healed double blaze.

The original basalt stone, 10 x 10 x 24 ins., mkd. G. A. 1-789, was found set alongside the iron post.

From this cor. the 1/4 sec. cor. of secs. 22 and 23, bears S. 81° 37' 52" W., 359.65 ft. dist.; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.

T 33 S R 5 W  
1/4  
S 22 | S 23  
1968

from which the original bearing trees

A fir, 34 ins. diam., bears S. 24 1/4° E., 56.8 ft. dist., with a healed blaze. (Record, S. 27° E., 56.1 ft.)

A ponderosa pine, 30 ins. diam., bears N. 39° W., 38.3 ft. dist., with a healed blaze. (Record, N. 41° W.)

**Dependent Resurvey of a Portion of Certain Claim Lines of  
Mineral Survey No. 789 (G & A Lode),  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>and a bearing tree mkd. by Aanrud</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears S. 52 3/4° W., 19.4 ft. dist., with a healed blaze. (Record, S. 51° W., 20.1 ft.)</p> <p>N. 44° 49' 09" W., on line 1-2, G. &amp; A. lode, Mineral Survey No. 789.</p>
598.97	<p>Corner No. 2, G. &amp; A. lode, perpetuated by the Josephine County Surveyor's Office, in 1979, filed in C. S. Book 7 page 118; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a collar of stone, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYOR 2 - 789 G. A. 1979</p> <p>from which bearing trees mkd. by the Josephine County Surveyor's Office</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S. 13 1/4° W., 84.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears N. 35 1/2° W., 12.8 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A cedar snag, 17 ins. diam., bears N. 69 3/4° W., 44.3 ft. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>The original basalt stone, 8 x 10 x 24 ins., mkd. G. A. 2-789 was found set alongside the iron post.</p> <hr/> <p>From corner No. 6, G. &amp; A. Lode, perpetuated by the Josephine County Surveyor's Office in 1979, filed in C. S. Book 7 page 119; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, in a collar of stone, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYOR 6 - 789 G. A. 1979</p> <p>from which remains of an original bearing tree</p> <p style="padding-left: 40px;">A rotted broken off oak stump, 8 ins. diam., bears N. 68 1/2° W., 36.4 ft. dist., with a healed and rotted blaze. (Record, N. 74° W., 34.1 ft. dist.)</p> <p>and bearing trees mkd. by the Josephine County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 75 1/4° E., 10.7 ft. dist., with a healed double blaze.</p>

**Dependent Resurvey of a Portion of Certain Claim Lines of  
Mineral Survey No. 789 (G & A Lode),  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>A cedar, 25 ins. diam., bears S. 51° E., 37.8 ft. dist., with a healed blaze.</p> <p>A fir, 21 ins. diam., bears S. 25° E., 21.2 ft. dist., with a healed blaze.</p> <p>The original cedar post, 6 x 6 ins. square, was found rotted with illegible scribe marks lying alongside the iron post.</p> <p>N. 47° 19' 41" E., on line 6-1, G. &amp; A. lode, Mineral Survey No. 789.</p>
878.98	<p>Corner No. 1, G. &amp; A. Lode, Mineral Survey No. 789.</p> <hr/> <p align="center"><b>Subdivision of Section 14, T. 33 S., R. 5 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 33 S R 5 W S 14 1/4 ——— S 23 1974</p> <p>from which an original bearing tree</p> <p>A fir, 24 ins. diam., bears S. 50° E., 22.4 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Roseberry and Evans</p> <p>A fir, 19 ins. diam., bears N. 74° W., 56.8 ft. dist., with a healed blaze.</p>
1344.52	<p>N. 0° 17' 02" W., on the N. and S. center line of sec. 14.</p> <p>Point for the center S 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">C S 1/16   S 14 C 2011</p> <p>from which a bearing tree mkd. by the BLM in an administrative survey in 1977</p> <p>A fir, 20 ins. diam., bears S. 49 1/4° W., 46.3 ft. dist., mkd. CS 1/16 S14 BT on new face, did not open healed blaze.</p>

**Subdivision of Section 14,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 40 3/4° W., 15.7 ft. dist., mkd. CS 1/16 S14 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by the BLM in 1977 for administrative purposes, bears N. 86° 03' 32" W., 0.94 ft. dist.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, and was not utilized for control in this survey. Remove the iron rod and place under the stainless steel post.</p>
2689.04	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W C 1/4 S 14 2011</p> <p>from which remains of bearing trees mkd. by the BLM in an administrative survey in 1977</p> <p style="padding-left: 40px;">A madrone, 7 ins. diam., bears N. 26 1/4° E., 19.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A madrone snag, 7 ins. diam., bears N. 64° W., 27.7 ft. dist., with spike in face of partially healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 80 1/4° E., 27.9 ft. dist., mkd. C 1/4 S14 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 34 3/4° W., 27.7 ft. dist., mkd. C 1/4 S14 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by the BLM in 1977 for administrative purposes, bears S. 63° 06' 03" W., 0.65 ft. dist.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, and was not utilized for control in this survey. Remove the iron rod and place under the stainless steel post.</p>
4029.52	<p>Point for the center N 1/16 sec. cor. of sec. 14.</p>

**Subdivision of Section 14,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">             C              N 1/16   S 14              C              2011           </p> <p>from which bearing trees mkd. by the BLM in an administrative survey in 1977</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears S. 81° E., 14.5 ft. dist., mkd. CN 1/16 S14 BT on new face, did not open healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 42 1/4° W., 11.9 ft. dist., mkd. CN 1/16 S14 BT on new face, did not open healed blaze.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., a point established by the BLM in 1977 for administrative purposes, bears N. 40° 28' 04" E., 0.61 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, and was not utilized for control in this survey. Remove the iron rod and place under the stainless steel post.</p>
5370.00	<p>The 1/4 sec. cor. of secs. 11 and 14; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <p align="center">             T 33 S R 5 W              S 11              1/4 ———              S 14              1967           </p> <p>from which remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 63 1/4° E., 4.0 ft. dist., with a healed blaze. (Record, S. 55° E., 4.6 ft.)</p> <p style="padding-left: 40px;">A fir snag, 17 ins. diam., bears N. 55° W., 6.6 ft. dist., with scribe marks 1/4S visible on partially healed blaze.</p> <p>and bearing trees mkd. by Gawron, Jelly, and Aanrud</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 72° E., 19.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 25° W., 16.2 ft. dist., with a healed blaze. (Record, S. 23° W).</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p>

**Subdivision of Section 14,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>N. 88° 19' 21" W., on the E. and W. center line of sec. 14.</p>
2696.83	<p>The center 1/4 sec. cor. of sec. 14.</p>
5401.49	<p>The 1/4 sec. cor. of secs. 14 and 15; monumented with an iron post, 2 1/2 ins. diam., loosely set, projecting 14 ins. above the ground, with brass cap mkd.</p> <p align="center">                     T 33 S R 5 W                      1/4                      S 15   S 14                      1967                 </p> <p>from which remains of the original bearing trees</p> <p style="padding-left: 40px;">A rotted and burned fir stump, 29 ins. diam., bears S. 72° E., 13.9 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 32 ins. diam., bears N. 76° W., 8.6 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 68 3/4° E., 5.8 ft. dist., mkd. 1/4 S14 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 7 1/2° W., 24.3 ft. dist., mkd. 1/4 S15 BT.</p> <p>Stabilized iron pipe in place.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>N. 88° 14' 01" W., on the E. and W. center line of the NE 1/4 of sec. 14.</p>
2695.98	<p>The center N 1/16 sec. cor. of sec. 14.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>N. 88° 17' 34" W., on the E. and W. center line of the SE 1/4 of sec. 14.</p>
2693.93	<p>The center S 1/16 sec. cor. of sec. 14.</p> <hr/> <p align="center"><b>Subdivision of Section 20, T. 33 S., R. 5 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29, perpetuated by Price, PLS No. 33, in 1955, and further perpetuated by the Josephine County Surveyor's Office, in 1971, filed in C. S. Book 6, page 116, and further perpetuated by Hull, PLS No. 901, in 1993; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with a brass cap mkd.</p>

Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">COUNTY SURVEYOR T 33 S R 5 W 20 1/4 S ————— 29 1971</p> <p>from which a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 48° W., 35.1 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Hull</p> <p style="padding-left: 40px;">A maple, 14 ins. diam., bears N. 77° E., 18.5 ft. dist., with scribe marks S 1/4 RS 901 on partially healed upper blaze and BT on partially healed lower blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 41 1/2° W., 20.3 ft. dist., with a healed double blaze.</p> <p>The original stone is lying alongside the iron post on the SW. side, with marks 1/4 visible on the top.</p> <p>N. 0° 12' 47" W., on the N. and S. center line of sec. 20.</p>
1321.09	<p>The center S 1/16 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass washer mkd. RS 33, from which bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears N. 48 3/4° E., 48.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 46 1/2° W., 17.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a brass cap with a stem, 3 1/4 ins. diam., 2 1/2 ins. long, inside of the iron pipe, mkd.</p> <div style="text-align: center;"> <p>C S 1/16   S 20 C 2010</p> <hr style="width: 20%; margin: 0 auto;"/> </div>
660.10	<p>N. 0° 32' 56" W., beginning new measurement.</p> <p>The center N-S 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; determined at record dist. intersection from bearing trees mkd. by Price</p>

**Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 23 ins. diam., bears S. 88 3/4° E., 10.6 ft. dist., with a healed blaze.</p> <p>A fir, 22 ins. diam., bears N. 27 1/2° W., 22.4 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 20 C-N-S 1/64 2010</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 21' 19" W., beginning new measurement.</p>
655.80	<p>The center 1/4 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; determined at record bearing and dist. from the remains of a bearing tree mkd. by Price</p> <p style="text-align: center;">A rotted fir stump, 20 ins. diam., bears N. 56° E., 1.3 ft. dist., with a portion of a healed blaze visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W C 1/4 S 20 2010</p> <p>from which</p> <p style="text-align: center;">A fir, 9 ins. diam., bears S. 13 1/4° W., 57.8 ft. dist., mkd. C 1/4 S20 BT.</p> <p style="text-align: center;">A maple, 9 ins. diam., bears N. 16 1/4° W., 52.9 ft. dist., mkd. C 1/4 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 34' 28" W., beginning new measurement.</p>

**Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

<p>FEET 654.71</p>	<p>The center S-N 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass washer mkd. RS 33, from which remains of a bearing tree mkd. by Price              A root hole, bears S. 35° W., 67.8 ft. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p align="center">S 20 C-S-N 1/64 2010</p> <p>and new bearing trees</p> <p>    A fir, 8 ins. diam., bears N. 55 1/4° E., 7.2 ft. dist., mkd. X at breast height and BT at the base.</p> <p>    A fir, 9 ins. diam., bears S. 64 3/4° E., 12.0 ft. dist., mkd. CSN 1/64 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p align="center">_____</p> <p>N. 0° 25' 37" W., beginning new measurement.</p>
<p>653.14</p>	<p>The center N 1/16 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass washer mkd. RS 33, from which the remains of bearing trees mkd. by Price</p> <p>    A black oak, 22 ins. diam., bears S. 48 1/4° E., 38.7 ft. dist., with a healed blaze.</p> <p>    A rotted black oak stump, 31 ins. diam., bears N. 8° W., 51.2 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a brass cap with a stem, 3 1/4 ins. diam., 2 1/2 ins. long, inside of the iron pipe, mkd.</p> <p align="center">C N 1/16   S 20 C 2010</p> <p>and a new bearing tree</p>

**Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p align="center">A fir, 8 ins. diam., bears N. 1 1/2° E., 10.2 ft. dist., mkd. CN 1/16 S20 BT.</p> <hr/> <p>N. 0° 22' 23" W., beginning new measurement.</p>
1312.18	<p>The 1/4 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21.</p> <p>N. 89° 13' 08" W., on the E. and W. center line of sec. 20.</p>
1338.98	<p>The center E 1/16 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass washer mkd. RS 33, from which bearing trees mkd. by Price</p> <p align="center">A fir, 30 ins. diam., bears S. 56° E., 14.7 ft. dist., with a healed blaze.</p> <p align="center">A fir, 33 ins. diam., bears N. 55° W., 10.4 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 20 \\ 2010 \end{array}</math> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89° 10' 29" W., beginning new measurement.</p>
652.86	<p>The center W-E 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; determined at record bearing and dist. from a bearing tree mkd. by Price</p> <p align="center">A fir, 20 ins. diam., bears N. 89° E., 19.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p align="center">S 20 C-W-E 1/64 2010</p> <p>and a new bearing tree</p> <p align="center">A fir, 11 ins. diam., bears S. 19° W., 25.5 ft. dist., mkd. CWE 1/64 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Note: The 1 in. diam., iron pipe, 36 ins. long, set by Price, was found lying loose on top of the ground under a log west of the cor. Deposit the iron pipe under the stainless steel post.</p> <hr/> <p>N. 89° 09' 34" W., beginning new measurement.</p>
672.31	<p>The center 1/4 sec. cor. of sec. 20.</p> <hr/> <p>N. 89° 13' 27" W., beginning new measurement.</p>
677.37	<p>The center E-W 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass washer mkd. RS 33, from which the remains of bearing trees mkd. by Price</p> <p align="center">A rotted fir stump, 19 ins. diam., bears N. 0 3/4° E., 7.9 ft. dist., with lower blaze partially visible.</p> <p align="center">A root hole, bears S. 55 1/2° W., 12.2 ft. dist., with two madrones, both 14 ins. diam., growing on each side.</p> <hr/> <p>N. 89° 12' 42" W., beginning new measurement.</p>
683.37	<p>The center W 1/16 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass washer mkd. RS 33, from which bearing trees mkd. by Price</p> <p align="center">A fir, 39 ins. diam., bears N. 51° E., 11.8 ft. dist., with a healed blaze.</p> <p align="center">A ponderosa pine, 23 ins. diam., bears S. 60 1/2° E., 9.0 ft. dist., with a healed blaze.</p> <hr/> <p>N. 89° 15' 21" W., beginning new measurement.</p>

**Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET 1353.01	<p>The 1/4 sec. cor. of secs. 19 and 20.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 20.</p> <p>N. 0° 07' 03" E., on the N. and S. center line of the NE 1/4 of sec. 20.</p>
657.73	<p>The center S-NE 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass washer mkd. RS 33, from which a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A black oak, 9 ins. diam., bears S. 48 1/4° E., 20.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">S 20 C-S-NE 1/64 2010</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 61° W., 9.3 ft. dist., mkd. 1/64 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 07' 15" W., beginning new measurement.</p>
659.01	<p>The NE 1/16 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass washer mkd. RS 33, from which the remains of bearing trees mkd. by Price</p> <p style="padding-left: 40px;">An oak root hole, bears N. 56° E., 12.0 ft. dist.</p> <p style="padding-left: 40px;">A root hole, bears S. 54 1/2° E., 14.3 ft. dist., with a dead and down oak alongside, 8 ins. diam., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 20 2010</p>

**Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 22 3/4° E., 21.4 ft. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 82° W., 12.2 ft. dist., mkd. NE 1/16 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89° 30' 40" W., on the E. and W. center line of the NE 1/4 of sec. 20.</p>
662	West edge of drainage, 15 ft. wide, drains S. 20° W.
667.36	<p>The center W-NE 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass washer mkd. RS 33, from which bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears N. 10 1/4° E., 29.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A black oak, 13 ins. diam., bears S. 53 1/4° W., 28.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">S 20 CW-NE 1/64 2010</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the center S-N 1/64 sec. cor. of sec. 20.</p> <p>S. 89° 13' 31" E., on the E. and W. center line of the SW 1/4 of the NE 1/4 of sec. 20.</p>
666.28	<p>The SW-NE 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, 2.3 ft. below the ground surface, leaning to the west, with brass washer mkd. RS 33, from which the remains of a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A rotted fir stump, 20 ins. diam., bears S. 74 3/4° E., 5.6 ft. dist., no marks visible.</p>

**Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 20 SW-NE 1/64 2010</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 12 3/4° E., 33.7 ft. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 29 3/4° E., 42.6 ft. dist., mkd. 1/64 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0° 10' 47" W., on the N. and S. center line of the SW 1/4 of the NE 1/4 of sec. 20.</p>
657.50	<p>The center W-NE 1/64 sec. cor. of sec. 20.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 20.</p> <p>N. 0° 18' 39" E., on the N. and S. center line of the NW 1/4 of sec. 20.</p>
653.92	<p>Point for the center S-NW 1/64 sec. cor. of sec. 20. Not monumented.</p> <p>From this point, a point erroneously established as the center S-NW 1/64 sec. cor. of sec. 20, by Price, PLS No. 33, in 1955, bears N. 0° 27' 20" W., 12.42 ft. dist., not utilized by Wytcherley, PLS No. 2724, in 2009, and was not utilized for control in this survey; monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, from which remains of bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A rotted pine stump, size indeterminate, bears N. 56 3/4° E., 30.0 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A black oak, 17 ins. diam., bears S. 33 3/4° W., 24.5 ft. dist., with a healed blaze.</p>
1307.84	<p>The NW 1/16 sec. cor. of sec. 20; established by Price, PLS No. 33, in 1955, and utilized by Wytcherley, PLS No. 2724 in 2009, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass washer mkd. RS 33, from which a bearing tree mkd. by Price</p>

Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon

<p>FEET</p>	<p>A black oak, 26 ins. diam., bears N. 76° E., 74.9 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Wytcherley</p> <p>A madrone, 7 ins. diam., bears N. 4 1/2° E., 5.2 ft. dist., with scribe marks 1/16 BT visible on open blaze and a spike in the right side center.</p> <p>A fir, 5 ins. diam., bears N. 71 1/4° W., 16.7 ft. dist., with scribe marks 1/16 BT visible on open blaze and a spike in the right side center.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 20 2010</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 19' 19" E., beginning new measurement.</p> <p>1307.95 The W 1/16 sec. cor. of secs. 17 and 20.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center S-N 1/64 sec. cor. of sec. 20.</p> <p>N. 89° 18' 39" W., on the E. and W. center line of the SE 1/4 of the NW 1/4 of sec. 20.</p> <p>677.13 The SE-NW 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; determined at record bearing and dist. from a bearing tree mkd. by Price</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 44° E., 15.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 20 SE-NW 1/64 2010</p> <p>and a new bearing tree</p>
-------------	---

**Subdivision of Section 20,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 7 ins. diam., bears N. 28 1/4° E., 32.8 ft. dist., mkd. 1/64 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0° 00' 13" E., on the N. and S. center line of the SE 1/4 of the NW 1/4 of sec. 20.</p>
655.72	<p>The center E-NW 1/64 sec. cor. of sec. 20, established by Price, PLS No. 33, in 1955, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above the ground, with brass washer mkd. RS 33, from which bearing trees mkd. by Price</p> <p style="padding-left: 40px;">A black oak, 21 ins. diam., bears S. 73 1/2° W., 42.3 ft. dist., with partially healed blaze, no marks visible.</p> <p style="padding-left: 40px;">A pine, 34 ins. diam., bears N. 46° W., 93.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">S 20 C-E-NW 1/64 2010</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89° 19' 39" W., on the E. and W. center line of the NW 1/4 of sec. 20.</p>
669.90	<p>The NW 1/16 sec. cor. of sec. 20.</p> <hr/>