

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
CORRECTIVE RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
AND SUBDIVISIONAL LINES,
AND SUBDIVISION OF SECTIONS 26 AND 30,
TOWNSHIP 26 SOUTH, RANGE 2 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Kenneth W. Saveland, Cadastral Surveyor

Under Special Instructions approved June 30, 2010,
and Supplemental Special Instructions approved August 10, 2011,
which provided for the surveys included under Group No. 2331,
and Assignment Instructions dated March 18, 2011,
and Supplemental Assignment Instructions August 17, 2011,

Survey commenced April 28, 2011

Survey completed October 18, 2011

T. 26 S., R. 2 W., Willamette Meridian, Oregon

The following field notes are those of the corrective resurvey of a portion of the south boundary, dependent resurvey of a portion of the west boundary and subdivisional lines, and subdivision of sections 26 and 30, and Township 26 South, Range 2 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1855, Addison R. Flint, U.S. Deputy Surveyor, surveyed the exterior and subdivisional lines, T. 26 S., R. 3 W., as shown on the official plat of survey approved December 10, 1855.

In 1882, Samuel C. Flint, U.S. Deputy Surveyor, surveyed the exterior and subdivisional lines, T. 27 S., R. 3 W., as shown on the official plat of survey approved October 23, 1882.

In 1882, Samuel C. Flint, U.S. Deputy Surveyor, surveyed a portion of the exterior and subdivisional lines, T. 27 S., R. 2 W., as shown on the official plat of survey approved December 7, 1882.

In 1883, John A. McQuinn, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved April 7, 1884.

In 1909-10, William N. Gibb, U.S. Deputy Surveyor, retraced a portion of the exterior and subdivisional lines, resurveyed a portion of the subdivisional lines, and surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved October 17, 1911.

In 1913-14, Charles M. Collier, U.S. Surveyor, reestablished a portion of the exterior lines, as shown on the official plat of survey approved June 21, 1917.

In 1916-18, Fred Mensch, U.S. Surveyor, retraced a portion of the south and west boundaries, resurveyed a portion of the subdivisional lines, and surveyed Tracts 37 and 38, T. 26 S., R. 2 W., as shown on the official plat of survey approved January 4, 1919.

In 1958, Harold D. Corbin, Cadastral Surveyor, resurveyed a portion of the north and west boundaries and subdivisional lines, T. 27 S., R. 3 W., and remonumented certain original corners as shown on the official plat of survey accepted March 16, 1960.

In 1975, G. Steven Popken, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 23, as shown on the official plat of survey accepted June 23, 1978.

In 1979, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the south boundary and subdivisional lines and subdivided section 9, as shown on the official plat of survey accepted June 16, 1983.

In 1992, Dale T. Bedell and Bryan S. Seibold, Cadastral Surveyors, and Robert H. Browning, Surveying Technician, resurveyed a portion of the south boundary, subdivisional lines, and boundary of Tract 38, and subdivided sections 11 and 35, as shown on the official plat of survey accepted June 3, 1997.

T. 26 S., R. 2 W., Willamette Meridian, Oregon

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, official title or Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Official Title or Registration Number</u>	<u>File Number</u>
1967	Douglas County Surveyor's Office	CS 54/40
1979	Thomas E. Shrum, Jr., PLS 1706	M 76-56
1981	Thomas E. Shrum, Jr., PLS 1706	M 89-28
1981	Gregory E. Quibell, Deputy County Surveyor	CS 61/27
1998	Randall W. Smith, Deputy County Surveyor	CS 66/2-11
1999	Gerald V. Nygren, PLS 1035	CS 65/70-3
1999	David A. Edwards, PLS 2339	CS 65/25-4
2007	Douglas County Surveyor's Office	CS 67/24-50
2011	Ronald L. Rice, PLS 54633	M 162-6

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions, (2009), and the special instructions approved June 30, 2010, and supplemental special instructions approved August 10, 2011, for Group No. 2331, Oregon.

The direction of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through GPS and conventional survey techniques. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 x 1/4 in. magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Only those lines bounding or crossing Federal interest land were blazed.

The geographic position in NAD 1983 (CORS 96) of the following corners as determined by a tie from a temporary GPS control point, utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), are:

The corner of sections 23 and 26 only:

Latitude: 43° 16' 59.11" N. Longitude: 122° 54' 48.91" W.

The 1/4 sec. corner of sections 28 and 29:

Latitude: 43° 16' 43.90" N. Longitude: 122° 57' 03.08" W.

The 1/4 section corner of sections 31 and 36 on west boundary of the township:

22916

T. 26 S., R. 2 W., Willamette Meridian, Oregon

Latitude: 43° 15' 50.96" N. Longitude: 122° 59' 26.81" W.

The corner of sections 29, 30, 31, and 32, determined by direct observation:

Latitude: 43° 16' 17.874" N. Longitude: 122° 58' 14.858" W.

**Corrective Dependent Resurvey of a Portion of the South Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

MEMORANDUM

The cor. of Tps. 26 and 27 S., Rgs. 2 and 3 W., was established by A. Flint in 1855 while surveying the S. bdy. of Tp. 26 S., R. 3 W. A position was also established by S. Flint in 1882, while surveying the E. bdy. of Tp. 27 S., R. 3 W. and given the same cor. designation. The cor. positions were erroneously reported as common in the resurveys performed by Collier and Corbin, but now function as the cors. of their respective townships.

The cor. of Tp. 27 S., Rgs. 2 and 3 W., formerly designated as the cor. of Tps. 26 and 27 S., Rgs. 2 and 3 W., established by S. Flint in 1882, perpetuated by Corbin in 1958, further perpetuated by Rice, PLS No. 54633, in 2011, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

T 26 S	
R 3 W	R 2 W
S 36	S 31

S 1	S 6
T 27 S	
1958	

from which the remaining original bearing tree

A sawed fir stump, 38 ins. diam., bears S. 38° W., 4.6 ft. dist., with scribe marks T2 R visible on a partially opened blaze.

and the remains of bearing trees mkd. by Corbin

A fir, 13 ins. diam., bears N. 51 1/2° E., 17.8 ft. dist., with a healed blaze.

A sawed fir stump, 28 ins. diam., bears S. 46° E., 7.3 ft. dist., with a healed blaze.

A sawed, decayed fir stump, 6 ft. high, 18 ins. diam., bears S. 76° W., 16.5 ft. dist., with a healed blaze.

A sawed, decayed fir stump, 14 ins. diam., bears N. 24° W., 42.9 ft. dist., with a healed blaze.

and a bearing tree mkd. by Rice

A fir, 13 ins. diam., bears S. 84 3/4° W., 13.6 ft. dist., with scribe marks T27S R2W S1 BT visible on an open blaze.

At the corner point

Change the cap markings to now read

22918

Corrective Dependent Resurvey of a Portion of the South Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

T 26 S R 2 W
S 31

S 1	S 6
R 3 W	R 2W
T 27 S	
2011	
1958	

from which new bearing trees

A fir, 6 ins. diam., bears S. $8\ 1/4^\circ$ E., 18.3 ft. dist., mkd. T27S R2W S6 BT.

A fir, 10 ins. diam., bears S. 32° W., 14.0 ft. dist., mkd. T27S R3W S1 BT.

This cor. is now designated as the cor. of Tp. 27 S., Rgs. 2 and 3 W.

**Corrective Dependent Resurvey of a Portion of the South Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The cor. of Tp. 26 S., Rgs. 2 and 3 W., established by A. Flint in 1855, formerly designated as the cor. of Tps. 26 and 27 S., Rgs. 2 and 3 W., perpetuated by Collier in 1913-14, at record bearing and distance from the remains of the original SE. bearing tree

A sawed fir stump, 46 ins. diam., bears S. 85° E., 11.9 ft. dist., with scribe marks BT visible on a partially opened blaze.

from which the remains of a bearing tree mkd. by Collier

A sawed fir stump, 58 ins. diam., bears S. 16° W., 9.9 ft. dist., with scribe marks R3W visible on a partially opened blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 26 S	
R 3 W	R 2 W
S 36	S 31

S 1	
T 27 S R 3 W	
2011	

from which new bearing trees

A fir, 6 ins. diam., bears N. 40 1/4° E., 20.0 ft. dist., mkd. T26S R2W S31 BT.

A fir, 16 ins. diam., bears N. 54° W., 9.9 ft. dist., mkd. T26S R3W S36 BT.

This cor. is now designated as the cor. of Tp. 26 S., Rgs. 2 and 3 W.

22920

**Dependent Resurvey of a Portion of the West Boundary
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 31 and 36, perpetuated by the Douglas County Surveyor's Office in 1966, further perpetuated by Smith, Deputy County Surveyor, in 1998, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.

T 26 S
R R
3 S | S 2
1/4 W 36 | 31 W
1966

from which the remains of an original bearing tree

A roothole bears N. 50° E., 15.8 ft. dist., alongside of which is an uprooted, decayed, sawed fir stump, 30 ins. diam., with no marks visible on a decayed, partially healed blaze.

and the bearing trees mkd. by the Douglas County Surveyor's Office

A fir, 19 ins. diam., bears S. 47 1/2° E., 24.7 ft. dist., with a healed double blaze.

A cedar, 23 ins. diam., bears N. 9 3/4° W., 29.5 ft. dist., with a healed double blaze.

and the bearing trees mkd. by Smith

A fir, 13 ins. diam., bears N. 58° E., 9.8 ft. dist., with a healed double blaze.

A fir, 11 ins. diam., bears S. 34 1/2° W., 2.0 ft. dist., with a healed double blaze.

Corner is located 230 ft. N. of a draw, drains, S. 50° E.

22921

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., loosely set, projecting 20 ins. above ground, with brass cap mkd.

T 26 S	R 2 W
S 26	S 25
<hr/>	
S 35	S 36
1916	

from which the remains of a bearing tree mkd. by Mensch

A sawed, hollow madrone stump, 28 ins. diam., bears N. 55° W., 25.1 ft. dist., with no marks visible.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1967

A maple, 12 ins. diam., bears N. 72° E., 27.1 ft. dist., with fragmentary raised scribe marks protruding through a healed blaze.

A fir, 24 ins. diam., bears S. 30° E., 16.5 ft. dist., with a healed double blaze.

A fir, 13 ins. diam., bears S. 66° W., 25.1 ft. dist., with a healed double blaze.

and a new bearing tree

A cedar, 5 ins. diam., bears N. 45° W., 32.3 ft. dist., mkd. X BT.

Raise a mound of stone, 3 ft. base, to top.

A search was made for all original line trees bet. secs. 25 and 26 and none were recovered.

22922

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 25 and 26, perpetuated by the Douglas County Surveyor's Office in 1967, monumented with an iron post, 1 in. diam., loosely set, projecting 24 ins. above ground, with brass cap mkd.

1/4
S 26 | S 25
1916

from which the bearing tree mkd. by the Douglas County Surveyor's Office

A cedar, 19 ins. diam., bears S. 28 1/2° W., 41.7 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears S. 85° E., 22.2 ft. dist., mkd. 1/4 S25 BT.

Raise a mound of stone, 3 ft. base, to top.

A search was made for all original line trees bet. secs. 25 and 26 and none were recovered.

22923

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 26 S	R 2 W
S 23	S 24
<hr/>	
S 26	S 25
1916	

from which the remains of the original bearing trees

A fir, 50 ins. diam., bears N. 53° E., 26.4 ft. dist., with a healed blaze and scribe marks T26S R2W S24 C visible in bark.

A burnt, decayed, chinquapin stump, size indeterminate, bears N. 14° W., 13.9 ft. dist., with no marks visible.

and a bearing tree mkd. by the Douglas County Surveyor's Office in 1967

A cedar, 28 ins. diam., bears S. 6 1/2° E., 91.1 ft. dist., with a healed double blaze.

and a bearing tree mkd. by Popken

A fir, 19 ins. diam., bears N. 83° W., 63.4 ft. dist., with a healed blaze. (Record, N. 80° W.)

and a new bearing tree

A fir, 9 ins. diam., bears S. 34 1/4° W., 23.8 ft. dist., mkd. T26S R2W S26 BT.

Corner is located 35 ft. E. of an overgrown logging road, 12 ft. wide, bears N. 20° E. and S. 20° W.

A search was made for all original line trees bet. secs. 24 and 25 as well as bet. secs. 25 and 26 and none were recovered.

22924

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 24 and 25, perpetuated by the Douglas County Surveyor's Office in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

S 24
1/4
—
S 25
1916

from which the remains of an original bearing tree

A fir snag, 35 ins. diam., bears North, 10.6 ft. dist., with a healed blaze.

and a bearing tree mkd. by Mensch

A cedar, 23 ins. diam., bears S. 20° E., 31.7 ft. dist., with a healed blaze.

and a bearing tree mkd. by the Douglas County Surveyor's Office

A cedar, 25 ins. diam., bears N. 24° W., 27.8 ft. dist., with a healed double blaze.

A search was made for all original line trees bet. secs. 24 and 25 and none were recovered.

The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd.

S 23 | S 24
1/4 S |
1916

from which the original bearing trees

A fir, 58 ins. diam., bears N. 47° E., 4.0 ft. dist., with a healed blaze.

A maple, 15 ins. diam., bears S. 38° W., 20.8 ft. dist., with no marks visible on a hollow double blaze.

and the bearing trees mkd. by the Douglas County Surveyor's Office in 1967

A cedar, 16 ins. diam., bears S. 2° E., 30.4 ft. dist., with a healed double blaze.

A hemlock, 13 ins. diam., bears N. 64 1/2° W., 27.1 ft. dist., with a healed double blaze.

22925

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The cor. of sec. 26 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

T 26 S
R 2 W
S 26

1916

from which an original bearing tree

A cedar, 30 ins. diam., bears N. 23° E., 24.4 ft. dist., with scribe marks T2 R2 S26
BT visible on a partially healed blaze.

and a bearing tree mkd. the Douglas County Surveyor's Office in 1967

The northerly trunk of a double hemlock, 15 ins. diam., bears N. 70° E., 21.8 ft. dist.,
with a healed blaze.

The cor. of secs. 27 and 34 only, monumented with an iron post, 2 ins. diam., firmly set,
projecting 16 ins. above ground, with a brass cap mkd. T26S R2W 1913

from which the remains of the original bearing trees

A sawed, decayed, sugar pine stump, 21 ins. diam., bears S. 45° W., 18.5 ft. dist.,
with a healed blaze.

A fir, 35 ins. diam., bears N. 72° W., 15.2 ft. dist., with a healed blaze.

At the corner point

Raise a mound of stone, 3 ft. base, to top, and add marks to the brass cap to read

T 26 S	R 2 W
S 27	
CC—	S 26
S 34	
	2011
	1913

and a new bearing tree

A cedar, 9 ins. diam., bears S. 66 1/4° W., 33.7 ft. dist., mkd. T26S R2W S34 BT.

Corner is located 70 ft. south of a rock face, 20 ft. high; edge bears generally E. and W.

22926

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

Point for the S 1/16 sec. cor. of sec. 26 only, on the line between the cor. of secs. 27 and 34 only and the 1/4 sec. cor. of sec. 26 only, at proportionate distance latitudinally between the cor. of sec. 26 only and the 1/4 sec. cor. of sec. 26 only.

Cement a brass tablet, 3 1/2 ins. diam., with 2 1/2 in. stem, in a drill hole, in a rock outcrop, (deposit a magnet in drill-hole beneath stem) with cap mkd.

| S 1/16
| S 26
2011

from which

A fir, 26 ins. diam., bears N. 14° E., 21.5 ft. dist., mkd. S1/16 S26 BT.

A fir, 11 ins. diam., bears S. 50 1/2° E., 25.1 ft. dist., mkd. X BT.

Corner is located 3 ft. N. of the southerly edge (bottom) of a rock outcropping, 10 ft. high, edge bears N. 70° E. and S. 70° W.

The 1/4 sec. cor. of sec. 26 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, with brass cap mkd.

| 1/4
| S 26
1916

from which the original bearing trees

A fir, 24 ins. diam., bears N. 36 3/4° E., 11.9 ft. dist., with a healed blaze. (Record, N. 28° E.)

A fir, 12 ins. diam., bears S. 43 1/2° E., 42.2 ft. dist., with a healed double blaze.

Corner is located 60 ft. E. of a wide spur, slopes N. 10° E.

22927

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, bent W., projecting 17 ins. above ground, with brass cap mkd.

1/4 S 23
—
S 26
1916

from which the bearing trees mkd. by the Douglas County Surveyor's Office in 1967

A cedar, 49 ins. diam., bears S. 85° E., 117.5 ft. dist., with a healed blaze.

A cedar, 40 ins. diam., bears N. 23° W., 57.8 ft. dist., with no marks visible on open blaze.

Straighten iron post, 36 ins. long, and reset to 30 ins. in ground. Raise a mound of stone, 3 ft. base, to top.

The cor. of secs. 23 and 26 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 26 S
| S 23
—
| S 26
R 2 W
1918

from which the remains of the original bearing trees

A roothole bears N. 43° E., 7.3 ft. dist., with a fallen, decayed fir snag, size indeterminate, lying alongside, with no marks visible.

A cedar, 35 ins. diam., bears S. 27° W., 29.7 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1967

A hemlock, 14 ins. diam., bears N. 55° E., 13.9 ft. dist., with a healed double blaze.
(Record, white fir)

A hemlock, 15 ins. diam., bears S. 38° E., 3.3 ft. dist., with a healed double blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 27 and 34, perpetuated by the Douglas County Surveyor's Office in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above a collar of stone, with brass cap mkd.

1/4 S 27
—————
1/4 S 34
1918

from which the remains of bearing trees mkd by Mensch

- A sawed, decayed, hemlock stump, 16 ins. diam., bears S. 10° E., 4.6 ft. dist., with a healed double blaze.
- A roothole bears N. 17° W., 10.6 ft. dist., with a fallen, decayed, hemlock snag, size indeterminate, lying alongside, with no marks visible.

and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office

- A sawed, decayed, hemlock stump, size indeterminate, bears N. 51 1/2° E., 15.3 ft. dist., with fallen, decayed hemlock trunk segment lying alongside, size indeterminate, with scribe marks 1/4 S27 CS BT visible on a partially healed blaze.

and new bearing trees

- A fir, 10 ins. diam., bears N. 13 1/2° E., 23.2 ft. dist., mkd. 1/4 S27 BT.
- A cedar, 5 ins. diam., bears S. 53° E., 17.1 ft. dist., mkd. 1/4 S34 BT.

Corner is located 25 ft. N. of a gravel road, 12 ft. wide, bears N. 70° W. and S. 85° E., in a curve.

The E 1/16 sec. cor. of secs. 27 and 34, established by Shrum, PLS No. 1706, in 1979, by proportionate measurement, and is accepted as the cor.; monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

T 26 S R 2 W RE 4287
S 27
E 1/16 ———
S 34
1978

from which the bearing trees mkd. by Shrum

- A cedar, 27 ins. diam., bears N. 36 1/2° E., 9.9 ft. dist., with two healed double blazes.
- A fir, 20 ins. diam., bears S. 39 1/4° W., 54.5 ft. dist., with a healed blaze.

22929

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above a collar of stone, with brass cap mkd.

T 26 S	
S 28	S 27

S 33	S 34
R 2 W	
1967	

from which the remains of the original bearing trees

A sawed, decayed, hemlock stump, 25 ins. diam., bears N. 34° E., 17.2 ft. dist., with fragmentary scribe marks visible on partially healed original blaze and scribe marks 26S R27 CS BT visible on an additional partially healed blaze.

A sawed cedar stump, 26 ins. diam., bears S. 78° E., 13.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze and scribe marks T26S R34 CS BT visible on an additional partially healed blaze.

and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office in 1967

A hemlock, 16 ins. diam., bears S. 43° W., 7.9 ft. dist., with a healed double blaze.

A hemlock, 13 ins. diam., bears N. 67° W., 9.9 ft. dist., with a healed double blaze.

and new bearing trees

A cedar, 7 ins. diam., bears N. 31 1/4° E., 42.2 ft. dist., mkd. T26S R2W S27 BT.

A fir, 5 ins. diam., bears S. 65° E., 19.8 ft. dist., mkd. X BT.

Corner is located in a shallow draw, drains N. 10° W.

22930

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 28 and 33, reestablished by proportionate measurement by Edwards, PLS No. 2339, in 1999; there is no remaining evidence of the original cor. and this position is accepted as a careful and faithful reestablishment of the cor.; monumented with a rebar, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with a red plastic cap mkd. D.A. Edwards LS 2339, from which the remains of the bearing trees mkd. by Edwards

A fir stump, 18 ins. diam., 5 1/2 ft. high, bears N. 4 3/4° E., 10.0 ft. dist., with a healed blaze.

A fir, 12 ins. diam., bears N. 64° E., 20.4 ft. dist., with a healed blaze.

A fir snag, 15 ins. diam., bears S. 33° E., 8.8 ft. dist., with scribe marks 1/4 S33 BT visible on an open blaze.

A fir, 18 ins. diam., bears S. 64° W., 29.4 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 26 S R 2 W
S 28
1/4 ———
S 33
2011

Place the rebar, 30 ins. long, inside the stainless steel post, and deposit a magnet in a white plastic case at the base.

From the cor. S. 89° 39' 14" E., at:

245 ft. dist., draw, drains N. 20° E.

810 ft. dist., spur, slopes N. 5° E.

1360 ft. dist., ravine, drains N. 35° E.

22931

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The cor. of secs. 28, 29, 32, and 33, perpetuated by person(s) unknown, subsequently perpetuated by Nygren, PLS No. 1035, in 1999, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with an aluminum cap mkd.

U.S.P.C. PROPERTY COR.
T 26 S | R 2 W
S 29 | S 28

S 32 | S 33
RE 4287

from which the remains of original bearing trees

- A decayed hemlock stump, size indeterminate, bears N. 48° E., 47.5 ft. dist., with a fallen, decayed hemlock snag, size indeterminate, lying alongside, with no marks visible on stump or snag.
- A sawed, decayed, hemlock stump, 38 ins. diam., bears S. 21° E., 13.9 ft. dist., with no marks visible.
- A decayed hemlock stump, size indeterminate, bears S. 52° W., 26.4 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by person(s) unknown

- A sawed hemlock stump, 43 ins. diam., bears S. 55° W., 35.4 ft. dist., with scribe marks S32 BT RE 4287 visible on an open blaze.
- A cedar, 26 ins. diam., bears N. 31° W., 75.0 ft. dist., with scribe marks S29 BT on upper and RE4287 visible on lower open double blaze.

and bearing the trees mkd. by Nygren

- A fir, 11 ins. diam., bears N. 1 1/2° W., 7.8 ft. dist., no marks visible on a partially healed blaze.
 - A hemlock, 9 ins. diam., bears S. 43 3/4° E., 13.4 ft. dist., with a healed double blaze.
 - A hemlock, 12 ins. diam., bears S. 53 1/4° W., 25.9 ft. dist., with scribe marks SEC COR S32 on upper and BT visible on lower open double blaze.
 - A fir, 9 ins. diam., bears N. 33° W., 42.6 ft. dist., with fragmentary scribe marks visible on a partially healed double blaze.
-

22932

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 28 and 29, perpetuated by the Douglas County Surveyor's Office in 1967, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above a collar of stone, (lying out of the ground nearby is the original igneous stone (Record, granite) 8 x 8 x 12 ins., with marks 1/4 visible) with brass cap mkd.

T 26 S
1/4 S 29 | S 28
R 2 W
1967

from which the remains of the original bearing trees

- A hemlock, 27 ins. diam., bears S. 33° E., 13.2 ft. dist., with scribe marks 1/4 S28 BT visible on a previously chopped open and now partially healed blaze.
- A cedar snag, 12 ins. diam., bears N. 41 1/2° W., 40.0 ft. dist., with scribe marks 1/4 and other fragmentary scribe marks visible on a chopped open blaze. (Record, N. 45° W., 33.7 ft. dist.)

and the bearing trees mkd. by the Douglas County Surveyor's Office

- A hemlock, 9 ins. diam., bears N. 45 3/4° E., 22.1 ft. dist., with a healed double blaze.
- A partially uprooted hemlock, 13 ins. diam., bears S. 68 1/2° W., 20.3 ft. dist., with a healed double blaze.

and a new bearing tree

- A cedar, 22 ins. diam., bears S. 58 3/4° W., 44.9 ft. dist., mkd. 1/4 S29 BT.

Incorporate original stone into collar of stone.

Corner is located 250 ft. S. of a gravel road, 15 ft. wide, bears N. 60° W. and S. 65° E., in a curve.

22933

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The cor. of secs. 29, 30, 31, and 32, perpetuated by person(s) unknown, subsequently perpetuated by Quibell, Deputy county Surveyor, in 1981, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above a collar of stone, with aluminum cap mkd.

USPC PROPERTY COR
T 26 S R 2 W
S 30 | S 29

S 31 | S 32
RE 4287 1963

from which the remains of original bearing trees

- A roothole, bears S. 7° E., 11.9 ft. dist., with a fallen, decayed fir snag, size indeterminate, lying uphill, with no marks visible.
- A cedar, 27 ins. diam., bears S. 38° W., 13.9 ft. dist., with a healed blaze.
- A sawed fir stump, 26 ins. diam., bears N. 9° W., 18.5 ft. dist., with a healed blaze.

and a bearing tree mkd. by Quibell

- A cedar, 12 ins. diam., bears N. 75 1/4° E., 40.5 ft. dist., with fragmentary scribe marks visible on partially healed double blazes.

and new accessories

- A rebar, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears N. 72° 45' 42" E, 81.33 ft. dist., with an aluminum cap mkd. RM T26S R2W 81.3 FT TO COR S29 2011, and an arrow pointing to the cor.
- A rebar, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears S. 34° 18' 07" E, 75.46 ft. dist., with an aluminum cap mkd. RM T26S R2W 75.5 FT TO COR S32 2011, and an arrow pointing to the cor.
- A rebar, 30 ins. long, 5/8 in. diam., 29 ins. in the ground for a reference monument, bears N. 51° 21' 50" W, 30.12 ft. dist., with an aluminum cap mkd. RM T26S R2W 30.1 FT TO COR S30 2011, and an arrow pointing to the cor.

Corner is located 40 ft. N. of a gravel road, 13 ft. wide, bears N. 80° E. and S. 80° W, and further located 20 ft. W. of the gravel access road of a rock quarry, 12 ft. wide, bears N. 35° E. and S. 35° W.

22934

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 30 and 31, perpetuated by the Douglas County Surveyor's Office in 1967, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 26 S
S 30
1/4 ———
S 31
R 2 W
1967

from which an original bearing tree

A madrone, 9 ins. diam., bears N. 27° W., 4.6 ft. dist., with no marks visible on a previously chopped open and partially healed decayed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office

A forked hemlock, 23 ins. diam., bears N. 28 1/4° E., 16.5 ft. dist., with a healed blaze.

A fir, 22 ins. diam., bears S. 40° W., 8.5 ft. dist., with a healed blaze.

and a bearing tree mkd. by person(s) unknown

A cedar, 13 ins. diam., bears S. 83 1/4° W., 9.8 ft. dist., with a healed blaze.

Corner is located 395 ft. S. of a double-poled, 3-strand power line, wires bear N. 60° E. and S. 60° W., and 435 ft. S. of a creek, 3 ft. wide, course N. 60° W.

Corner is further located 120 ft. W. of the head of a spring, 2 ft. wide, flows North.

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The cor. of secs. 19, 20, 29, and 30, perpetuated by the Douglas County Surveyor's Office in 1967 and 2007, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 26 S R 2 W
S 19 | S 20

S 30 | S 29
2007

from which an original bearing tree

- A madrone, 16 ins. diam., bears N. 8 1/4° W., 28.4 ft. dist., with axe marks visible on a previously chopped open and partially healed blaze. (Record, N. 6° W.)

and bearing trees mkd. the Douglas County Surveyor's Office in 1967

- A sugar pine, 45 ins. diam., bears N. 75 1/4° E., 32.1 ft. dist., with a healed double blaze.
- A chinquapin, 13 ins. diam., bears N. 49 1/4° W., 34.0 ft. dist., with fragmentary scribe marks visible on partially healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 2007

- A sugar pine, 25 ins. diam., bears N. 56 1/4° E., 28.1 ft. dist., with scribe marks 26R 2W S on upper and other fragmentary scribe marks visible on lower partially healed double blaze.
 - A fir, 8 ins. diam., bears S. 32° W., 23.1 ft. dist., with scribe marks X on upper and BT visible on lower partially healed blaze.
-

22936

**Dependent Resurvey of a Portion of the Subdivisional Lines
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 19 and 30, perpetuated by the Douglas County Surveyor's Office in 1967 and 1975, monumented with an iron post, 1 1/4 ins. diam., firmly set, flush with ground surface, (buried alongside of which I unearth and rebury the original basalt stone, 6 x 9 x 14 ins., with marks 1/4 visible) with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 26 S R 2 W
S 19
1/4 ———
S 30
1967

from which bearing trees mkd. by person(s) unknown, recorded by the Douglas County Surveyor's Office in 1967

A madrone, 13 ins. diam., bears S. 10 3/4° W., 21.0 ft. dist., with scribe marks /4 S30 visible on a weathered, partially healed blaze.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1967

A roothole, bears S. 40 1/2° W., 16.3 ft. dist., with a partially uprooted, sawed, decayed, fir stump alongside, size indeterminate, with no marks visible.

A cedar, 22 ins. diam., bears N. 51 1/2° W., 11.1 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1975

A roothole, bears S. 31 3/4° W., 24.1 ft. dist., with an uprooted, decayed fir lying alongside, 12 ins. diam., with no marks visible.

22937

**Subdivision of Section 26
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of sec. 26 only, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

1/4 S 26

1916

from which an original bearing tree

A cedar, 62 ins. diam., bears N. 42° W., 15.2 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1967

A cedar, 34 ins. diam., bears N. 54 1/2° E., 42.9 ft. dist., with a healed blaze.
(Record, N. 52° E.)

A cedar, 32 ins. diam., bears N. 55° W., 38.3 ft. dist., with a healed blaze.

Point for the center S 1/16 sec. cor. of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground to underlying rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

C
S 1/16 | S 26
C
2011

from which

A cedar, 10 ins. diam., bears S. 31 1/2° E., 24.2 ft. dist., mkd. CS1/16 S26 BT.

A fir, 21 ins. diam., bears S. 62° W., 48.9 ft. dist., mkd. CS1/16 S26 BT.

Corner is located 55 ft. N. of a gravel road, 18 ft. wide, bears N. 80° E. and S. 80° W., and further located 375 ft. E. of the same gravel road, 12 ft. wide, bears N. 60° W. and S. 60° E.

22938

**Subdivision of Section 26
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

The center 1/4 sec. cor. of sec. 26, established by Shrum, PLS No. 1706, in 1981, and is accepted as the cor.; monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with an aluminum cap mkd.

SEC 26
C 1/4
T 26 S R 2 W
LS 1706
1981

from which bearing trees mkd. by Shrum

A fir, 19 ins. diam., bears S. 55° W., 31.6 ft. dist., with a healed blaze.

A cedar, 23 ins. diam., bears N. 16 1/4° W., 6.4 ft. dist., with scribe marks 1/4 S26
BT visible on partially healed blaze.

Corner is located 10 ft. E. of a creek, 2 ft. wide, course N. 10° E.

22939

**Subdivision of Section 30
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

Point selected for a witness point on the N. and S. center line of sec. 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in an embedded collar of stone, with brass cap mkd.

W P
C
S | 30
C
2011

from which

A fir, 11 ins. diam., bears N. 42° E., 9.4 ft. dist., mkd. X BT.

A cedar, 13 ins. diam., bears N. 74 1/4° W., 24.6 ft. dist., mkd. X BT.

From the corner N. 0° 31' 56" W., at:

100 ft. dist., gravel road, 11 ft. wide, bears N. 75° E. and S. 75° W.

180 ft. dist., creek branch, 8 ft. wide, course N. 80° E.

200 ft. dist., creek branch, 3 ft. wide, course S. 85° E.

345 ft. dist., same road, 12 ft. wide, bears N. 85° E. and S. 55° W., in a curve.
