

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
PORTIONS OF
THE SOUTH BOUNDARY (FIFTH STANDARD PARALLEL SOUTH)
AND SUBDIVISIONAL LINES
TOWNSHIP 22 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions approved March 14, 2012,
which provided for the surveys included under Group No. 2653,
and Assignment Instructions dated June 4, 2012.

Survey commenced June 19, 2012

Survey completed July 26, 2012

T. 22 S., R. 6 W., Willamette Meridian, Oregon

The following field notes are those of the dependent resurvey of portions of the south boundary (Fifth Standard Parallel South) and subdivisional lines, Township 22 South, Range 6 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the Fifth Standard Parallel through Range 6 West, and the west boundary, as shown on the official plat of survey approved February 20, 1856.

In 1871, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved April 25, 1872.

In 1883, John A. McQuinn, U.S. Deputy Surveyor, surveyed the subdivisional lines of T. 23 S., R. 6 W., as shown on the official plat of survey approved April 7, 1884.

In 1897, Chapman S. Nicklin, U.S. Deputy Surveyor, resurveyed portions of the Fifth Standard Parallel South through Range 6 West, the west boundary, and subdivisional lines, and surveyed the remainder of the subdivisional lines as shown on the official plat of survey approved March 25, 1898.

In 1943-57, Otis O. Gould, Cadastral Engineer, and Joseph S. Gawron and Orville N. Eggen, Cadastral Surveyors, resurveyed portions of the Fifth Standard Parallel South through Range 6 West, and subdivisional lines of T. 23 S., R. 6 W., as shown on the official plat of survey accepted August 24, 1960.

In 1981, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted September 23, 1983.

In 2010, Kenneth W. Saveland, Cadastral Surveyor, retraced a portion of the subdivisional lines as shown on the official plat of survey accepted January 24, 2012.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by the surveyor's last name, official title or Professional Land Surveyor (PLS) No., and year.

Date	Name and Registration Number	File Number
1955	Wilford N. Haines, PLS No. 239	M2-13
1958	Wilford N. Haines, PLS No. 239	M13-66
1961	Milo E. Godfrey, Deputy County Surveyor	C.S. 49/143
1992	Douglas County Surveyor's Office	C.S. 64/24
1992	James A. Branch, PLS No. 1138	M115-23
1994	Ken W. Hoffine, PLS No. 2291	C.S. 63/154-5
2001	Ken W. Hoffine, PLS No. 2291	C.S. 65/37-7

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions approved March 14, 2012, for Group No. 2653, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and direct solar observation, carried forward by

T. 22 S., R. 6 W., Willamette Meridian, Oregon

sustained angulation using conventional survey techniques. All measurements along the lines were derived through GPS and conventional survey techniques. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the corner description field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position in NAD 1983 (CORS 96) of the following corners as determined by ties to temporary GPS control points, utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The corner of sections 19, 20, 29, and 30:

Latitude: 43° 38' 06.64" N. Longitude: 123° 26' 53.06" W.

The corner of sections 27, 28, 33, and 34:

Latitude: 43° 37' 17.03" N. Longitude: 123° 24' 29.45" W.

The closing corner of sections 33 and 34 on the Fifth Standard Parallel South:

Latitude: 43° 36' 22.47" N. Longitude: 123° 24' 29.65" W.

22981
Dependent Resurvey of a Portion of the South Boundary,
(Fifth Standard Parallel South)
T. 22 S., R. 6 W., Willamette Meridian, Oregon

The closing cor. of secs. 33 and 34, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1992, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, with brass cap mkd.

T 22 S	R 6 W
C	C
S 33	S 34

S 4
T 23 S R 6 W
1955

from which the remains of an original bearing tree

A roothole bears N. 78° W., 66.0 ft. dist., downhill of which is a fallen, decayed fir snag, 30 ins. diam., with no marks visible. (Record, N. 83° W.)

and bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 21 ins. diam., bears N. 33° E., 16.5 ft. dist., with a healed blaze.

A fir, 23 ins. diam., bears N. 67° W., 23.8 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office

A fir, 10 ins. diam., bears N. 83 1/4° E., 29.5 ft. dist., with a healed double blaze.

A fir, 21 ins. diam., bears N. 10° W., 15.1 ft. dist., with a healed double blaze.

Corner is located on a SW. slope, 140 ft. E. of a ravine, drains S. 40° E.

22982
Dependent Resurvey of a Portion of the South Boundary,
(Fifth Standard Parallel South)
T. 22 S., R. 6 W., Willamette Meridian, Oregon

The standard 1/4 sec. cor. of sec. 4 only, on the N. bdy. of T. 23 S., R. 6 W., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, with brass cap mkd.

1/4 S 4
SC

1955

from which the remains of a bearing tree mkd. by Nicklin

A sawed fir stump, 61 ins. diam., bears S. 50° W., 25.7 ft. dist., with a healed blaze.

and new accessories

An iron rod, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground for a reference monument, bears S. 30° 58' 11" E., 14.29 ft. dist., with aluminum cap mkd.
RM T23S R6W S4 14.3 FT TO COR 2012 and an arrow pointing to the cor.

An iron rod, 30 ins. long, 5/8 in. diam., driven 23 ins. in the ground for a reference monument, bears S. 56° 20' 30" W., 18.65 ft. dist., with aluminum cap mkd.
RM T23S R6W S4 18.6 FT TO COR 2012 and an arrow pointing to the cor.

Corner is located on a steep E. slope, 130 ft. W. of a ravine, drains N. 10° W., and 60 ft. N. of a ravine, drains N. 64° E.

Point for the 1/4 sec. cor. of sec. 33 only, on the S. bdy. of the Tp., at midpoint bet. the closing cor. of secs. 32 and 33 and the closing cor. of secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 S R 6 W
1/4 S 33

T 23 S R 6 W
2012

from which

A fir, 19 ins. diam., bears N. 72 1/2° E., 32.0 ft. dist., mkd. 1/4 S33 CC BT.

A fir, 19 ins. diam., bears N. 48 3/4° W., 27.6 ft. dist., mkd. 1/4 S33 CC BT.

Bury a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on a SW. slope, 130 ft. W. of a ridge, bears N. 10° E. and S. 10° W.

22983
Dependent Resurvey of a Portion of the South Boundary,
(Fifth Standard Parallel South)
T. 22 S., R. 6 W., Willamette Meridian, Oregon

The standard cor. of secs. 4 and 5, on the N. bdy. of T. 23 S., R. 6 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 2 ft. diam., 1 ft. high, with brass cap mkd.

T 22 S	R 6 W
S 33	

S 5	S 4

T 23 S	R 6 W
1955	

from which the remains of an original bearing tree

A burnt, decayed fir stump, size indeterminate, bears S. $8\frac{1}{4}^{\circ}$ W., 118.8 ft. dist., with no marks visible. (Record, S. $6\frac{1}{2}^{\circ}$ W.)

and remains of bearing trees mkd. by Gould, Gawron, and Eggen

A decayed fir stump, size indeterminate, bears S. $18\frac{1}{4}^{\circ}$ E., 29.0 ft. dist., with no marks visible. (Record, S. $22\frac{1}{2}^{\circ}$ E.)

A fir, 26 ins. diam., bears S. $33\frac{1}{2}^{\circ}$ W., 47.5 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 6 ins. diam., bears S. $31\frac{1}{4}^{\circ}$ E., 37.0 ft. dist., mkd. T23S R6W S4 SC BT.

Corner is located in the bottom of a draw, drains S. 50° W.

22984
Dependent Resurvey of a Portion of the South Boundary,
(Fifth Standard Parallel South)
T. 22 S., R. 6 W., Willamette Meridian, Oregon

The closing cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

T 22 S	R 6 W
C	C
S 32	S 33
S 5	
T 23 S R 6 W	
1955	

from which the remains of an original bearing tree

A sawed, decayed fir stump, 40 ins. diam., bears N. 11 1/2° W., 56.3 ft. dist., with no marks visible. (Record, 48.8 ft.)

and remains of bearing trees mkd. by Gould, Gawron, and Eggen

A fir snag, 11 ins. diam., bears N. 63 1/2° E., 23.1 ft. dist., with a healed blaze.

A sawed, decayed fir stump, 19 ins. diam., bears N. 46 1/2° W., 15.2 ft. dist., with a healed blaze.

and new bearing trees

A fir, 16 ins. diam., bears N. 8° E., 25.8 ft. dist., mkd. T22S R6W S33 CC BT.

A fir, 7 ins. diam., bears N. 64 3/4° W., 44.3 ft. dist., mkd. T22S R6W S32 CC BT.

Corner is located on a NW. slope, 215 ft. S. of a ravine, drains N. 70° W.

22985

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs 27, 28, 33, and 34, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 22 S R 6 W
S 28 | S 27

S 33 | S 34
1961

from which the remaining bearing tree mkd. by Nicklin

A hollow maple, 19 ins. diam., bears S. 72 1/2° E., 12.5 ft. dist., with reverse scribe marks T W S34 visible on the inside.

and remains of bearing trees mkd. by person(s) unknown

A cedar, 30 ins. diam., bears N. 14 3/4° E., 12.7 ft. dist., with a healed blaze.

A hemlock, 18 ins. diam., bears N. 62° E., 25.5 ft. dist., with a healed double blaze.

A roothole bears S. 63 1/2° W., 11.0 ft. dist., downhill of which is a fallen, decayed hemlock snag, 16 ins. diam., with no marks visible.

and bearing trees mkd. by Saveland

A cedar, 19 ins. diam., bears S. 36 1/2° W., 21.6 ft. dist., with scribe marks T22S R6W S33 BT visible on an open blaze.

A hemlock, 6 ins. diam., bears N. 76 3/4° W., 32.5 ft. dist., with scribe marks X BT visible on an open blaze.

22986

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs 28 and 33, perpetuated by Godfrey, Deputy County Surveyor, in 1961, from original evidence no longer in existence, further perpetuated by Hoffine, PLS No. 2291, in 2001, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S R 6 W

S 28

1/4 ———

S 33

1961

from which the remains of a bearing tree mkd. by Godfrey

A decayed cedar stump, 12 ins. diam., bears N. 26 1/2° E., 31.5 ft. dist., alongside of which is a fallen, decayed cedar snag, 12 ins. diam., with scribe marks 1/4 S28 CS visible on an open blaze.

and bearing trees mkd. by Hoffine

A fir, 10 ins. diam., bears S. 48 3/4° W., 22.9 ft. dist., with a healed blaze.

A fir, 9 ins. diam., bears N. 22° W., 5.0 ft. dist., with a healed blaze.

Corner is located on a broken SW. slope, 30 ft. W. of a graveled road, 12 ft. wide, bears N. 20° E. and S. 37° W., 60 ft. W. of a graveled road, 12 ft. wide, bears S. 20° E. and N. 10° W., and 115 ft. E. of a graveled road, 16 ft. wide, bears S. 35° E. and N. 44° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 28, 29, 32, and 33, perpetuated by Haines, PLS No. 239, in 1955, monumented with a steel bolt, 1 in. diam., firmly set, projecting 4 ins. above ground, with hex nut on top, from which the remains of an original bearing tree

A roothole bears N. 60° E., 6.6 ft. dist.

and remains of bearing trees mkd. by Haines

A sawed fir stump, 48 ins. diam., bears S. 8 1/4° W., 25.0 ft. dist., with a healed blaze.

A roothole bears N. 26° W., 8.3 ft. dist., downhill of which is a fallen, decayed, sawed fir stump, 11 ins. diam., with no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the steel bolt, with brass cap mkd.

T 22 S	R 6 W
S 29	S 28
S 32	S 33
2012	

from which

A fir, 3 ins. diam., bears N. 78 1/2° E., 15.4 ft. dist., mkd. X BT.

A fir, 13 ins. diam., bears S. 25 1/2° E., 32.9 ft. dist., mkd. T22S R6W S33 BT.

A fir, 10 ins. diam., bears S. 48 3/4° W., 11.6 ft. dist., mkd. T22S R6W S32 BT.

A fir, 9 ins. diam., bears N. 48 3/4° W., 24.9 ft. dist., mkd. T22S R6W S29 BT.

Bury a magnet in a white plastic case at the base of the stainless steel post.

22988

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 32 and 33, perpetuated by Haines, PLS No. 239, in 1958, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 11 ins. above ground, with brass disk attached, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of the original bearing trees

A fir, 42 ins. diam., bears S. 45° E., 34.3 ft. dist., with a healed blaze.

A fir snag, 23 ins. diam., bears N. 13 1/2° W., 17.8 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

1/4
S 32 | S 33
2012

from which

A fir, 20 ins. diam., bears S. 32° W., 11.2 ft. dist., mkd. 1/4 S32 BT.

Bury a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on an E. slope, 180 ft. N. of a ravine, drains N. 80° E.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

The S 1/16 sec. cor. of secs. 32 and 33, established by Haines, PLS No. 239, in 1958, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, broken off at ground level, with brass disk attached to a segment of "T" shaped iron rod lying alongside, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which bearing trees mkd. by Haines

A fir, 50 ins. diam., bears N. 37 1/4° E., 17.8 ft. dist., with fragmentary scribe marks visible on the bark.

A decayed fir snag, 56 ins. diam., bears S. 66 1/4° E., 38.0 ft. dist., with scribe marks S 1/16 S33 visible on the bark.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

S 1/16		
S 32		S 33
2012		

from which

A fir, 10 ins. diam., bears N. 14 1/2° W., 11.9 ft. dist., mkd. S 1/16 S32 BT.

Bury a magnet in a white plastic case and broken off segment of the "T" shaped iron rod at the base of the stainless steel post.

Corner is located on a SW. slope, 95 ft. N. of a dirt road, 16 ft. wide, bears S. 50° E. and N. 45° W.

22990

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, directly below an X mark on the NE. face of a basalt rock outcrop, 4 x 4 x 3 ft. high, with brass cap mkd.

T 22 S		R 6 W
S 19		S 20
S 30		S 29
1981		

from which the remains of the original bearing trees

- A decayed fir stump, size indeterminate, bears N. 34° E., 24.4 ft. dist., with no marks visible.
- A sawed, decayed fir stump, 80 ins. diam., bears S. 20° E., 124.1 ft. dist., with a healed blaze.
- A decayed fir snag, 51 ins. diam., bears S. 72° W., 37.3 ft. dist., with a healed blaze.
- A fir, 54 ins. diam., bears N. 1° W., 47.5 ft. dist., with a healed blaze.

and remains of bearing trees mkd. by Godfrey, Deputy County Surveyor, in 1961

- A sawed fir stump, 13 ins. diam., bears N. 82° E., 33.7 ft. dist., with a healed blaze.
- A roothole bears S. 48° E., 18.8 ft. dist., alongside of which is a fallen fir snag, 20 ins. diam., with no marks visible.
- A roothole bears N. 18° W., 37.5 ft. dist., alongside of which is a fallen fir snag, 19 ins. diam., with a healed blaze. (Record, N. 28° W., 29.4 ft.)

and new bearing trees

- hemlock, 5 ins. diam., bears N. 71 1/2° E., 77.0 ft. dist., mkd. X BT.
 - A fir, 20 ins. diam., bears S. 73 3/4° E., 29.3 ft. dist., mkd. T22S R6W S29 BT. (Mag-Nail driven in left side center)
 - A fir, 5 ins. diam., bears S. 45° W., 16.7 ft. dist., mkd. X BT.
-

22991

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist. There is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

S 19
1/4 ———
S 30
2012

from which

A fir, 12 ins. diam., bears S. 78 3/4° W., 23.2 ft. dist., mkd. 1/4 S30 BT.

A fir, 19 ins. diam., bears N. 7 3/4° W., 60.8 ft. dist., mkd. 1/4 S19 BT.

Bury a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on a SW. slope, 95 ft. W. of a graveled road, 10 ft. wide, bears S. 50° E. and N. 68° W., and 25 ft. S. of the same road, 10 ft. wide, bears S. 82° E. and West.

From this cor., a point established as the 1/4 sec. cor. of secs. 19 and 30 by Haines, PLS No. 239, in 1955, bears S. 81° 49' 29" W., 25.41 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 13 ins. above ground, with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which bearing trees mkd. by Haines

A fir, 54 ins. diam., bears S. 26 1/4° E., 99.3 ft. dist., with a healed blaze.

A cedar, 61 ins. diam., bears N. 13 1/4° W., 132.0 ft. dist., with a healed blaze.

This point was not correctly positioned and is not utilized in the course of this survey.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

The W 1/16 sec. cor. of secs. 19 and 30, established by Haines, PLS No. 239, in 1955, perpetuated by Hoffine, PLS No. 2291, in 1994, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, buried 3 ins. below the ground, from which bearing trees mkd. but not recorded by Haines

A fir, 28 ins. diam., bears S. 79° W., 184.6 ft. dist., with a healed double blaze.

A fir, 27 ins. diam., bears N. 34° W., 122.8 ft. dist., with a healed blaze.

and bearing tree mkd. by Hoffine

A fir, 13 ins. diam., bears N. 20 1/2° E., 13.3 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

S 19
W 1/16 ———
S 30
2012

from which

A fir, 11 ins. diam., bears S. 52 1/2° W., 30.7 ft. dist., mkd. W 1/16 S30 BT.

Bury a magnet in a white plastic case at the base of the stainless steel post.

From this cor., a point established as the W 1/16 sec. cor. of secs. 19 and 30 by Haines, PLS No. 239, in 1955, bears S. 83° 17' 33" W., 36.01 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 11 ins. above ground, with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines

A sawed fir stump, 48 ins. diam., bears S. 11° W., 59.0 ft. dist., with no marks visible.

A sawed, decayed fir stump, 39 ins. diam., bears N. 22 1/2° W., 48.0 ft. dist., with no marks visible.

This point was superceded by Haines when he corrected his cor. positions but did not correct his plat. It is not correctly positioned and is not utilized in the course of this survey

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon**

The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp., perpetuated by Haines, PLS No. 239, in 1955, further perpetuated by Godfrey, Deputy County Surveyor, in 1961, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 22 S R 6 W
 | S 19
SEC | S 30
COR₁₉₆₁

from which the remaining original bearing tree

A fir, 46 ins. diam., bears N. 80° E., 13.9 ft. dist., with no marks visible on an opened blaze. (Record, 60.1 ft.)

and an accessory mkd. by Haines

A "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 11 ins. above ground, for a reference monument, bears S. 74° 18' 13" W., 47.73 ft. dist., with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE

and bearing trees mkd. by Godfrey

A fir, 10 ins. diam., bears N. 36° E., 11.3 ft. dist., with a healed double blaze.

A fir, 9 ins. diam., bears S. 53° E., 9.7 ft. dist., with a healed blaze.

(Note: Godfrey recovered the remains of the original maple bearing tree with scribing visible at S. 20° E., 91 lks. dist., and determined the distances to the original bearing trees were reversed in Nicklin's notes.)
