

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

PERPETUATION OF THE CORNER OF SECTIONS 25 AND 36 ONLY

TOWNSHIP 25 SOUTH, RANGE 3 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions approved April 28, 2010, which provided for the surveys included under Group No. 2500, Oregon, Administrative File No. 1308, and Assignment Instructions dated May 28, 2013.

Survey commenced July 17, 2013

Survey completed July 17, 2013

T. 25 S., R. 3 W., Willamette Meridian, Oregon

The following field notes are those of the perpetuation of the corner of sections 25 and 36 only, Township 25 South, Range 3 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1883, Laban H. Wheeler, U.S. Deputy Surveyor, surveyed the east boundary as shown on the official plat of survey accepted May 19, 1884.

In 1900, Hezekiah H. Johnson, U.S. Deputy Surveyor, retraced the east boundary as shown on the official plat of survey accepted May 6, 1901.

In 1943-44, Norman D. Price, Associate Cadastral Engineer, resurveyed the east boundary as shown on the official plat of survey approved July 24, 1945, and accepted January 7, 1946.

In 1972-75, Daniel L. Berry, Harvey E. Wofford, and G. Steven Popken, Cadastral Surveyors, and Glenn S. Baughman, Registered Land Surveyor No. 536, resurveyed a portion of the east boundary, as shown on the official plat of survey of T. 25 S., R. 2 W., accepted March 7, 1977.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in the subsequent corner description and are referenced by surveyor's last name, official title or Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1966	Douglas County Surveyor's Office	C.S. 54/27
1998	David A. Edwards, PLS No. 2339	M128-61

The perpetuation of corner points was made at the request of the Oregon/Washington State Director, for the protection of the Public Land Survey System infrastructure.

The identified corner was remonumented in its original position.

**Perpetuation of the Corner of Sections 25 and 36 only,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

Restoring the 1883 survey by Laban H. Wheeler, the 1900 retracement by Hezekiah H. Johnson, the 1943-44 resurvey by Norman D. Price, and the 1972-75 resurvey by Daniel L. Berry, Harvey E. Wofford, G. Steven Popken, and Glenn S. Baughman

The cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.

23037

**Perpetuation of the Corner of Sections 25 and 36 Only,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

T25S		T25S
S25		
<hr/>		R2W
S36		
R3W		S30
1943		

from which the remains of an original bearing tree

A decayed hemlock stump, size indeterminate, bears S. $67\ 1/2^\circ$ E., 27.1 ft. dist., with no marks visible.

and remains of the bearing trees mkd. by Price in 1943-44

A cedar snag, 30 ins. diam., bears S. 43° W., 56.8 ft. dist., with scribe marks 25S R3W S36 visible on a partially healed blaze.

A root wad, size indeterminate, bears N. 39° W., 31.7 ft. dist., with no marks visible.

and remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1966

A yew snag, 6 ins. diam., bears N. 41° W., 25.1 ft. dist., with scribe marks T25S R3W visible on a partially healed blaze.

and bearing tree mkd. by Berry, Wofford, Popken, and Baughman in 1972-75

A white fir, 24 ins. diam., bears S. $57\ 1/4^\circ$ W., 57.4 ft. dist., with a healed blaze.
(Record, hemlock, S. 55° W.)

and a new bearing tree

A hemlock, 16 ins. diam., bears N. $14\ 1/4^\circ$ W., 13.9 ft. dist., mkd. T25S R3W S25 BT.
Drive a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) at the base on right side center.

The geographic position in NAD 1983 (2011) of this cor., as determined by a tie from a temporary Geographic Position System (GPS) control point, established utilizing dual frequency, carrier phase GPS receivers, relative to "DODSON BUTTE CORS ARP", "CAPE BLANCO CORS ARP", and "ROSEBURG COOP CORS ARP", is as follows:

Latitude: $43^\circ\ 21'\ 34.81''$ N. Longitude: $122^\circ\ 59'\ 25.55''$ W.
