

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES

TOWNSHIP 20 SOUTH, RANGE 8 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Kenneth W. Saveland, Cadastral Surveyor

Under Special Instructions approved May 17, 2012,
which provided for the surveys included under Group No. 2670,
and Assignment Instructions dated May 17, 2012.

Survey commenced May 23, 2012

Survey completed June 4, 2013

T. 20 S., R. 8 W., Willamette Meridian, Oregon

The following field notes are those of the dependent resurvey of portions of the subdivisional lines, Township 20 South, Range 8 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1883-84, William P. Wright, U.S. Deputy Surveyor, surveyed the exterior boundaries and subdivisional lines, as shown on the official plat of survey approved August 4, 1884.

In 1891, Charles M. Collier, U.S. Deputy Surveyor, resurveyed the north boundary of the township and surveyed the subdivisional lines of T. 19 S. R. 8 W., as shown on the official plat of survey of T. 19 S., R. 8 W. approved April 4, 1892.

In 1950, Thomas A. Tillman, Cadastral Engineer, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted February 7, 1952.

In 1952, Marvin J. Lytle and Palmer Norseth, Cadastral Engineers, resurveyed a portion of the north boundary of the township, as shown on the official plat of survey of T. 19 S., R. 8 W., accepted May 29, 1953.

In 1953-54, Thomas A. Tillman, Raymond M. Bicknell, Hans W. Thielsen, and Joseph S. Gawron, Cadastral Engineers, resurveyed a portion of the north, east, and west boundaries and a portion of the subdivisional lines, as shown on the official plat of survey accepted February 3, 1960.

In 1967, William W. Glenn, C. Albert White, and James E. Jelley, Cadastral Surveyors, remonumented certain original corner points, as shown in the official field notes approved March 3, 1977.

In 2005, Aaron M. Graham, Cadastral Surveyor, rehabilitated certain corner points, as shown in the official field notes approved January 30, 2009.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner description and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1983	Robert G. Dean, PLS No. 1808	C.S. 58/204 N. A & B
1989	Les D. Roberts, PLS No. 1039	C.S. 63/85
1993	Les D. Roberts, PLS No. 1039	C.S. 63/149
2012	Ronald S. Rice, PLS No. 54633	C.S. 65/76-36 & 37

The 1983 survey by Robert G. Dean, PLS No. 1808, established numerous iron rod monuments, 1/2 in. diam., along the south half mile between sections 7 and 8. These iron rods were not used for control during this resurvey.

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions dated May 17, 2012, for Group No. 2670, Oregon.

The direction of the lines are based on the true meridian as determined by direct solar observation and Global Positioning System (GPS) techniques, carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were

T. 20 S., R. 8 W., Willamette Meridian, Oregon

derived through GPS and conventional survey techniques. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data were thoroughly verified and only the corner description field notes are given herein.

A magnet in a white plastic case was deposited at the base of each stainless steel post and each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description. Only those lines bounding Federal interest land were blazed.

The geographic position in NAD 1983 (2011) as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The corner of sections 14, 15, 22, and 23:

Latitude: 43° 49' 16.02" N. Longitude: 123° 37' 12.64" W.

The 1/4 section corner of sections 9 and 10:

Latitude: 43° 50' 31.99" N. Longitude: 123° 38' 24.19" W.

The corner of sections 8, 9, 16, and 17:

Latitude: 43° 50' 06.84" N. Longitude: 123° 39' 34.24" W.

The corner of sections 4, 5, 32, and 33, on the N. bdy. of the Tp.:

Latitude: 43° 51' 46.26" N. Longitude: 123° 39' 32.65" W.

The 1/4 section corner of sections 7 and 18:

Latitude: 43° 50' 05.66" N. Longitude: 123° 41' 21.12" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap oriented northwesterly, mkd.

T	20	S	R	8	W
S	15		S	14	

S	22		S	23	
1950					

23041

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

from which the remains of a bearing tree mkd. by Tillman in 1950

A decayed fir stump, size indeterminate, bears S. $13\ 3/4^\circ$ W., 106.3 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Glenn, et al., in 1967

A burnt fir stump, 50 ins. diam., bears N. $25\ 1/2^\circ$ E., 68.3 ft. dist., no marks visible.

A burnt fir stump, 53 ins. diam., bears S. $68\ 1/2^\circ$ E., 108.2 ft. dist., no marks visible.

A burnt, decayed fir stump, 50 ins. diam., bears N. $78\ 1/2^\circ$ W., 107.6 ft. dist., with axe marks.

and the bearing trees mkd. by Graham in 2005

A fir, 19 ins. diam., bears N. $34\ 3/4^\circ$ E., 20.5 ft. dist., with a healed blaze.

A fir, 21 ins. diam., bears S. $84\ 1/4^\circ$ E., 113.3 ft. dist., with a healed blaze.

A fir, 15 ins. diam., bears S. 13° W., 74.5 ft. dist., with a healed blaze.

An alder, 9 ins. diam., bears N. 84° W., 31.8 ft. dist., with scribe marks T20S R8W S15 BT visible on bark.

The 1/4 sec. cor. of secs. 14 and 15, perpetuated by Roberts, PLS No. 1039, in 1993, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.

1/4
S 15 | S 14
1954

from which the bearing trees mkd. by Roberts

A fir, 15 ins. diam., bears S. 35° E., 8.7 ft. dist., with a healed blaze.

A fir, 18 ins. diam., bears S. 68° W., 48.6 ft. dist., with a healed blaze.

The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

S 15
1/4 ———
S 22
1950

from which new bearing trees

23042

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

A fir, 13 ins. diam., bears S. 64 1/4° E., 9.3 ft. dist., mkd. 1/4 S22 BT.

A fir, 17 ins. diam., bears N. 5° W., 12.8 ft. dist., mkd. 1/4 S15 BT.

The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.

T 20 S	R 8 W
S 16	S 15
S 21	S 22
1950	

from which the remains of the original bearing trees

A decayed cedar stump, 34 ins. diam., bears S. 33 3/4° E., 17.2 ft. dist., with illegible scribe marks visible on partially healed blaze.

A fir stump, 77 ins. diam., bears S. 54° W., 12.5 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Tillman in 1950

A cedar stump, 51 ins. diam., bears N. 30° W., 40.3 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A cedar stump, 40 ins. diam., bears N. 76° E., 8.3 ft. dist., no marks visible.

and the bearing trees mkd. by Graham in 2005

A fir, 14 ins. diam., bears N. 48° E., 24.9 ft. dist., with a healed blaze.

A fir, 24 ins. diam., bears S. 66 3/4° E., 30.0 ft. dist., with a healed blaze. (Record, S. 51 1/4° E.)

A fir, 26 ins. diam., bears S. 31° W., 54.7 ft. dist., with a healed blaze.

A fir, 10 ins. diam., bears N. 7 3/4° W., 16.4 ft. dist., with a healed blaze.

The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.

1/4	
S 16	S 15
1954	

from which the remains of a bearing tree mkd. by Tillman, et al. in 1953-54

A hemlock stump, 54 ins. diam., bears N. 44° W., 5.9 ft. dist., no marks visible.


**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

and the bearing trees mkd. by Graham in 2005

A fir, 15 ins. diam., bears N. 55 1/4° E., 13.4 ft. dist., with a healed blaze.

A fir, 15 ins. diam., bears S. 61° W., 20.4 ft. dist., with a healed blaze.

The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.



from which the remains of original bearing trees

A decayed fir stump, 50 ins. diam., bears S. 80° W., 32.3 ft. dist., with axe marks visible on open blaze.

A decayed fir stump, 50 ins. diam., bears N. 36° W., 23.1 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A fir stump, 43 ins. diam., bears S. 30° E., 31.0 ft. dist., with scribe marks 20S R8W S15 BT visible on an open blaze.

and the bearing trees mkd. by Graham in 2005

A fir, 14 ins. diam., bears N. 21 1/4° E., 6.6 ft. dist., with a healed blaze.


A fir, 17 ins. diam., bears S. 40 1/4° E., 13.7 ft. dist., with a healed blaze.

A fir, 17 ins. diam., bears S. 27° W., 11.9 ft. dist., with a healed blaze.
(Record, S. 30 1/2° W.)

A fir, 14 ins. diam., bears N. 61 1/4° W., 5.9 ft. dist., with a healed blaze.
(Record, N. 80° W.)

A steel fence post is alongside the cor.

The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.



from which the remains of bearing trees mkd. by Glenn, et al., in 1967

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

A decayed fir stump, 47 ins. diam., bears S. 36° E., 46.9 ft. dist., with scribe marks 4 S visible on partially healed blaze.

A decayed fir stump, 21 ins. diam., bears N. 11° W., 33.0 ft. dist., with no marks.

and the bearing trees mkd. by Graham in 2005

A fir, 14 ins. diam., bears N. 28 3/4° E., 15.9 ft. dist., with a healed blaze and a magnail on right side center.

A fir, 19 ins. diam., bears S. 48 1/2° W., 8.5 ft. dist., with a healed blaze and a magnail on right side center.

A steel fence post is alongside the cor.

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with a brass cap mkd.

T 20 S	R 8 W
S 8	S 9
S 17	S 16
1954	

from which the remains of original bearing trees

A fir stump, 86 ins. diam., bears S. 47° E., 42.2 ft. dist., no marks visible.

A fir stump, 40 ins. diam., bears N. 23° W., 29.1 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Tillman, et al., in 1953-54

A decayed cedar stump, size indeterminate, bears S. 56 1/4° E., 47.9 ft. dist., no marks visible.

A decayed fir stump, 75 ins. diam., bears S. 85 1/2° W., 31.7 ft. dist., no marks visible.

A cedar stump, 27 ins. diam., bears N. 8 1/2° W., 19.1 ft. dist., with scribe marks T20S R8W S8 BT visible on partially healed blaze.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A cedar stump, 36 ins. diam., bears N. 31° E., 49.2 ft. dist., with scribe marks T20S R8W visible on partially healed blaze.

and the bearing trees mkd. by Graham in 2005

An alder, 11 ins. diam., bears N. 63° E., 28.5 ft. dist., with scribe marks T20S R8W S9 BT visible on bark.

A fir, 18 ins. diam., bears S. 63 1/2° E., 35.6 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

- A fir, 11 ins. diam., bears S. 71 1/2° W., 35.5 ft. dist., with a healed blaze.
- A hemlock, 18 ins. diam., bears N. 20 1/2° W., 32.6 ft. dist., with scribe marks OS R8W S8 BT visible on partially healed blaze.

The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.

1/4
S 8 | S 9
1954

from which the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

- A burnt fir stump, 45 ins. diam., bears N. 11° W., 50.2 ft. dist., with a healed blaze.

and the bearing trees mkd. by Graham in 2005

- A fir, 11 ins. diam., bears N. 7 1/2° E., 22.4 ft. dist., with a healed blaze.
(Record, N. 9 1/4° E.)

- A fir, 18 ins. diam., bears N. 54 1/2° W., 15.0 ft. dist., with a healed blaze.

A steel fence post is alongside cor.

The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground (alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground), with a brass cap mkd.

T 20 S R 8 W
S 5 | S 4

S 8 | S 9
1954

from which the remains of an original bearing tree

- A decayed fir stump, size indeterminate, bears S. 65° E., 21.8 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Tillman, et al., in 1953-54

- A fir stump, 35 ins. diam., bears S. 12° W., 24.4 ft. dist., with scribe marks R8W S8 BT visible on open blaze.

- A fir stump, 21 ins. diam., bears N. 29° W., 37.6 ft. dist., with a healed blaze. (Record, N. 31 1/2° W., 40.2 ft. dist.)

and the bearing trees mkd. by Graham in 2005

23046

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

- A fir, 24 ins. diam., bears N. 63° E., 15.3 ft. dist., with a healed blaze. (Record, 16.9 ft. dist.)
 - A fir, 22 ins. diam., bears S. 4° E., 31.8 ft. dist., with a healed blaze.
 - A fir, 8 ins. diam., bears S. 42° W., 32.0 ft. dist., with a healed blaze. (Record, 30.5 ft. dist.)
 - A fir, 14 ins. diam., bears N. 57° W., 20.5 ft. dist., with a healed blaze.
-

The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

1/4
S 5 | S 4
1954

from which the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

- A fir stump, 30 ins. diam., bears N. 13° E., 25.3 ft. dist., no marks visible.

and the bearing trees mkd. by Graham in 2005

- A fir, 11 ins. diam., bears N. 55° E., 25.6 ft. dist., with a healed blaze and a magnail on right side center. (Record, N. 56 1/2° E.)
 - A fir, 9 ins. diam., bears S. 27° W., 5.4 ft. dist., with a healed blaze and a magnail on right side center.
-

The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

T 19 S R 8 W
S 32 | S 33

S 5 | S 4
T 20 S R 8 W
1952

from which the remains of original bearing trees

- A fir stump, 36 ins. diam., bears N. 51° E., 28.4 ft. dist., with a healed blaze.
- A decayed fir stump, 25 ins. diam., bears S. 16 1/2° E., 19.1 ft. dist., no marks visible.
- A fir stump, size indeterminate, bears N. 16 1/2° W., 26.8 ft. dist., with a healed blaze. (Record, 31.0 ft. dist.)

and the remains of the bearing trees mkd. by Lytle and Norseth in 1952

23047

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

A fir snag, 29 ins. diam., bears S. $6\frac{3}{4}^{\circ}$ W., 33.7 ft. dist., with a healed blaze.

A decayed fir stump, size indeterminate, bears N. $29\frac{3}{4}^{\circ}$ W., 31.7 ft. dist., with a healed blaze.

and new bearing trees

A fir, 15 ins. diam., bears N. $55\frac{3}{4}^{\circ}$ E., 16.3 ft. dist., mkd. T19S R8W S33.

A hemlock, 37 ins. diam., bears S. $9\frac{3}{4}^{\circ}$ E., 38.7 ft. dist., mkd. T20S R8W S4 BT.

A fir, 11 ins. diam., bears S. $67\frac{1}{4}^{\circ}$ W., 16.6 ft. dist., mkd. T20S R8W S5 BT.

A fir, 12 ins. diam., bears N. 41° W., 21.9 ft. dist., mkd. T19S R8W S32 BT.

The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.

T 20 S R 8 W	
S 7	S 8

S 18	S 17
1954	

from which the remains of the bearing trees mkd. by Tillman, et al., in 1953-54

A burnt fir stump, 21 ins. diam., bears S. 4° E., 33.0 ft. dist., with a healed blaze.

A decayed fir stump, 37 ins. diam., bears S. 88° W., 50.2 ft. dist., no marks visible.

and the bearing trees mkd. by Dean, PLS No. 1808, in 1983

A fir, 12 ins. diam., bears N. $71\frac{1}{2}^{\circ}$ E., 24.4 ft. dist., with a healed blaze.

A fir, 22 ins. diam., bears S. $60\frac{1}{4}^{\circ}$ E., 18.8 ft. dist., with a healed blaze.

A fir, 12 ins. diam., bears S. $21\frac{1}{4}^{\circ}$ W., 16.5 ft. dist., with a healed blaze.

A fir, 16 ins. diam., bears N. $52\frac{3}{4}^{\circ}$ W., 24.4 ft. dist., with a healed blaze.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.

$\frac{1}{4}$	
S 7	S 8

1954	

from which the remains of the original bearing trees

23048

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

A decayed cedar stump, 24 ins. diam., bears N. 55° E., 19.1 ft. dist., no marks visible.

A decayed cedar stump, 58 ins. diam., bears S. 60° W., 23.4 ft. dist., axe mark visible in face. (Record, 27.7 ft. dist.)

and new bearing trees

An alder, 13 ins. diam., bears S. 51 3/4° E., 24.4 ft. dist., mkd. 1/4 S8 BT.

A cedar, 8 ins. diam., bears S. 76° W., 69.3 ft. dist., mkd. 1/4 S7 BT.

At N. 0° 12' 34" W.:

At 5 ft. dist., Creek, 10 ft. wide, course N. 75° W.

The cor. of secs. 5, 6, 7, and 8, perpetuated by Rice, PLS No. 54633, in 2012, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with a brass cap mkd.

T 20 S R 8 W	
S 6	S 5

S 7	S 8
1954	

from which the remains of original bearing trees

A decayed fir stump, 23 ins. diam., bears S. 80° E., 7.9 ft. dist., with a healed blaze.

A decayed fir stump, 34 ins. diam., bears S. 60° W., 11.2 ft. dist., no marks visible.

and the bearing trees mkd. by Rice

A fir, 20 ins. diam., bears N. 67 1/4° E., 25.7 ft. dist., with scribe marks T20S R8W S5 BT visible on partially opened blaze.

A fir, 21 ins. diam., bears S. 47 1/2° W., 27.6 ft. dist., with scribe marks T20S R8W S7 BT visible on partially opened blaze.

A fir, 22 ins. diam., bears S. 80° W., 36.4 ft. dist., with scribe marks T20S R8W S7 BT visible on partially opened blaze.

A fir, 17 ins. diam., bears N. 43 3/4° W., 3.6 ft. dist., with scribe marks T20S R8W S6 BT visible on partially opened blaze.

The 1/4 sec. cor. of secs. 5 and 8, perpetuated by Rice, PLS No. 54633, in 2012, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.

23049

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

S 5
1/4 ———
S 8
1954

from which the remains of the bearing trees mkd. by Tillman, et al., in 1953-54

- A decayed fir stump, 21 ins. diam., bears S. 54 1/4° W., 44.7 ft. dist., with scribe marks 1/4 S8 BT visible on partially healed blaze. (Record, 47.5 ft. dist.)
- A decayed cedar stump, 30 ins. diam., bears N. 59° W., 42.7 ft. dist., no marks visible. (Record, 46.2 ft. dist.)

and the bearing trees mkd. by Graham in 2005

- A fir, 20 ins. diam., bears S. 17° E., 12.2 ft. dist., with a healed blaze.
- A fir, 9 ins. diam., bears N. 9 1/2° W., 23.0 ft. dist., with a healed blaze. (Record, N 7 1/2° W.)

and a bearing tree mkd. by Rice

- A fir, 24 ins. diam., bears N. 74° E., 12.1 ft. dist., with scribe marks 1/4 S5 BT visible on partially healed blaze.

At S. 89° 47' 12" E., at:

- 40 ft. dist., Herb Creek road, gravel surfaced, 10 ft. wide, bears N. 15° E. and S. 5° W., in curve.
- 90 ft. dist., Herb Creek, 27 ft. wide, course S. 5° W.

The 1/4 sec. cor. of secs. 7 and 18, perpetuated by Roberts, PLS No. 1039, in 1989, monumented with an iron post, 1 in. diam., firmly set, with top 12 ins. below the surface of the ground, with a brass cap mkd.

S 7
1/4 ———
S 18
1954

from which the remains of the bearing trees mkd. by Roberts

- A hemlock stump, 37 ins. diam., bears N. 27° E., 86.9 ft. dist., with scribe marks 1/4 S7 BT visible on partially opened blaze.
- A fir stump, 34 ins. diam., bears S. 50 1/2° E., 48.4 ft. dist., with scribe marks 1/4 S18 visible on open blaze.

and bearing trees mkd. by person(s) unknown

23050

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

A fir, 9 ins. diam., bears N. $51\ 1/2^\circ$ E., 6.5 ft. dist., with a healed blaze.

A fir, 11 ins. diam., bears S. $23\ 1/2^\circ$ W., 21.1 ft. dist., mkd. 1/4 S17 BT.

and new reference monuments

A rebar, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground bears
S. $51^\circ\ 31'\ 40''$ W., 30.31 ft. dist., with an aluminum cap mkd. RM 1/4 S18 30.3 ft. TO
COR 2013, and an arrow pointing to the cor.

A rebar, 30 ins. long, 5/8 in. diam., driven 30 ins. in the ground bears
N. $31^\circ\ 05'\ 03''$ W., 23.85 ft. dist., with an aluminum cap mkd. RM 1/4 S7 23.9 ft. TO
COR 2013, and an arrow pointing to the cor.

Corner is located in a dirt road, 10 ft. wide, bears E. and W.
