

Form 9180-6  
(April 1974)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT ORIGINAL

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 29 SOUTH, RANGE 9 WEST,

NOTE: THIS PAGE AND PAGE 23135 ARE THE ONLY PAGES  
OF THIS BLM REMONUMENTATION THAT IS FILED IN DOUGLAS  
CO. THE REST OF THE CORNERS VISITED ARE IN COOS CO.

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

Jack W. Bowder, Cadastral Surveyor

Under special instructions dated May 3, 19 57, approved May 6, 1957,

\_\_\_\_\_ , which provided for the surveys included under U.S. Survey/Group  
Number 350, and assignment instructions dated November 17, 19 77.

Survey commenced November 28, 19 77

Survey completed March 3, 19 78

## T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 29 south, range 9 west, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories, when Needed".

The remonumentation of original corner points was made at the request of the Coos Bay District Manager for administrative purposes of the Bureau of Land Management.

The mean magnetic declination is 20° 30' E.

South Boundary, T. 29 S., R. 9 W.,  
Willamette Meridian, Oregon

(Remonumenting a corner established by Dennis Hathorn,  
U. S. Deputy Surveyor, in 1855,  
and remonumented by William M. Porter,  
U. S. Deputy Surveyor, in 1907-09)

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with a sandstone, 12 x 12 x 8 ins., firmly set 6 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face, from which the remains of an original bearing tree:

A sawed fir stump, 50 ins. diam., bears S. 27° E., 20 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 9 W

$\frac{1}{4}$   $\frac{S 32}{S 5}$

T 30 S

1978

from which new bearing trees

A hemlock, 14 ins. diam., bears N. 24 $\frac{1}{2}$ ° E., 65 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S32 BT.

A hemlock, 25 ins. diam., bears S. 18° E., 51 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

Deposit corner stone alongside iron post.

Corner is located 1.50 chs. E. of creek, 4 lks. wide, course SW.

Subdivisions, T. 29 S., R. 9 W.,  
Willamette Meridian, Oregon

(Remonumenting corners established by William M. Porter,  
U. S. Deputy Surveyor, in 1907-09)