

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
AND
THE SUBDIVISION OF SECTION 20,
TOWNSHIP 20 SOUTH, RANGE 7 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

George M. Winter, Cadastral Surveyor

Under Special Instructions approved May 8, 2013,
which provided for the surveys included under Group No. 2699,
and Assignment Instructions dated May 8, 2013.

Survey commenced May 8, 2013

Survey completed September 12, 2013

T. 20 S., R. 7 W., Willamette Meridian, Oregon

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 20, Township 20 South, Range 7 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1891, Thomas E. Todd, U.S. Deputy Surveyor, surveyed the subdivisional lines as shown on the official plat of survey approved November 9, 1892.

In 1960, Floyd A. Brooks, Cadastral Surveyor, remonumented the original 1/4 section corner of sections 19 and 20 as described in the official field notes approved March 12, 1962.

In 1966-67, Lynn M. Roseberry and William W. Glenn, Cadastral Surveyors, resurveyed a portion of the east boundary of T. 20 S., R. 8 W., resurveyed a portion of the subdivisional lines and remonumented certain original corner points, as shown on the official plat of survey accepted January 19, 1970.

In 1983-84, Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, resurveyed a portion of the south boundary and subdivisional lines and subdivided sections 33 and 34, as shown on the official plat of survey accepted January 23, 1987.

In 2012, A. Bert Skeesick, Cadastral Surveyor, retraced a portion of the subdivisional lines as shown on the official plat of survey accepted January 10, 2013.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner description and are referenced by surveyor's last name, official title or Professional Land Surveyor (PLS) No., and year.

Date	Name and Registration Number	File Number
1961	Wilford N. Haines, PLS No. 239	CS 51/222, M21-76
1961	Wilford N. Haines, PLS No. 239	M20-38
1962	Milo E. Godfrey, Deputy County Surveyor	CS 49/89
1966	Douglas County Surveyor's Office	CS 54/22
1966	Leon V. Olson, PLS No. 423	CS 54/37b
1968	Douglas County Surveyor's Office	CS 54/22
1983	Daniel W. Baker, PLS No. 1978	M95-44
1985	Leslie D. Roberts, PLS No. 1039	CS 63/18, M99-7
1999	Leslie D. Roberts, PLS No. 1039	M131-45
2012	David A. Edwards, PLS No. 2339	M164-39
2013	Ronald L. Rice, PLS No. 54633	CS 65/79-4

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions approved May 8, 2013, for Group No. 2699, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques, carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through GPS and conventional survey techniques. All measurements have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted

T. 20 S., R. 7 W., Willamette Meridian, Oregon

mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the official original survey and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the corner description field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties to temporary GPS control points, utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The 1/4 section corner of sections 16 and 17:

Latitude: 43° 49' 46.91" N. Longitude: 123° 32' 55.82" W.

The corner of sections 17, 18, 19, and 20:

Latitude: 43° 49' 20.53" N. Longitude: 123° 34' 08.08" W.

The corner of sections 19, 20, 29, and 30:

Latitude: 43° 48' 30.07" N. Longitude: 123° 34' 08.25" W.

The corner of sections 28, 29, 32, and 33:

Latitude: 43° 47' 37.68" N. Longitude: 123° 32' 57.94" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T20S	R7W
S29	S28

S32	S33
1967	

from which the remaining original bearing tree

A hemlock, 33 ins. diam., bears S. 31° E., 3.3 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

and the remains of bearing trees mkd. by Haines, PLS No. 239, in 1961

- A decayed cedar stump, with a 16 in. diam. hemlock growing inside, bears S. 46° W., 27.7 ft. dist., with no marks visible.
- A fir, 64 ins. diam., bears N. 35° W., 52.1 ft. dist., with scribe marks T20S R7W S29 BT visible on bark and a healed blaze. (Record, 50.0 ft.)

and remains of a bearing tree mkd. by Godfrey, Deputy County Surveyor, in 1962

- A cedar stump, 50 ins. diam., bears S. 52° W., 40.3 ft. dist., with scribe marks 7W S3 visible on an open blaze.

and the remains of a bearing tree mkd. by Roseberry and Glenn in 1966-67

- A roothole bears N. 59° E., 110.2 ft. dist., with fallen fir snag, 45 ins. diam., lying downhill, with no marks visible.

and remains of a bearing tree mkd. by Rogers and Bishop in 1983-84

- A decayed hemlock stump, size indeterminate, bears S. 26° W., 46.2 ft. dist., with a decayed blaze and no marks visible.

and bearing trees mkd. by Skeesick in 2012

- A fir, 16 ins. diam., bears N. 49 3/4° E., 39.3 ft. dist., with illegible scribe marks visible on an open blaze.
- A fir, 9 ins. diam., bears S. 55° W., 46.0 ft. dist., with scribe marks T 20S R7W S32 BT visible on an open blaze.

Alongside the cor. is a T-shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with faintly mkd. brass disk on top

Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T20S R7W
1/4
S29 | S28
2013

from which


- A fir, 9 ins. diam., bears N. 75 1/4° E., 10.3 ft. dist., mkd. 1/4 S28 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

A fir, 13 ins. diam., bears S. $21\ 3/4^\circ$ W., 11.2 ft. dist., mkd. $1/4$ S29 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

The cor. of secs. 20, 21, 28, and 29, perpetuated by Haines, PLS No. 239, in 1961, further perpetuated by the Douglas County Surveyor's Office in 1966 and 1968 and by Edwards, PLS No. 2339, in 2012, monumented with an iron post, $1\ 1/4$ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.



from which the remains of an original bearing tree

A trace of a decayed stump, bears N. 69° W., 52.1 ft. dist.

and the remains of a bearing tree mkd. by Haines

A cedar snag, 24 ins. diam., bears N. $17\ 1/4^\circ$ W., 61.0 ft. dist., with a burnt blaze.

and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1966

A decayed hemlock stump, size indeterminate, bears N. $80\ 1/4^\circ$ W., 67.0 ft. dist., with a steel reinforcing rod set alongside and no marks visible.

and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1968

A decayed stump, 63 ins. diam., bears S. $85\ 1/4^\circ$ E., 120.1 ft. dist., with a steel reinforcing rod set in the center and no marks visible.

and bearing trees mkd. by Edwards

A fir, 15 ins. diam., bears S. 48° E., 5.2 ft. dist., with scribe marks T20S R7W S28 BT visible on an open blaze.

A fir, 12 ins. diam., bears S. 39° W., 11.2 ft. dist., with scribe marks T20S R7W S29 BT visible on an open blaze.

and new bearing trees

A fir, 9 ins. diam., bears N. 31° E., 16.3 ft. dist., mkd. T20S R7W S21 BT.

A fir, 13 ins. diam., bears N. 68° W., 8.7 ft. dist., mkd. T20S R7W S20 BT.

A search was made for the original line tree bet. secs. 28 and 29 and it was not recovered.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

Alongside the cor. is a T-shaped iron rod, 3/4 in. diam., firmly set, projecting 14 ins. above ground, with faintly mkd. brass disk on top

The S 1/16 sec. cor. of secs. 20 and 21, established by Roberts, PLS No. 1039, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, buried 10 ins. below ground, with aluminum cap mkd.

T20S R7W
S 1/16
S20 + S21
1985
PLS 1039

from which a reference set by person(s) unknown.

- A steel reinforcing rod, 5/8 in. diam. located in the center of a decayed fir stump, 40 ins. diam., bears S. 62 1/2° W., 24.0 ft. dist.

(Note: Roberts' plat, M99-7, indicates a 38 in. diam. stump at S. 65° W., 24.0 ft. to 5/8 in. pin as an accessory to the SE 1/16 sec. cor. of sec. 20, not the S 1/16 sec. cor. of secs. 20 and 21.)

and new bearing trees

- A fir, 11 ins. diam., bears S. 45° E., 23.7 ft. dist., mkd. S 1/16 S21 BT.

- A fir, 13 ins. diam., bears N. 83 1/2° W., 16.2 ft. dist., mkd. S 1/16 S20 BT.

From this cor., a point established as the S 1/16 sec. cor. of secs 20 and 21 by Olson, PLS No. 423, in 1966, bears S. 13° 42' W., 1.76 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above ground, and is not utilized in the course of this survey.

The 1/4 sec. cor. of secs. 20 and 21, perpetuated by the Douglas County Surveyor's Office in 1966 and 1968, monumented with an iron post, 1 1/4 ins. diam., firmly set, buried 4 ins. below ground, with brass cap mkd.

T20S
1/4
S20 | S21
R7W
1966

from which the remains of an original bearing tree

- A trace of root fragments bears West, 38.3 ft. dist.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1968

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

A fir stump, 60 ins. diam., bears N. 80 1/4° E., 25.2 ft. dist., with a steel reinforcing rod set in the center, with illegible scribe marks visible.

A fir stump, size indeterminate, bears N. 76 3/4° W., 56.6 ft. dist., with a steel reinforcing rod set in the center, with no marks visible.

and new bearing trees

A fir, 9 ins. diam., bears S. 82 1/4° E., 24.7 ft. dist., mkd. 1/4 S21 BT.

A fir, 10 ins. diam., bears N. 8 1/4° W., 15.8 ft. dist., mkd. 1/4 S20 BT.

The cor. of secs. 16, 17, 20, and 21, perpetuated by Baker, PLS No. 1978, in 1983, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T20S
S17 | S16

S20 | S21
R7W
1966

from which the remains of an original bearing tree

A fir snag, 36 ins. diam., bears N. 12° E., 27.7 ft. dist., with no marks visible. (Record, N. 10° E., 26.4 ft.)

and the remains of a bearing tree mkd. by Baker

A fir stump, 36 ins. diam., bears S. 34 1/2° E., 38.3 ft. dist., with scribe marks T20S R7W visible in the wood.

and new bearing trees

A fir, 9 ins. diam., bears N. 20 1/2° E., 37.4 ft. dist., mkd. T20S R7W S16 BT.

A fir, 10 ins. diam., bears S. 57 1/4° E., 6.9 ft. dist., mkd. T20S R7W S21 BT.

A fir, 14 ins. diam., bears S. 7 3/4° W., 21.4 ft. dist., mkd. T20S R7W S20 BT.

A fir, 9 ins. diam., bears N. 16 1/4° W., 20.4 ft. dist., mkd. T20S R7W S17 BT.

A search was made for the original line tree bet. secs. 20 and 21 and it was not recovered.

The 1/4 sec. cor. of secs. 16 and 17, monumented with the original sandstone, firmly set, showing 11 x 4 x 9 ins. above ground, mkd. 1/4 on the W. face, perpetuated by the Douglas County Surveyor's Office in 1966 with an iron post, 1 1/4 ins. diam., firmly set along the E. face of the stone, projecting 7 ins. above the stone, with brass cap mkd. T20S 1/4 S17 S16 R7W 1966, from which the remains of the original bearing trees

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

A burnt fir stump, 26 ins. diam., bears N. 61° E., 9.2 ft. dist., with no marks visible.

A burnt fir snag, 21 ins. diam., bears S. 80° W., 4.6 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office

A burnt fir snag, 50 ins. diam., bears N. 37 1/2° E., 29.0 ft. dist., with scribe marks 1/4 S16 CS BT visible on an open blaze.

A burnt fir snag, 42 ins. diam., bears S. 29° W., 25.7 ft. dist., with no marks visible.

and new bearing trees

A fir, 6 ins. diam., bears N. 40 1/2° E., 6.1 ft. dist., mkd. 1/4 S16 BT.

A fir, 8 ins. diam., bears S. 17 1/2° E., 6.0 ft. dist., mkd. 1/4 S16 BT.

A search was made for the original line tree bet. secs. 16 and 17 and it was not recovered.

The E 1/16 sec. cor. of secs. 20 and 29, established by Roberts, PLS No. 1039, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd.

T20S R7W
S20
E 1/16 + COR
S29
1985
PLS 1039

from which the remains of bearing trees mkd. by Roberts

A decayed fir stump, 40 ins. diam., bears N. 24 1/2° E., 41.8 ft. dist., with scribe marks E 1/16 S20 BT visible on a partially healed blaze.

A hemlock, 20 ins. diam., bears S. 12° W., 39.7 ft. dist., with a healed blaze.

and a new bearing tree

An alder, 14 ins. diam., bears N. 52 1/2° E., 19.2 ft. dist., mkd. E 1/16 S20 BT on the bark.

From the corner

S. 22 ft., a creek, 4 ft. wide, course S. 85° E.

The 1/4 sec. cor. of secs. 20 and 29, reestablished by proportionate measurement by Haines, PLS No. 239, in 1961, and perpetuated by Roberts, PLS No. 1039, in 1985; there is no remaining evidence of the original cor. and this position is accepted as a careful and faithful reestablishment of the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, flush with the ground with aluminum cap mkd.

23144

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

T20S R7W
S20
1/4 +
S29
1985
PLS 1039

from which a bearing tree mkd. by Haines

A fir, 44 ins. diam., bears S. $33\ 3/4^\circ$ W., 33.1 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by Roberts

A maple snag, 10 ins. diam., bears N. $16\ 1/2^\circ$ E., 5.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

and a new bearing tree

A fir, 12 ins. diam., bears N. $22\ 1/2^\circ$ W., 28.9 ft. dist., mkd. 1/4 S20 BT.

Alongside the cor. is a T-shaped iron rod, 3/4 in. diam., firmly set, flush with the ground, with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE

The cor. of secs. 19, 20, 29, and 30, perpetuated by Roberts, PLS No. 1039, in 1999, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 9 ins. above ground with brass cap mkd.

COUNTY SURVEYORS OFFICE

T20S
S19 | S20

S30 | S29
R7W
1966

from which the remains of an original bearing tree

A decayed fir snag, 37 ins. diam., bears N. 45° E., 17.8 ft. dist., with a burnt, open blaze.

and a bearing object mkd. by Haines in 1961

A vertical rock outcropping, 3 ft. high, 10 ft. long, bears S. $68\ 1/4^\circ$ E., 17.9 ft. dist., with chisel marks X S29 visible and a brass cap, 1 in. diam., nailed into the X.

and the remains of bearing trees mkd. by Roseberry and Glenn in 1966-67

A decayed fir stump, 38 ins. diam., bears S. 33° E., 53.7 ft. dist., with scribe marks 7W S 9 BT visible on an open blaze. (Record, S. $35\ 3/4^\circ$ E., 121.8 ft.)

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

A decayed fir stump, 53 ins. diam., bears N. $12\ 1/2^\circ$ W., 60.9 ft. dist., with no marks visible. (Record, N. $13\ 1/2^\circ$ W., 61.7 ft.)

and bearing trees mkd. by Roberts


A fir, 10 ins. diam., bears N. 70° E., 10.8 ft. dist., with a healed blaze.

A fir, 13 ins. diam., bears S. 76° W., 7.3 ft. dist., with a healed blaze.

A fir, 12 ins. diam., bears N. 51° W., 14.6 ft. dist., with a healed blaze.

Alongside the cor. is a T-shaped iron rod, $3/4$ in. diam., firmly set, projecting 7 ins. above ground, with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE

The $1/4$ sec. cor. of secs. 19 and 20, perpetuated by Roberts, PLS No. 1039, in 1985, monumented with an iron post, $2\ 1/2$ ins. diam., firmly set, flush with the ground, with brass cap mkd.



from which the bearing tree mkd. by Roberts


A fir, 17 ins. diam., bears S. $89\ 1/4^\circ$ E., 24.1 ft. dist., with no marks visible.

and a new bearing tree

A fir, 17 ins. diam., bears N. $32\ 1/2^\circ$ W., 14.2 ft. dist., mkd. $1/4$ S19 BT.

(Note: No evidence of the original bearing trees; bearing trees mkd. by Brooks, bearing trees mkd. by the Douglas County Surveyor's Office in 1966, or bearing trees mkd. by Roseberry and Glenn, could be located.)

The cor. of secs. 17, 18, 19, and 20, perpetuated by Rice, PLS No. 54633, in 2013, monumented with an iron post, $1\ 1/4$ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.



from which the remains of the original bearing trees

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

A burnt fir stump, 42 ins. diam., bears S. 52° E., 63.2 ft. dist., with scribe marks S20 CS visible on an open blaze. (Record, 53.4 ft.)

A burnt fir stump, 44 ins. diam., bears S. 14° W., 23.0 ft. dist., with scribe marks T20 R S visible on a partially healed blaze. (Record, 19.8 ft.)

and bearing trees mkd. by Rice

A fir, 20 ins. diam., bears N. 56 1/4° E., 42.5 ft. dist., with scribe marks T20S R7W S18 BT visible on an open blaze.

A fir, 16 ins. diam., bears S. 2° E., 7.4 ft. dist., with scribe marks T20S R7W S20 BT visible on an open blaze.

A fir, 12 ins. diam., bears S. 49° W., 20.0 ft. dist., with scribe marks T20S R7W S19 BT visible on an open blaze.

A fir, 15 ins. diam., bears N. 71° W., 8.6 ft. dist., with scribe marks T20S R7W S18 BT visible on an open blaze.

Alongside the cor. is a T-shaped iron rod, 3/4 in. diam., firmly set, projecting 3 ins. above ground.

The 1/4 sec. cor. of secs. 17 and 20, perpetuated by Haines, PLS No. 239, in 1961, further perpetuated by the Douglas County Surveyor's Office in 1966, monumented with an iron post, 1 1/4 ins. diam., firmly set, flush with the ground, with brass cap mkd.

T20S
S17
1/4 ———
S20
R7W
1966

from which the remains of the original bearing trees

A fir stump, 60 ins. diam., bears S. 34° E., 19.1 ft. dist., with a decayed blaze and no marks visible.

A fir stump, 32 ins. diam., bears N. 44° W., 23.8 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office

A decayed fir stump, 24 ins. diam., bears S. 38 1/4° W., 40.5 ft. dist., with no marks visible.

A fir stump, 36 ins. diam., bears N. 9 1/2° W., 44.2 ft. dist., with no marks visible.

and new bearing trees

A fir, 9 ins. diam., bears S. 22° W., 5.7 ft. dist., mkd. 1/4 S20 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

A fir, 9 ins. diam., bears N. 88° W., 6.5 ft. dist., mkd. 1/4 S17 BT.

Alongside the cor. is a T-shaped iron rod, 3/4 in. diam., firmly set, projecting 3 ins. above ground, with faintly mkd. brass disk on top.

**Subdivision of Section 20,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

The center S 1/16 sec. cor. of sec. 20, established by Roberts, PLS No. 1039, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd.

S20
CS 1/16 + COR
1985
PLS 1039

from which the remains of bearing trees mkd. by Roberts

A decayed stump, size indeterminate, bears S. 71° E., 5.6 ft. dist., with a steel reinforcing rod set in the center and no marks visible.

A decayed stump, size indeterminate, bears N. 30° W., 40.2 ft. dist., with a steel reinforcing rod set in the center and no marks visible.

The center 1/4 sec. cor. of sec. 20, established by Roberts, PLS No. 1039, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd.

T20S R7W
S20
C 1/4 + COR
1985
1039

from which bearing trees mkd. by Roberts

A fir, 17 ins. diam., bears S. 54 1/2° W., 12.9 ft. dist., with a healed blaze.

A fir, 19 ins. diam., bears N. 52° W., 17.1 ft. dist., with a healed blaze.

The center N 1/16 sec. cor. of sec. 20, established by Roberts, PLS No. 1039, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, buried 4 ins. below ground, with aluminum cap mkd.

23148

**Subdivision of Section 20,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

T20S R7W
S20
CN 1/16—+ COR
1985
1039

from which bearing trees mkd. by Roberts

A fir, 17 ins. diam., bears N. 25° E., 10.2 ft. dist., with a healed blaze.

A fir, 17 ins. diam., bears S. 41° W., 12.2 ft. dist., with a healed blaze.

From this cor., a point established as the center N 1/16 sec. cor. of sec. 20 by Olson, PLS No. 423, in 1966, bears S. 22° 00' W., 3.11 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, and is not utilized in the course of this survey.

The center E 1/16 sec. cor. of sec. 20, established by Roberts, PLS No. 1039, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with aluminum cap mkd.

T20S R7W
S20
CE 1/16—+ COR
1985
1039

from which the remains of bearing trees mkd. by Roberts

A decayed fir stump, 48 ins. diam., bears S. 83° E., 24.0 ft. dist., with no marks visible.

A decayed fir stump, 42 ins. diam., bears N. 44° W., 33.0 ft. dist., with no marks visible.

and new bearing trees

A fir, 10 ins. diam., bears S. 37° E., 29.7 ft. dist., mkd. CE 1/16 S20 BT.


A fir, 20 ins. diam., bears N. 73 3/4° W., 25.3 ft. dist., mkd. CE 1/16 S20 BT.

From this cor., a point established as the center E 1/16 sec. cor. of sec. 20 by Olson, PLS No. 423, in 1966, bears S. 5° 21' W., 5.61 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, and is not utilized in the course of this survey.

The NE 1/16 sec. cor. of sec. 20, established by Roberts, PLS No. 1039, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd.

23149

**Subdivision of Section 20,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

T20S R7W
S20
NE 1/16  COR
1985
PLS 1039


from which the remains of bearing trees mkd. by Roberts

- A decayed fir stump, 27 ins. diam., bears S. 83° W., 5.0 ft. dist., with a steel reinforcing rod set in the center and no marks visible.
- A decayed fir stump, 28 ins. diam., bears N. 8° W., 13.2 ft. dist., with a steel reinforcing rod set in the center and no marks visible.

and new bearing trees

- A fir, 8 ins. diam., bears S. 57 3/4° E., 5.9 ft. dist., mkd. NE 1/16 S20 BT.
- A fir, 10 ins. diam., bears N. 3 1/2° W., 9.1 ft. dist., mkd. NE 1/16 S20 BT.

The SE 1/16 sec. cor. of sec. 20, established by Roberts, PLS No. 1039, in 1985, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with aluminum cap mkd.

T20S R7W
S20
SE 1/16  COR
1985
PLS 1039

from which

- A fir, 14 ins. diam., bears N. 87 1/4° W., 25.9 ft. dist., mkd. SE 1/16 S20 BT.

From this cor., a point established as the SE 1/16 sec. cor. of sec. 20 by Olson, PLS No. 423, in 1966, bears S. 8° 42' E., 3.22 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, and is not utilized in the course of this survey.
