

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
A PORTION OF THE NORTH BOUNDARY  
AND SUBDIVISIONAL LINES,  
AND  
THE SUBDIVISION OF SECTION 15,  
**TOWNSHIP 29 SOUTH, RANGE 4 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

---

**EXECUTED BY**

***George M. Winter, Cadastral Surveyor***

Under Special Instructions approved April 24, 2014,  
which provided for the surveys included under Group No. 2747,  
and Assignment Instructions dated April 24, 2014.

***Survey commenced May 12, 2014***

***Survey completed July 31, 2014***

**T. 29 S., R. 4 W., Willamette Meridian, Oregon**

The following field notes are those of the dependent resurvey of a portion of the north boundary and subdivisional lines, and the subdivision of section 15, Township 29 South, Range 4 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1855, Nathaniel Ford, U.S. Deputy Surveyor, surveyed the north boundary and a portion of the subdivisional lines of T. 29 S., R. 4 W., as shown on the official plat of survey approved March 9, 1855.

In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed the south boundary of T. 28 S., R. 4 W., and surveyed the remainder of the subdivisional lines of T. 29 S., R. 4 W., as shown on the official plat of survey approved August 11, 1881.

In 1958, Irving Zirpel, Jr., and William W. Glenn, Cadastral Surveyors, resurveyed a portion of the subdivisional lines, T. 28 S., R. 4 W., as shown on the official plat of survey accepted August 18, 1959.

In 1967-77, Lynn M. Roseberry and James E. Jelley, Cadastral Surveyors, resurveyed a portion of the east boundary, a portion of the subdivisional lines, a portion of the claim lines, and subdivided sections 9, 21, and 24, as shown on the official plat of survey accepted October 11, 1978.

In 1991-93, Wayne L. Rogers, Dale T. Bedell, and Bryan S. Seibold, Cadastral Surveyors, and Robert H. Browning, Surveying Technician, resurveyed portions of the subdivisional lines as shown on the official plat of survey accepted March 5, 1997.

In 2006, A. Bert Skeesick, Cadastral Surveyor, retraced a portion of the subdivisional lines as shown on the official plat of survey accepted April 6, 2011.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner description and are referenced by surveyor's last name, official title, Professional Land Surveyor (PLS), or Professional Engineer (PE) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1922	G.G. Stewart, Deputy County Surveyor	M 2-4
1945	N.E. Richardson, Deputy County Surveyor	No record source listed
1950	Claude Kerr, PE No. 2125	CS 40/252
1956	James W. Byron, Deputy County Surveyor	CS 47/101
1961	James W. Byron, Deputy County Surveyor	CS 49/67
1963	James W. Byron, Deputy County Surveyor	CS 52/126
1964	John H. Markham, Jr., PE No. 2880	M 28-5
1965	James W. Byron, Deputy County Surveyor	CS 52/126
1968	Donald R. Martin, PE No. 3900	M 39-21
1969	Douglas County Surveyor's Office	CS 49/67
1973	Burton W. Holt, PLS No. 418	M 49-39
1981-82	Bruce A. Shaner, PLS No. 430	RM 3-54

In 1978, Alex Tupy subdivided section 15, T. 29 S., R. 4 W., in an unofficial administrative survey for the Roseburg District Bureau of Land Management (BLM). The record of this survey is located at the Roseburg District BLM office.

**T. 29 S., R. 4 W., Willamette Meridian, Oregon**

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), the special instructions approved April 24, 2014, for Group No. 2747, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques, carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through GPS and conventional survey techniques. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data were thoroughly verified and only the corner description field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties to temporary GPS points, utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The corner of sections 2, 3, 34, and 35, on the N. bdy. of the Tp.:

Latitude: 43° 05' 03.30" N.    Longitude: 123° 08' 55.04" W.

The corner of sections 1, 2, 11, and 12:

Latitude: 43° 04' 04.03" N.    Longitude: 123° 07' 59.05" W.

The corner of sections 9, 10, 15, and 16:

Latitude: 43° 03' 16.23" N.    Longitude: 123° 10' 17.51" W.

---

**Dependent Resurvey of a Portion of the North Boundary,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

---

The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., perpetuated by Shaner, PLS No. 430, in 1981-82, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with ground, with brass cap mkd.

T28S R4W	
S34	S35
S 3	S 2
T29S	
1958	

23195

**Dependent Resurvey of a Portion of the North Boundary,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

from which the remains of an original bearing tree

A fir snag, 14 ins. diam., bears S. 60° W., 27.7 ft. dist., with fragmentary scribe marks visible.

and the remains of bearing trees mkd. by Zirpel, Jr. and Glenn in 1957

A fir, 25 ins. diam., bears N. 30° E., 7.9 ft. dist., with a healed blaze.

A cedar, 34 ins. diam., bears S. 80 1/2° W., 37.3 ft. dist., with a healed blaze. (Record, 36.3 ft.)

A fir stump, 29 ins. diam., bears N. 66 1/2° W., 42.9 ft. dist., with no marks visible.

and a bearing tree mkd. by Shaner

A hemlock, 13 ins. diam., bears S. 26 1/4° E., 52.0 ft. dist., with a healed blaze.  
(County record, cedar)

and a new bearing tree

A fir, 11 ins. diam., bears N. 67 1/2° W., 13.4 ft. dist., mkd. T28S R4W S34 BT.

---

The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., perpetuated by Stewart, Deputy County Surveyor, in 1922, further perpetuated by Byron, Deputy County Surveyor, in 1961, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 2 ins. above ground, from which the remains of an original bearing tree

A fir stump, size indeterminate, bears N. 80° W., 23.1 ft. dist., with no marks visible.

and bearing trees mkd. by Byron

A fir, 20 ins. diam., bears N. 56 1/4° E., 8.5 ft. dist., with a healed blaze.

A fir, 16 ins. diam., bears S. 75° E., 21.4 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron pipe, with brass cap mkd.

T28S R4W  
S34  
1/4 —————  
S 3  
T29S  
2014

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of a Portion of the North Boundary,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

Corner is located under a field fence extending E. and W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

---

The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T29S R4W  
1/4  
S11 | S12  
1963

from which the remaining bearing tree mkd. by Kerr, PE No. 2125, in 1950

A cedar, 25 ins. diam., bears S. 71 1/2° W., 25.7 ft. dist., with a healed blaze.

and a bearing tree mkd. by Byron, Deputy County Surveyor, in 1963

A cedar, 26 ins. diam., bears S. 35 1/4° E., 22.4 ft. dist., with a healed blaze.

---

The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, encircled by the decayed remains of the original madrone corner tree, with brass cap mkd.

T29S R4W  
S 2 | S 1  
-----  
S11 | S12  
1969

from which the remains of the original bearing trees

A cedar, 23 ins. diam., bears S. 38 1/2° E., 21.4 ft. dist., with a healed blaze.

A cedar, 28 ins. diam., bears S. 20° W., 16.3 ft. dist., with a healed blaze. (Record, 18.3 ft.)

and remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1969

A madrone snag, 23 ins. diam., bears N. 14 1/2° E., 23.6 ft. dist., with fragmentary scribe marks visible.

and remains of a bearing tree mkd. by Skeesick in 2006

A sawed fir stump, 13 ins. diam., bears N. 55 1/4° W., 21.5 ft. dist., with a healed blaze.


**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

and new bearing trees

A fir, 13 ins. diam., bears N.  $10\ 1/4^\circ$  E., 13.8 ft. dist., mkd. T29S R4W S1 BT

A cedar, 5 ins. diam., bears N.  $38^\circ$  W., 5.4 ft. dist., mkd. X BT.

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.



from which a bearing tree mkd. by Richardson, Deputy County Surveyor, in 1945

A madrone, 28 ins. diam., bears S.  $39^\circ$  E., 26.4 ft. dist., with a healed blaze.

and a bearing tree mkd. by Byron, Deputy County Surveyor, in 1956

A fir, 33 ins. diam., bears N.  $17\ 1/4^\circ$  W., 91.1 ft. dist., with a healed blaze.

and a new bearing tree


A fir, 5 ins. diam., bears S.  $57\ 1/2^\circ$  W., 9.7 ft. dist., mkd. X BT.

From the corner

E., 2 ft. dist., to the cor. of fences extending N., E., and S.

The S 1/16 sec. cor. of secs. 14 and 15, established by person(s) unknown, and is accepted as the cor., monumented with an iron pipe, 2 ins. diam., firmly set, buried 1 in. below ground (alongside the iron pipe is an iron pipe, 7/8 in. diam., firmly set, buried 1 in. below ground).

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the larger iron pipe, with brass cap mkd.



from which

A fir, 13 ins. diam., bears N.  $39^\circ$  E., 26.4 ft. dist., mkd. S 1/16 S14 BT

A fir, 19 ins. diam., bears S.  $70^\circ$  E., 6.9 ft. dist., mkd. S 1/16 S14 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

From the corner

W., 3.5 ft. dist., to the cor. of fences extending N. and W.

E., 12 ft. dist., to the cor. of fences extending S. and W.

The 1/4 sec. cor. of secs. 14 and 15, perpetuated by Byron, Deputy County Surveyor, in 1963, from original evidence no longer in existence, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T29S R4W	
1/4	
S15	S14
1963	

from which new bearing trees

A fir, 5 ins. diam., bears S. 46 1/4° W., 7.9 ft. dist., mkd. X BT.

A fir, 6 ins. diam., bears N. 76 1/2° W., 5.7 ft. dist., mkd. X BT.

Search was made for the bearing trees established by Byron and none were recovered.

Corner is located on the W. side of an 8 ft. high field fence extending N. and S.

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.

T29S	R4W
S10	S11
S15	S14
1963	

from which the remaining bearing tree mkd. by Byron, Deputy County Surveyor, in 1963

A cedar, 24 ins. diam., bears N. 74° E., 41.6 ft. dist., with a healed blaze.

and a bearing tree mkd. by Rogers, et al., in 1991-93

A fir, 11 ins. diam., bears S. 59 1/2° E., 7.3 ft. dist., with a healed blaze.

and new bearing trees

A fir, 5 ins. diam., bears S. 76 3/4° W., 81.7 ft. dist., mkd. X BT.

A fir, 5 ins. diam., bears N. 64° W., 42.4 ft. dist., mkd. X BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

Corner is located on the N. side of a wood fencepost, with wire fence extending S.

---

The 1/4 sec. cor. of secs. 2 and 3, perpetuated by Byron, Deputy County Surveyor, in 1963 and 1965, further perpetuated by Shaner, PLS No. 430, in 1981-82, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

T29S R4W  
1/4  
S 3 | S 2  
1965

from which the remaining original bearing tree

A fir, 31 ins. diam., bears N. 55° E., 13.2 ft. dist., with a healed blaze. (Record, 11.2 ft. dist.)

and a bearing tree mkd. by Shaner

A fir, 27 ins. diam., bears S. 57 1/2° W., 68.0 ft. dist., with a healed blaze.

From the corner

W., 15 ft. dist., to a skid road, bears N. and S.

---

The N 1/16 sec. cor. of secs. 2 and 3, established by Shaner, PLS No. 430, in 1981-82, and is accepted as the cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

T29S R4W  
N 1/16  
S 3 | S 2  
PLS 430 1981

from which the remains of a bearing tree mkd. by Shaner

A fir stump, 29 ins. diam., bears N. 88° E., 25.7 ft. dist., with no marks visible.

and new bearing trees

A fir, 19 ins. diam., bears S. 37 1/4° E., 23.5 ft. dist., mkd. N 1/16 S2 BT. (Mag-Nail left side center)

A fir, 18 ins. diam., bears N. 45 1/4° W., 2.3 ft. dist., mkd. N 1/16 S3 BT. (Mag-Nail left side center)

---

23200

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with ground, with brass cap mkd.

T29S R4W  
S15  
1/4 —————  
S22  
1969

from which bearing trees mkd. by Roseberry and Jelley in 1967-77

A fir, 34 ins. diam., bears S. 39 1/4° W., 2.6 ft. dist., with a healed blaze.

A fir, 20 ins. diam., bears N. 69 1/4° W., 44.6 ft. dist., with a healed blaze.

Corner is located on the SE. side of a wood fencepost with wire fences extending N. and W.

From this cor., a point established by person(s) unknown bears S. 84° 30' W., 68.0 ft. dist., monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above ground, and is not utilized in the course of this survey.

---

The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T29S R4W  
1/4  
|  
S16 | S15  
1969

from which bearing trees mkd. by Roseberry and Jelley in 1967-77

A fir, 27 ins. diam., bears N. 62° E., 66.7 ft. dist., with a healed blaze.

A cedar, 31 ins. diam., bears S. 20° W., 100.9 ft. dist., with a healed blaze. (Record, 75.2 ft. dist.)

Corner is located under a wire fence extending N. and S.


From this cor., a point established as the 1/4 sec. cor. of secs. 15 and 16 by Markham, Jr., PE No. 2880, in 1964, bears S. 80° 49' E., 52.5 ft. dist., monumented with a truck axle, 1 in. diam., projecting 2 ins. above ground, bent to the south, and is not accepted as the cor. and not utilized in the course of this survey.

---

The N 1/16 sec. cor. of secs. 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

23201

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 4 W., Willamette Meridian, Oregon



from which new bearing trees

A fir, 25 ins. diam., bears N. 87° E., 37.2 ft. dist., mkd. N 1/16 S15 BT.

A fir, 18 ins. diam., bears S. 70 3/4° W., 25.9 ft. dist., mkd. N 1/16 S16 BT.


Search was made for the bearing trees mkd. by Roseberry and Jelley in 1967-77 and none were recovered.

From the corner

N., 99 ft. dist., to a gravel road, 12 ft. wide, bears N. 68° E. and S. 70° W.

---

The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.



from which bearing trees mkd. by Roseberry and Jelley in 1967-77

A fir stump, 22 ins. diam., bears N. 39° E., 17.8 ft. dist., with a healed blaze.

A chinquapin, 8 ins. diam., bears S. 69 1/2° E., 19.5 ft. dist., with a healed blaze.

A fir, 32 ins. diam., bears S. 82° W., 35.0 ft. dist., with a healed blaze.

A madrone, 65 ins. diam., bears N. 22° W., 29.0 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 4 ins. diam., bears N. 10 3/4° E., 5.2 ft. dist., mkd. X BT.

From this cor., a point established as the cor. of secs. 9, 10, 15, and 16, by Markham, Jr., PE No. 2880, in 1964, bears S. 83° 52' W., 34.6 ft. dist., monumented with an iron pipe, 1 in. diam., grown into the N. side of a fir tree, and is not accepted as the cor. and not utilized in the course of this survey.

---

23202

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

Point for the E 1/16 sec. cor. of secs 10 and 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

S10  
E 1/16 ———  
S15  
2014

from which

A fir, 3 ins. diam., bears N. 61 3/4° E., 11.5 ft. dist., mkd. X BT.

A madrone, 26 ins. diam., bears S. 50 3/4° E., 20.7 ft. dist., mkd. E 1/16 S15 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

T29S R4W  
S10  
1/4 ———  
S15  
1963

from which the remains of a bearing tree mkd. by Byron, Deputy County Surveyor, in 1963

A fir snag, 22 ins. diam., bears S. 49 1/4° W., 48.2 ft. dist., with no marks visible.

and new bearing trees

A fir, 5 ins. diam., bears S. 62 1/2° W., 30.7 ft. dist., mkd. X BT.

A fir, 8 ins. diam., bears N. 10 1/2° W., 37.9 ft. dist., mkd. T29S R4W S10 BT.

---

The W 1/16 sec. cor. of secs. 10 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

S10  
W 1/16 ———  
S15  
1969

from which bearing trees mkd. by Roseberry and Jelley in 1967-77

A cedar stump, 26 ins. diam., bears N. 10° E., 14.2 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

A fir stump, 31 ins. diam., bears S. 61° W., 51.5 ft. dist., with scribe marks W 1/16 S15 BT visible on an open blaze.

and new accessories

A steel reinforcing rod, 30 ins. long, 5/8 in. diam., driven 23 ins. in the ground for a reference monument, bears S. 54°10'15" E., 15.0 ft. dist., with an aluminum cap mkd. RM S15 15.0 FT TO COR 2014 and an arrow pointing to the cor.

A steel reinforcing rod, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 57°53'45" W., 15.0 ft. dist., with an aluminum cap mkd. RM S15 15.0 FT TO COR 2014 and an arrow pointing to the cor.

**Subdivision of Section 15,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

The center S 1/16 sec. cor. of sec. 15, established by Tupy in a 1978 administrative survey for the Roseburg District BLM and is accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron pipe, with brass cap mkd.

S 1/16  
C  
S | 15  
C  
2014

from which bearing trees mkd. by Tupy

A fir, 15 ins. diam., bears S. 13 1/2° E., 9.6 ft. dist., with a healed double blaze.

A fir, 17 ins. diam., bears S. 63 1/4° W., 7.8 ft. dist., with a healed blaze.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From the corner

SE., 1 ft. dist., to the cor. of fences extending E. and S.

Point for the center 1/4 sec. cor. of sec. 15, at the intersection of the N-S and E-W centerlines of sec. 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

23204

Subdivision of Section 15,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

T29S R4W  
C 1/4 S15  
2014

from which

A fir, 6 ins. diam., bears N.  $83\ 1/4^\circ$  E., 43.8 ft. dist., mkd. C 1/4 S15 BT.

A fir, 18 ins. diam., bears N.  $17\ 3/4^\circ$  W., 5.6 ft. dist., mkd. C 1/4 S15 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

Point for the center N 1/16 sec. cor. of sec 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16  
C  
S | 15  
C  
2014

from which

A fir, 8 ins. diam., bears N.  $81\ 1/4^\circ$  E., 11.0 ft. dist., mkd. CN 1/16 S15 BT.

A fir, 11 ins. diam., bears S.  $56\ 1/2^\circ$  E., 15.2 ft. dist., mkd. CN 1/16 S15 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor., a point established as the center N 1/16 sec. cor. of sec. 15 by Tupy in a 1978 administrative survey for the Roseburg District BLM bears S.  $88^\circ\ 05'$  E., 16.81 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above ground, and is not accepted as the cor. and not utilized in the course of this survey.

---

Point for the NE 1/16 sec. cor. of sec. 15 at the intersection of the N-S and E-W centerlines of the NE 1/4 of sec. 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S15  
2014

from which

A cedar, 12 ins. diam., bears N.  $62\ 1/4^\circ$  E., 4.4 ft. dist., mkd. NE 1/16 S15 BT.

23205

**Subdivision of Section 15,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

A fir, 13 ins. diam., bears S. 21 1/2° W., 26.4 ft. dist., mkd. NE 1/16 S15 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From the cor.

N., 89 ft. dist., to a gravel road, 12 ft. wide, bears N. 50° E. and S. 60° W.

W., 222 ft. dist., to a gravel road, 10 ft. wide, bears N. 30° E. and S. 20° W.

---

Point for the NW 1/16 sec. cor. of sec. 15 at the intersection of the N-S and E-W centerlines of the NW 1/4 of sec. 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NW 1/16 S15

2014

from which

A fir, 13 ins. diam., bears S. 21 1/2° E., 11.2 ft. dist., mkd. NW 1/16 S15 BT.

A madrone, 14 ins. diam., bears S. 40 1/2° W., 13.1 ft. dist., mkd. NW 1/16 S15 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---