

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY  
OF A PORTION OF THE SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF SECTION 10,  
**TOWNSHIP 33 SOUTH, RANGE 7 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON

---

**EXECUTED BY**

***Kevin G. Mulder, Cadastral Surveyor***

Under Special Instructions approved February 19, 2014,  
which provided for the surveys included under Group No. 2739,  
and Assignment Instructions dated February 19, 2014.

***Survey commenced April 16, 2014***

***Survey completed May 27, 2014***

**T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of section 10, Township 33 South, Range 7 West, Willamette Meridian, Oregon.

The history of official surveys pertaining to this survey is as follows:

In 1882, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved May 31, 1882.

In 1901, Oscar F. Thiel, U.S. Deputy Surveyor, completed the survey of the subdivisional lines, as shown on the official plat of survey approved July 17, 1902.

In 1975, Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted July 24, 1980.

In 1981, Rollin D. Aanrud and Lynn M. Roseberry, Cadastral Surveyors, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted June 15, 1984.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1973	Max H. Hull, PLS No. 901	M116-1
1985	Lloyd D. Smith, PLS No. 1101	M98-47
2014	Gerald V. Nygren, PLS No. 1035	M167-56

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the Special Instructions approved February 19, 2014, for Group No. 2739, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through GPS and conventional survey techniques. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

**T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET

Only those lines which represent the Bureau of Land Management (BLM) property lines were posted with aluminum angle posts, 5 feet long, 1 inch x 1 inch, blazed, painted, and tagged with BLM boundary signs.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position in NAD 1983 (2011) of the following corners as determined by a tie from a temporary GPS control point, utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The corner of sections 10, 11, 14, and 15:

Latitude: 42° 42' 33.11" N. Longitude: 123° 30' 14.22" W.

The corner of sections 16, 17, 20, and 21:

Latitude: 42° 41' 42.89" N. Longitude: 123° 32' 36.43" W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

---

Restoring the 1882 survey by William H. Byars, the 1901 survey by Oscar F. Thiel, the 1975 resurvey by Lynn M. Roseberry and Rollin D. Aanrud, and the 1981 resurvey by Rollin D. Aanrud and Lynn M. Roseberry

Beginning at the cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 33 S R 7 W  
S 10 | S 11  
-----  
S 15 | S 14  
1968

from which an original bearing tree

A burnt fir snag, 54 ins. diam., bears N. 9° W., 28.4 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1968

A maple, 17 ins. diam., bears N. 67° E., 21.8 ft. dist., with scribe marks CS visible on partially healed upper blaze and S visible on partially healed lower blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A burnt fir, 37 ins. diam., bears S. 55° W., 32.7 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A burnt chinquapin, 14 ins. diam., bears S. 27 1/4° E., 21.5 ft. dist., with scribe marks CS visible on partially healed upper blaze and S14 BT visible on partially healed lower blaze.</p> <p>No suitable trees available in section 10.</p> <p>S. 89° 54' 38" W., bet. secs. 10 and 15.</p>
2639.64	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">             COUNTY SURVEYORS OFFICE              T 33 S R 7 W              DOUG              S 10              1/4 _____              S 15              JOS              1968         </p> <p>from which the remains of an original bearing tree</p> <p>A sawed and burnt fir stump, 55 ins. diam., bears N. 33° W., 15.8 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1968</p> <p>A burnt and broken fir stump, 16 ins. diam., bears S. 58° W., 74.3 ft. dist., no marks visible.</p> <p>and new accessories</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears N. 50° 32' 33" E., 26.60 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S10 26.60 FT 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears S. 43° 41' 23" E., 21.60 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S15 21.60 FT 2014, and an arrow pointing to the cor.</p> <p style="text-align: center;">_____</p> <p>N. 89° 58' 48" W., beginning new measurement.</p>

23247

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

<p>FEET 1298.43</p>	<p>The W 1/16 sec. cor. of secs. 10 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 10 W 1/16 ————— S 15 1981</p> <p>from which the remains of bearing trees mkd. by Aanrud and Roseberry in 1981</p> <p>A fir, 26 ins. diam., bears S. 76° W., 16.5 ft. dist., with a healed blaze.</p> <p>A broken fir snag, 27 ins. diam., bears N. 41° W., 20.8 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 22 ins. diam., bears N. 71 1/4° E., 59.3 ft. dist., mkd. W 1/16 S10 BT.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 7 W S 17   S 16 ————— S 20   S 21 1975</p> <p>from which the remains of an original bearing tree</p> <p>A burnt fir snag, 35 ins. diam., bears S. 44° E., 7.3 ft. dist., with a healed double blaze.</p> <p>and the remains of bearing trees mkd. by Hull, PLS No. 901, in 1973</p> <p>A burnt madrone snag, 21 ins. diam., bears S. 67° E., 28.4 ft. dist., with a healed double blaze.</p> <p>A burnt madrone snag, 15 ins. diam., bears S. 28° W., 45.9 ft. dist., with a healed double blaze.</p> <p>and the remains of a bearing tree mkd. by Roseberry and Aanrud in 1975</p> <p>A burnt sugar pine snag, 15 ins. diam., bears S. 52 1/2° W., 33.0 ft. dist., with a healed blaze.</p> <p>and new accessories</p>
-------------------------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2659.75	<p>An iron rod, 24 ins. long, 5/8 in. diam., set 21 ins. in the ground for a reference monument, bears S. 72° 29' 51" W., 26.40 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM T33S R7W S20 26.40 FT 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 21 ins. in the ground for a reference monument, bears N. 13° 49' 06" W., 37.40 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM T33S R7W S17 37.40 FT 2014, and an arrow pointing to the cor.</p> <p>N. 2° 39' 30" E., bet. secs. 16 and 17.</p> <p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <p align="center">T 33 S R 7 W S 17   S 16 1975</p> <p>Add marks 1/4 and 2014 to the brass cap.</p> <p>from which the remains of a bearing tree mkd. by Roseberry and Aanrud in 1975</p> <p>A burnt fir snag, 15 ins. diam., bears N. 84 3/4° W., 43.6 ft. dist., with a healed blaze. (Record, N. 83° W.)</p> <p>and new accessories</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 24 ins. in the ground for a reference monument, bears N. 40° 38' 57" E., 25.40 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S16 25.40 FT 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 24 ins. in the ground for a reference monument, bears N. 54° 34' 00" W., 34.10 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S17 34.10 FT 2014, and an arrow pointing to the cor.</p> <p>From this cor., a point established by Hull, PLS No. 901, in 1973, bears West, 31.81 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, and was not utilized during the course of this survey. From which the bearing trees mkd. by Hull</p> <p>A burnt madrone snag, 13 ins. diam., bears N. 36° E., 17.5 ft. dist., with no marks visible on burned out double blaze.</p> <p>A burnt madrone snag, 22 ins. diam., bears N. 30° W., 3.3 ft. dist., with healed double blaze.</p> <hr/> <p>N. 2° 41' 29" E., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET 2658.05	<p>The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 33 S R 7 W</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="text-align: center;">S 9</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; height: 5px;"></td> </tr> <tr> <td style="text-align: center;">S 17</td> <td style="text-align: center;">S 16</td> </tr> <tr> <td colspan="2" style="text-align: center;">1975</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Roseberry and Aanrud in 1975</p> <p style="margin-left: 40px;">A burnt fir snag, 31 ins. diam., bears S. 65° E., 57.1 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A sawed and burnt fir stump, 22 ins. diam., bears N. 75 1/2° W., 41.6 ft. dist., with a healed blaze. (Record, N. 73° W.)</p> <p>and new accessories</p> <p style="margin-left: 40px;">An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the center of a sawed and burnt fir stump, 9 ins. diam., 1 ft. high, for a reference monument, bears N. 61° 39' 40" E., 27.50 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM T33S R7W S9 27.50 FT 2014, and an arrow pointing to the cor.</p> <p style="margin-left: 40px;">An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the center of a sawed and burnt fir stump, 11 ins. diam., 1 ft. high, for a reference monument, bears S. 10° 16' 34" E., 14.90 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM T33S R7W S16 14.90 FT 2014, and an arrow pointing to the cor.</p> <p>From this cor., a point established by Hull, PLS No. 901, in 1973, bears N. 87° 52' 56" W., 63.62 ft. dist. (Record, West), monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with a melted plastic cap, and was not utilized during the course of this survey. From which bearing trees mkd. by Hull</p> <p style="margin-left: 40px;">A burnt fir snag, 20 ins. diam., bears N. 71 1/4° E., 24.8 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A burnt madrone snag, 10 ins. diam., bears S. 27° E., 11.6 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A burnt madrone snag, 14 ins. diam., bears S. 19 3/4° W., 38.9 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A burnt live oak snag, 8 ins. diam., bears N. 36 1/4° W., 23.4 ft. dist., with no marks visible on open double blaze.</p> <hr style="width: 60%; margin-left: 40px; margin-top: 20px;"/>	T 33 S R 7 W		S 8	S 9			S 17	S 16	1975	
T 33 S R 7 W											
S 8	S 9										
S 17	S 16										
1975											

23250

Subdivision of Section 10,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

FEET	
1293.19	<p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0° 52' 25" E., on the N. and S. center line of sec. 10.</p> <p>The center S 1/16 sec. cor. of sec. 10, established by Nygren, PLS No. 1035, in 2014, and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with a yellow plastic cap mkd. NYGREN LS1035.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16   S 10 C 2014</p> <p>No suitable trees available and no suitable locations for reference monuments.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>
1294.31	<p>N. 0° 55' 25" E., beginning new measurement.</p> <p>The center 1/4 sec. cor. of sec. 10, established by Smith, PLS No. 1101, in 1985, and is accepted as the cor.; monumented with an Oregon State Department of Forestry aluminum post, 1 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 33 S R 7 W C 1/4 S 10 1985 LS1101</p> <p>from which the remains of bearing trees mkd. by Smith</p> <p>A burnt fir snag, 13 ins. diam., bears S. 15 1/2° E., 8.6 ft. dist., with a healed blaze.</p> <p>A burnt fir snag, 14 ins. diam., bears S. 70 3/4° W., 10.1 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears S. 46° 22' 01" W., 26.00 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM C1/4 S10 26.00 FT 2014, and an arrow pointing to the cor.</p>

23251

**Subdivision of Section 10,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears N. 5° 52' 30" W., 24.30 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM C1/4 S10 24.30 FT 2014, and an arrow pointing to the cor.</p> <hr/> <p>N. 0° 49' 30" E., beginning new measurement.</p> <p>1343.75 The center N 1/16 sec. cor. of sec. 10, established by Smith, PLS No. 1101, in 1985, and is accepted as the cor.; monumented with an Oregon State Department of Forestry aluminum post, 1 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C N 1/16   S 10 C 1985 LS1101</p> <p>from which the remains of bearing trees mkd. by Smith</p> <p>A burnt fir snag, 23 ins. diam., bears N. 65 3/4° E., 23.7 ft. dist., with a healed blaze.</p> <p>A burnt fir snag, 37 ins. diam., bears N. 0 1/2° W., 24.9 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears N. 32° 54' 54" E., 19.80 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM CN 1/16 S10 19.80 FT 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 19 ins. in the ground for a reference monument, bears N. 49° 32' 20" W., 14.40 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM CN 1/16 S10 14.40 FT 2014, and an arrow pointing to the cor.</p> <hr/> <p>N. 0° 52' 55" E., beginning new measurement.</p>
1344.95	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 33 S R 7 W S 3 1/4 _____ S 10 1968</p>

23252

**Subdivision of Section 10,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of original bearing trees</p> <p>A burnt sugar pine snag, 41 ins. diam., bears North, 31.7 ft. dist., no marks visible.</p> <p>A burnt and sawed fir stump, 49 ins. diam., bears S. 3° W., 8.6 ft. dist., with a rotted and burnt face, no marks visible.</p> <p>and new accessories</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears S. 51° 55' 07" W., 21.40 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S10 21.40 FT 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears N. 24° 57' 31" W., 21.60 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S3 21.60 FT 2014, and an arrow pointing to the cor.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 7 W 1/4 S 10   S 11 1981</p>
	<p>from which the remains of a bearing tree mkd. by BLM during an administrative survey, in 1978</p> <p>A burnt madrone snag, 14 ins. diam., bears S. 57 3/4° E., 11.7 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Aanrud and Roseberry in 1981</p> <p>A burnt fir snag, 20 ins. diam., bears S. 72 1/2° W., 42.6 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears N. 82° 01' 14" E., 24.00 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S11 24.00 FT 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 21 ins. in the ground for a reference monument, bears S. 24° 27' 20" W., 18.90 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S10 18.90 FT 2014, and an arrow pointing to the cor.</p>

23253

Subdivision of Section 10,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

FEET	
1299.16	<p>S. 88° 48' 11" W., on the E. and W. center line of sec. 10.</p> <p>The center E 1/16 sec. cor. of sec. 10, established by Smith, PLS No. 1101, in 1985, and is accepted as the cor.; monumented with an Oregon State Department of Forestry aluminum post, 1 1/2 ins. diam., firmly set, flush with the ground, with aluminum cap mkd.</p> <p style="text-align: center;">E 1/16 C ————— C S 10 1985 LS1101</p> <p>from which the remains of bearing trees mkd. by Smith</p> <p>A burnt fir snag, 15 ins. diam., bears N. 54 1/4° E., 26.8 ft. dist., with a healed blaze.</p> <p>A burnt and broken madrone stump, size indeterminate, bears S. 51 1/2° E., 10.7 ft. dist., no marks visible.</p> <p>and new accessories</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears N. 44° 18' 46" E., 29.60 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM CE 1/16 S10 29.60 FT 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears S. 54° 47' 19" E., 21.20 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM CE 1/16 S10 21.20 FT 2014, and an arrow pointing to the cor.</p> <hr/>
1298.99	<p>S. 88° 49' 04" W., beginning new measurement.</p> <p>The center 1/4 sec. cor. of sec. 10.</p> <hr/>
1311.08	<p>S. 88° 48' 15" W., beginning new measurement.</p> <p>The center W 1/16 sec. cor. of sec. 10, established by Smith, PLS No. 1101, in 1985, and is accepted as the cor.; monumented with an Oregon State Department of Forestry aluminum post, 1 1/2 ins. diam., firmly set, projecting 3 ins above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W 1/16 C ————— C S 10 1985 LS1101</p>

23254

**Subdivision of Section 10,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of bearing trees mkd. by Smith</p> <p>A burnt sugar pine snag, 19 ins. diam., bears S. 21 1/4° W., 21.9 ft. dist., with a healed blaze.</p> <p>A burnt fir snag, 20 ins. diam., bears N. 10 3/4° W., 16.2 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears S. 43° 18' 31" W., 21.80 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM CW 1/16 S10 21.80 FT 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears N. 33° 13' 42" W., 21.80 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM CW 1/16 S10 21.80 FT 2014, and an arrow pointing to the cor.</p> <hr/> <p>S. 88° 46' 11" W., beginning new measurement.</p>
1309.79	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 7 W 1/4 S 9   S 10 1981</p> <p>from which the remains of original bearing trees</p> <p>A burnt and rotted fir stump, 33 ins. diam., bears N. 35° E., 13.2 ft. dist., no marks visible.</p> <p>A burnt madrone snag, 19 ins. diam., bears N. 30° W., 85.8 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Aanrud and Roseberry in 1981</p> <p>A fir, 19 ins. diam., bears N. 47 1/2° W., 36.0 ft. dist., with a healed blaze.</p> <p>and a new accessory</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., set 22 ins. in the ground for a reference monument, bears N. 49° 41' 44" E., 22.40 ft. dist., with aluminum cap, 2 ins. diam., mkd. RM 1/4 S10 22.40 FT 2014, and an arrow pointing to the cor.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 10 and 15.</p>

23255

**Subdivision of Section 10,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1279.97	<p>N. 0° 37' 41" E., on the N. and S. center line of the SW 1/4 of sec. 10.</p> <p>A point established by Nygren, PLS No. 1035, in 2014 and is accepted as an Angle Point, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with yellow plastic cap mkd. NYGREN LS1035.</p> <p>At the corner point</p> <p>Remove yellow plastic cap and affix an aluminum cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">AP W S   10 W 2014</p> <hr/>
1279.55	<p>N. 0° 37' 41" E., beginning new measurement.</p> <p>The center W 1/16 sec. cor. of sec. 10.</p> <hr/>