

FILED ORIGINAL

Date: 3/21/2016 By: JC
This survey consists of:
Map: PLAT 122-10 2016-1,4-8
Narrative NOTES VOL 58
Corner Rpt. ASS 2319-2330
ALUMINUM PLAT
CLATSOP COUNTY
DOUGLAS COUNTY
SURVEYOR

TOWNSHIP 22 SOUTH, RANGE 10 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 2

DEPENDENT RESURVEY

OFFICIALLY FILED: 11/3/2016

(A) The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above a mound of stone, 4 ft. base, 1 ft. high, with a brass cap mkd.

S 25
1/4 S 36
T 22 S R 10 W
1970

from which the remains of the original bearing trees

A decayed fir stump, 56 ins. diam., bears N. 76° E., 17.8 ft. dist., no marks visible.

A decayed fir stump, 39 ins. diam., bears S. 66 1/2° E., 37.0 ft. dist., no marks visible.

and new accessories

A fir, 13 ins. diam., bears N. 53° E., 4.0 ft. dist., mkd. 1/4 S25 BT.

A sandstone boulder, 7 x 5 x 5 ft., bears S. 41 1/2° W., 23.8 ft. dist., to a Mag Nail pounded flush with the surface in the center of a chiseled X and BO above.

The bearing object mkd. by Jelley, in 1970, was recovered with no marks visible.

Drive an aluminum angle iron alongside the cor.

(B) The W 1/16 sec. cor. of sec. 25 only, on the N. by of sec. 36, monumented with a brass tablet, 3 1/4 ins. diam., firmly set in a rock face, with top mkd.

W 1/16 S 25
1970

from which the bearing trees mkd. by Jelley in 1970

A fir, 23 ins. diam., bears N. 7° E., 28.7 ft. dist., with axe marks — and a healed blaze at breast height.

A fir, 14 ins. diam., bears N. 45 3/4° E., 18.2 ft. dist., with a healed blaze.

An iron rod, 1/2 in. diam., 30 ins. long, with International Paper property sign, was found lying loose alongside the cor. Drive an aluminum angle iron 5 ft. E. of the cor.

(C) The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 1/2 ins. diam., cor. tree, a decayed fir stump, 32 ins. diam., no marks visible, from which the remains of a bearing tree mkd. by Todd in 1894

A decayed fir stump, 23 ins. diam., bears S. 57 3/4° W., 54.1 ft. dist., no marks visible. (Record, S. 61° W.)

and the reference monuments mkd. by Jelley in 1970

An iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, bears N. 30° 09' 30" E., 9.0 ft. dist., with a brass cap mkd. T22S R10W S25 RM 1970 and an arrow pointing to the cor. (Record, N. 26 1/2° E.) A steel fence post is alongside.

An iron post, 2 1/2 ins. diam., firmly set, with top flush with the ground, bears N. 59° 55' 37" W., 10.89 ft. dist., with a brass cap mkd. T22S R10W S26 RM 1970 and an arrow pointing to the cor. (Record, N. 57 1/4° W.)

At the corner point

Saw the cor. tree stump down to 6 ins. above ground and drive an iron rod, 31 ins. long, 5/8 in. diam., 30 ins. in the center of the stump, with an aluminum cap mkd.

T 22 S R 10 W
S 26 S 25
S 35 S 36
2014

from which new bearing trees

A fir, 14 ins. diam., bears S. 20 3/4° E., 99.8 dist., mkd. T22S R10W S36 BT.

An alder, 14 ins. diam., bears S. 44° W., 48.0 dist., mkd. T22S 10W S35 BT on bark.

The bearing objects mkd. by Jelley were recovered with no marks visible.

Drive an aluminum angle iron into the stump alongside the cor.

(D) The S 1/16 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.

S 1/16
S 26 S 25
T 22 S R 10 W
1970

from which a bearing tree mkd. by Jelley in 1970

A fir, 21 ins. diam., bears N. 83° W., 42.2 ft. dist., with a healed blaze at waist height. Tree is located behind a double fir, 16 ins. diam., 14 ft. dist. from cor.

and a new bearing tree

A fir, 16 ins. diam., bears S. 47 1/2° E., 12.0 ft. dist., mkd. S1/16 S25 BT.

Drive an aluminum angle iron alongside the cor.

(E) The 1/4 sec. cor. of secs. 25 and 26, monumented with a bearing tree, 3 1/4 ins. diam., firmly set in a nearly vertical rock face, with top mkd.

1/4
S 26 S 25
T 22 S R 10 W
1970

from which the remains of the bearing trees mkd. by Jelley in 1970

A decayed fir stump, size indeterminate, bears S. 33 1/4° E., 12.3 ft. dist., no marks visible. (Record, S. 40° E., 11.2 ft. dist.)

A yew, 9 ins. diam., bears S. 64 1/2° W., 11.2 ft. dist., with scribe marks 1/4 and other illegible scribe marks visible on partially healed blaze. (Record, S. 71° W.) and a new bearing tree

A pistol-butt hemlock, 11 ins. diam., bears S. 46 1/2° E., 26.5 ft. dist., mkd. 1/4 S25 BT.

Drive an aluminum angle iron 15 ft. S. of the cor.

(F) The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.

S 26
S 35
T 22 S R 10 W
1970

from which the remains of an original bearing tree

A decayed cedar snag, 75 ins. diam., bears S. 85° E., 52.8 ft. dist., with no marks visible on open blaze.

and a bearing tree mkd. by Jelley in 1970

A fir, 34 ins. diam., bears N. 14° E., 85.8 ft. dist., with a healed blaze.

and a new bearing tree

An alder, 13 ins. diam., bears S. 78 1/4° E., 41.8 ft. dist., mkd. 1/4 S35 BT on bark.

Drive an aluminum angle iron alongside the cor., which is located 20 ft. S. of a creek, 1 ft. wide, course W.

(G) The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

T 22 S R 10 W
S 27 S 26
S 34 S 35
1970

from which the remains of the original bearing trees

A fir, 50 ins. diam., bears S. 70° E., 5.3 ft. dist., with no marks visible on partially healed blaze at breast height.

A fir, 51 ins. diam., bears S. 8° W., 23.1 ft. dist., with a healed blaze at breast height.

A fir snag, 51 ins. diam., bears N. 8° W., 44.9 ft. dist., with a healed blaze at breast height. (Record, N. 14° W.)

and a bearing tree mkd. by person(s) unknown

A fir, 58 ins. diam., bears N. 76° E., 29.7 ft. dist., with a healed blaze at breast height.

and a bearing tree mkd. by Jelley in 1970

A fir, 19 ins. diam., bears N. 8° E., 35.6 ft. dist., with a small healed blaze at breast height and a healed blaze at bark with illegible scribe marks on the bark along the left side.

There are no new bearing trees available in sec. 27, within limits. Drive an aluminum angle iron alongside the cor.

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

The survey represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

Mary J. M. Hunt
Chief Cadastral Surveyor of Oregon

October 23, 2015

Date