

23326

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF PORTIONS OF
THE NORTH AND WEST BOUNDARIES AND SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 2 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON

EXECUTED BY

Richard J. Dieckmann, Cadastral Surveyor

Under Special Instructions approved August 5, 2014,
which provided for the surveys included under Group No. 2749,
and Assignment Instructions dated August 5, 2014.

Survey commenced August 12, 2014

Survey completed April 20, 2015

T. 25 S., R. 2 W., Willamette Meridian, Oregon

The following field notes are those of the dependent resurvey of portions of the north and west boundaries and subdivisional lines, Township 25 South, Range 2 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1883, John A. McQuinn, U.S. Deputy Surveyor, surveyed a portion of the south boundary and subdivisional lines of T. 24 S., R. 2 W., as shown on the official plat of survey approved April 7, 1884.

In 1883, Laban H. Wheeler, U.S. Deputy Surveyor, surveyed the east boundary and subdivisional lines of T. 25 S., R. 3 W., as shown on the official plat of survey approved May 19, 1884.

In 1900, Hezekiah H. Johnson, U.S. Deputy Surveyor, retraced the west boundary and surveyed the subdivisional lines as shown on the official plat of survey approved May 6, 1901.

In 1943-44, Norman D. Price, Associate Cadastral Engineer, resurveyed the east boundary and subdivisional lines of T. 25 S., R. 3 W., as shown on the official plat of survey approved July 24, 1945, and accepted January 7, 1946.

In 1962, Floyd A. Brooks, Cadastral Surveyor, remonumented certain original corner points as described in the official field notes approved May 13, 1964.

In 1951-63, Levi E. Tallett, Cadastral Engineer, and C. Albert White, Cadastral Surveyor, resurveyed the south boundary and a portion of the subdivisional lines of T. 24 S., R. 2 W., as shown on the official plat of survey accepted November 2, 1964.

In 1951-63, Levi E. Tallett, Cadastral Engineer, and C. Albert White, Cadastral Surveyor, resurveyed portions of the east boundary and subdivisional lines as shown on the official plat of survey accepted November 2, 1964.

In 1972-75, Daniel L. Berry, Harvey E. Wofford, and G. Steven Popken, Cadastral Surveyors, and Glenn S. Baughman, Registered Land Surveyor No. 536, under contract number 52500-CT5-1116, resurveyed a portion of the south boundary and subdivisional lines as shown on the official plat of survey accepted March 7, 1977. (Plat suspended June 16, 1998. Suspension lifted January 9, 2001.)

In 1993, Wayne L. Rogers, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the subdivisional lines and subdivided section 29 as shown on the official plat of survey accepted November 1, 1995.

In 2001-02, A. Bert Skeesick, Cadastral Surveyor, resurveyed portions of the east boundary and subdivisional lines and subdivided sections 11 and 13 as shown on the official plat of survey accepted June 24, 2004.

In 2010-11, A. Bert Skeesick, Cadastral Surveyor, resurveyed portions of the south and west boundaries and subdivisional lines and subdivided section 26 as shown on the official plat of survey accepted December 27, 2011.

T. 25 S., R. 2 W., Willamette Meridian, Oregon

In 2011, Kenneth W. Saveland, Cadastral Surveyor, resurveyed a portion of the subdivisional lines as shown on the official plat of survey accepted September 7, 2012.

The following local surveys, corner renewals, and public land corner reports, listed as CS (County Surveyor) and M (Map) files, filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name and official title, or last name and Professional Land Surveyor (PLS) No., or Company name, and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1948	Ben B. Irving, Douglas County Surveyor	M 12-34, CS 39/169-17
1957	Vernon W. Hosford, PLS No. 253	CS 42/308
1958	James W. Byron, Deputy County Surveyor	CS 49/102
1958	Glen McChesney, Land Agent, Weyerhaeuser	CS 53/112-14
1959	James W. Byron, Deputy County Surveyor	CS 49/102
1959	Glen McChesney, Land Agent, Weyerhaeuser	CS 53/112-9
1960	Vernon W. Hosford, PLS No. 253	M 19-77, CS 51/144
1961	Vernon W. Hosford, PLS No. 253	CS 51/220
1962	Milo E. Godfrey, Douglas County Surveyor	CS 49/102
1966	Douglas County Surveyor's Office	CS 54/7
1966	Douglas County Surveyor's Office	CS 54/27
1967	Douglas County Surveyor's Office	CS 54/27-77
1968	Douglas County Surveyor's Office	CS 54/27-88
1972	Douglas County Surveyor's Office	CS 54/27-90
1977	Douglas County Surveyor's Office	CS 59/38-23
1989	Weyerhaeuser Timber Company	CS 62/63-8
1989	Douglas County Surveyor's Office	CS 62/63-8
1990	Douglas County Surveyor's Office	CS 64/10
1995	Douglas County Surveyor's Office	CS 64/63-2
1995	Douglas County Surveyor's Office	CS 64/58-11
1995	Douglas County Surveyor's Office	CS 64/63-3
2009	Mark F. Smalley, PLS No. 2354	CS 65/66-45
2009	Mark F. Smalley, PLS No. 2354	CS 65/66-46
2009	David A. Edwards, PLS No. 2339	CS 65/66-56
2013	David A. Edwards, PLS No. 2339	M 165-53, CS 65/78-12

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions approved August 5, 2014, for Group No. 2749, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and direct solar observations and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot at an elevation of 2015 International feet above mean sea level.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were

T. 25 S., R. 2 W., Willamette Meridian, Oregon

perpetuated in their original positions. The retracement data were thoroughly verified and only the corner description field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet in a white plastic case deposited at the base of the stainless steel post, unless otherwise noted in the corner description.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties to temporary GPS points, utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The 1/4 section corner of sections 5 and 32 on the north boundary of the township:

Latitude: 43° 25' 55.48" N. Longitude: 122° 57' 37.49" W.

The closing corner of sections 18 and 19, on the west boundary of the township:

Latitude: 43° 23' 15.92" N. Longitude: 122° 59' 21.60" W.

The 1/4 section corner of sections 26 and 27:

Latitude: 43° 21' 57.17" N. Longitude: 122° 54' 51.01" W.

The corner of sections 15, 16, 21, and 22:

Latitude: 43° 23' 17.50" N. Longitude: 122° 56' 01.36" W.

The corner of sections 9, 10, 15, and 16:

Latitude: 43° 24' 09.83" N. Longitude: 122° 56' 01.22" W.

The 1/4 section corner of sections 32 and 33:

Latitude: 43° 21' 03.09" N. Longitude: 122° 57' 10.54" W.

The 1/4 section corner of sections 28 and 33:

Latitude: 43° 21' 29.95" N. Longitude: 122° 56' 35.87" W.

The corner of sections 19, 20, 29, and 30:

Latitude: 43° 22' 23.12" N. Longitude: 122° 58' 22.50" W.

**Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, in a mound of stone, 2 1/2 ft. base, to top, with a brass cap mkd.

S 32
1/4 ———
S 5
1951

from which bearing trees mkd. by Tallett and White in 1951-63

- A maple, 48 ins. diam., bears N. 76° E., 30.4 ft. dist., with a healed blaze.
- A red cedar, 30 ins. diam., bears S. 27° E., 83.2 ft. dist., with a healed blaze.

From this cor., a point established by person(s) unknown, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 3 ins. above the ground, bears S. 22° 20' 45" W., 4.55 ft. dist., and is not utilized in the course of this survey.

The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., perpetuated by Edwards, PLS No. 2339, in 2013, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, in a collar of stone, with a brass cap mkd.

T 24 S R 2 W
S 31 | S 32
———
S 6 | S 5
T 25 S
1951

from which the remains of the original bearing trees

- A decayed fir stump, 48 ins. diam., bears N. 25° E., 33.0 ft. dist., with fragmentary scribe marks visible on a partially healed, decayed blaze.
- A decayed hemlock stump, size indeterminate, bears N. 85° E., 46.2 ft. dist., with no marks visible.
- A fir stump, 52 ins. diam., bears S. 55 3/4° W., 13.2 ft. dist., with no marks visible.

and bearing trees mkd. by Tallett and White in 1951-63

- A hemlock, 18 ins. diam., bears S. 68° E., 60.1 ft. dist., with a healed blaze.
- A hemlock, 27 ins. diam., bears N. 12 1/4° W., 56.1 ft. dist., with a healed blaze.

and bearing trees mkd. by Edwards

- A Douglas fir, 10 ins. diam., bears N. 71° E., 36.3 ft. dist., with scribe marks T24S R2W S32 visible on a partially healed upper blaze and BT visible in lower blaze.

**Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

A Douglas fir, 11 ins. diam., bears S. 22 3/4° W., 31.3 ft. dist., with scribe marks T25S R2W S6 visible on a partially healed upper blaze and BT visible in lower blaze.

From this cor., a point established by person(s) unknown, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 4 ins. above the ground, bears N. 22° 56' 49" W., 4.00 ft. dist., and is not utilized in the course of this survey.

**Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

The closing cor. of secs. 19 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, with a brass cap mkd.

T 25 S	T 25 S
R 3 W	S 19 C
S 25	S 30 C
	R 2 W
	1943

from which a bearing tree mkd. by Johnson in 1900

A red cedar, 33 ins. diam., bears N. 56 1/2° E., 22.4 ft. dist., with a healed blaze.

and a bearing tree mkd. by Price in 1943-44

A Douglas fir, 42 ins. diam., bears S. 37° E., 42.9 ft. dist., with a healed blaze.

The cor. of secs. 24 and 25, T. 25 S., R. 3 W., on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground with a brass cap mkd.

T 25 S	T 25 S
S 24	R 2 W
S 25	S 19
R 3 W	
	1943

from which the remains of the original bearing trees

A red cedar stump, 38 ins. diam., bears S. 44 1/2° W., 19.8 ft. dist., with illegible scribe marks visible on a partially healed, decayed blaze, and a tin cap.

A decayed Douglas fir stump, 57 ins. diam., bears N. 65° W., 23.8 ft. dist., with a healed blaze.

and new bearing trees

**Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

- A red cedar, 11 ins. diam., bears S. 67° E., 3.0 ft. dist., mkd. T25S R2W S19 BT.
- A Douglas fir, 14 ins. diam., bears S. 34 3/4° W., 28.4 ft. dist., mkd. T25S R3W S25 SC BT.

The 1/4 sec. cor. of sec. 19 only, on the W. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1966 and 1995, under CS 64/63-3, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with a brass cap mkd.

| 1/4 S 19
1943

from which the remains of the original bearing trees

- A decayed Douglas fir stump, 36 ins. diam., bears N. 22° E., 36.3 ft. dist., with illegible scribe marks visible on a partially opened, decayed blaze.
- A Douglas fir, 35 ins. diam., bears S. 21° E., 28.4 ft. dist., with a healed blaze.

and remaining bearing tree mkd. by the Douglas County Surveyor's Office in 1966

- A hemlock, 13 ins. diam., bears N. 88 1/2° E., 39.1 ft. dist., with a healed double blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1995

- A hemlock, 14 ins. diam., bears N. 48 1/2° E., 5.0 ft. dist., with a healed blaze.
- A Douglas fir, 6 ins. diam., bears S. 76° E., 18.3 ft. dist., with a healed blaze and a scar at waist height.

Corner is located approximately 1 ft. E. of the edge of a large boulder, 6 ft. x 4 ft. x 4 ft.

The 1/4 sec. cor. of sec. 24 only, T. 25 S., R. 3 W., perpetuated by the Douglas County Surveyor's Office in 1995, under CS 64/63-2, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with a brass cap mkd.

1/4 S 24 |
1943

from which the remains of bearing trees mkd. by Price in 1943-44


- A Douglas fir stump, 54 ins. diam., bears S. 79 1/2° W., 27.1 ft. dist., with no marks visible.
- A decayed Douglas fir stump, 38 ins. diam., 5 ft. high, bears N. 15 1/2° W., 32.3 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office

**Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

- A hemlock, 20 ins. diam., bears S. 77 1/4° W., 12.0 ft. dist., with scribe marks S CS visible on a partially healed blaze at breast height.
- A Douglas fir, 15 ins. diam., bears N. 74° W., 26.1 ft. dist., with a healed blaze.
- A hemlock, 9 ins. diam., bears N. 2 1/4° W., 23.4 ft. dist., with a healed double blaze.

The closing cor. of secs. 18 and 19, on the W. bdy. of the Tp., perpetuated by Godfrey, Douglas County Surveyor, in 1962, further perpetuated by the Douglas County Surveyor's Office in 1966 and 1995, under CS 64/58-11, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, with a brass cap mkd.



from which the remains of an original bearing tree

- A red cedar snag, 11 ins. diam., bears N. 66 1/2° E., 18.5 ft. dist., with scribe marks T25S R2W S18 BT visible on a partially healed blaze. This snag is leaning to the SE.
 - A Douglas fir stump, 54 ins. diam., bears S. 70° E., 35.6 ft. dist., with no marks visible.
- and bearing trees mkd. by the Douglas County Surveyor's Office in 1995
- A hemlock, 10 ins. diam., bears N. 15° E., 12.0 ft. dist., with a healed double blaze.
 - A hemlock, 6 ins. diam., bears N. 59 1/4° E., 4.0 ft. dist., with a healed double blaze.
 - A hemlock, 15 ins. diam., bears S. 69 3/4° E., 14.0 ft. dist., with a healed double blaze.
 - A Douglas fir, 10 ins. diam., bears S. 14° E., 18.3 ft. dist., with a healed double blaze.

The reference monument established by the Douglas County Surveyor's Office in 1966, an iron pipe, 4 ins. diam., 8 ft. long, with weld marks T25S R2W S19 CC BT on the side of the pipe, was recovered lying on the ground, loose and out of position with no remains of the stump in which it was set; this position could not be determined or restored.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with a brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

1/4
S 27 | S 26
T 25 S R 2 W
1962

from which the remaining original bearing tree

- A yew, 12 ins. diam., bears S. 81° E., 21.1 ft. dist., with no marks visible on a partially healed blaze.

and the remains of the bearing tree mkd. by Brooks in 1962

- A Douglas fir stump, 37 ins. diam., bears S. 19 1/2° W., 27.1 ft. dist., with a healed blaze and tin cap.

and the bearing tree mkd. by Skeesick in 2010-11

- A hemlock, 13 ins. diam., bears S. 58 3/4° W., 21.4 ft. dist., with scribe marks 1/4 S27 BT visible on a partially healed blaze.

The original SW. bearing tree was recovered downed and out of position.

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with a brass cap mkd.

COUNTY SURVEYORS
OFFICE
T 25 S
S 22 | S 23
S 27 | S 26
R 2 W
1958

from which the remains of the original bearing trees

- A pine stump, 63 ins. diam., bears N. 39 1/2° E., 41.9 ft. dist., with a healed blaze and tin cap.
- A fir stump, 32 ins. diam., bears S. 23° E., 21.8 ft. dist., with a healed blaze.
- A fir stump, 40 ins. diam., bears N. 42 1/4° W., 37.1 ft. dist., with a healed blaze.

and a bearing tree mkd. by Byron, Deputy County Surveyor, in 1958, reported by Skeesick in 2001-02

- A hemlock, 11 ins. diam., bears S. 83° W., 22.3 ft. dist., with a healed double blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1990, reported by Skeesick

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

- A double trunk schoolmarm hemlock, 17 ins. diam., bears S. 21 1/4° W., 24.4 ft. dist., with a healed double blaze.
- A hemlock, 13 ins. diam., bears N. 40 3/4° W., 8.7 ft. dist., with a healed blaze (Record, 8.1 ft. dist.).

The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with a brass cap mkd.

T 25 S R 2 W
S 21 | S 22

S 28 | S 27
1962

from which the remains of the original bearing trees reported by Skeesick in 2001-02

- A hemlock, 31 ins. diam., bears N. 12 1/2° E., 20.5 ft. dist., with a healed blaze.
- A Douglas fir stump, 37 ins. diam., bears N. 75° W., 33.7 ft. dist., with a healed blaze. (Record, 39.7 ft. dist.)

and remaining bearing tree mkd. by Brooks in 1962, reported by Skeesick

- A chinquapin, 13 ins. diam., bears S. 62° E., 30.4 ft. dist., with a healed blaze.

and bearing trees mkd. by person(s) unknown

- A hemlock, 13 ins. diam., bears S. 69° W., 21.2 ft. dist., with scribe marks T25S R2W S28 BT visible on a partially healed blaze.
- A Douglas fir, 7 ins. diam., bears N. 64° W., 29.1 ft. dist., with a healed blaze.

The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with a brass cap mkd.

S 22
1/4 ———
S 27
T 25 S R 2 W
1962

from which the remaining original bearing tree

- A red cedar, 25 ins. diam., bears S. 24 1/2° E., 13.9 ft. dist., with a healed blaze.

and bearing tree mkd. by McChesney, Land Agent, Weyerhaeuser Timber Co., in 1958

- A red cedar, 23 ins. diam., bears N. 41° W., 21.2 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

and the bearing tree mkd. by Brooks in 1962

- A hemlock, 17 ins. diam., bears N. 58 1/2° E., 25.8 ft. dist., with a healed blaze.
(Record, 27.1 ft. dist.)

The 1/4 sec. cor. of secs. 21 and 22, perpetuated by Roseburg Resources in 1997 as reported by Smalley, PLS No. 2354, in 2009, under CS 65/66-46, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a brass cap mkd.

1/4
S 21 | S 22
T 25 S R 2 W
1962

from which a bearing tree mkd. by Hosford, PLS No. 253, in 1957, reported by Brooks in 1962

- A Douglas fir, 21 ins. diam., bears N. 23° W., 19.9 ft. dist., with a healed blaze.
(Record, 20.8 ft. dist.)

and bearing trees mkd. by Roseburg Resources

- A red cedar, 17 ins. diam., bears N. 59 1/2° E., 28.7 ft. dist., with a healed blaze.
A madrone, 11 ins. diam., bears S. 76 1/2° W., 10.2 ft. dist., with a healed blaze.
A Douglas fir, 24 ins. diam., bears N. 35° W., 34.7 ft. dist., with a healed blaze.

The cor. of secs. 15, 16, 21, and 22, perpetuated by Roseburg Resources in 1997 as reported by Smalley, PLS No. 2354, in 2009, under CS 65/66-45, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the top of a mound of stone, 2 1/2 ft. base, 6 ins. high, with a brass cap mkd.

T 25 S R 2 W
S 16 | S 15

S 21 | S 22
1962

from which bearing trees mkd. by Hosford, PLS No. 253, in 1957, reported by Skeesick in 2001-02

- A hemlock, 21 ins. diam., bears S. 21° W., 87.8 ft. dist., with a healed blaze.
A red cedar, 28 ins. diam., bears N. 43° W., 14.5 ft. dist., with a healed blaze.

and the bearing tree mkd by Brooks in 1962, reported by Skeesick

- A red cedar, 41 ins. diam., bears S. 23 1/2° E., 57.4 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

and a bearing tree mkd. by Roseburg Resources

- A Douglas fir, 18 ins. diam., bears N. 12° E., 12.4 ft. dist., with a healed blaze.

The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with a brass cap mkd.

T 25 S	R 2 W
S 9	S 10
S 16	S 15
1962	

from which the remaining original bearing tree

- A Douglas fir, 62 ins. diam., bears N. 37° E., 13.2 ft. dist., with a healed blaze.

and the remaining bearing tree mkd. by Irving, Douglas County Surveyor, in 1948

- A Douglas fir, 50 ins. diam., bears S. 32 1/2° E., 43.6 ft. dist., with scribe marks T25S R2W S15 CS visible on the bark.

and a bearing tree mkd. by Brooks in 1962

- A Douglas fir, 25 ins. diam., bears S. 36° W., 36.3 ft. dist., with a healed blaze.

and a bearing tree mkd. by Saveland in 2011

- A red cedar, 19 ins. diam., bears N. 40 3/4° W., 50.6 ft. dist., with scribe marks T25S R2W S9 BT visible on a partially healed blaze.

The 1/4 sec. cor. of secs. 9 and 10, perpetuated by the Douglas County Surveyor's Office in 1972, monumented with an iron post 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with a brass cap mkd.

1/4	
S 9	S 10
T 25 S	R 2 W
1962	

from which the bearing tree mkd. by the Douglas County Surveyor's Office

- A cedar, 40 ins. diam., bears N. 1 3/4° E., 20.5 ft. dist., with scribe marks 1/4 S10 visible on a partially healed upper blaze and scribe marks CS BT visible on a partially healed lower blaze.

and a new bearing tree

- A Douglas fir, 8 ins. diam., bears N. 74 3/4° W., 27.4 ft. dist., mkd. 1/4 S9 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

The original stone is set along the S. side of the iron post.

The remains of an original line tree, a fir stump, 84 ins. diam., approximately 4 ft. high, with one notch visible on the S. side, and now functions as an angle point.

At the corner point

Drive an iron rod, 36 ins. long, 5/8 in. diam., 35 ins. into the center of the stump, with an alum. cap mkd.

T 25 S R 2 W
AP
S 9 | S 10
2014

The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, with a brass cap mkd.

T 25 S R 2 W
S 4 | S 3

S 9 | S 10
1951

from which the remains of bearing trees mkd. by Tallett and White in 1951-63

- A decayed hemlock stump, size indeterminate, bears S. 33° W., 43.6 ft. dist., with fragmentary scribe marks visible on decayed remains of a blaze.

and new bearing trees

- A Douglas fir, 28 ins. diam., bears N. 65 3/4° E., 47.7 ft. dist., mkd. T25S R2W S3 BT with Mag-Nail placed on left side center, 5 ft. dist. below the face of the blaze.
- A Douglas fir, 9 ins. diam., bears S. 35 1/2° E., 36.1 ft. dist., mkd. T25S R2W S10 BT.
- A Douglas fir, 13 ins. diam., bears S. 18 3/4° W., 36.9 ft. dist., mkd. T25S R2W S9 BT.
- A Douglas fir, 5 ins. diam., bears N. 40 1/2° W., 23.8 ft. dist., mkd. T25S R2W S4 BT.

The NW. yew bearing tree mkd. by Tallett and White was recovered downed and out of position with no marks visible.

The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with a brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

T 25 S R 2 W
1/4
S 32 | S 33
1972

from which a bearing tree mkd. by Hosford, PLS No. 253, in 1960, reported by Berry, Wofford, Popken, and Baughman in 1972-75

A Douglas fir, 23 ins. diam., bears S. 46° W., 13.2 ft. dist., with a healed blaze.

and a new bearing tree

A maple, 11 ins. diam., bears S. 77 1/2° E., 22.1 ft. dist., mkd. 1/4 S33 BT in the bark.

An iron pipe, 2 ins. diam., firmly set. projecting 12 ins. above the ground, with a wood plug and tack off center in the top is set along the NE. side of the iron post.

The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. diam. base, to top, with a brass cap mkd.

T 25 S R 2 W
S 29 | S 28

S 32 | S 33
1962

from which the remains of an original bearing tree

A Douglas fir, 62 ins. diam., bears S. 29° W., 21.1 ft. dist., with a healed blaze.

and new bearing trees

A yew, 10 ins. diam., bears N. 11° E., 28.0 ft. dist., mkd. T25S R2W S28 BT.

A Douglas fir, 10 ins. diam., bears S. 40 1/2° E., 32.8 ft. dist., mkd. T25S R2W S33 BT.

A red cedar, 17 ins. diam., bears N. 33 1/2° W., 18.3 ft. dist., mkd. T25S R2W S29 BT.

The NE. rock outcrop bearing object, mkd. by Brooks in 1962, was searched for but not recovered.

The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, with a brass cap mkd.

S 28
1/4-----
S 33
T 25 S R 2 W
1962

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

from which the remains of an original bearing tree

- A decayed cedar stump, 42 ins. diam., bears N. 35° W., 52.8 ft. dist., with no marks visible.

and remains of bearing trees mkd. by Brooks in 1962

- A Douglas fir, 42 ins. diam., bears S. 25° E., 5.0 ft. dist., with a healed blaze.
- A fir stump, 34 ins. diam., bears N. 40 1/2° W., 33.0 ft. dist., with no marks visible on an open, decayed blaze.

and a new bearing tree

- A Douglas fir, 5 ins. diam., bears N. 21 3/4° E., 31.2 ft. dist., mkd. X in the bark at breast height and BT in low blaze.

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a mound of stone, 3 ft. diam. base, 1 ft. high, with a brass cap mkd.

T 25 S	R 2 W
S 8	S 9
S 17	S 16
1962	

from which the remaining original bearing tree

- A Douglas fir, 39 ins. diam., bears N. 37° E., 35.0 ft. dist., with a healed blaze.

and a bearing tree mkd. by McChesney, Land Agent, Weyerhaeuser Timber Co., in 1959

- A Douglas fir, 18 ins. diam., bears N. 22 3/4° E., 54.7 ft. dist., with a healed double blaze.

and accessories mkd. by Brooks in 1962

- A Douglas fir, 46 ins. diam., bears S. 14 1/2° E., 27.1 ft. dist., with a healed blaze and a large S scribed in the bark.

An XBO chiseled into the E. face of a rock outcrop bears S. 57 3/4° W., 9.2 ft. dist.

and a bearing tree mkd. by Edwards, PLS No. 2339, in 2009

- A red cedar, 9 ins. diam., bears N. 48° W., 32.0 ft. dist., with scribe marks T25S R2W S8 BT visible on a partially healed blaze.

The 1/4 sec. cor. of secs. 9 and 16, perpetuated by the Douglas County Surveyor's Office in 1967 and 1977, monumented with an iron post, 2 1/2 ins. diam., firmly set, buried 3 ins. below the ground, with a brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

S 9
1/4 ———
S 16
T 25 S R 2 W
RESET 1977
1962

from which the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1977

A Douglas fir stump, 16 ins. diam., bears S. 22° E., 14.6 ft. dist., with a healed blaze.

A Douglas fir, 25 ins. diam., bears N. 55 3/4° W., 44.4 ft. dist., with a healed blaze.

and a new bearing tree

A Douglas fir, 14 ins. diam., bears N. 63° E., 16.4 ft. dist., mkd. 1/4 S9 BT.

The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a brass cap mkd.

1/4
S 8 | S 9
T 25 S R 2 W
1962

from which the remains of a bearing tree mkd. by McChesney, Land Agent, Weyerhaeuser Timber Co., in 1959 and reported by Brooks in 1962 as a new bearing tree

A decayed sugar pine stump, 20 ins. diam., bears N. 44 1/4° W., 16.5 ft. dist., with scribe marks 1/4 S8 BT visible on a decayed blaze. (Record, white pine, N. 49 1/4° W.)

and new bearing trees

A Douglas fir, 12 ins. diam., bears S. 88 1/2° E., 9.1 ft. dist., mkd. 1/4 S9 BT.

A Douglas fir, 8 ins. diam., bears N. 3° W., 4.6 ft. dist., mkd. 1/4 S8 BT.

The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, with a brass cap mkd.

T 25 S R 2 W
S 5 | S 4
———
S 8 | S 9
1951

from which the remaining original bearing trees

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

A red cedar, 51 ins. diam., bears N. 59 1/2° E., 24.4 ft. dist., with a healed blaze.

A maple, 16 ins. diam., bears N. 83 1/2° W., 7.3 ft. dist., with a healed blaze.

and new bearing trees

A Douglas fir, 8 ins. diam., bears S. 69 1/4° E., 15.5 ft. dist., mkd. T25S R2W S9 BT.

A cedar, 21 ins. diam., bears S. 45° W., 28.8 ft. dist., mkd. T25S R2W S8 BT.

The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with a brass cap mkd.

S 4
1/4—
S 9
1951

from which the remains of an original bearing tree

A decayed madrone stump, size indeterminate, bears N. 34° E., 18.5 ft. dist., with no marks visible.

and a bearing tree mkd. by Tallett and White in 1951-63

A sugar pine, 31 ins. diam., bears S. 38° E., 23.1 ft. dist., with a healed blaze.

and a new bearing tree

An incense cedar, 7 ins. diam., bears N. 14 3/4° E., 11.6 ft. dist., mkd. 1/4 S4 BT.

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above the ground, in a collar of stone, with a brass cap mkd.

COUNTY SURVEYORS OFFICE
S 19 | S 20
—+—
S 30 | S 29
T 25 S R 2 W
1959

from which the remains of the original bearing trees

A chinquapin snag, 14 ins. diam., bears S. 69° E., 13.9 ft. dist., with no marks visible on a partially healed, decayed blaze.

A cedar stump, 41 ins. diam., bears S. 24° W., 19.8 ft. dist., with no marks visible on a partially healed, decayed blaze.

and bearing trees mkd. by Byron, Deputy County Surveyor, in 1959

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

- A Douglas fir, 29 ins. diam., bears N. 3° E., 15.8 ft. dist., with a healed blaze.
- A red cedar, 21 ins. diam., bears S. 39° E., 21.1 ft. dist., with a healed blaze.
- A Douglas fir, 36 ins. diam., bears N. 4 1/2° W., 28.4 ft. dist., with a healed blaze.

and bearing tree mkd. by Rogers and Browning in 1993

- A hemlock, 15 ins. diam., bears S. 78° W., 14.5 ft. dist., with a healed blaze.

The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. diam., 18 ins. high, with a brass cap mkd.

S 19
1/4—
S 30
T 25 S R 2 W
1962

from which the remaining original bearing tree

- A red cedar, 41 ins. diam., bears N. 14° W., 17.8 ft. dist., with a healed blaze.

and the remains of the bearing tree mkd. by Brooks in 1962

- A red cedar stump, 17 ins. diam., 5 ft. high, bears S. 44 1/2° E., 19.1 ft. dist., with a healed, decayed blaze.

and a new bearing tree

- A hemlock, 9 ins. diam., bears S. 68 3/4° E., 8.8 ft. dist., mkd. 1/4 S30 BT.

The 1/4 sec. cor. of secs. 19 and 20, perpetuated by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a brass cap mkd.

1/4
S 19 | S 20
T 25 S R 2 W
1962

from which the remaining bearing tree mkd. by Brooks in 1962

- A hemlock, 15 ins. diam., bears N. 33 1/2° E., 48.9 ft. dist., with a healed blaze.
(Record, 47.8 ft. dist.)


and bearing tree mkd. by the Douglas County Surveyor's Office

- A hemlock, 20 ins. diam., bears S. 88 3/4° W., 41.6 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

True point for the cor. of secs. 17, 18, 19, and 20, at record bearing and dist. from the found original witness cor., and is located on a rock bluff where it is impracticable to establish a permanent monument, not monumented.

From the true point, the witness cor. for the cor. of secs. 17, 18, 19, and 20 bears W., 13.20 ft. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone, with a brass cap mkd.




from which the remains of the original bearing trees reported by Brooks in 1962

- A Douglas fir, 36 ins. diam. on uphill side at breast height, bears N. 25° E., 6.6 ft. dist., with a healed blaze.
- A Douglas fir stump, 38 ins. diam., bears S. 45° E., 12.5 ft. dist., with no marks visible. (Record, 13.9 ft. dist.)

and a new bearing tree

- A red cedar, 8 ins. diam., bears S. 54 1/2° E., 10.4 ft. dist., mkd. X in the bark at breast height and BT in low blaze.

The 1/4 sec. cor. of secs. 18 and 19, perpetuated by the Weyerhaeuser Timber Co. in 1989, further perpetuated by the Douglas County Surveyor's Office in 1989, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, in a collar of stone, with a brass cap mkd.



from which bearing trees mkd. by the Weyerhaeuser Timber Co.

- An incense cedar stump, 34 ins. diam., bears N. 72 1/2° E., 32.3 ft. dist., with no marks visible and a "W" nail in face at the base of the stump.
- A hemlock, 14 ins. diam., bears S. 4° W., 2.2 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office

- A hemlock, 16 ins. diam., bears S. 81 1/2° W., 26.5 ft. dist., with a healed double blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

The southerly-most trunk of a multi-trunk madrone snag, 7 ins. diam., bears N. $5\frac{3}{4}^{\circ}$ W., 17.2 ft. dist., with a healed upper blaze and scribe mark B visible on a partially healed lower blaze.

The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with a brass cap mkd.

T	25	S	R	2	W
	S	6		S	5
			—		
	S	7		S	8
					1951

from which the original bearing trees reported by Skeesick in 2010-11

- A yew, 14 ins. diam., bears N. $54\frac{1}{4}^{\circ}$ E., 41.9 ft. dist., with scribe marks 2 2W 5 visible on a partially healed blaze. (Record, N. $52\frac{3}{4}^{\circ}$ E., 42.9 ft. dist.)
- A Douglas fir, 31 ins. diam., bears S. $34\frac{1}{2}^{\circ}$ E., 7.3 ft. dist., with a healed blaze.
- A yew, 19 ins. diam., bears S. 56° W., 46.2 ft. dist., with a healed blaze.
- A yew, 17 ins. diam., bears N. $77\frac{3}{4}^{\circ}$ W., 38.9 ft. dist., with no marks visible on a partially healed blaze.

and bearing trees mkd. by Tallett and White in 1951-63, reported by Skeesick

- A Douglas fir, 54 ins. diam., bears N. $31\frac{3}{4}^{\circ}$ E., 29.7 ft. dist., with a healed blaze.
- A decayed Douglas fir stump, 44 ins. diam., bears N. $86\frac{1}{2}^{\circ}$ W., 53.4 ft. dist., with marks T25S R2W S6 BT visible on a partially healed, decayed blaze. (Record, 50.2 ft. dist.)

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground with a brass cap mkd.

S	5
$\frac{1}{4}$	—
S	8
	1951

from which the remains of the original bearing trees

- A hemlock snag, 17 ins. diam., bears N. $13\frac{3}{4}^{\circ}$ E., 19.1 ft. dist., with illegible scribe marks visible on a partially healed blaze.
- A yew, 23 ins. diam., bears S. 41° E., 24.4 ft. dist., with no marks visible on an opened blaze.

and a new bearing tree

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

A red cedar, 23 ins. diam., bears N. 28 1/2° E., 15.8 ft. dist., mkd. 1/4 S5 BT.

The S 1/16 sec. cor. of secs. 5 and 6, established by Hosford, PLS No. 253, in 1961, perpetuated by Edwards, PLS No. 2339, in 2013, and is accepted as the cor., monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with no cap, from which the remains of bearing trees mkd. by Hosford

A hemlock, 24 ins. diam., bears S. 41° E., 33.3 ft. dist., with a healed blaze.

A decayed hemlock stump, 24 ins. diam., bears N. 55 3/4° W., 50.0 ft. dist., with scribe marks S 1/16 S6 253 BT visible on a partially healed, decayed blaze.

and bearing tree mkd. by Edwards

A chinquapin, 8 ins. diam., bears N. 44 1/2° W., 36.0 ft. dist., with scribe marks S 1/16 S6 BT visible on a partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.

S 1/16
S 6 | S 5
2014

The 1/4 sec cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with a brass cap mkd.

1/4
S 6 | S 5
1951

from which the original bearing trees

A red cedar, 44 ins. diam., bears N. 79 1/2° E., 27.1 ft. dist., with a decayed healed blaze.

A red cedar, 28 ins. diam., bears N. 50 3/4° W., 24.4 ft. dist., with a healed blaze.
