

23364

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE NORTH AND  
EAST BOUNDARIES AND SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF SECTIONS 1 AND 2,  
**TOWNSHIP 32 SOUTH, RANGE 8 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON

---

**EXECUTED BY**

***Brandon G. Courtright, Cadastral Surveyor***

Under Special Instructions approved April 22, 2014,  
which provided for the surveys included under Group No. 2754,  
and Assignment Instructions dated June 4, 2014.

***Survey commenced May 8, 2014***

***Survey completed July 23, 2014***

## T. 32 S., R. 8 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the north and east boundaries and subdivisional lines, and the subdivision of sections 1 and 2, Township 32 South, Range 8 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed the west boundary of T. 32 S., R. 7 W., as shown on the official plat of survey approved May 31, 1882.

In 1882, William H. Byars, U.S. Deputy Surveyor, surveyed the west boundary of T. 31 S., R. 7 W., as shown on the official plat of survey approved October 5, 1882.

In 1882, William H. Byars, U.S. Deputy Surveyor, surveyed the south boundary of T. 31 S., R. 8 W., as shown on the official plat of survey approved July 28, 1883.

In 1883, Richmond S. Dickerson, U.S. Deputy Surveyor, surveyed the subdivisional lines of T. 32 S., R. 8 W., as shown on the official plat of survey approved November 8, 1883.

In 1973-75, Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, dependently resurveyed a portion of the east boundary and subdivisional lines of T. 32 S., R. 8 W., as shown on the official plat of survey accepted January 28, 1980.

In 1976-77, James E. Jelley and James J. Carlson, Cadastral Surveyors, resurveyed a portion of the south boundary and subdivisional lines of T. 31 S., R. 8 W., as shown on the official plat of survey accepted April 24, 1980.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1965	John M. Powell, Deputy County Surveyor	C.S. 49/91
1966	John M. Powell, Deputy County Surveyor	C.S. 54/36
1968	John M. Powell, Deputy County Surveyor	C.S. 54/65
1970	John M. Powell, Deputy County Surveyor	C.S. 54/65
1980	Howard W. Johnstone, PLS No. 498	M 83-25
1980	Howard W. Johnstone, PLS No. 498	M 83-26
1996	Randall W. Smith, PLS No. 2469	C.S. 65/9-13
2003	Mark F. Smalley, PLS No. 2354	M143-2
2013	David A. Edwards, PLS No. 2339	M164-73

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions dated April 22, 2014, for Group No. 2754, Oregon.

**T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques. An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

Each corner that was recovered or established without a prior corner location post or Carsonite alongside has an aluminum fence post driven alongside.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The corner of Townships 31 and 32 South, Ranges 7 and 8 West:

Latitude: 42° 49' 29.98" N. Longitude: 123° 35' 03.65" W.

The 1/4 section corner of sections 3 and 10, Township 32 South, Range 8 West:

Latitude: 42° 48' 39.53" N. Longitude: 123° 37' 55.32" W.

---

**Dependent Resurvey of a Portion of the North Boundary,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

---

Restoring the Survey by William H. Byars, in 1882,  
and the Dependent Resurvey by James E. Jelley  
and James J. Carlson, in 1976-77

---

Beginning at the cor. of Tps. 31 and 32 S., Rs. 7 and 8 W., perpetuated by Powell, Deputy Douglas County Surveyor in 1966, monumented with an iron

**Dependent Resurvey of a Portion of the North Boundary,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>post, 1 1/2 ins. diam., firmly set, projecting 19 ins. above ground, with brass cap mkd.</p>
	<div style="text-align: center;"> </div>
	<p>from which the remains of an original bearing tree, reported by Jelley and Carlson in 1976-77</p>
	<p>A live oak snag, 12 ins. diam., bears S. 78 3/4° E., 39.3 ft. dist., no marks visible in a hollowed and charred blaze. (Record, S. 78° E., 40.3 ft. dist.)</p>
	<p>and the bearing trees mkd. by Powell, reported by Jelley and Carlson</p>
	<p>A live oak, 7 ins. diam., bears N. 48° E., 44.7 ft. dist., with a healed blaze. (Record, N. 49° E., 46.2 ft. dist.)</p>
	<p>A fir, 20 ins. diam., bears S. 48 1/2° E., 24.4 ft. dist., with a healed double blaze.</p>
	<p>A fir, 13 ins. diam., bears S. 69° W., 32.3 ft. dist., with a healed double blaze.</p>
	<p>A double live oak, 9 ins. diam., bears N. 41° W., 4.6 ft. dist., with a healed blaze.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N. 89° 51' 18" W., bet. secs. 1 and 36.</p>
<p>265</p>	<p>Creek, 4 ft. wide, course S. 20° E.</p>
<p>2521.15</p>	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>
	<div style="text-align: center;"> </div>
	<p>from which the bearing trees mkd. by Jelley and Carlson in 1976-77</p>
	<p>A fir, 12 ins. diam., bears N. 69 1/2° E., 24.8 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the North Boundary,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 11 ins. diam., bears S. 17° E., 38.4 ft. dist., with a healed double blaze. (Record, S. 17 1/2° W., 38.9 ft. dist.)</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 17 ins. diam., bears S. 28 1/2° E., 41.0 ft. dist., with a healed blaze and with a Roseburg Timber Products locator tag.</p> <hr/> <p>N. 89° 51' 22" W., beginning new measurement.</p>								
2526.47	<p>The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T 31 S</td> <td style="padding: 2px 5px;">R 8 W</td> </tr> <tr> <td style="padding: 2px 5px;">S 35</td> <td style="padding: 2px 5px;">S 36</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px 5px;">S 2</td> <td style="border-top: 1px solid black; padding: 2px 5px;">S 1</td> </tr> <tr> <td style="padding: 2px 5px;">T 32 S</td> <td style="padding: 2px 5px;">1977</td> </tr> </table> </div> <p>from which the bearing trees mkd. by Jelley and Carlson in 1976-77</p> <p>A fir, 14 ins. diam., bears N. 17° E., 43.6 ft. dist., with a healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 35 1/2° E., 31.0 ft. dist., with a healed blaze.</p> <p>A fir, 25 ins. diam., bears S. 51 1/2° W., 27.7 ft. dist., with a healed blaze.</p> <p>A fir, 10 ins. diam., bears N. 22 1/2° W., 23.1 ft. dist., with a healed blaze.</p> <hr/> <p align="center"><b>Dependent Resurvey of a Portion of the East Boundary, T. 32 S., R. 8 W., Willamette Meridian, Oregon</b></p> <hr/> <p align="center">Restoring the Survey by William H. Byars, in 1881, and the Dependent Resurvey by James E. Jelley and James J. Carlson, in 1976-77</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 6, perpetuated by Powell, Deputy Douglas County Surveyor, in 1965, further perpetuated by Smith, PLS No. 2469, in 1996, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>	T 31 S	R 8 W	S 35	S 36	S 2	S 1	T 32 S	1977
T 31 S	R 8 W								
S 35	S 36								
S 2	S 1								
T 32 S	1977								

Dependent Resurvey of a Portion of the East Boundary,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>SURVEYORS T32S 1/4 R R S 1   S 7 8 RESET W W 1996 1965 COUNTY OFFICE</p>
	<p>from which the remains of the original bearing trees</p> <p>A charred fir snag, broken at 8 ft., 9 ins. diam., bears S. 55° E., 6.6 ft. dist., no marks visible.</p> <p>A charred root wad of a dead and down tree, 6 ft. long, bears N. 70° W., 6.6 ft. dist., no marks visible.</p> <p>and the accessories mkd. by Smith</p> <p>A charred fir stump, 4 ft. tall, 20 ins. diam., bears N. 55 3/4° E., 52.3 ft. dist., measured to a boat spike projecting 2 ins. above the top of the stump.</p> <p>A rock outcrop bears S. 58° W., 18.8 ft. dist., measured to the center of a chiseled cross on the northerly face, with a white, red. and black painted target.</p> <p>A charred fir stump, 3.5 ft. tall, 40 ins. diam., bears N. 77 1/2° W., 12.3 ft. dist., measured to a boat spike set flush in the top of the stump.</p> <p>and new reference monuments</p> <p>An iron rod, 36 ins. long, 5/8 in. diam., driven 33 ins. in the ground for a reference monument, bears S. 84° 19' 03" E, 19.97 ft. dist., with alum. cap mkd. RM1 T32S R7W 19.97 FT TO COR 1/4 S6 2014 and an arrow pointing to the cor.</p> <p>An iron rod, 36 ins. long, 5/8 in. diam., driven 34 ins. in the ground for a reference monument, bears S. 65° 12' 00" W, 19.21 ft. dist., with alum. cap mkd. RM2 T32S R8W 19.21 FT TO COR 1/4 S1 2014 and an arrow pointing to the cor.</p> <hr/> <p>N. 0° 22' 28" E., bet. secs. 1 and 6.</p>
260	Middle Fork Creek, 10 ft. wide, course S. 45° W.
2591.26	The cor. of Tps. 31 and 32 S., Rs. 7 and 8 W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p align="center">Restoring the Survey by Richmond S. Dickerson, in 1883, and the Dependent Resurvey by Lynn M. Roseberry and Rollin D. Aanrud, in 1973-75</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 2, 11, and 12, perpetuated by Powell, Deputy Douglas County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">COUNTY</td> <td style="padding: 0 5px;">SURVEYORS</td> <td style="border-right: 1px solid black; padding: 0 5px;">OFFICE</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">T32S R8W</td> <td style="border-right: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 2   S 1</td> <td style="border-right: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 11   S 12</td> <td style="border-right: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1968</td> <td style="border-right: 1px solid black; padding: 0 5px;"></td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A madrone, 18 ins. diam., bears N. 40° E., 33.7 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A charred fir, 59 ins. diam., bears S. 20° W., 43.6 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Powell, reported by Roseberry and Aanrud in 1973-75</p> <p style="margin-left: 40px;">A charred and rotting fir stump, 3 ft. tall, 28 ins. diam., bears N. 21° E., 26.7 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A tanoak, 18 ins. diam., bears S. 77° E., 17.8 ft. dist., with a partially healed blaze.</p> <p style="margin-left: 40px;">A tanoak, 10 ins. diam., bears N. 85° W., 13.9 ft. dist., with a partially healed blaze.</p> <p>From this cor., a point established by person(s) unknown, and was not utilized in the course of this survey, monumented with an iron pipe, 1 1/4 ins. diam., firmly set projecting 15 ins. above ground, bears N., 1.00 ft. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 18' 02" E., bet. secs. 1 and 2.</p> <p>1311.17 Point for the S 1/16 sec. cor. of secs. 1 and 2.</p> <p style="margin-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 1/16</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 2   S 1</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">2014</td> <td style="padding: 0 5px;"></td> </tr> </table> </div> <p>from which</p>	COUNTY	SURVEYORS	OFFICE		T32S R8W			S 2   S 1			S 11   S 12			1968			S 1/16			S 2   S 1			2014	
COUNTY	SURVEYORS	OFFICE																							
	T32S R8W																								
	S 2   S 1																								
	S 11   S 12																								
	1968																								
	S 1/16																								
	S 2   S 1																								
	2014																								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 35 ins. diam., bears N. 13 3/4° E., 42.4 ft. dist., mkd. S1/16 S1 BT.</p> <p>A pine, 34 ins. diam., bears S. 31 3/4° W., 11.3 ft. dist., mkd. S1/16 S2 BT.</p>																																
2622.34	<p>The 1/4 sec. cor. of secs. 1 and 2, perpetuated by Powell, Deputy Douglas County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td></td> <td colspan="2">SURVEYORS</td> <td></td> </tr> <tr> <td></td> <td colspan="2">T 32 S R 8 W</td> <td></td> </tr> <tr> <td style="writing-mode: vertical-rl; transform: rotate(180deg);">COUNTY</td> <td style="border-right: 1px solid black; padding: 0 5px;">1/4 S 2</td> <td style="padding: 0 5px;">S 1</td> <td style="writing-mode: vertical-rl; transform: rotate(180deg);">OFFICE</td> </tr> <tr> <td></td> <td colspan="2" style="text-align: center;">1968</td> <td></td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A charred and rotted pine stump, size indeterminate, bears N. 16° E., 69.3 ft. dist., no marks visible.</p> <p>A charred and rotted pine stump, size indeterminate, bears N. 35° W., 75.2 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Powell</p> <p>A live oak snag, 8 ins. diam., bears S. 27° E., 22.3 ft. dist., with illegible scribe marks visible on an open charred blaze.</p> <p>A live oak snag, 9 ins. diam., bears N. 10° W., 20.1 ft. dist., with a healed blaze.</p> <p>and new reference monuments</p> <p>A Berntsen® FENO monument, 24 ins. long, 5/8 in. diam., driven 22 ins. in the ground for a reference monument, bears N. 57° 13' 21" E, 21.38 ft. dist., with alum. cap mkd. RM1 T32S R8W 1/4 S1 21.38 FT TO COR, and an arrow pointing to the cor.</p> <p>A Berntsen® FENO monument, 24 ins. long, 5/8 in. diam., driven flush with surface of ground, for a reference monument, bears N. 10° 25' 28" W, 17.39 ft. dist., with alum. cap mkd. RM2 T32S R8W 1/4 S2 17.39 FT TO COR, and an arrow pointing to the cor.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td></td> <td colspan="2">T 32 S R 8 W</td> <td></td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> <td></td> </tr> <tr> <td></td> <td colspan="2" style="border-top: 1px solid black; text-align: center;">1975</td> <td></td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> <td></td> </tr> </table> </div>		SURVEYORS				T 32 S R 8 W			COUNTY	1/4 S 2	S 1	OFFICE		1968				T 32 S R 8 W				S 3	S 2			1975				S 10	S 11	
	SURVEYORS																																
	T 32 S R 8 W																																
COUNTY	1/4 S 2	S 1	OFFICE																														
	1968																																
	T 32 S R 8 W																																
	S 3	S 2																															
	1975																																
	S 10	S 11																															

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of the bearing trees mkd. by Roseberry and Aanrud in 1973-75</p> <p>A charred fir snag, 18 ins. diam., bears N. 9 1/2° E., 16.5 ft. dist., with a healed blaze.</p> <p>A charred fir snag, 14 ins. diam., bears S. 83° E., 28.1 ft. dist., with a healed blaze.</p> <p>A charred fir snag, 15 ins. diam., bears S. 85 1/2° W., 18.5 ft. dist., with a healed blaze.</p> <p>A charred pine snag, 15 ins. diam., bears N. 28° W., 31.7 ft. dist., with a healed blaze.</p> <p>and new reference monuments</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 31 ins. in the ground for a reference monument, bears N. 30° 14' 35" E., 24.24 ft. dist., with alum. cap mkd. RM T32SR8W 24.24 FT TO COR S2 2014, and an arrow pointing to the cor.</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 32 ins. in the ground for a reference monument, bears S. 78° 58' 15" E., 18.22 ft. dist., with alum. cap mkd. RM T32SR8W 18.22 FT TO COR S11 2014, and an arrow pointing to the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 22' 15" W., bet. secs. 3 and 10.</p>
1120	Ravine, drains S. 5° W.
1290.51	<p>The E 1/16 sec. cor. of secs. 3 and 10, established by Smalley, PLS No. 2354, in 2003, and is accepted as the cor., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 9 ins. above ground, with alum. cap mkd. ROSEBURG RESOURCES S3 E1/16 S10 LS2354 2003 COMPANY, from which the remains of the bearing trees mkd. by Smalley</p> <p>A charred fir snag, cut off at 6 ft., 8 ins. diam., bears N. 60° E., 7.7 ft. dist., with a healed blaze.</p> <p>A charred fir snag, cut off at 6 ft., 7 ins. diam., bears S. 9° E., 6.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>S 3 E 1/16 ——— S 10 2014</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>from which new reference monuments</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 32 ins. in the ground for a reference monument, bears S. 60° 17' 05" W., 16.69 ft. dist., with alum. cap mkd. RM E1/16 S3 16.69 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 33 ins. in the ground for a reference monument, bears N. 25° 54' 31" W., 10.58 ft. dist., with alum. cap mkd. RM E1/16 S3 10.58 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>Dispose of the iron rod.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 19' 16" W., beginning new measurement.</p>																		
1291.60	<p>The 1/4 sec. cor. of secs. 3 and 10, perpetuated by Powell, Deputy Douglas County Surveyor in 1970, and further perpetuated by Smalley, PLS No. 2354, in 2003, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: 0 auto;"> <tr> <td style="padding: 0 10px;">COUNTY</td> <td style="padding: 0 10px;">SURVEYORS</td> <td style="padding: 0 10px;">OFFICE</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">T 32 S R 8 W</td> <td style="padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 3</td> <td style="padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">1/4 _____</td> <td style="padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 10</td> <td style="padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">1970</td> <td style="padding: 0 10px;"></td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p>A charred fir snag, size indeterminate, bears N. 30° E., 6.6 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Powell, reported by Roseberry and Aanrud in 1973-75</p> <p>A charred fir snag, size indeterminate, bears N. 75° E., 12.5 ft. dist., no marks visible.</p> <p>A fir, 16 ins. diam., bears S. 67 1/2° W., 15.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Roseberry and Aanrud in 1973-75</p> <p>A fir, 24 ins. diam., bears N. 5 1/2° E., 49.5 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Smalley</p> <p>A charred fir snag, 6 ins. diam., bears S. 14° E., 5.2 ft. dist., with a healed blaze and a washer in the face.</p>	COUNTY	SURVEYORS	OFFICE		T 32 S R 8 W			S 3			1/4 _____			S 10			1970	
COUNTY	SURVEYORS	OFFICE																	
	T 32 S R 8 W																		
	S 3																		
	1/4 _____																		
	S 10																		
	1970																		

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>A charred fir snag, 6 ins. diam., bears S. 45° W., 9.1 ft. dist., with a healed blaze and a washer in the face.</p> <hr/> <p align="center"><b>Subdivision of Section 1, T. 32 S., R. 8 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in the center of the original cor. tree (a hollow live oak, 24 ins. diam.) with brass cap mkd.</p> <p align="center">T 32 S R 8 W S 1 1/4 ——— S 12 1975</p> <p>from which the remains of the bearing trees mkd. by Roseberry and Aanrud in 1973-75</p> <p>A live oak, 12 ins. diam., bears N. 10° E., 17.2 ft. dist., with scribe marks S1 BT visible on partially healed blaze.</p> <p>A fir stump, 6 ft. high, 18 ins. diam., bears S. 56° E., 37.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 10 ins. diam., bears S. 50 1/2° E., 40.6 ft. dist., mkd. 1/4 S12 BT.</p> <p>From this cor., a point established by Edwards, PLS No. 2339, in 2013, as a point on the sec. line bet. secs. 1 and 12, bears S. 89° 25' 31" W., 68.89 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with alum. cap mkd. ROSEBURG RESOURCES CO PROP COR LS2339 2013 and was not utilized for control in the course of this survey.</p> <hr/> <p>N. 1° 10' 52" W., on the N. and S. center line of sec. 1.</p>
1050	Middle Creek Road, asphalt surface, 20 ft. wide, bears N. 55° E. and S. 55° W.
1282.46	<p>The center S 1/16 sec. cor. of sec. 1, established by Johnstone, PLS No. 498, in 1980, under M83-25, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., loosely set, projecting 10 ins. above ground, with alum. cap mkd. T32S R8W SEC1 CS 1/16 1980 LS498, from which the remains of bearing trees mkd. by Johnstone</p> <p>A charred fir snag, 6 ft. high, 6 ins. diam., bears N. 41° E., 36.6 ft. dist., with scribe marks 1/16 S1 visible on open blaze.</p>

**Subdivision of Section 1,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A charred fir snag, 7 ft. high, 16 ins. diam., bears S. 30° W., 18.5 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">           C            S 1/16   S 1            C            2014         </p> <p>from which new reference monuments</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 33 ins. in the ground for a reference monument, bears N. 45° 12' 20" E., 14.79 ft. dist., with alum. cap mkd. RM1 CS1/16 S1 14.79 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 34 ins. in the ground for a reference monument, bears N. 64° 04' 08" W., 16.06 ft. dist., with alum. cap mkd. RM2 CS1/16 S1 16.06 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>Deposit the iron rod inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 10' 53" W., beginning new measurement.</p>
1185	<p>Gulch, 3 ft. wide, 5 ft. deep, drains S. 45° E.</p>
1281.69	<p>The center 1/4 sec. cor. of sec. 1, established by Johnstone, PLS No. 498, in 1980, under M83-25, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, from which the remains of bearing trees mkd. by Johnstone</p> <p>A root hole bears S. 2° E., 22.8 ft. dist., alongside of which is a charred log, 13 ins. diam., no marks visible.</p> <p>A butt of a charred log, 5 ins. diam., bears N. 58 1/4° W., 31.3 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">           T 32 S R 8 W            C 1/4            S 1            2014         </p>

**Subdivision of Section 1,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>from which new accessories</p> <p>An iron rod, 5/8 in. diam., 36 ins. long, driven 31 ins. in the ground for a reference monument, bears S. 29° 46' 11" W., 11.74 ft. dist., with alum. cap mkd. RM T32S R8W C1/4 S1 11.74 FT TO COR, and an arrow pointing to the cor.</p> <p>A Mag Nail, 2 1/2 X 1/4 in. diam., driven into a boulder, 2x3x3 ft., bears N. 50° 40' 30" W., 16.30 ft. dist.</p> <p>Deposit the iron rod inside the stainless steel post.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 1° 10' 45" W., beginning new measurement.</p>
135	Dirt road, 10 ft. wide, bears S. 65° E. and N. 65° W.
2563.57	The 1/4 sec. cor. of secs. 1 and 36.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 1 and 6.</p> <p>N. 89° 11' 32" W., on the E. and W. center line of sec. 1</p>
2285	Dirt road, 10 ft. wide, bears S. 50° E. and N. 50° W.
2451.98	The center 1/4 sec. cor. of sec. 1.
	<hr style="width: 80%; margin: 10px auto;"/> <p>N. 89° 09' 15" W., beginning new measurement.</p>
2557.42	The 1/4 sec. cor. of secs. 1 and 2.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the center S 1/16 sec. cor. of sec. 1.</p> <p>N. 89° 49' 26" W., on the E. and W. center line of the SW 1/4 of sec. 1.</p>
1295.01	<p>The SW 1/16 sec. cor. of sec. 1, established by Johnstone, PLS No. 498, in 1980, under M83-25, verified utilizing the record data from the 1986 Official survey by Roseberry and Aanrud, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with an alum. cap mkd. T32S R8W SEC1 SW 1/16 1979 LS 498, from which the remains of a bearing tree mkd. by Johnstone</p> <p>A charred fir stump, 25 ins. diam., bears N. 47 3/4° E., 8.0 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 1,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p align="center">SW 1/16 S1 2014</p> <p>from which new reference monuments</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 29 ins. in the ground for a reference monument, bears N. 33° 44' 46" E., 20.78 ft. dist., with alum. cap mkd. RM1 SW1/16 S1 20.78 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 32 ins. in the ground for a reference monument, bears N. 66° 03' 43" W., 27.84 ft. dist., with alum. cap mkd. RM2 SW1/16 S1 27.84 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>Deposit the iron rod inside of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 49' 16" W., beginning new measurement.</p>
1295.60	<p>The S 1/16 sec. cor. of secs. 1 and 2.</p> <hr style="width: 80%; margin: 10px auto;"/> <p align="center"><b>Subdivision of Section 2, T. 32 S., R. 8 W., Willamette Meridian, Oregon</b></p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p align="center">T 32 S R 8 W S 2 1/4 _____ S 11 1975</p> <p>from which the remains of the bearing trees mkd. by Roseberry and Aanrud in 1973-75</p> <p>A fir stump, 7 ft. high, bears N. 49° E., 33.7 ft. dist., with a healed blaze.</p> <p>A fir, 42 ins. diam., bears S. 27 1/2° E., 92.4 ft. dist., with a healed blaze. (Record, S. 30° E.)</p> <p>and new bearing trees</p> <p>A pine, 17 ins. diam., bears S. 3 1/4° W., 34.6 ft. dist., mkd. 1/4 S11 BT.</p> <p>A pine, 18 ins. diam., bears N. 77 3/4° W., 73.7 ft. dist., mkd. 1/4 S2 BT.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Subdivision of Section 2,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	N. 0° 40' 25" E., on the N. and S. center line of sec. 2.
55	Graveled road, 15 ft. wide, bears N. 60° E. and S. 70° W.
1298.33	The center S 1/16 sec. cor. of sec. 2, established by Johnstone, PLS No. 498, under M83-26, in 1980, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with alum. cap mkd.
	<p align="center">T 32 S R 8 W CS 1/16 S 2 LS 498 1980</p>
	<p>from which the remains of a bearing tree mkd. by Johnstone</p> <p>A charred fir stump, 30 ins. diam., bears N. 58° E., 14.0 ft. dist., no marks visible.</p> <hr style="width: 20%; margin: 10px auto;"/>
	N. 0° 38' 17" E., beginning new measurement.
210	Dirt road, 20 ft. wide, bears N. 40° E. and S. 40° W.
1260	Skid trail, overgrown with charred snags, 12 ft. wide, bears N. 75° E. and S. 75° W.
1296.80	The center 1/4 sec. cor. of sec. 2, established by Johnstone, PLS No. 498, in 1980, under M83-26, and is accepted as the cor., monumented with an iron rod, 30 ins. long, 5/8 in. diam., loosely set, projecting 14 ins. above ground, with alum. cap mkd. T32S R8W SEC2 C1/4 1980 LS498
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p align="center">T 32 S R 8 W C 1/4 S 2 2014</p>
	<p>from which new reference monuments</p> <p>An iron rod, 5/8 in. diam., 30 ins. long, driven 24 ins. in the ground for a reference monument, bears N. 07° 55' 46" E., 12.13 ft. dist., with alum. cap mkd. RM2 T32S R8W C1/4 S2 12.13 FT TO COR 2014, and an arrow pointing to the cor.</p>
	<p>An iron rod, 5/8 in. diam., 30 ins. long, driven 25 ins. in the ground, bears N. 73° 12' 11" E., 17.69 ft. dist., with alum. cap mkd. RM1 T32S R8W C1/4 S2 17.69 FT TO COR 2014, and an arrow pointing to the cor.</p>

**Subdivision of Section 2,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>Deposit the iron rod inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 41' 35" E., beginning new measurement.</p>
330	<p>Railroad tracks, bears S. 80° E. and N. 85° W.</p>
1272.34	<p>The center N 1/16 sec. cor. of sec. 2, established by Johnstone, PLS No. 498, in 1980, under M83-26, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, with alum. cap mkd. T32S R8W SEC2 CN1/16 LS498 1980, from which the bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A charred fir, 12 ins. diam., bears N. 3 3/4° E., 18.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears N. 78 1/2° W., 9.6 ft. dist., with scribe marks 1/16 B visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>C N 1/16   S 2 C 2014</p> </div> <p>from which new reference monuments</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., 30 ins. long, driven 24 ins. in the ground for a reference monument, bears N. 38° 23' 37" E., 23.78 ft. dist., with alum. cap mkd. RM1 CN1/16 S2 23.78 FT TO COR 2014, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., 30 ins. long, driven 24 ins. in the ground for a reference monument, bears S. 44° 31' 03" E., 17.87 ft. dist., with alum. cap mkd. RM2 CN1/16 S2 17.87 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>Dispose of the iron rod.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 39' 34" E., beginning new measurement.</p>
1291.85	<p>The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p>

**Subdivision of Section 2,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>T 31 S R 8 W S 35 1/4 ——— S 2 T 32 S 1977</p>
	<p>from which the remains of the bearing trees mkd. by Jelley and Carlson in 1976-77</p> <p style="padding-left: 40px;">A charred fir stump, 38 ins. diam., bears S. 6 1/4° W., 34.3 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A charred fir snag, 9 ins. diam., bears N. 18 3/4° W., 11.6 ft. dist., with a healed blaze.</p> <p>and new reference monuments</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., 30 ins. long, driven 27 ins. in the ground for a reference monument, bears N. 84° 12' 11" E., 61.31 ft. dist., with alum. cap mkd. RM T31S R8W S35 61.3 FT TO COR 2014, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., 30 ins. long, driven 27 ins. in the ground for a reference monument, bears S. 23° 05' 07" W., 24.79 ft. dist., with alum. cap mkd. RM T32S R8W S2 24.8 FT TO COR 2014, and an arrow pointing to the cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>S. 89° 23' 49" W., on the E. and W. center line of sec. 2.</p>
1287.23	<p>The center E 1/16 sec. cor. of sec. 2, established by Johnstone, PLS No. 498, in 1980, under M83-26, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., loosely set, projecting 18 ins. above ground, with alum. cap mkd. T32S R8W CE1/16 SEC2 LS498 1980, from which the remains of bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A charred, hollow madrone snag, 5 ft. tall, 12 ins. diam., bears N. 20° E., 23.0 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A charred madrone snag, 9 ins. diam., bears S. 35° W., 19.6 ft. dist., with illegible scribe marks visible on open blaze.</p> <p>At the corner point</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to the top, with brass cap mkd.</p>

**Subdivision of Section 2,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>E 1/16 C-----C S 2 2014</p>
	<p>from which new reference monuments</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 28 ins. in the ground for a reference monument, bears N. 30° 50' 19" E., 22.72 ft. dist., with alum. cap mkd. RM1 CE1/16 S2 22.72 FT TO COR 2014.</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 27 ins. in the ground for a reference monument, bears N. 40° 38' 22" W, 17.17 ft. dist., with alum. cap mkd. RM2 CE1/16 S2 17.17 FT TO COR 2014.</p> <p>Dispose of the iron rod.</p> <p align="center">_____</p> <p>S. 89° 28' 49" W., beginning new measurement.</p>
1286.12	<p>The center 1/4 sec. cor. of sec. 2.</p> <p align="center">_____</p> <p>S. 89° 27' 30" W., beginning new measurement.</p>
1276.89	<p>Point for the center W 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center"> <p>W 1/16 C-----C S 2 2014</p> </p>
	<p>from which new reference monuments</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 24 ins. in the ground for a reference monument, bears S. 28° 48' 51" E., 15.96 ft. dist., with alum. cap mkd. RM1 CW1/16 S2 15.98 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 31 ins. in the ground for a reference monument, bears N. 78° 53' 19" W, 16.87 ft. dist., with alum. cap mkd. RM2 CW1/16 S2 16.87 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>From this cor., a point established as the center W 1/6 cor. of sec. 2 by Johnstone, PLS No. 498, in 1980, under M88-26, bears N. 10° 33' 18" E., 4.42 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 14 ins. above the ground, with alum. cap mkd. T32S R8W S5 CW1/16 LS498 1980, and was not utilized for control in the course of this survey, from which the remains of a bearing tree mkd. by Johnstone</p>

**Subdivision of Section 2,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
2553.78	<p>A charred fir snag, 22 ins. diam., bears N. 9° E., 22.1 ft. dist., no marks visible.</p> <p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 8 W 1/4 S 3   S 2 1975</p> <p>from which the remains of the bearing trees mkd. by Roseberry and Aanrud in 1973-75</p> <p>A charred, rotted fir stump, size indeterminate, bears East, 37.0 ft. dist., no marks visible.</p> <p>A root hole bears N. 52 1/2° W., 31.4 ft. dist., alongside of which is a down charred fir, 29 ins. diam., no marks visible.</p> <p>from which new reference monuments</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., driven 23 ins. in the ground for a reference monument, bears S. 57° 28' 02" E., 37.80 ft. dist., with alum. cap mkd. RM T32S R8W 1/4 S2 37.80 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>An iron rod, 24 ins. long, 5/8 in. diam., driven 23 ins. in the ground for a reference monument, bears S. 43° 43' 43" W., 17.20 ft. dist., with alum. cap mkd. RM T32S R8W 1/4 S3 17.20 FT TO COR 2014, and an arrow pointing to the cor.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 2 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 2 E 1/16 ——— S 11 1975</p> <p>from which the remains of the bearing trees mkd. by Roseberry and Aanrud in 1973-75</p> <p>A fir stump, 25 ins. diam., bears N. 31° E., 24.8 ft. dist., no marks visible.</p> <p>A charred fir snag, 24 ins. diam., bears S. 54 1/4° W., 23.8 ft. dist., no marks visible.</p> <p>and new reference monuments</p>

**Subdivision of Section 2,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>An iron rod, 24 ins. long, 5/8 in. diam., driven 21 ins. into the center of the stump of the NE. bearing tree for a reference monument, bears N. 30° 59' 13" E., 24.74 ft. dist., with alum. cap mkd. RM E1/16 S2 24.74 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 31 ins. in the ground for a reference monument, bears S. 29° 31' 18" E, 26.06 ft. dist., with alum. cap mkd. RM E1/16 S11 26.06 FT TO COR 2014, and an arrow pointing to the cor.</p> <hr/> <p>N. 0° 27' 53" E., on the N. and S. center line of the SE 1/4 of sec. 2</p>
1304.78	<p>Point for the SE 1/16 sec. cor. of sec. 2, at intersection with the E. and W. center line of the SE 1/4 of Sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">SE 1/16 S 2 2014</p> <p>from which</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 29 ins. in the ground for a reference monument, bears S. 85° 16' 45" E, 8.60 ft. dist., with alum. cap mkd. RM1 SE1/16 S2 8.60 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>An alum. drive rod, 36 ins. long, 3/4 in. diam., driven 34 ins. in the ground for a reference monument, bears N. 31° 54' 15" W., 14.40 ft. dist., with alum. cap mkd. RM2 SE1/16 S2 14.40 FT TO COR 2014, and an arrow pointing to the cor.</p>
2607.82	<p>The center E 1/16 sec. cor. of sec. 2.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 1 and 2.</p>
1290.93	<p>S. 89° 45' 39" W., on the E. and W. center line of the SE 1/4 of sec. 2.</p>
1290.93	<p>The SE 1/16 sec. cor. of sec. 2.</p>
2580.96	<p>The center S 1/16 sec. cor. of sec. 2.</p> <hr/>