

23384

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
SUBDIVISIONAL LINES, AND SUBDIVISION OF SECTION LINES IN SECTION 24,
THE SUBDIVISION OF SECTIONS 26 AND 35, AND THE REMONUMENTATION OF
THE 1/4 SECTION CORNER OF SECTIONS 3 AND 34 ON THE SOUTH BOUNDARY,
TOWNSHIP 23 SOUTH, RANGE 1 WEST,
AND THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 24 SOUTH, RANGE 1 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON

EXECUTED BY

Joseph M. Mannix, Cadastral Surveyor

Under Special Instructions approved April 10, 2015, and Supplemental Special Instructions approved July 31, 2015, which provided for the surveys included under Group No. 2763, and Assignment Instructions dated April 10, 2015, and Supplemental Assignment Instructions dated July 31, 2015.

Survey commenced April 10, 2015

Survey completed July 31, 2015

T. 23 S., R. 1 W., Willamette Meridian, Oregon

The following field notes are those of the dependent resurvey of a portion of the south boundary, subdivisional lines, and subdivision of section lines in section 24, the subdivision of sections 26 and 35, and the remonumentation of the 1/4 section corner of sections 3 and 34 on the south boundary, Township 23 South, Range 1 West, and the dependent resurvey of a portion of the subdivisional lines, Township 24 South, Range 1 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1894, Henry L. Chandler, U.S. Deputy Surveyor, surveyed the south boundary and subdivisional lines of T. 23 S., R. 1 W., as shown on the official plat of survey approved January 17, 1895.

In 1896, Carl S. Nicklin and Winfield S. Chapman, U.S. Deputy Surveyors, surveyed the subdivisional lines of T. 24 S., R. 1 W., as shown on the official plat of survey approved August 10, 1897.

In 1960, Harold D. Corbin, Cadastral Surveyor, resurveyed portions of the north and east boundaries and subdivisional lines of T. 23 S., R. 1 W., as shown on the official plat of survey accepted February 5, 1962.

In 1986-90, Craig L. Wanless, Cadastral Surveyor, resurveyed a portion of the east boundary and subdivisional lines and subdivided sections 1 and 24 of T. 23 S., R. 1 W., as shown on the official plat of survey accepted July 20, 1990.

The following local survey Map files (M) and County Surveys (CS), filed in the Douglas County Surveyor's Office, are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1970	Douglas County Surveyor's Office	CS 54/27
10/1976	Douglas County Surveyor's Office	CS 59/24
11/1976	Douglas County Surveyors Office	CS 59/26
1977	Glenn S. Baughman, PLS No. 536	M 65-51

The following Restored Corner Index (RC), filed in the Lane County Surveyor's Office, is referred to in subsequent corner descriptions and is referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
2003	William D. Robinson, PLS No. 1554	RC 14343

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), the special instructions approved April 10, 2015, and the supplemental special instructions approved July 31, 2015, for Group No. 2763, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning Systems (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

T. 23 S., R. 1 W., Willamette Meridian, Oregon

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the corner description field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each corner remonumented or new corner established has a magnet in a white plastic case deposited at the base of the stainless steel post, unless otherwise noted in the corner description.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The corner of sections 1, 2, 35, and 36, on the south boundary of the township:

Latitude: 43° 31' 24.35" N. Longitude: 122° 45' 41.14" W.

The corner of sections 26, 27, 34, and 35:

Latitude: 43° 32' 13.97" N. Longitude: 122° 46' 55.07" W.

The center W 1/16 section corner of section 24:

Latitude: 43° 33' 29.10" N. Longitude: 122° 45' 22.92" W.

The 1/4 section corner of sections 3 and 34, on the south boundary of the township:

Latitude: 43° 31' 23.97" N. Longitude: 122° 47' 28.13" W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

Restoring the 1894 survey by Henry L. Chandler

The cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in October, 1976, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.

23387

Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 1 W., Willamette Meridian, Oregon

DOUGLAS CO. SURVEYOR		
T 23 S		
S 35	S 36	R 1 W

S 2	S 1	
T 24 S		
1976		

from which the remains of the original bearing trees

A fir, 42 ins. diam., bears S. 76 3/4° E., 19.8 ft. dist., with a healed blaze. (Record, S. 81° E.)

A fir stump, 22 ins. diam., 6 ft. tall, bears N. 18° W., 17.8 ft. dist., with a healed blaze.

and the bearing trees mkd. by the Douglas County Surveyor's Office

A fir, 12 ins. diam., bears N. 73 1/4° E., 14.7 ft. dist., with a healed blaze.

A fir, 15 ins. diam., bears S. 6 1/4° W., 20.8 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 13 ins. diam., bears N. 66° W., 35.3 ft. dist., mkd. T23S R1W S35 BT.

A steel fence post is alongside the cor.

The 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1970, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground (alongside of which is the original basalt stone, 12x9x5 ins., mkd. with 1/4 on side and X on top, as reset by the DCSO in 1970), with a brass cap mkd.

SURVEYORS		
COUNTY	T 23 S R 1 W	OFFICE
	S 35	
	1/4 -----	
	S 2	
	T 24 S	
1970		

from which the remains of the original bearing trees

A fir stump, 29 ins. diam., 4 ft. high, bears N. 75° E., 20.5 ft. dist., with a healed blaze.

A fir stump, 31 ins. diam., 6 ft. high, bears S. 44° W., 16.5 ft. dist., with a healed blaze.

and new bearing trees

A fir, 23 ins. diam., bears N. 25 1/2° E., 87.5 ft. dist., mkd. 1/4 S35 BT.

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

A fir, 15 ins. diam., bears S. 63 1/4° E., 31.0 ft. dist., mkd. 1/4 S2 BT.

Point for the W 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a brass cap mkd.

S 35
 W 1/16 ———
 S 2
 2015

from which

A fir, 19 ins. diam., bears S. 30 1/2° E., 11.0 ft. dist., mkd. W1/16 S2 BT.

A fir, 15 ins. diam., bears N. 76 3/4° W., 18.5 ft. dist., mkd. W1/16 S35 BT.

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented a basalt stone, 12 x 10 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. with 4 notches on the W. side and 2 notches on the E. side visible, from which the remaining original bearing trees

A fir, 43 ins. diam., bears N. 22° E., 80.5 ft. dist., with a healed blaze.

A fir, 32 ins. diam., bears S. 7 1/4° W., 42.2 ft. dist., with a healed blaze. (Record, S. 5° W.)

A fir, 39 ins. diam., bears N. 1° W., 115.0 ft. dist., with a healed blaze. (Record, 121.4 ft. dist.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a mound of stone, 3 ft. base, to the top, with a brass cap mkd.

T 23 S R 1 W
 S 34 | S 35
 ———
 S 3 | S 2
 T 24 S
 2015

from which

A fir, 11 ins. diam., bears S. 58 1/4° E., 21.4 ft. dist., mkd. T24S R1W S2 BT.

Bury the basalt alongside the stainless steel post.

23389

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

Restoring the 1894 survey by Henry L. Chandler
and the 1960 resurvey by Harold D. Corbin

Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a brass cap mkd.

T 23 S R 1 W
1/4
S 34 | S 35
2015

from which

A fir, 12 ins. diam., bears S. 62 1/2° E., 23.2 ft. dist., mkd. 1/4 S35 BT.

A fir, 12 ins. diam., bears S. 62° W., 13.3 ft. dist., mkd. 1/4 S34 BT.

From the corner

N. 2° 22' 08" W., 25 ft. dist., center of Oakland to Bohemian Mine trail, dirt surface,
10 ft. wide, bears N. 75° W. and S. 75° E.

The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, in a collar of stone, with a brass cap mkd.

T 23 S R 1 W
S 27 | S 26
S 34 | S 35
1960

from which the remains of the original bearing trees reported by Corbin in 1960

A fir, 27 ins. diam., bears N. 58 1/2° E., 8.6 ft. dist., with a healed blaze. (Record, hemlock)

A hemlock, 16 ins. diam., bears S. 20° E., 15.5 ft. dist., with a healed blaze. (Record, fir, 17.2 ft. dist.)

A fir snag, 8 ins. diam., 6 ft. tall, bears S. 9 1/4° W., 14.5 ft. dist., with a healed blaze.

A pine snag, 22 ins. diam., bears N. 70 1/2° W., 7.3 ft. dist., with illegible scribe marks visible on an open blaze.

and the bearing trees mkd. by Corbin

A fir, 11 ins. diam., bears S. 37° E., 33.7 ft. dist., with a healed blaze.

23390

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

A fir, 12 ins. diam., bears S. 28° W., 15.2 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 19 ins. diam., bears N. 9 1/2° W., 18.3 ft. dist., mkd. T23S R1W S27 BT.

The 1/4 sec. cor. of secs. 26 and 27, perpetuated by Robinson, PLS No. 1554, in 2003, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, in a collar of stone, with a brass cap mkd.

T 23 S R 1 W
1/4
S 27 | S 26
1960

from which the remaining original bearing tree

A hemlock, 28 ins. diam., bears S. 57° W., 11.9 ft. dist., with a healed blaze and a Mag-Nail and washer driven into the face at the base of the blaze.

and the bearing trees mkd. by Robinson

A hemlock, 12 ins. diam., bears N. 47 3/4° E., 39.2 ft. dist., with scribe marks BT visible on a partially healed blaze and a Mag-Nail and washer driven into the face at the base of the blaze.

A hemlock, 29 ins. diam., bears S. 60 3/4° E., 14.6 ft. dist., with scribe marks CS BT visible on a partially healed blaze and a Mag-Nail and washer driven into the face at the base of the blaze.

A hemlock, 26 ins. diam., bears N. 52 1/4° W., 32.3 ft. dist., with a healed blaze and a Mag-Nail and washer driven into the face at the base of the blaze.

**Dependent Resurvey of a Portion of the Subdivision of Section Lines in Section 24,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

Restoring the 1986-90 survey by Craig L. Wanless

The center 1/4 sec. cor. of sec. 24, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with an aluminum cap mkd.

T 23 S R 1 W
C 1/4 S 24
1986

from which the bearing trees mkd. by Wanless in 1986-90

A fir, 15 ins. diam., bears S. 76° E., 15.2 ft. dist., with a healed blaze.

23391

**Dependent Resurvey of a Portion of the Subdivision of Section Lines in Section 24,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

A chinquapin, 9 ins. diam., bears S. 19° W., 20.1 ft. dist., with a healed blaze.

The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.

T 23 S R 1 W
S 13
1/4 ———
S 24
1960

from which the remaining bearing tree mkd. by Corbin in 1960

A fir, 36 ins. diam., bears N. 14 1/2° E., 16.5 ft. dist., with a healed blaze. (Record, hemlock)

and a new bearing tree

A fir, 9 ins. diam., bears S. 61 1/2° W., 19.8 ft. dist., mkd. 1/4 S24 BT.

There are aluminum posts set N., 3 ft. dist., and S., 3 ft. dist., from the cor.

The center W 1/16 sec. cor. of sec. 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.

W 1/16
C ——— C
S 24
1986

from which the bearing trees mkd. by Wanless in 1986-90

A fir, 25 ins. diam., bears S. 58° W., 18.8 ft. dist., with a healed blaze.

A fir, 35 ins. diam., bears N. 51° W., 21.8 ft. dist., with a healed blaze.

**Subdivision of Section 26,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, (alongside of which is the original basalt stone, 12 x 10 x 6 ins., mkd. /4) with a brass cap mkd.

T 23 S R 1 W
S 26
1/4 ———
S 35
1960

23392

**Subdivision of Section 26,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

from which the remaining original bearing tree reported by Corbin in 1960

A fir, 53 ins. diam., bears S. 70° E., 35.0 ft. dist., with a healed blaze. (Record, S. 65° E.)

and a new bearing tree

A cedar, 22 ins. diam., bears N. 5 1/2° W., 16.7 ft. dist., mkd. 1/4 S26 BT.

Point for the center 1/4 sec. cor. of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, 1 ft. high, with a brass cap mkd. (cap oriented southerly)

T 23 S R 1 W
C 1/4 S 26
2015

from which

A fir, 6 ins. diam., bears S. 74 3/4° E., 15.7 ft. dist., mkd. X BT.

A fir, 36 ins. diam., bears S. 6 1/4° W., 34.1 ft. dist., mkd. C1/4 S26 BT.

The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, in a collar of stone, with a brass cap mkd.

T 23 S R 1 W
S 23
1/4 ———
S 26
1960

from which new bearing trees

A fir, 14 ins. diam., bears S. 19 1/4° W., 11.2 ft. dist., mkd. 1/4 S26 BT.

A fir, 11 ins. diam., bears N. 40 3/4° W., 29.2 ft. dist., mkd. 1/4 S23 BT.

(Note: No remaining evidence of bearing trees mkd. by Corbin in 1960 was recovered.)

The 1/4 sec. cor. of secs. 25 and 26, perpetuated by the Douglas County Surveyor's Office in November, 1976, who found the 1960 Corbin monument disturbed from its original position and reset the 1960 monument using the Record ties from the recovered remains of the Corbin bearing trees; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.

23393

Subdivision of Section 26,
T. 23 S., R. 1 W., Willamette Meridian, Oregon

T 23 S R 1 W
1/4
S 26 | S 25
1976
1960

from which the remains of the bearing trees mkd. by Corbin in 1960

- A fir stump, 40 ins. diam., bears S. 57° E., 5.9 ft. dist., with scribe marks 1/4 S25 BT visible on an open blaze.
- A decayed hemlock stump, 22 ins. diam., bears N. 57° W., 29.0 ft. dist., with no marks visible.

and an accessory mkd. by the Douglas County Surveyor's Office

An iron rod, 5/8 in. diam., firmly set in the center of a fir stump, 48 ins. diam., projecting 3 ins. above top of the stump, bears N. 69° 48' 17" E, 70.31 ft. dist., with an aluminum cap mkd. DOUGLAS COUNTY SURVEYOR BO.

and a new bearing tree

- A fir, 20 ins. diam., bears S. 78 1/2° W., 6.9 ft. dist., mkd. 1/4 S26 BT.

Point for the center E 1/16 sec. cor. of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a brass cap mkd.

E 1/16 S26
C———C
2015

from which

- A fir, 16 ins. diam., bears S. 70 1/2° E., 32.3 ft. dist., mkd. CE1/16 S26 BT.
- A fir, 14 ins. diam., bears S. 51 3/4° W., 10.0 ft. dist., mkd. X BT.

The E 1/16 sec. cor. of secs. 23 and 26, determined at Record bearing and dist. from the remains of a bearing tree mkd. by Corbin in 1960

- A fir stump, size indeterminate, bears N. 16° E., 13.9 ft. dist., with a fallen fir trunk, size indeterminate, lying alongside, with scribe marks 1/16 visible on a partially healed blaze.

(Note: Corbin's iron post, 28 ins. long, 2 1/2 ins. diam. was found lying loose on the ground nearby, and determined to have been disturbed from its original location.)

At the corner point

23394

**Subdivision of Section 26,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

Reset the 1960 iron post, 21 ins. in the ground, and add marks 2015 to the brass cap to now read

S 23
E 1/16 ———
S 26
2015
1960

from which new bearing trees

A fir, 12 ins. diam., bears S. 67° E., 26.2 ft. dist., mkd. E1/16 S26 BT.

A fir, 12 ins. diam., bears N. 27 1/4° W., 42.5 ft. dist., mkd. E1/16 S23 BT.

**Subdivision of Section 35,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

Point for the center 1/4 sec. cor. of sec. 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a brass cap mkd.

T 23 S R 1 W
C 1/4 S 35
2015

from which

A cedar, 21 ins. diam., bears S. 56 1/4° W., 35.6 ft. dist., mkd. C1/4 S35 BT.

A fir, 14 ins. diam., bears N. 8 1/2° W., 31.7 ft. dist., mkd. C1/4 S35 BT.

The 1/4 sec. cor. of secs. 35 and 36, perpetuated by Baughman, PLS No. 536, in 1977, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a mound of stone, 3 ft. base, to the top, with a brass cap mkd.

T 23 S R 1 W
1/4
S 35 | S 36
1977
PLS 536

from which the remaining original bearing tree

A fir, 32 ins. diam., bears N. 50° W., 32.3 ft. dist., with scribe marks BT visible on an open blaze.

and the bearing trees mkd. by Baughman

23395

**Subdivision of Section 35,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

A hemlock, 10 ins. diam., bears S. $73\ 3/4^\circ$ E., 26.3 ft. dist., with scribe marks 36 visible on a partially healed blaze.

A fir, 13 ins. diam., bears S. $55\ 1/2^\circ$ W., 7.2 ft. dist., with a healed blaze.

A steel fence post is N., 3 ft. dist., from the cor.

Point for the center W 1/16 sec. cor. of sec. 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with a brass cap mkd.

W 1/16 S35
C———C
2015

from which

A fir, 18 ins. diam., bears S. $6\ 1/2^\circ$ E., 22.0 ft. dist., mkd. CW1/16 S35 BT.

A fir, 22 ins. diam., bears N. $66\ 1/2^\circ$ W., 15.8 ft. dist., mkd. CW1/16 S35 BT.

**Remonumentation of the 1/4 Section Corner of Sections 3 and 34
on the South Boundary,
T. 23 S., R. 1 W., Willamette Meridian, Oregon**

Restoring the 1894 survey by Henry L. Chandler

The 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., determined at record bearing and dist. from the remains of an original bearing tree

A fir stump, 40 ins. diam., bears S. 80° E., 25.7 ft. dist., with scribe marks BT visible on a partially opened blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with a brass cap mkd.

T 23 S R 1 W
S 34
1/4 ———
S 3
T 24 S
2015

from which

A fir, 16 ins. diam., bears N. $68\ 3/4^\circ$ E., 13.7 ft. dist., mkd. 1/4 S34 BT.

23396
Remonumentation of the 1/4 Section Corner of Sections 3 and 34
on the South Boundary,
T. 23 S., R. 1 W., Willamette Meridian, Oregon

A fir, 14 ins. diam., bears S. 21 1/4° W., 24.6 ft. dist., mkd. 1/4 S3 BT.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 1 W., Willamette Meridian, Oregon

Restoring the 1896 survey by Carl S. Nicklin and Winfield S. Chapman

The 1/4 sec. cor. of secs. 1 and 2, perpetuated by the Douglas County Surveyor's Office, in 1970, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

SURVEYORS		
COUNTY	T 24 S R 1 W 1/4 S 2 S 1 1970	OFFICE

from which the original bearing trees

A fir, 24 ins. diam., bears S. 72° E., 33.7 ft. dist., with illegible scribe marks visible on an open blaze.

A fir, 32 ins. diam., bears N. 70° W., 42.9 ft. dist., with a healed blaze.

and the bearing trees mkd. by the Douglas County Surveyor's Office

A fir, 11 ins. diam., bears S. 59 1/2° E., 16.2 ft. dist., with a healed blaze.

A fir, 29 ins. diam., bears S. 66° W., 8.9 ft. dist., with a healed blaze.
