

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
AND  
THE SUBDIVISION OF SECTION 23,  
**TOWNSHIP 23 SOUTH, RANGE 8 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON

---

**EXECUTED BY**

***Edith M. Forkner, Cadastral Surveyor***

Under Special Instructions approved May 5, 2015,  
which provided for the surveys included under Group No. 2781,  
and Assignment Instructions dated May 5, 2015.

***Survey commenced May 13, 2015***

***Survey completed August 5, 2015***

**T. 23 S., R. 8 W., Willamette Meridian, Oregon**

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 23, Township 23 South, Range 8 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1857, Dennis Hathorn, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved April 24, 1858.

In 1894, Williams R. Whipple, U.S. Deputy Surveyor, surveyed the remainder of the subdivisional lines, as shown on the official plat of survey approved June 27, 1895, and accepted January 15, 1897.

In 1958, Joseph S. Gawron, Cadastral Surveyor, remonumented certain original corner points, as shown in the official field notes of survey approved August 25, 1959.

In 1964, Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors, dependently resurveyed a portion of the subdivisional lines and remonumented an original corner point, as shown on the official plat of survey accepted August 20, 1965, suspended July 1, 1986, suspension lifted February 8, 1989. Refer to plat accepted September 30, 1988.

In 1970, James E. Jelley, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted April 19, 1972, suspended July 1, 1986, suspension lifted February 8, 1989. Refer to plat accepted September 30, 1988.

In 1985, Harvey E. Wofford, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted July 15, 1988.

In 1986, John A. Farmer, Cadastral Surveyor, correctively resurveyed a portion of the subdivisional lines and resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted September 30, 1988.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No. or official title, and year.

| <u>Date</u> | <u>Name and Registration Number</u>      | <u>File Number</u> |
|-------------|--|--------------------|
| 1960        | James W. Byron, Deputy County Surveyor   | M19-75, CS 52/57   |
| 1962        | Milo E. Godfrey, Deputy County Surveyor  | CS 49/49           |
| 1966        | Douglas County Surveyor's Office         | CS 54/12           |
| 1967        | Douglas County Surveyor's Office         | CS 54/12           |
| 1973        | Douglas County Surveyor's Office         | CS 56/25           |
| 1974        | Gary L. Langlitz, Deputy County Surveyor | CS 56/51           |
| 1980        | Les Roberts, PLS No. 1039                | CS 58/237-1        |
| 1981, Jan.  | Les Roberts, PLS No. 1039                | M86-65             |

## T. 23 S., R. 8 W., Willamette Meridian, Oregon

| FEET |  |                                     |                    |
|------|--|-------------------------------------|--------------------|
|      | <u>Date</u>  | <u>Name and Registration Number</u> | <u>File Number</u> |
|      | 1981, Feb.   | Les Roberts, PLS No. 1039           | M86-66             |
|      | 2010   | Ronald L. Rice, PLS No. 54633       | CS 65/69-52        |
|      | 2015   | Clyde F. Mulkins, PLS No. 2006      | M169-50            |
|      | <p>In 1977, an administrative survey by the Federal Highway Administration (FHA) established certain corners in section 23 for the Bureau of Land Management (BLM). Steel fence posts were set for corner monuments and location tags were placed on trees to reference the fence posts. The survey was done administratively and not under an official government survey. The record of this survey is located in the Coos Bay District Office.</p>   |                                     |                    |
|      | <p>The 1980 and the February 1981 surveys by Les Roberts, PLS No. 1039, established numerous iron rod line markers, 1/2 inch diam., projecting 2 feet above ground, as indicated on his plats. These iron rods were not used for control during this resurvey.</p>   |                                     |                    |
|      | <p>The survey was executed in accordance with the specification set forth in the <u>Manual of Surveying Instructions</u> (2009), and the special instructions approved May 5, 2015, for Group No. 2781, Oregon.</p>  |                                     |                    |
|      | <p>The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and direct solar observations and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.</p> |                                     |                    |
|      | <p>Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.</p>   |                                     |                    |
|      | <p>Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description. Aluminum angle irons were driven alongside each corner unless an existing guard post was noted in the corner description. Only those lines bounding Federal interest land were blazed.</p>   |                                     |                    |
|      | <p>The geographic position in NAD 1983 (2011) of the following corner as determined by direct occupation utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):</p>   |                                     |                    |

**T. 23 S., R. 8 W., Willamette Meridian, Oregon**

FEET

The corner of sections 21, 22, 27, and 28:

Latitude: 43° 32' 53.996" N. Longitude: 123° 38' 39.152" W.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS:

The corner of sections 8, 9, 16, and 17:

Latitude: 43° 34' 37.64" N. Longitude: 123° 39' 49.99" W.

The north 1/16 section corner of sections 22 and 23:

Latitude: 43° 33' 32.55" N. Longitude: 123° 37' 26.74" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

Restoring the survey by Hathorn in 1857, the survey by Whipple in 1894, the remonumentation by Gawron in 1958, the resurvey and remonumentation by Brooks and Peterson in 1964, the resurvey by Wofford in 1985, the resurvey by Wofford in 1985, and the resurvey by Farmer in 1986

Beginning at the cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with a brass cap mkd.

|        |           |       |        |
|--------|-----------|-------|--------|
| COUNTY | SURVEYORS |       | OFFICE |
|        | T 23 S    | R 8 W |        |
|        | S 23      | S 24  |        |
|        | S 26      | S 25  |        |
|        | 1960      |       |        |

from which the remains of the original bearing trees

A decayed fir stump, 48 ins. diam., bears N. 5° E., 50.2 ft. dist., no marks visible.

A fir, 29 ins. diam., bears S. 25° E., 24.4 ft. dist., with a healed double blaze.

and the remains of a bearing tree mkd. by Whipple in 1894 and reported by Brooks and Peterson in 1964

A roothole bears S. 24° W., 25.1 ft. dist., alongside of which is a down decayed fir, 24 ins. diam., no marks visible. (Record, 14.5 ft. dist.)

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |   |     |       |     |     |             |     |   |      |     |
|---------|---|-----|-------|-----|-----|-------------|-----|---|------|-----|
|         | <p>and the remains of the bearing trees mkd. by Byron, Deputy Douglas County Surveyor, in 1960 and reported by Brooks and Peterson</p> <p>A decayed fir stump, 59 ins. diam., bears S. 71° W., 46.2 ft. dist., no marks visible.</p> <p>A decayed fir stump, 21 ins. diam., bears N. 41 1/2° W., 56.1 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 17 ins. diam., bears N. 61° E., 27.3 ft. dist., mkd. T23S R8W S24 BT.</p> <p>A fir, 16 ins. diam., bears S. 63° W., 19.8 ft. dist., mkd. T23S R8W S26 BT.</p> <p>A fir, 10 ins. diam., bears N. 15° W., 37.8 ft. dist., mkd. T23S R8W S23 BT.</p> <p>N. 0° 14' 46" W., bet. secs. 23 and 24, marking and blazing the true line.</p>   |     |       |     |     |             |     |   |      |     |
| 590     | Graveled road, 10 ft. wide, bears N. 45° W. and S. 80° E.   |     |       |     |     |             |     |   |      |     |
| 830     | Graveled road, 10 ft. wide, bears N. 80° W. and E.  |     |       |     |     |             |     |   |      |     |
| 1235    | Creek, 1 ft. wide, course N. 40° W.   |     |       |     |     |             |     |   |      |     |
| 1322.37 | <p>The S 1/16 sec. cor. of secs. 23 and 24, established by Roberts, PLS No. 1039, in February, 1981, and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>PLS 1039</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">S</td> <td style="text-align: center;">S1/16</td> <td style="text-align: center;">R8W</td> </tr> <tr> <td style="text-align: center;">T23</td> <td style="text-align: center;">S 23   S 24</td> <td style="text-align: center;">R8W</td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">1981</td> <td style="text-align: center;">R8W</td> </tr> </table> </div> <p>from which the remains of a bearing tree mkd. by Roberts</p> <p>A fir snag, 30 ins. diam., bears N. 0 3/4° W., 19.2 ft. dist., with a healed double blaze.</p> <p>and new bearing trees</p> <p>A fir, 15 ins. diam., bears S. 74 1/2° E., 21.1 ft. dist., mkd. S1/16 S24 BT.</p> <p>A fir, 8 ins. diam., bears S. 81 3/4° W., 9.6 ft. dist., mkd. S1/16 S23 BT.</p> <p>An iron rod is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 12' 51" W., beginning new measurement.</p> | S   | S1/16 | R8W | T23 | S 23   S 24 | R8W | 1 | 1981 | R8W |
| S       | S1/16   | R8W |       |     |     |             |     |   |      |     |
| T23     | S 23   S 24   | R8W |       |     |     |             |     |   |      |     |
| 1       | 1981  | R8W |       |     |     |             |     |   |      |     |
| 835     | Top of cliff, 60 ft. high, rim bears N. 10° E. and S. 10° W.  |     |       |     |     |             |     |   |      |     |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

|         |  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|---------|--|--------|-----------|--------|--|--------------|--|--|-------------|--|--|-------|--|--|------|--|
| FEET    |  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
| 1270    | South end of dilapidated wire fence, extends N.; along fence.  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
| 1322.93 | <p>The 1/4 sec. cor. of secs. 23 and 24, reestablished by proportionate measurement by Byron, Deputy Douglas County Surveyor, in 1960. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with a brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border: none;"> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;">SURVEYORS</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">T 23 S R 8 W</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S 23   S 24</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1/4</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1960</td> <td></td> </tr> </table> <p>from which the remains of the bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A decayed fir stump, 18 ins. diam., bears S. 27 1/2° E., 34.7 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A decayed fir stump, 20 ins. diam., bears N. 13 1/4° W., 56.9 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 22° E., 29.1 ft. dist., mkd. 1/4 S24 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 9 1/2° W., 22.6 ft. dist., mkd. 1/4 S23 BT.</p> <p>Corner is located in dilapidated wire fence, bears N. and S.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 0° 16' 03" W., beginning new measurement, along dilapidated wire fence.</p> | COUNTY | SURVEYORS | OFFICE |  | T 23 S R 8 W |  |  | S 23   S 24 |  |  | 1/4   |  |  | 1960 |  |
| COUNTY  | SURVEYORS  | OFFICE |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|         | T 23 S R 8 W   |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|         | S 23   S 24  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|         | 1/4  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|         | 1960   |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
| 310     | North end of dilapidated wire fence, extends S.  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
| 410     | Mehl Creek, 10 ft. wide, course S. 70° E.  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
| 1321.36 | <p>The N 1/16 sec. cor. of secs. 23 and 24, established by Byron, Deputy Douglas County Surveyor, in 1960; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 18 ins. above ground, with a brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border: none;"> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;">SURVEYORS</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">T 23 S R 8 W</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S 23   S 24</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">N1/16</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1960</td> <td></td> </tr> </table> <p>from which the remains of a bearing tree mkd. by Byron</p>   | COUNTY | SURVEYORS | OFFICE |  | T 23 S R 8 W |  |  | S 23   S 24 |  |  | N1/16 |  |  | 1960 |  |
| COUNTY  | SURVEYORS  | OFFICE |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|         | T 23 S R 8 W   |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|         | S 23   S 24  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|         | N1/16  |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |
|         | 1960   |        |           |        |  |              |  |  |             |  |  |       |  |  |      |  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

|        |   |        |           |        |  |              |  |  |             |  |  |             |  |  |      |  |
|--------|---|--------|-----------|--------|--|--------------|--|--|-------------|--|--|-------------|--|--|------|--|
| FEET   | <p>A decayed fir stump, size indeterminate, bears S. 18° E., 25.7 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 32 ins. diam., bears N. 8 1/2° W., 25.6 ft. dist., no marks visible and a bearing tree tag dated 8/93. Add scribe marks N1/16 S23 BT.</p> <p>and a new bearing tree</p> <p>A fir, 20 ins. diam., bears N. 42° E., 21.3 ft. dist., mkd. N1/16 S24 BT.</p> <p>An iron rod is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 14' 12" W., beginning new measurement.</p>   |        |           |        |  |              |  |  |             |  |  |             |  |  |      |  |
| 835.66 | <p>The witness cor. of secs. 23 and 24, perpetuated by Byron, Deputy Douglas County Surveyor, in 1960; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">COUNTY</td> <td style="padding: 0 5px;">SURVEYORS</td> <td style="padding: 0 5px;">OFFICE</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">T 23 S R 8 W</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 23   S 24</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">WIT.   COR.</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">1960</td> <td style="padding: 0 5px;"></td> </tr> </table> </div> <p>from which the remaining original bearing tree</p> <p>A fir, 64 ins. diam., bears S. 55° W., 15.2 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Whipple in 1894</p> <p>A fir snag, 26 ins. diam., bears S. 35° E., 12.5 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A pistol-butt maple, 15 ins. diam., bears N. 74° E., 20.4 ft. dist., mkd. AP S24 BT on bark.</p> <p>This cor. now functions as an angle point.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 06' 15" W., beginning new measurement.</p> | COUNTY | SURVEYORS | OFFICE |  | T 23 S R 8 W |  |  | S 23   S 24 |  |  | WIT.   COR. |  |  | 1960 |  |
| COUNTY | SURVEYORS   | OFFICE |           |        |  |              |  |  |             |  |  |             |  |  |      |  |
|        | T 23 S R 8 W  |        |           |        |  |              |  |  |             |  |  |             |  |  |      |  |
|        | S 23   S 24   |        |           |        |  |              |  |  |             |  |  |             |  |  |      |  |
|        | WIT.   COR.   |        |           |        |  |              |  |  |             |  |  |             |  |  |      |  |
|        | 1960  |        |           |        |  |              |  |  |             |  |  |             |  |  |      |  |
| 486.57 | <p>The cor. of secs. 13, 14, 23, and 24, perpetuated by Byron, Deputy Douglas County Surveyor, in 1960; as determined at record bearings and distances from the remains of the original bearing trees</p> <p>A fir, 27 ins. diam., bears N. 88° E., 19.8 ft. dist., with a healed blaze.</p>  |        |           |        |  |              |  |  |             |  |  |             |  |  |      |  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

|              |  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
|--------------|--|--------|-------|------|------|--|--|------|------|------|--|------|---------|------|--------------|------|
| FEET         | <p>A maple stump with sprouts up to 6 ins. diam. bears S. 21° E., 30.6 ft. dist., no marks visible. (Record, 31.7 ft. dist.)</p> <p>A fir snag, 30 ins. diam., bears S. 34° W., 18.7 ft. dist., with a healed blaze. (Record and slope dist., 21.1 ft. dist.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 23 S</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 8 W</td> </tr> <tr> <td style="padding: 0 10px;">S 14</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 13</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 5px 0 5px 10px;"></td> </tr> <tr> <td style="padding: 0 10px;">S 23</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 24</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">2015</td> </tr> </table> </div> <p>from which</p> <p>A fir, 15 ins. diam., bears S. 48 1/2° E., 32.9 dist., mkd. T23S R8W S24 BT.</p> <p>A fir, 9 ins. diam., bears S. 28° W., 39.0 dist., mkd. T23S R8W S23 BT.</p> <p>A fir, 17 ins. diam., bears N. 32 1/2° W., 33.3 dist., mkd. T23S R8W S14 BT. A fir, 8 ins. diam., is growing alongside.</p> <p>The Byron monument, an iron post, 32 ins. long, 1 1/2 ins. diam., with brass cap mkd. COUNTY SURVEYORS OFFICE T23S R8W S14 S13 S23 S24 1960, was found lying loose and determined to have been disturbed from its original position. Remove and dispose of the iron post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89° 58' 49" W., bet. secs. 23 and 26.</p> <p>645 Spring, output 1 ft. wide, course N. 30° E.</p> <p>1670 Creek, 1 ft. wide, course N. 45° W.</p> <p>2633.37 The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap, oriented S., mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">S 23</td> </tr> <tr> <td style="padding: 0 10px;">1/4 ———</td> </tr> <tr> <td style="padding: 0 10px;">S 26</td> </tr> <tr> <td style="padding: 0 10px;">T 23 S R 8 W</td> </tr> <tr> <td style="padding: 0 10px;">1964</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> | T 23 S | R 8 W | S 14 | S 13 |  |  | S 23 | S 24 | 2015 |  | S 23 | 1/4 ——— | S 26 | T 23 S R 8 W | 1964 |
| T 23 S       | R 8 W  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
| S 14         | S 13   |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
|              |  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
| S 23         | S 24   |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
| 2015         |  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
| S 23         |  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
| 1/4 ———      |  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
| S 26         |  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
| T 23 S R 8 W |  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |
| 1964         |  |        |       |      |      |  |  |      |      |      |  |      |         |      |              |      |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

|          |  |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
|----------|--|-----------|--------|-----------|--------|----------|--|-------|--|-------|--|-------|--|--|--|--|--|-------|--|-------|--|---------|--|--|--|------|--|--|--|
| FEET     | <p>A fir stump, 49 ins. diam., bears S. 39° E., 23.1 ft. dist., with illegible scribe marks visible on open blaze.</p> <p>and the remains of the bearing trees mkd. by Brooks and Peterson in 1964</p> <p>A fir stump, 40 ins. diam., bears S. 77 1/2° E., 51.5 ft. dist., with a healed blaze.</p> <p>A decayed fir stump, 22 ins. diam., bears N. 38° W., 87.1 ft. dist., with illegible scribe marks and reverse scribe marks visible from the top of a healed blaze. (Record, 88.4 ft. dist.)</p> <p>and new bearing trees</p> <p>A fir, 12 ins. diam., bears S. 35° W., 11.0 ft. dist., mkd. 1/4 S 26 BT.</p> <p>A fir, 15 ins. diam., bears N. 5° W., 18.2 ft. dist., mkd. 1/4 S23 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 52' 16" W., beginning new measurement.</p>   |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| 980      | Spur, slopes N.  |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| 1314.23  | From this point, a steel fence post established by person(s) unknown, and was not utilized for control in this survey, bears North, 2.53 ft. dist., with an affixed location tag marked for the W1/16 of secs. 23 and 26.  |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| 1915     | Ravine, drains N. 45° W.   |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| 2160     | Creek, 1 ft. wide, course N. 30° W.  |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| 2465     | Creek, 2 ft. wide, course N. 10° E.  |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| 2628.32  | <p>The cor. of secs. 22, 23, 26, and 27, perpetuated by Godfrey, Douglas County Surveyor, in 1962; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground (alongside of which is the original sandstone, 10 x 1 ins., firmly set, projecting 5 ins. above ground, with one notch on the SE. edge), with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="2" style="padding: 0 10px;">COUNTY</td> <td style="padding: 0 10px;">SURVEYORS</td> <td style="padding: 0 10px;">OFFICE</td> </tr> <tr> <td style="padding: 0 5px;">T. 23 S.</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S. 23</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S. 22</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S. 26</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 0 5px;"></td> <td colspan="2" style="border-top: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S. 27</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S. 26</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">R. 8 W.</td> <td colspan="2" style="padding: 0 5px;"></td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1962</td> <td colspan="2" style="padding: 0 5px;"></td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p>A roothole bears S. 25 1/2° W., 91.1 ft. dist., alongside of which is a down fir, 50 ins. diam., with a healed blaze.</p> | COUNTY    |        | SURVEYORS | OFFICE | T. 23 S. |  | S. 23 |  | S. 22 |  | S. 26 |  |  |  |  |  | S. 27 |  | S. 26 |  | R. 8 W. |  |  |  | 1962 |  |  |  |
| COUNTY   |  | SURVEYORS | OFFICE |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| T. 23 S. |  | S. 23     |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| S. 22    |  | S. 26     |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
|          |  |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| S. 27    |  | S. 26     |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| R. 8 W.  |  |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |
| 1962     |  |           |        |           |        |          |  |       |  |       |  |       |  |  |  |  |  |       |  |       |  |         |  |  |  |      |  |  |  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

|        |  |             |           |        |     |                               |             |
|--------|--|-------------|-----------|--------|-----|-------------------------------|-------------|
| FEET   | <p>and the remains of the bearing trees mkd. by Godfrey</p> <p>A fir, 9 ins. diam., bears N. 34 1/2° E., 22.6 ft. dist., with a healed double blaze.</p> <p>A fir, 23 ins. diam., bears S. 0 3/4° W., 37.5 ft. dist., with a healed blaze.</p> <p>A fir, 31 ins. diam., bears S. 7° W., 42.1 ft. dist., with a healed blaze.</p> <p>A fir stump, 39 ins. diam., bears N. 6° W., 27.5 ft. dist., with a healed double blaze.</p> <p>and new accessories</p> <p>A cedar, 22 ins. diam., bears S. 20° E., 72.6 ft. dist., mkd. T23S R8W S26 BT.</p> <p>An iron rod, 30 ins. long, 5/8 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 34° 59' 02" W, 13.28 ft. dist., with aluminum cap mkd. RM T23S R8W 13.3 FT TO COR S22 2015, and an arrow pointing to the cor.</p> <p>A steel fence post is alongside the cor.</p> <p>Corner is located on the SE. cor. of fir reproduction, edge bears N. and W.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23, perpetuated by the Douglas County Surveyor's Office in 1967; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with a brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border: none;"> <tr> <td style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center; vertical-align: middle;">SURVEYORS</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">1/4</td> <td style="text-align: center; vertical-align: middle;">T 23 S<br/>S 22   S 23<br/>1967</td> <td style="text-align: center; vertical-align: middle;">R<br/>8<br/>W</td> </tr> </table> <p>from which the remains of an original bearing tree</p> <p>A fir stump, 62 ins. diam., bears N. 36° W., 22.4 ft. dist., with no marks visible on open blaze.</p> <p>and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A fir, 15 ins. diam., bears S. 52° E., 13.6 ft. dist., with a healed blaze.</p> <p>A fir snag, 12 ins. diam., bears S. 69 1/4° W., 4.1 ft. dist., with a healed blaze.</p> <p>A fir, 13 ins. diam., bears N. 28 1/2° W., 7.5 ft. dist., with a healed blaze.</p> <p>An iron rod is alongside the cor.</p> | COUNTY      | SURVEYORS | OFFICE | 1/4 | T 23 S<br>S 22   S 23<br>1967 | R<br>8<br>W |
| COUNTY | SURVEYORS  | OFFICE      |           |        |     |                               |             |
| 1/4    | T 23 S<br>S 22   S 23<br>1967  | R<br>8<br>W |           |        |     |                               |             |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |  |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
|---------|--|------|-----------|--|--|--|--------|--|--|--------|------|------|--------|----------------------------|--|--|------|------|--|--|-------|--|--|--|------|--|--|
| 1314.92 | <p>N. 0° 07' 56" E., bet. secs. 22 and 23.</p> <p>The N 1/16 sec. cor. of secs. 22 and 23, established by Roberts, PLS No. 1039, in 1980; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>PLS 1039<br/>S 22   S 23<br/>N • 1/16<br/>T 23 S R 8 W<br/>1980</p> </div> <p>from which the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 47 ins. diam., bears N. 88 1/2° E., 23.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A maple, 17 ins. diam., bears N. 2° W., 35.0 ft. dist., with a healed blaze.</p> <p>An iron rod with an International Paper sign is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 01' 56" E., beginning new measurement.</p>   |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
| 295     | Mehl Creek, 7 ft. wide, course S. 20° E.   |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
| 515     | Graveled road, 10 ft. wide, bears N. 65° W. and S. 65° E.  |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
| 1313.28 | <p>The cor. of secs. 14, 15, 22, and 23, perpetuated by the Douglas County Surveyor's Office in 1967; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td colspan="2">SURVEYORS</td> <td></td> </tr> <tr> <td></td> <td colspan="2">T 23 S</td> <td></td> </tr> <tr> <td rowspan="2" style="writing-mode: vertical-rl; transform: rotate(180deg);">COUNTY</td> <td>S 15</td> <td>  S 14</td> <td rowspan="2" style="writing-mode: vertical-rl; transform: rotate(180deg);">OFFICE</td> </tr> <tr> <td colspan="2"><hr style="width: 100%;"/></td> </tr> <tr> <td></td> <td>S 22</td> <td>  S 23</td> <td></td> </tr> <tr> <td></td> <td colspan="2">R 8 W</td> <td></td> </tr> <tr> <td></td> <td colspan="2">1967</td> <td></td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir stump, 43 ins. diam., bears N. 5° E., 15.2 ft. dist., with remains of a healed blaze.</p> <p>and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A decayed fir snag, 9 ins. diam., bears N. 40 1/2° E., 54.0 ft. dist., with remains of a healed blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 43 1/2° E., 24.2 ft. dist., with a healed blaze.</p> |      | SURVEYORS |  |  |  | T 23 S |  |  | COUNTY | S 15 | S 14 | OFFICE | <hr style="width: 100%;"/> |  |  | S 22 | S 23 |  |  | R 8 W |  |  |  | 1967 |  |  |
|         | SURVEYORS  |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
|         | T 23 S   |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
| COUNTY  | S 15   | S 14 | OFFICE    |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
|         | <hr style="width: 100%;"/>   |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
|         | S 22   | S 23 |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
|         | R 8 W  |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |
|         | 1967   |      |           |  |  |  |        |  |  |        |      |      |        |                            |  |  |      |      |  |  |       |  |  |  |      |  |  |

23408

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |   |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|---------|---|-----------|--------|-----------|--------|--|--|--------|--|--|--|--------|--|--|--|-----------|--|--|--|--------|--|--|--|------|--|
|         | <p>A decayed white fir stump, size indeterminate, bears S. 50° W., 24.0 ft. dist., no marks visible.</p> <p>A decayed white fir stump, size indeterminate, bears N. 27° W., 39.7 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A hemlock, 14 ins. diam., bears N. 46° E., 10.2 ft. dist., mkd. T23S R8W S14 BT.</p> <p>A fir, 15 ins. diam., bears S. 20° W., 19.3 ft. dist., mkd. T23S R8W S22 BT.</p> <p>A hemlock, 12 ins. diam., bears N. 57° W., 7.7 ft. dist., mkd. T23S R8W S15 BT.</p> <p>An iron rod is alongside the cor.</p> <hr/>  |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|         | <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89° 30' 01" W., bet. secs. 14 and 23.</p>   |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
| 295     | Spur, slopes S. 25° W.  |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
| 1300    | Creek, dry, 2 ft. wide, course S. 30° W.  |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
| 310.13  | Point for the E 1/16 sec. cor. of secs. 14 and 23. Not monumented.  |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
| 2160    | Spur, slopes S.   |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
| 2585    | North end of graveled road, 12 ft. wide, bears S. 20° W.  |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
| 2620.26 | The 1/4 sec. cor. of secs. 14 and 23, perpetuated by the Douglas County Surveyor's Office in 1967; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.   |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|         | <table border="0" style="margin-left: auto; margin-right: auto;"><tr><td></td><td style="text-align: center;">COUNTY</td><td style="text-align: center;">SURVEYORS</td><td style="text-align: center;">OFFICE</td></tr><tr><td></td><td></td><td style="text-align: center;">T 23 S</td><td></td></tr><tr><td></td><td></td><td style="text-align: center;">S 14 R</td><td></td></tr><tr><td></td><td></td><td style="text-align: center;">1/4 ——— 8</td><td></td></tr><tr><td></td><td></td><td style="text-align: center;">S 23 W</td><td></td></tr><tr><td></td><td></td><td style="text-align: center;">1967</td><td></td></tr></table> |           | COUNTY | SURVEYORS | OFFICE |  |  | T 23 S |  |  |  | S 14 R |  |  |  | 1/4 ——— 8 |  |  |  | S 23 W |  |  |  | 1967 |  |
|         | COUNTY  | SURVEYORS | OFFICE |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|         |   | T 23 S    |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|         |   | S 14 R    |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|         |   | 1/4 ——— 8 |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|         |   | S 23 W    |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|         |   | 1967      |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |
|         | <p>from which the remains of the original bearing trees</p> <p>A decayed fir stump, 38 ins. diam., bears N. 58° E., 9.2 ft. dist., with no marks visible on open blaze. (Record, N. 64° E.)</p> <p>A madrone snag, 18 ins. diam., bears S. 72° E., 32.3 ft. dist., with illegible scribe marks visible on partially healed blaze at waist height and no marks visible on decayed partially healed blaze at base.</p>  |           |        |           |        |  |  |        |  |  |  |        |  |  |  |           |  |  |  |        |  |  |  |      |  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |  |
|---------|--|
|         | <p>and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A decayed fir high stump, 11 ins. diam., bears N. 40 1/2° E., 25.0 ft. dist., with a healed blaze. Stump leans W.</p> <p>A fir, 27 ins. diam., bears S. 26° E., 42.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 9 ins. diam., bears N. 32 3/4° E., 24.9 ft. dist., mkd. 1/4 S14 BT.</p> <hr/> <p>S. 89° 52' 20" W., beginning new measurement.</p>  |
| 260     | Creek, 3 ft. wide, course N. 5° W.   |
| 805     | Spur, slopes S.  |
| 970     | Ravine, drains S. 10° E.   |
| 1307.68 | <p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 14<br/> W 1/16 ———<br/> S 23<br/> 2015</p> </div> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 12 1/4° E., 14.9 dist., mkd. W1/16 S14 BT.</p> <p>A fir, 10 ins. diam., bears S. 58° W., 10.9 dist., mkd. W1/16 S23 BT.</p> <p>From this cor., a steel fence post, established by person(s) unknown, and was not utilized for control in this survey, bears S. 8° 55' 48" W., 0.55 ft. dist., with an affixed location tag marked for the W1/16.</p> |
| 1315    | Spur, slopes S.  |
| 1885    | Creek, dry, 2 ft. wide, course S. 20° W.   |
| 2305    | Spur, slopes S.  |
| 2615.36 | <p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p>   |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

|         |   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|---------|---|--|-----------|--|--|--|--------|--|--|--------|------|--|--------|--|-------|--|--|--|------|--|--|--|-------|--|--|--|------|--|--|
| FEET    | N. 89° 38' 10" W., bet. secs. 22 and 27.  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 430     | Spur, slopes N. 55° E.  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 1440    | Graveled road, 10 ft. wide, bears N. 10° E. and S. 10° W.   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 1685    | Creek, 1 ft. wide, course N. 60° E.   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 1800    | Top of ascent, slopes N. 20° W.   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 2000    | Top of rock face, 75 ft. high, slopes N. Continue along rock face.  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 2190    | End of rock face, 35 ft. high.  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 2671.57 | The 1/4 sec. cor. of secs. 22 and 27, perpetuated by Langlitz, Deputy Douglas County Surveyor, in 1974; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 11 ins. above ground (alongside of which is the original sandstone, 6 x 3 ins., firmly set, projecting 6 ins. above ground, with 1/4 on the N. face), with a brass cap mkd.  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">T 23 S</td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">COUNTY</td> <td style="text-align: center;">S 22</td> <td></td> <td style="text-align: center;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">— 1/4</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S 27</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R 8 W</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1974</td> <td></td> <td></td> </tr> </table> |  | SURVEYORS |  |  |  | T 23 S |  |  | COUNTY | S 22 |  | OFFICE |  | — 1/4 |  |  |  | S 27 |  |  |  | R 8 W |  |  |  | 1974 |  |  |
|         | SURVEYORS   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | T 23 S  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| COUNTY  | S 22  |  | OFFICE    |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | — 1/4   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | S 27  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | R 8 W   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | 1974  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | from which the remains of the bearing trees mkd. by Langlitz  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | A cedar snag, 12 ins. diam., bears N. 63 3/4° E., 41.5 ft. dist., with scribe marks 1/4 S22 CS visible on open double blaze.  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | A decayed hemlock stump, size indeterminate, bears S. 38° E., 3.0 ft. dist., no marks visible and the decayed hemlock log alongside.  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | and new bearing trees   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | A fir, 12 ins. diam., bears N. 2 1/2° E., 10.9 ft. dist., mkd. 1/4 S22 BT.  |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | A fir, 12 ins. diam., bears S. 10° E., 10.7 ft. dist., mkd. 1/4 S27 BT.   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | _____   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
|         | N. 89° 35' 39" W., beginning new measurement.   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 160     | Creek, 2 ft. wide, course N. 20° W.   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 785     | Creek, 1 ft. wide, course N. 40° W.   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |
| 1329.27 | The W 1/16 sec. cor. of secs. 22 and 27, established by Roberts, PLS No. 1039, in January, 1981; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.   |  |           |  |  |  |        |  |  |        |      |  |        |  |       |  |  |  |      |  |  |  |       |  |  |  |      |  |  |

23411

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

|         |  |
|---------|--|
| FEET    | <p style="text-align: center;">           PLS 1039<br/>           W 1/16<br/>           T23S <u>    </u> S 22 R8W<br/>                     S 27<br/>                     1981         </p> <p>from which the remains of the bearing trees mkd. by Roberts</p> <p>A yew stump, 22 ins. diam., bears S. 65° E., 41.2 ft. dist., with scribe marks W1/16 S27 visible on open blaze.</p> <p>A hemlock, 31 ins. diam., bears N. 12° W., 22.6 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 16 ins. diam., bears S. 41° E., 39.3 ft. dist., mkd. W1/16 S27 BT.</p> <p>An iron rod is alongside the cor.</p> <p>Drive an aluminum angle iron alongside the cor.</p> <p>Corner is located on the upper face of a small slide, bears W.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 35' 18" W., beginning new measurement.</p> |
| 160     | Creek, 3 ft. wide, course N. 20° E.  |
| 1329.14 | <p>The cor. of secs. 21, 22, 27, and 28, monumented with a brass tablet, 3 1/4 ins. diam., firmly set, with top flush with the surface of solid rock, with top mkd.</p> <p style="text-align: center;">           DOUGLAS <span style="margin: 0 10px;">CO. SURVEYORS</span> OFFICE<br/>           T 23 S R 8 W<br/>           S 21   S 22<br/>           ————<br/>           S 28   S 27<br/>           1974         </p> <p>from which the remains of the bearing trees mkd. by Langlitz, Deputy Douglas County Surveyor's in 1974 and reported by Farmer</p> <p>A fir high stump, 15 ins. diam., bears S. 69° W., 34.3 ft. dist., with a healed blaze.</p> <p>A fir, 21 ins. diam., bears N. 69° W., 21.8 ft. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by Farmer in 1986</p>   |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |   |  |     |    |     |  |      |  |  |  |      |
|---------|---|--|-----|----|-----|--|------|--|--|--|------|
|         | <p>A fir, 18 ins. diam., bears S. 64 3/4° E., 40.3 ft. dist., with a healed blaze.<br/>and new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 22 1/4° E., 41.2 ft. dist., mkd. T23S R8W S21 BT.</p> <p>A fir, 6 ins. diam., bears S. 76° W., 27.0 ft. dist., mkd. X BT.</p> <p>Drive an aluminum angle iron 4 1/2 ft. northerly of the cor.</p> <p>Corner is located on steep bare rock face, 50 ft. wide, slopes NE.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>S. 89° 39' 13" W., bet. secs. 15 and 22.</p>  |  |     |    |     |  |      |  |  |  |      |
| 580     | Creek, dry, 1 ft. wide, course S. 45° W., in bottom, 30 ft. wide.   |  |     |    |     |  |      |  |  |  |      |
| 1225    | Creek, 2 ft. wide, course S. 5° W.  |  |     |    |     |  |      |  |  |  |      |
| 2140    | Creek, dry, 1/2 ft. wide, course S. 40° E.  |  |     |    |     |  |      |  |  |  |      |
| 2654.07 | <p>The 1/4 sec. cor. of secs. 15 and 22, reestablished by proportionate measurement by Roberts, PLS No. 1039, in January, 1981. There is no remaining evidence of the original cor., therefore this point is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a damaged brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td></td> <td style="text-align: center;">PLS</td> </tr> <tr> <td style="text-align: center;">23</td> <td style="text-align: center;">1/4</td> </tr> <tr> <td></td> <td style="text-align: center;">S 15</td> </tr> <tr> <td></td> <td style="text-align: center;"><hr style="width: 50px; margin: 0 auto;"/></td> </tr> <tr> <td></td> <td style="text-align: center;">S 22</td> </tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Roberts</p> <p>A decayed fir stump, 66 ins. diam., bears S. 18° W., 85.6 ft. dist., no marks visible.</p> <p>A burned decayed fir stump, 39 ins. diam., bears N. 79° W., 24.4 ft. dist., with scribe marks 1/4 S15 visible on open blaze at chest height and illegible scribe marks visible on partially healed blaze at base.</p> <p>and new bearing trees</p> <p>A fir, 7 ins. diam., bears N., 30.6 ft. dist., mkd. 1/4 S15 BT.</p> <p>A fir, 10 ins. diam., bears S. 49° W., 9.7 ft. dist., mkd. 1/4 S22 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> |  | PLS | 23 | 1/4 |  | S 15 |  | <hr style="width: 50px; margin: 0 auto;"/> |  | S 22 |
|         | PLS   |  |     |    |     |  |      |  |  |  |      |
| 23      | 1/4   |  |     |    |     |  |      |  |  |  |      |
|         | S 15  |  |     |    |     |  |      |  |  |  |      |
|         | <hr style="width: 50px; margin: 0 auto;"/>  |  |     |    |     |  |      |  |  |  |      |
|         | S 22  |  |     |    |     |  |      |  |  |  |      |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

|           |   |           |  |        |      |      |      |      |      |       |  |      |  |
|-----------|---|-----------|--|--------|------|------|------|------|------|-------|--|------|--|
| FEET      | <p>S. 89° 37' 40" W., beginning new measurement.</p>  |           |  |        |      |      |      |      |      |       |  |      |  |
| 625       | <p>Creek, 4 ft. wide, course S. 30° E.</p>  |           |  |        |      |      |      |      |      |       |  |      |  |
| 955       | <p>House-sized boulder on top of spur, slopes S. 35° E.</p>   |           |  |        |      |      |      |      |      |       |  |      |  |
| 2654.24   | <p>The cor. of secs. 15, 16, 21, and 22, perpetuated by the Douglas County Surveyor's Office in 1967; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 0 10px;">SURVEYORS</td> </tr> <tr> <td style="padding: 0 5px;">T 23 S</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td style="padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td style="padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">R 8 W</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1967</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <ul style="list-style-type: none"> <li>A fir high stump, 35 ins. diam., bears S. 66° E., 12.5 ft. dist., with illegible scribe marks visible on open blaze.</li> <li>A decayed fir high stump, 15 ins. diam., bears N. 77° W., 22.2 ft. dist., with a decayed healed blaze. (Record, 23.1 ft. dist.)</li> </ul> <p>and the remains of a bearing tree mkd. by person(s) unknown, as reported by Roberts, PLS 1039, in January, 1981</p> <ul style="list-style-type: none"> <li>A tin-capped fir stump, 19 ins. diam., bears S. 87° W., 7.3 ft. dist., with no marks visible on open decayed blaze.</li> </ul> <p>and new bearing trees</p> <ul style="list-style-type: none"> <li>A fir, 7 ins. diam., bears N. 5° E., 11.0 ft. dist., mkd. X BT.</li> <li>A fir, 15 ins. diam., bears S. 76° E., 53.3 ft. dist., mkd. T23S R8W S22 BT.</li> <li>A fir, 12 ins. diam., bears S. 32° W., 14.5 ft. dist., mkd. T23S R8W S21 BT.</li> <li>A fir, 15 ins. diam., bears N. 80° W., 16.6 ft. dist., mkd. T23S R8W S16 BT.</li> </ul> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 16, 17, 20, and 21, perpetuated by the Douglas County Surveyor's Office in 1966; further perpetuated by Rice, PLS No. 54633, in 2010; monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with a brass cap mkd.</p> | SURVEYORS |  | T 23 S | S 15 | S 16 | S 22 | S 21 | S 22 | R 8 W |  | 1967 |  |
| SURVEYORS |   |           |  |        |      |      |      |      |      |       |  |      |  |
| T 23 S    | S 15  |           |  |        |      |      |      |      |      |       |  |      |  |
| S 16      | S 22  |           |  |        |      |      |      |      |      |       |  |      |  |
| S 21      | S 22  |           |  |        |      |      |      |      |      |       |  |      |  |
| R 8 W     |   |           |  |        |      |      |      |      |      |       |  |      |  |
| 1967      |   |           |  |        |      |      |      |      |      |       |  |      |  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET |   |
|------|---|
|      | <p>T 23<br/>S 17   S 16<br/>-----<br/>S 20   S 21<br/>R 8 W<br/>1966</p>  |
|      | from which the remains of the original bearing trees  |
|      | A decayed fir stump, 65 ins. diam., bears S. 24° W., 17.2 ft. dist., with no marks visible on open blaze. (Record and slope dist., 21.8 ft. dist.)                        |
|      | A decayed fir stump, 58 ins. diam., bears N. 18° W., 52.1 ft. dist., no marks visible.  |
|      | and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office   |
|      | A decayed hemlock stump, size indeterminate, bears N. 61° E., 22.2 ft. dist., no marks visible. Replace tin cap found lying alongside.                                    |
|      | A decayed hemlock stump, size indeterminate, bears S. 60 1/2° W., 11.4 ft. dist., with remains of a healed blaze.   |
|      | and the bearing trees mkd. by Rice  |
|      | A fir, 17 ins. diam., bears N. 24° E., 22.4 ft. dist., with illegible scribe marks visible on partially healed blaze and a nail at the base on the right side center.     |
|      | A fir, 19 ins. diam., bears S. 51 1/2° E., 10.5 ft. dist., with a healed blaze and a nail at the base on the left side center.  |
|      | A fir, 18 ins. diam., bears S. 55 1/4° W., 15.6 ft. dist., with illegible scribe marks visible on partially healed blaze and a nail at the base on the right side center. |
|      | A fir, 15 ins. diam., bears N. 66° W., 16.0 ft. dist., with a healed blaze and a nail at the base on the left side center.  |
|      | An aluminum fence post is alongside the cor.  |
|      | N. 0° 30' 00" E., bet. secs. 16 and 17.   |
| 490  | Ravine, drains N. 55° W.  |
| 915  | Ravine, drains N. 40° W.  |
| 985  | Top of ascent, slopes W.  |
| 1305 | Ravine, drains N. 40° W.  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |   |
|---------|---|
| 1450    | Top of ascent, slopes W.  |
| 1825    | Creek, 1 ft. wide, course N. 50° W.   |
| 2626.46 | <p>The 1/4 sec. cor. of secs. 16 and 17, reestablished by proportionate measurement by Mulkins, PLS No. 2006, in 1995, filed in 2015. There is no remaining evidence of the original cor., therefore this point is accepted as the cor.; monumented with an aluminum rod, 3/4 ins. diam., firmly set, projecting 6 ins. above ground, with an aluminum cap mkd.</p> <p align="center">           RLS 2006<br/>           1/4<br/>           S 17   S 16<br/>           T 23 S R 8 W<br/>           1995         </p> <p>from which the bearing trees mkd. by Mulkins</p> <p>A fir, 18 ins. diam., bears S. 80° E., 9.8 ft. dist., with a healed blaze and a nail at the base on the right side center.</p> <p>A fir, 16 ins. diam., bears S. 5° E., 11.8 ft. dist., with a healed blaze and a nail at the base on the right side center.</p> <p>A fir, 19 ins. diam., bears N. 53 1/2° W., 10.4 ft. dist., with a healed blaze and a nail at the base on the left side center.</p> <p>A fir, 19 ins. diam., bears N. 1/2° W., 38.7 ft. dist., with a healed blaze and a nail at the base on the left side center.</p> <p>An aluminum fence post is alongside the cor..</p> <p>From this cor., the steel fence post reported by Mulkins bears S. 58° 47' 54" W., 5.40 ft. dist.</p> <p>A search was made for all original line trees bet. secs. 16 and 17 and none were recovered.</p> <hr/> <p>N. 0° 31' 35" E., beginning new measurement.</p> |
| 515     | Spur, slopes N. 25° W.  |
| 1155    | Creek, 5 ft. wide, course N. 45° W.   |
| 1885    | Creek, 1 ft. wide, course S. 30° W.   |
| 2625.92 | <p>The cor. of secs. 8, 9, 16, and 17, perpetuated by the Douglas County Surveyor's Office in 1973; monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground (alongside of which is an iron pipe, 2 ins. diam., firmly set, projecting 13 ins. above ground), with a brass cap mkd.</p>   |

23416

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET |   |
|------|---|
|      | <p style="text-align: center;">T 23 S R 8 W<br/>S 8   S 9<br/>-----<br/>S 17   S 16<br/>1958</p> <p>from which the remains of the bearing trees mkd. by Gawron in 1958</p> <p>A fir snag, 42 ins. diam., bears N. 12° E., 150.5 ft. dist., no marks visible.</p> <p>A white fir high stump, 26 ins. diam., bears S. 47 1/2° E., 195.4 ft. dist., with a healed blaze.</p> <p>A decayed white fir stump, size indeterminate, bears S. 26° W., 114.2 ft. dist., no marks visible.</p> <p>A decayed fir stump, size indeterminate, bears N. 15° W., 27.7 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office and reported by Gawron</p> <p>A fir, 18 ins. diam., bears N. 51° E., 11.3 ft. dist., with a healed blaze.</p> <p>A hemlock high stump, 17 ins. diam., bears S. 75° E., 18.5 ft. dist., with a healed blaze. (Record, white fir.)</p> <p>A fir, 25 ins. diam., bears N. 41° W., 19.5 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p>An iron rod, 30 ins. long, 5/8 ins. diam., set 27 ins. in the ground for a reference monument, bears S. 54° 13' 47" E, 29.93 ft. dist., with aluminum cap mkd. RM T23S R8W S16 29.9 FT TO COR 2015, and an arrow pointing to the cor.</p> <p>A fir, 19 ins. diam., bears S. 73° W., 44.2 ft. dist., mkd. T23S R8W S17 BT.</p> <p>Corner is located on the NW. cor. of young fir reproduction, edge bears S. and E. A steel fence post is alongside the cor.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 23,<br/>T. 23 S., R. 8 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 04' 55" W., on the N. and S. center line of sec. 23.</p> <p>2637.81 The center 1/4 sec. cor. of sec. 23, established by Roberts, PLS No. 1039, in February, 1981; and is accepted as the cor.; monumented with an iron post,</p> |

23417

Subdivision of Section 23,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |   |
|---------|---|
|         | <p>1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">PLS 1039<br/>T23S C 1/4 R8W<br/>S 23<br/>1981</p> <p>from which the remains of the bearing trees mkd. by Roberts</p> <p>A decayed fir stump, 19 ins. diam., bears N. 20° E., 14.9 ft. dist., no marks visible.</p> <p>A decayed tin-capped fir stump, 23 ins. diam., bears S. 46° E., 43.3 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears S. 19 1/2° E., 47.9 ft. dist., mkd. C1/4 S23 BT.</p> <p>A fir, 9 ins. diam., bears S. 31° W., 14.9 ft. dist., mkd. X BT.</p> <p>A steel fence post is alongside the cor., which is in the roots of a fir, 22 ins. diam., on the NE. side.</p> <hr/> <p>N. 0° 06' 00" W., beginning new measurement.</p> |
| 790     | Mehl Creek, 15 ft. wide, course S. 50° E.   |
| 1055    | Graveled road, 8 ft. wide, bears N. 50° W. and S. 70° E.  |
| 1313.54 | <p>The center N 1/16 sec. cor. of sec. 23, established by Roberts, PLS No. 1039, in February, 1981; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">PLS 1039<br/>T23S CN • 1/16 R8W<br/>S 23<br/>1981</p> <p>from which the bearing trees mkd. by Roberts</p> <p>A fir, 25 ins. diam., bears N. 26° E., 32.8 ft. dist., with a healed blaze.</p> <p>A fir, 22 ins. diam., bears S. 4 1/2° E., 43.7 ft. dist., with a healed blaze.</p> <p>An iron rod with an International Paper sign is alongside the cor.</p> <hr/> <p>N. 0° 06' 30" W., beginning new measurement.</p>  |

23418

Subdivision of Section 23,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |  |
|---------|--|
| 1313.73 | The 1/4 sec. cor. of secs. 14 and 23.<br><hr/>   |
|         | From the 1/4 sec. cor. of secs. 23 and 24.<br>S. 89° 51' 58" W., on the E. and W. center line of sec. 23.  |
| 465     | Creek, 2 ft. wide, course N. 25° W.  |
| 1313.00 | The center E 1/16 sec. cor. of sec. 23, established by Roberts, PLS No. 1039, in February, 1981; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.               |
|         | <p style="text-align: center;">PLS 1039<br/>CE • 1/16 R8W<br/>S 23<br/>1981<br/>T23S</p>   |
|         | from which the remains of the bearing trees mkd. by Roberts<br><br>A decayed white fir snag, 18 ins. diam., bears S. 47° W., 28.7 ft. dist., with a healed blaze.<br><br>A fir snag, 39 ins. diam., bears N. 70° W., 66.6 ft. dist., with a healed blaze.      |
|         | and new bearing trees  |
|         | A maple, 14 ins. diam., bears N. 19 1/2° E., 22.3 ft. dist., mkd. CE1/16 S23 BT on bark.   |
|         | A hemlock, 15 ins. diam., bears S. 57° W., 34.0 ft. dist., mkd. CE1/16 S23 BT.   |
|         | An iron rod with an International Paper sign is alongside the cor.<br><hr/>  |
|         | S. 89° 50' 53" W., beginning new measurement.  |
| 280     | Creek, 1 ft. wide, course N. 10° W.  |
| 705     | Creek, 2 ft. wide, course N. 55° E.  |
| 1313.21 | The center 1/4 sec. cor. of sec. 23.<br><hr/>  |
|         | S. 89° 48' 53" W., beginning new measurement.  |
| 1313.47 | The center W 1/16 sec. cor. of sec. 23, established by Roberts, PLS No. 1039, in February, 1981; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd. |

23419

Subdivision of Section 23,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |  |
|---------|--|
|         | <p style="text-align: center;">T23S      PLS 1039<br/>            CW • 1/16      R8W<br/>            S 23<br/>            1981</p> <p>from which the remains of the bearing trees mkd. by Roberts</p> <p>A decayed fir stump, 17 ins. diam., bears N. 88 1/2° W., 16.4 ft. dist., no marks visible.</p> <p>A decayed fir snag, 9 ins. diam., bears N. 7 1/2° W., 60.6 ft. dist., with scribe marks CW1/16 BT visible on open blaze.</p> <p>and new bearing trees</p> <p>A fir, 19 ins. diam., bears S. 8° E., 15.6 ft. dist., mkd. CW1/16 S23 BT.</p> <p>A fir, 10 ins. diam., bears N. 10° W., 15.7 ft. dist., mkd. X BT.</p> <p>An iron rod with an International Paper sign is alongside the cor.</p> <p>From this cor., a point established as the center W 1/16 sec. cor. of sec. 23 in an administrative survey for the BLM by the FHA, in 1977, and was not utilized for control in this survey, bears S. 20° 48' 23" W., 0.62 ft. dist., determined at record bearings and distances from the remains of the bearing trees mkd. by FHA</p> <p>Fir remains, size indeterminate, bears S. 17° E., 5.0 ft. dist., no marks visible.</p> <p>A decayed fir snag, 11 ins. diam., bears N. 15° W., 21.3 ft. dist., with no marks visible on open blaze.</p> <hr/> |
|         | <p>S. 89° 53' 26" W., beginning new measurement.</p>   |
| 45      | <p>Creek, 1 ft. wide, course N. 30° W.</p>   |
| 1005    | <p>Creek, 5 ft. wide, course N.</p>  |
| 1310.76 | <p>The 1/4 sec. cor. of secs. 22 and 23.</p> <hr/>   |
|         | <p>From the center E 1/16 sec. cor. of sec. 23.</p> <p>N. 0° 09' 39" W., on the N. and S. center line of the NE 1/4 of sec. 23.</p>  |
| 1317.16 | <p>The NE 1/16 sec. cor. of sec. 23, established by Roberts, PLS No. 1039, in February, 1981; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p>   |

23420

Subdivision of Section 23,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |  |
|---------|--|
|         | <p style="text-align: center;">T23S      PLS 1039      R8W<br/>            NE • 1/16<br/>            S 23<br/>            1981</p>   |
|         | <p>from which the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 47 1/2° E., 33.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 61° E., 105.9 ft. dist., with a healed blaze.</p> <p>An iron rod is alongside the cor.</p> <p style="text-align: center;">_____</p> <p>N. 0° 10' 33" W., beginning new measurement.</p> |
| 1318.06 | <p>The E 1/16 sec. cor. of secs. 14 and 23.</p> <p style="text-align: center;">_____</p>   |
|         | <p>From the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>S. 89° 40' 58" W., on the E. and W. center line of the NE 1/4 of sec. 23.</p>  |
| 1310.47 | <p>The NE 1/16 sec. cor. of sec. 23.</p> <p style="text-align: center;">_____</p>  |
|         | <p>S. 89° 41' 23" W., beginning new measurement.</p>   |
| 650     | <p>Graveled road, 8 ft. wide, bears N. 50° E. and S. 50° W.</p>  |
| 1311.74 | <p>The center N 1/16 sec. cor. of sec. 23.</p> <p style="text-align: center;">_____</p>  |
|         | <p>From the center W 1/16 sec. cor. of sec. 23.</p>  |
|         | <p>N. 0° 03' 05" E., on the N. and S. center line of the NW 1/4 of sec. 23.</p>  |
| 590     | <p>Graveled road, 12 ft. wide, bears N. 65° E. and S. 65° W.</p>   |
| 815     | <p>Mehl Creek, 15 ft. wide, course S. 75° E.</p>   |
| 1050    | <p>Graveled road, 12 ft. wide, bears N. 50° W. and S. 30° E.</p>   |
| 1314.03 | <p>The NW 1/16 sec. cor. of sec. 23, established by Roberts, PLS No. 1039, in February, 1981; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p>   |
|         | <p style="text-align: center;">T23S      PLS 1039      R8W<br/>            NW • 1/16<br/>            S 23<br/>            1981</p>   |

23421

**Subdivision of Section 23,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |  |
|---------|--|
|         | <p>from which the bearing trees mkd. by Roberts</p> <p>A fir, 52 ins. diam., bears N. 82 3/4° E., 27.6 ft. dist., with a healed blaze.</p> <p>A fir, 23 ins. diam., bears S. 47 3/4° W., 31.9 ft. dist., with a healed blaze.</p> <p>A steel fence post and an iron rod, both with International Paper signs, are alongside the cor.</p> <hr/> |
| 1314.58 | <p>N. 0° 00' 51" W., beginning new measurement.</p> <p>The W 1/16 sec. cor. of secs. 14 and 23.</p> <hr/>  |
| 1309.92 | <p>From the center N 1/16 sec. cor. of sec. 23.</p> <p>S. 89° 50' 08" W., on the E. and W. center line of the NW 1/4 of sec. 23.</p> <p>The NW 1/16 sec. cor. of sec. 23.</p> <hr/>  |
| 585     | <p>S. 89° 55' 46" W., beginning new measurement.</p> <p>Graveled road, 12 ft. wide, bears N. 50° W. and S. 50° E.</p>  |
| 945     | <p>Mehl Creek, 15 ft. wide, course S.</p>  |
| 1308.83 | <p>The N 1/16 sec. cor. of secs. 22 and 23.</p> <hr/>  |