

TOWNSHIP 29 SOUTH, RANGE 3 WEST, OF THE WILLAMETTE MERIDIAN, OREGON
DEPENDENT RESURVEY

SHEET 3 OF 3

FILED

Date: 8/21/2017 By: JC

This survey consists of:
Map: PLAT: T29-3 2017-1 (a PCS)

Narrative: VOL. 58 PAGES
Corner Rpt: 23423-23425

NO SEPARATE LINE NOTES
ALL INFORMATION CONTAINED
HEREIN IS UNCLASSIFIED
DATE 08-21-2017 BY 60281/2017
DOUGLAS COUNTY
SURVEYOR

(G) The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 29 S R 3 W
S 20
1/4 S 29
1980

from which bearing trees mkd. by Jelley and Rogers in 1979-80

A fir, 23 ins. diam., bears S 24° W., 41.6 ft. dist., with a healed double blaze. (Record, S. 24 1/2° E.)

A cedar, 18 ins. diam., bears N. 12 1/2° W., 42.9 ft. dist., with a healed double blaze.

The iron pipe, 3/4 in. diam., firmly set, projecting 3 ins. above ground, reset by Jelley and Rogers, is alongside the cor.

(F) The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T 29 S R 3 W
S 20 | S 21
S 29 | S 28
1980

from which the remaining original bearing tree reported by Jelley and Rogers in 1979-80

A madrone, 19 ins. diam., bears S. 86 1/4° W., 8.6 ft. dist., with a hollowed blaze. (Record, S. 70° W.)

and bearing trees mkd. by Markham, Jr., PE No. 2880, in 1952, reported by Jelley and Rogers as being mkd. by Powell

A madrone, 15 ins. diam., bears N. 22 1/2° E., 16.8 ft. dist., with a healed blaze.

A cedar, 17 ins. diam., bears S. 86 1/2° E., 14.5 ft. dist., with a healed blaze.

and bearing trees mkd. by Jelley and Rogers

A fir, 22 ins. diam., bears N. 57° E., 25.9 ft. dist., with a healed blaze. (Record, 27.7 ft. dist.)

A cedar, 10 ins. diam., bears S. 12° W., 48.9 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. (Record, 50.8 ft. dist.)

A fir, 25 ins. diam., bears N. 46° W., 39.6 ft. dist., with a healed double blaze.

The iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, reset by Jelley and Rogers, is alongside the cor.

(D) The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T 29 S R 3 W
S 21 | S 22
1980

from which the bearing trees mkd. by Jelley and Rogers in 1979-80

A fir, 14 ins. diam., bears S. 18° E., 16.5 ft. dist., with a healed blaze.

A fir, 15 ins. diam., bears S. 38 1/4° W., 30.4 ft. dist., with a healed blaze.

(E) The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 29 S R 3 W
S 16 | S 15
S 21 | S 22
1981

from which the remains of the original bearing trees reported by Jelley and Rogers in 1979-80

A cedar, 38 ins. diam., bears N. 80° E., 46.2 ft. dist., with a hollowed blaze.

A decayed fir snag, 33 ins. diam., bears S. 75° E., 11.2 ft. dist., with axe marks visible on a healed blaze. (Record, 6.6 ft. dist.)

A decayed cedar stump, 26 ins. diam., bears S. 65° W., 46.9 ft. dist., with axe marks visible on a healed blaze.

A decayed fir stump, 46 ins. diam., bears N. 2° W., 37.0 ft. dist., with no marks visible.

and bearing trees mkd. by Byron, Deputy County Surveyor, in 1961, reported by Jelley and Rogers

A fir, 16 ins. diam., bears N. 82° E., 21.8 ft. dist., with a healed double blaze.

A pine, 36 ins. diam., bears S. 46° E., 55.4 ft. dist., with a healed blaze.

A fir, 31 ins. diam., bears S. 62° W., 28.7 ft. dist., with a healed double blaze.

A fir, 25 ins. diam., bears N. 51° W., 9.2 ft. dist., with a healed double blaze.

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

The survey represented by this plat, having been correctly executed in accordance with the requirements of law, and the regulations of this Bureau, is hereby accepted.

For the Director

May J. M. Havel

Chief Cadastral Surveyor of Oregon

February 17, 2017
Date