

TOWNSHIP 31 SOUTH, RANGE 9 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 3

DEPENDENT RESURVEY AND SUBDIVISION OF SECTION 21

(A) The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with a brass cap mkd.

T 31 S R 9 W  
S 21 S 22  
S 28 S 27  
1973

from which the remains of the bearing trees mkd. by Roseberry in 1973

A roothole bears N. 17 1/2° E., 14.5 ft. dist., alongside of which is a down fir, 23 ins. diam., no marks visible.

A roothole bears S. 64 3/4° E., 44.9 ft. dist., alongside of which is a down fir, 17 ins. diam., no marks visible.

A decayed fir stump, 23 ins. diam., bears S. 62 1/2° W., 28.1 ft. dist., with remains of a healed blaze.

A decayed fir stump, 13 ins. diam., bears N. 45° W., 31.4 ft. dist., no marks visible.

and new accessories

A fir, 19 ins. diam., bears N. 80° E., 66.3 ft. dist., mkd. T31S R9W S22 BT.

A fir, 24 ins. diam., bears S. 50° E., 72.4 ft. dist., mkd. T31S R9W S27 BT.

An iron rod, 30 ins. long, 5/8 in. diam., set 26 ins. in the ground for a reference monument, bears S. 23° 45' 40" W., 17.50 ft. dist., with aluminum cap mkd. RM T31S R9W 17.5 FT TO COR S28 2015, and an arrow pointing to the cor.

A fir, 7 ins. diam., bears N. 44 1/4° W., 54.0 ft. dist., mkd. X BT.

Corner is located in fallen trees near the NE. cor. of timber, edge bears S. and E.; younger fir reproduction to the N. and W.

(B) The 1/4 sec. cor. of secs. 21 and 22, perpetuated by Swearingen, PE No. 4186, in 1960; further perpetuated by the Douglas County Surveyor's Office in 1967; from original evidence no longer in existence; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with a brass cap mkd.

DOUGLAS COUNTY  
SURVEYORS  
T 31 S R 9 W  
1/4 S 21 S 22  
1967

from which the remains of the bearing trees mkd. by Swearingen

A fir stump, 28 ins. diam., bears N. 35° E., 41.0 ft. dist., with a healed blaze.

A fir, 30 ins. diam., bears N. 29 1/2° W., 16.5 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 6 ins. diam., bears S. 66° E., 22.8 ft. dist., mkd. X BT.

(C) Point for the E 1/16 sec. cor. of secs. 21 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with a brass cap mkd.

E 1/16 S 21  
S 28  
2015

from which

A fir, 18 ins. diam., bears S. 20° E., 41.8 ft. dist., mkd. E1/16 S28 BT.

A fir, 10 ins. diam., bears N. 63 1/4° W., 33.1 ft. dist., mkd. E1/16 S21 BT.

From the corner

N. 89° 07' 25" W., 80 ft. dist., ridge, bears N. and S.

(D) The 1/4 sec. cor. of secs. 21 and 28, perpetuated by the Douglas County Surveyor's Office in 1967; monumented with the remains of the original corner tree, a decayed fir stump, 36 ins. diam., with no marks visible, from which the remains of an original bearing tree

A decayed burned fir stump, 48 ins. diam., bears N. 44 1/2° W., 73.4 ft. dist., no marks visible. (Record, N. 40° W.)

and accessories mkd. by the Douglas County Surveyor's Office

An iron post, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground, bears N. 24° 53' 53" E., 2.02 ft. dist., with a brass cap mkd. COUNTY SURVEYORS OFFICE T31S R9W S21 1/4 S28 1967. Change cap marks to read COUNTY SURVEYORS OFFICE RM T31S R9W 1/4 2.0 FT TO COR S21 2015 1967 and an arrow pointing to the cor.

A fir high stump, 11 ins. diam., bears S. 8° E., 19.4 ft. dist., with a healed blaze.

A fir, 6 1/2 ins. diam., bears N. 38 1/2° W., 45.3 ft. dist., with a healed blaze.

At the corner point

Saw the stump of the original cor. tree to ground level on the uphill side and drive an iron rod, 30 ins. long, 5/8 in. diam., 29 ins. into stump, with an aluminum cap mkd.

T 31 S R 9 W  
S 21  
S 28  
2015

and a new reference monument

An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears S. 33° 49' 12" E., 26.74 ft. dist., with aluminum cap mkd. RM T31S R9W 1/4 S28 26.7 FT TO COR 2015, and an arrow pointing to the cor.

Corner is located on the S. edge of timber, edge bears E. and W.; young fir reproduction to the S.

(E) The 1/4 sec. cor. of secs. 16 and 21, perpetuated by Stephens, PLS No. 238, in 1965; from original evidence no longer in existence; monumented with an iron pipe, 1 in. diam., firmly set, projecting 20 ins. above ground, from which the remains of the bearing trees mkd. by Stephens

A fir stump, 60 ins. diam., bears N. 42 1/4° E., 70.9 ft. dist., with axe mark X.

A tin-capped fir high stump, 35 ins. diam., bears S. 54° E., 60.9 ft. dist., with scribe marks 4 CEC23 R9 BT and other illegible scribe marks visible on partially healed blaze.

and a bearing tree mkd. by person(s) unknown

A fir, 22 ins. diam., bears S. 80° E., 26.4 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over iron pipe, with a brass cap mkd.

T 31 S R 9 W  
S 16  
1/4 S 21  
S 21  
2015

and a new reference monument

An iron rod, 30 ins. long, 5/8 in. diam., set 27 ins. in the ground for a reference monument, bears N. 38° 09' 00" E., 23.08 ft. dist., with aluminum cap mkd. RM T31S R9W 1/4 S16 23 1 FT TO COR 2015, and an arrow pointing to the cor.

Corner is located on the S. edge of young fir reproduction, edge bears E. and W.

(F) Point for the W 1/16 sec. cor. of secs. 16 and 21.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with a brass cap mkd.

W 1/16 S 16  
S 21  
2015

from which

A fir, 11 ins. diam., bears S. 36° W., 32.4 ft. dist., mkd. W1/16 S21 BT.

A white fir, 10 ins. diam., bears N. 8° W., 20.4 ft. dist., mkd. W1/16 S16 BT.

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Portland, Oregon

The survey represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

*Maury M. Hartzel*  
Chief Cadastral Surveyor of Oregon

*February 9, 2017*  
Date

THIS PLAT REPRESENTS THE ENTIRE RECORD OF THE DEPENDENT RESURVEY