

TOWNSHIP 20 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON
DEPENDENT RESURVEY AND SUBDIVISION OF SECTION 34

(A) The cor. of secs. 2, 3, 34, and 35 on the S. bdy. of the Twp. as determined at record bearing and dist. from the remains of the original bearing tree

A burned decayed fir stump, 55 ins. diam., bears S. 35° E., 19.1 ft. dist., no marks visible.

and the witness cor. established by the Douglas County Surveyor's Office in October, 1967, reset by the Douglas County Surveyor's Office in October, 1984, as follows: a steel fence post, 48 in. high, firmly set, projecting 8 ins. above ground, bears South, 55.00 ft. dist., with a brass cap mkd. WC 55 FT. T20S R8W S34 S35 S3 S2 N TO COR T21S 1950, and a steel fence post alongside. This monument now functions as a reference monument; remark the brass cap as RM T21S R8W S2 55.0 FT TO COR 2015 1950 and an arrow pointing to the cor., from which the remains of the bearing trees mkd. by the Douglas County Surveyor's Office in October, 1967

Hemlock remains, size indeterminate, bears N. 12° E., 10.5 ft. dist., no marks visible.

A decayed hemlock stump, size indeterminate, bears S. 88° E., 6.4 ft. dist., no marks visible.

A decayed hemlock stump, size indeterminate, bears N. 38° W., 6.7 ft. dist., no marks visible.

At the corner point

Drive a fanned aluminum rod, 30 ins. long, 3/4 in. diam., 28 ins. in the ground, with an aluminum cap mkd.

T 20 S R 8 W
S 34 | S 35
S 3 | S 2
T21 S
2015

from which new bearing trees

A fir, 13 ins. diam., bears N. 41 1/2° E., 70.0 ft. dist., mkd. T20S R8W S35 BT.

A fir, 16 ins. diam., bears S. 67° E., 30.7 ft. dist., mkd. T21S R8W S2 BT.

A fir, 18 ins. diam., bears S. 68° W., 50.0 ft. dist., mkd. T21S R8W S3 BT.

A fir, 23 ins. diam., bears N. 67° W., 75.4 ft. dist., mkd. T20S R8W S34 BT.

Corner is located in the loose dirt of a cut bank and 20 ft. S. of a graveled road, 10 ft. wide, bears N. 70° E. and N. 75° W.

(B) Point for the E. 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Twp.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a brass cap mkd.

S 34
E 1/16 | S 3
S 3
2015

from which

A fir, 12 ins. diam., bears S. 8° W., 25.5 ft. dist., mkd. E1/16 S3 BT.

A fir, 13 ins. diam., bears N. 57 1/2° W., 19.6 ft. dist., mkd. E1/16 S34 BT.

From the corner

N. 4° 00' 35" E., 455 ft. dist., Marsh Creek Ridge Road, graveled surface, 12 ft. wide, bears E. and W.

(C) The 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Twp., monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.

S 34
1/4 | S 3
S 3
1950

from which the remains of an original bearing tree

A decayed fir stump, 24 ins. diam., bears S. 5° W., 12.5 ft. dist., to a rebar, 1/2 in. diam., driven in the center of the stump by Baker, PLS 1978, in 1984, no marks visible.

and the remains of a bearing tree mkd. by Tillman in 1950

A decayed fir stump, 24 ins. diam., bears N. 15° E., 10.6 ft. dist., to a rebar, 1/2 in. diam., driven in the center of the stump by Baker, PLS 1978, in 1984, with scribe marks S34 BT visible on open blaze.

and the bearing trees mkd. by Graham in 2005

A fir, 18 ins. diam., bears S. 21° W., 9.6 ft. dist., with a healed blaze.

A fir, 14 ins. diam., bears N. 30 1/2° W., 14.9 ft. dist., with a healed blaze.

A steel fence post is alongside the monument. There is a lag nearby that reads "This is the second cor. I was at when started my surveying career June 1950 - W. W. Glenn".

(D) The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

1/4
S 34 | S 35
1950

from which the remains of the bearing trees mkd. by Tillman in 1950

A burned decayed fir stump, 30 ins. diam., bears N. 66° E., 19.1 ft. dist., no marks visible.

A burned decayed fir stump, 26 ins. diam., bears N. 46° W., 7.9 ft. dist., with a healed blaze.

and new bearing trees

A fir, 22 ins. diam., bears N. 29 1/2° E., 20.4 ft. dist., mkd. 1/4 S35 BT.

A fir, 11 ins. diam., bears N. 55 1/4° W., 14.7 ft. dist., mkd. 1/4 S34 BT, and a May Nail driven at the base on the left side corner.

A steel fence post is alongside the monument.

(E) The cor. of secs. 26, 27, 34, and 35, monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 3 ins. above a partially decayed log, with an aluminum cap mkd.

T 20 S R 8 W
S 27 | S 26
S 34 | S 35
2013

from which the remains of the bearing trees mkd. by Tillman in 1950

A burned decayed cedar stump, 47 ins. diam., bears N. 70 1/4° E., 24.4 ft. dist., no marks visible and 4 wraps of a logging cable.

A burned decayed cedar stump, 45 ins. diam., bears S. 69 1/4° W., 82.9 ft. dist., with remains of a healed blaze.

and the reference monuments set by Forkner in 2013-14

An iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, bears N. 84° 55' 57" E., 30.27 ft. dist., with an aluminum cap mkd. RM T20S R8W 30.3 FT S26 2013 and an arrow pointing to the cor.

An iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, bears N. 2° 27' 46" W. 70.22 ft. dist., with an aluminum cap mkd. RM T20S R8W 70.2 FT S27 2013 and an arrow pointing to the cor.

No suitable trees visible from corner.

An aluminum fence post is alongside the monument, which is located in bottom lands, in down woody debris and willow regrowth.

(F) The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd.

1/4
S 33 | S 34
1950

from which the remains of the bearing trees mkd. by Tillman in 1950

A decayed fir snag, 20 ins. diam., bears S. 85° E., 12.5 ft. dist., with scribe marks 1/4 and other illegible scribe marks visible on partially healed blaze.

A decayed fir snag, 12 ins. diam., bears N. 81° W., 13.2 ft. dist., with illegible scribe marks visible on falling-apart healed blaze (Record, 13.9 ft. dist.)

and the bearing trees mkd. by Graham in 2005

A fir, 11 ins. diam., bears N. 73 1/2° E., 12.2 ft. dist., with a healed blaze. (Record N. 71 1/2° E.)

A fir, 14 ins. diam., bears S. 34° W., 12.2 ft. dist., with a healed blaze.

A steel fence post is alongside the monument.

From the corner

N. 5° 29' 46" E., 300 ft. dist., Marsh Creek Ridge Road, graveled surface, 10 ft. wide, bears N. 40° W. and S. 35° E.

FILED
Date: 9/18/2017 By: JC
This survey consists of:
Map, PLAT T20-8 2016-1
Narrative, VOL. 58 PAGES
Corner-Rep. 23443-45
DOUGLAS COUNTY
SURVEYOR

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

The survey represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director
Mary J. W. Heutsy
Chief Cadastral Surveyor of Oregon

July 6, 2016
Date