

TOWNSHIP 20 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON
DEPENDENT RESURVEY AND SUBDIVISION OF SECTION 34

SHEET 3 OF 3

(G) Point for the N 1/16 sec. cor. of secs. 33 and 34.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with a brass cap mkd.

N 1/16
S 33 | S 34
2015

from which

A fir, 17 ins. diam., bears S. 28 1/2° E., 10.2 ft. dist.,
mkd. NW1/16 S34 BT.

A fir, 11 ins. diam., bears N. 6° W., 8.0 ft. dist.,
mkd. NW1/16 S33 BT.

(H) The cor. of secs. 27, 28, 33, and 34, monumented with
an iron post, 2 ins. diam., firmly set, with a brass cap mkd.

T 20 S R 8 W
S 28 | S 27
S 33 | S 34
1950

from which the remains of an original bearing tree

A decayed fir stump, 3 ins. diam., bears N. 16 1/2° W.,
23.1 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Tillman
in 1950

A decayed fir stump, 33 ins. diam., bears S. 61° E.,
15.2 ft. dist., no marks visible.

A burned decayed fir stump, size indeterminate,
bears N. 21° W., 45.5 ft. dist., with scribe marks T20S
R8W visible on open blaze.

and the bearing trees mkd. by Graham in 2005

A fir, 23 ins. diam., bears N. 2° E., 22.1 ft. dist.,
with a healed blaze and a Mag Nail at the base on
the right side center.

A fir, 14 ins. diam., bears S. 89 3/4° E., 41.6 ft. dist.,
with a healed blaze.

A fir, 11 ins. diam., bears S. 38° W., 8.6 ft. dist.,
with a healed blaze and a Mag Nail at the base on
the right side center.

A fir, 18 ins. diam., bears N. 59 3/4° W., 15.5 ft. dist.,
with a healed blaze.

A steel fence post is alongside the monument.

(I) The 1/4 sec. cor. of secs. 27 and 34, monumented with
an iron post, 1 in. diam., firmly set, projecting 2 ins. above
ground, with a brass cap, oriented W., mkd.

S 27
S 34
1950

from which the remains of a bearing tree mkd. by Tillman
in 1950

A root hole bears S. 30 1/4° E., 52.8 ft. dist.

and the remains of the bearing trees mkd. by Glenn,
et al., in 1967

A burned cedar snag, 19 ins. diam., bears
N. 22° E., 47.5 ft. dist., no marks visible.
(Record, N. 25° E.)

A burned decayed fir snag, 21 ins. diam., bears
S. 11° E., 92.4 ft. dist., no marks visible.
(Record, S. 10° E.)

and the bearing trees mkd. by Graham in 2005

A fir, 11 ins. diam., bears S. 66 1/2° E., 13.7 ft. dist.,
with a healed blaze and a Mag Nail at the base on
the right side center.

A fir, 14 ins. diam., bears N. 7 3/4° W., 15.0 ft. dist.,
with a healed blaze and a Mag Nail at the base on
the right side center.

A steel fence post is alongside the monument.

(J) Point for the center 1/4 sec. cor. of sec. 34.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
23 ins. in the ground, with a brass cap mkd.

T 20 S R 8 W
C 1/4 S 34
2015

from which

A fir, 17 ins. diam., bears N. 89° E., 23.7 ft. dist.,
mkd. X BT.

A fir, 14 ins. diam., bears N. 18 1/2° W., 18.6 ft. dist.,
mkd. C 1/4 S34 BT.

(K) Point for the center E 1/16 sec. cor. of sec. 34.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with a brass cap mkd.

E 1/16
S 34
2015

from which

A fir, 11 ins. diam., bears S. 26 1/2° E., 13.2 ft. dist.,
mkd. CE1/16 S34 BT.

A fir, 14 ins. diam., bears N. 17 3/4° W., 8.9 ft. dist.,
mkd. X BT.

From the corner

N. 88° 34' 55" W., 215 ft. dist., creek, 2 ft. wide,
course N. 30° E.

S. 4° 00' 35" W., 335 ft. dist., Marsh Creek, 3 ft. wide,
course W.

(L) Point for the center W 1/16 sec. cor. of sec. 34.

Set an iron rod, 17 ins. long, 5/8 in. diam., cemented
10 ins. in a drill hole in solid rock, with an aluminum
cap mkd

W 1/16
C S 34
2015

from which

A fir, 14 ins. diam., bears N. 19° E., 28.8 ft. dist.,
mkd. CW1/16 S34 BT.

A fir, 16 ins. diam., bears S. 44° E., 27.4 ft. dist.,
mkd. X BT.

From this cor., a point established by person(s)
unknown bears S. 34° 41' 03" E., 23 ft. dist.,
firmly set, projecting 13 ins. above ground. This point is
not utilized in this survey.

Also from the corner

N. 4° 58' 43" E., 70 ft. dist., Marsh Creek, 5 ft. wide,
course West.

S. 88° 34' 55" E., 305 ft. dist., same creek, 5 ft. wide,
course N. 65° W.

(M) Point for the NW 1/16 sec. cor. of sec. 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with a brass cap mkd.

NW 1/16 S 34
2015

from which

A fir, 17 ins. diam., bears N. 72 1/2° E., 14.7 ft. dist.,
mkd. X BT.

A fir, 17 ins. diam., bears S. 26 1/2° E., 13.3 ft. dist.,
mkd. NW1/16 S34 BT.

FILED
Date: 9/19/2017 By: JC
This survey consists of:
Map: PLAT T20-8 2016-1
Narrative: VOL. 58 PAGES
Corner-Ref: 23443-45
BY: MAURY J. MITCHELL
DOUGLAS COUNTY
SURVEYOR

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

The survey represented by this plat, having
been correctly executed in accordance with the
requirements of law and the regulations of this
Bureau, is hereby accepted.

For the Director
Maury J. Mitchell
Chief Cadastral Surveyor of Oregon

July 6, 2016
Date