

TOWNSHIP 20 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON
DEPENDENT RESURVEY

SHEET 2 OF 2

(A) The cor. of secs. 3, 4, 9, and 10, perpetuated by Rice, PLS No. 54633, in 2014; monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above ground, in a collar of stone, with a brass cap mkd.

T 20 S 1 R 8 W
S 4 | S 3
S 9 | S 10
1954

from which the remains of the bearing trees mkd. by Tillman, et al., in 1953-54

A fir stump, 53 ins. diam., bears N. 47 1/2° E., 33.7 ft. dist., no marks visible.

A fir, 41 ins. diam., bears S. 78 1/2° E., 33.7 ft. dist., with a healed blaze.

A fir snag, 60 ins. diam., bears S. 33° W., 73.3 ft. dist., no marks visible.

and the bearing trees mkd. by Rice

A fir, 19 ins. diam., bears N. 26° E., 63.0 ft. dist., with scribe marks T20S R8W S3 BT visible on partially healed blaze and a nail at the base on the right side center.

A fir, 17 ins. diam., bears N. 67 1/2° W., 48.4 ft. dist., with scribe marks T20S R8W S4 BT visible on partially healed blaze and a nail at the base on the right side center.

and a new bearing tree

A fir, 12 ins. diam., bears S. 77° W., 27.3 ft. dist., mkd. X BT.

Corner is located on a rocky outcrop. Drive an aluminum angle iron 2 ft. NE. of the cor.

(B) The 1/4 sec. cor. of secs. 4, and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above a sandstone, 4 x 3 x 2 ft., with a brass cap mkd.

1/4 S 4
S 9
1954

from which an original bearing tree

A fir, 57 ins. diam., bears S. 75° E., 8.6 ft. dist., with no marks visible on decayed partially healed blaze.

and the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A fir stump, 61 ins. diam., bears N. 62 1/2° E., 37.6 ft. dist., with no marks visible on burned partially healed blaze.

and a bearing tree mkd. by Graham in 2005

A fir, 13 ins. diam., bears N. 15 1/2° W., 5.6 ft. dist., with a healed blaze and a Mag Nail at the base on the right side center.

Drive an aluminum angle iron on the E. side of the sandstone.

(C) The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground (alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground), with a brass cap mkd.

T 20 S 1 R 8 W
S 5 | S 4
S 8 | S 9
1954

from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears S. 65° E., 21.8 ft. dist., with no marks visible on pitch face and a healed blaze.

and the remains of the bearing trees mkd. by Tillman, et al., in 1953-54

A decayed fir stump, 33 ins. diam., bears S. 12° W., 22.2 ft. dist., with scribe marks T20S R8W S8 BT visible on open blaze. (Record, 24.4 ft. dist.)

A decayed fir stump, 24 ins. diam., bears N. 29° W., 37.9 ft. dist., with a healed blaze, and the bearing trees mkd. by Graham in 2005

A fir, 26 ins. diam., bears N. 63° E., 15.3 ft. dist., with a healed blaze and an embedded Mag Nail at the base on the right side center.

A fir, 24 ins. diam., bears S. 4° E., 31.9 ft. dist., with a healed blaze.

A fir, 9 ins. diam., bears S. 42° W., 32.0 ft. dist., with a healed blaze and an embedded Mag Nail at the base on the right side center.

A fir, 15 ins. diam., bears N. 57° W., 20.5 ft. dist., with a healed blaze and an embedded Mag Nail at the base on the right side center.

An aluminum fence post is alongside the monument, which is located on the NE. cor. of a recently logged area, edge bears S. and W.

FILED

Date: 9/18/2017 By: J.C.
This survey consists of:
Map PLAT T20-8 2017-1
Narratives VOL 58 PAGES
Comments 23446-7
DOUGLAS COUNTY
SURVEYOR

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

The survey represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

Mary J. M. Hartzel
Chief Cadastral Surveyor of Oregon

March 24, 2017

Date