

# TOWNSHIP 26 SOUTH, RANGE 2 WEST, OF THE WILLAMETTE MERIDIAN, OREGON DEPENDENT RESURVEY

Date: 9/18/2017 By: JC  
This survey consists of:  
Map: PLAT: T26-2 2017-1  
Narrative: VOL. 58 PAGES  
Gernet-Rpt: 23486-23487  
INFORMATIONAL ONLY  
DOUGLAS COUNTY  
SURVEYOR

SHEET 2 OF 2

OFFICIALLY FILED: 7/20/2017

(A) The cor. of secs. 19, 24, 25, and 30, on the W. body of the Tp., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above the ground, (the original stone, 8 x 10 x 14 ins., buried alongside, projecting 2 ins. above the ground, with 4 grooves visible on N. face and 2 grooves visible on S. face) with brass cap mkd.

T 26 S	
R 24   S 19	R
3	2
W S 25   S 30	W
1979	

from which the remaining bearing trees mkd. by Gibb in 1909-10, and reported by Moore in 2004

A fir, 27 ins. diam., bears N. 52° E., 17.8 ft. dist., with a healed blaze.

A fir, 32 ins. diam., bears S. 14° E., 17.2 ft. dist., with a healed blaze.

A fir, 18 ins. diam., bears N. 18° W., 11.9 ft. dist., with a healed blaze.

and a bearing tree mkd. by Calder, RPE No. 2149, in 1952, and reported by Moore

A fir, 17 ins. diam., bears S. 51 1/2° W., 17.8 ft. dist., with a healed blaze.

A steel fence post is alongside the cor.

(B) The 1/4 sec. cor. of secs. 19 and 24, on the W. body of the Tp., perpetuated by the Douglas County Surveyor's Office in July of 1978, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 26 S	
S 24   S 19	S
1/4	2
R 3 W   R 2 W	R
1978	

from which the remains of a bearing tree mkd. by Gibb in 1909-10

A burnt madrone snag, 14 ins. diam., bears N. 69° E., 8.6 ft. dist., and a hollow blaze with no marks visible.

and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office

A burnt fir snag, 36 ins. diam., bears S. 53 1/4° E., 17.2 ft. dist., with a healed blaze.

A burnt fir snag, 22 ins. diam., bears S. 70 1/2° W., 33.5 ft. dist., with a healed blaze.

and new reference monuments

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 76° 57' 07" E., 30.10 ft. dist., with brass cap mkd. RM1 1/4 S19 30.1 FT TO COR 2015 and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 27° 40' 02" W., 50.20 ft. dist., with brass cap mkd. RM2 1/4 S24 50.2 FT TO COR 2015 and an arrow pointing to the cor.

A steel fence post alongside the cor.

(C) The cor. of secs. 13, 18, 19, and 24, on the W. body of the Tp., perpetuated by the Douglas County Surveyor's Office in 1965, from original evidence no longer in existence, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, in a rock outcrop, projecting 6 ins. above the ground, with brass cap mkd.

T 26 S	
R 13   S 18	R
3	2
W S 24   S 19	W
1965	

from which new accessories

A fir, 16 ins. diam., bears N. 46 1/2° E., 113.3 ft. dist., mkd. T26S R2W S18 BT.

A rock cut bank, 15 ft. high, bears S. 8° 58' 37" W., 36.30 ft. dist., to a Mag-Nail driven in crack, with marks BO chiseled in the rock face, 3 ft. high up the rock face.

A fir, 9 ins. diam., bears N. 32° W., 54.3 ft. dist., mkd. T26S R3W S13 BT.

Corner is located

S., 35 ft. dist., from a gravel road, 12 ft. wide, extending N., 80° E. and S., 80° W.

From this cor., a point established as a witness cor. for the cor. of secs. 13, 18, 19, and 24, on the W. body of the Tp., by Glenn S. Baughman, PLS No. 536, in 1980, in an unfilled survey, bears S. 0° 07' 32" E., 57.57 ft. dist., and is accepted as a reference monument, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above the ground in a collar of stone, with brass cap mkd. WC T26S R3W S13 S18 R2W S24 S19 1980 LS 536.

(D) The cor. of secs. 7, 12, 13, and 18, on the W. body of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground (alongside of which is the stone set by Collier in 1913-14, 14 x 10 x 6 ins., with no marks visible) in a mound of stone, 3 ft. base, to the top, with brass cap mkd.

T 26 S	
R 3 W   R 2 W	R
S 12   S 7	S
S 13   S 18	S
1959	

from which the remains of the bearing trees mkd. by Zirpel and Glenn in 1959

A burnt fir snag, 56 ins. diam., bears N. 59 1/4° E., 73.3 ft. dist., with a healed blaze.

A burnt sawed cedar stump, size indeterminate, bears S. 69 1/2° E., 39.9 ft. dist., with illegible scribe marks visible on a partially opened blaze.

A burnt cedar snag, 29 ins. diam., bears S. 70 1/2° W., 31.7 ft. dist., with a healed blaze.

A burnt cedar snag, 35 ins. diam., bears N. 57° W., 32.3 ft. dist., with a healed blaze.

and new reference monuments

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, in a mound of stone, 2 ft. base, to the top, for a reference monument, bears S. 32° 43' 48" W., 20.40 ft. dist., with brass cap mkd. RM1 S13 T26S R3W 20.4 FT TO COR 2015 and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, in a mound of stone, 2 ft. base, to the top, for a reference monument, bears N. 70° 38' 34" W., 41.6 ft. dist., with brass cap mkd. RM2 T26S R3W S12 41.6 FT TO COR 2015 and an arrow pointing to the cor.

B. C. V.

(E) The 1/4 sec. cor. of sec. 18 only, perpetuated by the Douglas County Surveyor's Office in March of 1978, monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

1/4 S18	
1918	

from which the remains of the bearing trees mkd. by Mensch in 1916-18

A burnt fir snag, size indeterminate, bears N. 47° E., 11.2 ft. dist., with illegible scribe marks visible on an open blaze.

A burnt fir stump, size indeterminate, bears N. 20° W., 38.3 ft. dist., with no marks visible and a spike in the stump facing the cor.

and the remains of a bearing tree mkd. by persons unknown, reported by the Douglas County Surveyor's Office

A burnt fir snag, 53 ins. diam., bears S. 29° W., 27.6 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office

A burnt fir snag, 33 ins. diam., bears S. 77 1/2° E., 41.3 ft. dist., with a healed blaze.

and new reference monuments

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 47° 32' 43" W., 53.20 ft. dist., with brass cap mkd. RM2 S19 53.2 FT TO COR 2015 and an arrow pointing to the cor. Build mound of stone, 2 ft. base, 1 ft. high, and drive an aluminum angle iron, 5 ft. long, alongside the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 16° 32' 50" W., 26.20 ft. dist., with brass cap mkd. RM1 1/4 S18 26.2 FT TO COR 2015 and an arrow pointing to the cor.

Drive an aluminum angle iron, 5 ft. long, alongside the cor.

Note: The source document for the perpetuation of this cor. by the Douglas County Surveyor's Office is CS 59/46. This document could not be found in the County Surveyor's Office at the time of this survey. The Douglas County Surveyor's Office Corner Renewal Index 140400 was utilized for the information for this cor.

(F) The cor. of secs. 7, 8, 17, and 18, perpetuated by the Douglas County Surveyor's Office in 2005, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 26 S R 2 W	
S 7   S 8	S
S 18   S 17	S
1959	

from which the remains of the bearing trees mkd. by Zirpel and Glenn in 1959

A root hole, bears N. 45 3/4° E., 43.6 ft. dist., with a fallen, decayed hemlock snag, 12 ins. diam., lying alongside, with illegible scribe marks visible on a partially healed blaze. (Record, N. 51° E.)

A cedar, 19 ins. diam., bears S. 54° E., 40.9 ft. dist., with illegible scribe marks visible on a partially healed blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office

A chinquapin, 14 ins. diam., bears N. 88° E., 23.3 ft. dist., with scribe marks T26S R2W S8 CS BT visible on a partially healed blaze.

A madrone, 25 ins. diam., bears N. 58 1/2° W., 1.8 ft. dist., with scribe marks T26S R2W S7 CS BT visible on a partially healed bark scribe.  
Note: Base of tree is growing around the iron post.

and a new bearing tree

A hemlock, 15 ins. diam., bears S. 55° W., 36.0 ft. dist., mkd. T26S R2W S18 BT.

Drive an aluminum angle iron, 5 ft. long, alongside the cor.

(G) The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base, to the top, with brass cap mkd.

T 26 S R 2 W	
1/4 S 7	
S 18	
1959	

from which the remains of the bearing trees mkd. by Zirpel and Glenn in 1959

A burnt fir stump, size indeterminate, bears S. 19° W., 45.5 ft. dist., with no marks visible.

A burnt fir snag, 33 ins. diam., bears N. 15° W., 38.3 ft. dist., with a healed blaze.

and new reference monuments

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears S. 42° 41' 14" W., 19.50 ft. dist., with brass cap mkd. RM1 1/4 S18 19.5 FT TO COR 2015 and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 45° 16' 47" W., 19.60 ft. dist., with brass cap mkd. RM2 1/4 S7 19.6 FT TO COR 2015 and an arrow pointing to the cor.

Drive an aluminum angle iron, 5 ft. long, alongside the cor.

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Portland, Oregon

The survey represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

*Mary J. M. Hurd*  
Chief Cadastral Surveyor of Oregon

April 18, 2017

Date