

23588

VOL. 638

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE DEPENDENT RESURVEY
OF A PORTION OF THE
SUBDIVISIONAL LINES AND A PORTION
OF THE SUBDIVISION OF
SECTION LINES IN SECTION 26,
TOWNSHIP 32 SOUTH, RANGE 1 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON

EXECUTED BY

Ernest Q. Lundeen, Cadastral Surveyor

Under Special Instructions approved May 16, 2017,
which provided for the surveys included under Group No. 2873,
and Assignment Instructions dated May 16, 2017.

Survey commenced May 16, 2017

Survey completed June 8, 2017

T. 32 S., R. 1 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision of section lines in section 26, Township 32 South, Range 1 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1883, Rufus S. Moore, U.S. Deputy Surveyor, surveyed the subdivisional lines as shown on the official plat of survey approved April 10, 1884.

In 1955, Hans W. Thielsen, Cadastral Cartographer, resurveyed a portion of the subdivisional lines as shown on the official plat of survey accepted March 29, 1956.

In 1965, Joseph S. Gawron and Rollin D. Aanrud, Cadastral Surveyors, resurveyed a portion of the subdivisional lines, subdivided section 26, and remonumented certain original corner points, as shown on the official plat of survey accepted June 24, 1966.

The following local surveys filed in the Jackson County and Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's or engineer's last name, Professional Land Surveyor (PLS) No. or Professional Engineer (PE) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1955	Mark E. Boyden, PLS No. 281	741
1958	Marvin C. Ramsey, PLS No. 404	1165
1971	Robert A. Morris, PE No. 7122	4663
1967-73	Mark E. Boyden PLS No. 281	5336
1978	Kurt C. Weaver, PLS No. 1679	7511
1979	Burton W. Holt, PLS. No. 418	7995
1989	Gerald V. Nygren, PLS No. 1035	CS 63/85-27

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions approved May 16, 2017, for Group No. 2873, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through GPS and conventional survey techniques. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

T. 32 S., R. 1 W., Willamette Meridian, Oregon

FEET

Only those lines which represent the Bureau of Land Management (BLM) property lines were posted with aluminum angle posts, 5 feet long, 1 inch x 1 inch, blazed, painted, and tagged with BLM boundary signs.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The 1/4 section corner of sections 25 and 26:

Latitude: 42° 45' 26.76" N. Longitude: 122° 46' 31.95" W.

The corner of sections 13, 14, 23, and 24:

Latitude: 42° 46' 43.61" N. Longitude: 122° 46' 30.67" W.

The corner of sections 21, 22, 27, and 28:

Latitude: 42° 45' 59.04" N. Longitude: 122° 48' 53.26" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

Restoring the 1883 survey by Rufus S. Moore,
the 1955 resurvey by Hans W. Thielsen, and the
1965 remonumentation by
Joseph S. Gawron and Rollin D. Aanrud

Beginning at the cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T 32 S	R 1 W
S 23	S 24
S 26	S 25
1965	

from which the remains of original bearing trees

A fir, 47 ins. diam., bears N. 28 3/4° E., 27.7 ft. dist., with a healed blaze.
(Record, N. 30° E., 26.4 ft.)

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

FEET	<p>A sawed fir stump, 25 ins. diam., bears S. 43° W., 13.9 ft. dist., with a healed blaze.</p> <p>A cedar, 19 ins. diam., bears N. 60° W., 26.4 ft. dist., with a healed blaze. (Record, N. 58° W.)</p> <p>and a bearing tree mkd by Gawron and Aunrud in 1965</p> <p>A fir, 12 ins. diam., bears S. 39 3/4° E., 34.3 ft. dist., with a healed blaze. (Record, S. 41° E.)</p> <p>and a new bearing tree</p> <p>A fir, 9 ins. diam., bears S. 19 1/2° W., 17.4 ft. dist., mkd. T32S R1W S26 BT.</p> <p>N. 2° 49' 37" E., bet. secs. 23 and 24.</p>
2549.82	<p>The 1/4 sec. cor. of secs. 23 and 24, reestablished by proportionate measurement by Boyden, PLS No. 281, in 1955, perpetuated by Morris, PE No. 7122, in 1971, and further perpetuated by the Jackson County Surveyor's Office in 2003, as shown on the Jackson County Surveyor's Office second reestablishment record in T. 32 S., R. 1 W., point identifier No. 600340. There is no remaining evidence of the original cor., and this position is accepted as a careful and faithful reestablishment of the cor., monumented with an iron post, 1 in. diam., firmly set, flush with the ground, in a collar of stone, with brass cap mkd.</p> <p align="center"> JACKSON COUNTY SURVEYOR T 32 S R 1 W 1/4 S 23 S 24 2003 </p> <p>from which the remains of a bearing tree mkd. by Morris</p> <p>A sawed fir stump, 17 ins. diam., bears N. 69 3/4° E., 27.3 ft. dist., with scribe marks 1/4 S24 visible on open blaze.</p> <p>and accessories established. by the Jackson County Surveyor's Office in 2003</p> <p>A sawed cedar stump, 47 ins. diam., bears N. 41 1/2° E., 16.5 ft. dist., with a mag nail flush with the center of the stump.</p> <p>An iron rod, 5/8 in. diam., firmly set, flush with the ground, bears N. 68° 48' 43" E., 25.80 ft. dist. with aluminum cap, 1 1/2 ins diam., mkd. JACKSON COUNTY SURVEYOR with a triangle and punch mark.</p> <p>An iron rod, 5/8 in. diam., firmly set, flush with the ground, bears S. 17° 30' 00" E., 19.80 ft. dist. with aluminum cap, 1 1/2 ins. diam., mkd. JACKSON COUNTY SURVEYOR with a triangle and punch mark.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

FEET											
2550.31	<p>N. 2° 49' 51" E., beginning new measurement.</p> <p>The cor. of secs. 13, 14, 23, and 24, perpetuated by person(s) unknown in 1967, and further perpetuated by the Jackson County Surveyor's Office in 1979, as shown on the Jackson County Surveyor's Office first reestablishment record in T. 32 S., R. 1 W., point identifier No. 600400; monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, with pot metal filled bell reducer mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 32 S</td> <td>R 1 W</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td colspan="2">1967</td> </tr> </table> </div> <p>from which the remains of original bearing trees</p> <p>A burnt fir snag, 28 ins. diam., 12 ft. tall, bears S. 10° W., 15.2 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 37 ins. diam., bears N. 56° W., 15.8 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by the Jackson County Surveyor's Office</p> <p>A fir, 25 ins. diam., bears S. 86 1/2° E., 48.8 ft. dist., with a healed double blaze.</p> <p>and new bearing trees</p> <p>A fir, 11 ins. diam., bears N. 26 3/4° E., 44.6 ft. dist., mkd. T32S R1W S13 BT.</p> <p>A fir, 28 ins. diam., bears S. 71 1/2° W., 85.5 ft. dist., mkd. T32S R1W S23 BT.</p> <p>A fir, 6 ins. diam., bears N. 53 1/2° W., 12.3 ft. dist., mkd. X at breast height and BT at the base.</p>	T 32 S	R 1 W	S 14	S 13	<hr/>		S 23	S 24	1967	
T 32 S	R 1 W										
S 14	S 13										
<hr/>											
S 23	S 24										
1967											
1344.13	<p>S. 86° 18' 05" W., bet. secs. 14 and 23.</p> <p>The E 1/16 sec. cor. of secs. 14 and 23, established by Boyden, PLS No. 281, in 1967-73, and is accepted as the cor.; monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with pot metal filled bell reducer mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>S 14</td> </tr> <tr> <td><hr/></td> </tr> <tr> <td>S 23</td> </tr> <tr> <td>E 1/16</td> </tr> <tr> <td>1967</td> </tr> </table> </div>	S 14	<hr/>	S 23	E 1/16	1967					
S 14											
<hr/>											
S 23											
E 1/16											
1967											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of a bearing tree mkd. by Boyden</p> <p style="padding-left: 40px;">A sawed fir stump, 31 ins. diam., bears N. 15° E., 19.2 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 63 3/4° E., 47.7 ft. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 24° W., 31.3 ft. dist., mkd. E 1/16 S14 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 86° 17' 29" W., beginning new measurement.</p>
1344.23	<p>The 1/4 sec. cor. of secs. 14 and 23, perpetuated by Boyden, PLS No. 281, in 1967-73, and further perpetuated by the Jackson County Surveyor's Office in 1981, as shown on the Jackson County Surveyor's Office first reestablishment record in T. 32 S., R. 1 W., point identifier No. 540400; monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>JACKSON COUNTY</p> <p>T 32 S R 1 W</p> <p style="padding-left: 40px;">14</p> <p style="padding-left: 40px;">1/4 S ———</p> <p style="padding-left: 40px;">23</p> <p style="padding-left: 40px;">1981</p> </div> <p>from which original bearing trees</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 38° E., 16.9 ft. dist., with scribe mark 4 visible on open blaze. (Record, S. 33° E., 15.8 ft.)</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 72° W., 2.6 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Boyden</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 35 3/4° E., 10.0 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 00' 07" W., beginning new measurement.</p>
1285.16	<p>The W 1/16 sec. cor. of secs. 14 and 23, established by Holt, PLS No. 418, in 1979, and is accepted as the cor.; determined at intersection of record distances from the remains of bearing trees mkd. by Holt.</p> <p style="padding-left: 40px;">A cedar, 32 ins. diam., bears N. 30° E., 15.2 ft. dist., with illegible scribe marks visible on a partially healed blaze. (Record, fir)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

FEET	<p>A fir snag, 48 ins. diam., bears S. 48 1/4° E., 52.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 14 W 1/16 ————— S 23 2017</p> </div> <p>and a new bearing tree</p> <p>A fir, 11 ins. diam., bears S. 71 3/4° W., 52.8 ft. dist., mkd. W 1/16 S23 BT.</p> <p>The 5/8 in. diam. iron rod set by Holt in 1979 was found lying loose on the ground near the cor. position.</p> <p>Deposit the iron rod directly under the stainless steel post and a magnet in a white plastic case at the base.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 00' 29" W., beginning new measurement.</p>										
1285.62	<p>The cor. of secs. 14, 15, 22, and 23, perpetuated by Ramsey, PLS No. 404, in 1958, subsequently perpetuated by Weaver, PLS No. 1679, in 1978, and further perpetuated by Nygren, PLS No. 1035, in 1989; monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 3 ft. base, 24 ins. high, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 32 S R 1 W</td> </tr> <tr> <td style="text-align: center;">S 15</td> <td style="text-align: center;">S 14</td> </tr> <tr> <td colspan="2" style="text-align: center;">—————</td> </tr> <tr> <td style="text-align: center;">S 22</td> <td style="text-align: center;">S 23</td> </tr> <tr> <td colspan="2" style="text-align: center;">LS 1679 1978</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Thielsen in 1955</p> <p>A rotted fir stump, size indeterminate, bears S. 78 3/4° E., 32.0 ft. dist., with scribe marks T32S R1W S23 BT visible on rotted exposed blaze. (Record, S. 83 1/2 E., 33.7 ft.)</p> <p>A fir, 43 ins. diam., bears S. 61 1/2° W., 93.3 ft. dist., with a healed blaze. (Record, S. 62 1/4° W., 90.4 ft.)</p> <p>A fir, 39 ins. diam., bears N. 38° W., 57.9 ft. dist., with a healed blaze. (Record, N. 35° W., 59.4 ft.)</p> <p>and bearing trees mkd. by Weaver</p>	T 32 S R 1 W		S 15	S 14	—————		S 22	S 23	LS 1679 1978	
T 32 S R 1 W											
S 15	S 14										
—————											
S 22	S 23										
LS 1679 1978											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

FEET											
	<p>A fir, 14 ins. diam., bears N. 69 1/4° E., 26.9 ft. dist., with a healed double blaze.</p> <p>A fir, 23 ins. diam., bears S. 1 3/4° E., 24.9 ft. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by Nygren</p> <p>A fir, 15 ins. diam., bears S. 78 3/4° E., 22.5 ft. dist., with a healed blaze.</p> <p>No remaining evidence of the iron post monument set by Thielsen in 1955 was found.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T 32 S R 1 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black; text-align: center;"> </td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> <tr> <td colspan="2">1965</td> </tr> </table> </div> <p>from which an original bearing tree</p> <p>A forked fir, 57 ins. diam., bears N. 58° W., 5.9 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Ramsey, PLS No. 404, in 1958, reported by Gawron and Aanrud in 1965.</p> <p>A sawed fir stump, 47 ins. diam., bears N. 60° E., 68.6 ft. dist., with a healed blaze.</p> <p>A hemlock, 44 ins. diam., bears S. 50 1/4° E., 30.0 ft. dist., with a healed blaze. (Record, S. 52 E., 29.0 ft.)</p> <p>and new bearing trees</p> <p>A fir, 12 ins. diam., bears N. 67 3/4° E., 64.1 ft. dist., mkd. T32S R1W S23 BT.</p> <p>A fir, 10 ins. diam., bears S. 3° W., 17.7 ft. dist., mkd. T32S R1W S27 BT</p> <p>N. 81° 42' 42" W., bet. secs. 22 and 27.</p>	T 32 S R 1 W		S 22	S 23			S 27	S 26	1965	
T 32 S R 1 W											
S 22	S 23										
S 27	S 26										
1965											
2727.27	<p>The 1/4 sec. cor. of secs. 22 and 27, reestablished by proportionate measurement by Ramsey, PLS No. 404, in 1958. There is no remaining evidence of the original cor., and this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground with a washer nailed to a</p>										

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

FEET	
	<p>wooden plug inside the iron pipe, mkd RS 404, from which the remains of a bearing tree mkd. by Ramsey</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 22 1/2° E., 5.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 25 ins. in the ground, directly over the iron pipe, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 32 S R 1 W</p> <p style="margin-left: 40px;">S 22</p> <p style="margin-left: 40px;">1/4 —————</p> <p style="margin-left: 40px;">S 27</p> <p style="margin-left: 40px;">2017</p> </div> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 71 3/4° E., 53.3 ft. dist., mkd. 1/4 S22 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 81° 50' 56" W., beginning new measurement.</p>
1366.58	<p>The W 1/16 sec. cor. of secs. 22 and 27, established by Ramsey, PLS No. 404, in 1958, and is accepted as the cor.; determined at intersection of record distances from the bearing trees mkd. by Ramsey</p> <p style="padding-left: 40px;">An oak, 6 ins. diam., bears N. 80 1/4° E., 25.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears S. 45° E., 135.3 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 12 ins. in the ground, in a mound of stone, 4 ft. base, to the top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin-left: 40px;">S 22</p> <p style="margin-left: 40px;">W 1/16 —————</p> <p style="margin-left: 40px;">S 27</p> <p style="margin-left: 40px;">2017</p> </div> <p>The 1 in. diam. iron pipe set by Ramsey in 1958 was found lying loose on the ground near the cor. position.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and bury the iron pipe alongside.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

FEET	<p>N. 81° 38' 34" W., beginning new measurement.</p>																		
1369.29	<p>The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 32 S R 1 W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 21</td><td style="padding: 0 5px;">S 22</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 28</td><td style="padding: 0 5px;">S 27</td></tr> <tr><td colspan="2">1955</td></tr> </table> </div> <p>from which bearing trees mkd. by Thielsen in 1955</p> <p style="margin-left: 40px;">A fir, 38 ins. diam., bears N. 37 3/4° E., 340.3 ft. dist., with a healed blaze. (Record, N. 38 1/4° E., 342.5 ft.)</p> <p style="margin-left: 40px;">A fir, 47 ins. diam., bears S. 38° E., 288.8 ft. dist., with a healed blaze. (Record, S. 37 1/2° E., 286.4 ft.)</p> <p style="margin-left: 40px;">A fir, 35 ins. diam., bears S. 10 1/4° W., 98.3 ft. dist., with a healed blaze. (Record, S. 11 1/2° W., 97.7 ft.)</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 30° W., 295.7 ft. dist., with a healed blaze. (Record, N. 29 1/2° W., 297.7 ft.)</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p align="center">Dependent Resurvey of a Portion of the Subdivision of Section Lines in Section 26, T. 32 S., R. 1 W., Willamette Meridian, Oregon</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p align="center">Restoring the 1965 survey by Joseph S. Gawron and Rollin D. Aanrud</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the 1/4 sec. cor. of secs. 25 and 26, perpetuated by the Jackson County Surveyor's Office in 1987, as shown on the Jackson County Surveyor's Office first reestablishment record in T. 32 S., R. 1 W., point identifier No. 600240; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 32 S R 1 W</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 26</td><td style="padding: 0 5px;">S 25</td></tr> <tr><td colspan="2">1965</td></tr> </table> </div> <p>from which a bearing tree mkd. by Gawron and Aanrud in 1965</p> <p style="margin-left: 40px;">A fir, 23 ins. diam., bears S. 20 1/4° E., 12.5 ft. dist., no marks visible. (Record, S. 24° E.)</p> <p>and a bearing tree mkd. by the Jackson County Surveyor's Office</p>	T 32 S R 1 W		S 21	S 22			S 28	S 27	1955		T 32 S R 1 W		1/4		S 26	S 25	1965	
T 32 S R 1 W																			
S 21	S 22																		
S 28	S 27																		
1955																			
T 32 S R 1 W																			
1/4																			
S 26	S 25																		
1965																			

**Dependent Resurvey of a Portion of the Subdivision of
Section Lines in Section 26,
T. 32 S., R. 1 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 28 ins. diam., bears S. 87° W., 55.2 ft. dist., with a healed double blaze.</p> <p>S. 89° 36' 23" W., on the E. and W. center line of sec. 26.</p>
2618.25	<p>The center 1/4 sec. cor. of sec. 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, flush with collar of stone, with brass cap mkd.</p> <p style="text-align: center;">C 1/4 S 26 1965</p> <p>from which bearing trees mkd. by Gawron and Aanrud in 1965</p> <p>A yew, 14 ins. diam., bears N. 78 1/2° E., 32.3 ft. dist., with a healed blaze. (Record, N. 76 E.)</p> <p>A yew, 9 ins. diam., bears S. 21° E., 18.5 ft. dist., with illegible scribe marks visible on a partially healed blaze.</p> <hr/>