

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF PORTIONS OF THE NORTH BOUNDARY,  
SUBDIVISIONAL LINES,  
AND SUBDIVISION OF SECTION LINES OF SECTION 10,  
AND THE SUBDIVISION OF SECTION 3,  
**TOWNSHIP 20 SOUTH, RANGE 9 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON

---

**EXECUTED BY**

***Jason A. Lightbown, Cadastral Surveyor***

Under Special Instructions approved June 21, 2016,  
which provided for the surveys included under Group No. 2841,  
and Assignment Instructions dated June 21, 2016.

***Survey commenced June 27, 2016***

***Survey completed October 24, 2016***

**T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET

The following field notes are those of the dependent resurvey of portions of the north boundary, subdivisional lines, and subdivision of section lines of section 10, and subdivision of section 3, Township 20 South, Range 9 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1891, William Thiel, U.S. Deputy Surveyor, surveyed portions of the north and east boundaries and subdivisional lines, as shown on the official plat of survey approved May 6, 1893.

In 1899, Henry L. Chandler, U.S. Deputy Surveyor, resurveyed a portion of the south boundary and surveyed the remainder of the south boundary of T. 19 S., R. 9 W., as shown on the official plat of survey approved February 12, 1901.

In 1921-22, Fred Mensch, U.S. Cadastral Engineer, resurveyed a portion of the south boundary of T. 19 S., R. 9 W., resurveyed a portion of the subdivisional lines, and surveyed the remainder of the subdivisional lines of T. 20 S., R. 9 W., as shown on the official plat of survey approved June 30, 1922.

In 1953-54, Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, resurveyed portions of the north boundary and subdivisional lines, as shown on the official plat of survey accepted March 23, 1960.

In 1984, Joel E. Robb, Cadastral Surveyor, subdivided section 10, as shown on the official plat of survey accepted October 31, 1986.

In 2006-09, Edith M. Forkner, Cadastral Surveyor, rehabilitated and remonumented certain corner points, as described in the official field notes approved January 15, 2010.

In 2016, Edith M. Forkner and Jason A. Lightbown, Cadastral Surveyors, resurveyed a portion of the west boundary of T. 19 S., R. 8 W., as shown on the official plat of survey accepted January 25, 2018.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1964	Milo Godfrey, County Surveyor	CS53/66
1972	Richard J. Hintz, PLS No. 497	CS55/259-2
1982	Donald L. Peel, PLS No. 752	M92-28
1993	Wayne R. Donovan, PLS No. 2553	CS63/53-56
2012	Ronald L. Rice, PLS No. 54633	CS65/76-50
2014	Robert B. Ward, Jr., PLS No. 1094	M167-71
2016	Ronald L. Rice, PLS No. 54633	M170-76

**T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET

The 1982 survey by Donald L. Peel, PLS No. 752, established numerous iron rod line markers, 1/2 inch diameter, as indicated on Peel's plat. These iron rods were not used for control during this survey.

In 1977, F. S. Munro, J. P. Farnsworth, and G.L. Freer surveyed a portion of the south boundary and subdivided section 36, T. 19 S., R. 9 W., in an unofficial administrative survey for the Bureau of Land Management (BLM), filed in the Coos Bay District Office of the BLM in North Bend, Oregon.

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions approved for Group No. 2841, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and direct solar observations and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data was thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each new monument established or reestablished has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

Aluminum angle irons were driven alongside each monument unless a similar marker was already in place.

Only those lines bounding Federal interest land were blazed.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The 1/4 section corner of section 36 only, on the south boundary of Township 19 South, Range 9 West:

Latitude: 43° 52' 13.56" N. Longitude: 123° 43' 06.07" W.

The corner of sections 2, 3, 10, and 11:

Latitude: 43° 51' 20.46" N. Longitude: 123° 44' 52.64" W.

**T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>The 1/4 section corner of sections 10 and 15:</p> <p>Latitude: 43° 50' 30.36" N.    Longitude: 123° 45' 28.93" W.</p> <hr/>
	<p style="text-align: center;"><b>Dependent Resurvey of a Portion of the North Boundary, T. 20 S., R. 9 W., Willamette Meridian, Oregon</b></p> <hr/>
	<p>Restoring the 1891 survey by William Thiel, the 1899 survey by Henry L. Chandler, the 1953-54 resurvey by Thomas A. Tillman and Joseph S. Gawron, the 2006-09 rehabilitation by Edith M. Forkner, and the 2016 resurvey by Edith M. Forkner and Jason A. Lightbown</p> <hr/> <p>Beginning at the 1/4 sec. cor. of sec. 36 only, on the S. bdy. of T. 19 S., R. 9 W., perpetuated by Rice, PLS No. 54633, in 2012; monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">1/4 S 36 ----- 1953</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 48 ins. diam., bears S.37° E., 7.9 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Tillman and Gawron in 1953-54</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears N. 26 1/2° E., 7.3 ft. dist., with a double healed blaze.</p> <p>and a bearing tree mkd. by Rice</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 39 1/2° W., 21.9 ft. dist., with a healed blaze.</p> <p>S. 89° 03' 36" E., bet. secs. 1 and 36.</p>
81.97	<p>The 1/4 sec. cor. of sec. 1 only, perpetuated by Donovan, PLS No. 2553, in 1993; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">----- 1/4 S 1 1953</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir stump, 24 ins. diam., bears N. 29° W., 19.1 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54</p>

**Dependent Resurvey of a Portion of the North Boundary,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed fir stump, 14 ins. diam., bears S. 55 1/2° E., 37.6 ft. dist., with a healed blaze.</p> <p>A decayed fir stump, 13 ins. diam., bears S. 68 1/2° W., 27.6 ft. dist., with 1/4 visible on open blaze.</p> <p>and the bearing trees mkd. by Donovan</p> <p>A fir, 18 ins. diam., bears S. 44 3/4° E., 15.4 ft. dist., with a healed blaze.</p> <p>A fir, 21 ins. diam., bears S. 23 1/4° W., 54.2 ft. dist., with a double healed blaze.</p> <hr/> <p>S. 89° 43' 53" E., beginning new measurement.</p>
140	Roman Nose Road, asphalt surface, 12 ft. wide, bears N. 55° E. and S. 55° W.
1240.29	<p>The E 1/16 sec. cor. of sec. 36 only, on the S. bdy. of T. 19 S., R. 9 W., established by an unofficial administrative survey conducted for the BLM in 1977; utilized by Ward, PLS No. 1091, in 2014; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, from which the bearing trees mkd. by the BLM and scribed by Ward</p> <p>A fir, 66 ins. diam., bears N. 30° E., 43.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A maple, 19 ins. diam., bears N. 66° W., 19.3 ft. dist., with scribe marks E1/16 S36 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over iron rod, with brass cap mkd.</p> <p align="center">E 1/16 S 36</p> <hr/> <p align="center">2016</p> <p>From this cor., a point erroneously established as the E 1/16 sec. cor. of sec. 36 only, on the S. bdy. of T. 19 S., R. 9 W., by Hintz, PLS No. 497, in 1972, bears S. 80° 14' 03" W., 2.50 ft. dist.; monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 2 ins. above ground. This point was established using improper procedures and was not utilized in the course of this survey.</p> <hr/> <p>S. 89° 38' 50" E., beginning new measurement.</p>
900	Ridge, bears N. 35° E. and S. 65° W.

23604

**Dependent Resurvey of a Portion of the North Boundary,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
1322.46	Point for the 1/16-80 sec. cor. of sec. 36 only, on the S. bdy. of T. 19 S., R. 9 W.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over iron rod, with brass cap mkd.
	$\frac{1/16 \text{ S}36 \text{ 80}}{2016}$
	from which the remains of the bearing trees mkd. by the BLM during an unofficial administrative survey
	A decayed fir stump, 26 ins. diam., bears S. 52° W., 13.1 ft. dist., no marks visible.
	A fir, 56 ins. diam., bears N. 74 1/4° W., 37.6 ft. dist., with a chaining notch.
	and new bearing trees
	A fir, 10 ins. diam., bears N. 71 1/4° E., 18.2 ft. dist., mkd. 1/16-80 S36 BT.
	A fir, 9 ins. diam., bears N. 9° W., 20.6 ft. dist., mkd. X at breast height and BT at base.
	A point erroneously established as the 1/16-80 sec. cor. of sec. 36 only, on the S. bdy. of T. 19 S., R. 9 W., by an unofficial administrative survey conducted by the BLM in 1977, was located alongside the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground. The iron rod was disturbed during establishment of the cor. and buried under the stainless steel post.
	From this cor., a point erroneously established as the 1/16-80 sec. cor. of sec. 36 only, on the S. bdy. of T. 19 S., R. 9 W., by Hintz, PLS No. 497, in 1972, bears S. 86° 55' 09" W., 4.72 ft. dist.; monumented with an iron rod, 5/8 in. diam., firmly set, 2 ins. below ground. This point was established using improper procedures and was not utilized in the course of this survey. The fir with a location sign by Hintz is the same tree as the SW. administrative bearing tree.
	_____
	S. 89° 38' 50" E., beginning new measurement.
	310 Creek, 2 ft. wide, course S. 15° E.
	805 Creek, 3 ft. wide, course South.
	1328.35 The closing cor. of Tps. 19 and 20 S., R. 9 W., on the W. boundary of T. 19 S., R. 8 W., with brass cap mkd. and accessories as described in the official resurvey by Forkner and Lightbown in 2016.
	_____

23605

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET									
	<p>Restoring the 1891 survey by William Thiel, the 1921-22 resurvey and survey by Fred Mensch, the 1953-54 resurvey by Thomas A. Tillman and Joseph S. Gawron, and the 2006-09 rehabilitation by Edith M. Forkner in 2006-09</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"><table border="1"><tr><td>T 20 S</td><td>R 9 W</td></tr><tr><td>S 3</td><td>S 2</td></tr><tr><td>S 10</td><td>S 11</td></tr><tr><td colspan="2">1921</td></tr></table></div> <p>from which the remains of an original bearing tree</p> <p>A roothole bears S. 86° W., 17.8 ft. dist., alongside of which is decayed fir remains, size indeterminate, no marks visible.</p> <p>and the remains of a bearing tree mkd. by Tillman and Gawron in 1953-54</p> <p>A roothole bears S. 4 1/4° E., 25.1 ft. dist., alongside of which is a down fir, 40 ins. diam., no marks visible.</p> <p>and the bearing trees mkd. by Forkner in 2006-09</p> <p>A chinquapin, 5 ins. diam., bears N. 78° E., 12.8 ft. dist., with healed X visible at breast height and scribe marks BT visible on bark at base.</p> <p>A fir, 13 ins. diam., bears S. 2 1/2° E., 21.9 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears S. 53° W., 3.4 ft. dist., with a healed blaze.</p> <p>A fir, 7 ins. diam., bears N. 23° W., 5.5 ft. dist., with a healed blaze at breast height and at base.</p> <p>A concrete-filled iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above ground, is alongside the cor.</p> <p>N. 0° 05' 01" W., bet. secs. 2 and 3.</p>	T 20 S	R 9 W	S 3	S 2	S 10	S 11	1921	
T 20 S	R 9 W								
S 3	S 2								
S 10	S 11								
1921									
100	Dirt road, 15 ft. wide, bears N. 60° W. and S. 60° E.								
1304.91	<p>Point for the S 1/16 sec. cor. of sec. 3 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"><table border="1"><tr><td>S 1/16</td></tr><tr><td>S 3</td></tr><tr><td>2016</td></tr></table></div>	S 1/16	S 3	2016					
S 1/16									
S 3									
2016									

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
1470.87	<p>from which</p> <p>An alder, 10 ins. diam., bears S. 70 3/4° W., 20.7 ft. dist., mkd. S1/16 S3 BT on bark.</p> <p>A hemlock, 12 ins. diam., bears N. 1° W., 25.4 ft. dist., mkd. S1/16 S3 BT.</p> <p>Point for the S 1/16 sec. cor. of sec. 2 only.</p> <p>Set an iron rod, 23 ins. long, 5/8 in. diam., 19 ins. in solid sandstone, with aluminum cap, 3 ins. diam., mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{ c} \text{S } 1/16 \\ \text{S } 2 \\ \hline 2016 \end{array}</math> </div>
2609.81	<p>from which</p> <p>An alder, 11 ins. diam., bears N. 70° E., 35.9 ft. dist., mkd. S1/16 S2 BT on bark.</p> <p>A hemlock, 21 ins. diam., bears S. 11 1/2° E., 62.2 ft. dist., mkd. S1/16 S2 BT.</p> <p>The 1/4 sec. cor. of sec. 3 only, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{ c} 1/4 \\ \text{S } 3 \\ \hline 1921 \end{array}</math> </div>
331.97	<p>from which the remains of the original bearing trees</p> <p>A metal-capped fir stump, 41 ins. diam., bears S. 86° W., 23.8 ft. dist., with a healed blaze.</p> <p>A metal-capped fir stump, 38 ins. diam., bears N. 37° W., 58.1 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 21 ins. diam., bears S. 73° W., 15.4 ft. dist., mkd. 1/4 S3 BT.</p> <p>A fir, 22 ins. diam., bears N. 39 1/2° W., 4.2 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 00' 17" W., between secs. 2 and 3, beginning new measurement.</p> <p>The 1/4 sec. cor. of sec. 2 only, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with a brass cap, oriented S., mkd.</p>

23607

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">  1/4   S 2 1921</p> <p>from which the remains of a bearing tree mkd. by Mensch in 1921-22</p> <p>A metal-capped fir stump, 33 ins. diam., bears S. 30° E., 24.4 ft. dist., with scribe marks 1/4 S BT visible on open blaze.</p> <p>and the remains of the bearing trees mkd. by Forkner in 2006-09</p> <p>A roothole bears N. 33° E., 10.8 ft. dist., alongside of which a down fir, 15 ins. diam., with a healed blaze.</p> <p>A fir, 22 ins. diam., bears S. 48 1/2° E., 17.0 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 21 ins. diam., bears N. 46 3/4° E., 35.6 ft. dist., mkd. X BT.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 3 and 10, perpetuated by Peel, PLS No. 752, in 1982, not reported by Robb in 1984; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">S 3 1/4 ——— S 10 1921</p> <p>from which the remains of a bearing tree mkd. by Peel</p> <p>A fir stump with railroad spike set in top, 32 ins. diam., bears N. 12° E., 47.5 ft. dist., with illegible scribe marks visible on open blaze.</p> <p>A fir, 58 ins. diam., bears S. 41 1/2° W., 25.1 ft. dist., with a healed blaze. This tree was incorrectly reported as being by person's unknown by Robb.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 13 ins. diam., bears N. 7° E., 45.5 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 44 ins. diam., bears S. 32 1/4° W., 25.9 ft. dist., mkd. 1/4 S10 BT.</p> <p>S. 89° 35' 02" W., bet. secs. 3 and 10.</p>
825	Creek, 4 ft. wide, course S. 40° W.
915	Creek, 5 ft. wide, course South.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET									
1323.92	Point for the W 1/16 sec. cor. of secs. 3 and 10, not monumented.								
1925	Dirt road, 15 ft. wide, bears North and South.								
2405	Crane Creek, 8 ft. wide, course S. 80° E.								
2647.84	<p>The cor. of secs. 3, 4, 9, and 10, perpetuated by Godfrey, Deputy Douglas County Surveyor, based on an affidavit by Fred Zeigler, in 1964, who provided testimonial evidence of the original cor. position which had been obliterated by the creek; monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, in a collar of stone, with a brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T 20 S</td> <td>R 9 W</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td colspan="2">1964</td> </tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Godfrey</p> <p style="padding-left: 40px;">A fir stump, 52 ins. diam., bears N. 30° E., 150.3 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A metal-capped fir stump, 53 ins. diam., bears N. 70 1/2° W., 62.7 ft. dist., with scribe marks R9W S4 CS B visible on partially healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">An alder, 12 ins. diam., bears N. 57° E., 26.4 ft. dist., mkd. T20S R9W S3 BT on bark.</p> <p style="padding-left: 40px;">An alder, 13 ins. diam., bears S. 44 1/4° E., 29.2 ft. dist., mkd. T20S R9W S10 BT on bark.</p> <p style="padding-left: 40px;">An alder, 13 ins. diam., bears S. 61 3/4° W., 35.9 ft. dist., mkd. T20S R9W S9 BT on bark.</p> <p style="padding-left: 40px;">An alder, 17 ins. diam., bears N. 2 1/4° W., 61.4 ft. dist., mkd. T20S R9W S4 BT on bark.</p> <p>Corner is located on the E. edge of a creek, 5 ft. wide, course N. 30° E.</p> <hr/> <p>N. 0° 09' 15" W., bet. secs. 3 and 4.</p>	T 20 S	R 9 W	S 4	S 3	S 9	S 10	1964	
T 20 S	R 9 W								
S 4	S 3								
S 9	S 10								
1964									
85	Creek, 4 ft. wide, course S. 55° E.								
410	Graveled road, 12 ft. wide, N. 70° W., S. 70° E.								
1310.98	The S 1/16 sec. cor. of secs. 3 and 4, established by Peel, PLS No. 752, in 1982; and is accepted as the cor.; monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p align="center">T 20 S PLS 752 R 9 W S 1/16 S3 1982</p> <p>from which the remains of the bearing trees mkd. by Peel</p> <p>A fir snag, 20 ins. diam., bears N. 41 1/2° E., 76.9 ft. dist., with a healed blaze.</p> <p>A fir, 48 ins. diam., bears N. 57 1/4° W., 64.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A maple, 15 ins. diam., bears N. 65 1/2° E., 49.9 ft. dist., mkd. S 1/16 S3 BT.</p> <hr/> <p>N. 0° 06' 53" W., beginning new measurement.</p> <p>1311.18 The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.</p> <p align="center">T 20 S S 4   S 3 1/4 R 9 W 1975</p> <p>from which the remains of the original bearing trees</p> <p>A metal-capped fir stump, 53 ins. diam., bears S. 35° E., 23.1 ft. dist., no marks visible.</p> <p>A metal-capped fir stump, 61 ins. diam., bears N. 84° W., 21.8 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Forkner</p> <p>A fir, 10 ins. diam., bears N. 81 1/4° E., 12.5 ft. dist., with a healed blaze. (Record, N. 80° E., 13.5 ft. dist.)</p> <p>A fir, 15 ins. diam., bears N. 79 3/4° W., 17.7 ft. dist., with a healed blaze. (Record, N. 82° W., 18.7 ft. dist.)</p> <p>A rusted, concrete-filled iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, is alongside the cor.</p> <hr/>
------	--

**23610**  
**Dependent Resurvey of a Portion of the**  
**Subdivision of Section Lines of Section 10,**  
**T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	Restoring the 1984 survey by Joel E. Robb
	<p style="text-align: center;">From the 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post,  1 in. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} \text{S } 10 \\ 1/4 \text{ ---} \\ \text{S } 15 \\ 1954 \end{array}</math> </div> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A maple, 78 ins. diam., bears S. 87 1/2° W., 43.6 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Tillman and Gawron in 1953-54</p> <p style="padding-left: 40px;">A fir stump, 50 ins. diam., bears N. 28 1/2° W., 25.7 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">An alder, 13 ins. diam., bears N. 40 1/2° E., 32.2 ft. dist., mkd. 1/4 S10 BT on bark.</p> <p>A rusted, concrete-filled iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, is alongside the cor.</p> <p>N. 0° 12' 39" E., on the N. and S. center line of sec. 10.</p>
1640	Creek, 2 ft. wide, course N. 65° E.
1900	Graveled road, 15 ft. wide, bears N. 20° W. and S. 20° E.
2110	Crane Creek, 10 ft. wide, course S. 20° E.
2599.69	<p>The center 1/4 sec. cor. of sec. 10, monumented with an iron post,  2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} \text{T } 20 \text{ S } \text{ R } 9 \text{ W} \\ \text{C } 1/4 \text{ S } 10 \\ 1984 \end{array}</math> </div> <p>from which the bearing trees mkd. by Robb in 1984</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 17 1/4° E., 79.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A maple, 16 ins. diam., bears N. 64° W., 15.5 ft. dist., with a healed blaze  (Record, N. 60 1/2° W., 14.9 ft. dist.).</p> <hr style="width: 60%; margin-left: auto; margin-right: auto;"/>

23611

**Subdivision of Section 3  
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
1302.17	<p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0° 30' 52" W., on the N. and S. center line of sec. 3.</p> <p>The center S 1/16 sec. cor. of sec. 3, established by Peel, PLS No. 752, in 1982; and is accepted as the cor.; monumented with a brass cap, 2 1/2 ins. diam., firmly set in sandstone, flush with the surface, mkd.</p> <p style="text-align: center;">T 20 S PLS 752 R 9 W CS 1/16 S 3 1982</p> <p>from which the remains of a bearing tree mkd. by Peel</p> <p style="padding-left: 40px;">A fir snag, 59 ins. diam., bears N. 88 1/2° W., 94.3 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A maple, 20 ins. diam., bears N. 43 3/4° E., 99.6 ft. dist., mkd. CS1/16 S3 BT.</p> <p style="padding-left: 40px;">An alder, 37 ins. diam., bears S. 21 1/2° E., 63.0 ft. dist., mkd. CS1/16 S3 BT on bark.</p> <hr style="width: 20%; margin: 10px auto;"/>
1302.09	<p>N. 0° 30' 02" W., beginning new measurement.</p> <p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.</p> <p>Set an iron rod, 5/8 in. diam., 30 ins. long, 28 ins. in a rock ledge, with an aluminum cap mkd.</p> <p style="text-align: center;">T 20 S R 9 W C 1/4 S3 2016</p> <p>from which</p> <p style="padding-left: 40px;">An alder, 13 ins. diam., bears S. 46° W., 35.2 ft. dist., mkd. C1/4 S3 BT on bark.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 36° W., 14.7 ft. dist., mkd. C1/4 S3 BT.</p>
4052.88	<p>The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp., perpetuated by Peel, PLS No. 752, in 1982, from original evidence no longer visible; subsequently perpetuated by Rice, PLS No. 54633, in 2016; monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p>

23612

Subdivision of Section 3  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T 20 S R 9 W ----- 1/4 S3 PLS 752 1982</p> <p>from which the remains of the bearing trees mkd. by Peel</p> <p>A burned decayed fir stump, 42 ins. diam., bears S. 67° E., 43.7 ft. dist., with illegible scribe marks visible on open blaze.</p> <p>A fir, 46 ins. diam., bears S. 8 1/4° W., 45.6 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Rice</p> <p>A fir, 6 ins. diam., bears S. 69 1/2° E., 11.3 ft. dist., with scribe marks X BT visible on partially healed blaze.</p> <p>A fir, 13 ins. diam., bears S. 15° W., 13.9 ft. dist., with scribe marks 1/4 S3 BT visible on partially healed blaze.</p> <hr/>
	<p>From the 1/4 sec. cor. of sec. 3 only, on the E. bdy. of the sec. S. 89° 58' 23" W., on the E. and W. center line of sec. 3.</p> <p>2655.82 The center 1/4 sec. cor. of sec. 3.</p> <p>3971.08 Point for the center W 1/16 sec. cor. of sec. 3, not monumented.</p> <p>5286.34 The 1/4 sec. cor. of secs. 3 and 4.</p> <hr/>
	<p>From the S 1/16 sec. cor. of sec. 3 only, on the E. bdy. of the sec. N. 89° 57' 53" W., on the E. and W. center line of the SE1/4 of sec. 3.</p> <p>285 Ridge, bears N. 30° E. and S. 30° W.</p> <p>740 Creek, dry, 10 ft. wide, course N. 20° E.</p> <p>940 Ridge, bears S. 20° E. and N. 20° W.</p> <p>980 Ravine, drains S. 30° E.</p> <p>1490 Ridge, bears S. 35° E. and N. 35° W.</p> <p>1770 Ravine, drains N. 45° E.</p> <p>2380 Ridge, bears N. 5° E. and S. 5° W.</p> <p>2630 Ravine, drains N. 15° W.</p>

23613

Subdivision of Section 3  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

FEET	
2646.51	The center S 1/16 sec. cor. of sec. 3. <hr/>
	From the W 1/16 sec. cor. of secs. 3 and 10. N. 0° 20' 17" W., on the N. and S. center line of the SW 1/4 of sec. 3.
1306.56	The SW 1/16 sec. cor. of sec. 3, established by Peel, PLS No. 752, in 1982; and is accepted as the cor.; monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd. <p style="text-align: center;">T20S PLS 752 R9W SW 1/16 S 3 1982</p> from which the remains of the bearing trees mkd. by Peel <p style="margin-left: 40px;">A fir stump, 28 ins. diam., bears N. 10 1/4° E., 34.4 ft. dist., with illegible scribe marks visible on partially healed decayed blaze.</p> <p style="margin-left: 40px;">A fir stump, 44 ins. diam., bears S. 80 1/2° W., 26.7 ft. dist., with scribe marks SW1/16 S3 BT visible on open blaze.</p> and new bearing trees <p style="margin-left: 40px;">A fir, 19 ins. diam., bears S. 45 1/2° W., 21.3 ft. dist., mkd. SW1/16 S3 BT.</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 39 1/4° W., 6.0 ft. dist., mkd. SW1/16 S3 BT.</p> <hr/>
1306.64	N. 0° 18' 09" W., beginning new measurement. The center W 1/16 sec. cor. of sec. 3. <hr/>
	From the center S 1/16 sec. cor. of sec. 3. S. 89° 46' 29" W., on the E. and W. center line of the SW1/4 of sec. 3.
130	Ridge, bears S. 40° E. and N. 30° W.
800	Creek, 2 ft. wide, course N. 60° W.
1319.83	The SW 1/16 sec. cor. of sec. 3. <hr/>
	S. 89° 46' 29" W., beginning new measurement.
190	Crane Creek, 10 ft. wide, course S. 10° E.
1055	Ridge, bears N. 25° E. and S. 25° W.

23614

**Subdivision of Section 3  
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
1290	Creek, 3 ft. wide, course N. 30° W.
1319.63	The S 1/16 sec. cor. of secs. 3 and 4. <hr/>