

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

AND SUBDIVISION OF SECTION LINES OF SECTION 17,

AND THE SUBDIVISION OF SECTION 5,

TOWNSHIP 30 SOUTH, RANGE 9 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON

EXECUTED BY

Randolph E. Younis, Cadastral Surveyor

Under Special Instructions approved August 9, 2016,
which provided for the surveys included under Group No. 2849,
and Assignment Instructions dated August 10, 2016.

Survey commenced September 8, 2016

Survey completed March 16, 2017

T. 30 S., R. 9 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and subdivision of section lines of section 17, and the subdivision of section 5, Township 30 South, Range 9 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1855, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the north boundary of the township, as shown on the official plat of survey approved July 7, 1856.

In 1893, William M. Bushey, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved June 26, 1894.

In 1907, William M. Porter, U.S. Deputy Surveyor, dependently resurveyed a portion of the south boundary of T. 29 S., R. 9 W., as shown on the official plat of survey approved March 19, 1909, amended and approved October 5, 1909.

In 1962, James E. Jelley, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted July 9, 1964.

In 1977-78, Jack W. Bowder, Cadastral Surveyor, remonumented the 1/4 section corner of sections 5 and 32 on the south boundary of T. 29 S., R. 9 W., as described in the official field notes approved February 7, 1980.

In 1980, Harvey E. Wofford, Cadastral Surveyor, surveyed a portion of the subdivisional lines as shown on the official plat of survey accepted May 11, 1984.

In 1982-83, Herman A. Pieske, Registered Land Surveyor No. 1651, dependently resurveyed a portion of the subdivisional lines and subdivided section 17, under Contract No. YA-553-CT2-67, as shown on the official plat of survey accepted April 20, 1984.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

| <u>Date</u> | <u>Name and Registration Number</u> | <u>File Number</u> |
|-------------|-------------------------------------|--------------------|
| 1965 | John M. Powell, Deputy Co. Surveyor | CS 53/53 |
| 1971 | Forest LaFlamme, PLS No. 473 | CS 55/209 |
| 1980 | Ronald E. Stuntzner, PLS No. 1342 | M85-18 |
| 1981 | Ronald E. Stuntzner, PLS No. 1342 | M87-20 |
| 1983 | Herman A. Pieske, PLS No. 1651 | M93-71 |
| 1/2001 | Gary T. Smither, PLS No. 2485 | M136-54 |
| 3/2001 | Gary T. Smither, PLS No. 2485 | CS 65/37-4 |
| 2015 | Michael L. Dado, PLS No. 2661 | CS 65/87-34 |

T. 30 S., R. 9 W., Willamette Meridian, Oregon

FEET

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions approved August 9, 2016, for Group No. 2849, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and direct solar observations and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data was thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description. Aluminum angle irons were driven alongside each monument unless a similar marker was already in place.

Only those lines bounding Federal interest land were blazed.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The south 1/16 section corner of sections 4 and 5:

Latitude: 42° 59' 08.49" N. Longitude: 123° 46' 52.50" W.

The north 1/16 section corner of sections 17 and 18:

Latitude: 42° 57' 50.51" N. Longitude: 123° 48' 03.74" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

Restoring the survey by William M. Bushey in 1893, the resurvey by James E. Jelley in 1962, the resurvey by Harvey E. Wofford in 1980, and the resurvey by Herman A. Pieske in 1982-83

23618

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

| FEET | | | | | | | | | | | |
|-----------|---|--------|-----------|------|-----|-------|--|-----|-----|------|--|
| | <p>Beginning at the cor. of secs. 4, 5, 8, and 9, perpetuated by Smither, PLS No. 2485, in March 2001; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"><table border="1"><tr><td>T 30 S</td><td>R 9 W</td></tr><tr><td>S 5</td><td>S 4</td></tr><tr><td colspan="2"><hr/></td></tr><tr><td>S 8</td><td>S 9</td></tr><tr><td colspan="2">1962</td></tr></table></div> <p>from which the remains of the original bearing trees</p> <p>A fir stump, 28 ins. diam., bears N. 83° E., 25.4 ft. dist., with a healed blaze.</p> <p>A badly decayed fir stump, 22 ins. diam., bears S. 50° W., 30.7 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Smither</p> <p>A decayed fir snag, 7 ins. diam., bears S. 70 3/4° E., 5.3 ft. dist., with hacked X at breast height and scribe marks BT visible on partially healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 21 3/4° E., 18.9 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears S. 82 3/4° W., 15.7 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A chinquapin, 8 ins. diam., bears N. 62 3/4° E., 12.7 ft. dist., mkd. T30S R9W S4 BT.</p> <p>A fir, 16 ins. diam., bears N. 71 1/4° W., 38.4 ft. dist., mkd. T30S R9W S5 BT.</p> <p>The original basalt stone, 8 x 8 ins., firmly set, projecting 10 ins. above ground, with 5 notches on S. edge and 4 notches on E. edge, is alongside the cor.</p> <p>N. 0° 59' 09" W., bet. secs. 4 and 5.</p> | T 30 S | R 9 W | S 5 | S 4 | <hr/> | | S 8 | S 9 | 1962 | |
| T 30 S | R 9 W | | | | | | | | | | |
| S 5 | S 4 | | | | | | | | | | |
| <hr/> | | | | | | | | | | | |
| S 8 | S 9 | | | | | | | | | | |
| 1962 | | | | | | | | | | | |
| 1329.85 | <p>The S 1/16 sec. cor. of secs. 4 and 5, perpetuated by Stuntzner, PLS No. 1342, in 1981; monumented with an iron post, 2 1/2 ins. diam., firmly set in the center of a gravel road, 12 ft. wide, bears N 60° E and S 60° W., with top 22 ins. below the surface, with a brass cap mkd.</p> <div style="text-align: center;"><table border="1"><tr><td>S 1/16</td></tr><tr><td>S 5 S 4</td></tr><tr><td>1980</td></tr></table></div> <p>from which the remains of the bearing trees mkd. by Wofford in 1980</p> | S 1/16 | S 5 S 4 | 1980 | | | | | | | |
| S 1/16 | | | | | | | | | | | |
| S 5 S 4 | | | | | | | | | | | |
| 1980 | | | | | | | | | | | |

23619

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

| FEET | |
|------|--|
| | <p>A fir high stump, 18 ins. diam., bears S. 47 1/4° E., 17.8 ft. dist., with a healed blaze.</p> <p>A fir, 51 ins. diam., bears N. 25 1/2° W., 40.9 ft. dist., with a healed blaze.</p> <p>and a reference monument established by Stuntzner</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, bears N. 89° 55' 14" W., 65.36 ft. dist.</p> <p>and new accessories</p> <p>A grand fir, 8 ins. diam., bears N. 32 1/4° E., 39.9 ft. dist., mkd. S1/16 S4 BT.</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 30 ins. in the ground for a reference monument, bears S. 55° 46' 22" W, 69.3 ft. dist., with aluminum cap mkd. RM S1/16 69.3 FT TO COR 2016 and an arrow pointing to the cor.</p> |
| | <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd.</p> |
| | <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S R 9 W 1/4 S 18 S 17 4 1965</p> |
| | <p>from which the remains of the bearing trees mkd. by Powell, Deputy Douglas County Surveyor, in 1965, reported by Pieske in 1982-83</p> |
| | <p>A cedar high stump, 26 ins. diam., bears S. 81 1/2° E., 45.6 ft. dist., with a healed blaze. (Record, S. 80° E., 46.2 ft. dist.)</p> |
| | <p>A fir, 29 ins. diam., bears N. 36 1/4° W., 51.5 ft. dist., with a healed blaze. (Record, N. 32° W.)</p> |
| | <p>and a new bearing tree</p> |
| | <p>A cedar, 6 ins. diam., bears S. 19 3/4° E., 12.5 ft. dist., mkd. 1/4 S17 BT. N. 0° 52' 42" W., bet. secs. 17 and 18.</p> |
| 175 | Graveled road, 15 ft. wide, bears N. 45° E. and S. 45° W. |
| 865 | Graveled road, 15 ft. wide, bears N. 75° E. and S. 75° W. |
| 985 | Graveled road, 9 ft. wide, bears E. and W. |

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| 1020 | Left bank of the Middle Fork Coquille River, bears S. 75° E. and N. 75° W., course N. 75° W. |
| 1100 | Right bank of the Middle Fork Coquille River, bears S. 75° E. and N. 75° W., course N. 75° W. |
| 1242 | Oregon State Highway No. 42, asphalt surfaced, 40 ft. wide, bears S. 82° E. and N. 82° W. |
| 1327.86 | The N 1/16 sec. cor. of secs. 17 and 18, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with an aluminum cap mkd. <div style="text-align: center;"> N 1/16 S 18 S 17 T 30 S R 9 W 1982 </div> from which new bearing trees A fir, 10 ins. diam., bears N. 57 1/4° E., 54.3 ft. dist., mkd. N1/16 S17 BT. A madrone, 12 ins. diam., bears N. 24 1/2° W., 27.9 ft. dist., mkd. N1/16 S18 BT. |
| 80 | Graveled road, 14 ft. wide, bears S. 45° E. and N. 45° W. |
| 365 | Graveled road, 14 ft. wide, bears N. 30° E. and S. 50° W. |
| 1455 | Ravine, drains N. 70° W. |
| 2648.75 | The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with a brass cap mkd. <div style="text-align: center;"> S 5 1/4 ——— S 8 T 30 S R 9 W 1962 </div> from which new accessories A hemlock, 21 ins. diam., bears N. 57 1/2° E., 36.2 ft. dist., mkd. 1/4 S5 BT. An iron rod, 24 ins. long, 5/8 in. diam., set 24 ins. in the ground for a reference monument, bears N. 43° 26' 04" W, 20.25 ft. dist., with |

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

FEET

aluminum cap mkd. RM T30S R9W 1/4 S5 20.2 FT TO COR 2016 and an arrow pointing to the cor.

From this cor., the remains of an original line tree recovered by Jelley in 1962 bears S. 89° 13' 37" W., 11.2 ft. dist., monumented with a burnt fir stump, 54 ins. diam., no marks visible.

**Dependent Resurvey of a Portion of the
Subdivision of Section Lines of Section 17,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

Restoring the survey by Herman A. Pieske in 1982-83

From the 1/4 sec. cor. of secs. 17 and 20, perpetuated by LaFlamme, PLS No. 473, in 1971; further perpetuated by Smither, PLS No. 2485, in January 2001; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S

S 17

1/4 _____

S 20

R 9 W

1964

from which an original bearing tree

A fir, 34 ins. diam., bears N. 58° E., 8.6 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by LaFlamme

A badly decayed fir stump, 8 ins. diam., bears S. 23 3/4° W., 49.9 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Smither

A fir, 10 ins. diam., bears S. 13° E., 40.0 ft. dist. to spike found in left side center, with a hacked X at breast height and healed blaze at base.

A fir high stump, 18 ins. diam., bears N. 88 1/4° W., 32.2 ft. dist., with a healed blaze.

A fir, 24 ins. diam., bears N. 19 3/4° W., 31.9 ft. dist. to spike found in left side center, with a healed blaze.

and a new reference monument

23622
Dependent Resurvey of a Portion of the
Subdivision of Section Lines of Section 17,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

| FEET | |
|---------|--|
| 1327.85 | <p>An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears N. 71° 00' 08" W, 31.16 ft. dist., with aluminum cap mkd. RM T30S R9W 1/4 S17 31.2 FT TO COR 2016 and an arrow pointing to the cor.</p> <p>N. 0° 20' 53" W., on the N. and S. center line of sec. 17.</p> <p>The center S 1/16 sec. cor. of sec. 17, established by Pieske, PLS No. 1651, in 1983; and is accepted as the cor.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W C S 1/16 S 17 C PLS 1651 1983</p> <p>from which the remains of the bearing trees mkd. by Pieske</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 84 1/2° E., 5.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir high stump, 15 ins. diam., bears N. 24 3/4° W., 11.7 ft. dist., with a double healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 33° W., 23.4 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 22' 52" W., beginning new measurement.</p> <p>The center 1/4 sec. cor. of sec. 17, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W C 1/4 S 17 1982</p> <p>from which the remains of a bearing tree mkd. by Pieske in 1982-83</p> <p style="padding-left: 40px;">A fir high stump, 18 ins. diam., bears S. 59° W., 13.9 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 34 1/4° E., 78.4 ft. dist., mkd. C1/4 S17 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 51 1/4° W., 60.9 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> |
| 1328.10 | <p>The center 1/4 sec. cor. of sec. 17, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W C 1/4 S 17 1982</p> <p>from which the remains of a bearing tree mkd. by Pieske in 1982-83</p> <p style="padding-left: 40px;">A fir high stump, 18 ins. diam., bears S. 59° W., 13.9 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 34 1/4° E., 78.4 ft. dist., mkd. C1/4 S17 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 51 1/4° W., 60.9 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> |

23623
Dependent Resurvey of a Portion of the
Subdivision of Section Lines of Section 17,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

| FEET | |
|--|--|
| | <p>From the center N 1/16 sec. cor. of sec. 17, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W C N 1/16 S 17 C 1982</p> <p>from which a bearing tree mkd. by Pieske in 1982-83</p> <p style="padding-left: 40px;">A tanoak, 15 ins. diam., bears N. 53 3/4° E., 21.8 ft. dist., with a healed blaze and bearing tree tag. (Record, N. 78° E., 15.8 ft. dist.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 9° E., 16.7 ft. dist., mkd. CN1/16 S17 BT.</p> <p>Corner is located at the top of the left bank of the Middle Fork of the Coquille River, bears N. 55° E. and S. 55° W., course S. 55° W.</p> <p>S. 89° 51' 47" W., on the E. and W. center line of the NW1/4 of sec. 17.</p> |
| 245 | Left bank of the Middle Fork Coquille River, bears N. 85° E. and S. 85° W., course S. 85° W. |
| 1145 | Right bank of the Middle Fork Coquille River, bears N. 80° E. and S. 80° W., course S. 80° W. |
| 1519 | South edge of pavement of Oregon State Highway No. 42, asphalt surfaced, 40 ft. wide, bears N. 71° E. and S. 71° W. |
| 1656 | North edge of pavement of Oregon State Highway No. 42, asphalt surfaced, bears N. 73° E. and S. 73° W. |
| 2663.63 | The N 1/16 sec. cor. of secs. 17 and 18. |
| <hr/> <p>Subdivision of Section 5, T. 30 S., R. 9 W., Willamette Meridian, Oregon</p> <hr/> | |
| | <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 1° 04' 49" W., on the N. and S. center line of sec. 5.</p> |
| 615 | Graveled road, 16 ft. wide, bears N. 60° E. and S. 60° W. |
| 1322.12 | The center S 1/16 sec. cor. of sec. 5, established by Stuntzner, PLS No. 1342, in 1981; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, from which a bearing tree mkd. by Stuntzner |

23624

Subdivision of Section 5,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

| FEET | |
|---------|---|
| | <p>A fir, 33 ins. diam., bears S. 85° E., 37.0 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over iron rod, with a brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 5 C 2016</p> <p>and a new bearing tree</p> <p>A fir, 8 ins. diam., bears N. 6 3/4° W., 13.2 ft. dist., mkd. CS1/16 S5 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 1° 16' 02" W., beginning new measurement.</p> |
| 1320.21 | <p>The center 1/4 sec. cor. of sec. 5, established by Stuntzner, PLS No. 1342, in 1980; and is accepted as the cor.; determined at record bearing and distance from a bearing tree mkd. by Stuntzner</p> <p>A hemlock snag, 15 ins. diam., bears N. 83° E., 13.2 ft. dist. to a spike in the root collar, with a bearing tree tag, and no other marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with a brass cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W C 1/4 S 5 2016</p> <p>from which new bearing trees</p> <p>A cedar, 18 ins. diam., bears N. 49° E., 9.9 ft. dist., mkd. C1/4 S5 BT.</p> <p>A hemlock, 10 ins. diam., bears N. 50° W., 27.0 ft. dist., mkd. C1/4 S5 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 1° 09' 15" W., beginning new measurement.</p> |
| 160 | Creek, 2 ft. wide, course N. 15° W. |
| 270 | Creek, 12 ft. wide, course N. 85° W. |
| 2515.95 | <p>The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., perpetuated by Dado, PLS No. 2661, in 2015; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> |

23625

Subdivision of Section 5,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

| FEET | |
|------|--|
| | <p style="text-align: center;">T 29 S R 9 W S 32 1/4 ——— S 5 T 30 S 1978</p> <p>from which the remains of an original bearing tree</p> <p>A fir stump, 44 ins. diam., bears S. 27° E., 13.2 ft. dist., with scribe marks BT visible on open blaze.</p> <p>and the bearing trees mkd. by Bowder in 1978</p> <p>A hemlock, 22 ins. diam., bears N. 23° E., 42.9 ft. dist., with a healed blaze. (Record, N. 24 1/2° E., 43.2 ft.)</p> <p>A hemlock, 38 ins. diam., bears S. 18° E., 33.7 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Dado</p> <p>A hemlock, 40 ins. diam., bears S. 58 1/2° W., 13.9 ft. dist., with scribe marks 1/4 S5 BT visible on bark and a spike in left side center.</p> <p>The original sandstone, 10 x 9 ins., firmly set, projecting 5 ins. above ground, with an X on top, is alongside the cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W 1/4 S 5 S 4 1980</p> <p>from which the remains of the bearing trees mkd. by Wofford in 1980</p> <p>A hemlock stump, 31 ins. diam., bears N. 57° E., 25.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A hemlock snag, 14 ins. diam., bears S. 73 3/4° W., 19.2 ft. dist., with scribe marks 1/4 S5 BT visible on partially healed blaze. (Record, S. 74 1/2° W., 19.8 ft. dist.)</p> <p>and new bearing trees</p> <p>A hemlock, 12 ins. diam., bears N. 86 1/2° E., 27.2 ft. dist., mkd. 1/4 S4 BT.</p> |

23626

Subdivision of Section 5,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

| FEET | |
|---------|--|
| | <p>A hemlock, 9 ins. diam., bears N. 20 1/2° W., 11.7 ft. dist., mkd. 1/4 S5 BT. N. 89° 37' 10" W., on the E. and W. center line of sec. 5</p> |
| 1329.34 | <p>Point for the center E 1/16 cor. of sec. 5. Not monumented.</p> <p>From this point, a point erroneously established as the center E 1/16 sec. cor. of sec. 5, by Stuntzner, PLS No. 1342, in 1981, bears N. 66° 55' 19" E., 9.82 ft. dist.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, and was not utilized for control during this survey; from which the remains of the bearing trees mkd. by Stuntzner</p> <p>A cedar, 29 ins. diam., bears N. 57° E., 14.4 ft. dist., with a healed blaze.</p> <p>A hemlock snag, 12 ins. diam., bears S. 29 1/2° E., 8.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> |
| 2658.68 | <p>The center 1/4 sec. cor. of sec. 5.</p> <hr/> <p>N. 89° 31' 16" W., beginning new measurement.</p> |
| 1930 | <p>Creek, 3 ft. wide, course S. 55° W.</p> |
| 2669.51 | <p>The 1/4 sec. cor. of secs. 5 and 6, determined at record bearings and distances from the accessories established by Jelley in 1962,</p> <p>A fir, 32 ins. diam., bears N. 29° E., 61.4 ft. dist., with a healed blaze.</p> <p>A hemlock, 23 ins. diam., bears S. 23 3/4° W., 29.7 ft. dist., with a healed blaze.</p> <p>An iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, bears S. 45° 00' 00" W, 33.00 ft. dist., with a brass cap mkd. RM S6 1962 and an arrow pointing to the cor. Add marks 33.0 FT TO COR 2016 to brass cap.</p> <p>At the corner point</p> <p>Set an iron rod, 24 ins. long, 5/8 in. diam., 24 ins. in the ground, 12 ins. of which are solid rock, flush with ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W 1/4 S 6 S 5 2016</p> <hr/> <p>From the S 1/16 cor. of secs. 4 and 5.</p> <p>N. 89° 23' 44" W., on the E. and W. center line of the SE 1/4 of sec. 5.</p> |

23627

Subdivision of Section 5,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

| FEET | |
|---------|---|
| 1330 | Creek, 1 ft. wide, course N. 25° W. |
| 1475 | Ridge, 50 ft. wide, bears S. 20° E. and N. 20° W. |
| 1570 | Ravine, drains N. 15° W. |
| 2650.55 | The center S 1/16 sec. cor. of sec. 5. |
| <hr/> | |