

COOS COUNTY: EAST LINE SECTIONS 21 AND 33 ARE ON  
THE COOS COUNTY - DOUGLAS COUNTY LINE

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY AND

SUBDIVISIONAL LINES, AND THE SUBDIVISION

OF SECTIONS 29 AND 33,

**TOWNSHIP 29 SOUTH, RANGE 9 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON

---

**EXECUTED BY**

***Joseph J. Johnson, Cadastral Surveyor***

Under Special Instructions approved February 24, 2017,  
which provided for the surveys included under Group No. 2864,  
and Assignment Instructions dated February 24, 2017.

***Survey commenced February 24, 2017***

***Survey completed October 16, 2018***

**T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and the subdivision of sections 29 and 33, Township 29 South, Range 9 West, Willamette Meridian, Oregon.</p> <p>The history of the official surveys pertaining to this survey is as follows:</p> <p>In 1855, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the south boundary and a portion of the subdivisional lines, as shown on the official plat of survey approved July 7, 1856.</p> <p>In 1893, William M. Bushey, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines of T. 30 S., R. 9 W., as shown on the official plat of survey approved June 26, 1894.</p> <p>In 1907, William M. Porter, U.S. Deputy Surveyor, retraced a portion of the south boundary and subdivisional lines, and surveyed the remainder of the subdivisional lines, as shown on the official plat of survey approved March 19, 1909, subsequently approved following amendment October 5, 1909.</p> <p>In 1968, Peter A. Peterson, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines as shown on the official plat of survey accepted March 12, 1971.</p> <p>In 1977-78, Jack W. Bowder, Cadastral Surveyor, remonumented certain original corner points, as described in the official field notes approved February 7, 1980.</p> <p>In 1980, Harvey E. Wofford, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines of T. 30 S., R. 9 W., as shown on the official plat of survey accepted May 11, 1984.</p> <p>In 1991, Wayne L. Rogers, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the north boundary and subdivisional lines of T. 30 S., R. 9 W., as shown on the official plat of survey accepted June 7, 1994.</p> <p>In 2013, George M. Winter, Cadastral Surveyor, retraced portions of the subdivisional lines as shown on the official plat of survey accepted June 26, 2014.</p> <p>In 2017-2018, Joseph J. Johnson, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 17 under Group No. 2865, not yet approved.</p> <p>The following local surveys filed in the Coos County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, official title, Professional Land Surveyor (PLS) No., or Professional Engineer (PE) No., and year. Some of the surveys are filed in both Counties under different file numbers.</p>
------	---

## T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
	1933	J.N. Gearhart, PE No. 183	Bk. 5, pgs. 1 and 5
	4/1957	James W. Byron, Douglas Co. Deputy Surveyor	Bk. 11, pg. 84
	7/1957	James W. Byron, Douglas Co. Deputy Surveyor	Bk. 11, pg. 373
	4/1959	James W. Byron, Douglas Co. Deputy Surveyor	Bk. 11, pg. 376
	9/1959	James W. Byron, Douglas Co. Deputy Surveyor	Bk. 11, pg. 85 Bk. 11, pg. 374
	10/1959	James W. Byron, Douglas Co. Deputy Surveyor	Bk. 11, pg. 86
	11/1962	Bruce A. Shaner, PLS No. 430	33B14
	12/1962	Bruce A. Shaner, PLS No. 430	PB11-18
	1962	Forest E. LaFlamme, Coos County Surveyor	BT Bk. 3, pg. 222
	1964	Vernon R. Tracy, Douglas Co. Deputy Surveyor	Bk. 11, pg. 88 Bk. 11, pg. 377
	1974	Gary L. Langlitz, Douglas Co. Surveyor	Bk. 12, pg. 154
	1990	Jack E. LaFlamme, PLS No. 378	Bk. 20, pg. 99 Bk. 20, pg. 102
	1991	Jack E. LaFlamme, PLS No. 378	Bk. 20, pg. 115
	1991	Larry E. Monrean, Douglas Co. Deputy Surveyor	Bk. 20, pg. 121
	1991	Russell F. Torbeck, PLS No. 582	Bk. 19, pgs. 171-179 33B25
	1995	Ken W. Hoffine, PLS No. 2291	33B27
	2000	Karlas E. Seidel, PLS No. 1845	BT Bk. 5, pg. 223
	2009	Ken W. Hoffine, PLS No. 2291	33B41
	2010	Kristian O. DeGroot, PLS No. 1941	33B43
	2014	Tony Hostetter, PLS No. 1975	Bk. 26, pg. 115 Bk. 26, pg. 116
	2/5/2015	Michael L. Dado, PLS No. 2661	BT Bk. 6, pg. 425
	2/13/2015	Michael L. Dado, PLS No. 2661	BT Bk. 6, pg. 424
	2/25/2015	Michael L. Dado, PLS No. 2661	BT Bk. 6, pg. 427
	4/2015	Michael L. Dado, PLS No. 2661	BT Bk. 6, pg. 444
	9/2016	Michael L. Dado, PLS No. 2661	BT Bk. 6, pg. 515
	10/2016	Michael L. Dado, PLS No. 2661	BT Bk. 6, pg. 526
<p>The following local surveys (M) and county surveyor files (CS) filed in the Douglas County Surveyors Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, official title or Professional Land Surveyor (PLS) No. and year. Some of the surveys are filed in both Counties under different file numbers.</p>			
	<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
	4/1957	James W. Byron, Douglas Co. Deputy Surveyor	CS47/173
	7/1957	James W. Byron, Douglas Co. Deputy Surveyor	CS49/7
	1959	James W. Byron, Douglas Co. Deputy Surveyor	CS49/100
	1964	Vernon R. Tracy, Douglas Co. Deputy Surveyor	CS53/53 CS57/12
	1974	Gary L. Langlitz, Douglas County Surveyor	CS57/12
	1991	Russell F. Torbeck, PLS No. 582	M113-20 CS64/16
	1991	Larry E. Monrean, Douglas Co. Deputy Surveyor	CS64/15
	1995	Ken W. Hoffine, PLS No. 2291	M168-78

## T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
	1996	Douglas County Surveyor's Office	CS65/9-29
	2/5/2015	Michael L. Dado, PLS No. 2661	CS65/87-49
	2/25/2015	Michael L. Dado, PLS No. 2661	CS68/87-51
	2010	Kristian O. DeGroot, PLS No. 1941	M160-78
<p>In 1977, an administrative survey by the Bureau of Land Management (BLM) reestablished the 1/4 section corner of sections 28 and 33, and posted and blazed the line between section 28 and 33. The survey was done administratively and not under an official government survey. The record is located in the Coos Bay District Office in North Bend, Oregon.</p> <p>The survey was executed in accordance with the specification set forth in the <u>Manual of Surveying Instructions</u> (2009), and the special instructions approved February 24, 2017, for Group No. 2864, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and direct solar observations and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.</p> <p>Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data was thoroughly verified and only the true line field notes are given herein.</p> <p>Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each monument established or reestablished has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description. Aluminum angle irons were driven alongside each monument unless a similar marker was already in place.</p> <p>Only those lines bounding Federal interest land were blazed.</p> <p>The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):</p> <p>The corner of sections 27, 28, 33, and 34:</p> <p>Latitude: 43° 00' 39.08" N.    Longitude: 123° 45' 41.70" W.</p>			

**T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET

The corner of sections 16, 17, 20, and 21:

Latitude: 43° 02' 23.34" N.    Longitude: 123° 46' 52.94" W.

---

**Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

---

Restoring the survey by Hathorn in 1855, the survey by Bushey in 1893,  
the survey by Porter in 1907, the resurvey by Wofford in 1980, and  
the resurvey by Rogers and Browning in 1991

Beginning at the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.,  
perpetuated by Dado, PLS No 2661, on February 5, 2015, monumented with  
an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the  
ground, with a brass cap mkd.

COOS COUNTY SURVEYOR  
T 29 S R 9 W  
S 33 | S 34  
-----  
S 4 | S 3  
T 30 S R 9 W  
2015

from which the remains of an original bearing tree

A decayed fir stump, 24 ins. diam., bears N. 70° E., 21.8 ft. dist., with  
scribe mark T visible on open blaze.

and the remains of the bearing trees mkd. by Rogers and Browning in 1991

A decayed fir stump, 24 ins. diam., bears N. 70° E., 32.3 ft. dist., with  
illegible scribe marks visible on open blaze.

A fir, 13 ins. diam., bears S. 8° E., 17.8 ft. dist., with a healed blaze and an  
aluminum nail driven at the base on right side center.

A fir, 13 ins. diam., bears S. 43 3/4° W., 15.2 ft. dist., with a healed blaze.  
(Record, S. 41° W.)

A decayed fir stump, 13 ins. diam., 6 ft. high, bears N. 82° W., 9.9 ft. dist.,  
with a healed blaze.

and an accessory mkd. by Dado

A spike bears N. 20 3/4° E., 36.9 ft. dist., with washer mkd.  
COOS COUNTY SURVEYOR driven in the top of a fir stump  
17 ins. diam., with an X chopped in bark at the base.

**Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>and new accessories</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 27 ins. in the ground for a reference monument, bears N. 82° 12' 00" E., 32.81 ft. dist., with aluminum cap mkd. RM T29S R9W S34 32.8 FT TO COR 2017 and an arrow pointing to the cor.</p> <p>A fir, 11 ins. diam., bears N. 62 1/2° W., 91.3 ft. dist., mkd. T29S R9W S33 BT.</p> <p>From this cor., a point established by persons unknown, reported by Rogers and Browning in 1991, and was not utilized in the course of this survey, bears S. 59° 40' 30" W., 20.27 ft. dist., (Record, S. 58° 54' 30" W., 20.1 ft. dist.) monumented with an iron rod, 5/8 in. diam., firmly set, bent to the SE., with top flush with the surface of the ground.</p> <p>S. 89° 58' 44" W., bet. secs. 4 and 33.</p>
20	<p>Graveled road, 10 ft. wide, bears N. 40° E. and South.</p>
1333.24	<p>The E 1/16 sec. cor. of secs. 4 and 33, established by Hoffine, PLS No. 2291, in 1995, and is accepted as the cor., monumented with an iron rod, 39 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above ground, (alongside of which is an iron rod established by person(s) unknown, 30 ins. long, 5/8 in. diam., disturbed and lying loose on the ground), from which bearing trees mkd. by Hoffine</p> <p>A fir, 13 ins. diam., bears S. 33 3/4° E., 21.7 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears N. 87 3/4° W., 18.6 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by person(s) unknown</p> <p>A chinquapin, 14 ins. diam., bears S. 40 1/4° W., 14.5 ft. dist., with no marks visible, an aluminum nail driven at the base on right side center, and a location tag.</p> <p>A fir snag, 8 ins. diam., bears N. 60 1/4° W., 7.1 ft. dist., with no marks visible, an aluminum nail driven at the base on right side center, and a location tag.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>S 33</p> <p>E 1/16 ———</p> <p>S 4</p> <p>2017</p> </div>

**Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>Bury the iron rod established by person(s) unknown alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 57' 35" W., beginning new measurement.</p>
1333.15	<p>The 1/4 sec. cor. of secs. 4 and 33, perpetuated by Langlitz, Douglas County Surveyor, in 1974, subsequently perpetuated by Dado, PLS No. 2661, on February 25, 2015, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <p align="center">                 COUNTY SURVEYORS OFFICE                  T 29 S                  S 33 R                  1/4 ——— 9                  S 4 W                  T 30 S                  1974             </p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. 23° E., 20.5 ft. dist., with scribe marks BT visible on open blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 39 ins. diam., bears S. 32° W., 28.2 ft. dist., with illegible scribe marks visible on open blaze. (Record, 26.4 ft. dist.)</p> <p>and the bearing trees mkd. by Langlitz</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears N. 10 1/2° E., 14.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears N. 76 1/2° E., 16.3 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Dado</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 62 1/4° W., 22.8 ft. dist., with scribe marks 1/4 S4 BT visible on open blaze and a spike driven at the base on right side center.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 49 1/2° W., 39.2 ft. dist., with scribe marks S33 BT visible on partially healed blaze and a spike driven at the base on left side center.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 58' 08" W., beginning new measurement.</p>
1332.22	<p>The W 1/16 sec. cor. of secs. 4 and 33, established by Torbeck, PLS No. 582, in 1991, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p>

**Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p align="center">COOS COUNTY SURVEYOR T 29 S 33 W 1/16 ——— R 9 W 4 T 30 S 1991</p> <p>from which the bearing trees mkd. by Torbeck</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 32 3/4° W., 6.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 18° W., 11.3 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 57' 12" W., beginning new measurement.</p> <p>215 Graveled road, 12 ft. wide, bears N. 60° E. and S. 60° W.</p> <p>360 Graveled road, 12 ft. wide, bears S. 70° E. and N. 70° W.</p> <p>1332.16 The cor. of secs. 4, 5, 32, and 33, perpetuated by Dado, PLS No. 2661, on February 13, 2015, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd.</p> <p align="center">DOUG CO SURVEYORS OFFICE T 29 S S 32   S 33 R ————— 9 S 5   S 4 W T 30 S 1964</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A hemlock snag, 19 ins. diam., 8 ft. high, bears S. 74° E., 22.4 ft. dist., with scribe marks 9 S visible on partially healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 53 ins. diam., bears S. 38° W., 9.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A hemlock stump, size indeterminate, bears N. 74° W., 27.1 ft. dist., with reverse scribe marks BT visible on a detached wood fragment.</p> <p>and the remains of a bearing tree mkd. by Bushey in 1893</p> <p style="padding-left: 40px;">A decayed fir stump, 32 ins. diam., bears N. 63 1/2° E., 38.6 ft. dist., with scribe marks R S33 visible on open blaze.</p>
------	--

**Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>and a bearing tree mkd. by Tracy, Douglas County Deputy Surveyor in 1964, reported by Wofford in 1980</p> <p>A hemlock, 19 ins. diam., bears S. 22° W., 26.4 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Dado</p> <p>A fir, 11 ins. diam., bears N. 52 3/4° E., 10.5 ft. dist., with scribe marks T29 R9 S33 BT visible on partially healed blaze and a spike driven at the base on right side center.</p> <p>A fir, 21 ins. diam., bears S. 76° E., 5.4 ft. dist., with scribe marks T30 R9 S4 BT visible on partially healed blaze and a spike driven at the base on left side center.</p> <p>A fir, 31 ins. diam., bears N. 33 1/2° W., 18.2 ft. dist., with scribe marks 29S R9W S32 BT visible on partially healed blaze and a spike driven at the base on left side center.</p>
1325.30	<p align="center"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 29 S., R. 9 W., Willamette Meridian, Oregon</b></p> <hr/> <p>Restoring the survey by Hathorn in 1855, the survey by Porter in 1907, the resurvey by Peterson in 1968, the remonumentation by Bowder in 1977-78, and the resurvey by Winter in 2014</p> <hr/> <p>From the corner of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.</p> <p>N. 0° 07' 41" W., bet. secs. 33 and 34.</p> <p>The S 1/16 sec. cor. of secs. 33 and 34, established by Hoffine, PLS No. 2291, in 1995, and is accepted as the cor., monumented with a PK nail, firmly set, with top flush with the surface of bedrock, from which the bearing trees mkd. by Hoffine</p> <p>A fir stump, 20 ins. diam., bears S. 49 1/2° E., 10.7 ft. dist., with a healed blaze.</p> <p>A hemlock, 19 ins. diam., bears N. 20 1/4° W., 40.3 ft. dist., with scribe marks S1/16 S33 BT visible on partially healed blaze and aluminum nail driven at the base on left side center.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, directly above a magnet, with top mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p align="center">S 1/16 S 33   S 34 2017</p> <p>and a new reference monument</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears N. 78° 06' 32" E., 54.71 ft. dist., with aluminum cap mkd. RM S1/16 S34 54.7 FT TO COR 2017 and an arrow pointing to the cor.</p> <p>Removed the PK nail from the area.</p> <p>From this cor., a point established by person(s) unknown, rejected by Hoffine, PLS No. 2291, in 1995, and was not utilized in the course of this survey bears S. 61° 26' 21" W., 11.64 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground.</p> <hr/> <p>N. 0° 17' 20" W., beginning new measurement.</p>
1326.48	<p>The 1/4 sec. cor. of secs. 33 and 34, perpetuated by Byron, Douglas County Deputy Surveyor, in April, 1957, subsequently perpetuated by Hoffine, PLS No. 2291, in 1995, further perpetuated by Dado, PLS No. 2661, in April 2015, from original evidence no longer in existence, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.</p> <p align="center">COOS CO. - DOUG CO SURVEYORS OFFICE T. 29 S. R. 9 W. 1/4 S.   33   34 1957</p> <p>from which the remains of the bearing trees mkd. by Byron</p> <p>A cedar stump, 23 ins. diam., bears S. 25 1/4° E., 14.2 ft. dist., with a healed blaze and aluminum nail driven at the base on right side center.</p> <p>A cedar, 32 ins. diam., bears N. 83 3/4° W., 22.5 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 40 ins. diam., bears S. 17 1/2° W., 21.6 ft. dist., with an X chopped in bark at base by Dado.</p> <p>and an accessory mkd. by Dado</p> <p>A spike bears N. 70° E., 58.2 ft. dist. with a washer mkd COOS COUNTY SURVEY, driven in the top of a hollow cedar stump, 44 ins. diam., with an X chopped in bark at base.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>and a new reference monument</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 27 ins. in the ground for a reference monument, bears N. 76° 07' 37" E., 17.56 ft. dist., with aluminum cap mkd. RM T29S R9W 1/4 S34 17.6 FT TO COR 2017 and an arrow pointing to the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0° 13' 13" E., beginning new measurement.</p>
780	<p>Creek, 4 ft. wide, course N. 80° E.</p>
1665	<p>Spur, slopes E.</p>
2646.80	<p>The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.</p>
	<p align="center">DOUG COUNTY SURVEYORS OFFICE T 29 S R 9 W S 28   S 27 ----- S 33   S 34 RESET 1991 1957</p>
	<p>from which the remains of the original bearing trees</p>
	<p>A decayed fir stump, size indeterminate, bears S. 70° E., 115.5 ft. dist., no marks visible.</p>
	<p>A decayed fir stump, 72 ins. diam., bears N. 78° W., 27.1 ft. dist., no marks visible.</p>
	<p>and a bearing tree mkd. by Porter in 1909, reported by Winter in 2013</p>
	<p>A maple, 27 ins. diam., bears S. 78° E., 11.9 ft. dist., with a healed blaze.</p>
	<p>and the remains of a bearing tree mkd. by Byron, Douglas County Deputy Surveyor in July, 1957, reported by Winter in 2013</p>
	<p>A decayed hemlock stump, 25 ins. diam., bears S. 52 1/4° E., 40.0 ft. dist., with a healed blaze.</p>
	<p>A maple, 26 ins. diam., bears S. 46 1/4° W., 26.2 ft. dist., with a healed blaze.</p>
	<p>A fir stump, 55 ins. diam., bears N. 60° W., 52.7 ft. dist., with a healed blaze.</p>
	<p>and a bearing tree mkd. by Winter in 2013</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 9 ins. diam., bears N. 45 1/2° E., 48.8 ft. dist., with scribe marks T29S R9W S27 BT visible on partially healed blaze.</p> <p>and a new reference monument</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° 11' 15" W., 24.09 ft. dist., with aluminum cap mkd. RM S28 24.1 FT TO COR T29S R9W 2017 and an arrow pointing to the cor.</p> <p>From this cor., a point established by Byron, Douglas County Deputy Surveyor, in July, 1957, redesignated and perpetuated by Monrean, Douglas County Deputy Surveyor, in 1991, and was not utilized in the course of this survey, bears S. 10° 57' 47" W., 5.40 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with an aluminum cap mkd. DOUGLAS CO SURVEYOR.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22, perpetuated by Douglas County Surveyor's Office, in 1996, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <p align="center">T 29 S R 9 W 1/4 S 21   S 22 1978</p> <p>from which a bearing tree mkd. by Bowder in 1978</p> <p>A fir, 20 ins. diam., bears N. 46 3/4° W., 10.9 ft. dist., with a healed blaze. (Record, bears N. 38° W.)</p> <p>and the bearing trees mkd. by Douglas County Surveyor's Office</p> <p>A fir, 9 ins. diam., bears S. 9° E., 14.0 ft. dist., with a healed double blaze.</p> <p>A fir, 10 ins. diam., bears S. 50 1/2° W., 15.4 ft. dist., with a healed blaze.</p> <p>A hemlock, 13 ins. diam., bears S. 77 3/4° W., 27.9 ft. dist., with a healed blaze.</p> <p>N. 0° 31' 14" E., bet. secs. 21 and 22.</p> <p>2604.16 The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with a brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>DOUG COUNTY SURVEYORS OFF COOS CO T 29 S R 9 W S 16   S 15 ----- S 21   S 22 1959</p>
	<p>from which the remains of an original bearing tree</p> <p>A decayed fir stump, 39 ins. diam., bears N. 43° W., 19.8 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Byron, Douglas County Deputy Surveyor, in September, 1959, reported by Winter in 2013</p> <p>A fir, 30 ins. diam., bears N. 68° E., 44.2 ft. dist., with a healed blaze.</p> <p>A fir snag, 27 ins. diam., bears S. 15° E., 16.5 ft. dist., with a healed blaze.</p> <p>A fir, 28 ins. diam., bears S. 63° W., 9.9 ft. dist., with a healed blaze.</p> <p>A decayed fir stump, 23 ins. diam., bears N. 39° W., 40.9 ft. dist., no marks visible.</p> <p>and the reference monuments set by Winter in 2013</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, bears S. 2° 51' 59" E., 27.17 ft. dist., (Record, S. 2° 57' 15" E., 27.0 ft. dist.) with an aluminum cap mkd. RM T29S R9W S22 27.0 FT TO COR 2013 and an arrow pointing to the cor.</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, bears N. 53° 00' 56" W., 25.46 ft. dist., (Record 25.0 ft. dist.) with an aluminum cap mkd. RM T29S R9W S16 25.0 FT TO COR 2013 and an arrow pointing to the cor.</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp. N. 0° 26' 05" E., bet. secs. 32 and 33.</p>
95	Graveled road, 18 ft. wide, bears N. 55° E. and S. 55° W.
1295	Graveled road, 13 ft. wide, bears N. 70° W. and S. 70° E.
1304.12	The S 1/16 sec. cor. of secs. 32 and 33, established by Torbeck, PLS No. 582, in 1991, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, with top 4 ins. below the surface of the ground, with a brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	COOS COUNTY SURVEYOR T 29 S R 9 W S 32   S 33 S 1/16 1991
	from which the bearing trees mkd. by Torbeck
	A hemlock, 18 ins. diam., bears N. 80 1/2° E., 17.2 ft. dist., with scribe marks 1/16 S33 BT visible on partially healed blaze.
	A hemlock, 35 ins. diam., bears N. 20 1/4° W., 24.3 ft. dist., with scribe marks 1/16 S32 BT visible on partially healed blaze.
	Place a white carsonite post N., 3 ft. dist. from the cor.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0° 27' 20" E., beginning new measurement.
965	Graveled road, 13 ft. wide, bears N. 35° E. and S. 45° W.
1304.69	The 1/4 sec. cor. of secs. 32 and 33, perpetuated by LaFlamme, PLS No. 378, in 1983, filed with the Coos County Surveyors Office in 1991, subsequently perpetuated by LaFlamme, PLS No. 378, in 1990, from original evidence no longer in existence, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.
	G. P. 1/4 COR. S 32   S 33 T 29 R 9 1983
	from which the remains of the bearing trees mkd. by LaFlamme in 1983, filed in 1991
	A fir stump, 83 ins. diam., bears S. 85 1/2° E., 27.1 ft. dist., with scribe marks 1/4 S33 BT 378 visible on open blaze.
	A fir stump, 13 ins. diam., bears S. 31 1/2° W., 23.0 ft. dist., with a healed blaze.
	and the remains of the bearing trees mkd. by LaFlamme in 1990
	A fir stump, 60 ins. diam., bears S. 2 3/4° E., 40.2 ft. dist., with scribe marks 1/4 S33 BT visible on open blaze.
	A decayed fir stump, 58 ins. diam., bears N. 17 1/2° W., 32.1 ft. dist., with X chopped in bark at base.
	and new bearing trees
	A fir, 15 ins. diam., bears S. 46 1/4° E., 20.3 ft. dist., mkd. 1/4 S33 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 9 ins. diam., bears N. 84 1/2° W., 19.3 ft. dist., mkd. 1/4 S32 BT.</p> <p>A metal fence post is alongside the cor.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 0° 31' 41" W., beginning new measurement.</p>
275	Creek, 6 ft. wide, course W.
2440	Ravine, drains N. 62° W.
2647.19	<p>The cor. of secs. 28, 29, 32, and 33, monumented with the original cor. tree, a fir, 24 ins. diam., with healed blazes on NE., SE., and SW. faces and high cruiser marks, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir snag, 13 ins. diam., bears S. 52° W., 21.1 ft. dist., with no marks visible on hollowed, decayed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 32° W., 11.2 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Shaner, PLS No. 430, in 1962, reported by Bowder in 1977</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 8° E., 17.2 ft. dist., with a healed blaze.</p> <p>and the reference monuments set by Bowder in 1977</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, in an embedded collar of stone, bears N. 40° 00' 00" E., 13.20 ft. dist., with a brass cap mkd. T29S R9W S28 RM 1977 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears S. 50° 00' 00" E., 13.20 ft. dist., with a brass cap mkd. RM T29S R9W S33 1977 and an arrow pointing to the cor.</p> <p>and a new reference monument</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., set 27 ins. in the ground for a reference monument, bears S. 60° 32' 34" W., 14.81ft. dist., with aluminum cap mkd. RM T29S R9W S32 14.8 FT TO COR 2017 and an arrow pointing to the cor.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>S. 89° 30' 28" W., bet. secs. 28 and 33.</p>
410	Creek, 3 ft. wide, course N. 35° E.
1840	Top of bluff, edge bears generally NE. and SW.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2280	Creek, 2 ft. wide, course S. 45° E.
2666.95	<p>The 1/4 sec. cor. of secs. 28 and 33, reestablished by proportionate measurement by DeGroot, PLS No. 1941, in 2010. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor., monumented with an iron rod, 30 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above ground, in a collar of stone, with an aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R 9 W S 28 1/4 ——— S 33 2010 PLS 1941</p> <p>from which the bearing trees mkd. during a 1977 BLM administrative survey, rescribed by DeGroot</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 38° W., 33.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 28 ins. diam., bears N. 3 1/2° W., 17.2 ft. dist., with scribe marks 1/4 S28 BT visible on partially healed blaze.</p> <p>and the accessories mkd. by DeGroot</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 58 3/4° E., 18.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, bears N. 60° 10' 46" W., 27.02 ft. dist., with a yellow plastic cap mkd. BTS ENG-SURV.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 9 W S 28 1/4 ——— S 33 2017</p> <p>A metal fence post is alongside the cor.</p> <p>From this cor., a point established during an administrative survey by the BLM in 1977, rejected by DeGroot, PLS No. 1941, in 2010, and was not utilized in the course of this survey, bears S. 7° 06' 02" W., 2.21 ft. dist., monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 6 ins. above ground.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2667.43	<p>S. 89° 30' 17" W., beginning new measurement.</p> <p>The cor. of secs. 28, 29, 32, and 33.</p> <hr/>
1347.63	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 0° 07' 36" E., bet. secs. 28 and 29.</p> <p>The S 1/16 sec. cor. of secs. 28 and 29, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron rod, 35 ins. long, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of the bearing trees mkd. by Shaner</p> <p style="padding-left: 40px;">A fir stump, 19 ins. diam., 5 ft. high, bears S. 69 1/2° E., 23.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 20 ins. diam., 5 ft. high, bears S. 33° W., 11.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>S 1/16 S 29   S 28 2017</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 67 1/2° E., 32.2 ft. dist., mkd. S1/16 S28 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 20 1/4° W., 9.2 ft. dist., mkd. S1/16 S29 BT.</p> <hr style="width: 20%; margin: 10px auto;"/>
190	<p>N. 0° 05' 20" E., beginning new measurement.</p> <p>Graveled road, 16 ft. wide, bears N. 85° E. and S. 70° W.</p>
375	<p>Creek, 1 ft. wide, course N. 35° W.</p>
1345.77	<p>The 1/4 sec. cor. of secs. 28 and 29, perpetuated by Seidel, PLS No. 1845, in 2000, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a mound of stone, 4 ft. base, to the top, with a brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 29 S R 9 W 1/4 S 29   S 28 1977</p> </div>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of the original bearing trees</p> <p>A decayed cedar stump, 21 ins. diam., bears S. 4° W., 33.7 ft. dist., with scribe marks 1/4 S visible on partially healed blaze.</p> <p>and a bearing tree mkd. by LaFlamme, Coos County Surveyor, in 1962, reported by Bowder in 1977</p> <p>A cedar, 20 ins. diam., bears N. 10 1/4° W., 29.7 ft. dist., with scribe marks S8 visible on partially healed blaze.</p> <p>and a bearing tree mkd. by Bowder in 1977</p> <p>A fir, 33 ins. diam., bears S. 35° E., 36.3 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Seidel</p> <p>A cedar, 16 ins. diam., bears S. 77 3/4° W., 24.1 ft. dist., with a healed blaze.</p> <p>The remains of the original NE. bearing tree, a decayed fir stump, 52 ins. diam., with scribe marks S 28 BT visible on a partially healed blaze was found to have slid downhill and rotated out of position.</p> <p>A red carsonite post bears N., 3 ft. dist. from the cor.</p> <p align="center">_____</p> <p>N. 0° 05' 30" W., beginning new measurement.</p>
560	Graveled road, 18 ft. wide, bears S. 80° E. and N. 55° W.
1319.89	Point for the N 1/16 sec. cor. of secs. 28 and 29. Not monumented.
2639.78	<p>The cor. of secs. 20, 21, 28, and 29, perpetuated by Dado, PLS No. 2661, in September, 2016, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, (alongside of which is a galvanized iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground), with a brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 9 W</p> <p>S 20   S 21</p> <hr style="width: 100%; border: 0.5px solid black;"/> <p>S 29   S 28</p> <p>1968</p> </div> <p>from which the remains of the original bearing trees</p> <p>A decayed cedar stump, 22 ins. diam., bears N. 65° E., 33.0 ft. dist., with scribe marks 2 S R S 1 and other illegible scribe marks visible on open blaze at breast height.</p> <p>A decayed fir stump, 63 ins. diam., bears N. 17° W., 46.2 ft. dist., with no marks visible on partially healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET

and the remains of the bearing trees mkd. by Shaner, PLS No. 430, in December, 1962, reported by Peterson in 1968

A decayed hemlock stump, size indeterminate, bears S. 84° E., 23.1 ft. dist., with no marks visible.

A decayed fir stump, 62 ins. diam., bears S. 86° W., 23.8 ft. dist., with scribe marks 29 BT visible on partially healed blaze.

and the bearing trees mkd. by Peterson in 1968

A fir, 25 ins. diam., bears N. 30° E., 29.7 ft. dist., with a healed blaze.

A hemlock, 36 ins. diam., bears S. 85° W., 34.3 ft. dist., with a healed blaze.

A fir, 36 ins. diam., bears N. 29° W., 13.9 ft. dist., with a healed blaze.

and a bearing tree mkd. by Dado

A hemlock, 8 ins. diam., bears S. 17° E., 20.1 ft. dist., with scribe marks X BT visible on partially healed double blaze.

From the cor. of secs. 21, 22, 27, and 28, perpetuated by Byron, Douglas County Deputy Surveyor, in October, 1959, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.

DOUG COUNTY SURVEYORS OFFICE

T 29 S R 9 W	
S 21	S 22
S 28	S 27
1959	

from which the remains of the bearing trees mkd. by Porter in 1907

A fir, 32 ins. diam., bears S. 70° E., 25.1 ft. dist., with a healed blaze.

A yew snag, split in half, 16 ins. diam., bears N. 12° W., 28.6 ft. dist., with illegible scribe marks visible on partially healed blaze. (Record, bears N. 14° W., 30.4 ft. dist.)

and the remains of a bearing tree mkd. by Byron

A fir stump, 45 ins. diam., bears N. 34 1/4° E., 124.2 ft. dist., with no marks visible on decayed open blaze.

and new bearing trees

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>A maple, 14 ins. diam., bears N. 61 1/2° E., 41.5 ft. dist., mkd. T29S R9W S22 BT.</p> <p>A maple, 9 ins. diam., bears S. 63 1/4° W., 15.0 ft. dist., mkd. T29S R9W S28 BT.</p> <p>A fir, 35 ins. diam., bears N. 15 1/2° W., 16.8 ft. dist., mkd. T29S R9W S21 BT.</p> <p>S. 88° 14' 18" W., bet. secs. 21 and 28.</p>
2724.26	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 9 W</p> <p>S 21</p> <p>1/4 ———</p> <p>S 28</p> <p>1977</p> </div> <p>from which the remains of the original bearing trees</p> <p>A fir, 32 ins. diam., bears N. 30° E., 5.1 ft. dist., with scribe marks 1/4 S21 BT visible on open blaze. (Record, 3.3 ft. dist.)</p> <p>A decayed fir stump, 44 ins. diam., bears S. 11° E., 31.0 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Bowder in 1977</p> <p>A fir, 16 ins. diam., bears N. 40° W., 23.1 ft. dist., with a healed blaze.</p> <p>A decayed fir stump, 21 ins. diam., 7 ft. high, bears S. 0 1/2° E., 52.8 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 8 ins. diam., bears S. 35° W., 42.6 ft. dist., mkd. 1/4 S28 BT.</p> <p>A metal fence post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 44' 04" W., beginning new measurement.</p>
150	<p>Asphalt road, 18 ft. wide, bears N. 16° E. and S. 8° E.</p>
2636.20	<p>The cor. of secs. 20, 21, 28, and 29.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 20, 21, 28, and 29.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2657.10	<p>N. 0° 38' 14" E., bet. secs. 20 and 21.</p> <p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 20   S 21 T 29 S R 9 W 1968</p> </div> <p>from which the remains of a bearing tree mkd. by Peterson in 1968</p> <p>A decayed fir stump, 23 ins. diam., bears N. 1° W., 70.0 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A hemlock, 8 ins. diam., bears S. 41° E., 36.8 ft. dist., mkd. 1/4 S21 BT.</p> <p>A hemlock, 13 ins. diam., bears S. 3° W., 22.8 ft. dist., mkd. 1/4 S20 BT.</p> <hr style="width: 20%; margin: 10px auto;"/>
140	<p>N. 0° 12' 49" E., beginning new measurement.</p> <p>Spur, slopes. E.</p>
2395	<p>Creek, 1 ft. wide, course S. 45° W.</p>
2613.15	<p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 9 W S 17   S 16 S 20   S 21 1968</p> </div> <p>from which the remains of the bearing trees mkd. by Peterson in 1968</p> <p>A decayed fir stump, 17 ins. diam., bears N. 83° E., 11.2 ft. dist., no marks visible.</p> <p>A cedar snag, 7 ins. diam., bears, S. 43 1/2° E., 5.9 ft. dist., with a healed blaze. (Record, S. 35° E.)</p> <p>A fir, 21 ins. diam., bears S. 85° W., 13.2 ft. dist., with a healed blaze.</p> <p>A fir, 24 ins. diam., bears N. 52° W., 5.9 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A hemlock, 13 ins. diam., bears N. 25° E., 21.6 ft. dist., mkd. T29S R9W S16 BT.</p> <p>A fir, 29 ins. diam., bears S. 59° E., 31.3 ft. dist., mkd. T29S R9W S21 BT.</p> <hr/>
2639.34	<p>From the sec. cor. of secs. 15, 16, 21, and 22.</p> <p>N. 89° 33' 17" W., bet. secs. 16 and 21.</p> <p>The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>S 16</p> <p>1/4 ———</p> <p>S 21</p> <p>T 29 S R 9 W</p> <p>1968</p> </div> <p>from which the bearing trees mkd. by Peterson in 1968</p> <p>A fir, 36 ins. diam., bears S. 54° W., 31.7 ft. dist., with a healed blaze.</p> <p>A hemlock, 32 ins. diam., bears N. 50° W., 2.0 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 36' 33" W., beginning new measurement.</p>
2673.77	<p>The sec. cor. of secs. 16, 17, 20, and 21.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89° 41' 34" W., bet. secs. 29 and 32.</p>
1389.22	<p>The E 1/16 sec. cor. of secs. 29 and 32, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, with top 3 ins. below the surface of the ground, from which the remains of the bearing trees mkd. by Shaner</p> <p>A cedar stump, 28 ins. diam., bears N. 37 1/2° E., 31.6 ft. dist., no marks visible on open blaze.</p> <p>A hemlock, 30 ins. diam., bears S. 45° E., 37.7 ft. dist., with scribe mark 3 and other illegible scribe marks visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">S 29 E 1/16 _____ S 32 2017</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears N. 2 1/2° W., 25.3 ft. dist., mkd. E1/16 S29 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 44' 01" W., beginning new measurement.</p> <p>1385.86 The 1/4 sec. cor. of secs. 29 and 32, perpetuated by Shaner, PLS No. 430, in December, 1962, subsequently perpetuated by LaFlamme, PLS No. 378, in 1990, further perpetuated by Hostetter, PLS No. 1975, in 2014, further perpetuated by Dado, PLS No. 2661, in October, 2016, monumented with an iron rod, 35 ins. long, 5/8 in. diam., firmly set, projecting 6 ins. above ground,</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir stump, 32 ins. diam., bears S. 25° E., 11.9 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Shaner</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 29 3/4° W., 27.7 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by LaFlamme</p> <p style="padding-left: 40px;">A fir stump, 24 ins. diam., bears S. 76° E., 13.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar stump, 52 ins. diam., bears N. 48° E., 9.6 ft. dist., with scribe marks 1/4 S29 BT visible on partially healed blaze.</p> <p>and a bearing tree mkd. by Hostetter</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears N. 6° E., 7.0 ft. dist., with scribe marks S1/4 S29 BT visible on partially healed blaze.</p> <p>and a bearing tree mkd. by Dado</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears S. 42 1/2° W., 21.2 ft. dist., with no marks visible and a spike on the right side center.</p> <p>At the corner point</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p>
------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T 29 S R 9 W S 29 1/4 _____ S 32 2017</p> <p>A metal fence post is alongside the cor.</p>
	<p>From the 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">T 29 S R 9 W 1/4 S 30   S 29 1978</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 22° E., 21.8 ft. dist., with reverse scribe mark T and other illegible scribe marks visible on open blaze.</p> <p style="padding-left: 40px;">A fir stump, 32 ins. diam., 7 ft. high, bears N. 52° W., 9.2 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Bowder in 1977-78</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears S. 5 3/4° E., 93.4 ft. dist., with a healed blaze. (Record, S. 5° E.)</p> <p style="padding-left: 40px;">A cedar, 29 ins. diam., bears N. 36° W., 46.9 ft. dist., with a healed blaze.</p> <p>N. 0° 14' 23" E., bet. secs. 29 and 30.</p>
1358.76	<p>The N 1/16 sec. cor. of secs. 29 and 30, established by Shaner, PLS No. 430, in November, 1962, and is accepted as the cor., monumented with an iron pipe, 36 ins long, 1 in. diam., firmly set, leaning to E., with top 12 ins. below the surface of the ground</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 30   S 29 2017</p> <p>from which new reference monuments</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>An iron rod, 30 ins. long, 5/8 in. diam., set 27 ins. in the ground for a reference monument, bears S. 31° 28' 16" E., 23.09 ft. dist., with aluminum cap mkd. RM N1/16 S29 23.1 FT TO COR 2017 and an arrow pointing to the cor.</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 26 ins. in the ground for a reference monument, bears S. 79° 48' 16" W., 19.11 ft. dist., with aluminum cap mkd. RM N1/16 S30 19.1 FT TO COR 2017 and an arrow pointing to the cor.</p> <hr/> <p>N. 0° 11' 16" E., beginning new measurement.</p>								
1358.97	<p>The cor. of secs. 19, 20, 29, and 30, perpetuated by Hoffine, PLS No. 2291, in 2009, monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, (alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground) with a brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 29 S</td> <td>R 9 W</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td colspan="2">1977</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p>A decayed fir snag, 23 ins. diam., bears S. 38° E., 33.0 ft. dist., no marks visible.</p> <p>and the remains of a bearing tree mkd. by Gearhart, Coos County Surveyor, in 1933, reported by Bowder in 1977</p> <p>A decayed fir stump, 44 ins. diam., bears S. 35° W., 48.8 ft. dist., no marks visible on open decayed blaze.</p> <p>and the remains of a bearing tree mkd. by Shaner, PLS No. 430, in November, 1962, reported by Bowder in 1977. (Record, mkd. in 1959)</p> <p>A decayed fir stump, 32 ins. diam., bears N. 35° W., 16.5 ft. dist., with scribe marks S19 BT visible on partially healed blaze.</p> <p>and the accessories mkd. by Bowder in 1977</p> <p>A white cedar, 15 ins. diam., bears N. 64 3/4° E., 54.9 ft. dist., with a healed blaze. (Record, N. 66° E., 51.8 ft.)</p> <p>The vertical face of a sandstone outcropping, bears S. 82 1/2° E., 42.9 ft. dist., mkd. X BO. (Record, S. 81 1/2° E.)</p> <p>and a bearing tree mkd. by person(s) unknown, reported by Hoffine</p>	T 29 S	R 9 W	S 19	S 20	S 30	S 29	1977	
T 29 S	R 9 W								
S 19	S 20								
S 30	S 29								
1977									

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A pistol butt white cedar, 22 ins. diam., bears S. 87 1/2° E., 82.8 ft. dist., with scribe marks S29 BT 378 visible on open blaze and a Georgia Pacific location tag.</p> <p>and new reference monuments</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears S. 49° 58' 15" W., 13.20 ft. dist., with aluminum cap mkd. RM T29S R9W S30 13.2 FT TO COR 2017 and an arrow pointing to the cor.</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears N. 62° 41' 06" W., 21.39 ft. dist., with aluminum cap mkd. RM T29S R9W S19 21.4 FT TO COR 2017 and an arrow pointing to the cor.</p>
	<p>From the cor. of secs. 20, 21, 28, and 29.</p>
	<p>N. 89° 27' 46" W., bet. sec. 20 and 29.</p>
650	<p>Graveled road, 13 ft. wide, bears N. 50° E. and S. 30° W.</p>
1327.72	<p>Point for the E 1/16 sec. cor. of secs. 20 and 29. Not monumented.</p>
2655.44	<p>The 1/4 sec. cor. of secs. 20 and 29, perpetuated by Gearhart, PE No. 183, in 1933, subsequently perpetuated by Shaner, PLS No. 430, in December, 1962, monumented with an iron pipe, 36 ins. long, 1 in. diam., firmly set, projecting 7 ins. above ground, from which the remains of the original bearing trees</p> <p>A decayed fir snag, 9 ins. diam., bears S. 50 1/2° W., 11.9 ft. dist., with scribe marks 1/4 S visible on open blaze. (Record, bears S. 58° W.)</p> <p>A decayed cedar stump, 38 ins. diam., bears N. 24° W., 7.9 ft. dist., with scribe marks 4 visible on partially healed blaze.</p> <p>and the remains of a bearing tree mkd. by Gearhart</p> <p>A hollow, decayed, cedar stump, 53 ins. diam., bears S. 38° E., 25.6 ft. dist., no marks visible, with a hemlock, 5 ins. diam., growing from the center.</p> <p>and a bearing tree mkd. by Shaner</p> <p>A fir, 51 ins. diam., bears S. 69 1/4° E., 26.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">T 29 S R 9 W S 20 1/4 _____ S 29 2017</p>
	<p>from which</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears N. 24 3/4° W., 3.3 ft. dist., mkd. 1/4 S20 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 21' 07" W., beginning new measurement.</p>
1296.83	<p>The W 1/16 sec. cor. of secs. 20 and 29, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, from which the bearing trees mkd. by Shaner</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. 18° E., 18.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 4° E., 31.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">S 20 W 1/16 _____ S 29 2017</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 17' 10" W., beginning new measurement.</p>
1295.97	<p>The sec. cor. of secs. 19, 20, 29, and 30.</p> <hr style="width: 80%; margin: auto;"/> <p style="text-align: center;"><b>Subdivision of Section 29, T. 29 S., R. 9 W., Willamette Meridian, Oregon</b></p> <hr style="width: 80%; margin: auto;"/>
1334.12	<p>From the 1/4 sec. cor. of secs. 29 and 32.</p> <p>N. 1° 12' 58" E., on the N. and S. center line of sec. 29.</p> <p>The center S 1/16 sec. cor. of sec. 29, established by Shaner, PLS No. 430, in December, 1962, perpetuated by Hostetter, PLS No. 1975, in 2014, and is accepted as the cor., monumented with an iron rod, 35 ins. long, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of the bearing trees mkd. by Shaner</p>

**Subdivision of Section 29,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed fir stump, 14 ins. diam., bears N. 68° E., 40.9 ft. dist., no marks visible.</p> <p>A decayed fir stump, 37 ins. diam., bears N. 47 1/4° W., 15.8 ft. dist., with no marks visible on open blaze.</p> <p>and a bearing tree mkd. by Hostetter</p> <p>A fir, 7 ins. diam., bears N. 33° E., 5.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, directly over the iron rod, in a mound of stone, 3 ft. base, to the top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 9 W C S 1/16   S 29 C 2017</p> </div> <p>and a new reference monument</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., set 28 ins. in the ground for a reference monument, bears N. 42° 12' 57" W., 27.49 ft. dist., with aluminum cap mkd. RM CS1/16 S29 27.5 FT TO COR 2017 and an arrow pointing to the cor.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 1° 12' 52" E., beginning new measurement.</p>
1332.71	<p>The center 1/4 sec. cor. of sec. 29, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, from which the remains of the bearing trees mkd. by Shaner</p> <p>A decayed fir stump, 17 ins. diam., bears S. 20 1/2° E., 19.4 ft. dist., with scribe marks C1/4 S29 BT visible on open blaze.</p> <p>A decayed fir stump, 19 ins. diam., bears N. 71° W., 42.0 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set an aluminum cap, 3 ins. diam., onto the iron rod, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 9 W C 1/4 S 29 2017</p> </div> <p>and new bearing trees</p>

**Subdivision of Section 29,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 17 ins. diam., bears S. 64° E., 39.5 ft. dist., mkd. C1/4 S29 BT.</p> <p>A fir, 8 ins. diam., bears N. 63 3/4° W., 21.6 ft. dist., mkd. C1/4 S29 BT.</p> <p>Place a white carsonite post alongside the cor.</p> <p>Corner is located immediately N. and uphill of a boulder, 5 ft. diam.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 24' 57" E., beginning new measurement.</p>
1341.16	<p>The center N 1/16 sec. cor. of sec. 29, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron rod, 34 ins. long, 5/8 in. diam., firmly set, with top 6 ins. below the surface of the ground, from which the remains of the bearing trees mkd. by Shaner</p> <p>A cedar snag, 24 ins. diam., bears S. 22 1/4° W., 32.8 ft. dist., with scribe marks CN1/16 S29 BT visible on partially healed blaze.</p> <p>A decayed fir stump, 21 ins. diam., 5 ft., high, partially uprooted and leaning to E., now bears N. 10 1/2° W., 9.8 ft. dist., with scribe mark 9 and other illegible scribe marks visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C N 1/16   S 29 C 2017</p> </div> <p>and new bearing trees</p> <p>A hemlock, 8 ins. diam., bears N. 49 1/4° E., 20.7 ft. dist., mkd. CN1/16 S29 BT.</p> <p>A fir, 7 ins. diam., bears S. 30 1/2° W., 19.0 ft. dist., mkd. CN1/16 S29 BT.</p> <p>Place a white carsonite post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 17' 40" E., beginning new measurement.</p>
1337.56	<p>The 1/4 sec. cor. of secs. 20 and 29.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 28 and 29.</p> <p>S. 89° 44' 24" W., on the E. and W. center line of sec. 29.</p>

**Subdivision of Section 29,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
1359.03	<p>The center E 1/16 sec. cor. of sec. 29, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron rod, 30 ins. long, 5/8 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the bearing trees mkd. by Shaner</p> <p style="padding-left: 40px;">A roothole bears N. 69 1/4° E., 24.3 ft. dist., alongside of which is a down fir, 31 ins. diam., with illegible scribe marks visible on open blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 38 ins. diam., bears N. 31 1/2° W., 41.7 ft. dist., with scribe marks C S 2 visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>E 1/16</p> <p>C ————— C</p> <p>S 29</p> <p>2017</p> </div> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 32 1/4° E., 16.7 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 35° E., 27.8 ft. dist., mkd. CE1/16 S29 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 42' 03" W., beginning new measurement.</p>
1364.23	<p>The center 1/4 sec. cor. of sec. 29.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 47' 54" W., beginning new measurement.</p>
1269.86	<p>Point for the center W 1/16 sec. cor. of sec. 29. Not monumented.</p>
2539.72	<p>The 1/4 sec. cor. of secs. 29 and 30.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center E 1/16 sec. cor. of sec. 29.</p> <p>N. 0° 32' 07" E., on the N. and S. center line of the NE1/4 of sec. 29.</p>
1330.26	<p>The NE 1/16 sec. cor. of sec. 29, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron post, 33 ins. long, 5/8 in. diam., firmly set, projecting 7 ins. above ground, from which the bearing trees mkd. by Shaner</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 22 3/4° E., 18.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears S. 24 1/4° E., 26.7 ft. dist., with a healed blaze.</p>

**Subdivision of Section 29,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 29 2017</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 37' 39" E., beginning new measurement.</p>
1328.27	<p>The E 1/16 sec. cor. of secs. 20 and 29.</p> <hr style="width: 80%; margin: auto;"/> <p>From the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>N. 89° 49' 23" W., on the E. and W. center line of the NE1/4 of sec. 29.</p>
1344.41	<p>The NE 1/16 sec. cor. of sec. 29.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 51' 15" W., beginning new measurement.</p>
1200	<p>Graveled road, 15 ft. wide, bears S. 20° E. and N. 35° W.</p>
1343.42	<p>The center N 1/16 sec. cor. of sec. 29.</p> <hr style="width: 80%; margin: auto;"/> <p>From the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>N. 0° 43' 23" E., on the N. and S. center line of the SE1/4 of sec. 29.</p>
1341.81	<p>The SE 1/16 sec. cor. of sec. 29, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron rod, 34 ins. long, 5/8 in. diam., firmly set, projecting 8 ins. above ground, from which the bearing trees mkd. by Shaner</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears N. 25 3/4° E., 10.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears S. 55 1/4° E., 18.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 29 2017</p> <p>and a new bearing tree</p>

**Subdivision of Section 29,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 9 ins. diam., bears S. 70° W., 19.8 ft. dist., mkd. SE1/16 S29 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 46' 38" E., beginning new measurement.</p>
1338.20	<p>The center E 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 28 and 29.</p> <p>N. 89° 56' 11" W., on the E. and W. center line of the SE1/4 of sec. 29.</p>
1375.16	<p>The SE 1/16 sec. cor. of sec. 29.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 56' 23" W., beginning new measurement.</p>
1374.39	<p>The center S 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 29.</p> <p>N. 0° 51' 00" E., on the N. and S. center line of the NW1/4 of sec. 29.</p>
1350.05	<p>The NW 1/16 sec. cor. of sec. 29, established by Shaner, PLS No. 430, in December, 1962, and is accepted as the cor., monumented with an iron post, 5/8 in. diam., firmly set, projecting 8 ins. above ground, from which the bearing trees mkd. by Shaner</p> <p style="padding-left: 40px;">A decayed fir stump, 17 ins. diam., bears S. 62° E., 28.6 ft. dist., with scribe marks NW1/16 S29 BT visible on open blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 25 ins. diam., bears N. 30 1/4° W., 14.2 ft. dist., with scribe marks NW 1/16 S29 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 29 2017</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 40 1/2° E., 24.4 ft. dist., mkd. NW1/16 S29 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 76 3/4° W., 16.9 ft. dist., mkd. NW1/16 S29 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 41' 32" E., beginning new measurement.</p>

**Subdivision of Section 29,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
785	Graveled road, 15 ft. wide, bears S. 70° W. and N. 80° W.
1347.29	The W 1/16 sec. cor. of secs. 20 and 29. <hr/>
	From the center N 1/16 sec. cor. of sec. 29.
	N. 89° 47' 26" W., on the E. and W. center line of the NW1/4 of sec. 29.
1282.89	The NW 1/16 sec. cor. of sec. 29. <hr/>
	N. 89° 48' 17" W., beginning new measurement.
1284.13	The N 1/16 sec. cor. of secs. 29 and 30. <hr/>
	<b>Subdivision of Section 33, T. 29 S., R. 9 W., Willamette Meridian, Oregon</b>
	From the 1/4 sec. cor. of secs. 4 and 33.
	N. 0° 00' 22" W., on the N. and S. center line of sec. 33.
1315.00	Point for the center S 1/16 sec. cor. of sec. 33. Not monumented.
2630.00	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line.  Set a galvanized iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 S R 9 W C 1/4 S 33 2017
	from which new bearing trees
	A fir, 33 ins. diam., bears S. 30 1/2° W., 22.1 ft. dist., mkd. C1/4 S33 BT.
	A fir, 14 ins. diam., bears S. 34° E., 18.0 ft. dist., mkd. X BT.
2700	Ravine, drains N. 50° E.
5277.06	The 1/4 sec. cor. of secs. 28 and 33. <hr/>
	From the 1/4 sec. cor. of secs. 33 and 34.
	S. 89° 29' 59" W., on the E. and W. center line of sec. 33.

**Subdivision of Section 33,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
1328.40	Point for the center E 1/16 sec. cor. of sec. 33. Not monumented.
2656.80	The center 1/4 sec. cor. of sec. 33.
3978.61	Point for the center W 1/16 sec. cor. of sec. 33. Not monumented.
5300.42	The 1/4 sec. cor. of secs. 32 and 33.
	<hr/>
	From the E 1/16 sec. cor. of secs. 4 and 33.
	N. 0° 06' 47" W., on the N. and S. center line of the SE1/4 of sec. 33.
1030	Creek, 2 ft. wide, course N. 20° E.
1320.48	The SE 1/16 sec. cor. of sec. 33, established by Hoffine, PLS No. 2291, in 1995, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with an aluminum cap mkd.
	LONE ROCK TIMBER SE 1/16 S 33 1995 PLS 2291
	from which a bearing tree mkd. by Hoffine
	A fir, 19 ins. diam., bears S. 6 3/4° W., 15.9 ft. dist., with a healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.
	SE 1/16 S 33 2017
	and a new bearing tree
	A fir, 9 ins. diam., bears N. 25 1/4° E., 12.1 ft. dist., mkd. SE1/16 S33 BT.
	<hr/>
	N. 0° 06' 02" W., beginning new measurement.
1320.18	The center E 1/16 sec. cor. of sec. 33.
	<hr/>
	From the S 1/16 sec. cor. of secs. 33 and 34.
	S. 89° 46' 17" W., on the E. and W. center line of the SE1/4 of sec. 33.
1200	Creek, 2 ft. wide, course N. 65° E.

**Subdivision of Section 33,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
1332.81	<p>The SE 1/16 sec. cor. of sec. 33.</p> <hr style="width: 25%; margin-left: auto; margin-right: auto;"/> <p>S. 89° 43' 26" W., beginning new measurement.</p>
1330.62	<p>The center S 1/16 sec. cor. of sec. 33.</p> <hr style="width: 60%; margin-left: 0; margin-right: auto;"/> <p>From the W 1/16 sec. cor. of secs. 4 and 33.</p> <p>N. 0° 14' 49" E., on the N. and S. center line of the SW1/4 of sec. 33.</p>
1310.13	<p>Point for the SW 1/16 sec. cor. of sec. 33, established by Torbeck, PLS No. 582, in 1991, and is accepted as the cor., as determined at record distances from the remains of the bearing trees mkd. by Torbeck</p> <p style="padding-left: 40px;">A fir snag, 12 ins. diam., bears S. 21° W., 19.5 ft. dist., with scribe marks 1/16 S33 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir snag, 14 ins. diam., bears N. 53 1/4° W., 10.7 ft. dist., with scribe marks 1/16 S33 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set a galvanized iron post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 33 2017</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A hemlock, 7 ins. diam., bears S. 78° E., 24.7 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A hemlock, 7 ins. diam., bears N. 81 3/4° W., 17.3 ft. dist., mkd. SW1/16 S33 BT.</p> <p>The 1991 Torbeck monument was found disturbed and out of position. Bury the iron post, 36 ins. long, 2 1/2 ins. diam., with brass cap mkd. COOS COUNTY SURVEYOR SW 1/16 S33 1991 alongside the cor.</p> <hr style="width: 25%; margin-left: auto; margin-right: auto;"/> <p>N. 0° 11' 30" E., beginning new measurement</p>
1309.08	<p>The center W 1/16 sec. cor. of sec. 33.</p> <hr style="width: 60%; margin-left: 0; margin-right: auto;"/> <p>From the center S 1/16 sec. cor. of sec. 33.</p> <p>S. 89° 45' 27" W., on the E. and W. center line of the SW1/4 of sec. 33.</p>

Subdivision of Section 33,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
1326.37	The SW 1/16 sec. cor. of sec. 33. <hr/>
	S. 89° 41' 34" W., beginning new measurement.
1327.85	The S 1/16 sec. cor. of secs. 32 and 33. <hr/>