

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE SOUTH BOUNDARY
AND SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTIONS 2, 10, AND 33,
TOWNSHIP 33 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON

EXECUTED BY

Kevin G. Mulder, Cadastral Surveyor

Under Special Instructions approved July 2, 2018,
which provided for the surveys included under Group No. 2925,
and Assignment Instructions dated July 2, 2018.

Survey commenced July 9, 2018

Survey completed October 4, 2018

T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and the subdivision of sections 2, 10, and 33, Township 33 South, Range 6 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1855, Wells Lake and George W. Hyde, U.S. Deputy Surveyors, surveyed the north boundary (Seventh Standard Parallel South) the south boundary and a portion of the subdivisional lines, as shown on the official plat of survey approved March 31, 1856.

In 1882, William H. Byars, U.S. Deputy Surveyor, completed the survey of the subdivisional lines, as shown on the official plat of survey approved June 16, 1882.

In 1958-63, Joseph S. Gawron and Hans W. Thielsen, Cadastral Surveyors, resurveyed a portion of the subdivisional lines, as described in the official field notes accepted September 15, 1964.

In 1963-64, Joseph S. Gawron, Cadastral Surveyor, remonumented certain original corner points, as shown on the official plat of survey accepted November 1, 1965.

In 1982, Virgil L. Stanger, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted July 20, 1984.

In 1994, Francis J. Simon, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, and subdivided sections 9 and 11, as shown on the official plat of survey accepted May 16, 1997.

In 2006-07, Richard J. Dieckmann, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, and subdivided sections 34 and 35 of T. 32 S., R. 6 W., as shown on the official plat of survey accepted December 28, 2007.

The following local surveys filed in the Josephine County and Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's or engineer's last name, Professional Land Surveyor (PLS) No. or Professional Engineer (PE) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>	<u>County</u>
1956	H.W. Lawrence, PE No. 1543	108-56	Josephine
1962	Robert M. Thompson, PE No. 3683	34-62	Josephine
1974	Richard L. Templin, PE No. 3024	166-7	Josephine
1979	Ronald A Brandt, PLS No. 841	214-79	Josephine
1993	Max H. Hull, PLS No. 901	127-93	Josephine
2000	James M. McIntosh, PLS No. 2103	42-2000	Josephine
2004	Raymond W. Wytcherley, PLS No. 2724	71-2004	Josephine
1988	John E. Hollingsworth, PLS No. 691	M 107-16	Douglas

T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET			
	<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u> <u>County</u>
	1990	Lloyd D. Smith, PLS No. 1101	M 110-30 Douglas
	1995	Gerald V. Nygren, PLS No. 1035	M 121-31 Douglas
	1998	Gerald V. Nygren, PLS No. 1035	M 130-10 Douglas
	<p>The survey was executed in accordance with the specification set forth in the <u>Manual of Surveying Instructions</u> (2009), and the special instructions approved July 2, 2018, for Group No. 2925, Oregon.</p>		
	<p>The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.</p>		
	<p>Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data was thoroughly verified and only the true line field notes are given herein.</p>		
	<p>Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each monument established or reestablished has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.</p>		
	<p>Only those lines which represent the Bureau of Land Management (BLM) property lines were posted with aluminum angle posts, 5 feet long, 1 inch x 1 inch, blazed, painted, and tagged with BLM boundary signs.</p>		
	<p>The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):</p>		
	<p>The corner of sections 3, 4, 33, and 34, on the south boundary of the township:</p>		
	<p>Latitude: 42° 39' 07.74" N. Longitude: 123° 24' 23.79" W.</p>		
	<p>The 1/4 section corner of section 2 and 11:</p>		
	<p>Latitude: 42° 43' 29.77" N. Longitude: 123° 22' 35.97" W.</p>		
	<p>The corner of sections 10, 11, 14, and 15:</p>		

T. 33 S., R. 6 W., Willamette Meridian, Oregon


FEET

Latitude: 42° 42' 37.21" N. Longitude: 123° 23' 11.67" W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

Restoring the 1855 survey by Wells Lake and George W. Hyde,
the 1958-63 resurvey by Joseph S. Gawron and Hans W. Thielsen,
and the 1963-64 remonumentation by Joseph S. Gawron

Beginning at the cor. of secs. 3, 4, 33, and 34, reported by Gawron and Thielsen in 1958-63, perpetuated by the Josephine County Surveyor's Office in 2014, not recorded at the time of this survey, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.



from which the remains of bearing trees reported by Gawron and Thielsen

A fir, 34 ins. diam., bears N. 35° E., 6.6 ft. dist., with a healed blaze and a spike at the base on right side center.

A fir, 38 ins. diam., bears S. 32 1/2° E., 23.8 ft. dist., with a healed blaze and a spike at the base on right side center. (Record, S. 29° E.)

A fir, 26 ins. diam., bears S. 29 1/4° W., 32.3 ft. dist., with a healed blaze and a spike at the base on right side center. (Record, S. 30 1/2° W., 33.0 ft.)

A sawed fir stump, 13 ins. diam., 6 ft. high, bears N. 36° W., 36.2 ft. dist., with a healed blaze and a spike at the base on right side center. (Record, 38.3 ft.)

and a bearing tree mkd. by the Josephine County Surveyor's Office

A fir, 9 ins. diam., bears N. 55 1/4° W., 12.2 ft. dist., with a healed double blaze and a spike at the base on left side center.

S. 89° 49' 45" W., bet. secs. 4 and 33.

1337.43

The E 1/16 sec. cor. of secs. 4 and 33, established by Templin, PE No. 3024, in 1974, and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with cracked plastic cap mkd. TEMPLIN RE 3024.

**Dependent Resurvey of a Portion of the South Boundary,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p align="center">S 33 E 1/16 ——— S 4 2018</p> <p>from which</p> <p>A fir, 11 ins. diam., bears S. 43 1/2° W., 36.8 ft. dist., mkd. E 1/16 S4 BT.</p> <p>A fir, 10 ins. diam., bears N. 26° W., 12.7 ft. dist., mkd. E 1/16 S33 BT.</p> <p>From this cor., a point established by person(s) unknown, bears S. 11° 47' 01" E., 6.86 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, and was not utilized during the course of this survey.</p> <hr/> <p>S. 89° 48' 37" W., beginning new measurement.</p>
1337.14	<p>The 1/4 sec. cor. of secs. 4 and 33, reported by Gawron in 1963-64, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <p align="center">T 33 S R 6 W S 33 1/4 ——— S 4 T 34 S 1963</p> <p>from which new bearing trees</p> <p>A madrone, 13 ins. diam., bears N. 48° E., 34.1 ft. dist., mkd. 1/4 S33 BT.</p> <p>An oak, 17 ins. diam., bears S. 4 1/4° E., 7.4 ft. dist., mkd. 1/4 S4 BT.</p> <hr/> <p align="center">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p align="center">Restoring the 1855 survey by Wells Lake and George W. Hyde, the 1882 survey by William H. Byars, and the 1994 resurvey by Francis J. Simon</p> <hr/>

23780

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>From the 1/4 sec. cor. of secs. 2 and 11, reported by Simon in 1994, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W S 2 1/4 ——— S 11 1994</p> <p>from which a bearing tree reported by Simon</p> <p style="padding-left: 40px;">A black oak, 22 ins. diam., bears S. 21 1/4° E., 40.9 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A madrone, 7 ins. diam., bears N. 59 1/2° W., 19.8 ft. dist., mkd. 1/4 S2 BT.</p> <p>S. 89° 27' 54" W., bet. secs. 2 and 11.</p>
1340.57	<p>The W 1/16 sec. cor. of secs. 2 and 11, reported by Simon in 1994, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 2 W 1/16 ——— S 11 1994</p> <p>from which bearing trees reported by Simon</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 65 1/4° E., 17.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 54 1/4° W., 22.8 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 89° 27' 54" W., beginning new measurement.</p>
1340.57	<p>The cor. of secs. 2, 3, 10, and 11, reported by Simon in 1994, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 33 S R 6 W S 3 S 2 ————— S 10 S 11 1967</p> <p>from which bearing trees reported by Simon</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A ponderosa pine, 21 ins. diam., bears N. 56 1/2° E., 12.9 ft. dist., with a healed double blaze.</p> <p>A black oak, 13 ins. diam., bears S. 25 1/4° E., 8.9 ft. dist., with a healed double blaze.</p> <p>A fir, 9 ins. diam., bears S. 41 1/4° W., 8.6 ft. dist., with a healed double blaze.</p> <p>A white oak, 10 ins. diam., bears N. 80° W., 23.8 ft. dist., with a healed double blaze.</p> <p>A black oak, 19 ins. diam., bears N. 70 1/2° W., 68.0 ft. dist., with no marks visible on rotted open blaze. (Original) (Record, N. 70° W.)</p> <hr/>
1292.88	<p>N. 0° 20' 36" W., bet. secs. 2 and 3.</p> <p>The S 1/16 sec. cor. of secs. 2 and 3, established by Smith, PLS No. 1101, in 1990, and is accepted as the cor.; monumented with an aluminum post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd.</p> <p align="center">STATE OF OREGON DEPARTMENT OF FORESTRY S 1/16 S 3 S 2 1990 1101</p> <p>from which bearing trees mkd. by Smith</p> <p>A fir, 50 ins. diam., bears S. 69 3/4° E., 19.3 ft. dist., with a healed blaze.</p> <p>A fir, 12 ins. diam., bears S. 51 1/4° W., 17.1 ft. dist., with a healed blaze.</p> <hr/>
1292.88	<p>N. 0° 24' 12" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 2 and 3, perpetuated by person(s) unknown, further perpetuated by the Douglas County Surveyor's Office in 1967, recorded in C.S. File 54/53-34; monumented with an iron rod, 1/2 in. diam., firmly set, projecting 16 ins. above the ground, from which original bearing trees</p> <p>A fir, 24 ins. diam., bears S. 64° E., 32.3 ft. dist., with a healed blaze. (Record, 35.6 ft.)</p> <p>A fir, 40 ins. diam., bears N. 46° W., 18.5 ft. dist., with no marks visible on partially open blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p>

23782

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 38 ins. diam., bears S. 11 3/4° E., 15.2 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W 1/4 S 3 S 2 2018</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15, restored by Lawrence, PE No. 1543, in 1956, perpetuated by person unknown, and further perpetuated by the Josephine County Surveyor's Office in 1982, recorded in C.S. Book 7, page 188, and is accepted as the best available evidence of the position of the original cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 17 ins. above the ground, from which bearing trees mkd. by person(s) unknown</p> <p>A fir, 31 ins. diam., bears S. 35 3/4° E., 14.5 ft. dist., with a healed blaze.</p> <p>A fir, 33 ins. diam., bears S. 5 3/4° W., 24.5 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the Josephine County Surveyor's Office</p> <p>A black oak, 23 ins. diam., bears N. 28 1/4° E., 67.7 ft. dist., with a healed double blaze.</p> <p>A black oak, 16 ins. diam., bears N. 44 3/4° W., 28.4 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W S 10 S 11 ----- S 15 S 14 2018</p> <p>From this cor., a wood post, 3 1/2 x 5 1/2 ins., 2 ft. high, bears East, 1.0 ft. dist.</p> <p>S. 89° 49' 46" W., bet. secs. 10 and 15.</p>
1328.44	Point for the E 1/16 sec. cor. of secs. 10 and 15.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 10 E 1/16 ——— S 15 2018</p> <p>from which</p> <p style="padding-left: 40px;">A white oak, 6 ins. diam., bears N. 85 1/4° E., 53.0 ft. dist., mkd. E 1/16 S10 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 65 1/2° E., 71.0 ft. dist., mkd. E 1/16 S15 BT.</p>
2656.88	<p>The 1/4 sec. cor. of secs. 10 and 15, reestablished by proportionate measurement by Hull, PLS No. 901, in 1993. There is no remaining evidence of the original cor., therefore this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with yellow plastic cap mkd. HULL RS 901, from which bearing trees mkd. by Hull</p> <p style="padding-left: 40px;">A white oak, 9 ins. diam., bears N. 88 3/4° E., 65.0 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A white oak, 6 ins. diam., bears S. 24 1/4° E., 30.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A white oak, 14 ins. diam., bears N. 70° W., 46.6 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A live oak, 14 ins. diam., bears N. 39 1/2° W., 40.6 ft. dist., with scribe marks S 1/4 RS 901 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W S 10 1/4 ——— S 15 2018</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 49' 46" W., beginning new measurement.</p>
1328.44	<p>Point for the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, in a mound of stone, 3 ft. base, to the top, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;"> S 10 W 1/16 _____ S 15 2018 </p> <p>from which</p> <p>A black oak, 7 ins. diam., bears S. 46 1/4° W., 48.6 ft. dist., mkd. W 1/16 S15 BT.</p> <p>A fir, 11 ins. diam., bears N. 25 1/2° W., 30.7 ft. dist., mkd. W 1/16 S10 BT.</p>
2656.88	<p>The cor. of secs. 9, 10, 15, and 16, reported by Simon in 1994, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 33 S R 6 W S 9 S 10 _____ S 16 S 15 1994 </p> <p>from which bearing trees reported by Simon</p> <p>A fir, 41 ins. diam., bears N. 12 1/2° E., 25.1 ft. dist., with a healed blaze.</p> <p>A fir, 34 ins. diam., bears S. 25° E., 8.3 ft. dist., with a healed double blaze.</p> <p>A fir, 32 ins. diam., bears S. 86° W., 12.5 ft. dist., with a healed triple blaze.</p> <p>A fir, 24 ins. diam., bears N. 59 1/4° W., 36.0 ft. dist., with a healed double blaze.</p>
	<p style="text-align: center;"> Subdivision of Section 2, T. 33 S., R. 6 W., Willamette Meridian, Oregon </p>
	<p>From the 1/4 sec. cor. of secs. 2 and 11.</p> <p>N. 0° 24' 50" E., on the N. and S. center line of sec. 2.</p>
1303.85	<p>Point for the center S 1/16 sec. cor. of sec. 2, not monumented.</p>
2607.70	<p>The center 1/4 sec. cor. of sec. 2, established by Hollingsworth, PLS No. 691, in 1988, and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. T33S R6W C1/4 S2 1988 OREGON STATE PARKS DIVISION, from which bearing trees mkd. by Hollingsworth</p>

23785

Subdivision of Section 2,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 21 ins. diam., bears N. 15 1/2° E., 15.5 ft. dist., with a healed blaze.</p> <p>A fir, 21 ins. diam., bears N. 48° W., 19.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W C 1/4 S 2 2018</p> <hr/> <p>N. 0° 24' 14" E., beginning new measurement.</p>
1336.63	<p>The center N 1/16 sec. cor. of sec. 2, established by Hollingsworth, PLS No. 691, in 1988, and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, from which the remains of a bearing tree mkd. by Hollingsworth</p> <p>A fir, 22 ins. diam., bears S. 27 1/2° E., 17.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Affix an aluminum cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">C N 1/16 S 2 C 2018</p> <p>and a new bearing tree</p> <p>A fir, 9 ins. diam., bears N. 24° W., 22.5 ft. dist., mkd. CN 1/16 S2 BT.</p> <hr/>
1375.36	<p>N. 0° 24' 43" E., beginning new measurement.</p> <p>The 1/4 sec. cor. of sec. 2 only, on the N. bdy. of the Tp., reported by Dieckmann in 2006-07, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">OREGON STATE PARKS T 32 S R 6 W <hr/>1/4 S 2 T 33 S R 6 W 1988 LS 691</p> <p>from which a new bearing tree</p>

23786

**Subdivision of Section 2,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 8 ins. diam., bears S. 4 3/4° W., 40.2 ft. dist., mkd. 1/4 S2 BT.</p> <p>From this cor., a point reported by Dieckmann, bears N. 38° 03' 00" E., 2.60 ft. dist., monumented with an iron rod, 1 in. diam., firmly set, projecting 2 ins. above the ground, from which a bearing tree reported by Dieckmann</p> <p>A fir, 19 ins. diam., bears S. 45° E., 29.1 ft. dist., with a healed blaze.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 1 and 2, reestablished by proportionate measurement by Hollingsworth, PLS No. 691, in 1988. There is no remaining evidence of the original cor., therefore this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">OREGON STATE PARKS T 33 S R 6 W 1/4 S 2 S 1 1988 LS 691</p>
	<p>from which bearing trees mkd. by Thompson, PE No. 3683, in 1962, and reported by Hollingsworth</p>
	<p>A madrone, 13 ins. diam., bears N. 55° E., 21.2 ft. dist., with a healed blaze.</p>
	<p>A fir, 38 ins. diam., bears S. 76 1/4° W., 23.9 ft. dist., with a healed blaze.</p>
	<p>From this cor., a point established by Thompson, PE No. 3683, in 1962, bears N. 41° 50' 50" E., 8.54 ft. dist., monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 7 ins. above the ground, not accepted by Hollingsworth in 1988, and not utilized during the course of this survey.</p>
	<p>S. 89° 01' 45" W., on the E. and W. center line of sec. 2.</p>
1483.33	<p>A point established by Hollingsworth, PLS No. 961, in 1988, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with yellow plastic cap mkd. OREGON STATE PARKS.</p>
2666.39	<p>The center 1/4 sec. cor. of sec. 2.</p> <hr/>
	<p>S. 89° 01' 45" W., beginning new measurement.</p>
1358.40	<p>The center W 1/16 sec. cor. of sec. 2, established by Nygren, PLS No. 1035, in 1998, and is accepted as the cor.; monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p>

23787

Subdivision of Section 2,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">OREGON STATE BOARD OF FORESTRY T 32 S R 6 W WM W 1/16 C———C S 2 1998 LS 1035</p> <p>from which bearing trees mkd. by Nygren</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 60 1/4° E., 14.9 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 22 1/4° E., 18.6 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 4° W., 27.9 ft. dist., mkd. CW 1/16 S2 BT.</p> <hr/> <p>S. 88° 59' 24" W., beginning new measurement.</p> <p>1358.40 The 1/4 sec. cor. of secs. 2 and 3.</p> <hr/>
	<p>From the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>N. 0° 01' 18" E., on the N. and S. center line of the SW 1/4 of sec. 2.</p> <p>1298.41 Point for the SW 1/16 sec. cor. of sec. 2, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 2 2018</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 23° E., 7.7 ft. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 89° W., 17.0 ft. dist., mkd. SW 1/16 S2 BT.</p>
	<p>2597.20 The center W 1/16 sec. cor. of sec. 2.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 2.</p>

23788

**Subdivision of Section 2,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	S. 89° 14' 08" W., on the E. and W. center line of the SW 1/4 of sec. 2.
1349.49	The SW 1/16 sec. cor. of sec. 2.
2698.27	The S 1/16 sec. cor. of secs. 2 and 3.
<hr/> Subdivision of Section 10, T. 33 S., R. 6 W., Willamette Meridian, Oregon <hr/>	
	From the 1/4 sec. cor. of secs. 10 and 15.
	N. 0° 09' 03" E., on the N. and S. center line of sec. 10.
2666.05	Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
T 33 S R 6 W C 1/4 S 10 2018	
	from which
A fir, 16 ins. diam., bears S. 47 1/2° W., 12.5 ft. dist., mkd. C 1/4 S10 BT.	
A white oak, 8 ins. diam., bears N. 27 1/4° W., 8.1 ft. dist., mkd. C 1/4 S10 BT.	
5328.71	The 1/4 sec. cor. of secs. 3 and 10, reestablished by proportionate measurement by Nygren, PLS No. 1035, in 1995. There is no remaining evidence of the original cor., therefore this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with yellow plastic cap mkd. NYGREN LS 1035, from which bearing trees mkd. by Nygren A tan oak, 6 ins. diam., bears N. 70 1/4° E., 35.5 ft. dist., with scribe marks X at breast height and BT at the base visible on bark. A tan oak, 8 ins. diam., bears S. 12 1/4° W., 6.0 ft. dist., with scribe marks X at breast height and BT at the base visible on bark. A madrone, 6 ins. diam., bears S. 78 1/2° W., 6.3 ft. dist., with scribe marks X at breast height and BT at the base visible on bark. A madrone, 15 ins. diam., bears N. 35 3/4° W., 8.6 ft. dist., with scribe marks 1/4 S3 BT visible on bark.
	At the corner point

23789

Subdivision of Section 10,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W S 3 1/4 ——— S 10 2018</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11, reported by Simon in 1994, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W 1/4 S 10 S 11 1994</p> <p>from which the remains of bearing trees reported by Simon</p> <p>A black oak, 30 ins. diam., bears S. 37 1/4° E., 17.2 ft. dist., with no marks visible on open blaze. (Original)</p> <p>A broken off and rotted ponderosa pine snag, size indeterminate, bears N. 38 1/2° W., 13.9 ft. dist., with scribe marks 1/4 BT visible on open blaze. (Original)</p> <p>and a new bearing tree</p> <p>A fir, 4 ins. diam., bears N. 64 1/2° W., 3.9 ft. dist., mkd. X at breast height and BT at the base.</p> <p>N. 89° 49' 07" W., on the E. and W. center line of sec. 10.</p>
1317.46	<p>Point for the center E 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S 10 2018</p> <p>from which</p> <p>A fir, 9 ins. diam., bears S. 56 3/4° W., 26.9 ft. dist., mkd. CE 1/16 S10 BT.</p> <p>A fir, 7 ins. diam., bears N. 37 1/2° W., 21.6 ft. dist., mkd. X at breast height and BT at the base.</p>

23790

**Subdivision of Section 10,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
2634.92	The center 1/4 sec. cor. of sec. 10.
3955.22	<p>Point for the center W 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ————— C S 10 2018</p> <p>from which</p> <p style="padding-left: 40px;">A maple, 9 ins. diam., bears N. 29 1/4° E., 24.5 ft. dist., mkd. CW 1/16 S10 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 30° E., 40.4 ft. dist., mkd. X at breast height and BT at the base.</p>
5275.52	<p>The 1/4 sec. cor. of secs. 9 and 10, reported by Simon in 1994, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W 1/4 S 9 S 10 1994</p> <p>from which bearing trees reported by Simon</p> <p style="padding-left: 40px;">A cedar, 43 ins. diam., bears N. 2 1/4° E., 61.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. 86° W., 117.5 ft. dist., with a healed blaze.</p> <hr/>
2657.96	<p>From the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 0° 04' 55" W., on the N. and S. center line of the SE 1/4 of sec. 10.</p> <p>The center E 1/16 sec. cor. of sec. 10.</p> <hr/>
Subdivision of Section 33, T. 33 S., R. 6 W., Willamette Meridian, Oregon	
<p>From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.</p> <p>N. 0° 53' 02" E., on the N. and S. center line of sec. 33.</p>	

23791

Subdivision of Section 33,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET	
1410.43	<p>Point for the center S 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 33 C 2018</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 17 3/4° W., 44.4 ft. dist., mkd. CS 1/16 S33 BT.</p> <p style="padding-left: 40px;">An alder, 18 ins. diam., bears N. 64° W., 29.9 ft. dist., mkd. CS 1/16 S33 BT.</p>
2820.86	<p>Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W C 1/4 S 33 2018</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 12 3/4° W., 7.4 ft. dist., mkd. C 1/4 S33 BT.</p> <p style="padding-left: 40px;">A white oak, 9 ins. diam., bears N. 36 3/4° W., 66.1 ft. dist., mkd. C 1/4 S33 BT.</p>
5547.62	<p>The 1/4 sec. cor. of secs. 28 and 33, reported by Stanger in 1982, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W S 28 1/4 ——— S 33 1982</p> <p>from which bearing trees reported by Stanger</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 71 3/4° E., 43.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 7° W., 36.6 ft. dist., with a healed blaze. (Record, N. 8 1/4° W.)</p> <hr/>

23792

Subdivision of Section 33,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>From the 1/4 sec. cor. of secs. 33 and 34, reported by Gawron and Thielsen in 1958-63, perpetuated by person(s) unknown, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 33 S 34 T 33 S R 6 W 1958</p> <p>from which the remains of a bearing tree reported by Gawron and Thielsen</p> <p>A sawed and rotted fir stump, size indeterminate, 6 ft. high, bears S. 74 3/4° E., 46.7 ft. dist., with a healed blaze. (Record, S. 74° E., 47.5 ft.)</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 17 ins. diam., bears S. 7 1/2° W., 33.1 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p>A fir, 10 ins. diam., bears N. 46 1/2° E., 79.3 ft. dist., mkd. 1/4 S34 BT. S. 89° 55' 15" W., on the E. and W. center line of sec. 33.</p>
1335.78	Point for the center E 1/16 sec. cor. of sec. 33, not monumented.
2671.56	The center 1/4 sec. cor. of sec. 33.
5145.47	<p>The 1/4 sec. cor. of secs. 32 and 33, reported by Stanger in 1982, perpetuated by Mcintosh, PLS No. 2103, in 2000, further perpetuated by the Josephine County Surveyor's Office in 2015, not recorded at the time of this survey, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 6 W 1/4 S 32 S 33 1963</p> <p>from which a bearing tree mkd. by Mcintosh</p> <p>A fir, 27 ins. diam., bears N. 49 1/4° W., 63.8 ft. dist., with a healed blaze and a spike at the base on right side center.</p> <p>and bearing trees mkd. by the Josephine County Surveyor's Office</p> <p>A fir, 12 ins. diam., bears S. 4 3/4° E., 50.1 ft. dist., with a healed double blaze and a spike at the base on left side center.</p>

23793

Subdivision of Section 33,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

FEET	
1409.32	<p>A fir, 7 ins. diam., bears N. 83 1/4° W., 39.2 ft. dist., with a healed double blaze and a spike at the base on right side center.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp. N. 0° 51' 53" E., on the N. and S. center line of the SE 1/4 of sec. 33.</p> <p>The SE 1/16 sec. cor. of sec. 33, established by Wytcherley, PLS No. 2724, in 2004, and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with yellow plastic cap mkd. WYTCHERLEY LS 2724, from which bearing trees mkd. by Wytcherley</p> <p>A fir, 14 ins. diam., bears N. 35 3/4° E., 18.3 ft. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 79° W., 27.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 33 2018</p> <hr/>
1408.94	<p>N. 0° 51' 23" E., beginning new measurement.</p> <p>The center E 1/16 sec. cor. of sec. 33.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 33 and 34, determined at record bearing and dist. from the remains of bearing trees reported by Gawron and Thielsen in 1958-63</p> <p>A fir, 25 ins. diam., bears S. 48° E., 26.4 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 21 ins. diam., 6 ft. high, bears S. 33° W., 14.5 ft. dist., with a healed blaze.</p> <p>Found the 1958 iron post set by Gawron and Thielsen disturbed from logging activity.</p> <p>At the corner point</p> <p>Reset the 1958 iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 33 S 34 T 33 S R 6 W 1958</p>

**Subdivision of Section 33,
T. 33 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	and a new bearing tree
	A fir, 9 ins. diam., bears N. 5 3/4° W., 36.4 ft. dist., mkd. S 1/16 S33 BT.
	From this cor., a point established by Brandt, PLS No. 841, in 1979, bears S. 77° 38' 58" W., 3.55 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground. Brandt didn't use the bearing trees to determine the cor. position but instead reestablished the cor. position at midpoint between the cor. of sections 3, 4, 33, and 34 to the south and the 1/4 section cor. of sections 33 and 34 to the north, and was therefore not accepted or utilized during the course of this survey.
	S. 89° 51' 34" W., on the E. and W. center line of the SE 1/4 of sec. 33.
1339.91	The SE 1/16 sec. cor. of sec. 33. <hr style="width: 20%; margin: 10px auto;"/>
	S. 89° 51' 34" W., beginning new measurement.
1336.57	The center S 1/16 sec. cor. of sec. 33. <hr style="width: 60%; margin: 10px auto;"/>
	S. 89° 22' 29" W., on the E. and W. center line of the SW 1/4 of sec. 33.
2556.17	The S 1/16 sec. cor. of secs. 32 and 33, reported by Stanger in 1982, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. <div style="text-align: center;">S 1/16 S 32 S 33 1982</div>
	from which bearing trees reported by Stanger
	A fir, 17 ins. diam., bears S. 40° E., 15.5 ft. dist., with a healed blaze.
	A fir, 16 ins. diam., bears S. 84 1/4° W., 10.6 ft. dist., with a healed blaze. <hr style="width: 60%; margin: 10px auto;"/>