

23800

513

VOL 701

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES AND SUBDIVISION OF SECTION 11,
TOWNSHIP 19 SOUTH, RANGE 8 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON

EXECUTED BY

Joseph M. Mannix, Cadastral Surveyor

Under Special Instructions approved June 27, 2016,
which provided for the surveys included under Group No. 2846,
and Assignment Instructions dated June 27, 2016.

Survey commenced July 26, 2016

Survey completed November 16, 2016

T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and subdivision of section 11, Township 19 South, Range 8 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1891, Charles M. Collier, U.S. Deputy Surveyor, surveyed the subdivisional lines, as shown on the official plat of survey approved April 4, 1892, and accepted February 14, 1893.

In 1952, Marvin J. Lytle and Palmer Norseth, Cadastral Engineers, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted May 29, 1953.

In 1958, Floyd Brooks, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted October 21, 1959.

In 1980, Lester E. Fischer and David W. Mattson, Cadastral Surveyors, dependently resurveyed a portion of the subdivisional lines, and remonumented certain original corners, as shown on the official plat of survey accepted August 31, 1983.

In 2009, Daniel N. Patterson, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, and subdivided section 13, as shown on the official plat of survey accepted August 29, 2011.

The following local surveys (CS) filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1985	Leslie D. Roberts, PLS 1039	CS 62/30-4
2015	Ronald L. Rice, PLS No. 54633	CS 65/88-3

The following local surveys (CS) and Recovered Corner Index (RCI) filed in the Lane County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1978	William A. Eimstad, PLS No. 377	CS 21846
1986	Leslie D. Roberts, PLS No. 1039	CS 27344
1988	Daniel W. Baker, PLS No. 1978	CS 28466
2006	Harvey Christensen, PLS No. 2603	CS 39634
2007	Kent R. Inman, PLS No. 60050	CS 40711
2015	Mikeal J. Blomme, PLS No. 74387	RCI 16001, RCI 16002
2016	Robert B. Ward, Jr., PLS No. 1091	RCI 16430

T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>In July 1983, the Bureau of Land Management (BLM), Eugene District Office, conducted an unofficial administrative survey subdividing a portion of section 11, as shown on the plat of survey filed at the Interagency Office of the Northwest District in Springfield, Oregon.</p> <p>The survey was executed in accordance with the specification set forth in the <u>Manual of Surveying Instructions</u> (2009), and the special instructions approved June 27, 2016, for Group No. 2846, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observation and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.</p> <p>Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description. Aluminum angle irons were driven alongside each monument unless a similar marker was already in place.</p> <p>Only those lines bounding Federal interest land were blazed.</p> <p>The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):</p> <p>The 1/4 section corner of sections 11 and 12: Latitude: 43° 55' 41.06" N. Longitude: 123° 35' 57.90" W.</p> <p>The 1/4 section corner of sections 27 and 28: Latitude: 43° 53' 04.38" N. Longitude: 123° 38' 21.55" W.</p> <p>The corner of sections 9, 10, 15, and 16: Latitude: 43° 55' 17.00" N. Longitude: 123° 38' 20.20" W.</p>
------	--

T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>The 1/4 section corner of sections 10 and 15:</p> <p>Latitude: 43° 55' 16.64" N. Longitude: 123° 37' 43.72" W.</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 S., R. 8 W., Willamette Meridian, Oregon</p>
	<p style="text-align: center;">Restoring the survey by Charles M. Collier in 1891, the resurvey by Marvin J. Lytle and Palmer Norseth in 1952, the resurvey by Floyd Brooks in 1958, the resurvey and remonumentation by Lester Fischer and David M. Mattson in 1980, and the resurvey by Patterson in 2009</p>
	<p>Beginning at the cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd. and accessories as described in the 2009 official survey by Patterson.</p>
	<p>N. 0° 07' 18" E., bet. secs. 11 and 12.</p>
1356.00	<p>The S 1/16 sec. cor. of secs. 11 and 12, established by Christensen, PLS No. 2603, in 2006; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, with an aluminum cap mkd. T19S R8W S1/16 S11 S12 PLS2603 2006, from which the remains of the bearing trees mkd. by Christensen</p> <p style="padding-left: 40px;">A hemlock stump, 13 ins. diam., bears N. 39 3/4° E., 26.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 20 3/4° E., 41.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Drive the iron rod 12 ins. below the surface of the ground and set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., directly over the top, 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 11 S 12 2016</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">An alder, 16 ins. diam., bears S. 36 3/4° W., 58.2 ft. dist., mkd. S1/16 S11 BT in the bark.</p> <p>A steel fence post is alongside the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
1355.88	<p>N. 0° 08' 31" E., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 11 and 12, perpetuated by Eimstad, PLS No. 377, in 1978; subsequently perpetuated by Christensen, PLS No. 2603, in 2006; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with an aluminum cap mkd. ROSEBURG RESC. CO. T19S R8W ¼ S11 S12 PLS2603 2006, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed cedar stump, size indeterminate, bears N. 83 1/2° E., 35.0 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Christensen</p> <p style="padding-left: 40px;">An alder, 17 ins. diam., bears N. 2 1/2° E., 54.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An alder snag, 17 ins. diam., bears S. 85 1/2° E., 39.1 ft. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., directly over the iron rod, 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 S R 8 E</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 40px;">S 11 S 12</p> <p style="margin-left: 40px;">2016</p> </div> <p>from which</p> <p style="padding-left: 40px;">A maple, 10 ins. diam., bears S. 15 3/4° W., 11.5 ft. dist., mkd. 1/4 S11 BT.</p> <p>A galvanized fence post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>
1367.10	<p>N. 0° 08' 16" E., beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 11 and 12. Not monumented.</p>
2734.20	<p>The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 S R 8 W</p> <p style="margin-left: 40px;">S 2 S 1</p> <hr style="width: 100%;"/> <p style="margin-left: 40px;">S 11 S 12</p> <p style="margin-left: 40px;">1980</p> </div> <p>from which the bearing trees reported by Fischer and Mattson in 1980</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 27 ins. diam., bears N. 15° E., 40.6 ft. dist., with a healed blaze.</p> <p>A maple clump, size indeterminate, bears N. 56° E., 34.3 ft. dist., no marks visible. (Original)</p> <p>A fir, 26 ins. diam., bears N. 86° E., 15.8 ft. dist., with a healed blaze.</p> <p>An alder, 17 ins. diam., bears S. 17° E., 53.1 ft. dist., with illegible scribe marks visible on bark.</p> <p>A decayed fir stump, 41 ins. diam., bears S. 82 1/4° E., 26.4 ft. dist., with illegible scribe marks visible on open blaze. (Original)</p> <p>A fir, 26 ins. diam., bears S. 19 1/2° W., 6.6 ft. dist., with a healed blaze.</p> <p>An alder, 18 ins. diam., bears N. 35 1/2° W., 21.8 ft. dist., with illegible scribe marks visible on bark.</p> <p>A steel fence post is alongside the cor.</p> <p>A search was made for all original line trees bet. secs. 11 and 12 and none were recovered.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15, determined at distance-distance intersection from the accessories reported by Fischer and Mattson in 1980</p> <p>A hemlock, 65 ins. diam., bears S. 19° W., 82.5 ft. dist., with no scribe marks visible on open blaze. (Original)</p> <p>An iron post, 2 1/2 ins. diam., firmly set, with top 6 ins. below the surface of the ground, bears S. 19° 00' 00" W, 26.40 ft. dist., with a brass cap mkd. T19S R8W RM 40 LKS TO COR 1/4 S15 1980 and an arrow pointing to the cor.</p> <p>A cedar, 46 ins. diam., bears N. 4 1/2° W., 111.2 ft. dist., with a healed blaze.</p>
	<p>At the corner point</p> <p>Set an aluminum angle iron, 5 ft. long, 24 ins. in the ground.</p> <p>Corner is located in a creek, 10 ft. wide, course N. 20° E.</p> <p>N. 0° 44' 54" E., bet. secs. 14 and 15.</p>
935	Graveled road, 10 ft. wide, bears S. 85° E. and N. 85° W.
2716.44	The cor. of secs. 10, 11, 14, and 15, perpetuated by Rice, PLS No. 54633, in 2015; further perpetuated by Blomme, PLS No. 74387, in 2015, under RCI 16002; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	<div data-bbox="812 325 1015 472" style="text-align: center;"> T 19 S R 8 W S 10 S 11 <hr style="width: 100%;"/> S 15 S 14 1958 </div> <p data-bbox="422 504 1323 535">from which the remains of the bearing trees reported by Brooks in 1958</p> <p data-bbox="462 556 1372 619">A fir snag, 35 ins. diam., bears N. 16 1/4° E., 34.3 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p data-bbox="462 640 1380 703">A fir snag, 26 ins. diam., bears S. 22 1/4° E., 15.8 ft. dist., with a healed blaze. (Original)</p> <p data-bbox="462 724 1404 787">A decayed fir snag, 24 ins. diam., bears S. 61 3/4° W., 46.9 ft. dist., with a healed blaze.</p> <p data-bbox="462 808 1364 871">A decayed fir snag, 22 ins. diam., bears N. 86° W., 39.6 ft. dist., with a healed blaze.</p> <p data-bbox="422 903 828 934">and a bearing tree mkd. by Rice</p> <p data-bbox="462 955 1404 1018">A fir, 8 ins. diam., bears N., 13.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p data-bbox="422 1050 844 1081">and accessories mkd. by Blomme</p> <p data-bbox="462 1102 1380 1197">An iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, bears N. 77° 55' 54" E, 20.02 ft. dist., with an aluminum cap mkd. LANE COUNTY SUVEYORS OFFICE RP1 2015.</p> <p data-bbox="462 1218 1404 1312">An iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, bears S. 4° 14' 29" E, 17.49 ft. dist., with an aluminum cap mkd. LCSO RP2 2015.</p> <p data-bbox="462 1333 1396 1396">A fir, 14 ins. diam., bears S. 72 1/2° W., 7.8 ft. dist., with scribe marks BT visible on partially healed blaze.</p> <p data-bbox="422 1428 714 1459">and a new bearing tree</p> <p data-bbox="462 1480 1396 1512">A fir, 8 ins. diam., bears N. 30° W., 26.4 ft. dist., mkd. T19S R8W S10 BT.</p> <p data-bbox="422 1543 982 1575">A galvanized fence post is alongside the cor.</p> <p data-bbox="422 1596 1323 1659">A search was made for all original line trees on the line resurveyed bet. secs. 14 and 15 and none were recovered.</p> <hr data-bbox="422 1680 1404 1690"/> <p data-bbox="422 1711 941 1743">From the cor. of secs. 11, 12, 13, and 14.</p> <p data-bbox="422 1764 917 1795">N. 88° 10' 19" W., bet. secs. 11 and 14.</p>
------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
374.56	<p>The remains of the original line tree, recovered by Eimstad, PLS No. 377, in 1978, described as a fir stump, 57 ins. diam., double blazed; subsequently perpetuated by Baker, PLS No. 1978, in 1988, monumented with a fir stump, 40 ins. diam., with no marks visible, and an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the top of the stump, with a yellow plastic cap mkd. DW BAKER 1978. This position now functions as Angle Point No. 1 on the line bet. secs. 11 and 14.</p> <p>At the corner point</p> <p>Remove yellow plastic cap and affix an aluminum cap mkd.</p> <div style="text-align: center;"> <p>AP 1</p> <p>S 11</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S 14</p> <p>2016</p> </div>
912.09	<p>N. 88° 10' 02" W., beginning new measurement.</p> <p>The E 1/16 sec. cor. of secs. 11 and 14, established by Baker, PLS No. 1978, in 1988; and is accepted as the cor.; monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 7 ins. above ground, with an aluminum cap mkd. RLS1978 S11 E1/16 S14 19S R8W 1988, from which the remains of the bearing trees mkd. by Baker</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 10° E., 30.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A roothole bears S. 31 1/2° E., 33.9 ft. dist., alongside of which is a down fir, 20 ins. diam., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., directly over the aluminum rod, 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 11</p> <p>E 1/16 <hr style="width: 50px; display: inline-block; vertical-align: middle;"/></p> <p>S 14</p> <p>2016</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 47 1/2° W., 37.5 ft. dist., mkd. E1/16 S14 BT.</p> <p>An aluminum fence post is alongside the cor.</p> <div style="text-align: center;"> <hr style="width: 50px; margin: 0 auto;"/> </div> <p>N. 88° 11' 31" W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET 1287.47	<p>The 1/4 sec. cor. of secs. 11 and 14, reestablished by proportionate measurement by Eimstad, PLS No. 377, in 1978; utilized by Baker, PLS No. 1978, in 1988. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with a steel shaft, 2 1/8 ins. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Eimstad</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 13 1/4° E., 32.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An alder, 16 ins. diam., bears N. 63 3/4° W., 31.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 S R 8 W</p> <p>S 11</p> <p>1/4 ———</p> <p>S 14</p> <p>2016</p> </div> <p>Remove the steel shaft from the area.</p> <p>An aluminum post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 27' 29" W., beginning new measurement.</p>
1070.31	<p>The original line tree, a fir, 79 ins. diam., mkd. with two hack marks on the E. and W. sides. This position now functions as Angle Point No. 2 on the line bet. secs. 11 and 14.</p> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., set 30 ins. in the ground for a reference monument, bears N. 61° 34' 48" E, 15.66 ft. dist., with aluminum cap mkd. RM AP2 15.7 FT TO COR S11 2016 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., set 30 ins. in the ground for a reference monument, bears S. 43° 06' 13" E, 15.09 ft. dist., with aluminum cap mkd. RM AP2 15.1 FT TO COR S14 2016 and an arrow pointing to the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 27' 29" W., beginning new measurement.</p>
217.35	<p>The W 1/16 sec. cor. of secs. 11 and 14, established by Eimstad, PLS No. 377, in 1978; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, from which a bearing tree mkd. by Eimstad</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>A hemlock, 38 ins. diam., bears S. 13° E., 46.9 ft. dist., with a healed blaze.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> S 11 W 1/16 ——— S 14 2016 </p>
	<p>from which a new bearing tree</p>
	<p>An ash, 20 ins. diam., bears N. 53° W., 49.3 ft. dist., mkd. W1/16 S11 BT.</p>
	<p>N. 88° 32' 44" W., beginning new measurement.</p>
<p>590</p>	<p>Siuslaw River, 60 ft. wide, course N. 80° E.</p>
<p>750</p>	<p>Graveled road, 10 ft. wide, bears N. 60° E. and S. 60° W.</p>
<p>1287.47</p>	<p>The cor. of secs. 10, 11, 14, and 15.</p>
	<p>N. 0° 28' 44" E., bet. secs. 10 and 11.</p>
<p>135</p>	<p>Ridge, bears N. 65° E. and S. 65° W.</p>
<p>1326.14</p>	<p>The S 1/16 sec. cor. of secs. 10 and 11, established by Eimstad, PLS No. 377, in 1978; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, from which the remains of the bearing trees mkd. by Eimstad</p>
	<p>A roothole bears N. 68° E., 3.5 ft. dist., alongside of which is a down fir log, 9 ins. diam., with a healed blaze.</p>
	<p>A roothole bears S. 5° E., 6.5 ft. dist., alongside of which is a down fir log, 16 ins. diam., with a healed blaze.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., directly over the iron rod, 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> S 1/16 S 10 S 11 2016 </p>
	<p>from which</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 13 ins. diam., bears S. 45 1/2° E., 45.4 ft. dist., mkd. S1/16 S11 BT.</p> <p>A fir, 6 ins. diam., bears S. 66° W., 9.0 ft. dist., mkd. S1/16 S10 BT.</p> <p>A galvanized fence post is alongside the cor.</p> <hr/>
1273.74	<p>N. 0° 28' 16" E., beginning new measurement.</p> <p>The remains of the original line tree, perpetuated by Eimstad, PLS No. 377, in 1978, described as a line stump; monumented with a decayed double fir stump, 52 ins. diam., with no marks visible, and with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the top of the northerly stump, and is accepted for the original line tree. This position now functions as an Angle Point on the line bet. secs. 10 and 11.</p> <p>At the corner point</p> <p>Affix an aluminum cap to the top of the iron rod mkd.</p> <p align="center">AP S 10 S 11 2016</p> <hr/>
52.42	<p>N. 0° 20' 24" E., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 10 and 11, monumented the remains of the original cor. tree, a decayed fir snag, 24 ins. diam., with scribe marks 1/4 S visible on partially opened blaze on W. side, from which the accessories reported by Fischer and Mattson in 1980</p> <p>A fir snag, 26 ins. diam., bears N. 65° E., 23.1 ft. dist., with no scribe marks visible on open blaze. (Original)</p> <p>A fir stump, 18 ins. diam., bears N. 81° E., 9.2 ft. dist., with a healed blaze.</p> <p>A fir stump, 21 ins. diam., bears S. 11° W., 17.2 ft. dist., with a healed blaze.</p> <p>An iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, bears S. 30° W., 13.2 ft. dist., with a brass cap mkd. T19S R8W RM 1/4 S10 20LS TO COR 1980 and an arrow pointing to the cor.</p> <p>A steel fence post is alongside the cor.</p> <p>At the corner point</p> <p>Cut down the original cor. tree and drove an iron rod, 30 ins. long, 5/8 in. diam., 30 ins. deep in the center of the stump, with an aluminum cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET											
815	Right bank of the Siuslaw River, bears S. 85° E. and N. 85° W., course N. 85° W. Exit River and continue over land.										
865	Asphalt road, 15 ft. wide, bears S. 60° E. and N. 60° W.										
1428.16	<p>The cor. of secs. 2, 3, 10, and 11, perpetuated by Inman, PLS No. 60050, in 2007; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T 19 S R 8 W</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td colspan="2">1980</td> </tr> </table> </div> <p>from which the remains of the original bearing trees reported by Fischer and Mattson in 1980</p> <ul style="list-style-type: none"> A decayed fir stump, size indeterminate, bears N. 7 1/2° E., 8.6 ft. dist., no marks visible. A fir, 27 ins. diam., bears S. 6° E., 23.1 ft. dist., with a healed blaze. A fir stump, 32 ins. diam., bears S. 14 1/2° W., 25.1 ft. dist., with a healed blaze. A fir, 25 ins. diam., bears N. 32 1/2° W., 13.9 ft. dist., with a healed blaze. <p>and the bearing tree mkd. by Inman</p> <ul style="list-style-type: none"> A fir, 11 ins. diam., bears N. 45° E., 16.2 ft. dist., with a healed blaze. <p>and a new bearing tree</p> <ul style="list-style-type: none"> A fir, 8 ins. diam., bears S. 6 1/2° W., 20.0 ft. dist., mkd. T19S R8W S10 BT. <p>A steel fence post and a galvanized fence post are alongside the cor.</p> <p>A search was made for all original line trees bet. secs. 10 and 11 and none were recovered.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89° 35' 37" W., bet. sec. 2 and 11.</p>	T 19 S R 8 W		S 3	S 2	-----		S 10	S 11	1980	
T 19 S R 8 W											
S 3	S 2										

S 10	S 11										
1980											
55	Creek, 5 ft. wide, course S. 35° E.										
1283.59	Point for the E 1/16 sec. cor. of secs. 2 and 11. Not monumented.										
2190	Graveled road, 20 ft. wide, bears S. 20° E. and N. 20° W.										

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
2567.18	<p>The 1/4 sec. cor. of secs. 2 and 11, reestablished by proportionate measurement by Eimstad, PLS No. 377, in 1978; utilized by Baker, PLS No. 1978, in 1988, and by Christensen, PLS No. 2603, in 2006. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, from which the bearing trees mkd. by Eimstad</p> <p>A fir stump, 6 ft. tall, 15 ins. diam., bears N. 76° E., 6.6 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears S. 30° E., 10.7 ft. dist., with a healed blaze and an aluminum nail right side center.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 W S 2 1/4 ——— S 11 2016</p> <p>No suitable trees in sec. 2 available.</p> <p>A galvanized fence post is alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 36' 15" W., beginning new measurement</p>
2567.88	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>A search was made for all original line trees bet. secs. 2 and 11 and none were recovered.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 W 1/4 S 28 S 27 1952</p> <p>from which the remains of the bearing trees mkd. by Lytle and Norseth in 1952</p> <p>A fir, 80 ins. diam., bears S. 55 1/2° E., 46.9 ft. dist., no marks visible.</p> <p>A cedar snag, 19 ins. diam., bears N. 67 1/4° W., 54.8 ft. dist., no marks visible.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>and a new bearing tree</p> <p>A fir, 18 ins. diam., bears N. 67 1/2° W., 56.4 ft. dist., mkd. 1/4 S28 BT.</p> <p>N. 0° 00' 19" E., bet. secs. 27 and 28.</p>																				
2724.24	<p>The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 19 S R 8 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black; text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table> </td> </tr> </table> </div> <p>from which the remains of bearing trees reported by Lytle and Norseth in 1952</p> <p>A fir stump, 43 ins. diam., bears N. 83° E., 46.7 ft. dist., with a healed blaze. (Original)</p> <p>A fir, 43 ins. diam., bears S. 79 1/2° E., 19.8 ft. dist., no marks visible. (Original)</p> <p>A fir, 52 ins. diam., bears S. 67° W., 46.2 ft. dist., with a healed blaze.</p> <p>A maple, 17 ins. diam., bears N. 45° W., 42.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 6 ins. diam., bears N. 79° E., 5.4 ft. dist., mkd. X BT.</p> <p>A steel fence post is alongside the cor.</p> <p>A search was made for all original line trees on the line resurveyed bet. secs. 27 and 28 and none were recovered.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 19 S R 8 W</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4 ———</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1980</td> </tr> </table> </div> <p>from which the remains of bearing trees reported by Fischer and Mattson in 1980</p> <p>A fir stump, 32 ins. diam., bears N. 26° E., 19.1 ft. dist., no marks visible and a tin cap. (Original)</p>	T 19 S R 8 W		S 21	S 22	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table>		S 28	S 27	1952		T 19 S R 8 W		S 22		1/4 ———		S 27		1980	
T 19 S R 8 W																					
S 21	S 22																				
<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table>		S 28	S 27	1952																	
S 28	S 27																				
1952																					
T 19 S R 8 W																					
S 22																					
1/4 ———																					
S 27																					
1980																					

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
2631.68	<p>A fir stump, 40 ins. diam., bears S. 42° E., 12.5 ft. dist., no marks visible. (Original. Record, S. 39 1/2° W.)</p> <p>A maple, 23 ins. diam., bears S. 8° E., 75.6 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 43 1/4° E., 7.6 ft. dist., mkd. 1/4 S22 BT.</p> <p>A fir, 10 ins. diam., bears S. 2 3/4° E., 4.7 ft. dist., mkd. 1/4 S27 BT.</p> <p>Steel fence posts are alongside the cor. to the N. and W.</p> <p>N. 88° 21' 02" W., bet. secs. 22 and 27.</p> <p>The cor. of secs. 21, 22, 27, and 28.</p> <p>A search was made for all original line trees on the line resurveyed bet. secs. 22 and 27 and none were recovered.</p>
2656.11	<p>N. 0° 07' 10" E., bet. secs. 21 and 22.</p> <p>The 1/4 sec. cor. of secs. 21 and 22, perpetuated by Roberts, PLS No. 1039, in 1985; monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <p align="center">1/4 S 21 S 22 1952</p> <p>from which the remains of an original bearing tree reported by Lytle and Norseth in 1952</p> <p>A fir stump, 38 ins. diam., bears S. 55° E., 28.4 ft. dist., with a healed blaze and cruiser marks on face.</p> <p>and the accessories mkd. by Roberts</p> <p>A concrete nail, set in a rock face 3 ft. above ground, bears N. 38° 08' 06" E., 23.70 ft. dist.</p> <p>A fir, 33 ins. diam., bears S. 81 3/4° W., 20.2 ft. dist., with a healed blaze.</p> <p>A steel fence post is alongside the cor.</p> <p>A search was made for all original line trees on the line resurveyed bet. secs. 21 and 22 and none were recovered.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET											
	<table style="margin: auto;"> <tr> <td colspan="2">T 19 S R 8 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table>	T 19 S R 8 W		S 16	S 15			S 21	S 22	1952	
T 19 S R 8 W											
S 16	S 15										
S 21	S 22										
1952											
	<p>from which the remains of bearing trees reported by Lytle and Norseth in 1952</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears S. 7 1/4° E., 21.8 ft. dist., with a healed blaze. (Original)</p> <p style="padding-left: 40px;">A hemlock stump, 27 ins. diam., bears S. 78° W., 30.4 ft. dist., with a healed blaze. (Original)</p> <p style="padding-left: 40px;">A fir, 52 ins. diam., bears N. 47° W., 91.1 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears N. 46 1/2° E., 30.6 ft. dist., mkd. T19S R8W S15 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 48 1/2° W., 39.9 ft. dist., mkd. T19S R8W S21 BT.</p> <p>N. 0° 44' 55" E., bet. secs. 15 and 16.</p>										
2726.62	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">1/4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table> </p> <p>from which the remains of the bearing trees mkd. by Lytle and Norseth in 1952</p> <p style="padding-left: 40px;">A roothole bears N. 20° E., 57.4 ft. dist., alongside of which is a down fir log, size indeterminate, no marks visible.</p> <p style="padding-left: 40px;">A fir, 52 ins. diam., bears N. 31° W., 79.9 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 24 3/4° E., 6.8 ft. dist., mkd. 1/4 S15 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 49' 02" E., beginning new measurement.</p>	1/4		S 16	S 15	1952					
1/4											
S 16	S 15										
1952											
2655.95	<p>The witness cor. to the cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd. WC T19S R8W S 9 S10 S16 S15 1952, from which the remains of a bearing tree mkd. by Lytle and Norseth in 1952</p>										

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>A fir snag, 29 ins. diam., bears S. 28° W., 27.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>This position now functions as an Angle Point. Remove marks WC S9 S10 and add marks AP 2016 to the cap to now read</p> <div style="text-align: center; margin: 10px 0;"> <p>AP</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 19 S</td> <td style="padding: 0 5px;">R 8 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1952</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2016</td> </tr> </table> </div> <p>2658.70 The cor. of secs. 9, 10, 15, and 16, perpetuated by Rice, PLS No. 54633, in 2015; monumented with the remains of the original cor. tree, a decayed fir snag, size indeterminate, with no marks visible, from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A decayed fir snag, size indeterminate, bears N. 74 1/2° E., 16.5 ft. dist., with scribe marks T19S R8W visible on open blaze.</p> <p>and the bearing trees mkd. by Rice</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears N. 81 3/4° E., 31.8 ft. dist., with scribe marks R8W visible on partially healed blaze and an aluminum nail right side center.</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears S. 26 3/4° E., 5.5 ft. dist., with illegible scribe marks visible on partially healed blaze and an aluminum nail right side center.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 1 3/4° W., 12.7 ft. dist., with illegible scribe marks visible on partially healed blaze and an aluminum nail right side center.</p> <p>At the corner point</p> <p>Remove fir snag and set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 19 S</td> <td style="padding: 0 5px;">R 8 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 0 5px;">S 16</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">S 15</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">2016</td> </tr> </table> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A dogwood, 8 ins. diam., bears S. 62° W., 10.4 ft. dist., mkd. T19S R8W S16 BT.</p>	T 19 S	R 8 W	S 16	S 15	1952		2016		T 19 S	R 8 W	S 9	S 10	S 16		S 15		2016	
T 19 S	R 8 W																		
S 16	S 15																		
1952																			
2016																			
T 19 S	R 8 W																		
S 9	S 10																		
S 16																			
S 15																			
2016																			

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p>A search was made for all original line trees on the line bet. secs. 15 and 16 and none were recovered.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 88° 20' 17" W., bet. secs. 10 and 15.</p>
2593.66	<p>The 1/4 sec. cor. of secs. 10 and 15, perpetuated by Blomme, PLS No. 74387, in 2015, under RCI 16001; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 S R 8 W S 10 1/4 ——— S 15 1980</p> </div> <p>from which the remains of bearing trees reported by Fischer and Mattson in 1980</p> <ul style="list-style-type: none"> A fir stump, 6 ft. tall, 18 ins. diam., bears S. 7° W., 11.2 ft. dist., with scribe marks BT visible on open blaze. (Original) A double chinquapin, 12 ins. diam., bears S. 46 3/4° W., 22.8 ft. dist., with illegible scribe marks visible on partially healed blaze. (Record, S. 53° W.) A fir, 21 ins. diam., bears N. 81 1/2° W., 3.6 ft. dist., with a healed blaze and an aluminum nail right side center. <p>and a bearing tree reported by Rice, PLS No. 54633, in 2015, to have been marked by Ward, PLS No. 1091, during an unfiled survey in 2000</p> <ul style="list-style-type: none"> A fir, 20 ins. diam., bears N. 60 1/2° E., 19.2 ft. dist., with a healed blaze and an aluminum nail right side center. <p>and a bearing tree mkd. by Blomme in 2015</p> <ul style="list-style-type: none"> A fir, 9 ins. diam., bears S. 84 1/4° E., 12.3 ft. dist., with illegible scribe marks visible on partially healed blaze and an aluminum nail right side center. <p>A steel fence post is alongside the cor.</p> <hr/> <div style="text-align: center; margin: 10px 0;"> <p>Subdivision of Section 11, T. 19 S., R. 8 W., Willamette Meridian, Oregon</p> </div> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0° 11' 27" E., on the N. and S. center line of sec. 11.</p>

**Subdivision of Section 11,
T. 19 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
1341.05	Point for the center S 1/16 sec. cor. of sec. 11. Not monumented.
2682.10	<p>The center 1/4 sec. cor. of sec. 11, established by Eimstad, PLS No. 377, in 1978; utilized by Baker, PLS No. 1978, in 1988; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, from which the bearing trees mkd. by Eimstad</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 24 3/4° E., 13.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A double fir, 13 ins. diam., bears N. 83 3/4° E., 27.2 ft. dist., with a healed blaze on west tree.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., directly over the iron rod, 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 W C 1/4 S 11 2016</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 11' 00" E., beginning new measurement.</p>
1350.89	<p>The center N 1/16 sec. cor. of sec. 11, established by Christensen, PLS No. 2603, in 2006, and is accepted as the cor.; determined by distance-distance intersection from the accessories mkd. by Christensen; monumented with a maple, 12 ins. diam., in a clump of maple trees</p> <p>At the corner point</p> <p>Paint the tree with red pain and set a BLM Location Tag sign on the tree mkd. for the cor.</p> <p>from which the accessories mkd. by Christensen</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, bears N. 84° 14' 15" E., 1.00 ft. dist., with an aluminum cap mkd. T19S R8W S11 2001 1/16 2603 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 75 3/4° E., 7.8 ft. dist., with a healed blaze and an aluminum nail left side center.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 51 3/4° W., 27.7 ft. dist., with a healed blaze.</p> <p>and accessories established by the BLM, Eugene District Office, under an Administrative Survey in 1983</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, for a reference monument, bears N. 77° 43' 58" W, 12.05 ft. dist.; set an aluminum cap on top of the iron rod, mkd. RM CN1/16 S11 12.1 FT TO COR 2016 and an arrow pointing to the cor.</p>

Subdivision of Section 11,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>A fir stump, 29 ins. diam., bears S. 11° W., 22.4 ft. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 85° W., 6.7 ft. dist., with a healed blaze.</p> <hr/>
	<p>N. 0° 11' 47" E., beginning new measurement.</p>
1349.55	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 11 and 12.</p>
	<p>N. 88° 49' 49" W., on the E. and W. center line of sec. 11.</p>
1285.14	<p>The center E 1/16 sec. cor. of sec. 11, established by Christensen, PLS No. 2603, in 2006; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with an aluminum cap mkd. ROSEBURG RES. CO. 19S R 8 W CE 1/16 C S 11 2603 2001, from</p>
	<p>which the remains of a bearing tree mkd. by Christensen</p> <p>A roothole bears N. 85 1/2° E., 16.4 ft. dist., alongside of which is a down fir log, 13 ins. diam., with illegible scribe marks visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., directly over the iron rod, 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C ——— C</p> <p>S 11</p> <p>2016</p> </div>
	<p>from which new bearing trees</p>
	<p>A fir, 11 ins. diam., bears N. 71 3/4° E., 12.4 ft. dist., mkd. CE1/16 S11 BT.</p>
	<p>A fir, 15 ins. diam., bears N. 44 3/4° W., 17.6 ft. dist., mkd. CE1/16 S11 BT.</p>
	<p>A galvanized fence post is alongside the cor.</p> <hr/>
	<p>N. 88° 51' 11" W., beginning new measurement.</p>
1285.20	<p>The center 1/4 sec. cor. of sec. 11.</p> <hr/>
	<p>N. 88° 50' 46" W., beginning new measurement.</p>
1280.52	<p>Point for the center W 1/16 sec. cor. Not monumented</p>

Subdivision of Section 11,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
1285.20	The center 1/4 sec. cor. of sec. 11. <hr/>
	N. 88° 50' 46" W., beginning new measurement.
1280.52	Point for the center W 1/16 sec. cor. Not monumented
2561.04	The 1/4 sec. cor. of secs. 10 and 11. <hr/>
	From the center E 1/16 sec. cor. of sec. 11.
	N. 0° 09' 06" E., on the N. and S. center line of the NE 1/4 of sec. 11.
1358.88	The NE 1/16 sec. cor. of sec. 11, established by Christensen, PLS No. 2603, in 2006; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., 30 ins. long, firmly set, projecting 3 ins. above ground, with an aluminum cap mkd. T 19 S R 8 W S 11 NE 1/16 2006, from which the bearing trees mkd. by Christensen A fir, 14 ins. diam., bears S. 77 1/4° W., 13.3 ft. dist., with a healed blaze. A fir, 18 ins. diam., bears N. 47 3/4° W., 9.7 ft. dist., with a healed blaze. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, with brass cap mkd. NE 1/16 S 11 2016
	Deposit the iron rod and the aluminum cap inside of the stainless steel post. <hr/>
	N. 0° 10' 27" E., beginning new measurement.
1358.18	The E 1/16 sec. cor. of secs. 2 and 11. <hr/>
	From the N 1/16 sec. cor. of secs. 11 and 12.
	N. 89° 11' 46" W., on the E. and W. center line of the NE 1/4 of sec. 11.
1284.61	The NE 1/16 sec. cor. of sec. 11. <hr/>
	N. 89° 12' 32" W., beginning new measurement.
1284.25	The center N 1/16 sec. cor. of sec. 11. <hr/>

Subdivision of Section 11,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	From the E 1/16 sec. cor. of secs. 11 and 14.
	N. 0° 08' 32" E., on the N. and S. center line of the SE 1/4 of sec. 11.
1348.27	The SE 1/16 sec. cor. of sec. 11, established by Baker, PLS No. 1978, in 1988; utilized by Christensen, PLS No. 2603, in 2006; and is accepted as the cor.;
	monumented with an aluminum rod, 1 in. diam., 42 ins. long, firmly set, projecting 1 in. above ground, with an aluminum cap mkd. RLS 1978 SE 1/16 S11 19S R8W 1988, from which the bearing trees mkd. by Baker
	A fir, 20 ins. diam., bears S. 87 1/2° E., 9.9 ft. dist., with a healed blaze.
	A fir, 16 ins. diam., bears S. 37 1/2° W., 13.9 ft. dist., with a healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SE 1/16 S 11 2016
	Deposit the aluminum rod and cap inside of the stainless steel post.
	An aluminum fence post is alongside the cor.

	N. 0° 09' 50" E., beginning new measurement.
1348.73	The center E 1/16 sec. cor. of sec. 11

	From the S 1/16 sec. cor. of secs. 11 and 12.
	N. 88° 30' 43" W., on the E. and W. center line of the SE 1/4 of sec. 11.
1285.88	The SE 1/16 sec. cor. of sec. 11.

	N. 88° 30' 43" W., beginning new measurement.
1286.06	The center S 1/16 sec. cor. of sec. 11.

	From the W 1/16 sec. cor. of secs. 11 and 14.
	N. 0° 20' 25" E., on the N. and S. center line of the SW 1/4 of sec. 11.
60	Siuslaw River, 50 ft. wide, course E.
1327.04	The SW 1/16 sec. cor. of sec. 11, established by Eimstad, PLS No. 377, in 1978; subsequently perpetuated by Ward, PLS No. 1091, in 2016; and is accepted as the cor.;
	monumented with an iron rod, 5/8 in. diam., firmly set,

Subdivision of Section 11,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>projecting 3 ins. above ground, with an aluminum cap mkd. ROSEBURG RESOURCES CO. SW1/16 S11 2000 LS1091, from which the remains of bearing trees mkd. by Eimstad</p> <p>A fir stump, 38 ins. diam., bears N. 75 1/2° E., 14.0 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A decayed fir stump, 23 ins. diam., bears S. 10 1/2° E., 23.3 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Ward</p> <p>A fir, 10 ins. diam., bears N. 19° E., 17.1 ft. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears N. 79 1/4° W., 3.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 11 2016</p> <p>A galvanized fence post is alongside the cor.</p> <hr/> <p>N. 0° 18' 58" E., beginning new measurement.</p>
1332.10	<p>The center W 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 11.</p> <p>N. 88° 26' 55" W., on the E. and W. center line of the SW 1/4 of sec. 11.</p>
1283.69	<p>The SW 1/16 sec. cor. of sec. 11.</p> <hr/> <p>N. 88° 34' 57" W., beginning new measurement.</p>
1284.17	<p>The S 1/16 sec. cor. of secs. 10 and 11.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 11.</p> <p>N. 89° 14' 15" W., on the E. and W. center line of the NW 1/4.</p>
2564.16	<p>The N 1/16 sec. cor. of secs. 10 and 11.</p> <hr/>