

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF PORTIONS OF THE
WEST AND SOUTH BOUNDARIES,
SUBDIVISIONAL LINES, AND MINERAL SURVEY NO. 805,
AND THE SUBDIVISION OF SECTIONS 29, 31, AND 32
TOWNSHIP 30 SOUTH, RANGE 4 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON

EXECUTED BY

Jeffrey O. Covington, Cadastral Surveyor

Under Special Instructions approved April 7, 2017,
which provided for the surveys included under Group No. 2872,
and Assignment Instructions dated April 7, 2017.

Survey commenced April 19, 2017

Survey completed October 28, 2019

T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>The following field notes are those of the dependent resurvey of portions of the west and south boundaries, subdivisional lines, and Mineral Survey No. 805, and the subdivision of sections 29, 31, and 32, Township 30 South, Range 4 West, Willamette Meridian, Oregon.</p> <p>The history of the official surveys pertaining to this survey is as follows:</p> <p>In 1854, Butler Ives and George W. Hyde, U.S. Deputy Surveyors, surveyed a portion of the west boundary, as shown on the official plat of survey for Township 30 South, Range 5 West, approved November 6, 1897.</p> <p>In 1855, Nathaniel Ford, U.S. Deputy Surveyor, surveyed the south boundary and a portion of the subdivisional lines, as shown on the official plat of survey approved March 9, 1855.</p> <p>In 1889, William Thiel, U.S. Deputy Surveyor, resurveyed the south and west boundaries and a portion of the subdivisional lines, and surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved February 18, 1890. None of the Ford corners were recovered on the south boundary and Thiel concluded that Ford did not survey this line. Thiel established new corners common to both townships on the south boundary and the closing corner of Townships 30 and 31 South, Range 4 West, on the meridional line of Range 5 West.</p> <p>In 1893, William M. Bushey, U.S. Deputy Surveyor, surveyed the remainder of the subdivisional lines, as shown on the official plat of survey approved June 29, 1895. Closing corners were established on the south boundary and the common corners established by Thiel on this boundary were remarked for Township 31 South only. The field notes state that "Blank Lines" were surveyed along the south and west boundaries, but the results of this work appear on the plat of survey, including the positions of the Thiel common corners and were used for the final calculation of the lot acres for both surveys by Bushey in Townships 30 and 31 South, Range 4 West.</p> <p>In 1894, William M. Bushey, U.S. Deputy Surveyor, surveyed the subdivisional lines of T. 31 S., R. 4 W., and established closing corners on the north boundary, as shown on the official plat of survey approved June 29, 1895. There is no reference to the Thiel common corners on the north boundary in the field notes or shown on the plat of survey.</p> <p>In 1919, C. Frank Rhodes, U.S. Mineral Surveyor, surveyed the Theodore Lode, Mineral Survey No. 805, as shown on the official plat of survey approved April 11, 1919.</p> <p>In 1921, a Supplemental Plat was created to identify the Lots in section 32 adjacent to the Theodore Lode, Mineral Survey No. 805, as shown on the amended plat approved September 12, 1921, and accepted October 4, 1921.</p> <p>In 1966-68, John M. Jelly, Lynn M. Roseberry, and Floyd A. Brooks, Cadastral Surveyors, resurveyed a portion of the north boundary as shown on the official plat of survey for Township 31 South, Range 5 West, accepted December 28, 1970.</p>

T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET

In 1984-86, Wayne L. Rogers, Rick A. McMullen, and Lance J. Bishop, Cadastral Surveyors, resurveyed a portion of the south boundary as shown on the official plat of survey for Township 31 South, Range 4 West, accepted September 25, 1987. The corners established by Thiel as common corners for both townships were changed to function as angle points.

In 1999, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted April 19, 2002.

The following local surveys (M) and county surveyor files (CS), filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name and official title, Professional Land Surveyor (PLS) No., or Professional Engineer (PE) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1949	John H. Markham Jr., PE No. 2880	CS40/179
1951	John H. Markham Jr., PE No. 2880	CS40/296
1953	John H. Markham Jr., PE No. 2880	CS41/161-2 & 3
1956	Robert M. Thompson, PLS No. 1358	CS42/152
1957	James W. Byron, Deputy County Surveyor	CS47/175
1957	James W. Byron, Deputy County Surveyor	CS49/45
1959	John H. Markham Jr., PE No. 2880	CS42/356
1960	John H. Markham Jr., PE No. 2880	CS42/356
1961	John H. Markham Jr., PE No. 2880	CS42/356
1961	James W. Prochnau, PLS No. 1305	M21-33
1963	James W. Byron, Deputy County Surveyor	CS53/26-83
1963	James W. Byron, Deputy County Surveyor	CS53/26-69
1963	James W. Byron, Deputy County Surveyor	CS53/26-74
1963	James W. Byron, Deputy County Surveyor	CS53/26-72
1963	James W. Byron, Deputy County Surveyor	CS53/26-84
1963	James W. Byron, Deputy County Surveyor	CS53/26-63
1963	James W. Byron, Deputy County Surveyor	CS53/26-66
1971	John M. Powell, Deputy County Surveyor	CS53/26-98
1991	Mark F. Smalley, PLS No. 2354	M113-18
1996	Ken W. Hoffine, PLS No. 2291	M123-69
1997	Randall W. Smith, PLS No. 2469	CS64/71-15
2000	Bruce A. Shaner, PLS No. 430	M132-37, CS65/30-191
2002	Mark F. Smalley, PLS No. 2354	CS65/45-1
2004	Ronald L. Rice, PLS No. 54633	M145-20
2013	Ken W. Hoffine, PLS No. 2291	M166-6, CS65/81-1
2013	Randall W. Smith, PLS No. 2469	CS67/38-18

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions approved April 7, 2017, for Group No. 2872, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment.

T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET

Measured distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each monument established or reestablished has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description. Aluminum angle irons were driven alongside each monument unless a similar marker was already in place.

Only those lines bounding Federal interest land were blazed.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The corner of sections 20, 21, 28, and 29:

Latitude: 42° 56' 27.94" N. Longitude: 123° 11' 20.60" W.

The corner of sections 27, 28, 33, and 34:

Latitude: 42° 55' 33.77" N. Longitude: 123° 10' 09.39" W.

The corner of sections 29, 30, 31, and 32:

Latitude: 42° 55' 36.19" N. Longitude: 123° 12' 29.11" W.

**Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

Restoring the survey by Butler Ives and George W. Hyde in 1854, the resurvey by William Thiel in 1889, the resurvey by William M. Bushey in 1893-94, and the resurvey by John M. Jelly, Lynn M. Roseberry, and Floyd A. Brooks in 1966-68, T. 31 S., R. 5 W.

Beginning at the cor. of secs. 25, 30, 31, and 36, perpetuated by Byron, Douglas County Deputy Surveyor, in 1963, filed as CS 53/26-83; subsequently perpetuated by Smalley, PLS No. 2354, in 2002; monumented with an iron

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S R S 25 S 30 R 5 ———— 4 W S 36 S 31 W 1963</p>
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir stump, 30 ins. diam., bears S. 18° W., 23.1 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Thiel in 1889</p> <p style="padding-left: 40px;">A fir snag, 43 ins. diam., bears S. 16° E., 10.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A tin-capped, fir stump, 34 ins. diam., bears N. 78 1/4° W., 113.2 ft. dist., with a healed blaze. (Record, 110.9 ft. dist.)</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 77° E., 44.4 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Smalley</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 73 3/4° E., 12.4 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 1 1/2° E., 37.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears N. 64 3/4° W., 49.8 ft. dist., mkd. T30S R5W S25 BT.</p> <p>S. 0° 05' 19" E., bet. secs. 31 and 36, on the W. bdy. of the Tp.</p>
1335	Graveled road, 15 ft. wide, bears N. 60° E. and S. 50° W.
1360.71	<p>The N 1/16 sec. cor. of sec. 31 only, established by Hoffine, PLS No. 2291, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">LONE ROCK TIMBER N 1/16 S 31 2013 PLS 2291</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>from which the remains of the bearing trees mkd. by Hoffine</p> <p>A fir stump, 16 ins. diam., bears N. 24° E., 9.3 ft. dist., with scribe marks N1/16 S31 BT visible on partially healed blaze.</p> <p>A fir stump, 48 ins. diam., bears S. 45 1/4° E., 35.6 ft. dist., with scribe marks N1/16 S31 BT visible on bark.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p> N1/16 S 31 2017</p> </div> <p>from which</p> <p>A fir, 17 ins. diam., bears N. 66 1/4° E., 42.8 ft. dist., mkd. N1/16 S31 BT.</p> <p>A fir, 22 ins. diam., bears N. 17 1/2° W., 14.1 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0° 06' 53" E., beginning new measurement.</p>
20	<p>Creek, 2 ft. wide, course S. 65° W.</p>
1236.85	<p>The 1/4 sec. cor. of sec. 36 only, perpetuated by Byron, Douglas County Deputy Surveyor, in 1957, filed as CS47/175; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE T 30 S R 5 W R 4 W 1/4 S 36 S 31 1957</p> </div> <p>from which the remains of the original bearing trees</p> <p>A hollowed, decayed madrone stump, 22 ins. diam., bears N. 35 1/4° E., 22.4 ft. dist., with axe marks visible. (Record, bears N. 40° E.)</p> <p>A burnt, decayed fir stump, 48 ins. diam., bears S. 29° W., 50.8 ft. dist., no marks visible.</p> <p>and the remains of a bearing tree mkd. by Byron</p> <p>A cedar stump, 21 ins. diam., bears S. 62° E., 19.3 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>and new bearing trees</p> <p>A fir, 5 ins. diam., bears S. 14 3/4° W., 35.3 ft. dist., mkd. X BT.</p> <p>A fir, 7 ins. diam., bears N. 84 1/2° W., 38.2 ft. dist., mkd. 1/4 S36 BT.</p> <hr/> <p>S. 0° 24' 35" E., beginning new measurement.</p>
75	<p>Graveled road, 18 ft. wide, bears N. 80° E. and S. 70° W.</p>
123.36	<p>The 1/4 sec. cor. of sec. 31 only, established by Hoffine, PLS No. 2291, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">LONE ROCK TIMBER T 30 S R 5 W R 4 W 1/4 S 31 2013 PLS 2291</p> <p>from which the remains of the accessories mkd. by Hoffine</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, bears N. 85° 56' 55" E., 46.86 ft. dist., with an orange plastic cap mkd. LONE ROCK TIMBER LS 2291. Removed plastic cap and replaced with an aluminum cap mkd. T30S R4W RM 1/4 S31 46.86 FT. TO COR. 2017 and an arrow pointing to the cor.</p> <p>A cedar stump, 16 ins. diam., bears N. 2 3/4° W., 74.0 ft. dist., with illegible scribe marks visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 5 W R 4 W 1/4 S 31 2017</p> <p>from which</p> <p>A madrone, 4 ins. diam., bears S. 27 3/4° E., 28.6 ft. dist., mkd. 1/4 S31 BT on bark.</p> <hr/> <p>S. 0° 25' 18" E., beginning new measurement.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	Graveled road, 18 ft. wide, bears S. 70° E. and N. 60° W.
65	
216.46	<p>True point for the closing cor. of Tps. 30 and 31 S., R. 4 W., at intersection with the S. bdy. of the Tp., established by Hoffine, PLS No. 2291, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">LONE ROCK TIMBER T 30 S R 4 W S 31 T 30 S R 5 W S 6 T 31 S 2013 PLS 2291</p> <p>from which a bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 39 1/2° E., 44.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 26 ins. long, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 5 W R 4 W C S 31 S 36 C S 6 T 31 S 2017</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 40 1/4° E., 33.8 ft. dist., mkd. T31S R4W S6 BT.</p> <p>From this cor., the amended closing cor. of Tps. 30 and 31 S., R. 4 W., bears S. 89° 25' 21" W., 6.48 ft. dist., perpetuated by Byron, Douglas County Deputy Surveyor, in 1957, filed as CS47/175; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE CC T 30 S T 30 S S 31 R R 5 W S 6 4 S 36 S 6 W T 31 S 1957</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

FEET

from which the remains of the bearing trees mkd. by Bushey in 1893

A fir, 22 ins. diam., bears N. 55° E., 48.8 ft. dist., with a healed blaze.

A decayed fir stump, 23 ins. diam., bears S. 83 3/4° E., 47.2 ft. dist., with scribe marks R4W S6 visible on open blaze.

A decayed pine stump, size indeterminate, bears S. 23 1/2° W., 25.1 ft. dist., with illegible scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by Byron

A madrone stump with strong regrowth, 20 ins. diam., bears N. 51° W., 21.1 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.

```

      AM
    T 30 S
R 5 W | R 4 W
      | C S 31
      | C S 6
      | T 31 S
      |
      | 2019
  
```

Buried the iron post, 36 ins. long, alongside the stainless steel post.

From this same cor., the cor. of Tps. 30 and 31 S., R. 5 W. only, bears S. 0° 22' 02" E., 2309.77 ft. dist.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with a brass cap mkd.

COUNTY SURVEYORS OFFICE

```

      BLM 1966
    T 30 S | T 31 S
R 5 W | R 4 W
      | 36
      |
      | 6
      | CLO
      | COR
      |
      | 1957
  
```

from which the bearing trees mkd. by Byron in 1957, filed under CS 47/175 reported by Berry and Akin, Jr. in 1972

A fir, 34 ins. diam., bears S. 18° E., 18.5 ft. dist., with a healed double blaze.

**Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

FEET

A fir, 28 ins. diam., bears N. 7° W., 28.4 ft. dist., with a healed double blaze.

and a bearing tree mkd. by person(s) unknown

A fir, 14 ins. diam., bears N. 9 1/4° W., 12.0 ft. dist., with a healed double blaze.

and a new bearing tree

A fir, 31 ins. diam., bears S. 54° W., 59.6 ft. dist., mkd. T31S R5W S1 BT.

**Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

Restoring the survey by Nathaniel Ford in 1855,
the resurvey by William Thiel in 1889,
the resurveys by William M. Bushey in 1893-94, and the resurvey by
Wayne L. Rogers, Rick A. McMullen, and Lance J. Bishop in 1984-86

From the angle point bet. secs. 4 and 33, formerly the original cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.

AP
T 30 S R 4 W
S 33
—
S 4
T 31 S
1985

from which the remains of an original bearing tree, reported by Rogers, McMullen, and Bishop in 1984-86

A decayed fir stump, 66 ins. diam., bears S. 73° W., 18.5 ft. dist., with axe marks visible on decayed blaze.

and the bearing trees mkd. by Rogers, McMullen, and Bishop in 1984-86

A fir, 18 ins. diam., bears N. 1° E., 25.7 ft. dist., with a healed blaze.
(Record, N. 1° W.)

A fir, 20 ins. diam., bears S. 24 3/4° E., 20.5 ft. dist., with a healed blaze.

S. 89° 04' 59" W., bet. secs. 4 and 33.

Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET 476.79	<p>True point for the closing cor. of secs. 32 and 33, hereinafter described.</p> <hr/> <p>S. 89° 04' 59" W., bet. secs. 4 and 32.</p>
152.59	<p>The closing cor. of secs. 4 and 5, T. 31 S., R. 4 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 S R 4 W</p> <p>S 32</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 5 S 4</p> <p>T 31 S</p> <p>CC</p> <p>1985</p> </div> <p>from which the bearing trees mkd. by Rogers, McMullen, and Bishop in 1984-86</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 27 1/2° E., 31.0 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 21 ins. diam., bears S. 60° W., 11.6 ft. dist., with a healed blaze.</p> <hr/> <p>S. 89° 06' 54" W., bet. secs. 5 and 32.</p>
1949.66	<p>An angle point bet. secs. 5 and 32; formerly the 1/4 sec. cor. of secs. 5 and 32, monumented with a magnet in a white plastic case, buried 4 ins. below the surface of the ground, from which the remains of a bearing tree mkd. by Rogers, McMullen, and Bishop in 1984-86</p> <p style="margin-left: 40px;">A burnt and decayed fir stump, 32 ins. diam., bears N. 7 1/4° E., 47.9 ft. dist., with scribe marks AP visible on a separated fragment of the blaze lying alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>AP</p> <p>T 30 S R 4 W</p> <p>S 32</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 5</p> <p>T 31 S</p> <p>2017</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 5 3/4° E., 8.3 ft. dist., mkd. AP S32 BT.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 11 ins. diam., bears S. 39 1/4° W., 41.6 ft. dist., mkd. AP S5 BT. Deposit the magnet at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 37' 25" W., beginning new measurement.</p>
80	Graveled road, 18 ft. wide, bears N. 30° E. and S. 45° W.
417.87	<p>Point for the 1/4 sec. cor. of sec. 32 only, at proportionate dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 4 W 1/4 S 32</p> <hr style="width: 10%; margin: auto;"/> <p>T 31 S 2017</p> </div> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 39 1/2° E., 13.3 ft. dist., mkd. 1/4 S32 BT. A fir, 8 ins. diam., bears S. 40° E., 12.8 ft. dist., mkd. X BT.</p>
2568.67	<p>An angle point bet. secs. 5 and 32; formerly the cor. of secs. 5, 6, 31, and 32, perpetuated by Hoffine, PLS No. 2291, in 2013, monumented with an iron post, 2 1/2 ins. diam., firmly set, with a brass cap mkd.</p> <div style="text-align: center;"> <p>AP T 30 S R 4 W S 32</p> <hr style="width: 10%; margin: auto;"/> <p>S 5 T 31 S 1985</p> </div> <p>from which the remains of the original bearing trees, reported by Rogers, McMullen, and Bishop in 1984-86</p> <p>A decayed fir stump, 30 ins. diam., bears N. 45° E., 5.9 ft. dist., with axe marks visible on bark. A decayed fir stump, size indeterminate, bears S. 63 1/2° W., 14.5 ft. dist., no marks visible. A fir stump, 50 ins. diam., bears N. 35° W., 37.0 ft. dist., with scribe marks 4W visible on bark.</p> <p>and a bearing tree mkd. by Rogers, McMullen, and Bishop in 1984-1986</p>

Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 25 ins. diam., bears N. 77 3/4° E., 48.8 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Hoffine</p> <p>A fir, 16 ins. diam., bears S. 43 3/4° W., 21.1 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <hr/> <p>S. 89° 43' 24" W., beginning new measurement,</p>
120	Graveled road, 14 ft. wide, bears N. 35° E. and S. 20° W.
506.80	True point for the closing cor. of secs. 31 and 32, hereinafter described.
	<hr/> <p>S. 89° 43' 24" W., bet. secs. 5 and 31.</p>
111.13	<p>True point for the closing cor. of secs. 5 and 6 only, at intersection with the line bet. secs. 5 and 6, T. 31 S., R. 4 W., established by Hoffine, PLS No. 2291, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with an aluminum cap mkd.</p>
	<p>LONE ROCK TIMBER T 30 S R 4 W S 31</p> <hr style="width: 10%; margin: auto;"/> <p>S 6 S 5 T 31 S R 4 W 2013 PLS 2291</p>
	<p>from which an original bearing tree mkd. for the original closing cor.</p> <p>A fir, 38 ins. diam., bears N. 22 1/4° W., 15.4 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Byron, Douglas County Deputy Surveyor, in 1957 for the original closing cor.</p> <p>A madrone, 11 ins. diam., bears N. 72 1/2° E., 19.2 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>T 30 S R 4 W S 31</p> <hr style="width: 100px; margin: auto;"/> <p>C C S 6 S 5 T 31 S R 4 W 2017</p>
	<p>From this cor., the original closing cor. of secs. 5 and 6, perpetuated by Byron, Douglas County Deputy Surveyor, in 1957, filed as CS47/175; bears N. 0° 37' 52" E., 11.24 ft. dist., monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A decayed fir snag, 18 ins. diam., bears S. 54 1/2° E., 28.7 ft. dist., with illegible scribe marks visible on open blaze.</p> <p style="margin-left: 40px;">A decayed fir snag, 20 ins. diam., bears S. 78° W., 12.5 ft. dist., with scribe marks T31S R4W S6 visible on open blaze.</p> <p style="margin-left: 40px;">A fir, 38 ins. diam., bears N. 68° W., 6.9 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Byron</p> <p style="margin-left: 40px;">A madrone, 11 ins. diam., bears S. 73 1/2° E., 19.0 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A fir stump, 45 ins. diam., bears S. 31° W., 12.2 ft. dist., with scribe marks T31S R4W CC visible on bark.</p> <p>Drove the iron rod flush with the surface of the ground.</p> <hr style="width: 100%; margin-top: 20px;"/> <p>S. 89° 44' 51" W., bet. secs. 6 and 31.</p> <p>485 Creek, 1 ft. wide, course S. 10° E.</p> <p>815 Ridge, bears N. and S.</p> <p>1225 Creek, 2 ft. wide, course S. 20° W.</p> <p>2305 Ridge, bears N. 25° E. and S. 25° W.</p> <p>2016.27 Point for the original 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; bet. the angle point bet. secs. 5 and 32, formerly the original cor. of secs. 5, 6, 31, and 32; and the original closing cor. bet. Tps. 30 and 31 S., R. 4 W. there is no remaining evidence of the original cor. This point now becomes an angle point.</p> <p style="margin-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">AP T 30 S R 4 W S 31 <hr/>S 6 T 31 S 2017</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 15 1/4° E., 17.9 ft. dist., mkd. AP S31 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 77 1/4° E., 26.4 ft. dist., mkd. AP S6 BT.</p> <p style="text-align: center;"><hr/></p> <p>S. 89° 46' 38" W., beginning new measurement</p>
1300	Creek, 2 ft. wide, course S. 40° W.
526.13	<p>The 1/4 cor. of sec. 31 only, established by Hoffine, PLS No. 2291, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">LONE ROCK TIMBER T 30 S R 4 W 1/4 S 31 <hr/>T 31 S R 4 W 2013 PLS 2291</p> <p>from which the bearing trees mkd. by Hoffine</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 30 3/4° E., 35.4 ft. dist., with scribe marks S31 BT and other illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 14° W., 22.2 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 4 W 1/4 S 31 <hr/>T 31 S R 4 W 2017</p> <p style="text-align: center;"><hr/></p> <p>S. 89° 44' 08" W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

<p>FEET</p> <p>2455</p> <p>2723.28</p>	<p>Graveled road, 15 ft. wide, bears S. 30° E. and N. 40° W.</p> <p>True point for the closing cor. of Tps. 30 and 31 S., R. 4 W., hereinbefore described.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 30 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">Restoring the survey by Nathaniel Ford in 1855, the resurvey by William Thiel in 1889, the survey by Bushey in 1893, and the resurvey by Moore and Browning in 1999</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S S 28 S 27 R ----- 4 S 33 S 34 W 1963</p> <p>from which the remains of the original bearing trees reported by Moore and Browning in 1999</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears N. 38° E., 8.9 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A decayed fir stump, 30 ins. diam., bears S. 75 1/2° E., 30.0 ft. dist., with no marks visible on open blaze.</p> <p style="margin-left: 40px;">A hollowed, decayed fir stump, 23 ins. diam., bears N. 23° W., 24.6 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Markham Jr., reported by Moore and Browning in 1999</p> <p style="margin-left: 40px;">A decayed fir stump, 56 ins. diam., bears S. 50 1/2° W., 39.5 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A decayed fir stump, 60 ins. diam., bears N. 32 3/4° W., 109.4 ft. dist., with axe marks visible.</p> <p>and the bearing trees mkd. by Byron, reported by Moore and Browning in 1999</p> <p style="margin-left: 40px;">A madrone, 16 ins. diam., bears S. 26 1/4° E., 39.5 ft. dist., with a healed blaze.</p>
----------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon


FEET	<p>A madrone, 22 ins. diam., bears N. 82 1/4° W., 29.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Moore in 1999</p> <p>A fir, 11 ins. diam., bears S. 63° W., 22.9 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p>A madrone, 7 ins. diam., bears N. 67 1/4° E., 17.3 ft. dist., mkd. T30S R4W S27 BT in the bark.</p> <p>S. 0° 11' 43" E., bet. secs. 33 and 34.</p>
2629.09	<p>The 1/4 sec. cor. of secs. 33 and 34, perpetuated by Markham Jr., PE No. 2880, in 1959; subsequently perpetuated by Shaner, PLS No. 430, in 2000; monumented with a threaded iron rod, 1/2 in. diam., firmly set, projecting 4 ins. above ground (alongside of which is a bent angle iron, 1 in. square, firmly set, projecting 2 ins., above the ground) with an aluminum cap mkd.</p> <p style="text-align: center;">ROSEBURG RESOURCES COMPANY T 30 S R 4 W 1/4 S 33 S 34 RLS 430 2000</p> <p>from which the original bearing trees</p> <p>A fir, 30 ins. diam., bears N. 42 1/2° E., 7.3 ft. dist., with a healed blaze.</p> <p>A fir, 25 ins. diam., bears N. 56° W., 6.6 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Markham, Jr.</p> <p>A roothole bears N. 71 1/2° W., 16.4 ft. dist., alongside of which is a down and decayed alder, 7 ins. diam., no marks visible.</p> <p>A fir, 28 ins. diam., bears N. 12 3/4° W., 5.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the threaded iron rod, 50 ins. long, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 4 W 1/4 S 33 S 34 2017</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET

Buried the angle iron, 32 ins. long, alongside the stainless steel post.

From the cor. of secs. 28, 29, 32, and 33, perpetuated by Markham Jr., PE No. 2880, in 1961; subsequently perpetuated by Rice, PLS No. 54633, in 2004; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground (alongside of which is an iron pipe, 1 in. diam., 24 ins. long, lying loose on the ground), with an aluminum cap mkd.



from which the remains of the original bearing trees

A fir stump, 43 ins. diam., bears N. 79° E., 93.2 ft. dist., with a healed blaze. (Record, 89.8 ft. dist.)

A decayed fir stump, size indeterminate, bears N. 73 3/4° W., 46.2 ft. dist., no marks visible. (Record, bears N. 68 1/4° W.)


and the remains of the bearing trees mkd. by Markham

A decayed fir snag, 10 ins. diam., bears N. 72 1/2° E., 6.5 ft. dist., alongside of which is a tin-capped down fir trunk segment, with a healed blaze.

A tin-capped decayed fir stump, 18 ins. diam., bears S. 39° E., 10.0 ft. dist., no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 30 ins. long, with brass cap mkd.



from which

A fir, 6 ins. diam., bears N. 45 3/4° E., 17.3 ft. dist., mkd. T30S R4W S28 BT.

A fir, 9 ins. diam., bears S. 84° E., 25.9 ft. dist., mkd. T30S R4W S33 BT.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 5 ins. diam., bears S. 24 1/2° W., 19.6 ft. dist., mkd. T30S R4W S32 BT.</p> <p>A fir, 7 ins. diam., bears N. 37 1/2° W., 18.2 ft. dist., mkd. T30S R4W S29 BT.</p> <p>Buried the iron pipe, 24 ins. long, alongside the stainless steel post.</p> <p>S. 0° 39' 40" E., bet. secs. 32 and 33.</p>
1299.81	<p>The N 1/16 sec. cor. of secs. 32 and 33, established by Prochnau, PLS No. 1305, in 1961; and is accepted as the cor.; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 2 ins. above ground, from which the remains of the bearing trees mkd. by Prochnau</p> <p>A decayed cedar stump, 26 ins. diam., bears S. 44° E., 13.2 ft. dist., no marks visible.</p> <p>A madrone root crown, 12 ins. diam., bears N. 81 1/2° W., 12.9 ft. dist., with regrowth around crown and no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the iron pipe, 24 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S 32 S 33 2017</p> </div> <p>from which</p> <p>A fir, 10 ins. diam., bears S. 78 3/4° E., 12.9 ft. dist., mkd. N1/16 S33 BT.</p> <p>A fir, 8 ins. diam., bears N. 19 1/4° W., 12.8 ft. dist., mkd. N1/16 S32 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0° 24' 38" E., beginning new measurement.</p>
1296.31	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate measurement; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 4 W 1/4 S 32 S 33 2017</p> </div> <p>from which</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>A fir, 26 ins. diam., bears N. 76 3/4° E., 30.2 ft. dist., mkd. 1/4 S33 BT.</p> <p>A fir, 22 ins. diam., bears N. 5 3/4° W., 34.4 ft. dist., mkd. 1/4 S32 BT.</p>																						
1770.10	<p>The amended closing cor. of secs. 32 and 33, perpetuated by Byron, Douglas County Deputy Surveyor, in 1963, filed as CS53/26-69; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 11 ins. above ground (alongside of which is the original basalt stone, 12 x 8 ins., firmly set, projecting 7 ins. above ground, mkd. CC on N. face, with 4 notches on east face and 2 notches on west face), with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 30 S R 4 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">CC</td> <td style="padding: 0 10px;">S 32</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 10px;">S 33</td> <td style="padding: 0 10px;">R</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; text-align: center; padding: 0 10px;"></td> <td style="padding: 0 10px;">4</td> </tr> <tr> <td colspan="3"></td> <td style="padding: 0 10px;">W</td> </tr> </table> <p style="margin: 0 10px;">T 31 S</p> <p style="margin: 0 10px;">1963</p> </div> <p>from which the remains of the original bearing trees, reported by Rogers, McMullen, and Bishop in 1984-86</p> <p>A decayed fir snag, 36 ins. diam., bears N. 25 1/2° E., 76.6 ft. dist., with a healed blaze.</p> <p>A fir snag, 46 ins. diam., bears S. 33 3/4° E., 35.6 ft. dist., with a healed blaze.</p> <p>A decayed fir stump, size indeterminate, bears N. 25° W., 69.3 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Byron, reported by Rogers, McMullen, and Bishop in 1984-86</p> <p>A madrone, 10 ins. diam., bears N. 31 3/4° E., 32.3 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A fir, 24 ins. diam., bears N. 33° W., 31.0 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>AM</p> <p>T 30 S R 4 W</p> <p>CC</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">S 32</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 10px;">S 33</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center; padding: 0 10px;"></td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">T 31 S</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">2019</td> </tr> </table> </div>	CC	S 32	S 33	R				4				W	S 32	S 33			S 4		T 31 S		2019	
CC	S 32	S 33	R																				
			4																				
			W																				
S 32	S 33																						
S 4																							
T 31 S																							
2019																							

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>Buried the iron post, 36 ins. long, alongside the stainless steel post.</p>
1777.26	<p>True point for the closing cor. of secs. 32 and 33, at intersection with the S. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 S R 4 W CC S 32 S 33 ----- S 4 T 31 S 2017</p> </div> <p>from which the bearing trees mkd. by Byron in 1963, filed under CS 53/26-69, for the amended closing cor.</p> <p style="margin-left: 40px;">A madrone, 10 ins. diam., bears N. 17 3/4° E., 38.3 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears N. 28° W., 36.2 ft. dist., with a healed blaze.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the 1/4 sec. cor. of secs. 29 and 30, perpetuated by Markham Jr., PE No. 2880, in 1949; subsequently perpetuated by Byron, Douglas County Deputy Surveyor, in 1963, filed as CS53/26-63; from original evidence no longer in existence; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron pipe, 28 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 S R 4 W 1/4 S 30 S 29 2017</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 67 3/4° E., 30.9 ft. dist., mkd. 1/4 S29 BT.</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 45 1/2° W., 56.1 ft. dist., mkd. 1/4 S30 BT.</p> <p>S. 0° 32' 39" E., bet. secs. 29 and 30.</p>
2629.74	<p>The cor. of secs. 29, 30, 31, and 32, perpetuated by Markham Jr., PE No. 2880, in 1951; subsequently perpetuated by Smith, PLS No. 2469, in 2013; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>8 ins. above ground (alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground), with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S R 4 W S 30 S 29 ----- S 31 S 32 2013</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir stump, 18 ins. diam., bears S. 66 1/4° E., 51.5 ft. dist., with scribe marks S3 visible on open blaze.</p> <p style="padding-left: 40px;">A madrone snag, 28 ins. diam., bears S. 66 3/4° W., 21.6 ft. dist., alongside of which is a down madrone, 28 ins. diam., no marks visible. (Record, 23.8 ft. dist.)</p> <p>and the remains of the bearing trees mkd. by Markham, Jr.</p> <p style="padding-left: 40px;">A decayed fir stump, 16 ins. diam., bears N. 81° E., 24.7 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A decayed fir stump, 26 ins. diam., bears S. 24 1/2° E., 64.4 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears N. 16 1/4° W., 53.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>and the bearing trees mkd. by Smith</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 58 1/4° E., 13.4 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 20 3/4° E., 9.3 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 61 1/2° W., 17.3 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33, hereinbefore described.</p> <p>N. 89° 11' 36" W., bet. secs. 29 and 32.</p> <p>512.21 The E-E 1/64 sec. cor. of secs. 29 and 32, established by Prochnau, PLS No. 1305, in 1961; and is accepted as the cor.; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of a bearing tree mkd. by Prochnau</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>A decayed fir stump, 15 ins. diam., bears S. 21 1/2° W., 14.3 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the iron pipe, 26 ins. long, with brass cap mkd.</p> <p style="text-align: center;"> S 29 E-E 1/64 ————— S 32 2017 </p> <p>from which</p> <p>A fir, 16 ins. diam., bears S. 13 1/4° E., 17.4 ft. dist., mkd. E E 1/64 S32 BT.</p> <p>A fir, 20 ins. diam., bears N. 53 1/4° W., 16.1 ft. dist., mkd. E E 1/64 S29 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 54' 12" W., beginning new measurement.</p>
450	Graveled road, 16 ft. wide, bears N. 35° E. and S. 30° W.
656.24	<p>The E 1/16 sec. cor. of secs. 29 and 32, established by Prochnau, PLS No. 1305, in 1961; and is accepted as the cor.; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 2 ins. above ground, from which the remains of the bearing trees mkd. by Prochnau</p> <p>A decayed hemlock stump, 12 ins. diam., bears S. 86 3/4° E., 14.6 ft. dist., no marks visible.</p> <p>A hemlock, 10 ins. diam., bears N. 44 3/4° W., 17.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron pipe, 26 ins. long, with brass cap mkd.</p> <p style="text-align: center;"> S 29 E 1/16 ————— S 32 2017 </p> <p>from which</p> <p>A hemlock, 10 ins. diam., bears S. 19 3/4° W., 17.0 ft. dist., mkd. E1/16 S32 BT.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1311.63	<p>N. 88° 36' 59" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 29 and 32, perpetuated by Byron, Douglas County Deputy Surveyor, in 1963, filed as CS53/26-72; monumented with an iron post, 1 1/4 ins. diam., firmly set, with top 24 ins. below the surface of the ground, with a brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE T 30 S S 29 R 1/4 ——— 4 S 32 W 1963</p> <p>from which the remains of the original bearing trees</p> <p>A burnt, decayed fir stump, size indeterminate, bears N. 41° E., 27.7 ft. dist., with a healed blaze.</p> <p>A fir, 23 ins. diam., bears S. 37 3/4° W., 38.9 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p>A fir, 22 ins. diam., bears N. 20 3/4° E., 52.4 ft. dist., with a healed double blaze.</p> <p>Corner is located in the east berm of an old skid trail, 10 ft. wide, bears N. and S. 10° W. Dug the berm out so the iron pipe is now flush with the surface of the ground.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the W bdy. of the Tp.</p> <p>N. 86° 59' 55" E., bet. secs. 30 and 31.</p>
2729.51	<p>The 1/4 sec. cor. of secs. 30 and 31, perpetuated by Thompson, PLS No. 1358, in 1956; subsequently perpetuated by Byron, Douglas County Deputy Surveyor, in 1963, filed as CS53/26-84; further perpetuated by Smalley, PLS No. 2354, in 1991; reported by Hoffine, PLS No. 2291, in 2013; monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 11 ins. above ground (alongside of which is the original basalt stone, 14 x 14 x 10 ins., firmly set, projecting 11 ins. above ground, with illegible marks visible on the north face, from which the remains of an original bearing tree</p> <p>A decayed fir stump, 17 ins. diam., bears N. 71° E., 25.4 ft. dist., no marks visible.</p> <p>and the remains of a bearing tree mkd. by Thompson</p> <p>A decayed fir stump, 20 ins. diam., bears S. 11 3/4° W., 21.3 ft. dist., no marks visible.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>and the bearing trees mkd. by Smalley</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 55° E., 33.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 31° E., 21.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, directly over the iron pipe, 24 ins. long, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 30 S R 4 W</p> <p>S 30</p> <p>1/4 _____</p> <p>S 31</p> <p>2017</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 84 1/2° E., 37.2 ft. dist., mkd. 1/4 S30 BT.</p> <p>Buried the original stone, 14 x 14 x 10 ins., alongside the stainless steel post. (Record, 16 x 14 x 10 ins.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="padding-left: 40px;">N. 86° 36' 38" E., beginning new measurement.</p>
2657.40	<p>The cor. of secs. 29, 30, 31, and 32.</p> <hr style="border: 1px solid black;"/>
45	<p>S. 0° 01' 04" E., bet. secs. 31 and 32.</p>
1320.16	<p>Graveled road, 16 ft. wide, bears S. 70° E. and N. 70° W.</p> <p>The N 1/16 sec. cor. of secs. 31 and 32, established by Hoffine, PLS No. 2991, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with an aluminum cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>LONE ROCK TIMBER</p> <p>N 1/16</p> <p>S 31 S 32</p> <p>2013</p> <p>PLS 2291</p> </div> <p>from which the remains of the bearing trees mkd. by Hoffine</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 78 1/4° E., 13.3 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 24 ins. diam., bears S. 70° W., 20.7 ft. dist., with scribe marks N1/16 S31 BT visible on partially healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 31 S 32 2017</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 89° W., 75.6 ft. dist., mkd. N1/16 S31 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0° 01' 43" E., beginning new measurement.</p>
1320.60	<p>The 1/4 sec. cor. of secs. 31 and 32, perpetuated by Powell, Douglas County Deputy Surveyor, in 1971; from original evidence no longer in existence; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S R 4 W 1/4 S 31 S 32 1971</p> <p>from which the bearing trees mkd. by Powell</p> <p style="padding-left: 40px;">A fir, 65 ins. diam., bears S. 7 3/4° E., 26.2 ft. dist., with scribe marks 1/4 S32 CS BT visible on bark.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 53 1/4° W., 15.1 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0° 20' 52" E, beginning new measurement.</p>
564.33	<p>The original closing cor. of secs. 31 and 32, perpetuated by Byron, Douglas County Deputy Surveyor, in 1957, filed as CS49/45; monumented with an iron rod, 3/4 in. diam., firmly set, projecting 14 ins. above ground (alongside of which is the original basalt stone, 11 x 8 x 6 ins. (Record, 14 x 12 x 5 ins.) firmly set, projecting 5 ins. above ground, with no marks visible), from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 48 ins. diam., bears N. 57 1/2° E., 62.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 59 ins. diam., bears S. 21 1/2° W., 43.7 ft. dist., with a healed blaze. (Record, 38.0 ft. dist.)</p> <p style="padding-left: 40px;">A decayed fir snag, 30 ins. diam., bears N. 76 1/4° W., 67.3 ft. dist., with scribe marks T30S R4W visible on open blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>and the bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 61 1/2° E., 19.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 54 1/2° W., 21.0 ft. dist., with a healed blaze.</p> <p>Reset the iron rod, 28 ins. long, flush with the ground. Buried the fractured basalt stone alongside the iron rod. Impractical to add marks AM to original stone.</p>																										
572.62	<p>True point for the closing cor. of secs. 31 and 32, at the intersection with the S. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T 30 S</td><td style="padding: 0 10px;">R 4 W</td></tr> <tr><td style="padding: 0 10px;">S 31</td><td style="padding: 0 10px;">S 32</td></tr> <tr><td style="padding: 0 10px;">C</td><td style="padding: 0 10px;">C</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td colspan="2" style="text-align: center;">S 5</td></tr> <tr><td colspan="2" style="text-align: center;">T 31 S</td></tr> <tr><td colspan="2" style="text-align: center;">2017</td></tr> </table> </div> <p>from which the bearing trees mkd. by Byron in 1957 for the original closing cor.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 44 1/4° E., 24.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 40° W., 26.8 ft. dist., with a healed blaze.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 20, 21, 28, and 29, subsequently perpetuated by Markham Jr., PE No. 2880, in 1953, filed as CS41/161-3; from original evidence no longer in existence; monumented with an axle shaft, 1 in. diam., with a 6 hole steel flange, 7 ins. diam., firmly set, with top flush with the surface of the ground, from which bearing trees mkd. by Markham</p> <p style="padding-left: 40px;">An oak, 20 ins. diam., bears N. 14 3/4° E., 13.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An oak, 16 ins. diam., bears S. 39 3/4° E., 23.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, directly over the inverted axle shaft, 24 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T 30 S</td><td style="padding: 0 10px;">R 4 W</td></tr> <tr><td style="padding: 0 10px;">S 20</td><td style="padding: 0 10px;">S 21</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td colspan="2" style="text-align: center;">S 29</td></tr> <tr><td colspan="2" style="text-align: center;">S 28</td></tr> <tr><td colspan="2" style="text-align: center;">2017</td></tr> </table> </div>	T 30 S	R 4 W	S 31	S 32	C	C			S 5		T 31 S		2017		T 30 S	R 4 W	S 20	S 21			S 29		S 28		2017	
T 30 S	R 4 W																										
S 31	S 32																										
C	C																										
S 5																											
T 31 S																											
2017																											
T 30 S	R 4 W																										
S 20	S 21																										
S 29																											
S 28																											
2017																											

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>N. 88° 31' 23" W., bet. secs. 20 and 29.</p>
2465	<p>Ridge, bears N. 5° E. and South.</p>
2614.64	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, determined by irregular boundary method; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 4 W S 20 1/4 ——— S 29 2017</p> </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears S. 10° E., 50.0 ft. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears N. 88 3/4° W., 57.0 ft. dist., mkd. 1/4 S20 BT.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 89° 37' 18" W., beginning new measurement.</p>
170	<p>Ridge, bears S. 10° E. and N. 10° W.</p>
2556.18	<p>The cor. of secs. 19, 20, 29, and 30, perpetuated by Markham Jr., PE No. 2880, in 1953, filed as CS41/161-2; subsequently perpetuated by Byron, Douglas County Deputy Surveyor, in 1963, filed as CS53/26; monumented with an iron post, 1 1/4 ins. diam., firmly set, bent over with top flush with the surface of the ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE T 30 S R 4 W S 19 S 20 ————— S 30 S 29 1963</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole bears N. 20° E., 27.7 ft. dist., alongside of which is a down decayed oak snag, 15 ins. diam., no marks visible.</p> <p style="padding-left: 40px;">An oak, 27 ins. diam., bears N. 56° W., 30.4 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Markham</p> <p style="padding-left: 40px;">A decayed oak snag, size indeterminate, bears N. 73 1/4° E., 33.3 ft. dist., with a healed blaze.</p>


**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

FEET

An oak, 42 ins. diam., bears N. 24 1/4° W., 48.8 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

An oak, 13 ins. diam., bears S. 2 3/4° E., 76.9 ft. dist., mkd.
T30S R4W S29 BT.

An oak, 4 ins. diam., bears S. 20° W., 5.7 ft. dist., mkd. X BT.

Bury the iron post, 32 ins. long, alongside the stainless steel post.


**Dependent Resurvey of Mineral Survey No. 805, Therodore Lode,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

Restoring the survey by C. Frank Rhodes 1919

From Corner No. 1, Therodore Lode, restored by person(s) unknown; from evidence no longer in existence; and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 15 ins. above ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron pipe, 48 ins. long, with brass cap mkd.



from which

Dependent Resurvey of Mineral Survey No. 805, Therodore Lode,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

<p>514.99</p>	<p>A fir, 5 ins. diam., bears S. 70 1/2° E., 9.3 ft. dist., mkd. X BT.</p> <p>A fir, 9 ins. diam., bears S. 31 1/4° W., 20.8 ft. dist., mkd. MS805 TL-1 BT.</p> <p>From this cor., the cor. of secs. 28, 29, 32, and 33., bears N. 2° 38' 10" E., 509.88 ft. dist., hereinbefore described.</p> <p>N. 70° 40' 02" W., on line 1-2, Therodore Lode.</p> <p>Intersect the N. and S. center line of the NE1/4 NE1/4 of sec. 32, established by Prochnau, PLS No. 1305, in 1961; perpetuated by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, projecting 32 ins. above ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron pipe, 46 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 4 W S 32 MS 805 2017</p> </div> <p>from which</p> <p>A fir, 6 ins. diam., bears S. 41 3/4° W., 11.8 ft. dist., mkd. INT MS805 BT.</p> <p>A fir, 10 ins. diam., bears N. 42 1/4° W., 15.9 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 70° 40' 02" W., beginning new measurement.</p>
<p>68.13</p>	<p>Corner No. 2, Therodore Lode, restored by person(s) unknown; from original evidence no longer in existence; reported by Prochnau, PLS No. 1305, in 1961; monumented with an iron pipe, 1 ins. diam., firmly set, with top 12 ins. below the surface of the ground (alongside of which is an iron pipe, 1 in. diam., 23 ins. long, lying loose on the ground).</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, directly over the iron pipe, 20 ins. long, with brass cap mkd.</p>


Dependent Resurvey of Mineral Survey No. 805, Theodore Lode,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

	<div data-bbox="760 300 997 512" data-label="Diagram"> <p>T 30 S R 4 W</p> <p>S 32 2</p> <p>MS 805 TL 2017</p> </div> <p>from which</p> <p>A fir, 13 ins. diam., bears S. 54 1/2° E., 45.5 ft. dist., mkd. X BT.</p> <p>A fir, 9 ins. diam., bears S. 15 1/4° W., 23.1 ft. dist., mkd. X BT.</p> <p>Buried the other iron pipe, 23 ins. long, alongside the stainless steel post.</p> <hr/> <p>S. 19° 15' 07" W., on line 2-3, Theodore Lode, beginning new measurement.</p>
1037.90	<p>Intersect the E. and W. center line of the NE 1/4 of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div data-bbox="760 1003 974 1243" data-label="Diagram"> <p>T 30 S R 4 W</p> <p>S 32 MS 805</p> <p>2017</p> </div> <p>from which</p> <p>A fir, 5 ins. diam., bears N. 72 3/4° E., 10.3 ft. dist., mkd. X BT.</p> <p>A fir, 8 ins. diam., bears N. 32 1/4° W., 15.7 ft. dist., mkd. INT MS805 BT.</p> <p>From this point, a point established by Prochnau, PLS No. 1305, in 1961, as the intersection of the E. and W. center line of the NE 1/4 and line 2-3 of the Theodore Lode; perpetuated by person(s) unknown; bears S. 60° 35' 59" E., 6.21 ft. dist., and was not utilized in the course of this survey, monumented with an iron pipe, 1 in. diam., firmly set, projecting 26 ins. above ground.</p>
1470.18	<p>Corner No. 3, Theodore Lode, perpetuated by person(s) unknown; monumented with an iron pipe, 1 in. diam., firmly set, projecting 14 ins. above ground, from which an original bearing tree</p> <p>A fir, 46 ins. diam., bears N. 3 3/4° W., 17.6 ft. dist., with a healed blaze.</p>

Dependent Resurvey of Mineral Survey No. 805, Therodore Lode,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, directly over the iron pipe, 48 ins. long, with brass cap mkd.</p> <div data-bbox="779 451 1031 703" style="text-align: center;"> <p>T 30 S R 4 W S 32 MS 805 TL 3 2017</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 51 1/4° E., 37.4 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 71° 03' 48" E., on line 3-4, Therodore Lode.</p> <p>598.16 Corner No. 4, Therodore Lode, perpetuated by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, projecting 20 ins. above ground, from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears S. 53 1/4° E., 21.0 ft. dist., with a healed blaze. (Record, bears S. 57° 20' E.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <div data-bbox="803 1291 1031 1543" style="text-align: center;"> <p>T 30 S R 4 W MS 805 TL 4 S 32 2017</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 17 1/2° W., 23.1 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 18° 39' 58" E., on line 4-1, Therodore Lode, beginning new measurement.</p> <p>633.11 Intersect the E. and W. center line of the NE 1/4 of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
--	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of Mineral Survey No. 805, Therodore Lode,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

<p>1466.15</p>	<p style="text-align: center;">T 30 S R 4 W</p>  <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 72 3/4° E., 10.3 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 32 1/4° W., 15.7 ft. dist., mkd. INT MS805 BT.</p> <p>Corner No. 1, Therodore Lode.</p> <hr/> <p style="text-align: center;">Subdivision of Section 29, T. 30 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/>
<p>2656.80</p>	<p>From the 1/4 sec. cor. of secs. 29 and 32, hereinbefore described.</p> <p>N. 2° 02' 31" W., on the N. and S. center line of sec. 29.</p> <p>Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
<p>5343.66</p>	<p style="text-align: center;">T 30 S R 4 W C 1/4 S 29 2017</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 45 3/4° E., 12.1 ft. dist., mkd. T30S R4W C1/4 S29 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 85 1/2° W., 33.8 ft. dist., mkd. X BT.</p> <p>The 1/4 sec. cor. of secs. 20 and 29, hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 29, perpetuated by Markham Jr., PE No. 2880, in 1949; subsequently perpetuated by Byron, Douglas County Deputy Surveyor, in 1963, filed as CS53/26-66; further perpetuated by Smith, PLS No. 2469, in 1997; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground (alongside of which is an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground), with a brass cap mkd.</p>

**Subdivision of Section 29,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>DOUGLAS COUNTY SURVEYORS OFFICE T 30 S R 4 W 1/4 S 29 S 28 1997</p>
	<p>from which the remains of an original bearing tree</p> <p>A decayed fir snag, 22 ins. diam., bears S. 84° W., 35.0 ft. dist., with no marks visible on partially healed blaze.</p> <p>and a bearing tree mkd. by Markham</p> <p>A fir, 28 ins. diam., bears S. 10 1/4° W., 37.5 ft. dist., with scribe marks 1/4 28 visible on bark.</p> <p>and a bearing tree mkd. by Byron</p> <p>A fir, 23 ins. diam., bears N. 0 1/4° W., 22.7 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Smith</p> <p>A fir, 8 ins. diam., bears S. 75 3/4° E., 10.6 ft. dist., with a healed double blaze.</p> <p>A fir, 15 ins. diam., bears N. 49 1/4° W., 9.2 ft. dist., with a healed blaze.</p> <p>N. 89° 50' 07" W., on the E. and W. center line of sec. 29.</p>
2534.17	The center 1/4 sec. cor. of sec. 29.
5138.14	The 1/4 sec. cor. of secs. 29 and 30.
	<hr/> <p>Subdivision of Section 31, T. 30 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/>
	<p>From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 04' 55" W., on the N. and S. center line of sec. 31.</p>
397.07	<p>The center 1/4 sec. cor. of sec. 31, established by Hoffine, PLS No. 2291, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, with an aluminum cap mkd.</p>
	<p>LONE ROCK TIMBER T 30 S R 4 W C 1/4 S 31 2013 PLS 2291</p>

Subdivision of Section 31,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>from which the bearing trees mkd. by Hoffine</p> <p>A fir, 19 ins. diam., bears N. 82° E., 46.3 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A cedar, 11 ins. diam., bears S. 24 1/4° E., 41.4 ft. dist., with scribe marks T30S R4W S31 BT visible on partially healed blaze.</p> <p>A fir, 7 ins. diam., bears S. 39° W., 19.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A fir, 8 ins. diam., bears N. 54 1/4° W., 14.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 4 W C 1/4 S 31 2017</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 04' 48" W., beginning new measurement.</p>
1335.22	<p>The center N 1/16 sec. cor. of sec. 31, established by Hoffine, PLS No. 2291, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">C N 1/16 S 31 C 2013</p> <p>from which the bearing trees marked by Hoffine</p> <p>A fir, 13 ins. diam., bears N. 67 3/4° E., 26.9 ft. dist., with a healed blaze.</p> <p>A fir stump, 15 ins. diam., bears S. 65 1/4° E., 9.9 ft. dist., with scribe marks CN 1/16 S31 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 31 C 2017</p>

**Subdivision of Section 31,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 17 1/2° W., 21.4 ft. dist., mkd. CN 1/16 S31 BT.</p> <hr style="width: 25%; margin: auto;"/> <p>N. 0° 04' 28" W., beginning new measurement.</p>
1335.44	<p>The 1/4 sec. cor. of secs. 30 and 31.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32, hereinbefore described.</p> <p>S. 85° 57' 51" W., on the E. and W. center line of sec. 31.</p>
2657.13	<p>The center 1/4 sec. cor. of sec. 31.</p> <hr style="width: 25%; margin: auto;"/> <p>S. 85° 56' 38" W., beginning new measurement.</p>
2731.08	<p>The 1/4 sec. cor. of sec. 31 only, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 31 and 32, hereinbefore described.</p> <p>S. 86° 16' 48" W., on the E. and W. center line of the NE 1/4 of sec. 31.</p>
2657.18	<p>The center N 1/16 sec. cor. of sec. 31, hereinbefore described.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 31, hereinbefore described.</p> <p>S. 86° 28' 08" W., on the E. and W. center line of the NW 1/4 of sec. 31.</p>
2730.75	<p>The N 1/16 sec. cor. of sec. 31 only, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 32, T. 30 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of sec. 32 only, on the S bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 13' 19" E., on the N. and S. center line of sec. 32.</p>
380	<p>Graveled road, 18 ft. wide, bears S. 80° E. and N. 80° W.</p>
535.43	<p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.</p>

Subdivision of Section 32,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 4 W C 1/4 S 32 2017</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 45° E., 17.6 ft. dist., mkd. C1/4 S32 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 57 1/2° E., 13.1 ft. dist., mkd. C1/4 S32 BT.</p>
1849.57	Point for the center N 1/16 sec. cor. of sec. 32. Not monumented.
3163.71	The 1/4 sec. cor. of secs. 29 and 32.
<hr/>	
	<p>From the 1/4 sec. cor. of secs. 32 and 33, hereinbefore described.</p> <p>N. 89° 33' 35" W., on the E. and W. center line of sec. 32.</p>
1188.57	Point for the center E 1/16 sec. cor. of sec. 32. Not monumented.
2514.36	The center 1/4 sec. cor. of sec. 32.
5177.46	The 1/4 sec. cor. of secs. 31 and 32.
<hr/>	
	<p>From the point for the center E 1/16 sec. cor. of sec. 32.</p> <p>N. 0° 19' 57" E., on the N. and S. center line of the NE 1/4 of sec. 32.</p>
1291.72	<p>The NE 1/16 sec. cor. of sec. 32, established by Prochnau, PLS No. 1305, in 1961; and is accepted as the cor.; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, from which the bearing trees mkd. by Prochnau</p> <p style="padding-left: 40px;">A hemlock, 34 ins. diam., bears S. 40° E., 14.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 29 ins. diam., bears S. 36° W., 27.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, 28 ins. long, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 32 2017</p> <p style="text-align: center;">_____</p>

**Subdivision of Section 32,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	N. 0° 30' 30" W., beginning new measurement.
1315.05	The E 1/16 sec. cor. of secs. 29 and 32.

	From the N 1/16 sec. cor. of secs. 32 and 33, hereinbefore described.
	N. 89° 46' 50" W., on the E. and W., center line of the NE 1/4.
305.07	Intersect line 4-1, of the Therodore Lode, MS No. 805 hereinbefore described.
516.75	Point for the C-E-NE 1/64 sec. cor. of sec. 32. Not monumented.
930.94	Intersect line 2-3, of the Therodore Lode, MS No. 805 hereinbefore described.
1330	Creek, 4.0 ft. wide, course N. 10° E.
1171.70	The NE 1/16 sec. cor. of sec. 32.

	N. 88° 35' 46" W., beginning new measurement.
1328.48	The center N 1/16 sec. cor. of sec. 32.

	From the point for the C-E-NE 1/64 sec. cor. of sec. 32.
	N. 0° 27' 31" W., on the N. and S. center line of the NE1/4 of the NE1/4 of sec. 32.
958.91	Intersect line 1-2, of the Therodore Lode, MS No. 805 hereinbefore described.
1304.99	The E-E 1/64 sec. cor. of secs. 29 and 32.

	From the point for the center N 1/16 sec. cor. of sec. 32.
	N. 89° 25' 07" W., on the E. and W. center line of the NW1/4 of sec. 32.
2668.76	The N1/16 sec. cor. of secs. 31 and 32, hereinbefore described.
