

ORIGINAL

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
SUBDIVISIONAL LINES, AND THE SUBDIVISION OF  
SECTION LINES OF SECTION 15,  
AND THE SUBDIVISION OF SECTIONS 11, 13, AND 14,  
TOWNSHIP 22 SOUTH, RANGE 7 WEST,  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON

---

EXECUTED BY

***Jeffrey O. Covington, Cadastral Surveyor***

Under Special Instructions approved April 28th, 2016,  
and Supplemental Special Instructions approved March 24th, 2017,  
which provided for the surveys included under Group No. 2824,  
and Assignment Instructions dated April 28th, 2016,  
and Supplemental Assignment Instructions dated March 24th, 2017.

***Survey commenced May 9th, 2016***

***Survey completed March 28, 2018***

# INDEX DIAGRAM

TOWNSHIP 22 SOUTH RANGE 7 WEST

	<b>34</b>						<b>9</b>
6	<b>34</b>	5	4	3	2	1	<b>8</b>
	<b>33</b>				<b>30 24</b>	<b>25</b>	<b>7</b>
7	8	9	10	<b>29</b>	11	<b>23</b>	12
				<b>29</b>	<b>36 21</b>	<b>22</b>	<b>6</b>
18	17	16	<b>35</b>	15	<b>45</b>	14	<b>20</b>
						<b>20</b>	13
						<b>28 27 19</b>	<b>18 17 4</b>
19	20	21	22	23	24		
			<b>32</b>	<b>31 31 26</b>		<b>15</b>	<b>15 17</b>
30	29	28	27	<b>26</b>	26	<b>13</b>	<b>14 16</b>
				<b>25</b>		<b>12</b>	25
						<b>11</b>	<b>10 11</b>
31	32	33	34	35	36		

Dependent Resurvey of a Portion of the Subdivision of Section Lines of Section 15 .. Pages 35-36  
 Subdivision of Section 11 ..... Pages 36-38  
 Subdivision of Section 13 ..... Pages 38-43  
 Subdivision of Section 14 ..... Pages 43-45

**T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>The following field notes are those of the dependent resurvey of a portion of the east boundary, subdivisional lines, and the subdivision of section lines of section 15, and the subdivision of sections 11, 13, and 14, Township 22 South, Range 7 West, Willamette Meridian, Oregon.</p> <p>The history of the official surveys pertaining to this survey is as follows:</p> <p>In 1855-56, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the exterior boundaries and a portion of the subdivisional lines, as shown on the official plat of survey approved February 20, 1856.</p> <p>In 1871, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines of T. 22 S., R. 6 W., as shown on the official plat of survey approved April 26, 1872.</p> <p>In 1871, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved April 26, 1872.</p> <p>In 1897, Carl S. Nicklin, U.S. Deputy Surveyor, resurveyed a portion of the subdivisional lines and surveyed the remainder of the subdivisional lines, as shown on the official plat of survey approved March 25, 1898.</p> <p>In 1897, Carl S. Nicklin, U.S. Deputy Surveyor, resurveyed a portion of the west boundary of T. 22 S., R. 6 W., as shown on the official plat of survey approved March 25, 1898.</p> <p>1964-65, Floyd A Brooks and James E. Jelley, resurveyed a portion of the south boundary and subdivisional lines and remonumented a certain original corner point, T. 21 S., R. 7 W., as shown in the official plat of survey accepted August 20, 1965.</p> <p>In 1965, John M. Jelley and Donald R. Beck, Cadastral Surveyors, dependently resurveyed a portion of the subdivisional lines and subdivided section 15, as shown on the official plat of survey accepted June 14, 1967.</p> <p>In 1968, Peter A. Peterson, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted December 30, 1970.</p> <p>In 1984, Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, dependently resurveyed a portion of the subdivisional lines and subdivided sections 23 and 35, as shown on the official plat of survey accepted May 1, 1987.</p> <p>In 1986, Boyd W. Peterson, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted December 23, 1988.</p> <p>In 1996, Bryan S. Seibold, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted June 23, 1998.</p>

## T. 22 S., R. 7 W., Willamette Meridian, Oregon

FEET

In 2012, A. Bert Skeesick, Cadastral Surveyor, retraced a portion of the north boundary, as shown on the official plat of survey accepted January 10, 2013.

The following local survey map files (M), volume and pages (Vol., pgs.), and County Surveyor files (CS), filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, official title or Professional Land Surveyor (PLS) No., and year.

Date	Name and Registration Number	File Number
1915	J.W. Cole, Deputy County Surveyor	Vol. 02, pgs. 245A-C
1956	Wilford N. Haines, PLS No. 239	M3-22
1957	Wilford N. Haines, PLS No. 239	M1-59; CS 42/309
1960	Wilford N. Haines, PLS No. 239	M11-72
1960	James W. Byron, Deputy County Surveyor	CS 52/14-3
1960	James W. Byron, Deputy County Surveyor	CS 52/14-4
1961	Milo E. Godfrey, Deputy County Surveyor	CS 52/14-119
8/1961	Milo E. Godfrey, Deputy County Surveyor	CS 49/143-66
9/1961	Milo E. Godfrey, Deputy County Surveyor	CS 49/143-75
1962	Milo E. Godfrey, Deputy County Surveyor	CS 52/14-15
1962	Milo E. Godfrey, Deputy County Surveyor	CS 52/14-96
1962	Milo E. Godfrey, Deputy County Surveyor	CS 52/14-102
1962	Milo E. Godfrey, Deputy County Surveyor	CS 52/14-104
1962	Milo E. Godfrey, Deputy County Surveyor	CS 52/14-106
1962	Milo E. Godfrey, Deputy County Surveyor	CS 52/14-107
1962	Milo E. Godfrey, Deputy County Surveyor	CS 52/14-115
1964	Wilford N. Haines, PLS No. 239	CS 51/282
1966	Douglas County Surveyor's Office	CS 54/14
1975	Douglas County Surveyor's Office	CS 57/39
1976	Douglas County Surveyor's Office	CS 59/8-17
1977	Larry E. Monrean, Deputy County Surveyor	CS 59/31-30
1978	Douglas County Surveyor's Office	CS 60/11-8
1981	Larry E. Monrean, Deputy County Surveyor	CS 61/27
1986	Donald L. Branch, PLS No. 1137	M102-29
1987	Charles W. Guile, PLS No. 472	CS 63/54
1987	John E. Hollingswirth, PLS No. 691	CS 63/62-H
1993	Ken W. Hoffine, PLS No. 2291	M117-4
1994	Ken W. Hoffine, PLS No. 2291	M119-23
1995	Les Roberts, PLS No. 1039	M121-27
2/1995	Ken W. Hoffine, PLS No. 2291	M121-43
6/1995	Ken W. Hoffine, PLS No. 2291	CS 63/161-27
1995	Randall W. Smith, PLS No. 2469	CS 64/58-3
2006	Ken W. Hoffine, PLS No. 2291	M151-22
2007	Ken W. Hoffine, PLS No. 2291	CS 65/60-54
2008	Ken W. Hoffine, PLS No. 2291	M158-38
2009	Ken W. Hoffine, PLS No. 2291	M160-18
2010	Kent Inman, PLS No. 60050	M160-64
2013	Douglas County Surveyor's Office	CS 67/38-8
2015	David A. Edwards, PLS No. 2339	CS 65/89-39

**T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET

Wilford N. Haines, PLS No. 239, perpetuated certain original corners and established local corners as described in undated field books (FB) filed in the Douglas County Surveyor's Office as FB H-102 and H-117.

Wilford N. Haines, PLS No. 239, also restored or perpetuated certain original corners and established local corners in the township at unknown dates. Haines' record for these corners were not located. Other local surveyors had recovered and utilized Haines' positions as described in these notes.

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions (2009), and the special instructions approved April, 28th, 2016, and the supplemental special instructions approved March 24, 2017, for Group No. 2824, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description. Aluminum angle irons were driven alongside each monument unless a similar marker was already in place.

Only those lines bounding Federal interest land were blazed.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The closing corner of sections 25 and 36, on the east boundary of the township:

Latitude: 43° 37' 12.93" N.      Longitude: 123° 28' 02.20" W.

**T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET

The corner of sections 25, 26, 35, and 36:

Latitude: 43° 37' 12.03" N. Longitude: 123° 29' 05.35" W.

The corner of sections 1, 2, 11, and 12:

Latitude: 43° 40' 38.88" N. Longitude: 123° 29' 12.44" W.

The corner of sections 22, 23, 26, and 27:

Latitude: 43° 38' 03.05" N. Longitude: 123° 30' 22.81" W.

The corner of sections 5, 6, 7, and 8:

Latitude: 43° 40' 42.07" N. Longitude: 123° 33' 54.65" W.

The 1/4 section corner of sections 15 and 16:

Latitude: 43° 39' 24.88" N. Longitude: 123° 31' 32.92" W.

**Dependent Resurvey of a Portion of the East Boundary,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

Restoring the 1855-56 survey by Harvey Gordon and Charles T. Gardner,  
and the 1897 resurvey by Carl S. Nicklin

Beginning at the cor. of secs. 13, 18, 19, and 24, perpetuated by Haines, PLS No. 239, under FB H-117, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the original bearing trees reported by Nicklin in 1897

A sawed fir stump, 27 ins. diam., bears N. 77° E., 24.4 ft. dist., with no marks visible on a partially opened blaze.

A sawed decayed fir stump, 38 ins. diam., bears S. 72° W., 13.2 ft. dist., with no marks visible on a partially opened blaze.

and the remains of the bearing trees mkd. by Haines

A sawed fir stump, 40 ins. diam., bears S. 66 1/4° E., 55.1 ft. dist., with illegible scribe marks visible on bark.

A fir, 27 ins. diam., bears S. 47 3/4° W., 32.3 ft. dist., with a healed blaze.

A chinquapin, 21 ins. diam., bears N. 14 1/2° W., 27.7 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the East Boundary,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 22 S</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 7 W</td><td style="padding: 0 5px;">R 6 W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 13</td><td style="padding: 0 5px;">S 18</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> <tr><td colspan="2">2016</td></tr> </table> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 27 1/2° E., 15.2 ft. dist., mkd. T22S R6W S18 BT.</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears S. 53 1/2° E., 34.9 ft. dist., mkd. T22S R6W S19 BT.</p> <p>N. 0° 20' 41" E., bet. secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>1307.75 Point for the S 1/16 sec. cor. of secs. 13 and 18, not monumented.</p> <p>2615.50 The 1/4 sec. cor. of secs. 13 and 18, perpetuated by Haines, PLS No. 239, in 1956 and under FB H-102; and further perpetuated by Smith, PLS No. 2469, in 1995; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground (alongside of which is a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>DOUGLAS COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr><td>R</td><td>T 22 S</td><td>R</td></tr> <tr><td>7</td><td>S 13   S 18</td><td>6</td></tr> <tr><td>W</td><td>1/4</td><td>W</td></tr> <tr><td colspan="3">1995</td></tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A root hole bears S. 55° E., 6.6 ft. dist., alongside of which is a decayed fallen maple trunk, size indeterminate, with a hollowed blaze.</p> <p style="margin-left: 40px;">A decayed fir stump, 55 ins. diam., bears N. 85° W., 17.8 ft. dist., with axe marks visible on bark.</p> <p>and the remains of a bearing tree mkd. by Haines</p> <p style="margin-left: 40px;">A sawed decayed fir stump, 26 ins. diam., bears N. 9° E., 23.5 ft. dist., with a healed blaze.</p>	T 22 S		R 7 W	R 6 W	S 13	S 18			S 24	S 19	2016		R	T 22 S	R	7	S 13   S 18	6	W	1/4	W	1995		
T 22 S																									
R 7 W	R 6 W																								
S 13	S 18																								
S 24	S 19																								
2016																									
R	T 22 S	R																							
7	S 13   S 18	6																							
W	1/4	W																							
1995																									

**Dependent Resurvey of a Portion of the East Boundary,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET																			
	<p>and the remains of the bearing trees mkd. by Smith</p> <p>A sawed decayed fir stump, 20 ins. diam., bears S. 54 1/2° E., 42.4 ft. dist., with a healed blaze.</p> <p>A fir, 56 ins. diam., bears S. 11 3/4° W., 24.7 ft. dist., with scribe marks 1/4 S13 BT visible on bark.</p> <p>A maple, 18 ins. diam., bears N. 41 1/2° W., 16.0 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 34' 23" E., beginning new measurement.</p>																		
2629.73	<p>The cor. of secs. 7, 12, 13, and 18, reestablished by proportionate measurement by Haines, PLS No. 239, in 1956; recovered and accepted by Godfrey, Deputy County Surveyor, in September, 1961; by the Douglas County Surveyor's Office, in 1976; by Branch, PLS No. 1137, in 1986; and by Hoffine, PLS No. 2291, in February, 1995; and is accepted as a careful and faithful reestablishment of the cor., monumented with a cross (X) chiseled in a sandstone boulder, 4 ft. x 6 ft. x 12 ins. high, from which the bearing trees mkd. by Haines as reported by the Douglas County Surveyor's Office</p> <p>A sawed fir stump, 25 ins. diam., bears N. 57 3/4° E., 18.1 ft. dist., with a healed blaze.</p> <p>A fir, 29 ins. diam., bears S. 40° W., 34.8 ft. dist., with a healed blaze.</p> <p>A fir, 27 ins. diam., bears S. 48 3/4° W., 25.0 ft. dist., with a healed blaze.</p> <p>A fir, 12 ins. diam., bears N. 45 1/2° W., 2.6 ft. dist., with a healed blaze.</p> <p>Note: the bearing trees reported by Haines on M3-22 were so out of agreement with those found by Godfrey and the Douglas County Surveyor's Office that the Douglas County Surveyor's Office wrote to Haines in a letter dated May 25, 1976, asking him about the trees. A response to the Douglas County Surveyor's Office letter was not found.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in drill hole, flush with the top of the sandstone boulder, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td></td> <td style="text-align: center;">T 22 S</td> <td></td> </tr> <tr> <td style="text-align: center;">R 7 W</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">R 6 W</td> <td></td> </tr> <tr> <td style="text-align: center;">S 12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 7</td> <td></td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; height: 5px;"></td> </tr> <tr> <td style="text-align: center;">S 13</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 18</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center;">2016</td> </tr> </table> </div> <p>from which new bearing trees</p>		T 22 S		R 7 W	R 6 W		S 12	S 7					S 13	S 18		2016		
	T 22 S																		
R 7 W	R 6 W																		
S 12	S 7																		
S 13	S 18																		
2016																			

**Dependent Resurvey of a Portion of the East Boundary,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A hemlock, 4 ins. diam., bears N. 12° E., 40.7 ft. dist., mkd. T22S R6W S7 BT.</p> <p>A fir, 9 ins. diam., bears S. 10 1/2° E., 31.6 ft. dist., mkd. T22S R6W S18 BT.</p>
	<p>N. 0° 34' 46" E., bet. secs. 7 and 12.</p>
<p>2642.22</p>	<p>The 1/4 sec. cor. of secs. 7 and 12, reestablished by Haines, PLS No. 239, in 1956, by proportionate measurement; and perpetuated by Guile, PLS No. 472 in 1987; and is accepted as a careful and faithful reestablishment of the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 11 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines</p> <p>A fir, 26 ins. diam., bears N. 45 1/2° E., 42.3 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 26 ins. diam., bears N. 73 1/4° W., 58.7 ft. dist., with a healed blaze.</p> <p>and the remaining bearing tree mkd. by Guile</p> <p>A fir, 10 ins. diam., bears N. 44 1/2° E., 8.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S 1/4 R 7 W   R 6 W S 12   S 7 2016</p> </div> <p>from which a new bearing tree</p> <p>A fir, 11 ins. diam., bears N. 40 3/4° W., 8.9 ft. dist., mkd. 1/4 S12 BT.</p>
<p>2632.06</p>	<p>N. 0° 35' 55" E., beginning new measurement.</p> <p>The cor. of secs. 1, 6, 7, and 12, reestablished by Haines, PLS No. 239, in 1956, by proportionate measurement; recovered and accepted by Branch, PLS No. 1137, in 1986; and by Roberts, PLS No. 1039, in 1995; and is accepted as a careful and faithful reestablishment of the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the bearing trees mkd. by Haines</p>

**Dependent Resurvey of a Portion of the East Boundary,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 14 ins. diam., bears N. 37 1/2° E., 17.0 ft. dist., with a healed blaze.</p> <p>A fir, 42 ins. diam., bears S. 43° E., 50.9 ft. dist., with a healed blaze.</p> <p>A fir, 49 ins. diam., bears S. 6 1/2° E., 45.6 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears S. 6 1/2° W., 14.2 ft. dist., with a healed blaze.</p> <p>Note: the bearing and distance ties to these trees do not match the Haines survey record M3-22 but all have a Haines brass washer attached.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">T 22 S</td><td></td></tr> <tr><td style="text-align: center;">R 7 W</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">R 6 W</td><td></td></tr> <tr><td style="text-align: center;">S 1</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 6</td><td></td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td style="text-align: center;">S 12</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 7</td><td></td></tr> <tr><td></td><td style="text-align: center;">2016</td><td></td></tr> </table> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 23 1/2° W., 25.0 ft. dist., mkd. T22S R7W S1 BT.</p> <p>From the cor., E., 32 ft. dist., to a dirt road, 16 ft. wide, bears N. 35° W. and S. 25° E., in a curve.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 32' 04" E., beginning new measurement.</p> <p>2630.67 The 1/4 sec. cor. of secs. 1 and 6, perpetuated by Haines, PLS No. 239, in 1956, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears S. 88° W., 14.5 ft. dist., with no marks visible.</p> <p>and the remains of the bearing trees mkd. by Haines</p> <p style="margin-left: 40px;">A sawed decayed fir stump, 28 ins. diam., bears S. 45 3/4° E., 161.3 ft. dist., with no marks visible.</p> <p style="margin-left: 40px;">A root hole bears N. 60 3/4° W., 71.0 ft. dist., alongside of which is a decayed fir snag, 24 ins. diam, with no marks visible.</p>		T 22 S		R 7 W	R 6 W		S 1	S 6					S 12	S 7			2016	
	T 22 S																		
R 7 W	R 6 W																		
S 1	S 6																		
S 12	S 7																		
	2016																		

**Dependent Resurvey of a Portion of the East Boundary,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>and the remains of the bearing trees mkd. by person(s) unknown</p> <p>A fir, 15 ins. diam., bears N. 87 1/2° E., 11.1 ft. dist., with a healed blaze.</p> <p>A root hole bears S. 71 1/2° E., 17.2 ft. dist., alongside of which is a decayed fir snag, 10 ins. diam., with illegible scribe marks visible on partially healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 32 3/4° W., 19.1 ft. dist., with a healed blaze.</p> <p>A fir, 22 ins. diam., bears N. 33 3/4° W., 13.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S 1/4 R 7 W   R 6 W S 1   S 6 2016</p> <hr style="width: 20%; margin: auto;"/> </div> <p>N. 0° 20' 24" E., beginning new measurement.</p>
2816.32	<p>The cor. of Tps. 21 and 22 S., Rgs. 6 and 7 W., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 S R 7 W   R 6 W S 36   S 31</p> <hr style="width: 20%; margin: auto;"/> <p>S 1   S 6 T 22 S 1986</p> </div> <p>from which the remains of the original bearing trees reported by Peterson in 1986</p> <p>A decayed fir stump, size indeterminate, bears N. 59° E., 37.6 ft. dist., with axe marks visible on bark.</p> <p>A cedar, 43 ins. diam., bears S. 68° W., 9.2 ft. dist., with a hollowed blaze.</p> <p>and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office in 1966</p> <p>A root hole bears N. 80° E., 23.8 ft. dist., alongside of which is a hemlock snag, 16 ins. diam., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the East Boundary,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET

A cedar, 35 ins. diam., bears S. 59 1/2° E., 29.7 ft. dist., with a healed blaze.

A hemlock, 19 ins. diam., bears N. 27° W., 12.5 ft. dist., with a healed blaze.

and a new bearing tree

A hemlock, 17 ins. diam., bears N. 45 1/2° E., 19.5 ft. dist., mkd.  
T21S R6W S31 BT.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

---

Restoring the 1855-56 survey by Harvey Gordon and Charles T. Gardner,  
the 1871 survey by William H. Byars, the 1897 survey by Carl S. Nicklin,  
the 1964-65 resurvey by Floyd A. Brooks and James E. Jelley,  
the 1965 resurvey by John M. Jelley and Donald R. Beck,  
the 1968 survey by Peter A. Peterson,  
the 1984 survey by Wayne L. Rogers and Lance J. Bishop,  
the 1986 resurvey by Boyd W. Peterson,  
and the 1996 survey by Brian S. Seibold

From the 1/4 sec. cor. of secs. 25 and 36, perpetuated by Godfrey, Deputy County Surveyor, in 1962 under CS 52/14-106, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S R 7 W

S 25

1/4 ———

S 36

1962

from which the remains of an original bearing tree

A decayed fir stump, 55 ins. diam., bears S. 19° W., 40.9 ft. dist., with a healed blaze. (Record, S. 27° W.)

and the remains of the bearing trees mkd. by Godfrey

A fir, 37 ins. diam., bears N. 56 1/4° E., 35.1 ft. dist., with a healed double blaze.

A decayed fir stump, 24 ins. diam., bears S. 39 3/4° W., 21.0 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET																									
	<p>and a new bearing tree</p> <p>A fir, 12 ins. diam., bears S. 2 1/2° E., 12.8 ft. dist., mkd. 1/4 S36 BT.</p> <p>N. 88° 05' 18" E., bet. secs. 25 and 36.</p>																								
2109.06	<p>The closing cor. of secs. 25 and 36, on the E. bdy. of the Tp., perpetuated by Byron, Deputy County Surveyor, in 1960, under CS 52/14-3; further perpetuated by Monrean, Deputy County Surveyor, in 1981; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <div data-bbox="703 667 1120 846" style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto;"> <tr> <td></td> <td></td> <td>T 22 S</td> <td></td> </tr> <tr> <td>R</td> <td>S 25</td> <td> </td> <td>R</td> </tr> <tr> <td>7</td> <td>—</td> <td></td> <td>6</td> </tr> <tr> <td>W</td> <td>S 36</td> <td> </td> <td>W</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>1960</td> <td></td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p>A root hole bears N. 71° W., 93.1 ft. dist., alongside of which is a decayed fir log, 25 ins. diam., with no marks visible.</p> <p>and the remains of the bearing trees mkd. by Monrean</p> <p>A fir, 41 ins. diam., bears S. 29 1/4° E., 38.2 ft. dist., with a healed blaze.</p> <p>A sawed decayed fir stump, 34 ins. diam., bears S. 35 3/4° W., 22.3 ft. dist., with illegible scribe marks visible on partially opened blaze.</p> <p>A fir, 32 ins. diam., bears N. 26° W., 52.7 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p>A cedar, 9 ins. diam., bears S. 77 1/4° W., 34.7 ft. dist., mkd. T22S R7W S36 BT.</p>			T 22 S		R	S 25		R	7	—		6	W	S 36		W							1960	
		T 22 S																							
R	S 25		R																						
7	—		6																						
W	S 36		W																						
		1960																							
	<hr/> <p>From the cor. of secs. 25, 26, 35, and 36, perpetuated by Haines, PLS No. 239, in 1957; further perpetuated by Hoffine, PLS No. 2291, in June 1995; monumented with an iron rod, 5/8 in. diam. firmly set, projecting 6 ins. above ground, with aluminum cap mkd. LONE ROCK TIMBER T 22 S R 7 W S 26 S 25 S 35 S 36 1994 PLS 2291, from which the remains of the original bearing trees</p> <p>A sawed decayed fir stump, 34 ins. diam., bears N. 40 1/2° E., 97.0 ft. dist., with a healed blaze. (Record, cedar, N. 45° E.)</p> <p>A fir, 54 ins. diam., bears S. 29° W., 60.7 ft. dist., with a healed blaze.</p>																								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A sawed fir stump, 51 ins. diam., bears N. 18 3/4° W., 54.7 ft. dist., with illegible scribe marks visible on a partially opened blaze. (Record, N. 12° W., 58.1 ft. dist.)</p> <p>and the remains of the bearing trees mkd. by Hoffine</p> <p>A fir, 30 ins. diam., bears N. 74 1/2° E., 7.9 ft. dist., with a healed blaze.</p> <p>A sawed decayed fir stump, 24 ins. diam., bears S. 49 3/4° E., 16.6 ft. dist., with no marks visible on a partially opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 22 S R 7 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">S 26</td> <td style="padding: 2px 10px;">S 25</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">S 35</td> <td style="padding: 2px 10px;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center;">2016</td> </tr> </table> </div> <p>from which new bearing trees</p> <p>A hemlock, 14 ins. diam., bears S. 24 1/4° E., 44.6 ft. dist., mkd. T22S R7W S36 BT.</p> <p>A hemlock, 8 ins. diam., bears N. 55 1/4° W., 27.9 ft. dist., mkd. T22S R7W S26 BT.</p> <p>N. 0° 17' 29" W., bet. secs. 25 and 26.</p> <p>1285.94 The S 1/16 sec. cor. of secs. 25 and 26, established by Haines, PLS No. 239, in 1957; and perpetuated by Douglas County Surveyor's Office, in 1978; and is accepted as the cor.; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>DOUGLAS COUNTY SURVEYOR</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 22 S R 7 W</td> </tr> <tr> <td colspan="2">S 1/16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">S 26</td> <td style="padding: 2px 10px;">S 25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1978</td> </tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Haines</p> <p>A root hole bears N. 54° E., 33.5 ft. dist., downhill of which is a fir log, 25 ins. diam., with a healed blaze.</p> <p>A fir, 30 ins. diam., bears N. 39 3/4° W., 19.0 ft. dist., with a healed blaze.</p>	T 22 S R 7 W		S 26	S 25			S 35	S 36	2016		T 22 S R 7 W		S 1/16		S 26	S 25	1978	
T 22 S R 7 W																			
S 26	S 25																		
S 35	S 36																		
2016																			
T 22 S R 7 W																			
S 1/16																			
S 26	S 25																		
1978																			

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>and the remains of a bearing tree mkd. by Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A decayed fir stump, 14 ins. diam., bears N. 79° E., 24.8 ft. dist., with illegible scribe marks visible on partially opened blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 74 1/2° E., 3.9 ft. dist., mkd. S1/16 S25 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 13' 25" W., beginning new measurement.</p>
1284.19	<p>The 1/4 sec. cor. of secs. 25 and 26, perpetuated by Haines, PLS No. 239, in 1957, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which an original bearing tree</p> <p style="padding-left: 40px;">A cedar, 54 ins. diam., bears N. 33° E., 125.4 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears N. 56° W., 17.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 7 W 1/4 S 26   S 25 2016</p> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>N. 3° 01' 22" W., beginning new measurement.</p>
1309.03	<p>The N 1/16 sec. cor. of sec. 26 only, established by Haines, PLS No. 239, in 1957, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 82° E., 26.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 28 3/4° W., 8.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p align="center">N 1/16 S 26   2018</p> <hr/>
1322.63	<p>N. 3° 03' 02" W., beginning new measurement.</p> <p>True point for the closing cor. of secs. 25 and 26, at intersection with the S. bdy. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 S R 7 W S 24</p> <hr/> <p align="center">C   C S 26   S 25 2017</p> <p>from which</p> <p>A fir, 19 ins. diam., bears S. 68 1/2° E., 19.6 ft. dist., mkd. T22S R7W S25 CC BT.</p> <p>A fir, 7 ins. diam., bears S. 41 3/4° W., 19.8 ft. dist., mkd. T22S R7W S26 CC BT.</p> <p>From this cor., a point established by person(s) unknown bears S. 59° 00' 25" W., 2.61 ft. dist., and was not utilized in the course of this survey, monumented with the original closing corner, a sandstone, 14x12x10 ins., lying loose on top of the ground, mkd. CC on one face, 1 groove on an adjacent face and 2 grooves on the other face, with a nail driven flush with the ground surface directly underneath the stone. The stone was removed and returned to its original location and the nail was removed from the area.</p> <p>From this same cor., the original closing cor. of secs. 25 and 26, perpetuated by Haines, PLS No. 239, in 1957, further perpetuated by Douglas County Surveyor's Office, in 1975, bears N. 3° 03' 02" W., 20.15 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 12 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the original bearing trees</p> <p>A sawed decayed fir stump, 35 ins. diam., bears S. 59° E., 33.0 ft. dist., with a healed blaze.</p> <p>A sawed decayed fir stump, 60 ins. diam., bears S. 78 3/4° W., 26.4 ft. dist., with illegible scribe marks visible on partially opened blaze. (Record, S. 85° W.)</p> <p>and the remains of a bearing tree mkd. by Douglas County Surveyor's Office</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed decayed fir stump, 24 ins. diam., bears S. 40° W., 57.8 ft. dist., with a healed double blaze.</p> <p>At the original closing corner</p> <p>Drive the "T" shaped iron rod, flush with the ground and add the marks AM to the original stone and bury alongside the "T" shaped iron rod.</p> <hr/> <p>From the cor. of secs. 23 and 24 only, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground (alongside of which is a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 10 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center), with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS CO. SURVEYOR T 22 S R 7 W S 23   S 24 ----- S 26 1975</p> <p>from which the remains of a bearing tree mkd. by Nicklin in 1897</p> <p>A decayed fir stump, 27 ins. diam., bears N. 31 1/2° E., 29.0 ft. dist., with no marks visible on partially opened blaze.</p> <p>and the remains of a bearing tree mkd. by Godfrey in 1962, under CS 52/14-104</p> <p>A decayed fir stump, 30 ins. diam., bears S. 23° E., 13.2 ft. dist., with a healed double blaze.</p> <p>and the remains of a bearing tree mkd. by Rogers and Bishop in 1984</p> <p>A root hole bears N. 86 3/4° W., 52.8 ft. dist., downhill of which is a maple log, size indeterminate, with a healed blaze. (Record, S. 86 3/4° W.)</p> <p>and new bearing trees</p> <p>A fir, 7 ins. diam., bears N. 9° E., 13.0 ft. dist., mkd. T22S R7W S24 BT.</p> <p>A fir, 9 ins. diam., bears N. 87 1/2° W., 17.5 ft. dist., mkd. T22S R7W S23 BT.</p> <p>N. 89° 52' 21" E., bet. secs. 24 and 26.</p>
462.62	The closing cor. of secs. 25 and 26, hereinbefore described. Continue measurement bet. secs. 24 and 25.
2629.45	The 1/4 sec. cor. of sec. 24 only, restored by Haines, PLS No. 239, date unknown; recovered and reported by Godfrey, Deputy County Surveyor, in 1962, under CS 52/14-15; perpetuated by Hoffine, PLS No. 2291, in 1990; and

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>is accepted as the best available evidence of the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 11 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines as reported by Hoffine</p> <p style="padding-left: 40px;">A fir, 45 ins. diam., bears S. 65 1/2° E., 73.6 ft. dist., with scribe marks 1/4 S BT visible on bark.</p> <p style="padding-left: 40px;">A hollowed decayed fir snag, 22 ins. diam., bears N. 31° W., 21.7 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree tagged by Hoffine</p> <p style="padding-left: 40px;">A decayed fir snag, 14 ins. diam., bears N. 60 3/4° E., 11.9 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 7 W 1/4 S 24 <hr style="width: 50px; margin: 0 auto;"/>2016</p> </div> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 26° W., 13.9 ft. dist., mkd. 1/4 S24 BT.</p> <hr style="width: 200px; margin: 10px auto;"/> <p>N. 89° 51' 44" E., beginning new measurement.</p> <p>464.42 Point for the 1/4 sec. cor. of sec. 25 only, determined at proportionate distance, on the S. bdy. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 7 W <hr style="width: 50px; margin: 0 auto;"/>1/4 S 25 2016</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 47° E., 39.9 ft. dist., mkd. 1/4 S25 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 13° W., 57.7 ft. dist., mkd. X BT.</p> <p>Corner is located 15 ft. east of a creek, 3 ft. wide, course N. 65° W.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

<p>FEET 2628.62</p>	<p>The closing cor. of secs. 24 and 25, on the E. bdy. of the Tp., perpetuated by Haines, PLS No. 239, date unknown, recorded and further perpetuated by Godfrey, Deputy County Surveyor, in August 1961, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 9 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which an original bearing tree</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears S. 77° W., 30.4 ft. dist., with a healed blaze. (Record, S. 68° W.)</p> <p>and the bearing trees mkd. by Godfrey</p> <p style="padding-left: 40px;">A cedar, 27 ins. diam., bears N. 9 1/2° E., 26.2 ft. dist., with illegible scribe marks visible on partially opened blaze.</p> <p style="padding-left: 40px;">A maple, 14 ins. diam., bears S. 42° E., 12.6 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, supported in a mound of stone, 3 ft. base, to the top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <pre>       T 22 S     R 7 W  R 6 W       S 24                     S 25   S 30                       2016           </pre> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears N. 21 1/2° W., 19.0 ft. dist., mkd. T22S R7W CC S24 BT.</p> <p>Bury the iron rod, 30 ins. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp.</p> <p>S. 85° 58' 35" W., bet. secs. 13 and 24.</p>
<p>1180.68</p>	<p>The E 1/16 sec. cor. of secs. 13 and 24, established by Hoffine, PLS No. 2291, in 2009, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd. LONE ROCK TIMBER E 1/16 S 13 S 24 2009 PLS 2291, from which the remains of the bearing trees mkd. by Haines, PLS. No. 239, under FB H-117, reported by Hoffine</p> <p style="padding-left: 40px;">A sawed decayed hemlock, 23 ins. diam., bears S. 17 1/2° W., 25.2 ft. dist., with illegible scribe marks visible on partially opened blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 51 ins. diam., bears N. 41 1/4° W., 17.1 ft. dist., with no marks visible.</p> <p>and the remains of the bearing trees mkd. by Hoffine</p> <p>A fir, 21 ins. diam., bears N. 47 3/4° E., 12.4 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 14 ins. diam., bears S. 27° W., 9.9 ft. dist., with scribe marks E1/16 S24 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 13 E 1/16 ——— S 24 2016</p> </div> <p>and a new reference monument</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 26 ins. in the ground for a reference monument, bears S. 43° 27' 29" E., 10.00 ft. dist., with aluminum cap mkd. RM E 1/16 S24 10.0 FT TO COR 2016, and an arrow pointing to the cor.</p> <p>Note: Hoffine reports that Haines established a position for this cor. at an unknown date. Haines' bearing trees were recovered, as referenced by Hoffine, but the "T" shaped iron rod was not found.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 85° 57' 56" W., beginning new measurement.</p>
1180.14	<p>The 1/4 sec. cor. of secs. 13 and 24, perpetuated by Haines, PLS No. 239, under FB H-117, from original evidence no longer in existence; further perpetuated by Hoffine, PLS No. 2291, in 1994; and perpetuated by person(s) unknown as reported by Hoffine in 2009; monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 7 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines</p> <p>A sawed decayed fir stump, 31 ins. diam., bears N. 22 3/4° E., 68.2 ft. dist., with a healed blaze.</p> <p>A sawed decayed fir stump, 30 ins. diam., bears S. 38 1/4° W., 59.7 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Hoffine in 1994</p> <p>A fir, 19 ins. diam., bears S. 79 1/4° E., 38.0 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET							
	<p>and a bearing tree mkd. by person(s) unknown, reported by Hoffine in 2009</p> <p>A hemlock, 20 ins. diam., bears N. 84 1/2° W., 38.5 ft. dist., with scribe marks 1/4 S13 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 7 W</p> <p>S 13</p> <p>1/4 _____</p> <p>S 24</p> <p>2016</p> <hr style="width: 20%; margin: 0 auto;"/> </div> <p>N. 89° 30' 48" W., beginning new measurement.</p>						
1310.08	Point for the W 1/16 sec. cor. of secs. 13 and 24, not monumented.						
2620.16	<p>The cor. of secs. 13, 14, 23, and 24, perpetuated by Haines, PLS No. 239, date unknown, and further perpetuated by Godfrey, Deputy County Surveyor, in 1962, under CS 52/14-107, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 2 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of an original bearing tree</p> <p>A fir, 66 ins. diam., bears N. 48° E., 9.2 ft. dist., with scribe marks T22S R7W S13 363 BT, reported by Godfrey to have been rescribed on the bark by Haines.</p> <p>and a bearing tree mkd. by Haines</p> <p>A fir, 23 ins. diam., bears S. 74 1/4° W., 17.9 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Godfrey</p> <p>A fir, 24 ins. diam., bears S. 17 3/4° E., 12.1 ft. dist., with a healed blaze.</p> <p>A fir, 15 ins. diam., bears N. 78 3/4° W., 23.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 34 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 7 W</p> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2016</td> </tr> </table> <hr style="width: 20%; margin: 0 auto;"/> </div>	S 14	S 13	S 23	S 24	2016	
S 14	S 13						
S 23	S 24						
2016							

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1262.55	<p>N. 2° 09' 58" W., bet. secs. 13 and 14.</p> <p>The S 1/16 sec. cor. of secs. 13 and 14, established by Hoffine, PLS No. 2291, in 1994, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. LONE ROCK TIMBER S 1/16 S 13 S 14 1993 PLS 2291, from which the remains of a bearing tree mkd. by Haines, date unknown, as reported by Hoffine</p> <p>A decayed fir stump, 12 ins. diam., bears N. 28 1/4° W., 9.3 ft. dist., with axe marks visible.</p> <p>and the bearing tree mkd. by Hoffine</p> <p>A fir, 27 ins. diam., bears S. 30° E., 38.7 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <p align="center">S 1/16 S 14   S 13 2016</p> <p>and a new bearing tree</p> <p>An alder, 6 ins. diam., bears N. 84 1/2° W., 11.2 ft. dist., mkd. S1/16 S14 BT.</p> <p>Note: Hoffine reports that Haines established a position for this cor. at an unknown date.</p> <hr/>
1261.23	<p>N. 2° 10' 09" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 13 and 14, perpetuated by Cole, Deputy County Surveyor, in 1915; further perpetuated by Haines, PLS No. 239, date unknown, as reported and further perpetuated by Godfrey, Deputy County Surveyor, in 1961, under CS 52/14-119; and perpetuated by Hoffine, PLS No. 2291, in 1993, from original evidence no longer in existence; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE T 22 S 1/4 S 14   S 13 R 7 W 1961</p> <p>from which the remains of the bearing tree mkd. by Haines, reported by Godfrey</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed fir stump, 30 ins. diam., bears N. 10 1/4° E., 41.6 ft. dist., with axe marks visible.</p> <p>and a bearing tree mkd. by Haines, reported by Hoffine</p> <p>A fir, 44 ins. diam., bears N. 42 3/4° W., 125.6 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Godfrey</p> <p>A cedar, 29 ins. diam., bears S. 78 3/4° W., 29.7 ft. dist., with a healed blaze.</p> <p>and a bearing tree by Hoffine</p> <p>A root hole bears N. 44 1/4° E., 12.3 ft. dist., alongside of which is a down fir log, 14 ins. diam., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 12 ins. diam., bears S. 19 1/4° E., 48.0 ft. dist., mkd. 1/4 S13 BT.</p> <hr/> <p>N. 0° 53' 29" W., beginning new measurement.</p>
1414.93	Point for the N 1/16 sec. cor. of secs. 13 and 14, not monumented.
2710	A dirt road, 8 ft. wide, bears N. 45° E. and S. 50° W.
2829.86	<p>The cor. of secs. 11, 12, 13, and 14, reestablished by Haines, PLS No. 239, in 1956, from topography calls in the original field notes, and is accepted as a careful and faithful reestablishment of the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines</p> <p>A decayed fir stump, 24 ins. diam., bears N. 72 1/2° E., 22.2 ft. dist., with no marks visible.</p> <p>A decayed fir snag, 14 ins. diam., bears S. 27 1/4° E., 23.4 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p>
	<p>T 22 S R 7 W S 11   S 12 ----- S 14   S 13 2016</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>from which new bearing trees</p> <p>A fir, 9 ins. diam., bears N. 68 1/2° E., 48.5 ft. dist., mkd. T22S R7W S12 BT.</p> <p>A fir, 11 ins. diam., bears S. 54° E., 14.9 ft. dist., mkd. T22S R7W S13 BT.</p> <p>A fir, 7 ins. diam., bears S. 23° W., 16.3 ft. dist., mkd. T22S R7W S14 BT.</p> <p>An alder, 28 ins. diam., bears N. 25° W., 31.2 ft. dist., mkd. T22S R7W S11 BT.</p> <p>From this cor., W., 265 ft. dist., to Elk Creek, 40 ft. wide, course S. 50° W.</p> <hr/>
2579.72	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp. S. 89° 36' 23" W., bet. secs. 12 and 13.</p> <p>The 1/4 sec. cor. of secs. 12 and 13, reestablished by Haines, PLS No. 239, in 1956, by proportionate measurement, perpetuated by the Douglas County Surveyor's Office in 2013, and is accepted as a careful and faithful reestablishment of the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., 36 ins. long, firmly set, projecting 9 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines</p> <p>A sawed decayed fir stump, 12 ins. diam., bears N. 31° E., 7.0 ft. dist., with a healed blaze.</p> <p>A sawed decayed fir stump, 26 ins. diam., bears S. 63 1/4° W., 5.5 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Douglas County Surveyor's Office</p> <p>A fir, 7 ins. diam., bears N. 73 1/2° E., 10.0 ft. dist., with scribe marks S BT visible on partially healed double blaze.</p> <p>A fir, 9 ins. diam., bears S. 0 3/4° W., 6.0 ft. dist., with illegible scribe marks visible on partially healed double blaze.</p> <p>A fir, 8 ins. diam., bears S. 89 3/4° W., 24.6 ft. dist., with scribe marks 1/4 S12 CS BT visible on partially healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	T 22 S R 7 W S 12 1/4 ——— S 13 2016  _____
	S. 89° 34' 02" W., beginning new measurement.
1287.88	Point for the W 1/16 sec. cor. of secs. 12 and 13, not monumented.
2265	A dirt road, 8 ft. wide, bears E. and S. 80° W.
2575.76	The cor. of secs. 11, 12, 13, and 14.  _____
	N. 0° 54' 51" W., bet. secs. 11 and 12.
160	Elk Creek, 80 ft. wide, course S. 50° W.
2539.34	The 1/4 sec. cor. of secs. 11 and 12, reestablished by Haines, PLS No. 239, in 1956; and perpetuated by Hoffine, PLS No. 2291, in 1994; and is accepted as a careful and faithful reestablishment of the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 13 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the accessories mkd. by Haines  A burnt, sawed fir stump, 32 ins. diam., bears N. 52 1/4° E., 47.5 ft. dist., with scribe marks 1/4 BT visible on bark.  A boulder, 4 x 4 ft., projecting 4 ft. above ground, bears S. 82° W., 14.2 ft. dist., mkd. with a cross (X) chiseled on the east face.  A boulder, 6 x 6 ft., projecting 6 ft. above ground, bears S. 45 1/4° W., 5.0 ft. dist., mkd. with a cross (X) chiseled on the NE face.  and a bearing tree mkd. by Hoffine  A fir, 9 ins. diam., bears S. 26 1/2° E., 8.4 ft. dist., with a healed blaze.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.  T 22 S R 7 W 1/4 S 11   S 12 2016  _____
	N. 0° 44' 58" W., beginning new measurement.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET 2537.26	<p>The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE T 22 S R 7 W S 2   S 1 ----- S 11   S 12 1962</p> <p>from which the remains of the original bearing trees reported by Peterson in 1986</p> <p style="padding-left: 40px;">A cedar, 45 ins. diam., bears N. 60° E., 24.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 50 ins. diam., bears S. 25° W., 9.9 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by Godfrey, Deputy County Surveyor, in 1962, under CA 52/14-102</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 76° E., 34.3 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 39° E., 33.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A root hole bears S. 85 3/4° W., 27.7 ft. dist., alongside of which is a fir log, 14 ins. diam., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. 59 3/4° W., 42.9 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 39° W., 59.6 ft. dist., mkd. T22S R7W S11 BT.</p> <p>From this cor., a point established as the cor. of secs. 1, 2, 11, and 12, by Haines, PLS No. 239, in 1956, as rejected by Peterson, bears N. 76° 56' W., 3.6 ft. dist., and is not utilized in the course of this survey, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12 on the E. bdy. of the Tp. S. 87° 27' 05" W., bet. secs. 1 and 12.</p>
1321.81	<p>Point for the E 1/16 sec. cor. of secs. 1 and 12. Not monumented.</p> <p>From this cor., a point erroneously established as the E 1/16 sec. cor. of secs. 1 and 12, by Haines, PLS No. 239, in 1956, bears N. 7° 20' 44" W., 8.05 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set,</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>projecting 4 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center. This point was not correctly positioned and was not utilized for control in this survey, from which the remains of the bearing trees mkd. by Haines</p> <p>A root hole bears N. 15 1/4° E., 14.6 ft. dist., alongside of which is a fir log, 39 ins. diam, with a healed blaze.</p> <p>A sawed decayed fir stump, 42 ins. diam., bears S. 54° E., 16.2 ft. dist., with axe marks visible.</p>
2643.62	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 S R 7 W S 1 1/4 ——— S 12 2016</p> <p>from which</p> <p>A fir, 10 ins. diam., bears S. 63° W., 44.9 ft. dist., mkd. 1/4 S12 BT.</p> <p>A fir, 9 ins. diam., bears N. 26 1/4° W., 7.9 ft. dist., mkd. 1/4 S1 BT.</p> <p>Note: No evidence of the local 1/4 sec. cor. of secs. 1 and 12, reestablished by Haines, PLS No. 239, in 1956, was found.</p>
5287.24	<p>The sec. cor. of secs. 1, 2, 11, and 12.</p> <hr/> <p>From the cor. of secs. 27 and 34 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with brass cap mkd. (record, aluminum post and cap)</p> <p align="center">T 22 S R 7 W S 27   —————  S 26 S 34   1984</p> <p>from which the bearing trees mkd. by Haines, PLS No. 239, in 1957, reported by Rogers and Bishop in 1984</p> <p>A fir, 36 ins. diam., bears S. 76 1/2° W., 29.7 ft. dist., with a healed blaze.</p> <p>A fir, 23 ins. diam., bears N. 57 3/4° W., 26.4 ft. dist., with a healed blaze. (Record, N. 53 1/4° W.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1022.28	<p>N. 0° 12' 18" W., bet. secs. 26 and 27.</p> <p>From this point, a point established as the S 1/16 sec. cor. of sec. 26 only by Haines, PLS No. 239, in 1957, bears East, 1.41 ft. dist., and is not utilized in the course of this survey, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 9 ins. above ground, with no brass washer, from which the remains of the bearing trees mkd. by Haines, reported by Rogers and Bishop in 1984</p> <p>A sawed decayed fir stump, size indeterminate, bears N. 85° E., 10.9 ft. dist., with a healed blaze.</p> <p>A sawed decayed fir stump, size indeterminate, bears N. 45° W., 21.1 ft. dist., with no marks visible on partially opened blaze.</p>
2414.89	<p>The 1/4 sec. cor. of secs. 26 and 27, perpetuated by Hoffine, PLS No. 2291, in 2007, monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 7 W 1/4 S 27   S 26 1984</p> <p>from which the bearing tree mkd. by Haines, PLS No. 239, in 1957, reported by Rogers and Bishop in 1984</p> <p>A fir, 62 ins. diam., bears N. 73° W., 103.0 ft. dist., with illegible scribe marks visible on bark.</p> <p>and the bearing trees mkd. by Hoffine</p> <p>A fir snag, 19 ins. diam., bears S. 23 1/4° W., 45.8 ft. dist., with a healed blaze.</p> <p>A fir, 23 ins. diam., bears N. 53° W., 22.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 9 ins. diam., bears N. 50 1/2° E., 31.5 ft. dist., mkd. 1/4 S 26 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 08' 44" W., beginning new measurement.</p>
2502.32	<p>The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground (alongside of which is an iron rod, 1 1/2 ins. diam., firmly set, projecting 3 ins. above ground, and a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 5 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center), with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET									
	<table border="1"> <tr> <td>T 22 S</td> <td>R 7 W</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td colspan="2">1965</td> </tr> </table>	T 22 S	R 7 W	S 22	S 23	S 27	S 26	1965	
T 22 S	R 7 W								
S 22	S 23								
S 27	S 26								
1965									
	<p>from which the remains of the bearing trees mkd. by Nicklin in 1897, reported by Rogers and Bishop in 1984</p> <p>A burned fir stump, 18 ins. diam., bears N. 28° E., 25.1 ft. dist., no marks visible.</p> <p>A decayed burned stump, size indeterminate, bears S. 21° W., 26.4 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Byron, Deputy County Surveyor, in 1960, under CS 52/14-4</p> <p>A fir, 32 ins. diam., bears N. 19° E., 100.3 ft. dist., with a healed blaze.</p> <p>A fir stump, 52 ins. diam., bears S. 34° W., 40.9 ft. dist., with illegible scribe marks visible on partially opened blaze.</p> <p>and the bearing trees mkd. by Jelley and Beck in 1965, reported by Rogers and Bishop in 1984</p> <p>A cedar, 28 ins. diam., bears S. 43° W., 51.5 ft. dist., with a healed blaze.</p> <p>A fir, 32 ins. diam., bears N. 26° W., 103.6 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 6 ins. diam., bears S. 67 1/4° E., 20.0 ft. dist., mkd. X BT.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89° 57' 30" W., bet. secs. 14 and 23.</p>								
1358.85	<p>The E 1/16 sec. cor. of secs. 14 and 23, established by Haines, PLS No. 239, date unknown, perpetuated by Hoffine, PLS No. 2291, in 1993, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines</p> <p>A fir, 54 ins. diam., bears S. 17° E., 91.6 ft. dist., with a healed blaze.</p> <p>A root hole bears N. 49 1/2° W., 95.0 ft. dist., uphill of which is a downed decayed cedar snag, 88 ins. diam, with no marks visible.</p>								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>and a bearing tree mkd. by Hoffine</p> <p>A fir, 36 ins. diam., bears S. 39 1/4° E., 11.5 ft. dist., with no marks visible.</p> <p>at the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <p align="center">S 14 E 1/16 ——— S 23 2016</p> <p>and a new bearing tree</p> <p>A fir, 15 ins. diam., bears N. 54 3/4° E., 9.0 ft. dist., mkd. E 1/16 S 14 BT.</p> <hr/> <p>S. 89° 52' 11" W., beginning new measurement.</p>
1357.35	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground (alongside of which is a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 12 ins. above ground, with brass washer mkd. WILFORD N. HAINES SURVEY 239 DRAIN, ORE., with a tack in center), with brass cap mkd.</p> <p align="center">T 22 S R 7 W S 14 1/4 ——— S 23 1965</p> <p>from which the remains of an original bearing tree reported by Jelley and Beck in 1965</p> <p>A sawed decayed fir stump, 67 ins. diam., bears N. 31° E., 54.8 ft. dist., with scribe marks BT visible on bark.</p> <p>and the remains of the bearing tree mkd. by Cole, Deputy County Surveyor, in 1915</p> <p>A root hole bears S. 41 3/4° E., 99.0 ft. dist., alongside of which is a down decayed oak log, size indeterminate, with no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 7 ins. diam., bears N. 7 1/4° E., 12.6 ft. dist., mkd. 1/4 S14 BT.</p> <p>A fir, 6 ins. diam., bears S. 81° W., 14.2 ft. dist., mkd. 1/4 S23 BT.</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET									
	<p>From the cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 1/2 ins. diam, firmly set, with top flush with the surface of the ground (alongside of which is a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 1 in. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center), with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 22 S</td><td>R 7 W</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td>S 15</td><td>S 14</td></tr> <tr><td colspan="2">1965</td></tr> </table> </div> <p>from which the bearing tree mkd. by Haines, PLS No. 239, in 1960</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S. 74° W., 2.0 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Jelley and Beck in 1965</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 44° E., 46.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 63 1/2° W., 29.7 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 26 3/4° E., 36.5 ft. dist., mkd. T22S R7W S11 BT.</p> <p>Corner is located alongside the SW BT.</p> <p>N. 1° 27' 19" W., bet. secs. 10 and 11.</p>	T 22 S	R 7 W	S 10	S 11	S 15	S 14	1965	
T 22 S	R 7 W								
S 10	S 11								
S 15	S 14								
1965									
2660.73	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground (alongside of which is a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center), with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 22 S</td><td>R 7 W</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td colspan="2">1965</td></tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Haines, PLS No. 239, in 1960, reported by Jelley and Beck in 1965</p> <p style="padding-left: 40px;">A decayed fir stump, 18 ins. diam., bears S. 12 1/4° E., 11.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 52° W., 4.0 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p>	T 22 S	R 7 W	1/4		S 10	S 11	1965	
T 22 S	R 7 W								
1/4									
S 10	S 11								
1965									

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2679.74	<p>A fir, 12 ins. diam., bears S. 20 1/2° E., 19.0 ft. dist., mkd. 1/4 S11 BT.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 87° 18' 27" W., bet. secs. 2 and 11.</p> <p>The true point for the 1/4 sec. cor. of secs. 2 and 11, reestablished by Haines, PLS No. 239, in 1960, by proportionate measurement, and perpetuated by Monrean, Deputy County Surveyor, in 1977, and is accepted as a careful and faithful reestablishment of the cor., located in a dirt road; there is no remaining evidence of the T iron set by Haines. Determined at the record bearing and distance from the witness cor. established by Monrean, from which the bearing trees mkd. by Haines</p> <p>A maple, 18 ins. diam., bears N. 24 1/2° E., 42.7 ft. dist., with a healed blaze.</p> <p>A cedar, 40 ins. diam., bears S. 15° E., 45.8 ft. dist., with a healed blaze.</p> <p>From the true point, the off-line witness cor. for the 1/4 sec. cor. of secs. 2 and 11, established by Monrean, bears West, 17.00 ft. dist., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p align="center">DOUGLAS COUNTY SURVEYOR T 22 S R 7 W WIT. COR. EAST 17.0 FT TO S 2 1/4 ——— S 11 1977</p> <p>from which accessories mkd. by Monrean</p> <p>A fir, 38 ins. diam., bears N. 27 3/4° E., 15.0 ft. dist., with a healed blaze.</p> <p>A boulder on the cut bank on the NW edge of the same dirt road, with exposed face 3 ft. wide, 18 ins. tall, bears S. 76 1/2° W., 9.8 ft. dist., mkd. with a cross (X) chiseled on the exposed east face.</p> <p>The witness cor. is located W., 24 ft. dist., from the center of the same dirt road.</p> <p>Note: Haines' reestablished position was verified using his record and the survey by Jelley and Beck in 1965.</p> <hr/> <p>From the sec. cor. of secs. 22, 23, 26, and 27.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	N. 85° 33' 28" W., bet. secs. 22 and 27.
1095.39	A private lot cor., established by Hoffine, PLS No. 2291, in 2008, monumented with an iron rod, 5/8 in. diam., firmly set, top flush with the surface of the ground, with a yellow plastic cap mkd., LONE ROCK TIMBER LS 2291.
1293.88	The E 1/16 sec. cor. of secs. 22 and 27, established by Hoffine, PLS No. 2291, in 2006, and is accepted as the cor., monumented with and iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd.
	<p align="center">LONE ROCK TIMBER S 22 E 1/16 <u>        </u> S 27 2006 PLS 2291</p>
	<p>from which bearing trees mkd. by Hoffine</p> <p>A fir, 23 ins. diam., bears S. 4° E., 11.7 ft. dist., with a healed blaze.</p> <p>A fir, 13 ins. diam., bears N. 59 1/4° W., 12.9 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <hr/>
	N. 85° 33' 28" W., beginning new measurement.
1293.81	<p>The 1/4 sec. cor. of secs. 22 and 27, reestablished by Hoffine, PLS No. 2291, in 2006, by proportionate measurement and is accepted as a careful and faithful reestablishment of the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. LONE ROCK TIMBER T 22 S R 7 W 1/4 S 22 S 27 2006 PLS 2291, from which bearing trees mkd. by Hoffine</p> <p>A sawed fir stump, 21 ins. diam., bears N. 58 3/4° E., 40.9 ft. dist., with a healed blaze.</p> <p>A fir, 14 ins. diam., bears S. 19 3/4° E., 55.4 ft. dist., with a healed blaze.</p> <p>A tin capped sawed fir stump, 30 ins. diam., bears S. 82 1/2° W., 58.2 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 26 ins. diam., bears N. 8 1/4° W., 19.0 ft. dist., with scribe marks T22S R7W S22 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the iron rod, 30 ins. long, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon


FEET	<p style="text-align: center;">T 22 S R 7 W S 22 1/4 ——— S 27 2016</p> <p>No new bearing trees available in sec. 22.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 85° 32' 57" W., beginning new measurement.</p>
2587.62	<p>The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting, 2 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 7 W S 21   S 22 ————— S 28   S 27 1996</p> <p>from which the remains of the original bearing trees reported by Seibold in 1996</p> <ul style="list-style-type: none"> <li>A sawed fir stump, 44 ins. diam., bears N. 27° E., 16.5 ft. dist., with a healed blaze.</li> <li>A sawed fir stump, 44 ins. diam., bears N. 10° W., 8.6 ft. dist., with a healed blaze.</li> </ul> <p>and the remains of the bearing trees mkd. by Godfrey, Deputy County Surveyor, in 1962 under CS 52/14-115</p> <ul style="list-style-type: none"> <li>A fir snag, 9 ins. diam., bears S. 62 3/4° E., 26.1 ft. dist., with a healed double blaze.</li> <li>A fir snag, 10 ins. diam., bears S. 3 1/2° W., 21.5 ft. dist., with a healed double blaze.</li> </ul> <p>and new accessories</p> <ul style="list-style-type: none"> <li>An iron rod, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground for a reference monument, bears N. 47° 43' 39" E, 6.00 ft. dist., with an aluminum cap mkd. RM T22S R7W S22 6.00 FT TO COR 2016, and an arrow pointing to the cor.</li> <li>A fir, 8 ins. diam., bears S. 59 1/2° E., 40.2 ft. dist., mkd. T22S R7W S27 BT.</li> <li>An iron rod, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears S. 38° 17' 21" W, 5.00 ft. dist., with an aluminum cap mkd. RM T22S R7W S28 5.00 FT TO COR 2016, and an arrow pointing to the cor.</li> </ul>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET

An iron rod, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears N. 63° 50' 43" W, 10.00 ft. dist., with an aluminum cap mkd. RM T22S R7W S21 10.00 FT TO COR 2016, and an arrow pointing to the cor.

From the cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.



from which the remains of the original bearing trees reported by Peterson in 1968

A sawed decayed fir stump, 48 ins. diam., bears S. 52° E., 92.4 ft. dist., with axe marks visible on bark.

A sawed decayed fir stump, 36 ins. diam., bears S. 16 1/4° W., 22.4 ft. dist., with axe marks visible over a healed blaze. (Record, S. 10° W.)

and the remains of the bearing trees mkd. by Godfrey, Deputy County Surveyor, in 1962 under CA 52/14-96

A sawed burnt fir stump, 20 ins. diam., bears N. 40° E., 26.4 ft. dist., with axe marks visible.

A burnt decayed fir stump, 14 ins. diam., bears S. 70° E., 21.8 ft. dist., no marks visible.

A decayed hemlock stump, size indeterminate, bears N. 17° W., 37.6 ft. dist., with no marks visible.

and the remains of a bearing tree mkd. by Peterson

A root hole bears N. 62° E., 42.2 ft. dist., alongside of which is a partially uprooted fir trunk, 17 ins. diam., with a healed blaze.

and the remains of the bearing trees mkd. by person(s) unknown

A fir, 18 ins. diam., bears N. 75 1/4° E., 14.3 ft. dist., with a healed blaze.

A fir, 16 ins. diam., bears S. 66 1/2° E., 31.9 ft. dist., with a healed blaze.

A fir, 15 ins. diam., bears S. 83° W., 15.2 ft. dist., with a double healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2722.11	<p>A sawed fir stump, 12 ins. diam., bears N. 26° W., 13.0 ft. dist., with a double healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 4 ins. diam., bears N. 53 1/4° W., 79.8 ft. dist., mkd. X BT.</p> <p>N. 2° 44' 07" E., bet. secs. 5 and 6.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6, determined at proportionate measurement; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 7 W 1/4 S 6   S 5 2016</p> </div> <p>from which</p> <p>A fir, 8 ins. diam., bears N. 28 1/4° E., 20.4 ft. dist., mkd. 1/4 S5 BT.</p> <p>A fir, 9 ins. diam., bears N. 17 1/4° W., 6.1 ft. dist., mkd. 1/4 S6 BT.</p>
5458.50	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 S R 7 W S 31   S 32 ----- S 6   S 5 T 22 S 1964</p> </div> <p>from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964-65, reported by Skeesick in 2012</p> <p>A fir, 19 ins. diam., bears N. 63 1/2° E., 12.3 ft. dist., with a healed blaze.</p> <p>A fir, 22 ins. diam., bears S. 73° E., 13.9 ft. dist., with a healed blaze.</p> <p>A sawed decayed fir stump, 13 ins. diam., bears S. 36 3/4° W., 10.9 ft. dist., with a healed blaze.</p> <p>A fir, 43 ins. diam., bears N. 5° W., 26.4 ft. dist., with a healed blaze with a cable scar at the base of the tree.</p> <p>and a bearing tree mkd. by Skeesick</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 5 ins. diam., bears S. 74 1/4° W., 28.6 ft. dist., with a double healed blaze.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Subdivision of Section Lines of Section 15, T. 22 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p style="text-align: center;">Restoring the 1965 survey by John M. Jelley and Donald R. Beck</p> <hr/> <p>From the center west 1/16 sec. cor. of sec. 15, perpetuated by Edwards, PLS No. 2339, in 2015, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 15 \\ 1965 \end{array}</math> </div> <p>from which the remains of the bearing trees mkd. by Jelley and Beck in 1965</p> <p style="padding-left: 40px;">A sawed fir stump, 23 ins. diam., bears N. 70/2° E., 37.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 78 1/2° W., 20.8 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Edwards</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 19 1/2° E., 27.8 ft. dist., with scribe marks CW 1/16 S15 BT visible on partially opened blaze.</p> <p>N. 87° 05' 29" W., on the E. and W. center line of sec. 15.</p> <p>1309.81 The 1/4 sec. cor. of secs. 15 and 16, perpetuated by Inman, PLS No. 60050, in 2010, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{T } 22 \text{ S } \text{ R } 7 \text{ W} \\ 1/4 \\ \text{S } 16 \text{   } \text{S } 15 \\ 1965 \end{array}</math> </div> <p>from which the remains of an original bearing tree reported by Jelley and Beck in 1965</p> <p style="padding-left: 40px;">A decayed fir stump, 14 ins. diam., bears N. 38° W., 23.1 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by Jelley and Beck</p>
------	--

**Dependent Resurvey of a Portion of  
the Subdivision of Section Lines of Section 15,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>A fir, 35 ins. diam., bears N. 68° E., 36.3 ft. dist., with a healed blaze. and an accessory by Inman</p> <p>An iron rod, 5/8 in. diam., firmly set, with top flush with the surface of the ground, for a reference monument, bears N. 39° 00' 49" W, 20.92 ft. dist., with orange plastic cap mkd. INMAN 60050 LS. and a new bearing tree</p> <p>A maple, 12 ins. diam., bears S. 89° W., 28.2 ft. dist., mkd. 1/4 S16 BT.</p> <hr/> <p>From the SW 1/16 sec. cor. of sec. 15, perpetuated by Inman, PLS No. 60050, in 2010, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 15 1965</p> <p>from which the remains of a bearing tree mkd. by Jelley and Beck in 1965</p> <p>A sawed fir stump, 30 ins. diam., bears S. 15° E., 29.4 ft. dist., with a healed blaze. and the remains of a bearing tree mkd. by Inman</p> <p>A root hole bears N. 75 1/2° E., 28.6 ft. dist., alongside of which is a fir snag, 11 ins. diam., with a healed blaze. and new bearing trees</p> <p>A fir, 15 ins. diam., bears N. 25° E., 35.8 ft. dist., mkd. SW 1/16 S15 BT. A maple, 16 ins. diam., bears S. 75 3/4° E., 15.1 ft. dist., mkd. SW 1/16 S15 BT.</p> <p>N. 0° 30' 04" W., on the N. and S. center line of the SW 1/4 of sec. 15.</p> <p>1262.26 The center W 1/16 sec. cor. of sec. 15.</p> <hr/> <p style="text-align: center;"><b>Subdivision of section 11, T. 22 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p>
------	--

Subdivision of Section 11,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T 22 S R 7 W S 11 1/4 _____ S 14 1965</p> <p>from which the bearing trees mkd. by Haines, PLS No. 239, in 1960, reported by Jelley and Beck in 1965</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears S. 42° W., 17.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 6 3/4° W., 28.4 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Jelley and Beck</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 10° E., 42.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 3 1/4° W., 41.9 ft. dist., with a healed blaze.</p> <p>N. 0° 33' 25" W., on the N. and S. center line of sec. 11.</p>
2507.95	<p>The center 1/4 sec. cor. of sec. 11, established by Haines, PLS No. 239, in 1960, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 9 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears S. 52 1/4° E., 75.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 52 ins. diam., bears S. 3 3/4° W., 38.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the iron rod, 38 ins. long, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 7 W C 1/4 S 11 2016</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 32' 25" W., beginning new measurement.</p>
2598.93	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr style="width: 80%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>N. 88° 37' 57" W., on the E. and W. center line of sec. 11.</p>
2686.54	<p>The center 1/4 sec. cor. of sec. 11.</p> <hr style="width: 20%; margin: auto;"/>

**Subdivision of Section 11,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>N. 88° 39' 32" W., beginning new measurement.</p>
2632.21	<p>The 1/4 sec. cor. of secs. 10 and 11.</p> <hr/> <p align="center"><b>Subdivision of Section 13, T. 22 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 1° 57' 08" W., on the N. and S. center line of sec. 13.</p>
1333.87	<p>The center S 1/16 sec. cor. of sec. 13, established by Haines, PLS No. 239, date unknown; perpetuated by Hoffine, PLS No. 2291, in 1994; and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. LONE ROCK TIMBER C S 1/16 S 13 C 1994 PLS 2291, from which the remains of the bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A root hole bears S. 67 3/4° E., 89.3 ft. dist., alongside of which is a chinquapin snag, 19 ins. diam., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 72 1/4° W., 12.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Hoffine</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 4 1/2° E., 12.5 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C S 1/16   S 13 C 2016</p> <hr style="width: 20%; margin: 0 auto;"/> </div>
1328.07	<p>N. 1° 55' 38" W., beginning new measurement.</p> <p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line of the section.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 7 W C 1/4 S 13 2016</p> </div> <p>from which</p>

**Subdivision of Section 13,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2692.74	<p>A fir, 15 ins. diam., bears N. 46 1/4° E., 15.8 ft. dist., mkd. C1/4 S13 BT.</p> <p>A fir, 19 ins. diam., bears S. 68 1/4° E., 37.4 ft. dist., mkd. C1/4 S13 BT.</p> <p>The center N 1/16 sec. cor. of sec. 13, established by Haines, PLS No. 239, date unknown; perpetuated by Hoffine, PLS No. 2291, in 1994; and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 22 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines</p> <p>A fir, 50 ins. diam., bears S. 6 1/2° E., 61.3 ft. dist., with illegible scribe marks visible on bark.</p> <p>A sawed decayed fir stump, 25 ins. diam., bears N. 3° W., 75.4 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Hoffine</p> <p>A fir, 17 ins. diam., bears S. 82 3/4° E., 6.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>C N 1/16   S 13 C 2016</p> <hr style="width: 20%; margin: auto;"/> </div> <p>N. 1° 58' 34" W., beginning new measurement.</p>
1369.70	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr style="width: 80%; margin: auto;"/>
1231.75	<p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>S. 87° 11' 24" W., on the E. and W. center line of sec. 13.</p>
2463.50	<p>Point for the center E 1/16 sec. cor. of sec. 13, not monumented.</p>
3776.31	<p>The center 1/4 sec. cor. of sec. 13.</p>
	<p>The center W 1/16 sec. cor. of sec. 13, established by Haines, PLS No. 239, date unknown; recovered and reported by Hoffine, PLS No. 2291, in 1994; and is accepted as the cor., determined at Hoffine's record distance-distance intersection from the bearing trees mkd. by Haines</p> <p>A fir, 39 ins. diam., bears N. 68 1/4° E., 18.1 ft. dist., with scribe marks CW 1/16 S13 BT visible on bark.</p>

**Subdivision of Section 13,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 32 ins. diam., bears S. 35° E., 26.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 13 \\ \text{2016} \end{array}</math> <hr style="width: 20%; margin: auto;"/> </div> <p>S. 87° 44' 06" W., beginning new measurement.</p>
1314.90	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr style="width: 80%; margin: auto;"/> <p>From the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>N. 0° 48' 11" W., on the N. and S. center line of the SE 1/4 of sec. 13.</p>
1320.59	<p>The SE 1/16 sec. cor. of sec. 13, established by Hoffine, PLS No. 2291, in 2009, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 11 ins. above ground, with aluminum cap mkd. LONE ROCK TIMBER SW 1/16 S 13 2009 PLS 2291, from which the remains of the bearing trees mkd. by Haines, PLS No. 239, in 1956, utilized by Hoffine</p> <p>A fir, 20 ins. diam., bears S. 54 1/4° E., 10.9 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 27 ins. diam., bears S. 41° W., 52.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{SE } 1/16 \text{ S } 13 \\ \text{2016} \end{array}</math> </div> <p>from which</p> <p>A fir, 24 ins. diam., bears N. 16 1/4° E., 38.0 ft. dist., mkd. SW 1/16 S13 BT.</p> <p>From this cor., a point erroneously established as the SE 1/16 sec. cor. of sec. 13 by Haines, PLS No. 239, date unknown, bears S. 1° 40' 22" W., 4.61 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center. This point was not correctly positioned and was not utilized for control in this survey. The bearing</p>

**Subdivision of Section 13,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>trees mkd. by Haines were utilized by Hoffine to reference the SE 1/16 sec. cor.</p> <hr/> <p>N. 0° 48' 01" W., beginning new measurement.</p>
1317.51	<p>Point for the center E 1/16 sec. cor. of sec. 13.</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 13 and 18, on the E bdy. of the Tp. S. 86° 40' 03" W., on the E. and W. center line of the SE 1/4 of sec. 13.</p>
1206.11	<p>The SE 1/16 sec. cor. of sec. 13.</p> <hr/>
	<p>S. 86° 39' 16" W., beginning new measurement.</p>
1206.13	<p>Point for the center S 1/16 sec. cor. of sec. 13.</p> <hr/>
	<p>From the W 1/16 sec. cor. of secs. 13 and 24.</p>
	<p>N. 1° 51' 13" W., on the N. and S. center line of the SW 1/4 of sec. 13.</p>
1296.66	<p>The SW 1/16 sec. cor. of sec. 13, established by Haines, PLS No. 239, date unknown, perpetuated by Hoffine, PLS No. 2291, in 1994, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 22 1/4° E., 4.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 87 1/2° E., 29.9 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 36 ins. long, with brass cap mkd.</p> <p align="center">SW 1/16 S 13 2016</p> <hr/>
	<p>N. 2° 12' 01" W., beginning new measurement.</p>
1290.04	<p>The center W 1/16 sec. cor. of sec. 13.</p> <hr/>
	<p>From the center S 1/16 sec. cor. of sec. 13.</p>

**Subdivision of Section 13,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1306.72	<p>S. 88° 51' 36" W., on the E. and W. center line of the SW 1/4 of sec. 13.</p> <p>The SW 1/16 sec. cor. of sec. 13.</p> <hr/>
1315.94	<p>S. 88° 59' 23" W., beginning new measurement.</p> <p>The S 1/16 sec. cor. of secs. 13 and 14.</p> <hr/>
1400.86	<p>From the center W 1/16 sec. cor. of sec. 13.</p> <p>N. 1° 26' 52" W., on the N. and S. center line of the NW 1/4 of sec. 13.</p> <p>The NW 1/16 sec. cor. of sec. 13, established by Haines, PLS No. 239, date unknown, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 11 ins. above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A sawed maple stump, 26 ins. diam., bears N. 42° E., 4.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A root hole bears S. 73° E., 14.0 ft. dist., alongside of which is a fir snag, 13 ins. diam., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, 40 ins. long, with brass cap mkd.</p> <p align="center">SW 1/16 S 13 2016</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 2° E., 14.6 ft. dist., mkd. NW1/16 S13 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 79 3/4° W., 15.5 ft. dist., mkd. NW1/16 S13 BT.</p> <hr/>
1387.29	<p>N. 1° 25' 29" W., beginning new measurement.</p> <p>The W 1/16 sec. cor. of secs. 12 and 13.</p> <hr/>
1300.96	<p>From the center N 1/16 sec. cor. of sec. 13.</p> <p>S. 88° 46' 46" W., on the E. and W. center line of the NW 1/4 of sec. 13.</p> <p>The NW 1/16 sec. cor. of sec. 13.</p> <hr/>

**Subdivision of Section 13,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	S. 88° 20' 34" W., beginning new measurement.
1300.95	The N 1/16 sec. cor. of secs. 13 and 14.
<hr/> <p><b>Subdivision of section 14, T. 22 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/>	
2609.50	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 1° 20' 04" W., on the N. and S. center line of sec. 14.</p> <p>The center 1/4 sec. cor. of sec. 14, established by Hoffine, PLS No. 2291, in 1993, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., 38 ins. long, firmly set, projecting 5 ins. above ground, with aluminum cap mkd. LONE ROCK TIMBER T 22 S R 7 W C 1/4 S 14 1993 PLS 2291, from which the bearing trees mkd. by Hoffine</p> <ul style="list-style-type: none"> <li>A fir, 15 ins. diam., bears N. 14 1/4° E., 33.9 ft. dist., with a healed blaze.</li> <li>A fir, 15 ins. diam., bears S. 18 3/4° E., 4.3 ft. dist., with a healed blaze.</li> <li>A fir, 13 ins. diam., bears S. 34 1/2° W., 81.7 ft. dist., with a healed blaze.</li> <li>An oak, 50 ins. diam., bears N. 59 1/2° W., 33.6 ft. dist., with no marks visible on partially opened blaze.</li> </ul> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 7 W C 1/4 S 14 2016</p> <p>From this cor., a point erroneously established as the center 1/4 sec. cor. of sec. 14 by Cole, Deputy County Surveyor, in 1915, perpetuated by Haines, PLS No. 239, in 1964, bears N. 51° 20' 47" W., 14.83 ft. dist., monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 14 ins. above ground. This point was not correctly positioned and was not utilized for control in this survey, from which the bearing tree mkd. by Cole</p> <ul style="list-style-type: none"> <li>An oak, 50 ins. diam., bears N. 65 3/4° W., 19.0 ft. dist., with no marks visible on partially opened blaze.</li> </ul>
2842.83	<p>N. 1° 19' 05" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/>

**Subdivision of Section 14,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 88° 14' 13" W., on the E. and W. center line of sec. 14.</p>
1341.14	<p>The center E 1/16 sec. cor. of sec. 14, established by Hoffine, PLS No. 2291, in 1993, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with aluminum cap mkd. LONE ROCK TIMBER C E 1/16 C S 14 1993 PLS 2291, from which the remains of the bearing trees by Hoffine</p> <p style="padding-left: 40px;">A root hole bears S. 25 1/4° E., 17.8 ft. dist., alongside of which is a down fir log, 17 ins. diam., with no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 34 ins. diam., bears N. 82 1/2° W., 30.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, 38 ins. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} \text{E 1/16} \\ \text{C} \text{---} \text{C} \\ \text{S 14} \\ \text{2016} \end{array}</math> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 19° E., 14.2 ft. dist., mkd. CE1/16 S14 BT.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 37 1/4° E., 4.9 ft. dist., mkd. X BT.</p> <p>Note: No evidence of the cor. set by Cole, Deputy County Surveyor, in 1915, or the "T" iron set by Haines, PLS No. 239, date unknown, that was reported by Hoffine, was found.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 13' 39" W., beginning new measurement.</p>
1341.33	<p>The center 1/4 sec. cor. of sec. 14.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 13' 31" W., beginning new measurement.</p>
1393.33	<p>The center W 1/16 sec. cor. of sec. 14, established by Hoffine, PLS No. 2291, in 1993, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.</p>

Subdivision of Section 14,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">LONE ROCK TIMBER W 1/16 C ————— C S 14 1993 PLS 2291</p> <p>from which the bearing tree mkd. by Hoffine</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 77 3/4° W., 32.8 ft. dist., with a healed blaze.</p> <p>From this cor., a point erroneously established as the center W 1/16 sec. cor. of sec. 14 by Cole, Deputy County Surveyor, in 1915, bears N. 79° 44' 20" W., 60.02 ft. dist., monumented with an iron bolt, 1/2 in. diam., firmly set, with top flush with the surface of the ground, with a square head on top, 1 in. diam. This point was not correctly positioned and was not utilized for control in this survey.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 88° 16' 47" W., beginning new measurement.</p>
1394.14	<p>The 1/4 sec. cor. of secs. 14 and 15, perpetuated by Hollingsworth, PLS No. 691, in 1987, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 7 W 1/4 S 15   S 14 1965</p> <p>from which the bearing tree mkd. by Jelley and Beck in 1965.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 27 1/2° W., 20.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Hollingsworth</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 80 1/4° E., 10.7 ft. dist., with a healed blaze.</p> <p>From this cor., the top center of the easterly archway entering the Oregon State Highway No. 38 tunnel bears N. 7° 21' 05" E., 58.8 ft. dist. (record, N. 14° E., 49.5 ft. dist.).</p> <hr style="width: 80%; margin: 20px auto;"/> <p>From the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 1° 43' 34" W., on the N. and S. center line of the SE 1/4 of sec. 14.</p>
2565.38	<p>The center E 1/16 sec. cor. of sec. 14.</p> <hr style="width: 80%; margin: 20px auto;"/>