

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES
AND SUBDIVISION OF SECTION LINES OF SECTION 19,
TOWNSHIP 24 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON

EXECUTED BY

Jeffrey O. Covington, Cadastral Surveyor

Under Special Instructions approved December 16, 2019,
which provided for the surveys included under Group No. 2963,
and Assignment Instructions dated December 16, 2019.

Survey commenced January 7, 2020

Survey completed April 30, 2020

T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of portions of the subdivisional lines and subdivision of section lines of section 19, Township 24 South, Range 6 West, Willamette Meridian, Oregon.

The history of the official surveys pertaining to this survey is as follows:

In 1853, Robert Elder and Henry S. Gile, U.S. Deputy Surveyors, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved June 30, 1853.

In 1891, Williams R. Whipple, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved February 3, 1892.

In 1962, Joseph S. Gawron, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines and subdivided section 19, as shown on the official plat of survey accepted September 27, 1963.

In 1963, C. Albert White and Norman J. McDonald, Cadastral Surveyors, dependently resurveyed a portion of the subdivisional lines as shown on the official plat of survey accepted November 19, 1964.

In 2003, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, rehabilitated the corner of sections 17, 18, 19, and 20, as described in the official field notes approved November 3, 2004.

The following local surveys (M) and county surveyor files (CS), filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name, official title or Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1959	Douglas County Surveyor's Office	CS49/83-5
1997	Randall W. Smith, PLS No. 2469	CS64/78-38
1998	Mark F. Smalley, PLS No. 2354	M129-12
2010	Ronald L. Rice, PLS No. 54633	CS65/69-43
2014	Randall W. Smith, PLS No. 2469	CS67/41-15
2018	David A. Edwards, PLS No. 2339	M174-53

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions (2009), and the special instructions approved December 16, 2019, for Group No. 2963, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET

Preliminary to the resurvey the lines of the official original surveys and resurveys were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions. The retracement data was thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center and each monument established or reestablished has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description. Aluminum angle irons, 5 ft. long, were driven alongside each monument unless a similar marker was already in place.

Only those lines bounding Federal interest land were blazed.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

The corner of sections 8, 9, 16, and 17:

Latitude: 43° 29' 25.69" N. Longitude: 123° 25' 34.20" W.

The 1/4 section corner of sections 18 and 19:


Latitude: 43° 28' 33.24" N. Longitude: 123° 27' 21.57" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

Restoring the 1853 survey by Elder and Gile, the 1891 survey by Whipple, the 1962 resurvey by Gawron, the 1963 resurvey by White and McDonald, and the 2003 rehabilitation by Moore and Browning

From the cor. of secs. 16, 17, 20, and 21, reported by White and McDonald in 1963; perpetuated by Smalley, PLS No. 2354, in 1998; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with a brass cap mkd.

COUNTY SURVEYORS OFFICE



from which the accessories reported by White and McDonald

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>A decayed fir stump, 34 ins. diam., bears N. 82 1/2° E., 58.7 ft. dist., with a steel spike driven into the center of the stump.</p> <p>A hollowed madrone, 33 ins. diam., bears S. 13° W., 27.1 ft. dist., with a healed blaze. (Original)</p> <p>A maple, 23 ins. diam., bears S. 44 1/4° W., 24.4 ft. dist., with a healed blaze.</p> <p>A sandstone outcropping, 5 x 5 x 3 ft. above ground, bears S. 70° W., 13.2 ft. dist., mkd. BXO on N. face.</p> <p>and the remains of a bearing tree mkd. by Smalley</p> <p>A roothole bears N. 37 1/2° E., 10.1 ft. dist., alongside of which is a down fir, 16 ins. diam., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 22 ins. diam., bears N. 15 1/2° E., 46.4 ft. dist., mkd. T24S R6W S16 BT.</p> <p>A fir, 21 ins. diam., bears N. 29 1/4° W., 36.7 ft. dist., mkd. T24S R6W S17 BT.</p> <p>From this cor., a point established, established by person(s) unknown for unknown purpose; reported by Smalley, and was not utilized for control in this survey, bears N. 13° 18' 02" W., 1.60 ft. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above ground.</p> <p>N. 0° 07' 41" W., bet. secs. 16 and 17.</p>
65	Ravine, drains N. 60° E.
2605	Spur, slopes S. 60° E.
2649.09	<p>The 1/4 sec. cor. of secs. 16 and 17, reported by White and McDonald in 1963; and perpetuated by Smalley, PLS No. 2354, in 1998; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">1/4 S 17 S 16 T 24 S R 6 W 1963</p> <p>from which the remains of the bearing trees reported by White and McDonald</p> <p>A fir, 23 ins. diam., bears S. 57° E., 201.8 ft. dist., with a healed blaze. (Record, 204.6 ft. dist.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

FEET									
	<p>A decayed fir snag, 30 ins. diam., bears N. 45° W., 123.4 ft. dist., with a healed blaze. (Record, 128.7 ft. dist.)</p> <p>and the bearing trees mkd. by Smalley</p> <p>A fir, 15 ins. diam., bears S. 28 1/4° E., 30.0 ft. dist., with a healed blaze.</p> <p>A fir, 21 ins. diam., bears S. 68° W., 14.4 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears N. 39° W., 22.1 ft. dist., with a healed blaze.</p> <p>A fir, 20 ins. diam., bears N. 1° W., 17.2 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 09' 29" W., beginning new measurement.</p>								
170	Spur, slopes S. 80° E.								
2590	Graveled road, 14 ft. wide, bears S. 70° E. and N. 70° W.								
2652.97	<p>The cor. of secs. 8, 9, 16, and 17, reported by White and McDonald in 1963; perpetuated by Smalley, PLS No. 2354, in 1998; and subsequently perpetuated by Rice, PLS No. 54633, in 2010; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 24 S</td> <td style="padding: 0 5px;">R 6 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1963</td> </tr> </table> </div> <p>from which the remains of the bearing trees reported by White and McDonald</p> <p>A hemlock, 31 ins. diam., bears N. 35 1/2° E., 15.2 ft. dist., with a healed blaze.</p> <p>A decayed fir stump, size indeterminate, bears N. 74° E., 33.7 ft. dist., no marks visible. (Original)</p> <p>and the bearing trees mkd. by Smalley</p> <p>A fir, 11 ins. diam., bears S. 17 1/4° W., 23.2 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears S. 69 1/2° W., 24.2 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Rice</p> <p>A fir, 15 ins. diam., bears S. 84° E., 45.4 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p>	T 24 S	R 6 W	S 8	S 9	S 17	S 16	1963	
T 24 S	R 6 W								
S 8	S 9								
S 17	S 16								
1963									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A maple, 12 ins. diam., bears N. 29 1/2° W., 28.4 ft. dist., mkd. T24S R6W S8 BT.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 9 and 16, reported by White and McDonald in 1963; perpetuated by Smalley, PLS No. 2354, in 1998; and subsequently perpetuated by Edwards, PLS No. 2339, in 2018; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 3 ft. base, to the top, with a brass cap mkd.</p> <div style="text-align: center;"> <p>S 9 E 1/16 ——— S 16 T 24 S R 6 W 1963</p> </div> <p>from which the remains of the bearing trees mkd. by Smalley</p> <p>A madrone snag, 10 ins. diam., bears S. 19 1/2° E., 35.7 ft. dist., with scribe marks E1/16 BT visible on partially healed blaze.</p> <p>A fir, 23 ins. diam., bears N. 68 1/2° W., 37.2 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Edwards</p> <p>A fir, 12 ins. diam., bears S. 25° E., 3.5 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>N. 89° 25' 53" W., bet. secs. 9 and 16.</p>
10	Creek, 2 ft. wide, course S.
1115	Ravine, drains S. 10° E.
1348.15	<p>The 1/4 sec. cor. of secs. 9 and 16, reported by White and McDonald in 1963; and perpetuated by Smalley, PLS No. 2354, in 1998; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>S 9 1/4 ——— S 16 T 24 S R 6 W 1963</p> </div> <p>from which the remains of the bearing trees reported by White and McDonald</p> <p>A decayed fir stump, 18 ins. diam., bears E., 2.6 ft. dist., no marks visible. (Original)</p> <p>A decayed fir stump, 30 ins. diam., bears S. 5° E., 5.9 ft. dist., no marks visible. (Original)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>A decayed fir stump, 38 ins. diam., bears S. 69° W., 53.5 ft. dist., no marks visible.</p> <p>A sandstone outcropping, 7 x 6 x 4 ft. high, bears N. 37 1/2° W., 21.2 ft. dist., mkd. BXO and FFB directly below on SE face. (Record, N. 37° W., 21.8 ft. dist.)</p> <p>and the bearing trees mkd. by Smalley</p> <p>A fir, 20 ins. diam., bears N. 65 1/4° E., 37.3 ft. dist., with a healed blaze.</p> <p>A fir, 21 ins. diam., bears S. 78 1/2° W., 65.5 ft. dist., with a healed blaze.</p> <hr/> <p>N. 89° 13' 46" W., beginning new measurement.</p>
1309.86	<p>The W 1/16 sec. cor. of secs. 9 and 16, established by Smalley, PLS No. 2354, in 1998; and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, with an aluminum cap mkd.</p> <div style="text-align: center;"> <p>ROSEBURG RESOURCES COMPANY</p> <p>T 24 S R 6 W</p> <p>S 9 W</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S 16 W 1/16</p> <p>1998</p> <p>L.S. 2354</p> </div> <p>from which the bearing trees mkd. by Smalley</p> <p>A fir, 24 ins. diam., bears S. 25 1/4° W., 31.5 ft. dist., with a healed blaze.</p> <p>A fir, 30 ins. diam., bears N. 8 3/4° W., 23.7 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 9</p> <p>W 1/16 ———</p> <p>S 16</p> <p>2020</p> </div> <hr/> <p>N. 89° 14' 11" W., beginning new measurement.</p>
1065	<p>Graveled road, 14 ft. wide, bears S. 5° W. and N. 20° W.</p>
1309.76	<p>The cor. of secs. 8, 9, 16, and 17.</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>From the 1/4 sec. cor. of secs. 19 and 20, reported by Gawron in 1962; and perpetuated by Smith, PLS No. 2469, in 2014; monumented with an iron post, 1 1/4 ins. diam., firmly set, with top 4 ins. below the surface of the ground, with a brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYOR T 24 S R 6 W S 19 S 20 1/4 2014</p> <p>from which the remains of the bearing trees reported by Gawron</p> <ul style="list-style-type: none"> A broken cedar snag, 44 ins. diam., bears N. 58 3/4° E., 74.9 ft. dist., with a healed blaze. (Record, N. 55 1/2° E.) A decayed fir stump, 36 ins. diam., bears N. 71 1/4° E., 44.9 ft. dist., no marks visible. (Record, N. 81 1/2° E.) A broken, decayed cedar snag, 39 ins. diam., bears S. 53° E., 52.1 ft. dist., no marks visible. (Original) A decayed fir stump, 44 ins. diam., bears N. 84 1/2° W., 38.9 ft. dist., no marks visible. (Original) A fir, 35 ins. diam., bears N. 42° W., 116.8 ft. dist., with no marks visible on open blaze. <p>and accessories as reported by Smith</p> <ul style="list-style-type: none"> A fir, 20 ins. diam., bears S. 82 1/4° W., 37.2 ft. dist., with a healed double blaze. A cattle guard set in a 9.4 x 14.4 ft. concrete foundation, bears N. 13 1/4 E., 17.1 ft dist. to the NE cor. and N 31 3/4 W., 4.2 ft. dist. to the SE cor. <p>and a new bearing tree</p> <ul style="list-style-type: none"> A cedar, 5 ins. diam., bears N. 27 1/2° E., 28.7 ft. dist., mkd. 1/4 S20 BT. <p>Corner is located S., 10 ft. dist. of Gallagher Canyon Rd., asphalt surface, 12 ft. wide, bears S. 60° E. and N. 65° W.</p> <p>N. 0° 19' 44" E., bet. secs. 19 and 20.</p>
155	Creek, 3 ft. wide, course N. 80° W.
1319.68	The N 1/16 sec. cor. of secs. 19 and 20, established by person(s) unknown; and is accepted as the cor.; monumented with a T-shaped iron rod, 3/4 in. diam., firmly set, projecting 12 ins. above ground, with a brass washer mkd. WILFORD N. HAINES SURVEY POINT 239 DRAIN, ORE., with a tack in center.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 19 S 20 2020</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A madrone, 7 ins. diam., bears N. 25 1/4° E., 22.9 ft. dist., mkd. N1/16 S20 BT on bark.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 85 3/4° W., 35.4 ft. dist., mkd. N 1/16 S19 BT.</p> <p>Deposit T-shaped iron rod, 36 ins. long, inside stainless steel post.</p> <p>Corner is located in a 2-strand barbed and woven wire fence, extends N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 20' 02" E., beginning new measurement.</p>
185	<p>Ridge, bears N. 45° E. and S. 45° W.</p>
1321.73	<p>The cor. of secs. 17, 18, 19, and 20, reported by Moore and Browning in 2003; monumented with the original sandstone, 14 x 10 x 5 ins., firmly set, projecting 6 ins. above ground, with chisel mark F on W. face; with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, plumbed over the original stone, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE S 18 S 17 ----- S 19 S 20 T 24 S R 6 W 1959</p> <p>from which the remains of the bearing trees reported by Moore and Browning</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 22 3/4° E., 26.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A decayed madrone stump, 16 ins. diam., bears N. 51° E., 45.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A madrone snag, 15 ins. diam., bears S. 17 1/2° E., 66.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 7 1/2° E., 14.4 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>A fir snag, 8 ins. diam., bears S. 54 3/4° W., 14.2 ft. dist., with a healed blaze.</p> <p>A broken, decayed fir stump, size indeterminate, bears S. 69° W., 89.1 ft. dist., no marks visible. (Original)</p> <p>A fir, 12 ins. diam., bears N. 63 1/2° W., 11.0 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 11 ins. diam., bears S. 79 1/4° W., 17.8 ft. dist., mkd. T24S R6W S19 BT.</p> <p>At the corner point</p> <p>Removed the original stone and reset the iron post, 36 ins. long, 1 1/4 ins. diam., 24 ins. in the ground. Add the marks BLM 2020 to the cap. Bury the stone alongside the cor.</p>
	<hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89° 53' 47" W., bet. secs. 17 and 20.</p>
2360	<p>Creek, 2 ft. wide, course S. 45° E.</p>
2636.94	<p>The 1/4 sec. cor. of secs. 17 and 20, perpetuated by Douglas County Surveyor's Office, in 1959; and subsequently perpetuated by Smith, PLS No. 2469, in 1997; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE S 17 1/4 ——— S 20 1959</p> <p>from which the remains of the original bearing trees</p> <p>A decayed cedar snag, 30 ins. diam., bears S. 20° E., 21.1 ft. dist., with no marks visible on open blaze.</p> <p>A decayed cedar stump, 12 ins. diam., bears N. 30° W., 18.8 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Smith</p> <p>A fir stump, 20 ins. diam., bears S. 59° E., 25.1 ft. dist., no marks visible.</p> <p>An incense cedar, 16 ins. diam., bears N. 88° W., 20.7 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir snag, 18 ins. diam., bears N. 5 1/4° W., 13.1 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 4 ins. diam., bears S. 57 3/4° W., 12.2 ft. dist., mkd. X BT.</p> <hr/> <p>S. 89° 15' 21" W., beginning new measurement.</p>
2658.49	<p>The cor. of secs. 17, 18, 19, and 20.</p> <hr/>
2635.91	<p>N. 89° 32' 51" W., bet. secs. 18 and 19.</p> <p>The 1/4 sec. cor. of secs. 18 and 19, reported by Gawron in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.</p>
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE S 18 1/4 _____ S 19 T 24 S R 6 W 1959</p>
	<p>from which the bearing trees reported by Gawron</p> <p>An oak, 24 ins. diam., bears S. 38° E., 75.9 ft. dist., no marks visible. (Original)</p> <p>A maple, 40 ins. diam., bears N. 6 1/2° W., 64.0 ft. dist., with a healed blaze.</p> <p>From this cor., a point reported by Gawron, established by person(s) unknown for unknown purpose, and was not utilized for control in this survey, bears S. 21° 47' 22" E., 55.19 ft. dist.; monumented with an iron rod, 3/4 in. diam., firmly set, projecting 1 in. above ground. (Record, S. 21° E., 54.78 ft. dist.)</p> <hr/>
	<p style="text-align: center;">Dependent Resurvey of Subdivision of Section Lines of Section 19, T. 24 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/>
	<p style="text-align: center;">Restoring the 1962 survey by Gawron</p> <hr/>
	<p>From the center S 1/16 sec. cor. of sec. 19, reported by Gawron in 1962, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.</p>

Dependent Resurvey of Subdivision of Section Lines of Section 19,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">C S 1/16 S 19 C 1962</p> <p>from which the bearing trees reported by Gawron</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears S. 7 1/2° E., 26.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears S. 51° W., 6.6 ft. dist., no marks visible.</p> <p>N. 0° 07' 28" E., on the N. and S. center line of sec. 19.</p>
1327.12	<p>The center 1/4 sec. cor. of sec. 19, reported by Gawron in 1962, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">C 1/4 S 19 1962</p> <p>from which the bearing tree reported by Gawron</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. 16° E., 160.4 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A maple, 16 ins. diam., bears S. 62 1/2° E., 70.3 ft. dist., mkd. C1/4 S19 BT.</p> <p>Corner is located N., 5 ft. dist. of Creek, 2 ft. wide, course N. 50° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 06' 16" E., beginning new measurement.</p>
1333.85	<p>The center N 1/16 sec. cor. of sec. 19, reported by Gawron in 1962, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, in a mound of stone, 1 1/2 ft. base, 12 ins. high, with a brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 19 C 1962</p> <p>from which the bearing objects reported by Gawron</p> <p style="padding-left: 40px;">A face of a sandstone bluff, 6 ft. high, bears S. 84° E., 15.3 ft. dist., mkd. BXO. (Record, 15.8 ft. dist.)</p>

Dependent Resurvey of Subdivision of Section Lines of Section 19,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>A face of a sandstone bluff, 20 ft. high, bears N. 74 3/4° W., 59.9 ft. dist., mkd. BXO. (Record, N. 77° W., 59.4 ft. dist.)</p> <p>and new bearing trees</p> <p>A fir, 9 ins. diam., bears S. 44 1/4° E., 26.8 ft. dist., mkd. CN1/16 S19 BT.</p> <p>A madrone, 11 ins. diam., bears N. 5° W., 25.1 ft. dist., mkd. CN1/16 S19 BT on bark.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 07' 40" E., beginning new measurement.</p>
1330.67	<p>The 1/4 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>S. 89° 58' 47" W., on the E. and W. center line of sec. 19.</p>
1314.05	<p>The center E 1/16 sec. cor. of sec. 19, reported by Gawron in 1962, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>E 1/16</p> <p>C ————— C</p> <p>S 19</p> <p>1962</p> </div> <p>from which the bearing trees reported by Gawron</p> <p>A fir, 44 ins. diam., bears N. 70° E., 114.2 ft. dist., with a healed blaze.</p> <p>A cedar, 45 ins. diam., bears S. 18° W., 41.6 ft. dist., with a healed double blaze.</p> <hr/> <p>From the SE 1/16 sec. cor. of sec. 19, reported by Gawron in 1962, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SE 1/16</p> <p>S 19</p> <p>1962</p> </div> <p>from which the remains of the bearing trees reported by Gawron</p> <p>A fir stump, 25 ins. diam., bears S. 64° E., 56.1 ft. dist., with a healed blaze.</p> <p>A burnt fir stump, 26 ins. diam., bears S. 45 1/2° W., 25.7 ft. dist., no marks visible.</p>

Dependent Resurvey of Subdivision of Section Lines of Section 19,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>and new bearing trees</p> <p>A maple, 13 ins. diam., bears N. 27 1/4° E., 32.3 ft. dist., mkd. SE1/16 S19 BT.</p> <p>A fir, 6 ins. diam., bears N. 41 3/4° W., 61.8 ft. dist., mkd. SE1/16 S19 BT.</p> <p>N. 0° 00' 47" E., on the N. and S. center line of the SE 1/4 of sec. 19.</p>
1322.21	<p>The center E 1/16 sec. cor. of sec. 19.</p> <hr/>
	<p>From the SE 1/16 sec. cor. of sec. 19.</p> <p>S. 89° 42' 18" W., on the E. and W. center line of the SE 1/4 of sec. 19.</p>
1314.89	<p>The center S 1/16 sec. cor. of sec. 19.</p> <hr/>