

T21S. R11W.

✓ 1/4 CORNER Bet. Secs. 27 & 28.

✓ April 18, 1939

I found the witness corner to the 1/4 corner between 27 & 28. I could not find the stone as described in the government field notes, but found two dead witness trees in place; I therefore set cedar post 4' long, 4" diam., 18" in ground, marked 1/4 S.W.C. from which;
A Fir, 16" diam., bears S 79° E 23 ft. Marked 1/4 S.W.C. B.T. 722.
A Fir 12" diam., bears S 9° W 5 ft. Marked 1/4 S.W.C. B.T. 722.

H. T. Lewis REN. #1
ENGR 722.

✓ 1/4 Corner Bet Secs 34 & 35.

✓ REN. #2
May 9, 1939

At the 1/4 corner between Sections 34 & 35, I found the scribe on the original alder bearing tree had been rotted out, but in the soft muck where the post was supposed to set I found the well preserved point of an old wooden stake, also, running N from this point is a well blazed line, whose topography checks for a considerable distance with the government field notes. I therefore set an 1 1/2" galvanized pipe 4' long from which;
A forked spruce 28" diam., bears S 10° E 5 ft. Marked 1/4 S T21S. R11W. 535. B.T. 722.
A spruce, 36" diam., bears S 75° W 24 ft. Marked 1/4 S T21S R11W 534 B.T. 722.

By F.C. Frear R.M.
WITNESS
N.E. Richardson
James H Wolford
V-16-E55.

✓
10-20-1940

SEC COR of Secs. 18-19 T21S R11W & Sec 13-24 T21S. R.12W. on Range line.
Drove 2" X 5' Pipe for corner from which.
7" Fir bears S. 70 3/4° E. 7.4 ft
12" Fir " S 12 1/2° W. 8.3 ft
8" Fir " N 49 1/2° W. 18.2 ft,
10" Fir " N 44° E. 21.8 ft.

~~####~~

Ren #3