

Can not find
 any more info
 concerning Cain's
 Ren. - If you
 leave ~~out~~^{off} the
 decimal in front of
 the dist than
~~He~~ Hutz's FD Tree
 Fits - Cains last
 BT Fits w/long info.

22, 23,

dist.
 .
 .
 .

(Jean) (D.C.S.O) 4-3-95

REN #1

Field notes
 26 & 27, Tp. 21

Set a nail
 properly marked,

an Alder
 .
 a spruce
 an Alder

REN #1

REN #2

Field notes of reestablishment of the A.C. Gibbs Donation
 Land Claim, #37, tp. 21 S. R. 12 W.
 The South West Corner on River bank.

Set a Fir post 4" square firmly in the ground and properly
 marked, from which

An Alder 6 (12)" diam bears S. 59° E.	32 lbs dist.
An Alder 12" " " N. 58° E.	44 " "

The South East Corner.

Set a spruce post 4" square firmly in the ground, properly
 marked, from which,-

An Alder 20" diam bears S. 59° E.	28 lbs dist.
An Alder 20" " " N. 75° W.	12 " "

The North East Corner.

Set a spruce post firmly in the ground and properly marked,
 from which,-

An Alder 12" diam bears S. 48° W.	- - lbs dist
An Spruce 30" " " N. 55° W.	10 " "
A Fir 60" " " S. 15° E.	38 " "
A Spruce 8" " " S. 35° W.	48 " "

Ben B Irving D.C.S. Jan 25/1929

Journal 9/29/26
 among J. Cains notes
 M. C. Bowker

REN #9

21-12

REN #1

Field notes of the reestablishment of corner to secs. 22, 23, 26 & 27, Tp. 21 S. R. 12 W.

Set a hemlock post 4" square firmly in the ground and properly marked, from which

an Alder	20"	in diam	bears N.	19°	E.	.50	lks	dist.
"	"	20"	"	"	S.	289	R.	.46 " "
a spruce	12"	"	"	"	S.	32°	W.	.57 " "
an Alder	15"	"	"	"	N.	69°	W.	47 " "

REN #2

Field notes of reestablishment of the A.C. Gibbs Donation Land Claim, #37, tp. 21 S. R. 12 W. The South West Corner on River bank.

Set a Fir post 4" square firmly in the ground and properly marked, from which

An Alder	6 (12)"	diam	bears S.	59°	E.	32	lks	dist.
An Alder	12"	"	"	"	N.	58°	E.	44 " "

REN #3

The South East Corner. Set a spruce post 4" square firmly in the ground, properly marked, from which,-

An Alder	20"	diam.	bears S.	58°	E.	25	lks.	dist.
An Alder	20"	"	"	"	N.	75°	W.	12 " "

REN #4

The North East Corner. Set a spruce post firmly in the ground and properly marked, from which,-

An Alder	12"	diam	bears S.	45°	W.	- -	lks	dist
An Spruce	30"	"	"	"	N.	33°	W.	10 " "
A Fir	60"	"	"	"	S.	15°	E.	38 " "
A Spruce	8"	"	"	"	S.	35°	W.	48 " "

Found 9/24/26
among 7 claims notes
among C. Bowker

Ren. #3

1/4 cor. bet. Secs. 32 & 5 on S. ldy of 21-12
Set in a 6" x 48" sp. stake fr. wh.
C 30" sp. br. N 36° W. 32 lbs.

Both old trees found

Wit. J. Ford
M.C. Boucher
T.L. Eppstein
C. H. Mayo
3/17/1925

N.E. Cor of D.L.C. 37 Set 4" x 4" x 4" post
from old B.T. standing, which were
a 12" alder S 58° E 25 lbs. REN. #4

Jan 25 1929
Wit. Frank Colman
Wang Henderson
T.L. Eppstein
C.S. Boucher

Cor 13, 18, 19, 24. T 21 S R 11 & 12 W, There was an
iron pipe 2" x 5' driven in ground for this corner
by previous surveyor, the old Bearing Trees gone
but remains of stump check with Field notes, but
burned so bad no scribe marks visible, did not
mark new tree on account of being too far off.
###

Ben B Irving D.C.S.
Wit. N.E. Richardson
Loren Weber
(Ren. #6)

Sec. Cor. 14-15-22-23
Location identified from old stake and a B.T. Fir 24" dia.
S 42° W scribed T 21 S R 12 W S 22. The stake & tree are not original
but were set approximately 35-40 years ago. Set a 2 1/2" x 2 1/2" x 48"
Post for corner from which:
A Fir 50" diam. bears S 82° W. 50 ft. T. 21 S. R. 12 W. S 22. C.S. B.T.
Alder 15" " " N 70° E. 23 1/2" " " 5 14 " "
" 15" " " S 33° E. 47° " " " 5 23 " "
Fir 60" " " N 38° W 32 1/2" " " 5 15 " "
This location fits topography as records original field notes.

Ren. #7

Meander Cor. bet Sec. 15-22 on Rt. Bank of Umpqua River.
Location determined from line West from Sec. Cor. 14-15-22-23, and
falls in a drainage ditch. Set a 6" x 6" x 15" block of concrete in top
of dike, 33 ft west of corner for a witness corner and set 2 x 6 x 48"
Post along side. ###

Ben B Irving D.C.S.
Witness N.E. Richardson
Loren Weber

1/4 Cor bet Secs. 15 & 16
Set by proportional measurement between Sec. Cor. 9-10-15-16
and meander Cor 15-16. Drove an iron pipe 1" x 48" flush with
the ground & set a 4" x 6" x 36" post along side from which:
A spruce 36" diam. bears S 47° W 235 ft. marked 1/4 5 16 C.S. B.T.
A spruce 30" diam. bears N 80 1/2° W 308 ft. marked 1/4 5 16 C.S. B.T.
REN. #8

N.W. Corner Addison, Gibbs D.L.C. #37.
Set from 1/4 Cor tie as recorded in original Government
field notes.
Set a cedar post 4" x 4" x 36" and drove an iron pipe alongside
from which:
A spruce 18" diam. bears S 42 1/2° W. 565 ft. marked D.L.C. 37. C.S. B.T.
A spruce 8" diam. bears N 70° W 305 ft. marked D.L.C. 37 C.S. B.T.

REN. #9