

C.W. Springer Dep't B
Feb 1923
H. Bergh claim
W.A. Downing's abt. (Ren #15)
J.A. Benis

1/4 Sec cor bet Sec. 142 - Reset from 1 orig. B.T. and evidence of second B.T. Renewed cor with an iron pipe 1 1/4" x 30" driven in ground from which a B. Oak 16" in dia bears S 59° W 58 lks N. B. Oak bears N 28° E 30 lks.

A. Rayer D.C.
C.W. Springer Dep't B
Feb 1923
H. Bergh claim
W.A. Downing's abt. (Ren #16)
J.A. Benis

S.W. Cor. Joseph L. Gilbert A. #61. Reset the cor from the given to Sec cor. Put in iron pipe 1 1/2" x 30" and erected a mound of rock from which a B. Oak 6" in dia bears N 51° E 129 lks slope distance. (Ren #16)

H. Rayer D.C.
C.W. Springer Dep't B
June 28 1923
C.A. Beckman
Chamman
Witness - M. F. De Costa - Robert Lehman
J. A. Cole - Guy Cole (Ren #17)

Sec. Cor. Common to Secs 5-6-7-8
Reset from 3 B.Ts only one of which was alive & standing
Drove an Oak stake 3 x 3 x 36 in ground and from which I marked new trees as follows -

- 12" Fir N 16° E 20.5 ft
- 48" Fir S 16° E 340 ft
- 10" Chincapin S 8° 30' W 232.7 ft
- 6" Oak Quib N 71° W 253.6 ft.

David B. Shung Dep. Co. Surveyor
Jan 28 1924.
Witness Emmett Hall
Jake Roth.
(Ren #19)

1/4 Sec cor bet Sec 6 & 7
Orig. cor, 60" Cedar, alive and standing but I marked two new B.Ts as follows, (Ren #18)
10" W. Fir N 36° 30' W 21 ft
18" " " S 55° 00' E 57.5 ft
One original still standing but chopped open S 50° E 33 ft.

Sec. Cor. Common to Secs. 23-24-25-26
One Original B.T. standing in excellent shape. One Orig. B.T. chopped open; tree dying. One Orig. B.T. hollow and dying. Stump properly located for fourth B.T. badly rotted.

- Set 1" iron pipe 30" long from which Original B.T.
- 24" B.O. N 41° W 37 ft. (This recorded original N 45° W + one N 41° E which had apparently been reversed)
- 8" W.O. S 44° 44' W 71 ft.
- 30" B.O. S 18° 04' E 81 ft
- 6" W.O. N 75° 40' E 64 ft.

Ben B. Shung Jan 28 1924
F.C. Frear
Co. Surveyor

25-6

Remo being Jan 28/1924
Witnessed
Emmett Hall
Jake Roth.
(Rev. #20)

✓ S.W. Corner D.L.C. # 58. Sec. 25 T 25 S R 6 W
Both Original B.Ts. standing & cut open one of which
face is badly rotted. Other good shape. 3" old oak stake.
Drove ³/₄" Iron pipe and marked New BT
A 30" B.O. 544°17' E 23 ft.

(Rev. #21)

✓ S E Cor DLC # 58 and S.W. Cor. DLC # 59.
✓ Two Original B.Ts. standing and in excellent shape.
Also old oak stake. Drove ³/₄" IRON pipe

James Johnson Rep. Co Surveyor
NE Richardson } witness
Cecil Fessler } May 9 1931
(Rev. #22)
(Rev. #23)

✓ NE Cor. Nicholas Day DLC # 40
Location identified from stump of orig. BT.
Letters "BT" in good condition
Set Oak Post 4x4x36"
10" W Oak 555° E 94 lks. blazed & scribed NE C 140 CS BT
10" B Oak N 84° W 9 " " " "

SE Cor Thomas Watson DLC # 41
Location identified from snag of one OBT letters
legible but badly rotted and stump which checked
location of other OBT.
Set Oak post 4x4x36"
30" W Oak 532° W 62 lks. Scribed SE C 141 CS BT
10" " " N 41° E 18 " " "

F.L. Frear
Co. Rdmsr
J. Wolford
B.D. Lane
Nov 22-1932
(Rev. #24)

1/4 Cor. 11 & 14 - Re-Set from 1 Old B.T. Marks Plain
Det 1 3/4" x 30" I. Bolt with nut from wh. a 24" W. Oak brs
a Plowshare East 150 ft - set 4-11-47 - Fred
5.75 1/2° W. - 548.0 ft. - a 30" W. Oak brs. S. 57 1/4° E. 685.0 ft. (Rev. #25)

7100.3.1119
(Rev. #25)
7100.4.1108
(Rev. #26)
C.E. Roberts

N.W. Cor. N. Day D.L.C. No. 40 (F.B. No. 7 Page 76)
B. Oak 17" S. 6° E. 97 Lks. W. Oak 8" N. 49° W 65 Lks.

(Rev. #27)

Cor. Secs. 31-32-5-6
Sandstone 8x8x16 marked C.S.

1/4 Cor. Bet. Secs. 30 & 31
Sandstone 6x6x14
See Page 180.