

Jan. 29 - 31 J.W. Cole C.S.

H. Strave
John Harding
Ed. Musher
Witnesses
(Rev. #13)

1/4 Cor N Side Sec 8.

I renewed this corner from the Original B To
I set an oak post and a sand rock 8"x8"x20"
marked 1/4 S C.S. The original tree called for
as N 59° W bore scars but I could find no
scribe marks. The tree S 89° W was nearly
dead and blazes were badly decayed but
I found a portion of scribe marks on lower
blaze. I marked new trees

A B Oak 12" S 87° 15' W 133 ft - slope - 12' 00"
A W " 10 N 18° W 985 " - 12' 15"

1/4 Cor on the North side of Sec 9.

I renewed this corner from the original
B Ts which were both alive and standing
but bearing no scribe marks. I set
a 4x4"x36" Oak post and remarked
the old trees 1/4 S C.S. B T. Both trees checked
with Government field notes.

1/4 Corner on South side Sec 8.

I renewed this corner from an original B T.
which was 40 in dia plainly marked and
facing N 59° E. I set post to correspond
with facing 50 lbs from tree and
checked position by measurement west
to creek and a blazed line passing
through this position. I marked a face of
Bluff 1/4 S C.S. B O. and set a large
Maple post for corner. Bluff bears S 31° E 64' 6"

2 Most northerly NW. cor. D.L.C. 49 (Mary Pierce) Found S.S. Rock orig. set for this cor. Drove 1 1/2" pipe,
1" pipe in center of 1 1/2" pipe, beside rock fr. wh. 12" Φ conc. cor (SE) post of cemetery brs. N 54 1/2° E. 197.2'

3 Int. "L" corner D.L.C. 49 (Mary Pierce) Set from stumps of two ^{orig.} ash trees, the one N 13 Lks for B.T.
shows cut 4" old wood inside shell, decayed, set 4" oak roller, 2" iron bar in center fr. wh. 24' W.O. Brs. S 87 1/2° E. 567' 2"
12" W.O. Brs. S 44° W 39.5' Both mkd. cl. 49 C.S. B.T.

Feb. 7. 1924

Witnesses as above
plus Henry Emmitt
Witness same as above

Oct 26, 1937
Arthur Boyer D.C.S.
B.A. Lane
Will Long
Jno Paulson
Ed Thompson
of 1913 Anna & Emery Thompson
Witnesses
Same as above
(Rev. #14)
(Rev. #15)
(Rev. #16)
(Rev. #17)

25-7

Edmund Johnson Dep. Co. Surv.
(Ren. #18)
Dec. 12 1932.
Witness - N.E. Richardson
R.L. Irving.

✓ 1/4 Cor between Secs 24 & 25. Renewed from BTs as recorded (see p 37) Drove an iron pin 1" dia. for corner.

✓ OBT 12" W. Oak 53°24'W 140 chs.

✓ OBT 40" B. Oak N 81°52'W 1.17 chs I reblazed and scribed this tree 1/4 S C5 BT.

Meander Corner Right Bank of Umpqua River between Secs. 24 & 25 from measurement from 1/4 sec. corner and OBT as originally recorded in govt. field notes. drove a 1 1/4" iron

✓ pipe and remarked the O.B.T. 40" B. Oak N 26°E 16 lbs. Note:- This tree is the same as is used as a BT for the 1/4 sec. Corner

(Ren. #20)

✓ N.E. Cor. D.L.C. 47 (F.B. 61-P. 55)

B. Oak 12" S. 84°W. 140 lbs.

C.C. Boyer

May 2

✓ S.E. Cor. D.L.C. 48

1913

W. Oak 6" N. 85°W. 26.85 ft.

(Ren. #21)

Marked C48 T25S.R.7W. B.T.

Apr. 25, 1936
(Arthur Boyer, D.C.S.) (#22)
Henry Teller
George Gurnee
Witnesses
Oct 26 1937
Arthur Boyer, D.C.S.
B.A. Lane (#23)
Will Long
Jno Paulsen
Ed Thompson

✓ 1/4 Cor bet. Sec's 20 & 29 Renewed from dead fir stump to the S.E. 9/16 from fir stump to NW. which is not dead but scribe marks, which were undoubtedly originally made on the bark, were gone - this stump is cut high. drove 1" x 20" round steel bar for Cor, which is in fence Cor on S. side post, fr. which an 8" B.O. Brs N 42°E 28.1 ft.

13" W.O. " S 26°W 42.0 ft.

✓ @ Most Westerly NW. Cor. D.L.C. 49 (Mary Pierce) Found orig S.S. Rock 6" x 12" x 18" (approx) firmly set in ground, drove 1" pipe beside, S. side of, Rock fr. wh. a 4" round oak roller 30" lg with Rd. 1/2" steel rod in cen. brs. S. 504.2' (No trees available)