

T26 S R 3 W

H. L. Appertem Sep 30 1921  
J. H. Smith  
N. E. Richardson  
Bent Lane

Section corner common to sections 31 & 36 T25 S R 34 W and section 186 T26 S R 34 W.  
Established corner from old B.T.s. which I chopped into and found old scribe marks.  
Set 4" x 4" x 36" Oak stake for corner and mark B.T.s. as follows

W.O. 12"	India Bears	N 27-30 E	77 lbs
Cedar 8"	"	"	"
"	"	N 33 W	32 "
W.O. 13"	"	"	"
"	"	S 70 E	94 "
Cedar 20"	"	"	"
"	"	S 16 W	131 "

June 6 1921  
J. W. Cole  
L. H. Smith  
J. H. Mathews  
A. Hays Watson

Corner to Secs. 4-5-32-33 on S by T26 S R 3 W  
Renewed the corner by setting a 4x4x36 oak post and erecting a mound of rock from which original trees  
A Laurel 24" S 29° E 79 lbs scarred  
A Wood 18" S 26° W 158 ft. scarred  
A Oak 40" N 15° W 263<sup>3</sup> ft. bears scribe  
A Oak 15" N 70° E 156<sup>4</sup> dead scarred

1/4 Corner bet. 32 + 33  
Renewed from original Bearing trees both alive and standing set a rock corner and erected mound of rock from which original trees bear.  
Pine 60" S 78° E 149<sup>2</sup> ft.

#18  
Oak 14" bearing scars N 70° W 398<sup>2</sup> ft.

1/4 Cor. bet Secs 31 + 32  
Renewed this corner from the decaying remains of original tree set at hole where tree stood and ran S 35° W 22 ft. set a Cedar post also a Rock 6x10x20 from which hole where other bt stood bears N 89° W 31 ft.  
Marked next tree a B. Oak 24" India S 33° E 83<sup>3</sup> ft.  
Chimney of Forest Blackley house. S 62° 40 W.

#19

7-17-1923  
O. W. Cole  
C. S.

E. G. Stewart Deputy C.S. 3/18/22  
Max Shellabarger, M.L. Kimmel witnesses

Sec Cor 9-10-15-16.  
Renew from stump and use O.B.T. Set 6x6x16" Rock  
Remarked O.B.T. S. Pine 30" S 85° E 18" ft  
#20 42" Fir South 61 1/2 ft. 30" <sup>w</sup> Fir N 47° W 56" ft. 10 other suitable

Sec. Cor 10-11-14-15.  
Renew from one O.B.T. standing and 2 rotten.  
Set 1" g.I.P. with yellow marker. Marked 36" Fir N 46° W 16 1/2  
#21 30" Fir N 30° E 21 1/2 ft; 24" Fir S 58° E 42' ft. 10" yellow S 41° W 19 1/2 ft.

1/4 Cor Bet 10/15.  
Set hay way between section corners. all signs of B.T.s  
gone. Set 2" Pipe. 12" Cedar S 15° E 65" ft.  
#22 18" Maple. N 31° E 22" ft.

J.W. Gre C.S. 7-12-1923  
C.W. Springs  
M.L. Kimmel Present  
Joe DeBernardi

1/4 Sec Cor Bet Secs 10 and 11  
No evidence of old B.T.s so set this cor  
from the given to river and line of old blazes  
to the South. Set a Witness cor. North 10 ft.  
An iron pipe 5/8" x 30 from which a Norway Pine  
36" N 37° E 60.6 ft and a Fir 40" N 74° 45' W  
#23 92.8 ft.

1/4 Sec Cor Bet Sec 24 & 3  
From one orig. B.T.s. set a stone in ground  
12" x 12" x 6" from which the orig. B.T.s. bears  
N 45° W 50 lks and a new B.T. bears S 60° 30' E  
#24 42.8 ft.

C.W. Springs Q.C.S.  
N.E. Richardson Present  
M.L. Kimmel  
See also Pg 63 (V.3 P. 137)

Set Cor to Secs 2-3-10 & 11  
No evidence left for this corner so established  
it by double proportional measurement as  
per Govt Instructions. Drove an iron bolt 5/8" x 30"  
in ground and erected a pile of rock 2 ft in dia x 18"  
high from which - Alder 10" N 15° E 36.2 ft - Fir  
#25 8" N 42° W 77.2 ft - B. Oak 9" S 41° 45' E 126' ft -  
Cedar 9" S 20° 30' W 97.0 ft. On this corner see  
Page 63